



AMENDMENT

I-ETS 300 219

A1

November 1996

Source: ETSI TC-RES

Reference: RI/RES-02023

ICS: 33.060.20, 33.060.50

Key words: Mobile, radio, testing

**This amendment A1, will modify
the European Telecommunication Standard ETS 300 219 (1993)**

**Radio Equipment and Systems (RES);
Land Mobile Service;
Technical characteristics and test conditions for
radio equipment transmitting signals to initiate
a specific response in the receiver**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.

Foreword

This amendment to I-ETS 300 219 (1993) has been produced by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI).

Transposition dates	
Date of adoption of this ETS:	25 October 1996
Date of latest announcement of this ETS (doa):	28 February 1997
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	31 August 1997
Date of withdrawal of any conflicting National Standard (dow):	31 August 1997

Amendments

Page 7, Foreword

Replace fifth paragraph with:

Channel separations, maximum transmitter output power / effective radiated power, class of transmitter intermodulation attenuation and the inclusion of automatic transmitter shut-off facility may all be conditions required for the issue of a licence by the appropriate regulatory authority.

Page 22, subclause 7.4.1

Replace entire subclause with:

For tests at extreme temperatures, measurements shall be made in accordance with the procedures specified in subclause 7.5, at the upper and lower temperatures of the following range:

-20 °C to + 55 °C.

For the purpose of note (a) to table 1 in subclause 6.1.1, an additional reduced extreme temperature range of 0 °C to + 30 °C shall be used when appropriate.

Type test reports shall state the temperature range used.

History

Document history	
October 1993	First Edition
November 1996	Amendment 1 to First Edition