

# EUROPEAN TELECOMMUNICATION STANDARD

Source: ETSI TC-NA

ICS: 33.020

Key words: ATM, B-ISDN, congestion, traffic

# DRAFT pr ETS 300 301

December 1996

**Second Edition** 

Reference: RE/NA-052808

# Broadband Integrated Services Digital Network (B-ISDN); Traffic control and congestion control in B-ISDN

[ITU-T Recommendation I.371 (1996)]

### ETSI

European Telecommunications Standards Institute

#### **ETSI Secretariat**

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE **Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE **X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

#### Page 2 Draft prETS 300 301: December 1996

#### Foreword

This draft European Telecommunication Standard (ETS) has been produced by the Network Aspects (NA) Technical Committee of the European Telecommunications Standards Institute (ETSI), and is now submitted for the Unified Approval Procedure phase of the ETSI standards approval procedure.

NOTE: With respect to edition 1 of ETS 300 301, this ETS provides the definition of additional traffic parameters besides the Peak Cell Rate, namely, the Sustainable Cell Rate and the Intrinsic Burst Tolerance. It provides also the definition of additional ATM layer Transfer Capabilities suitable for statistical allocation of network resources, besides the basic transfer capability based on peak allocation (Deterministic Bit Rate transfer capability), namely, the Statistical Bit Rate transfer capability, the Available Bit Rate transfer capability and the ATM Block Transfer capability.

| Proposed transposition dates  |                                 |
|---|---------------------------------|
| Date of latest announcement of this ETS (doa):  | 3 months after ETSI publication |
| Date of latest publication of new National Standard or endorsement of this ETS (dop/e): | 6 months after doa              |
| Date of withdrawal of any conflicting National Standard (dow):                          | 6 months after doa              |

#### **Endorsement notice**

The text of ITU-T Recommendation I.371 (1996) was approved by ETSI as an ETS without any modification.

Whilst every care has been taken in the preparation and publication of this document, errors in content, typographical or otherwise, may occur. If you have comments concerning its accuracy, please write to "ETSI Editing and Committee Support Dept." at the address shown on the title page.

### History

| Document history |                            |         |                          |  |
|------------------|----------------------------|---------|--------------------------|--|
| June 1996        | First Edition              |         |                          |  |
| December 1996    | Unified Approval Procedure | UAP 61: | 1996-12-16 to 1997-04-11 |  |
|                  |                            |         |                          |  |
|                  |                            |         |                          |  |
|                  |                            |         |                          |  |