



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 350

May 1995

Source: ETSI TC-SPS

Reference: T/S 23-01

ICS: 33.080

Key words: ISDN, basic, circuit mode, bearer, service, stage 2

**Integrated Services Digital Network (ISDN);
Basic call control procedures for
circuit-switched bearer services;
Functional capabilities and information flows**

[ITU-T Recommendation Q.71 (1993), modified]

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1995. All rights reserved.

Foreword

This European Telecommunication Standard (ETS) has been produced by the Signalling Protocols and Switching (SPS) Technical Committee of the European Telecommunications Standards Institute (ETSI).

Proposed transposition dates	
Date of latest announcement of this ETS (doa):	31 August 1995
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	29 February 1996
Date of withdrawal of any conflicting National Standard (dow):	29 February 1996

Endorsement notice

The text of ITU-T Recommendation Q.71 (1993) was approved by ETSI as an ETS with agreed modifications as given below.

Page 1

Insert the following two clauses (scope and normative references):

Scope

This European Telecommunication Standard (ETS) defines the stage two of the basic call handling for circuit-switched telecommunication services for the pan-European Integrated Services Digital Network (ISDN) as provided by European public telecommunications operators. Stage two identifies the functional capabilities and information flows needed to support the service description. The stage two description also identifies user operations not directly associated with a call (see CCITT Recommendation I.130 [1]).

This ETS is defined according to the methodology specified in CCITT Recommendation Q.65 [2].

Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] CCITT Recommendation I.130 (1988): "Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN".
- [2] CCITT Recommendation Q.65 (1988): "Stage 2 of the method for the characterization of services supported by an ISDN".

Throughout the text of ITU-T Recommendation Q.71, i.e. page 1, subclause 1.1, page 2, subclause 1.4.1 item 3), and page 3, subclause 1.5

Delete any reference to the multi-use 7 kHz information service. This service is out of the scope of this ETS.

Page 19, subclause 2.2.4 and page 20, table 2-1/Q.71

Delete subclause 2.2.4 and table 2-1/Q.71 explaining the information flow meanings. They do not apply for this ETS.

Page 68, table 2-2/Q.71

Delete scenario B (NT2 access to public ISDN) and scenario C (single node call), and notes 1 and 2 in table 2-2/Q.71. Scenarios B and C do not apply for this ETS.

Page 69, annex A

Delete annex A. It does not form part of this ETS.

History

Document history	
August 1994	Public Enquiry PE 68: 1994-08-08 to 1994-12-02
March 1995	Vote V 76: 1995-03-20 to 1995-05-12
May 1995	First Edition
January 1996	Converted into Adobe Acrobat Portable Document Format (PDF)