



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 443-2

May 1997

Source: ETSI TC-SPS

Reference: DE/SPS-05024-2

ICS: 33.020

Key words: B-ISDN, DSS2, UNI, layer 3, basic, PICS

**Broadband Integrated Services Digital Network (B-ISDN);
Digital Subscriber Signalling System No. two (DSS2) protocol;
B-ISDN user-network interface layer 3
specification for basic call/bearer control;
Part 2: Protocol Implementation Conformance Statement (PICS)
proforma specification**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.

Contents

Foreword	7
Introduction	7
1 Scope	9
2 Normative references	9
3 Definitions and abbreviations	9
3.1 Definitions	9
3.2 Abbreviations	10
4 Conformance	10
Annex A (normative): PICS proforma for ETS 300 443-1	11
A.1 Guidance for completing the PICS proforma	11
A.1.1 Purpose and structure	11
A.1.2 Abbreviations and conventions	11
A.1.3 Instructions for completing the PICS proforma	12
A.2 Identification of the implementation	12
A.2.1 Date of the statement	13
A.2.2 Implementation Under Test (IUT) identification	13
A.2.3 System Under Test (SUT) identification	13
A.2.4 Product supplier	13
A.2.5 Client	14
A.2.6 PICS contact person	14
A.3 Identification of the protocol to which this PICS proforma applies	15
A.4 PICS proforma tables	15
A.4.1 Correspondence to a physical interface	15
A.4.2 Structure of the tables	15
A.4.3 Complexity of conditions in Protocol Data Unit (PDU) parameter tables	15
A.4.4 Support for received PDU parameters	15
A.5 Global statement of conformance	16
A.6 Roles	16
A.7 User	17
A.7.1 Major capabilities	17
A.7.2 Subsidiary capabilities	18
A.7.3 PDUs	19
A.7.3.1 Messages received by the user	19
A.7.3.2 Messages transmitted by the user	20
A.7.4 PDU parameters	21
A.7.4.1 Information elements in messages received by the user	22
A.7.4.2 Information elements in messages transmitted by the user	27
A.7.5 Timers	32
A.7.6 Structure of information elements received	33
A.7.6.1 Broadband locking shift	33
A.7.6.2 Broadband non-locking shift	33
A.7.6.3 ATM adaptation layer parameters	34
A.7.6.4 ATM traffic descriptor	34

A.7.6.5	Broadband bearer capability	35
A.7.6.6	Broadband high layer information	35
A.7.6.7	Broadband low layer information	36
A.7.6.8	Call state	37
A.7.6.9	Called party number	37
A.7.6.10	Called party subaddress	38
A.7.6.11	Calling party number	38
A.7.6.12	Calling party subaddress	39
A.7.6.13	Connection identifier	39
A.7.6.14	End-to-end transit delay	39
A.7.6.15	Quality of service parameter	40
A.7.6.16	Restart indicator	40
A.7.6.17	OAM traffic descriptor	40
A.7.7	Structure of information elements transmitted	41
A.7.7.1	Broadband locking shift	41
A.7.7.2	Broadband non-locking shift	41
A.7.7.3	ATM adaptation layer parameters	42
A.7.7.4	ATM traffic descriptor	42
A.7.7.5	Broadband bearer capability	43
A.7.7.6	Broadband high layer information	43
A.7.7.7	Broadband low layer information	44
A.7.7.8	Call state	45
A.7.7.9	Called party number	45
A.7.7.10	Called party subaddress	46
A.7.7.11	Calling party number	46
A.7.7.12	Calling party subaddress	47
A.7.7.13	Connection identifier	47
A.7.7.14	End-to-end transit delay	47
A.7.7.15	Quality of service parameter	48
A.7.7.16	Restart indicator	48
A.7.7.17	Transit network selection	48
A.7.7.18	OAM traffic descriptor	49
A.8	Network	50
A.8.1	Major capabilities	50
A.8.2	Subsidiary capabilities	51
A.8.3	PDU's	52
A.8.3.1	Messages received by the network	52
A.8.3.2	Messages transmitted by the network	53
A.8.4	PDU parameters	53
A.8.4.1	Information elements in messages received by the network	54
A.8.4.2	Information elements in messages transmitted by the network	58
A.8.5	Timers	62
A.8.6	Structure of information elements received	63
A.8.6.1	Broadband locking shift	63
A.8.6.2	Broadband non-locking shift	63
A.8.6.3	ATM adaptation layer parameters	64
A.8.6.4	ATM traffic descriptor	64
A.8.6.5	Broadband bearer capability	65
A.8.6.6	Broadband high layer information	65
A.8.6.7	Broadband low layer information	66
A.8.6.8	Call state	67
A.8.6.9	Called party number	67
A.8.6.10	Called party subaddress	68
A.8.6.11	Calling party number	68
A.8.6.12	Calling party subaddress	69
A.8.6.13	Connection identifier	69
A.8.6.14	End-to-end transit delay	69
A.8.6.15	Quality of service parameter	70
A.8.6.16	Restart indicator	70
A.8.6.17	Transit network selection	70
A.8.6.18	OAM traffic descriptor	71

A.8.7	Structure of information elements transmitted.....	71
A.8.7.1	Broadband locking shift.....	71
A.8.7.2	Broadband non-locking shift.....	71
A.8.7.3	ATM adaptation layer parameters.....	72
A.8.7.4	ATM traffic descriptor.....	72
A.8.7.5	Broadband bearer capability.....	73
A.8.7.6	Broadband high layer information.....	73
A.8.7.7	Broadband low layer information.....	74
A.8.7.8	Call state.....	75
A.8.7.9	Called party number.....	75
A.8.7.10	Called party subaddress.....	76
A.8.7.11	Calling party number.....	76
A.8.7.12	Calling party subaddress.....	77
A.8.7.13	Connection identifier.....	77
A.8.7.14	End-to-end transit delay.....	77
A.8.7.15	Quality of service parameter.....	78
A.8.7.16	Restart indicator.....	78
A.8.7.17	OAM traffic descriptor.....	78
	History.....	79

Blank page

Foreword

This European Telecommunication Standard (ETS) has been produced by the Signalling Protocols and Switching (SPS) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This ETS is part 2 of a multi-part standard covering the specification of the Broadband Integrated Services Digital Network (B-ISDN) user-network interface layer 3 protocol for basic call/bearer control of Digital Subscriber Signalling System No. two (DSS2) as described below:

- Part 1: "Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]";
- Part 2: "Protocol Implementation Conformance Statement (PICS) proforma specification";**
- Part 3: "Test Suite Structure and Test Purposes (TSS&TP) specification for the user";
- Part 4: "Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma specification for the user";
- Part 5: "TSS&TP specification for the network";
- Part 6: "ATS and partial PIXIT proforma specification for the network".

Transposition dates	
Date of adoption:	2 May 1997
Date of latest announcement of this ETS (doa):	31 August 1997
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	28 February 1998
Date of withdrawal of any conflicting National Standard (dow):	28 February 1998

Introduction

To evaluate conformance of a particular implementation, it is necessary to have a statement of which capabilities and options have been implemented for a given protocol. Such a statement is called an Implementation Conformance Statement (ICS). An ICS stating what capabilities and options have been implemented for a particular protocol is called a protocol ICS. This is commonly abbreviated to "PICS".

ETS 300 443-1 is derived from ITU-T Recommendation Q.2931 (1995). However, no PICS proforma exists for this Recommendation. Therefore, ETSI has created a PICS proforma that is specific to the European environment. This PICS proforma reflects the requirements contained in ITU-T Recommendation Q.2931 with the modifications applied by ETS 300 443-1. This has been done to assist understanding of how the European requirements relate to the requirements contained within ITU-T Recommendation Q.2931 (and in particular, to the options specified in that recommendation that are selected by the ETS). In practical terms, this means that a number of capabilities specified by ITU-T Recommendation Q.2931 appear as items in this PICS proforma with a status more akin to the status that would be expected in a profile ICS (i.e. out-of-scope (I), prohibited (X)).

Blank page

1 Scope

This second part of ETS 300 443 provides the Protocol Implementation Conformance Statement (PICS) proforma for the Broadband Integrated Services Digital Network (B-ISDN) Digital Subscriber Signalling System No. two (DSS2) protocol user-network interface layer 3 specification for basic call control defined in ETS 300 443-1 [1] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [3].

The supplier of a protocol implementation that is claimed to conform to ETS 300 443-1 [1] is required to complete a copy of the PICS proforma provided in annex A of this ETS and is required to provide the information necessary to identify both the supplier and the implementation.

2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] ETS 300 443-1 (1996): "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]".
- [2] ISO/IEC 9646-1: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [3] ISO/IEC 9646-7: "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of this ETS, the definitions in ETS 300 443-1 [1], ISO/IEC 9646-1 [2], and ISO/IEC 9646-7 [3] apply. In particular, the following terms defined in ISO/IEC 9646-1 [2] apply:

Implementation Conformance Statement (ICS): A statement made by the supplier of an implementation or system claimed to conform to a given specification, stating which capabilities have been implemented. The ICS can take several forms: protocol ICS, profile ICS, profile specific ICS, and information object ICS.

Protocol Implementation Conformance Statement (PICS): An ICS for an implementation or system claimed to conform to a given protocol specification.

PICS proforma: A document, in the form of a questionnaire, which when completed for an implementation or system becomes a PICS.

The following definitions also apply:

network: The DSS2 protocol entity at the network side of the user-network interface.

user: The DSS2 protocol entity at the user side of the user-network interface.

3.2 Abbreviations

For the purposes of this ETS, the following abbreviations apply:

AAL	ATM Adaptation Layer
ATM	Asynchronous Transfer Mode
BCOB	Broadband Class Of Bearer
B-ISDN	Broadband ISDN
CBR	Constant Bit Rate
CLP	Cell Loss Priority
CPCS	Common Part Convergence Sublayer
DSS2	Digital Subscriber Signalling System No. two
DTE	Data Terminal Equipment
FEC	Forward Error Correction
HDLC	High-level Data Link Control
HDLC ABM	HDLC Asynchronous Balanced Mode
HDLC ARM	HDLC Asynchronous Response Mode
HDLC NRM	HDLC Normal Response Mode
ICS	Implementation Conformance Statement
ISDN	Integrated Services Digital Network
IUT	Implementation Under Test
LAN	Local Area Network
LAPB	Link Access Protocol Balanced
MID	Multiplexing Identifier
NSAP	Network layer Service Access Point
OAM	Operations And Maintenance
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation eXtra Information for Testing
QOS	Quality Of Service
SDU	Service Data Unit
SLP	Single Link Procedure
SSCOP	Service Specific Connection-Oriented Protocol
SSCS	Service Specific Convergence Sublayer
SUT	System Under Test
VC	Virtual Connection
VCI	VC Identifier
VP	Virtual Path
VPC	VP Connection
VPCI	VPC Identifier

4 Conformance

A PICS proforma that conforms to this PICS proforma specification shall be technically equivalent to annex A, and shall preserve the numbering and ordering of the items in annex A.

A PICS that conforms to this PICS proforma specification shall:

- a) describe an implementation which conforms to ETS 300 443-1 [1];
- b) be a conforming PICS proforma, which has been completed in accordance with the instructions for completion given in clause A.1;
- c) include the information necessary to uniquely identify both the supplier and the implementation.

Annex A (normative): PICS proforma for ETS 300 443-1

Notwithstanding the provisions of the copyright clause related to the text of this ETS, ETSI grants that users of this ETS may freely reproduce the PICS proforma in this annex so that it can be used for its intended purposes and may further publish the completed PICS.

A.1 Guidance for completing the PICS proforma

A.1.1 Purpose and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in ETS 300 443-1 [1] may provide information in a standardized manner.

The PICS proforma is subdivided into clauses as follows:

- A.1: guidance for completing the various parts of the PICS proforma;
- A.2: identification of the implementation;
- A.3: identification of the protocol to which this PICS proforma applies;
- A.4: explanation of the PICS proforma tables;
- A.5: global statement of conformance;
- A.6: questions to determine roles;
- A.7: questions for the user role;
- A.8: questions for the network role.

A.1.2 Abbreviations and conventions

The PICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [3].

Item column

The item column contains a unique reference (a mnemonic plus a number) for each item within the PICS proforma. Items are not always numbered sequentially.

Item description column

The item description contains a brief summary of the static requirement for which a support answer is required.

Conditions for status column

The conditions for status column contains a specification, if appropriate, of the predicate upon which a conditional status is based.

Status column

The following notations, defined in ISO/IEC 9646-7 [3], are used for the status column:

- | | |
|-----|---|
| I | Irrelevant or out-of-scope - this capability is outside the scope of the ETS to which this PICS proforma applies and is not subject to conformance testing in this context. |
| M | Mandatory - the capability is required to be supported. |
| N/A | Not Applicable - in the given context, it is impossible to use the capability. No answer in the support column is required. |
| O | Optional - the capability may be supported or not. |

- O.i qualified Optional - for mutually exclusive or selectable options from a set. "i" is an integer that identifies an unique group of related optional items and the logic of their selection, defined below the table.
- X eXcluded or prohibited - there is a requirement not to use this capability in a given context.

Reference column

Except where explicitly stated, the reference column refers to the appropriate text of ITU-T Recommendation Q.2931 as modified by ETS 300 443-1 [1] describing the particular item.

NOTE: A reference indicates only the location of the most essential information about an item. All additional requirements contained in ETS 300 443-1 [1] have also to be taken into account when making a statement about the conformance of that particular item.

Support column

The following notation, defined in ISO/IEC 9646-7 [3], is used for the support column:

- Yes Tick "Yes" if item is supported.
- No Tick "No" if item is not supported.
- N/A Tick "N/A" if the item is "not applicable".

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a subclause heading or table title indicates that the whole subclause or the whole table is not required to be completed if the predicate is FALSE.

A.1.3 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma. For each row in each PICS proforma table the supplier shall enter an explicit answer (i.e. by ticking the appropriate "Yes", "No", or "N/A" in each of the support column boxes provided). Where a support column box is left blank, or where it is marked "N/A" without any tickbox, no answer is required.

If necessary, the supplier may enter additional comments at the end of each table, or separately.

More detailed instructions may be found at the beginning of each subclause of the proforma.

A.2 Identification of the implementation

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in to provide as much detail as possible regarding version numbers and configuration options.

The product supplier and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

A.2.1 Date of the statement

.....

A.2.2 Implementation Under Test (IUT) identification

IUT name:

.....

.....

IUT version:

.....

A.2.3 System Under Test (SUT) identification

SUT name:

.....

.....

Hardware configuration:

.....

.....

.....

Operating system:

.....

A.2.4 Product supplier

Name:

.....

Address:

.....

.....

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

A.2.5 Client

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

A.2.6 PICS contact person

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

A.3 Identification of the protocol to which this PICS proforma applies

This PICS proforma applies to the following standard:

ETS 300 443-1 (1996): "Broadband Integrated Services Digital Network (B-ISDN); Digital Subscriber Signalling System No. two (DSS2) protocol; B-ISDN user-network interface layer 3 specification for basic call/bearer control; Part 1: Protocol specification [ITU-T Recommendation Q.2931 (1995), modified]".

A.4 PICS proforma tables

A.4.1 Correspondence to a physical interface

The "implementation" (IUT) about which this PICS proforma asks questions corresponds to a layer 3 implementation on top of ONE physical interface. If the SUT implements more than one configuration, then a layer 3 PICS shall be created for each type of interface (and for each configuration of each interface) provided by the SUT.

A.4.2 Structure of the tables

The supplier shall provide answers to the questions concerning the major roles of the IUT (see table A.1). The supplier shall then provide answers to the questions relating to the capabilities of the IUT in one of the major roles as appropriate. Apart from the initial questions to determine roles, the major roles of the IUT (the user role (R 1) and the network role (R 2)) are treated completely separately in the PICS proforma. It is only necessary to complete the questions for the supported role. Clause A.7 concerns the capabilities of the IUT whilst in the user role. Clause A.8 concerns the capabilities of the IUT whilst in the network role.

A.4.3 Complexity of conditions in Protocol Data Unit (PDU) parameter tables

The conditions governing when an individual information element has to be supported in a specific message are quite complex. To make the conditions for status easier to understand questions about these information elements have been split into several sub-items.

A.4.4 Support for received PDU parameters

In the PDU parameter tables (see subclauses A.7.5 and A.8.5), the PICS proforma asks questions about the information elements (parameters) supported in messages (PDUs) received by the IUT. This subclause explains, in the context of ETS 300 443-1 [1], what "to support a received PDU parameter" means.

The requirement that an IUT is able to parse an information element in a received message is already implied by claiming support for the receipt of that received message. This means that "to support a received PDU parameter" implies more.

Information elements in received messages are regarded as either transparent or non-transparent.

A non-transparent information element is one that causes the protocol control entity to vary its behaviour in accordance with the content of the information element. To support a non-transparent information element means an IUT can process the received parameter and behave according to the procedures described in ETS 300 443-1 [1].

An information element is transparent if the actions taken according to its contents are not detectable in the subsequent behaviour of the protocol (i.e. ETS 300 443-1 [1] does not specify the protocol behaviour). To support a transparent information element means an IUT can receive the information element concerned and pass it to an appropriate processing entity (e.g. call control); the information element is not discarded by the protocol control entity. Non-support of a transparent information element means that the IUT discards it.

This PICS proforma considers the Cause information element to be transparent in all circumstances where it is possible to be received. Other information elements may be transparent in some circumstances.

A.5 Global statement of conformance

Does the implementation described in this PICS meet all the mandatory requirements of the referenced standard?

Yes

No

NOTE: Answering "No" to this question indicates non-conformance to the protocol specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming. Explanations may be entered in the comments field at the bottom of each table or on attached pages.

A.6 Roles

Table A.1: Roles

Item	Role: Does the implementation support...	Conditions for status	Status	Reference	Support
R 1	the user role?		O.1		<input type="checkbox"/> Yes <input type="checkbox"/> No
R 2	the network role?		O.1		<input type="checkbox"/> Yes <input type="checkbox"/> No
O.1	Support of one, and only one, of these options is required.				
Comments:					

A.7 User

The tables provided in this clause need only to be completed for user implementations:

Prerequisite: R 1

A.7.1 Major capabilities

Each question in table A.2 refers to a major function of the protocol. Answering "Yes" to a particular question states that the implementation supports all the mandatory procedures for that function defined in the referenced clauses and subclauses of ITU-T Recommendation Q.2931 as modified by ETS 300 443-1 [1]. Answering "No" to a particular question states that the implementation does not support that function of the protocol.

Table A.2: Major capabilities of the user role

Item	Major capability: Does the implementation support...	Conditions for status	Status	Reference	Support
Call establishment at the originating interface					
MCu 1	outgoing calls		O.2	5.1	[]Yes []No
MCu 1.1	associated signalling on the originating side	MCu 1 NOT MCu 1	O N/A	5.1.2	[]Yes []No []N/A
Call establishment at the destination interface					
MCu 2	incoming calls		O.2	5.2	[]Yes []No
MCu 2.1	associated signalling on the destination side	MCu 2 NOT MCu 2	O N/A	5.2.3, 5.2.3.1	[]Yes []No []N/A
Others					
MCu 3	initiation of call clearing		M	5.4	[]Yes []No
MCu 4	restart procedure		M	5.5	[]Yes []No
MCu 5	handling of error conditions		M	5.6	[]Yes []No
MCu 5.1	invocation of the status enquiry procedure on receipt of an AAL-ESTABLISH.indication in the call establishment phase		O	5.6.9 b)	[]Yes []No
MCu 6	error procedures with explicit action indication		M	5.7	[]Yes []No
MCu 7	handling of messages with insufficient information		M	5.8	[]Yes []No
MCu 8	notification procedures		M	5.9	[]Yes []No
MCu 9	additional procedures for the provision of 64 kbit/s circuit-mode services		O	6	[]Yes []No
MCu 10	broadband low layer information negotiation		O	annex C	[]Yes []No
MCu 11	transit network selection procedures		O	clause D.2	[]Yes []No
MCu 12	ATM adaptation layer parameters indication and negotiation		O	annex F	[]Yes []No
MCu 13	handling of the OAM traffic descriptor		O	annex I	[]Yes []No
MCu 14	handling of the End-to-end transit delay information element		O	annex K	[]Yes []No
O.2	Support of at least one of these options is required.				
Comments:					

A.7.2 Subsidiary capabilities

Indicating support for an item in table A.3 states that the implementation supports special cases or options within a major capability.

Table A.3: Subsidiary capabilities of the user role

Item	Subsidiary capability: Does the implementation support...	Conditions for status	Status	Reference	Support
Call establishment at the originating interface					
SCu 1	sending of the called party address information in the Called party number information element	MCu 1 NOT MCu 1	M N/A	5.1.1	[]Yes []No []N/A
SCu 2	overlap sending	MCu 9 AND MCu 1 NOT (MCu 9 AND MCu 1)	O N/A	6.5.2	[]Yes []No []N/A
SCu 2.1	sending of the Broadband sending complete information element	SCu 2 NOT SCu 2	O N/A	6.5.2	[]Yes []No []N/A
Call establishment at the destination interface					
SCu 3	compatibility checking	MCu 2 NOT MCu 2	M N/A	5.2.2.2	[]Yes []No []N/A
SCu 4	overlap receiving (note)	MCu 9 AND MCu 2 NOT (MCu 9 AND MCu 2)	O N/A	6.5.3	[]Yes []No []N/A
SCu 5.1	the sending of the ALERTING message as a first response to a SETUP message?	MCu 2 NOT MCu 2	O N/A	5.2.3	[]Yes []No []N/A
SCu 5.2	the sending of the CALL PROCEEDING message as a first response to a SETUP message?	MCu 2 NOT MCu 2	O N/A	5.2.3	[]Yes []No []N/A
SCu 5.3	the sending of the CONNECT message as a first response to a SETUP message?	MCu 2 NOT MCu 2	O N/A	5.2.3	[]Yes []No []N/A
NOTE:	Non-support of this item may preclude proper operation in certain countries.				
Comments:					

A.7.3 PDUs

The tables in this subclause ask questions related to the supported PDUs in the user role. In the DSS2 protocol, PDUs are known by the term "messages".

A.7.3.1 Messages received by the user

Indicating support for an item in table A.4 states that the implementation has the ability to recognize the message listed in that item. Support for the receipt of a particular type of PDU means support for recognising and acting upon all valid instances of that PDU type, including all valid PDU parameters, to the extent required by ETS 300 443-1 [1].

Table A.4: Messages received by the user

Item	Message: Does the implementation support the receipt of...	Conditions for status	Status	Reference	Support
MRu 1	ALERTING	MCu 1 NOT MCu 1	M N/A	3.1.1, 3.2.1, 5.1.6	[]Yes []No []N/A
MRu 2	CALL PROCEEDING	MCu 1 NOT MCu 1	M N/A	3.1.2, 3.2.2, 5.1.5	[]Yes []No []N/A
MRu 3	CONNECT	MCu 1 NOT MCu 1	M N/A	3.1.3, 3.2.3, 5.1.7	[]Yes []No []N/A
MRu 4	CONNECT ACKNOWLEDGE	MCu 2 NOT MCu 2	M N/A	3.1.4, 5.2.7	[]Yes []No []N/A
MRu 5	INFORMATION	SCu 4 NOT SCu 4	M N/A	3.2.4, 6.5.3	[]Yes []No []N/A
MRu 6	NOTIFY		M	3.1.10, 5.9	[]Yes []No
MRu 7	PROGRESS	MCu 9 NOT MCu 9	M N/A	3.2.5, 6.6.1, 6.6.2	[]Yes []No []N/A
MRu 8	RELEASE		M	3.1.5, 3.2.6, 5.4.4, 5.4.5	[]Yes []No
MRu 9	RELEASE COMPLETE		M	3.1.6, 5.1.2, 5.1.3, 5.2.5.3, 5.4.3, 5.6.3.2, 5.6.7, 5.6.8.1, 5.7.2	[]Yes []No
MRu 10	RESTART		M	3.3.1, 5.5.2	[]Yes []No
MRu 11	RESTART ACKNOWLEDGE		M	3.3.2, 5.5.1	[]Yes []No
MRu 12	SETUP	MCu 2 NOT MCu 2	M N/A	3.1.7, 3.2.7, 5.2	[]Yes []No []N/A
MRu 13	SETUP ACKNOWLEDGE	SCu 2 NOT SCu 2	M N/A	3.2.8, 6.5.2	[]Yes []No []N/A
MRu 14	STATUS		M	3.1.8, 5.6.3.2, 5.6.12	[]Yes []No
MRu 15	STATUS ENQUIRY		M	3.1.9, 5.6.3.2, 5.6.11	[]Yes []No
Comments:					

A.7.3.2 Messages transmitted by the user

Indicating support for an item in table A.5 states that the implementation has the ability to transmit the message listed in that item.

Table A.5: Messages transmitted by the user

Item	Message: Does the implementation support the receipt of...	Conditions for status	Status	Reference	Support
MTu 1	ALERTING	MCu 2 NOT MCu 2	M N/A	3.1.1, 3.2.1, 5.2.5.1	[]Yes []No []N/A
MTu 2	CALL PROCEEDING	MCu 2 NOT MCu 2	M N/A	3.1.2, 3.2.2, 5.2.5.1	[]Yes []No []N/A
MTu 3	CONNECT	MCu 2 NOT MCu 2	M N/A	3.1.3, 3.2.3, 5.2.6	[]Yes []No []N/A
MTu 4	CONNECT ACKNOWLEDGE	MCu 1 NOT MCu 1	M N/A	3.1.4, 5.1.7	[]Yes []No []N/A
MTu 5	INFORMATION	SCu 2 NOT SCu 2	M N/A	3.2.4, 6.5.2	[]Yes []No []N/A
MTu 6	NOTIFY		M	3.1.10, 5.9	[]Yes []No
MTu 7	PROGRESS	MCu 9 NOT MCu 9	M N/A	3.2.5, 6.6.1, 6.6.2	[]Yes []No []N/A
MTu 8	RELEASE		M	3.1.5, 3.2.6, 5.4.3	[]Yes []No
MTu 9	RELEASE COMPLETE		M	3.1.6, 5.2.2.2.2, 5.2.3, 5.2.4, 5.2.5, 5.4.4	[]Yes []No
MTu 10	RESTART		M	3.3.1, 5.5.1	[]Yes []No
MTu 11	RESTART ACKNOWLEDGE		M	3.3.2, 5.5.2	[]Yes []No
MTu 12	SETUP	MCu 1 NOT MCu 1	M N/A	3.1.7, 3.2.7, 5.1	[]Yes []No []N/A
MTu 13	SETUP ACKNOWLEDGE	SCu 4 NOT SCu 4	M N/A	3.2.8, 6.5.3	[]Yes []No []N/A
MTu 14	STATUS		M	3.1.8, 5.5.2.1, 5.6.3.2, 5.6.4, 5.6.7, 5.6.8, 5.6.11, 5.7	[]Yes []No
MTu 15	STATUS ENQUIRY		M	3.1.9, 5.6.3.2, 5.6.11	[]Yes []No
Comments:					

A.7.4 PDU parameters

The tables in this subclause ask questions related to the support of PDU parameters in messages received and transmitted by the IUT in the user role. In the DSS2, protocol PDU parameters are known by the term "information elements".

Tables A.6 and A.7 deal with the four information elements that appear in all messages that are either received or transmitted (respectively) by the IUT in the user role (Protocol discriminator, Call reference, Message type and Message length) and two information elements which may appear in a message for which it is mandatory for the receiver to interpret (shift information elements).

Table A.6: Information elements in all messages received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu-IE1	Protocol discriminator		M	3.1, 3.2, 4.2	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRu-IE2	Call reference		M	3.1, 3.2, 4.3	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRu-IE3	Message type		M	3.1, 3.2, 4.4.1	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRu-IE4	Message length		M	3.1, 3.2, 4.4.2	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRu-IE5	Broadband locking shift		M	4.5.3	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRu-IE25	Broadband non-locking shift		M	4.5.4	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.7: Information elements in all messages transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu-IE1	Protocol discriminator		M	3.1, 3.2, 4.2	<input type="checkbox"/> Yes <input type="checkbox"/> No
MTu-IE2	Call reference		M	3.1, 3.2, 4.3	<input type="checkbox"/> Yes <input type="checkbox"/> No
MTu-IE3	Message type		M	3.1, 3.2, 4.4.1	<input type="checkbox"/> Yes <input type="checkbox"/> No
MTu-IE4	Message length		M	3.1, 3.2, 4.4.2	<input type="checkbox"/> Yes <input type="checkbox"/> No
MTu-IE5	Broadband locking shift		O	4.5.3	<input type="checkbox"/> Yes <input type="checkbox"/> No
MTu-IE25	Broadband non-locking shift		O	4.5.4	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

A.7.4.1 Information elements in messages received by the user

Indicating support for an item in the tables in this subclause states that the implementation has the ability to process the information elements listed in the specified received messages.

Table A.8: Information elements in ALERTING received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu1-IE13	Connection identifier	MRu 1 NOT MRu 1	M N/A	3.1.1, 3.2.1	[]Yes []No []N/A
MRu1-IE23	Narrowband bearer capability	MCu 9 AND MRu 1 NOT (MCu 9 AND MRu 1)	O N/A	3.2.1	[]Yes []No []N/A
MRu1-IE6	Narrowband high layer compatibility	MCu 9 AND MRu 1 NOT (MCu 9 AND MRu 1)	O N/A	3.2.1	[]Yes []No []N/A
MRu1-IE20	Notification indicator	MRu 1 NOT MRu 1	M N/A	3.1.1, 3.2.1	[]Yes []No []N/A
MRu1-IE22	Progress indicator	MCu 9 AND MRu 1 NOT (MCu 9 AND MRu 1)	M N/A	3.2.1	[]Yes []No []N/A
Comments:					

Table A.9: Information elements in CALL PROCEEDING received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu2-IE13	Connection identifier	MRu 2 NOT MRu 2	M N/A	3.1.2, 3.2.2	[]Yes []No []N/A
MRu2-IE23	Narrowband bearer capability	MCu 9 AND MRu 2 NOT (MCu 9 AND MRu 2)	O N/A	3.2.2	[]Yes []No []N/A
MRu2-IE6	Narrowband high layer compatibility	MCu 9 AND MRu 2 NOT (MCu 9 AND MRu 2)	O N/A	3.2.2	[]Yes []No []N/A
MRu2-IE20	Notification indicator	MRu 2 NOT MRu 2	M N/A	3.1.2, 3.2.2	[]Yes []No []N/A
MRu2-IE22	Progress indicator	MCu 9 AND MRu 2 NOT (MCu 9 AND MRu 2)	M N/A	3.2.2	[]Yes []No []N/A
Comments:					

Table A.10: Information elements in CONNECT received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu3-IE11	AAL parameters	MRu 3 NOT MRu 3	M N/A	3.1.3, 3.2.3	[]Yes []No []N/A
MRu3-IE17	Broadband low layer information	MRu 3 NOT MRu 3	M N/A	3.1.3	[]Yes []No []N/A
MRu3-IE13	Connection identifier	MRu 3 NOT MRu 3	M N/A	3.1.3, 3.2.3	[]Yes []No []N/A
MRu3-IE19	End-to-end transit delay	MRu 3 NOT MRu 3	M N/A	3.1.3, 3.2.3	[]Yes []No []N/A
MRu3-IE23	Narrowband bearer capability	MCu 9 AND MRu 3 NOT (MCu 9 AND MRu 3)	O N/A	3.2.3	[]Yes []No []N/A
MRu3-IE6	Narrowband high layer compatibility	MCu 9 AND MRu 3 NOT (MCu 9 AND MRu 3)	O N/A	3.2.3	[]Yes []No []N/A
MRu3-IE5	Narrowband low layer compatibility	MCu 9 AND MRu 3 NOT (MCu 9 AND MRu 3)	M N/A	3.2.3	[]Yes []No []N/A
MRu3-IE20	Notification indicator	MRu 3 NOT MRu 3	M N/A	3.1.3, 3.2.3	[]Yes []No []N/A
MRu3-IE14	OAM traffic descriptor	MRu 3 NOT MRu 3	M N/A	3.1.3, 3.2.3	[]Yes []No []N/A
MRu3-IE23	Progress indicator	MCu 9 AND MRu 3 NOT (MCu 9 AND MRu 3)	M N/A	3.2.3	[]Yes []No []N/A
Comments:					

Table A.11: Information elements in CONNECT ACKNOWLEDGE received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu4-IE20	Notification indicator	MRu 4 NOT MRu 4	M N/A	3.1.4	[]Yes []No []N/A
Comments:					

Table A.12: Information elements in INFORMATION received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu5-IE7	Broadband sending complete	MRu 5 NOT MRu 5	M N/A	3.2.4	[]Yes []No []N/A
MRu5-IE1	Called party number	MRu 5 NOT MRu 5	M N/A	3.2.4	[]Yes []No []N/A
Comments:					

Table A.13: Information elements in NOTIFY received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu6-IE20	Notification indicator		M	3.1.10	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.14: Information elements in PROGRESS received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu7-IE23	Narrowband bearer capability	MRu 7 NOT MRu 7	O N/A	3.2.5	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
MRu7-IE6	Narrowband high layer compatibility	MRu 7 NOT MRu 7	O N/A	3.2.5	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
MRu7-IE20	Notification indicator	MRu 7 NOT MRu 7	M N/A	3.2.5	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
MRu7-IE23	Progress indicator	MRu 7 NOT MRu 7	M N/A	3.2.5	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
Comments:					

Table A.15: Information elements in RELEASE received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu8-IE24	Cause		M	3.1.5, 3.2.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRu8-IE20	Notification indicator		M	3.1.5, 3.2.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRu8-IE22	Progress indicator		M	3.2.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.16: Information elements in RELEASE COMPLETE received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu9-IE24	Cause		M	3.1.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.17: Information elements in RESTART received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu10-IE13	Connection identifier		M	3.3.1	[]Yes []No
MRu10-IE4	Restart indicator		M	3.3.1	[]Yes []No
Comments:					

Table A.18: Information elements in RESTART ACKNOWLEDGE received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu11-IE13	Connection identifier		M	3.3.2	[]Yes []No
MRu11-IE4	Restart indicator		M	3.3.2	[]Yes []No
Comments:					

Table A.19: Information elements in SETUP received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu12-IE11	AAL parameters	MRu 12 NOT MRu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE12	ATM traffic descriptor	MRu 12 NOT MRu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE16	Broadband bearer capability	MRu 12 NOT MRu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE18	Broadband high layer information	MRu 12 NOT MRu 12	M N/A	3.1.7	[]Yes []No []N/A
MRu12-IE8	Broadband repeat indicator	MCu 10 AND MRu 12 NOT (MCu 10 AND MRu 12)	M N/A	3.1.7, annex C	[]Yes []No []N/A
MRu12-IE17	Broadband low layer information	MRu 12 NOT MRu 12	M N/A	3.1.7	[]Yes []No []N/A
MRu12-IE1	Called party number	MRu 12 NOT MRu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE2	Called party subaddress	MRu 12 NOT MRu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE9	Calling party number		I	3.1.7, 3.2.7	[]Yes []No
MRu12-IE10	Calling party subaddress		I	3.1.7, 3.2.7	[]Yes []No
MRu12-IE13	Connection identifier	MRu 12 NOT MRu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE19	End-to-end transit delay	MRu 12 NOT MRu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE23	Narrowband bearer capability	MCu 9 AND MRu 12 NOT (MCu 9 AND MRu 12)	M N/A	3.2.7	[]Yes []No []N/A
MRu12-IE6	Narrowband high layer compatibility	MCu 9 AND MRu 12 NOT (MCu 9 AND MRu 12)	M N/A	3.2.7	[]Yes []No []N/A
MRu12-IE5	Narrowband low layer compatibility	MCu 9 AND MRu 12 NOT (MCu 9 AND MRu 12)	M N/A	3.2.7	[]Yes []No []N/A
MRu12-IE20	Notification indicator	MRu 12 NOT MRu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE14	OAM traffic descriptor	MRu 12 NOT MRu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE22	Progress indicator	MCu 9 AND MRu 12 NOT (MCu 9 AND MRu 12)	M N/A	3.2.7	[]Yes []No []N/A
MRu12-IE15	QOS parameter	MRu 12 NOT MRu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE7	Broadband sending complete	MRu 12 NOT MRu 12	O N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MRu12-IE3	Transit network selection		X		[]Yes []No
Comments:					

Table A.20: Information elements in SETUP ACKNOWLEDGE received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu13-IE13	Connection identifier	MRu 13 NOT MRu 13	M N/A	3.2.8	[]Yes []No []N/A
MRu13-IE20	Notification indicator	MRu 13 NOT MRu 13	M N/A	3.2.8	[]Yes []No []N/A
MRu13-IE22	Progress indicator	MRu 13 NOT MRu 13	M N/A	3.2.8	[]Yes []No []N/A
Comments:					

Table A.21: Information elements in STATUS received by the user

Item	Information element	Conditions for status	Status	Reference	Support
MRu14-IE21	Call state		M	3.1.8	[]Yes []No
MRu14-IE24	Cause		M	3.1.8	[]Yes []No
Comments:					

A.7.4.2 Information elements in messages transmitted by the user

Indicating support for an item in the tables in this subclause states that the implementation has the ability to generate, and to transmit in the specified message, the information elements listed. Such support does not necessarily mean that the indicated information element is included in every instance of the transmitted message.

Table A.22: Information elements in ALERTING transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu1-IE13	Connection identifier	SCu 5.1 NOT SCu 5.1	M N/A	3.1.1, 3.2.1	[]Yes []No []N/A
MTu1-IE23	Narrowband bearer capability	MCu 9 AND MTu 1 NOT (MCu 9 AND MTu 1)	O N/A	3.2.1	[]Yes []No []N/A
MTu1-IE6	Narrowband high layer compatibility	MCu 9 AND MTu 1 NOT (MCu 9 AND MTu 1)	O N/A	3.2.1	[]Yes []No []N/A
MTu1-IE20	Notification indicator	MTu 1 NOT MTu 1	O N/A	3.1.1, 3.2.1	[]Yes []No []N/A
MTu1-IE22	Progress indicator	MCu 9 AND MTu 1 NOT (MCu 9 AND MTu 1)	O N/A	3.2.1	[]Yes []No []N/A
Comments:					

Table A.23: Information elements in CALL PROCEEDING transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu2-IE13	Connection identifier	SCu 5.2 NOT SCu 5.2	M O	3.1.2, 3.2.2	[]Yes []No
MTu2-IE23	Narrowband bearer capability	MCu 9 AND MTu2 NOT (MCu 9 AND MTu2)	O N/A	3.2.2	[]Yes []No []N/A
MTu2-IE6	Narrowband high layer compatibility	MCu 9 AND MTu2 NOT (MCu 9 AND MTu2)	O N/A	3.2.2	[]Yes []No []N/A
MTu2-IE20	Notification indicator	MTu2 NOT MTu2	O N/A	3.1.2, 3.2.2	[]Yes []No []N/A
MTu2-IE22	Progress indicator	MCu 9 AND MTu2 NOT (MCu 9 AND MTu2)	O N/A	3.2.2	[]Yes []No []N/A
Comments:					

Table A.24: Information elements in CONNECT transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu3-IE11	AAL parameters	MTu 3 NOT MTu 3	O N/A	3.1.3, 3.2.3	[]Yes []No []N/A
MTu3-IE17	Broadband low layer information	MTu 3 NOT MTu 3	O N/A	3.1.3	[]Yes []No []N/A
MTu3-IE13	Connection identifier	SCu 5.3 NOT SCu 5.3	M N/A	3.1.3, 3.2.3	[]Yes []No []N/A
MTu3-IE19	End-to-end transit delay	MTu 3 NOT MTu 3	M N/A	3.1.3, 3.2.3	[]Yes []No []N/A
MTu3-IE23	Narrowband bearer capability	MCu 9 AND MTu 3 NOT (MCu 9 AND MTu 3)	O N/A	3.2.3	[]Yes []No []N/A
MTu3-IE6	Narrowband high layer compatibility	MCu 9 AND MTu 3 NOT (MCu 9 AND MTu 3)	O N/A	3.2.3	[]Yes []No []N/A
MTu3-IE5	Narrowband low layer compatibility	MCu 9 AND MTu 3 NOT (MCu 9 AND MTu 3)	O N/A	3.2.3	[]Yes []No []N/A
MTu3-IE20	Notification indicator	MTu 3 NOT MTu 3	O N/A	3.1.3, 3.2.3	[]Yes []No []N/A
MTu3-IE14	OAM traffic descriptor	MTu 3 NOT MTu 3	M N/A	3.1.3, 3.2.3	[]Yes []No []N/A
MTu3-IE23	Progress indicator	MCu 9 AND MTu 3 NOT (MCu 9 AND MTu 3)	O N/A	3.2.3	[]Yes []No []N/A
Comments:					

Table A.25: Information elements in CONNECT ACKNOWLEDGE transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu4-IE20	Notification indicator	MTu 4 NOT MTu 4	O N/A	3.1.4	[]Yes []No []N/A
Comments:					

Table A.26: Information elements in INFORMATION transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu5-IE7	Broadband sending complete	MTu 5 NOT MTu 5	O N/A	3.2.4	[]Yes []No []N/A
MTu5-IE1	Called party number	MTu 5 NOT MTu 5	M N/A	3.2.4	[]Yes []No []N/A
Comments:					

Table A.27: Information elements in NOTIFY transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu6-IE20	Notification indicator		M	3.1.10	[]Yes []No
Comments:					

Table A.28: Information elements in PROGRESS transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu7-IE23	Narrowband bearer capability	MTu 7 NOT MTu 7	O N/A	3.2.5	[]Yes []No []N/A
MTu7-IE6	Narrowband high layer compatibility	MTu 7 NOT MTu 7	O N/A	3.2.5	[]Yes []No []N/A
MTu7-IE20	Notification indicator	MTu 7 NOT MTu 7	O N/A	3.2.5	[]Yes []No []N/A
MTu7-IE23	Progress indicator	MTu 7 NOT MTu 7	M N/A	3.2.5	[]Yes []No []N/A
Comments:					

Table A.29: Information elements in RELEASE transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu8-IE24	Cause		M	3.1.5, 3.2.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
MTu8-IE20	Notification indicator		O	3.1.5, 3.2.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
MTu8-IE22	Progress indicator		O	3.2.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.30: Information elements in RELEASE COMPLETE transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu9-IE24	Cause		M	3.1.6 note 2	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.31: Information elements in RESTART transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu10-IE13	Connection identifier		M	3.3.1	<input type="checkbox"/> Yes <input type="checkbox"/> No
MTu10-IE4	Restart indicator		M	3.3.1	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.32: Information elements in RESTART ACKNOWLEDGE transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu11-IE13	Connection identifier		M	3.3.2	<input type="checkbox"/> Yes <input type="checkbox"/> No
MTu11-IE4	Restart indicator		M	3.3.2	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.33: Information elements in SETUP transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu12-IE11	AAL parameters	MTu 12 NOT MTu 12	O N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE12	ATM traffic descriptor	MTu 12 NOT MTu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE16	Broadband bearer capability	MTu 12 NOT MTu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE18	Broadband high layer information	MTu 12 NOT MTu 12	O N/A	3.1.7	[]Yes []No []N/A
MTu12-IE8	Broadband repeat indicator	MCu 10 AND MTu 12 NOT (MCu 10 AND MTu 12)	O N/A	3.1.7, annex C	[]Yes []No []N/A
MTu12-IE17	Broadband low layer information	MTu 12 NOT MTu 12	O N/A	3.1.7	[]Yes []No []N/A
MTu12-IE1	Called party number	SCu2 NOT SCu2	O M	3.1.7, 3.2.7	[]Yes []No
MTu12-IE2	Called party subaddress	MTu 12 NOT MTu 12	O N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE9	Calling party number	MTu 12 NOT MTu 12	O N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE10	Calling party subaddress	MTu 12 NOT MTu 12	O N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE13	Connection identifier	MCu1.1 NOT MCu1.1	M O	3.1.7, 3.2.7	[]Yes []No
MTu12-IE19	End-to-end transit delay	MTu 12 NOT MTu 12	O N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE23	Narrowband bearer capability	MCu 9 NOT MCu 9	M N/A	3.2.7	[]Yes []No []N/A
MTu12-IE6	Narrowband high layer compatibility	MCu 9 NOT MCu 9	O N/A	3.2.7	[]Yes []No []N/A
MTu12-IE5	Narrowband low layer compatibility	MCu 9 NOT MCu 9	O N/A	3.2.7	[]Yes []No []N/A
MTu12-IE20	Notification indicator	MTu 12 NOT MTu 12	O N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE14	OAM traffic descriptor	MTu 12 NOT MTu 12	O N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE22	Progress indicator	MCu 9 NOT MCu 9	O N/A	3.2.7	[]Yes []No []N/A
MTu12-IE15	QOS parameter	MTu 12 NOT MTu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE7	Broadband sending complete	MTu 12 NOT MTu 12	M N/A	3.1.7, 3.2.7	[]Yes []No []N/A
MTu12-IE3	Transit network selection	MTu 12 NOT MTu 12	O N/A	3.1.7, 3.2.7	[]Yes []No []N/A
Comments:					

Table A.34: Information elements in SETUP ACKNOWLEDGE transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu13-IE13	Connection identifier	MTu 13 NOT MTu 13	M N/A	3.2.8	[]Yes []No []N/A
MTu13-IE20	Notification indicator	MTu 13 NOT MTu 13	O N/A	3.2.8	[]Yes []No []N/A
MTu13-IE22	Progress indicator	MTu 13 NOT MTu 13	O N/A	3.2.8	[]Yes []No []N/A
Comments:					

Table A.35: Information elements in STATUS transmitted by the user

Item	Information element	Conditions for status	Status	Reference	Support
MTu14-IE21	Call state		M	3.1.8	<input type="checkbox"/> Yes <input type="checkbox"/> No
MTu14-IE24	Cause		M	3.1.8	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

A.7.5 Timers

Indicating support for an item in table A.36 states that the implementation has a timer that operates in accordance with the description in clause 7 and with the relevant behaviour specified in clauses 5 and 6 of ITU-T Recommendation Q.2931 as modified by ETS 300 443-1 [1].

The table indicates the permitted range of values for each timer. The supplier shall state the values supported by their implementation.

Table A.36: Timers in the user role

Item	Timer: Does the implementation support...	Conditions for status	Status	Reference	Support	Values Allowed	Value Supported
TMu 1	T301	MCu 1 NOT MCu 1	O N/A	table 7-3	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	minim. 3 min	
TMu 2	T302	SCu 4 NOT SCu 4	M N/A	table 7-4	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	10 - 15 s	
TMu 3	T303	MCu 1 NOT MCu 1	M N/A	table 7-3	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	4 s	
TMu 4	T304	SCu 2 NOT SCu 2	O N/A	table 7-4	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	30 s	
TMu 5	T308		M	table 7-3	<input type="checkbox"/> Yes <input type="checkbox"/> No	30 s	
TMu 6	T309		M	table 7-3	<input type="checkbox"/> Yes <input type="checkbox"/> No	10 s	
TMu 7	T310	MCu 1 NOT MCu 1	M N/A	table 7-3	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	30 - 120 s	
TMu 8	T313	MCu 2 NOT MCu 2	M N/A	table 7-3	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A	4 s	
TMu 9	T316		M	table 7-3	<input type="checkbox"/> Yes <input type="checkbox"/> No	120 s	
TMu 10	T317		M	table 7-3	<input type="checkbox"/> Yes <input type="checkbox"/> No	< T316	
TMu 11	T322		M	table 7-3	<input type="checkbox"/> Yes <input type="checkbox"/> No	4 s	
Comments:							

A.7.6 Structure of information elements received

These tables are to be completed in order to evaluate the likelihood of successful interoperation of two implementations. The answers supplied are not used for conformance testing.

A.7.6.1 Broadband locking shift

Table A.37: Broadband locking shift information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 25.1	New codeset identification	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Codeset 4	M	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Codeset 5	M	5	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Codeset 6	M	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Codeset 7	M	7	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.6.2 Broadband non-locking shift

Table A.38: Broadband non-locking shift information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 26.1	Temporary codeset identification	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Codeset 0	M	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Codeset 4	M	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Codeset 5	M	5	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Codeset 6	M	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
	5. Codeset 7	M	7	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.6.3 ATM adaptation layer parameters

Table A.39: ATM adaptation layer parameters information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 11.1	AAL type	M		[]Yes []No
	1. AAL for voice	O	0	[]Yes []No
	2. AAL type 1	O	1	[]Yes []No
	3. AAL type 2	O	2	[]Yes []No
	4. AAL type 3/4	O	3	[]Yes []No
	5. AAL type 5	O	5	[]Yes []No
	6. User defined AAL	O	16	[]Yes []No
IERu 11.2	Subtype	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. Voice-band signal transport based on 64 kbit/s	O	1	[]Yes []No
	3. Circuit transport	O	2	[]Yes []No
	4. High-quality audio signal transport	O	4	[]Yes []No
	5. Video signal transport	O	5	[]Yes []No
IERu 11.3	CBR rate	O		[]Yes []No
	1. 64 kbit/s	O	1	[]Yes []No
	2. 1 544 kbit/s	O	4	[]Yes []No
	3. 6 312 kbit/s	O	5	[]Yes []No
	4. 32 064 kbit/s	O	6	[]Yes []No
	5. 44 736 kbit/s	O	7	[]Yes []No
	6. 97 728 kbit/s	O	8	[]Yes []No
	7. 2 048 kbit/s	O	16	[]Yes []No
	8. 8 448 kbit/s	O	17	[]Yes []No
	9. 34 368 kbit/s	O	18	[]Yes []No
	10. 139 264 kbit/s	O	19	[]Yes []No
	11. n x 64 kbit/s	O	64	[]Yes []No
	12. n x 8 kbit/s	O	65	[]Yes []No
IERu 11.4	Source clock frequency recovery method	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. Synchronous residual time stamp method	O	1	[]Yes []No
	3. Adaptive clock method	O	2	[]Yes []No
IERu 11.5	Error correction method	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. FEC for loss sensitive signal transport	O	1	[]Yes []No
	3. FEC for delay sensitive signal transport	O	2	[]Yes []No
IERu 11.6	Structured data transfer block size	O		[]Yes []No
IERu 11.7	Partially filled cells method	O		[]Yes []No
IERu 11.8	Forward maximum CPCS-SDU size	O		[]Yes []No
IERu 11.9	Backward maximum CPCS-SDU size	O		[]Yes []No
IERu 11.10	MID range	O		[]Yes []No
IERu 11.11	SSCS type	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. Data SSSC based on SSCOP (assured)	O	1	[]Yes []No
	3. Data SSSC based on SSCOP (non-assured)	O	2	[]Yes []No
	4. Frame relay SSSC	O	4	[]Yes []No
IERu 11.12	User defined AAL information	O		[]Yes []No
Comments:				

A.7.6.4 ATM traffic descriptor

Table A.40: ATM traffic descriptor information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 12.1	Forward peak cell rate (CLP=0)	O	N/A	[]Yes []No
	Backward peak cell rate (CLP=0)	O	N/A	[]Yes []No
	Forward peak cell rate (CLP=0+1)	M	N/A	[]Yes []No
	Backward peak cell rate (CLP=0+1)	M	N/A	[]Yes []No
Comments:				

A.7.6.5 Broadband bearer capability

Table A.41: Broadband bearer capability information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 16.1	Bearer class	M		[]Yes []No
	1. BCOB-A	O	1	[]Yes []No
	2. BCOB-C	O	3	[]Yes []No
	3. BCOB-X	O	16	[]Yes []No
IERu 16.2	Traffic type	O		[]Yes []No
	1. No indication	O	0	[]Yes []No
	2. Constant bit rate	O	1	[]Yes []No
	3. Variable bit rate	O	2	[]Yes []No
IERu 16.3	Timing requirements	O		[]Yes []No
	1. No indication	O	0	[]Yes []No
	2. End-to-end timing required	O	1	[]Yes []No
	3. End-to-end timing not required	O	2	[]Yes []No
IERu 16.4	Susceptibility to clipping	M		[]Yes []No
	1. Not susceptible to clipping	O	0	[]Yes []No
	2. Susceptible to clipping	O	1	[]Yes []No
IERu 16.5	User plane connection configuration	M		[]Yes []No
	1. Point-to-point	O	0	[]Yes []No
	2. Point-to-multipoint	O	1	[]Yes []No
Comments:				

A.7.6.6 Broadband high layer information

Table A.42: Broadband high layer information information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 18.1	High layer information type	M		[]Yes []No
	1. ISO/IEC	O	0	[]Yes []No
	2. User specific	O	1	[]Yes []No
	3. Vendor specific application identifier	O	3	[]Yes []No
	4. Reference to ITU-T SG 1 B-ISDN teleservice recommendation	O	4	[]Yes []No
Comments:				

A.7.6.7 Broadband low layer information

Table A.43: Broadband low layer information information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 17.1	User information layer 2 protocol	<input type="radio"/>		[]Yes []No
	1. Basic mode ISO 1745	<input type="radio"/>	1	[]Yes []No
	2. ITU-T Recommendation Q.921 (I.441)	<input type="radio"/>	2	[]Yes []No
	3. ITU-T Recommendation X.25 link layer	<input type="radio"/>	6	[]Yes []No
	4. ITU-T Recommendation X.25 multilink	<input type="radio"/>	7	[]Yes []No
	5. Extended LAPB; for half duplex operation	<input type="radio"/>	8	[]Yes []No
	6. HDLC ARM	<input type="radio"/>	9	[]Yes []No
	7. HDLC NRM	<input type="radio"/>	10	[]Yes []No
	8. HDLC ABM	<input type="radio"/>	11	[]Yes []No
	9. LAN logical link control (ISO/IEC 8802/2)	<input type="radio"/>	12	[]Yes []No
	10. ITU-T Recommendation X.75 SLP	<input type="radio"/>	13	[]Yes []No
	11. ITU-T Recommendation Q.922	<input type="radio"/>	14	[]Yes []No
	12. User specified	<input type="radio"/>	16	[]Yes []No
13. ISO/IEC 7776 DTE-DTE operation	<input type="radio"/>	17	[]Yes []No	
IERu 17.2	Mode of operation (octet 6a)	<input type="radio"/>		[]Yes []No
	1. Normal mode	<input type="radio"/>	1	[]Yes []No
	2. Extended mode	<input type="radio"/>	2	[]Yes []No
IERu 17.3	Q.33 use	<input type="radio"/>		[]Yes []No
IERu 17.4	User specified layer 2 protocol information	<input type="radio"/>		[]Yes []No
IERu 17.5	Window size	<input type="radio"/>		[]Yes []No
IERu 17.6	User information layer 3 protocol	<input type="radio"/>		[]Yes []No
	1. ITU-T Recommendation X.25, packet layer	<input type="radio"/>	6	[]Yes []No
	2. ISO/IEC 8208	<input type="radio"/>	7	[]Yes []No
	3. X.223 or ISO/IEC 8878	<input type="radio"/>	8	[]Yes []No
	4. X.233 or ISO/IEC 8473	<input type="radio"/>	9	[]Yes []No
	5. ITU-T Recommendation T.70	<input type="radio"/>	10	[]Yes []No
	6. ISO/IEC TR 9577	<input type="radio"/>	11	[]Yes []No
7. User specified	<input type="radio"/>	16	[]Yes []No	
IERu 17.7	Mode of operation (octet 7a)	<input type="radio"/>		[]Yes []No
	1. Normal packet sequence numbering	<input type="radio"/>	1	[]Yes []No
	2. Extended packet sequence numbering	<input type="radio"/>	2	[]Yes []No
IERu 17.8	User specified layer 3 protocol information	<input type="radio"/>		[]Yes []No
IERu 17.9	Default packet size	<input type="radio"/>		[]Yes []No
	1. 16 octets	<input type="radio"/>	4	[]Yes []No
	2. 32 octets	<input type="radio"/>	5	[]Yes []No
	3. 64 octets	<input type="radio"/>	6	[]Yes []No
	4. 128 octets	<input type="radio"/>	7	[]Yes []No
	5. 256 octets	<input type="radio"/>	8	[]Yes []No
	6. 512 octets	<input type="radio"/>	9	[]Yes []No
	7. 1 024 octets	<input type="radio"/>	10	[]Yes []No
	8. 2 048 octets	<input type="radio"/>	11	[]Yes []No
9. 4 096 octets	<input type="radio"/>	12	[]Yes []No	
IERu 17.10	Packet window size	<input type="radio"/>		[]Yes []No
IERu 17.11	Additional layer 3 protocol information for ISO/IEC TR 9577	<input type="radio"/>		[]Yes []No
Comments:				

A.7.6.8 Call state

Table A.44: Call state information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 21.1	Call state value	M		[]Yes []No
	1. Null	M	0	[]Yes []No
	2. Call initiated	M	1	[]Yes []No
	3. Overlap sending	O	2	[]Yes []No
	4. Outgoing call proceeding	M	3	[]Yes []No
	5. Call delivered	M	4	[]Yes []No
	6. Call present	M	6	[]Yes []No
	7. Call received	M	7	[]Yes []No
	8. Connect request	M	8	[]Yes []No
	9. Incoming call proceeding	M	9	[]Yes []No
	10. Active	M	10	[]Yes []No
	11. Release request	M	11	[]Yes []No
	12. Release indication	M	12	[]Yes []No
	13. Overlap receiving	O	25	[]Yes []No
	14. Restart null	M	0	[]Yes []No
	15. Restart request	M	61	[]Yes []No
16. Restart	M	62	[]Yes []No	
Comments:				

A.7.6.9 Called party number

Table A.45: Called party number information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 1.1	Type of number	M		[]Yes []No
	1. Unknown	O	0	[]Yes []No
	2. International	O	1	[]Yes []No
	3. National	O	2	[]Yes []No
	4. Network specific	O	3	[]Yes []No
	5. Subscriber	O	4	[]Yes []No
IERu 1.2	6. Abbreviated	O	6	[]Yes []No
	Addressing/numbering plan identification	M		[]Yes []No
	1. Unknown	O	0	[]Yes []No
	2. ISDN numbering plan	O	1	[]Yes []No
	3. NSAP addressing	O	2	[]Yes []No
4. Private numbering plan	O	9	[]Yes []No	
Comments:				

A.7.6.10 Called party subaddress

Table A.46: Called party subaddress information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 2.1	Type of subaddress	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. NSAP	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. User specified ATM endsystem address	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. User specified	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERu 2.2	Odd/even indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Even number of address signals	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Odd number of address signals	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.6.11 Calling party number

Table A.47: Calling party number information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 9.1	Type of number	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unknown	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. International	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. National	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Network specific	O	3	<input type="checkbox"/> Yes <input type="checkbox"/> No
	5. Subscriber	O	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	6. Abbreviated	O	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERu 9.2	Addressing/numbering plan identification	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unknown	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. ISDN numbering plan	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. NSAP addressing	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Private numbering plan	O	9	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERu 9.3	Presentation indicator	O		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Presentation allowed	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Presentation restricted	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Number not available	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERu 9.4	Screening indicator	O		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. User provided, not screened	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. User provided, verified and passed	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. User provided, verified and failed	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Network provided	O	3	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.6.12 Calling party subaddress

Table A.48: Calling party subaddress information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 10.1	Type of subaddress	M		[]Yes []No
	1. NSAP	O	0	[]Yes []No
	2. User specified ATM endsystem address	O	1	[]Yes []No
	3. User specified	O	2	[]Yes []No
IERu 10.2	Odd/even indicator	M		[]Yes []No
	1. Even number of address signals	O	0	[]Yes []No
	2. Odd number of address signals	O	1	[]Yes []No
Comments:				

A.7.6.13 Connection identifier

Table A.49: Connection identifier information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 13.1	VP-associated signalling	M		[]Yes []No
	1. VP-associated signalling	O	0	[]Yes []No
	2. Explicit indication of VPCI	M	1	[]Yes []No
IERu 13.2	Preferred/exclusive	M		[]Yes []No
	1. Exclusive VPCI, exclusive VCI	O	0	[]Yes []No
	2. Exclusive VPCI, any VCI	O	1	[]Yes []No
Comments:				

A.7.6.14 End-to-end transit delay

Table A.50: End-to-end transit delay information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 19.1	Maximum end-to-end transit delay	O		[]Yes []No
Comments:				

A.7.6.15 Quality of service parameter

Table A.51: Quality of service parameter information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 15.1	QOS class forward	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unspecified QOS class	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Parameterized QOS	O	255	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERu 15.2	QOS class backward	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unspecified QOS class	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Parameterized QOS	O	255	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.6.16 Restart indicator

Table A.52: Restart indicator information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 4.1	Class	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Indicated virtual channel	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. All VCs in indicated VPC controlled by the signalling VC	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. All VCs controlled by the layer 3 entity	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.6.17 OAM traffic descriptor

Table A.53: OAM traffic descriptor information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERu 14.1	Shaping indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. No user requirement	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Aggregate shaping not allowed	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERu 14.2	Compliance indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Optional end-to-end OAM F5 flow	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Mandatory end-to-end OAM F5 flow	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERu 14.3	User-network fault management indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. No user-originated indications	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Use of user-originated indications	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERu 14.4	Forward end-to-end OAM F5 flow indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. 0 %	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. 0,1 %	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. 1 %	O	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERu 14.5	Backward end-to-end OAM F5 flow indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. 0 %	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. 0,1 %	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. 1 %	O	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.7 Structure of information elements transmitted

These tables are to be completed in order to evaluate the likelihood of successful interoperation of two implementations. The answers supplied are not used for conformance testing.

A.7.7.1 Broadband locking shift

Table A.54: Broadband locking shift information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 25.1	New codeset identification			<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Codeset 4	M	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Codeset 5	M	5	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Codeset 6	M	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Codeset 7	M	7	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.7.2 Broadband non-locking shift

Table A.55: Broadband non-locking shift information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 26.1	Temporary codeset identification			<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Codeset 0	M	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Codeset 4	M	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Codeset 5	M	5	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Codeset 6	M	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
	5. Codeset 7	M	7	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.7.3 ATM adaptation layer parameters

Table A.56: ATM adaptation layer parameters information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 11.1	AAL type	M		[]Yes []No
	1. AAL for voice	O	0	[]Yes []No
	2. AAL type 1	O	1	[]Yes []No
	3. AAL type 2	O	2	[]Yes []No
	4. AAL type 3/4	O	3	[]Yes []No
	5. AAL type 5	O	5	[]Yes []No
IETu 11.2	6. User defined AAL	O	16	[]Yes []No
	Subtype	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. Voice-band signal transport based on 64 kbit/s	O	1	[]Yes []No
	3. Circuit transport	O	2	[]Yes []No
IETu 11.3	4. High-quality audio signal transport	O	4	[]Yes []No
	5. Video signal transport	O	5	[]Yes []No
	CBR rate	O		[]Yes []No
	1. 64 kbit/s	O	1	[]Yes []No
	2. 1 544 kbit/s	O	4	[]Yes []No
	3. 6 312 kbit/s	O	5	[]Yes []No
	4. 32 064 kbit/s	O	6	[]Yes []No
	5. 44 736 kbit/s	O	7	[]Yes []No
	6. 97 728 kbit/s	O	8	[]Yes []No
	7. 2 048 kbit/s	O	16	[]Yes []No
	8. 8 448 kbit/s	O	17	[]Yes []No
	9. 34 368 kbit/s	O	18	[]Yes []No
10. 139 264 kbit/s	O	19	[]Yes []No	
11. n x 64 kbit/s	O	64	[]Yes []No	
12. n x 8 kbit/s	O	65	[]Yes []No	
IETu 11.4	Source clock frequency recovery method	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. Synchronous residual time stamp method	O	1	[]Yes []No
IETu 11.5	3. Adaptive clock method	O	2	[]Yes []No
	Error correction method	O		[]Yes []No
	1. Null	O	0	[]Yes []No
IETu 11.6	2. FEC for loss sensitive signal transport	O	1	[]Yes []No
	3. FEC for delay sensitive signal transport	O	2	[]Yes []No
IETu 11.7	Structured data transfer block size	O		[]Yes []No
IETu 11.8	Partially filled cells method	O		[]Yes []No
IETu 11.9	Forward maximum CPCS-SDU size	O		[]Yes []No
IETu 11.10	Backward maximum CPCS-SDU size	O		[]Yes []No
IETu 11.11	MID range	O		[]Yes []No
IETu 11.12	SSCS type	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. Data SSSC based on SSCOP (assured)	O	1	[]Yes []No
	3. Data SSSC based on SSCOP (non-assured)	O	2	[]Yes []No
IETu 11.12	4. Frame relay SSSC	O	4	[]Yes []No
	User defined AAL information	O		[]Yes []No
Comments:				

A.7.7.4 ATM traffic descriptor

Table A.57: ATM traffic descriptor information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 12.1	Forward peak cell rate (CLP=0)	O	N/A	[]Yes []No
	Backward peak cell rate (CLP=0)	O	N/A	[]Yes []No
	Forward peak cell rate (CLP=0+1)	M	N/A	[]Yes []No
	Backward peak cell rate (CLP=0+1)	M	N/A	[]Yes []No
Comments:				

A.7.7.5 Broadband bearer capability

Table A.58: Broadband bearer capability information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 16.1	Bearer class	M		[]Yes []No
	1. BCOB-A	O	1	[]Yes []No
	2. BCOB-C	O	3	[]Yes []No
	3. BCOB-X	O	16	[]Yes []No
IETu 16.2	Traffic type	O		[]Yes []No
	1. No indication	O	0	[]Yes []No
	2. Constant bit rate	O	1	[]Yes []No
	3. Variable bit rate	O	2	[]Yes []No
IETu 16.3	Timing requirements	O		[]Yes []No
	1. No indication	O	0	[]Yes []No
	2. End-to-end timing required	O	1	[]Yes []No
	3. End-to-end timing not required	O	2	[]Yes []No
IETu 16.4	Susceptibility to clipping	M		[]Yes []No
	1. Not susceptible to clipping	O	0	[]Yes []No
	2. Susceptible to clipping	O	1	[]Yes []No
IETu 16.5	User plane connection configuration	M		[]Yes []No
	1. Point-to-point	O	0	[]Yes []No
	2. Point-to-multipoint	O	1	[]Yes []No
Comments:				

A.7.7.6 Broadband high layer information

Table A.59: Broadband high layer information information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 18.1	High layer information type	M		[]Yes []No
	1. ISO/IEC	O	0	[]Yes []No
	2. User specific	O	1	[]Yes []No
	3. Vendor specific application identifier	O	3	[]Yes []No
	4. Reference to ITU-T SG 1 B-ISDN teleservice recommendation	O	4	[]Yes []No
Comments:				

A.7.7.7 Broadband low layer information

Table A.60: Broadband low layer information information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 17.1	User information layer 2 protocol	<input type="radio"/>		[]Yes []No
	1. Basic mode ISO 1745	<input type="radio"/>	1	[]Yes []No
	2. ITU-T Recommendation Q.921 (I.441)	<input type="radio"/>	2	[]Yes []No
	3. ITU-T Recommendation X.25 link layer	<input type="radio"/>	6	[]Yes []No
	4. ITU-T Recommendation X.25 multilink	<input type="radio"/>	7	[]Yes []No
	5. Extended LAPB; for half duplex operation	<input type="radio"/>	8	[]Yes []No
	6. HDLC ARM	<input type="radio"/>	9	[]Yes []No
	7. HDLC NRM	<input type="radio"/>	10	[]Yes []No
	8. HDLC ABM	<input type="radio"/>	11	[]Yes []No
	9. LAN logical link control (ISO/IEC 8802/2)	<input type="radio"/>	12	[]Yes []No
	10. ITU-T Recommendation X.75 SLP	<input type="radio"/>	13	[]Yes []No
	11. ITU-T Recommendation Q.922	<input type="radio"/>	14	[]Yes []No
	12. User specified	<input type="radio"/>	16	[]Yes []No
13. ISO/IEC 7776 DTE-DTE operation	<input type="radio"/>	17	[]Yes []No	
IETu 17.2	Mode of operation (octet 6a)	<input type="radio"/>		[]Yes []No
	1. Normal mode	<input type="radio"/>	1	[]Yes []No
	2. Extended mode	<input type="radio"/>	2	[]Yes []No
IETu 17.3	Q.33 use	<input type="radio"/>		[]Yes []No
IETu 17.4	User specified layer 2 protocol information	<input type="radio"/>		[]Yes []No
IETu 17.5	Window size	<input type="radio"/>		[]Yes []No
IETu 17.6	User information layer 3 protocol	<input type="radio"/>		[]Yes []No
	1. ITU-T Recommendation X.25, packet layer	<input type="radio"/>	6	[]Yes []No
	2. ISO/IEC 8208	<input type="radio"/>	7	[]Yes []No
	3. X.223 or ISO/IEC 8878	<input type="radio"/>	8	[]Yes []No
	4. X.233 or ISO/IEC 8473	<input type="radio"/>	9	[]Yes []No
	5. ITU-T Recommendation T.70	<input type="radio"/>	10	[]Yes []No
	6. ISO/IEC TR 9577	<input type="radio"/>	11	[]Yes []No
7. User specified	<input type="radio"/>	16	[]Yes []No	
IETu 17.7	Mode of operation (octet 7a)	<input type="radio"/>		[]Yes []No
	1. Normal packet sequence numbering	<input type="radio"/>	1	[]Yes []No
	2. Extended packet sequence numbering	<input type="radio"/>	2	[]Yes []No
IETu 17.8	User specified layer 3 protocol information	<input type="radio"/>		[]Yes []No
IETu 17.9	Default packet size	<input type="radio"/>		[]Yes []No
	1. 16 octets	<input type="radio"/>	4	[]Yes []No
	2. 32 octets	<input type="radio"/>	5	[]Yes []No
	3. 64 octets	<input type="radio"/>	6	[]Yes []No
	4. 128 octets	<input type="radio"/>	7	[]Yes []No
	5. 256 octets	<input type="radio"/>	8	[]Yes []No
	6. 512 octets	<input type="radio"/>	9	[]Yes []No
	7. 1 024 octets	<input type="radio"/>	10	[]Yes []No
	8. 2 048 octets	<input type="radio"/>	11	[]Yes []No
9. 4 096 octets	<input type="radio"/>	12	[]Yes []No	
IETu 17.10	Packet window size	<input type="radio"/>		[]Yes []No
IETu 17.11	Additional layer 3 protocol information for ISO/IEC TR 9577	<input type="radio"/>		[]Yes []No
Comments:				

A.7.7.8 Call state

Table A.61: Call state information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 21.1	Call state value	M		[]Yes []No
	1. Null	M	0	[]Yes []No
	2. Call initiated	M	1	[]Yes []No
	3. Overlap sending	O	2	[]Yes []No
	4. Outgoing call proceeding	M	3	[]Yes []No
	5. Call delivered	M	4	[]Yes []No
	6. Call present	M	6	[]Yes []No
	7. Call received	M	7	[]Yes []No
	8. Connect request	M	8	[]Yes []No
	9. Incoming call proceeding	M	9	[]Yes []No
	10. Active	M	10	[]Yes []No
	11. Release request	M	11	[]Yes []No
	12. Release indication	M	12	[]Yes []No
	13. Overlap receiving	O	25	[]Yes []No
	14. Restart null	M	0	[]Yes []No
	15. Restart request	M	61	[]Yes []No
16. Restart	M	62	[]Yes []No	
Comments:				

A.7.7.9 Called party number

Table A.62: Called party number information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 1.1	Type of number	M		[]Yes []No
	1. Unknown	O	0	[]Yes []No
	2. International	O	1	[]Yes []No
	3. National	O	2	[]Yes []No
	4. Network specific	O	3	[]Yes []No
	5. Subscriber	O	4	[]Yes []No
IETu 1.2	6. Abbreviated	O	6	[]Yes []No
	Addressing/numbering plan identification	M		[]Yes []No
	1. Unknown	O	0	[]Yes []No
	2. ISDN numbering plan	O	1	[]Yes []No
	3. NSAP addressing	O	2	[]Yes []No
	4. Private numbering plan	O	9	[]Yes []No
Comments:				

A.7.7.10 Called party subaddress

Table A.63: Called party subaddress information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 2.1	Type of subaddress	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. NSAP	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. User specified ATM endsystem address	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. User specified	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETu 2.2	Odd/even indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Even number of address signals	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Odd number of address signals	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.7.11 Calling party number

Table A.64: Calling party number information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 9.1	Type of number	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unknown	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. International	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. National	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Network specific	O	3	<input type="checkbox"/> Yes <input type="checkbox"/> No
	5. Subscriber	O	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	6. Abbreviated	O	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETu 9.2	Addressing/numbering plan identification	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unknown	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. ISDN numbering plan	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. NSAP addressing	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Private numbering plan	O	9	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETu 9.3	Presentation indicator	O		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Presentation allowed	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Presentation restricted	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Number not available	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETu 9.4	Screening indicator	O		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. User provided, not screened	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. User provided, verified and passed	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. User provided, verified and failed	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Network provided	O	3	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.7.7.12 Calling party subaddress

Table A.65: Calling party subaddress information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 10.1	Type of subaddress	M		[]Yes []No
	1. NSAP	O	0	[]Yes []No
	2. User specified ATM endsystem address	O	1	[]Yes []No
	3. User specified	O	2	[]Yes []No
IETu 10.2	Odd/even indicator	M		[]Yes []No
	1. Even number of address signals	O	0	[]Yes []No
	2. Odd number of address signals	O	1	[]Yes []No
Comments:				

A.7.7.13 Connection identifier

Table A.66: Connection identifier information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 13.1	VP-associated signalling	M		[]Yes []No
	1. VP-associated signalling	O	0	[]Yes []No
	2. Explicit indication of VPCI	M	1	[]Yes []No
IETu 13.2	Preferred/exclusive	M		[]Yes []No
	1. Exclusive VPCI, exclusive VCI	O	0	[]Yes []No
	2. Exclusive VPCI, any VCI	O	1	[]Yes []No
Comments:				

A.7.7.14 End-to-end transit delay

Table A.67: End-to-end transit delay information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 19.1	Maximum end-to-end transit delay	O		[]Yes []No
Comments:				

A.7.7.15 Quality of service parameter

Table A.68: Quality of service parameter information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 15.1	QOS class forward	M		[]Yes []No
	1. Unspecified QOS class	O	0	[]Yes []No
	2. Parameterized QOS	O	255	[]Yes []No
IETu 15.2	QOS class backward	M		[]Yes []No
	1. Unspecified QOS class	O	0	[]Yes []No
	2. Parameterized QOS	O	255	[]Yes []No
Comments:				

A.7.7.16 Restart indicator

Table A.69: Restart indicator information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 4.1	Class	M		[]Yes []No
	1. Indicated virtual channel	O	0	[]Yes []No
	2. All VCs in indicated VPC controlled by the signalling VC	O	1	[]Yes []No
	3. All VCs controlled by the layer 3 entity	O	2	[]Yes []No
Comments:				

A.7.7.17 Transit network selection

Table A.70: Transit network selection information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 3.1	Type of network identification	M		[]Yes []No
	1. User specified	O	0	[]Yes []No
	2. National network identification	O	2	[]Yes []No
	3. International network identification	O	3	[]Yes []No
IETu 3.2	Network identification plan	M		[]Yes []No
	1. Unknown	O	0	[]Yes []No
	2. Carrier identification code	O	1	[]Yes []No
	3. Data network identification code	O	3	[]Yes []No
Comments:				

A.7.7.18 OAM traffic descriptor

Table A.71: OAM traffic descriptor information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETu 14.1	Shaping indicator	M		[]Yes []No
	1. No user requirement	O	0	[]Yes []No
	2. Aggregate shaping not allowed	O	1	[]Yes []No
IETu 14.2	Compliance indicator	M		[]Yes []No
	1. Optional end-to-end OAM F5 flow	O	0	[]Yes []No
	2. Mandatory end-to-end OAM F5 flow	O	1	[]Yes []No
IETu 14.3	User-network fault management indicator	M		[]Yes []No
	1. No user-originated indications	O	0	[]Yes []No
	2. Use of user-originated indications	O	1	[]Yes []No
IETu 14.4	Forward end-to-end OAM F5 flow indicator	M		[]Yes []No
	1. 0 %	O	0	[]Yes []No
	2. 0,1 %	O	1	[]Yes []No
	3. 1 %	O	4	[]Yes []No
IETu 14.5	Backward end-to-end OAM F5 flow indicator	M		[]Yes []No
	1. 0 %	O	0	[]Yes []No
	2. 0,1 %	O	1	[]Yes []No
	3. 1 %	O	4	[]Yes []No
Comments:				

A.8 Network

The tables provided in this clause need only to be completed for network implementations:

Prerequisite: R 2

A.8.1 Major capabilities

Each question in table A.72 refers to a major function of the protocol. Answering "Yes" to a particular question states that the implementation supports all the mandatory procedures for that function defined in the referenced clauses and subclauses of ITU-T Recommendation Q.2931 as modified by ETS 300 443-1 [1]. Answering "No" to a particular question states that the implementation does not support that function of the protocol.

Table A.72: Major capabilities of the network role

Item	Major capability: Does the implementation support...	Conditions for status	Status	Reference	Support
Call establishment at the originating interface					
MCn 1	call establishment at the originating interface (outgoing calls from the user's point of view)		M	5.1	[]Yes []No
MCn 1.1	support associated signalling on the originating side		O	5.1.2	[]Yes []No
Call establishment at the destination interface					
MCn 2	call establishment at the destination interface (incoming calls from the user's point of view)		M	5.2	[]Yes []No
MCn 2.1	support associated signalling on the destination side		O	5.2.3	[]Yes []No
Others					
MCn 3	initiation of call clearing		M	5.4	[]Yes []No
MCn 4	restart procedure		M	5.5	[]Yes []No
MCn 5	handling of error conditions		M	5.6	[]Yes []No
MCn 5.1	invoke the status enquiry procedure on receipt of an AAL-ESTABLISH.indication in the call establishment phase		O	5.6.9 b)	[]Yes []No
MCn 6	error procedures with explicit action indication		M	5.7	[]Yes []No
MCn 7	handling of messages with insufficient information		M	5.8	[]Yes []No
MCn 8	notification procedures		M	5.9	[]Yes []No
MCn 9	additional procedures for the provision of 64 kbit/s circuit-mode services		O	6	[]Yes []No
MCn 11	transit network selection procedures		O	clause D.2	[]Yes []No
MCn 13	handling of the OAM traffic descriptor		O	annex I	[]Yes []No
Comments:					

A.8.2 Subsidiary capabilities

Indicating support for an item in table A.73 states that the implementation supports special cases or options within a major capability.

Table A.73: Subsidiary capabilities of the network role

Item	Subsidiary capability: Does the implementation support...	Conditions for status	Status	Reference	Support
Call establishment at the originating interface					
SCn 1	sending of the called party address information in the Called party number information element		M	5.1.1	[]Yes []No
SCn 2	overlap sending	MCn 9 NOT MCn 9	M N/A	6.5.2	[]Yes []No []N/A
Call establishment at the destination interface					
SCn 4	overlap receiving	MCn 9 NOT MCn 9	M N/A	6.5.3	[]Yes []No []N/A
SCn 5	sending of Broadband sending complete information element	SCn 4 NOT SCn4	O M	6.5.3	[]Yes []No
Comments:					

A.8.3 PDUs

The tables in this subclause ask questions related to the supported PDUs in the network role. In the DSS2 protocol, PDUs are known by the term "messages".

A.8.3.1 Messages received by the network

Indicating support for an item in table A.74 states that the implementation has the ability to recognize the message listed in that item. Support for the receipt of a particular type of PDU means support for recognising and acting upon all valid instances of that PDU type, including all valid PDU parameters, to the extent required by ETS 300 443-1 [1].

Table A.74: Messages received by the network

Item	Message: Does the implementation support the receipt of...	Conditions for status	Status	Reference	Support
MRn 1	ALERTING		M	3.1.1, 3.2.1, 5.2.5	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 2	CALL PROCEEDING		M	3.1.2, 3.2.2, 5.2.5	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 3	CONNECT		M	3.1.3, 3.2.3, 5.2.7	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 4	CONNECT ACKNOWLEDGE		M	3.1.4, 5.1.7	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 5	INFORMATION	MCn 9 NOT MCn 9	M N/A	3.2.4, 6.5.2	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
MRn 6	NOTIFY		M	3.1.10, 5.9	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 7	PROGRESS	MCn 9 NOT MCn 9	M N/A	3.2.5, 6.6.1, 6.6.2	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
MRn 8	RELEASE		M	3.1.5, 3.2.6, 5.4.3, 5.4.5	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 9	RELEASE COMPLETE		M	3.1.6, 5.2.2.2.2, 5.2.3, 5.2.4, 5.2.5, 5.4.2, 5.4.4, 5.6.3.2, 5.6.4, 5.6.7, 5.6.8.1, 5.7.2	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 10	RESTART		M	3.3.1, 5.5.2	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 11	RESTART ACKNOWLEDGE		M	3.3.2, 5.5.1	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 12	SETUP		M	3.1.7, 3.2.7, 5.1	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 13	SETUP ACKNOWLEDGE	MCn 9 NOT MCn 9	M N/A	3.2.8, 6.5.3	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
MRn 14	STATUS		M	3.1.8, 5.6.3.2, 5.6.12	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn 15	STATUS ENQUIRY		M	3.1.9, 5.6.3.2, 5.6.11	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

A.8.3.2 Messages transmitted by the network

Indicating support for an item in table A.75 states that the implementation has the ability to transmit the message listed in that item.

Table A.75: Messages transmitted by the network

Item	Message: Does the implementation support the receipt of...	Conditions for status	Status	Reference	Support
MTn 1	ALERTING		M	3.1.1, 3.2.1, 5.1.6	[]Yes []No
MTn 2	CALL PROCEEDING		M	3.1.2, 3.2.2, 5.1.5	[]Yes []No
MTn 3	CONNECT		M	3.1.3, 3.2.3, 5.1.7	[]Yes []No
MTn 4	CONNECT ACKNOWLEDGE		M	3.1.4, 5.2.7	[]Yes []No
MTn 5	INFORMATION	MCn 9 NOT MCn 9	M N/A	3.2.4, 6.5.3	[]Yes []No []N/A
MTn 6	NOTIFY		M	3.1.10, 5.9	[]Yes []No
MTn 7	PROGRESS	MCn 9 NOT MCn 9	M N/A	3.2.5, 6.6.1, 6.6.2	[]Yes []No []N/A
MTn 8	RELEASE		M	3.1.5, 3.2.6, 5.4.4	[]Yes []No
MTn 9	RELEASE COMPLETE		M	3.1.6, 5.1.2, 5.1.3, 5.4.2, 5.4.3, 5.6.3, 5.6.7, 5.6.8.1, 5.6.12, 5.7.2	[]Yes []No
MTn 10	RESTART		M	3.3.1, 5.5.1	[]Yes []No
MTn 11	RESTART ACKNOWLEDGE		M	3.3.2, 5.5.2	[]Yes []No
MRn 12	SETUP		M	3.1.7, 3.2.7, 5.2	[]Yes []No
MTn 13	SETUP ACKNOWLEDGE	MCn 9 NOT MCn 9	M N/A	3.2.8, 6.5.2	[]Yes []No []N/A
MTn 14	STATUS		M	3.1.8, 5.5.2.1, 5.6.3.2, 5.6.4, 5.6.7, 5.6.8, 5.6.11, 5.7	[]Yes []No
MTn 15	STATUS ENQUIRY		M	3.1.9, 5.6.3.2, 5.6.11	[]Yes []No
Comments:					

A.8.4 PDU parameters

The tables in this subclause ask questions related to the support of PDU parameters in messages received and transmitted by the IUT in the network role. In the DSS2, protocol PDU parameters are known by the term "information elements".

Tables A.76 and A.77 deal with the four information elements that appear in all messages that are either received or transmitted (respectively) by the IUT in the network role (Protocol discriminator, Call reference, Message type and Message length) and two information elements which may appear in a message for which it is mandatory for the receiver to interpret (shift information elements).

Table A.76: Information elements in all messages received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn-IE1	Protocol discriminator		M	3.1, 3.2, 4.2	[]Yes []No
MRn-IE2	Call reference		M	3.1, 3.2, 4.3	[]Yes []No
MRn-IE3	Message type		M	3.1, 3.2, 4.4.1	[]Yes []No
MRn-IE4	Message length		M	3.1, 3.2, 4.4.2	[]Yes []No
MRn-IE5	Broadband locking shift		M	4.5.3	[]Yes []No
MRn-IE25	Broadband non-locking shift		M	4.5.4	[]Yes []No
Comments:					

Table A.77: Information elements in all messages transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn-IE1	Protocol discriminator		M	3.1, 3.2, 4.2	[]Yes []No
MTn-IE2	Call reference		M	3.1, 3.2, 4.3	[]Yes []No
MTn-IE3	Message type		M	3.1, 3.2, 4.4.1	[]Yes []No
MTn-IE4	Message length		M	3.1, 3.2, 4.4.2	[]Yes []No
MTn-IE5	Broadband locking shift		O	4.5.3	[]Yes []No
MTn-IE25	Broadband non-locking shift		O	4.5.4	[]Yes []No
Comments:					

A.8.4.1 Information elements in messages received by the network

Indicating support for an item in the tables in this subclause states that the implementation has the ability to process the information elements listed in the specified received messages.

Table A.78: Information elements in ALERTING received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn1-IE13	Connection identifier		M	3.1.1, 3.2.1	[]Yes []No
MRn 1-IE23	Narrowband bearer capability	MCn 9 NOT MCn 9	O N/A	3.2.1	[]Yes []No []N/A
MRn1-IE6	Narrowband high layer compatibility	MCn 9 NOT MCn 9	O N/A	3.2.1	[]Yes []No []N/A
MRn1-IE20	Notification indicator		M	3.1.1, 3.2.1	[]Yes []No
MRn1-IE22	Progress indicator	MCn 9 NOT MCn 9	M N/A	3.2.1	[]Yes []No []N/A
Comments:					

Table A.79: Information elements in CALL PROCEEDING received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn2-IE13	Connection identifier		M	3.1.2, 3.2.2	[]Yes []No
MRn2-IE23	Narrowband bearer capability	MCn 9 NOT MCn 9	O N/A	3.2.2	[]Yes []No []N/A
MRn2-IE6	Narrowband high layer compatibility	MCn 9 NOT MCn 9	O N/A	3.2.2	[]Yes []No []N/A
MRn2-IE20	Notification indicator		M	3.1.2, 3.2.2	[]Yes []No
MRn2-IE22	Progress indicator	MCn 9 NOT MCn 9	M N/A	3.2.2	[]Yes []No []N/A
Comments:					

Table A.80: Information elements in CONNECT received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn3-IE11	AAL parameters		M	3.1.3, 3.2.3	[]Yes []No
MRn3-IE17	Broadband low layer information		M	3.1.3	[]Yes []No
MRn3-IE13	Connection identifier		M	3.1.3, 3.2.3	[]Yes []No
MRn3-IE19	End-to-end transit delay		M	3.1.3, 3.2.3	[]Yes []No
MRn3-IE23	Narrowband bearer capability	MCn 9 NOT MCn 9	O N/A	3.2.3	[]Yes []No []N/A
MRn3-IE6	Narrowband high layer compatibility	MCn 9 NOT MCn 9	O N/A	3.2.3	[]Yes []No []N/A
MRn3-IE5	Narrowband low layer compatibility	MCn 9 NOT MCn 9	M N/A	3.2.3	[]Yes []No []N/A
MRn3-IE20	Notification indicator		M	3.1.3, 3.2.3	[]Yes []No
MRn3-IE14	OAM traffic descriptor		M	3.1.3, 3.2.3	[]Yes []No
MRn3-IE23	Progress indicator	MCn 9 NOT MCn 9	M N/A	3.2.3	[]Yes []No []N/A
Comments:					

Table A.81: Information elements in CONNECT ACKNOWLEDGE received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn4-IE20	Notification indicator		M	3.1.4	[]Yes []No
Comments:					

Table A.82: Information elements in INFORMATION received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn5-IE7	Broadband sending complete	MRn 5 NOT MRn 5	M N/A	3.2.4	[]Yes []No []N/A
MRn5-IE1	Called party number	MRn 5 NOT MRn 5	M N/A	3.2.4	[]Yes []No []N/A
Comments:					

Table A.83: Information elements in NOTIFY received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn6-IE20	Notification indicator		M	3.1.10	[]Yes []No
Comments:					

Table A.84: Information elements in PROGRESS received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn7-IE23	Narrowband bearer capability	MRn 7 NOT MRn 7	O N/A	3.2.5	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
MRn7-IE6	Narrowband high layer compatibility	MRn 7 NOT MRn 7	O N/A	3.2.5	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
MRn7-IE20	Notification indicator	MRn 7 NOT MRn 7	M N/A	3.2.5	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
MRn7-IE23	Progress indicator	MRn 7 NOT MRn 7	M N/A	3.2.5	<input type="checkbox"/> Yes <input type="checkbox"/> No <input type="checkbox"/> N/A
Comments:					

Table A.85: Information elements in RELEASE received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn8-IE24	Cause		M	3.1.5, 3.2.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn8-IE20	Notification indicator		M	3.1.5, 3.2.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn8-IE22	Progress indicator		M	3.2.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.86: Information elements in RELEASE COMPLETE received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn9-IE24	Cause		M	3.1.6	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.87: Information elements in RESTART received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn10-IE13	Connection identifier		M	3.3.1	<input type="checkbox"/> Yes <input type="checkbox"/> No
MRn10-IE4	Restart indicator		M	3.3.1	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:					

Table A.88: Information elements in RESTART ACKNOWLEDGE received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn11-IE13	Connection identifier		M	3.3.2	[]Yes []No
MRn11-IE	Restart indicator		M	3.3.2	[]Yes []No
Comments:					

Table A.89: Information elements in SETUP received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn12-IE11	AAL parameters		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE12	ATM traffic descriptor		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE16	Broadband bearer capability		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE18	Broadband high layer information		M	3.1.7	[]Yes []No
MRn12-IE8	Broadband repeat indicator		M	3.1.7, annex C	[]Yes []No
MRn12-IE17	Broadband low layer information		M	3.1.7	[]Yes []No
MRn12-IE1	Called party number		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE2	Called party subaddress		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE9	Calling party number		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE10	Calling party subaddress		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE13	Connection identifier		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE19	End-to-end transit delay		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE23	Narrowband bearer capability	MCn 9 NOT MCn 9	M N/A	3.2.7	[]Yes []No []N/A
MRn12-IE6	Narrowband high layer compatibility	MCn 9 NOT MCn 9	M N/A	3.2.7	[]Yes []No []N/A
MRn12-IE5	Narrowband low layer compatibility	MCn 9 NOT MCn 9	M N/A	3.2.7	[]Yes []No []N/A
MRn12-IE20	Notification indicator		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE14	OAM traffic descriptor		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE22	Progress indicator	MCn 9 NOT MCn 9	M N/A	3.2.7	[]Yes []No []N/A
MRn12-IE15	QOS parameter		M	3.1.7, 3.2.7	[]Yes []No
MRn12-IE7	Broadband sending complete		O	3.1.7, 3.2.7	[]Yes []No
MRn12-IE3	Transit network selection		O	3.1.7, 3.2.7	[]Yes []No
Comments:					

Table A.90: Information elements in SETUP ACKNOWLEDGE received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn13-IE13	Connection identifier	MRn 13 NOT MRn 13	M N/A	3.2.8	[]Yes []No []N/A
MRn13-IE20	Notification indicator	MRn 13 NOT MRn 13	M N/A	3.2.8	[]Yes []No []N/A
MRn13-IE22	Progress indicator	MRn 13 NOT MRn 13	M N/A	3.2.8	[]Yes []No []N/A
Comments:					

Table A.91: Information elements in STATUS received by the network

Item	Information element	Conditions for status	Status	Reference	Support
MRn14-IE21	Call state		M	3.1.8	[]Yes []No
MRn14-IE24	Cause		M	3.1.8	[]Yes []No
Comments:					

A.8.4.2 Information elements in messages transmitted by the network

Indicating support for an item in the tables in this subclause states that the implementation has the ability to generate, and to transmit in the specified message, the information elements listed. Such support does not necessarily mean that the indicated information element is included in every instance of the transmitted message.

Table A.92: Information elements in ALERTING transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn1-IE13	Connection identifier		O	3.1.1 note 1, 3.2.1 note 1	[]Yes []No
MTn1-IE23	Narrowband bearer capability	MCn 9 NOT MCn 9	O N/A	3.2.1	[]Yes []No []N/A
MTn1-IE6	Narrowband high layer compatibility	MCn 9 NOT MCn 9	O N/A	3.2.1	[]Yes []No []N/A
MTn1-IE20	Notification indicator		O	3.1.1, 3.2.1	[]Yes []No
MTn1-IE22	Progress indicator	MCn 9 NOT MCn 9	O N/A	3.2.1	[]Yes []No []N/A
Comments:					

Table A.93: Information elements in CALL PROCEEDING transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn2-IE13	Connection identifier		M	3.1.2 note 1, 3.2.2 note 1	[]Yes []No
MTn2-IE23	Narrowband bearer capability	MCn 9 NOT MCn 9	O N/A	3.2.2	[]Yes []No []N/A
MTn2-IE6	Narrowband high layer compatibility	MCn 9 NOT MCn 9	O N/A	3.2.2	[]Yes []No []N/A
MTn2-IE20	Notification indicator		O	3.1.2, 3.2.2	[]Yes []No
MTn2-IE22	Progress indicator	MCn 9 NOT MCn 9	O N/A	3.2.2	[]Yes []No []N/A
Comments:					

Table A.94: Information elements in CONNECT transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn3-IE11	AAL parameters		M	3.1.3 note 1, 3.2.3 note 1	[]Yes []No
MTn3-IE17	Broadband low layer information		O	3.1.3	[]Yes []No
MTn3-IE13	Connection identifier		O	3.1.3 note 3, 3.2.3 note 2	[]Yes []No
MTn3-IE19	End-to-end transit delay		M	3.1.3 note 4	[]Yes []No
MTn3-IE23	Narrowband bearer capability	MCn 9 NOT MCn 9	O N/A	3.2.3	[]Yes []No []N/A
MTn3-IE6	Narrowband high layer compatibility	MCn 9 NOT MCn 9	O N/A	3.2.3	[]Yes []No []N/A
MTn3-IE5	Narrowband low layer compatibility	MCn 9 NOT MCn 9	M N/A	3.2.3 note 6	[]Yes []No []N/A
MTn3-IE20	Notification indicator		O	3.1.3, 3.2.3	[]Yes []No
MTn3-IE14	OAM traffic descriptor		M	3.1.3, 3.2.3	[]Yes []No
MTn3-IE23	Progress indicator	MCn 9 NOT MCn 9	O N/A	3.2.3	[]Yes []No []N/A
Comments:					

Table A.95: Information elements in CONNECT ACKNOWLEDGE transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn4-IE20	Notification indicator		O	3.1.4	[]Yes []No
Comments:					

Table A.96: Information elements in INFORMATION transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn5-IE7	Broadband sending complete	MTn 5 NOT MTn 5	O N/A	3.2.4	[]Yes []No []N/A
MTn5-IE1	Called party number	MTn 5 NOT MTn 5	M N/A	3.2.4	[]Yes []No []N/A
Comments:					

Table A.97: Information elements in NOTIFY transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn6-IE20	Notification indicator		M	3.1.10	[]Yes []No
Comments:					

Table A.98: Information elements in PROGRESS transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn7-IE23	Narrowband bearer capability	MTn 7 NOT MTn 7	O N/A	3.2.5	[]Yes []No []N/A
MTn7-IE6	Narrowband high layer compatibility	MTn 7 NOT MTn 7	O N/A	3.2.5	[]Yes []No []N/A
MTn7-IE20	Notification indicator	MTn 7 NOT MTn 7	O N/A	3.2.5	[]Yes []No []N/A
MTn7-IE23	Progress indicator	MTn 7 NOT MTn 7	M N/A	3.2.5	[]Yes []No []N/A
Comments:					

Table A.99: Information elements in RELEASE transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn8-IE24	Cause		M	3.1.5, 3.2.6	[]Yes []No
MTn8-IE20	Notification indicator		O	3.1.5, 3.2.6	[]Yes []No
MTn8-IE22	Progress indicator		O	3.2.6	[]Yes []No
Comments:					

Table A.100: Information elements in RELEASE COMPLETE transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn9-IE24	Cause		M	3.1.6 note 2	[]Yes []No
Comments:					

Table A.101: Information elements in RESTART transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn10-IE13	Connection identifier		M	3.3.1	[]Yes []No
MTn10-IE4	Restart indicator		M	3.3.1	[]Yes []No
Comments:					

Table A.102: Information elements in RESTART ACKNOWLEDGE transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn11-IE13	Connection identifier		M	3.3.2	[]Yes []No
MTn11-IE4	Restart indicator		M	3.3.2	[]Yes []No
Comments:					

Table A.103: Information elements in SETUP transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn12-IE11	AAL parameters		M	3.1.7 note 1, 3.2.7	[]Yes []No
MTn12-IE12	ATM traffic descriptor		M	3.1.7, 3.2.7	[]Yes []No
MTn12-IE16	Broadband bearer capability		M	3.1.7, 3.2.7	[]Yes []No
MTn12-IE18	Broadband high layer information		M	3.1.7 note 2	[]Yes []No
MTn12-IE8	Broadband repeat indicator		M	3.1.7, annex C	[]Yes []No
MTn12-IE17	Broadband low layer information		M	3.1.7 note 4	[]Yes []No
MTn12-IE1	Called party number	SCn 2 NOT SCn 2	O M	3.1.7, 3.2.7	[]Yes []No
MTn12-IE2	Called party subaddress		M	3.1.7 note 6, 3.2.7	[]Yes []No
MTn12-IE9	Calling party number		I	3.1.7 note 7, 3.2.7 note 4	[]Yes []No
MTn12-IE10	Calling party subaddress		I	3.1.7 note 8, 3.2.7 note 5	[]Yes []No
MTn12-IE13	Connection identifier	MCn 2.1 NOT MCn 2.1	M O	3.1.7 note 9, 3.2.7	[]Yes []No
MTn12-IE19	End-to-end transit delay		M	3.1.7 note 10, 3.2.7	[]Yes []No
MTn12-IE23	Narrowband bearer capability	MCn 9 NOT MCn 9	M N/A	3.2.7	[]Yes []No []N/A
MTn12-IE6	Narrowband high layer compatibility	MCn 9 NOT MCn 9	M N/A	3.2.7 note 10	[]Yes []No []N/A
MTn12-IE5	Narrowband low layer compatibility	MCn 9 NOT MCn 9	M N/A	3.2.7 note 12	[]Yes []No []N/A
MTn12-IE20	Notification indicator		O	3.1.7, 3.2.7	[]Yes []No
MTn12-IE14	OAM traffic descriptor		O	3.1.7, 3.2.7	[]Yes []No
MTn12-IE22	Progress indicator	MCn 9 NOT MCn 9	O N/A	3.2.7	[]Yes []No []N/A
MTn12-IE15	QOS parameter		M	3.1.7, 3.2.7	[]Yes []No
MTn12-IE7	Broadband sending complete		M	3.1.7, 3.2.7	[]Yes []No
MTn12-IE3	Transit network selection		X		[]Yes []No
Comments:					

Table A.104: Information elements in SETUP ACKNOWLEDGE transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn13-IE13	Connection identifier	MTn 13 NOT MTn 13	M N/A	3.2.8	[]Yes []No []N/A
MTn13-IE20	Notification indicator	MTn 13 NOT MTn 13	O N/A	3.2.8	[]Yes []No []N/A
MTn13-IE22	Progress indicator	MTn 13 NOT MTn 13	O N/A	3.2.8	[]Yes []No []N/A
Comments:					

Table A.105: Information elements in STATUS transmitted by the network

Item	Information element	Conditions for status	Status	Reference	Support
MTn14-IE21	Call state		M	3.1.8	[]Yes []No
MTn14-IE24	Cause		M	3.1.8	[]Yes []No
Comments:					

A.8.5 Timers

Indicating support for an item in table A.106 states that the implementation has a timer that operates in accordance with the description in clause 7 and with the relevant behaviour specified in clauses 5 and 6 of ITU-T Recommendation Q.2931 as modified by ETS 300 443-1 [1].

The table indicates the permitted range of values for each timer. The supplier shall state the values supported by their implementation.

Table A.106: Timers in the network role

Item	Timer: Does the implementation support...	Conditions for status	Status	Reference	Support	Values Allowed	Value Supported
TMn 1	T301		M	table 7-1	[]Yes []No	minim. 3 min	
TMn 2	T302	MCn 9 NOT MCn 9	M N/A	table 7-2	[]Yes []No []N/A	10 - 15 s	
TMn 3	T303		M	table 7-1 & 7-2	[]Yes []No	4 s	
TMn 4	T304	MCn 9 NOT MCn 9	M N/A	table 7-2	[]Yes []No []N/A	20 s	
TMn 12	T306	MCn 9 NOT MCn 9	M N/A	table 7-2	[]Yes []No []N/A	30 s	
TMn 5	T308		M	table 7-1	[]Yes []No	30 s	
TMn 6	T309		M	table 7-1	[]Yes []No	10 s	
TMn 7	T310		M	table 7-1	[]Yes []No	30 - 120 s	
TMn 9	T316		M	table 7-1	[]Yes []No	120 s	
TMn 10	T317		M	table 7-1	[]Yes []No	< T316	
TMn 11	T322		M	table 7-1	[]Yes []No	4 s	
Comments:							

A.8.6 Structure of information elements received

These tables are to be completed in order to evaluate the likelihood of successful interoperation of two implementations. The answers supplied are not used for conformance testing.

A.8.6.1 Broadband locking shift

Table A.107: Broadband locking shift information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 25.1	New codeset identification	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Codeset 4	M	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Codeset 5	M	5	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Codeset 6	M	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Codeset 7	M	7	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.6.2 Broadband non-locking shift

Table A.108: Broadband non-locking shift information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 26.1	Temporary codeset identification	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Codeset 0	M	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Codeset 4	M	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Codeset 5	M	5	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Codeset 6	M	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
	5. Codeset 7	M	7	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.6.3 ATM adaptation layer parameters

Table A.109: ATM adaptation layer parameters information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 11.1	AAL type	M		[]Yes []No
	1. AAL for voice	O	0	[]Yes []No
	2. AAL type 1	O	1	[]Yes []No
	3. AAL type 2	O	2	[]Yes []No
	4. AAL type 3/4	O	3	[]Yes []No
	5. AAL type 5	O	5	[]Yes []No
	6. User defined AAL	O	16	[]Yes []No
IERn 11.2	Subtype	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. Voice-band signal transport based on 64 kbit/s	O	1	[]Yes []No
	3. Circuit transport	O	2	[]Yes []No
	4. High-quality audio signal transport	O	4	[]Yes []No
	5. Video signal transport	O	5	[]Yes []No
IERn 11.3	CBR rate	O		[]Yes []No
	1. 64 kbit/s	O	1	[]Yes []No
	2. 1 544 kbit/s	O	4	[]Yes []No
	3. 6 312 kbit/s	O	5	[]Yes []No
	4. 32 064 kbit/s	O	6	[]Yes []No
	5. 44 736 kbit/s	O	7	[]Yes []No
	6. 97 728 kbit/s	O	8	[]Yes []No
	7. 2 048 kbit/s	O	16	[]Yes []No
	8. 8 448 kbit/s	O	17	[]Yes []No
	9. 34 368 kbit/s	O	18	[]Yes []No
	10. 139 264 kbit/s	O	19	[]Yes []No
	11. n x 64 kbit/s	O	64	[]Yes []No
12. n x 8 kbit/s	O	65	[]Yes []No	
IERn 11.4	Source clock frequency recovery method	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. Synchronous residual time stamp method	O	1	[]Yes []No
	3. Adaptive clock method	O	2	[]Yes []No
IERn 11.5	Error correction method	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. FEC for loss sensitive signal transport	O	1	[]Yes []No
	3. FEC for delay sensitive signal transport	O	2	[]Yes []No
IERn 11.6	Structured data transfer block size	O		[]Yes []No
IERn 11.7	Partially filled cells method	O		[]Yes []No
IERn 11.8	Forward maximum CPCS-SDU size	O		[]Yes []No
IERn 11.9	Backward maximum CPCS-SDU size	O		[]Yes []No
IERn 11.10	MID range	O		[]Yes []No
IERn 11.11	SSCS type	O		[]Yes []No
	1. Null	O	0	[]Yes []No
	2. Data SSSC based on SSCOP (assured)	O	1	[]Yes []No
	3. Data SSSC based on SSCOP (non-assured)	O	2	[]Yes []No
	4. Frame relay SSSC	O	4	[]Yes []No
IERn 11.12	User defined AAL information	O		[]Yes []No
Comments:				

A.8.6.4 ATM traffic descriptor

Table A.110: ATM traffic descriptor information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 12.1	Forward peak cell rate (CLP=0)	O	N/A	[]Yes []No
	Backward peak cell rate (CLP=0)	O	N/A	[]Yes []No
	Forward peak cell rate (CLP=0+1)	M	N/A	[]Yes []No
	Backward peak cell rate (CLP=0+1)	M	N/A	[]Yes []No
Comments:				

A.8.6.5 Broadband bearer capability

Table A.111: Broadband bearer capability information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 16.1	Bearer class	M		[]Yes []No
	1. BCOB-A	O	1	[]Yes []No
	2. BCOB-C	O	3	[]Yes []No
	3. BCOB-X	O	16	[]Yes []No
IERn 16.2	Traffic type	O		[]Yes []No
	1. No indication	O	0	[]Yes []No
	2. Constant bit rate	O	1	[]Yes []No
	3. Variable bit rate	O	2	[]Yes []No
IERn 16.3	Timing requirements	O		[]Yes []No
	1. No indication	O	0	[]Yes []No
	2. End-to-end timing required	O	1	[]Yes []No
	3. End-to-end timing not required	O	2	[]Yes []No
IERn 16.4	Susceptibility to clipping	M		[]Yes []No
	1. Not susceptible to clipping	O	0	[]Yes []No
	2. Susceptible to clipping	O	1	[]Yes []No
IERn 16.5	User plane connection configuration	M		[]Yes []No
	1. Point-to-point	O	0	[]Yes []No
	2. Point-to-multipoint	O	1	[]Yes []No
Comments:				

A.8.6.6 Broadband high layer information

Table A.112: Broadband high layer information information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 18.1	High layer information type	M		[]Yes []No
	1. ISO/IEC	O	0	[]Yes []No
	2. User specific	O	1	[]Yes []No
	3. Vendor specific application identifier	O	3	[]Yes []No
	4. Reference to ITU-T SG 1 B-ISDN teleservice recommendation	O	4	[]Yes []No
Comments:				

A.8.6.7 Broadband low layer information

Table A.113: Broadband low layer information information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 17.1	User information layer 2 protocol	<input type="radio"/>		[]Yes []No
	1. Basic mode ISO 1745	<input type="radio"/>	1	[]Yes []No
	2. ITU-T Recommendation Q.921 (I.441)	<input type="radio"/>	2	[]Yes []No
	3. ITU-T Recommendation X.25 link layer	<input type="radio"/>	6	[]Yes []No
	4. ITU-T Recommendation X.25 multilink	<input type="radio"/>	7	[]Yes []No
	5. Extended LAPB; for half duplex operation	<input type="radio"/>	8	[]Yes []No
	6. HDLC ARM	<input type="radio"/>	9	[]Yes []No
	7. HDLC NRM	<input type="radio"/>	10	[]Yes []No
	8. HDLC ABM	<input type="radio"/>	11	[]Yes []No
	9. LAN logical link control (ISO/IEC 8802/2)	<input type="radio"/>	12	[]Yes []No
	10. ITU-T Recommendation X.75 SLP	<input type="radio"/>	13	[]Yes []No
	11. ITU-T Recommendation Q.922	<input type="radio"/>	14	[]Yes []No
	12. User specified	<input type="radio"/>	16	[]Yes []No
13. ISO/IEC 7776 DTE-DTE operation	<input type="radio"/>	17	[]Yes []No	
IERn 17.2	Mode of operation (octet 6a)	<input type="radio"/>		[]Yes []No
	1. Normal mode	<input type="radio"/>	1	[]Yes []No
	2. Extended mode	<input type="radio"/>	2	[]Yes []No
IERn 17.3	Q.33 use	<input type="radio"/>		[]Yes []No
IERn 17.4	User specified layer 2 protocol information	<input type="radio"/>		[]Yes []No
IERn 17.5	Window size	<input type="radio"/>		[]Yes []No
IERn 17.6	User information layer 3 protocol	<input type="radio"/>		[]Yes []No
	1. ITU-T Recommendation X.25, packet layer	<input type="radio"/>	6	[]Yes []No
	2. ISO/IEC 8208	<input type="radio"/>	7	[]Yes []No
	3. X.223 or ISO/IEC 8878	<input type="radio"/>	8	[]Yes []No
	4. X.233 or ISO/IEC 8473	<input type="radio"/>	9	[]Yes []No
	5. ITU-T Recommendation T.70	<input type="radio"/>	10	[]Yes []No
	6. ISO/IEC TR 9577	<input type="radio"/>	11	[]Yes []No
7. User specified	<input type="radio"/>	16	[]Yes []No	
IERn 17.7	Mode of operation (octet 7a)	<input type="radio"/>		[]Yes []No
	1. Normal packet sequence numbering	<input type="radio"/>	1	[]Yes []No
	2. Extended packet sequence numbering	<input type="radio"/>	2	[]Yes []No
IERn 17.8	User specified layer 3 protocol information	<input type="radio"/>		[]Yes []No
IERn 17.9	Default packet size	<input type="radio"/>		[]Yes []No
	1. 16 octets	<input type="radio"/>	4	[]Yes []No
	2. 32 octets	<input type="radio"/>	5	[]Yes []No
	3. 64 octets	<input type="radio"/>	6	[]Yes []No
	4. 128 octets	<input type="radio"/>	7	[]Yes []No
	5. 256 octets	<input type="radio"/>	8	[]Yes []No
	6. 512 octets	<input type="radio"/>	9	[]Yes []No
	7. 1 024 octets	<input type="radio"/>	10	[]Yes []No
	8. 2 048 octets	<input type="radio"/>	11	[]Yes []No
9. 4 096 octets	<input type="radio"/>	12	[]Yes []No	
IERn 17.10	Packet window size	<input type="radio"/>		[]Yes []No
IERn 17.11	Additional layer 3 protocol information for ISO/IEC TR 9577	<input type="radio"/>		[]Yes []No
Comments:				

A.8.6.8 Call state

Table A.114: Call state information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 21.1	Call state value	M		[]Yes []No
	1. Null	M	0	[]Yes []No
	2. Call initiated	M	1	[]Yes []No
	3. Overlap sending	O	2	[]Yes []No
	4. Outgoing call proceeding	M	3	[]Yes []No
	5. Call delivered	M	4	[]Yes []No
	6. Call present	M	6	[]Yes []No
	7. Call received	M	7	[]Yes []No
	8. Connect request	M	8	[]Yes []No
	9. Incoming call proceeding	M	9	[]Yes []No
	10. Active	M	10	[]Yes []No
	11. Release request	M	11	[]Yes []No
	12. Release indication	M	12	[]Yes []No
	13. Overlap receiving	O	25	[]Yes []No
	14. Restart null	M	0	[]Yes []No
	15. Restart request	M	61	[]Yes []No
16. Restart	M	62	[]Yes []No	
Comments:				

A.8.6.9 Called party number

Table A.115: Called party number information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 1.1	Type of number	M		[]Yes []No
	1. Unknown	O	0	[]Yes []No
	2. International	O	1	[]Yes []No
	3. National	O	2	[]Yes []No
	4. Network specific	O	3	[]Yes []No
	5. Subscriber	O	4	[]Yes []No
IERn 1.2	6. Abbreviated	O	6	[]Yes []No
	Addressing/numbering plan identification	M		[]Yes []No
	1. Unknown	O	0	[]Yes []No
	2. ISDN numbering plan	O	1	[]Yes []No
	3. NSAP addressing	O	2	[]Yes []No
4. Private numbering plan	O	9	[]Yes []No	
Comments:				

A.8.6.10 Called party subaddress

Table A.116: Called party subaddress information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 2.1	Type of subaddress	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. NSAP	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. User specified ATM endsystem address	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. User specified	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 2.2	Odd/even indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Even number of address signals	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Odd number of address signals	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.6.11 Calling party number

Table A.117: Calling party number information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 9.1	Type of number	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unknown	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. International	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. National	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Network specific	O	3	<input type="checkbox"/> Yes <input type="checkbox"/> No
	5. Subscriber	O	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	6. Abbreviated	O	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 9.2	Addressing/numbering plan identification	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unknown	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. ISDN numbering plan	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. NSAP addressing	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Private numbering plan	O	9	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 9.3	Presentation indicator	O		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Presentation allowed	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Presentation restricted	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Number not available	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 9.4	Screening indicator	O		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. User provided, not screened	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. User provided, verified and passed	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. User provided, verified and failed	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Network provided	O	3	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.6.12 Calling party subaddress

Table A.118: Calling party subaddress information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 10.1	Type of subaddress	M		[]Yes []No
	1. NSAP	O	0	[]Yes []No
	2. User specified ATM endsystem address	O	1	[]Yes []No
	3. User specified	O	2	[]Yes []No
IERn 10.2	Odd/even indicator	M		[]Yes []No
	1. Even number of address signals	O	0	[]Yes []No
	2. Odd number of address signals	O	1	[]Yes []No
Comments:				

A.8.6.13 Connection identifier

Table A.119: Connection identifier information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 13.1	VP-associated signalling	M		[]Yes []No
	1. VP-associated signalling	O	0	[]Yes []No
	2. Explicit indication of VPCI	M	1	[]Yes []No
IERn 13.2	Preferred/exclusive	M		[]Yes []No
	1. Exclusive VPCI, exclusive VCI	O	0	[]Yes []No
	2. Exclusive VPCI, any VCI	O	1	[]Yes []No
Comments:				

A.8.6.14 End-to-end transit delay

Table A.120: End-to-end transit delay information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 19.1	Maximum end-to-end transit delay	O		[]Yes []No
Comments:				

A.8.6.15 Quality of service parameter

Table A.121: Quality of service parameter information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 15.1	QOS class forward	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unspecified QOS class	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Parameterized QOS	O	255	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 15.2	QOS class backward	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unspecified QOS class	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Parameterized QOS	O	255	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.6.16 Restart indicator

Table A.122: Restart indicator information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 4.1	Class	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Indicated virtual channel	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. All VCs in indicated VPC controlled by the signalling VC	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. All VCs controlled by the layer 3 entity	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.6.17 Transit network selection

Table A.123: Transit network selection information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 3.1	Type of network identification	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. User specified	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. National network identification	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. International network identification	O	3	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 3.2	Network identification plan	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unknown	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Carrier identification code	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Data network identification code	O	3	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.6.18 OAM traffic descriptor

Table A.124: OAM traffic descriptor information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IERn 14.1	Shaping indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. No user requirement	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 14.2	Aggregate shaping not allowed	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	Compliance indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 14.3	1. Optional end-to-end OAM F5 flow	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Mandatory end-to-end OAM F5 flow	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 14.3	User-network fault management indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. No user-originated indications	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 14.4	2. Use of user-originated indications	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	Forward end-to-end OAM F5 flow indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 14.4	1. 0 %	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. 0,1 %	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. 1 %	O	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
IERn 14.5	Backward end-to-end OAM F5 flow indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. 0 %	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. 0,1 %	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. 1 %	O	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.7 Structure of information elements transmitted

These tables are to be completed in order to evaluate the likelihood of successful interoperation of two implementations. The answers supplied are not used for conformance testing.

A.8.7.1 Broadband locking shift

Table A.125: Broadband locking shift information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 25.1	New codeset identification			<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Codeset 4	M	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Codeset 5	M	5	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Codeset 6	M	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 25.1	4. Codeset 7	M	7	<input type="checkbox"/> Yes <input type="checkbox"/> No
	Comments:			

A.8.7.2 Broadband non-locking shift

Table A.126: Broadband non-locking shift information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 26.1	Temporary codeset identification			<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Codeset 0	M	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Codeset 4	M	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Codeset 5	M	5	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Codeset 6	M	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 26.1	5. Codeset 7	M	7	<input type="checkbox"/> Yes <input type="checkbox"/> No
	Comments:			

A.8.7.3 ATM adaptation layer parameters

Table A.127: ATM adaptation layer parameters information element contents

Item	Does the implementation support the information element field:	Status	Value	Support	
IETn 11.1	AAL type	M		[]Yes []No	
	1. AAL for voice	O	0	[]Yes []No	
	2. AAL type 1	O	1	[]Yes []No	
	3. AAL type 2	O	2	[]Yes []No	
	4. AAL type 3/4	O	3	[]Yes []No	
	5. AAL type 5	O	5	[]Yes []No	
IETn 11.2	6. User defined AAL	O	16	[]Yes []No	
	Subtype	O		[]Yes []No	
	1. Null	O	0	[]Yes []No	
	2. Voice-band signal transport based on 64 kbit/s	O	1	[]Yes []No	
	3. Circuit transport	O	2	[]Yes []No	
IETn 11.3	4. High-quality audio signal transport	O	4	[]Yes []No	
	5. Video signal transport	O	5	[]Yes []No	
	CBR rate	O		[]Yes []No	
	1. 64 kbit/s	O	1	[]Yes []No	
	2. 1 544 kbit/s	O	4	[]Yes []No	
IETn 11.4	3. 6 312 kbit/s	O	5	[]Yes []No	
	4. 32 064 kbit/s	O	6	[]Yes []No	
	5. 44 736 kbit/s	O	7	[]Yes []No	
	6. 97 728 kbit/s	O	8	[]Yes []No	
	7. 2 048 kbit/s	O	16	[]Yes []No	
	8. 8 448 kbit/s	O	17	[]Yes []No	
	9. 34 368 kbit/s	O	18	[]Yes []No	
	10. 139 264 kbit/s	O	19	[]Yes []No	
	11. n x 64 kbit/s	O	64	[]Yes []No	
	12. n x 8 kbit/s	O	65	[]Yes []No	
	IETn 11.5	Source clock frequency recovery method	O		[]Yes []No
		1. Null	O	0	[]Yes []No
2. Synchronous residual time stamp method		O	1	[]Yes []No	
IETn 11.6	3. Adaptive clock method	O	2	[]Yes []No	
	Error correction method	O		[]Yes []No	
	1. Null	O	0	[]Yes []No	
IETn 11.7	2. FEC for loss sensitive signal transport	O	1	[]Yes []No	
	3. FEC for delay sensitive signal transport	O	2	[]Yes []No	
IETn 11.8	Structured data transfer block size	O		[]Yes []No	
IETn 11.9	Partially filled cells method	O		[]Yes []No	
IETn 11.10	Forward maximum CPCS-SDU size	O		[]Yes []No	
IETn 11.11	Backward maximum CPCS-SDU size	O		[]Yes []No	
IETn 11.12	MID range	O		[]Yes []No	
	SSCS type	O		[]Yes []No	
	1. Null	O	0	[]Yes []No	
	2. Data SSSC based on SSCOP (assured)	O	1	[]Yes []No	
IETn 11.13	3. Data SSSC based on SSCOP (non-assured)	O	2	[]Yes []No	
	4. Frame relay SSSC	O	4	[]Yes []No	
IETn 11.14	User defined AAL information	O		[]Yes []No	
Comments:					

A.8.7.4 ATM traffic descriptor

Table A.128: ATM traffic descriptor information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 12.1	Forward peak cell rate (CLP=0)	O	N/A	[]Yes []No
	Backward peak cell rate (CLP=0)	O	N/A	[]Yes []No
	Forward peak cell rate (CLP=0+1)	M	N/A	[]Yes []No
	Backward peak cell rate (CLP=0+1)	M	N/A	[]Yes []No
Comments:				

A.8.7.5 Broadband bearer capability

Table A.129: Broadband bearer capability information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 16.1	Bearer class	M		[]Yes []No
	1. BCOB-A	O	1	[]Yes []No
	2. BCOB-C	O	3	[]Yes []No
	3. BCOB-X	O	16	[]Yes []No
IETn 16.2	Traffic type	O		[]Yes []No
	1. No indication	O	0	[]Yes []No
	2. Constant bit rate	O	1	[]Yes []No
	3. Variable bit rate	O	2	[]Yes []No
IETn 16.3	Timing requirements	O		[]Yes []No
	1. No indication	O	0	[]Yes []No
	2. End-to-end timing required	O	1	[]Yes []No
	3. End-to-end timing not required	O	2	[]Yes []No
IETn 16.4	Susceptibility to clipping	M		[]Yes []No
	1. Not susceptible to clipping	O	0	[]Yes []No
	2. Susceptible to clipping	O	1	[]Yes []No
IETn 16.5	User plane connection configuration	M		[]Yes []No
	1. Point-to-point	O	0	[]Yes []No
	2. Point-to-multipoint	O	1	[]Yes []No
Comments:				

A.8.7.6 Broadband high layer information

Table A.130: Broadband high layer information information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 18.1	High layer information type	M		[]Yes []No
	1. ISO/IEC	O	0	[]Yes []No
	2. User specific	O	1	[]Yes []No
	3. Vendor specific application identifier	O	3	[]Yes []No
	4. Reference to ITU-T SG 1 B-ISDN teleservice recommendation	O	4	[]Yes []No
Comments:				

A.8.7.7 Broadband low layer information

Table A.131: Broadband low layer information information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 17.1	User information layer 2 protocol	<input type="radio"/>		[]Yes []No
	1. Basic mode ISO 1745	<input type="radio"/>	1	[]Yes []No
	2. ITU-T Recommendation Q.921 (I.441)	<input type="radio"/>	2	[]Yes []No
	3. ITU-T Recommendation X.25 link layer	<input type="radio"/>	6	[]Yes []No
	4. ITU-T Recommendation X.25 multilink	<input type="radio"/>	7	[]Yes []No
	5. Extended LAPB; for half duplex operation	<input type="radio"/>	8	[]Yes []No
	6. HDLC ARM	<input type="radio"/>	9	[]Yes []No
	7. HDLC NRM	<input type="radio"/>	10	[]Yes []No
	8. HDLC ABM	<input type="radio"/>	11	[]Yes []No
	9. LAN logical link control (ISO/IEC 8802/2)	<input type="radio"/>	12	[]Yes []No
	10. ITU-T Recommendation X.75 SLP	<input type="radio"/>	13	[]Yes []No
	11. ITU-T Recommendation Q.922	<input type="radio"/>	14	[]Yes []No
	12. User specified	<input type="radio"/>	16	[]Yes []No
13. ISO/IEC 7776 DTE-DTE operation	<input type="radio"/>	17	[]Yes []No	
IETn 17.2	Mode of operation (octet 6a)	<input type="radio"/>		[]Yes []No
	1. Normal mode	<input type="radio"/>	1	[]Yes []No
	2. Extended mode	<input type="radio"/>	2	[]Yes []No
IETn 17.3	Q.33 use	<input type="radio"/>		[]Yes []No
IETn 17.4	User specified layer 2 protocol information	<input type="radio"/>		[]Yes []No
IETn 17.5	Window size	<input type="radio"/>		[]Yes []No
IETn 17.6	User information layer 3 protocol	<input type="radio"/>		[]Yes []No
	1. ITU-T Recommendation X.25, packet layer	<input type="radio"/>	6	[]Yes []No
	2. ISO/IEC 8208	<input type="radio"/>	7	[]Yes []No
	3. X.223 or ISO/IEC 8878	<input type="radio"/>	8	[]Yes []No
	4. X.233 or ISO/IEC 8473	<input type="radio"/>	9	[]Yes []No
	5. ITU-T Recommendation T.70	<input type="radio"/>	10	[]Yes []No
	6. ISO/IEC TR 9577	<input type="radio"/>	11	[]Yes []No
7. User specified	<input type="radio"/>	16	[]Yes []No	
IETn 17.7	Mode of operation (octet 7a)	<input type="radio"/>		[]Yes []No
	1. Normal packet sequence numbering	<input type="radio"/>	1	[]Yes []No
	2. Extended packet sequence numbering	<input type="radio"/>	2	[]Yes []No
IETn 17.8	User specified layer 3 protocol information	<input type="radio"/>		[]Yes []No
IETn 17.9	Default packet size	<input type="radio"/>		[]Yes []No
	1. 16 octets	<input type="radio"/>	4	[]Yes []No
	2. 32 octets	<input type="radio"/>	5	[]Yes []No
	3. 64 octets	<input type="radio"/>	6	[]Yes []No
	4. 128 octets	<input type="radio"/>	7	[]Yes []No
	5. 256 octets	<input type="radio"/>	8	[]Yes []No
	6. 512 octets	<input type="radio"/>	9	[]Yes []No
	7. 1 024 octets	<input type="radio"/>	10	[]Yes []No
	8. 2 048 octets	<input type="radio"/>	11	[]Yes []No
9. 4 096 octets	<input type="radio"/>	12	[]Yes []No	
IETn 17.10	Packet window size	<input type="radio"/>		[]Yes []No
IETn 17.11	Additional layer 3 protocol information for ISO/IEC TR 9577	<input type="radio"/>		[]Yes []No
Comments:				

A.8.7.8 Call state

Table A.132: Call state information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 21.1	Call state value	M		[]Yes []No
	1. Null	M	0	[]Yes []No
	2. Call initiated	M	1	[]Yes []No
	3. Overlap sending	O	2	[]Yes []No
	4. Outgoing call proceeding	M	3	[]Yes []No
	5. Call delivered	M	4	[]Yes []No
	6. Call present	M	6	[]Yes []No
	7. Call received	M	7	[]Yes []No
	8. Connect request	M	8	[]Yes []No
	9. Incoming call proceeding	M	9	[]Yes []No
	10. Active	M	10	[]Yes []No
	11. Release request	M	11	[]Yes []No
	12. Release indication	M	12	[]Yes []No
	13. Overlap receiving	O	25	[]Yes []No
	14. Restart null	M	0	[]Yes []No
	15. Restart request	M	61	[]Yes []No
16. Restart	M	62	[]Yes []No	
Comments:				

A.8.7.9 Called party number

Table A.133: Called party number information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 1.1	Type of number	M		[]Yes []No
	1. Unknown	O	0	[]Yes []No
	2. International	O	1	[]Yes []No
	3. National	O	2	[]Yes []No
	4. Network specific	O	3	[]Yes []No
	5. Subscriber	O	4	[]Yes []No
IETn 1.2	6. Abbreviated	O	6	[]Yes []No
	Addressing/numbering plan identification	M		[]Yes []No
	1. Unknown	O	0	[]Yes []No
	2. ISDN numbering plan	O	1	[]Yes []No
	3. NSAP addressing	O	2	[]Yes []No
4. Private numbering plan	O	9	[]Yes []No	
Comments:				

A.8.7.10 Called party subaddress

Table A.134: Called party subaddress information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 2.1	Type of subaddress	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. NSAP	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. User specified ATM endsystem address	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. User specified	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 2.2	Odd/even indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Even number of address signals	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Odd number of address signals	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.7.11 Calling party number

Table A.135: Calling party number information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 9.1	Type of number	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unknown	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. International	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. National	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Network specific	O	3	<input type="checkbox"/> Yes <input type="checkbox"/> No
	5. Subscriber	O	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
	6. Abbreviated	O	6	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 9.2	Addressing/numbering plan identification	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unknown	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. ISDN numbering plan	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. NSAP addressing	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Private numbering plan	O	9	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 9.3	Presentation indicator	O		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Presentation allowed	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Presentation restricted	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. Number not available	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 9.4	Screening indicator	O		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. User provided, not screened	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. User provided, verified and passed	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. User provided, verified and failed	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
	4. Network provided	O	3	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.7.12 Calling party subaddress

Table A.136: Calling party subaddress information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 10.1	Type of subaddress	M		[]Yes []No
	1. NSAP	O	0	[]Yes []No
	2. User specified ATM endsystem address	O	1	[]Yes []No
	3. User specified	O	2	[]Yes []No
IETn 10.2	Odd/even indicator	M		[]Yes []No
	1. Even number of address signals	O	0	[]Yes []No
	2. Odd number of address signals	O	1	[]Yes []No
Comments:				

A.8.7.13 Connection identifier

Table A.137: Connection identifier information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 13.1	VP-associated signalling	M		[]Yes []No
	1. VP-associated signalling	O	0	[]Yes []No
	2. Explicit indication of VPCI	M	1	[]Yes []No
IETn 13.2	Preferred/exclusive	M		[]Yes []No
	1. Exclusive VPCI, exclusive VCI	O	0	[]Yes []No
	2. Exclusive VPCI, any VCI	O	1	[]Yes []No
Comments:				

A.8.7.14 End-to-end transit delay

Table A.138: End-to-end transit delay information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 19.1	Maximum end-to-end transit delay	O		[]Yes []No
Comments:				

A.8.7.15 Quality of service parameter

Table A.139: Quality of service parameter information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 15.1	QOS class forward	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unspecified QOS class	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Parameterized QOS	O	255	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 15.2	QOS class backward	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Unspecified QOS class	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Parameterized QOS	O	255	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.7.16 Restart indicator

Table A.140: Restart indicator information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 4.1	Class	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Indicated virtual channel	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. All VCs in indicated VPC controlled by the signalling VC	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. All VCs controlled by the layer 3 entity	O	2	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

A.8.7.17 OAM traffic descriptor

Table A.141: OAM traffic descriptor information element contents

Item	Does the implementation support the information element field:	Status	Value	Support
IETn 14.1	Shaping indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. No user requirement	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Aggregate shaping not allowed	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 14.2	Compliance indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. Optional end-to-end OAM F5 flow	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Mandatory end-to-end OAM F5 flow	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 14.3	User-network fault management indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. No user-originated indications	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. Use of user-originated indications	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 14.4	Forward end-to-end OAM F5 flow indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. 0 %	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. 0,1 %	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. 1 %	O	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
IETn 14.5	Backward end-to-end OAM F5 flow indicator	M		<input type="checkbox"/> Yes <input type="checkbox"/> No
	1. 0 %	O	0	<input type="checkbox"/> Yes <input type="checkbox"/> No
	2. 0,1 %	O	1	<input type="checkbox"/> Yes <input type="checkbox"/> No
	3. 1 %	O	4	<input type="checkbox"/> Yes <input type="checkbox"/> No
Comments:				

History

Document history			
October 1995	Public Enquiry	PE 93:	1995-10-09 to 1996-02-02
February 1997	Vote	V 9717:	1997-02-25 to 1997-04-25
May 1997	First Edition		