



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 449

February 1996

Source: ETSI TC-BTC

Reference: DE/BTC-02029

ICS: 33.020

Key words: ONP, leased line, A2S

**Business TeleCommunications (BTC);
Special quality voice bandwidth
2-wire analogue leased line (A2S);
Connection characteristics and network interface presentation**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

*

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.

Contents

Foreword	5
Introduction	5
1 Scope	7
2 Normative references	7
3 Definitions and abbreviations	8
3.1 Definitions	8
3.2 Abbreviations	8
4 Requirements	9
4.1 Connection characteristics	9
4.1.1 Tabulation of connection characteristics	9
4.1.2 Overall loss	10
4.1.3 Loss/frequency distortion	10
4.1.4 Transmission signals	11
4.1.4.1 Maximum mean input power	11
4.1.4.2 Maximum instantaneous power	11
4.1.4.3 Maximum power in a 10 Hz bandwidth	11
4.1.4.4 Maximum input power outside the voice band	11
4.1.5 Transmission delay	11
4.1.6 Group delay distortion	12
4.1.7 Variation of overall loss with time	13
4.1.7.1 Amplitude hits	13
4.1.7.2 Other variations	13
4.1.8 Random circuit noise	13
4.1.9 Impulsive noise	14
4.1.10 Phase jitter	14
4.1.11 Distortion	14
4.1.11.1 Quantizing distortion	14
4.1.11.2 Total distortion	14
4.1.12 Single tone interference	14
4.1.13 Frequency error	15
4.1.14 Harmonic distortion	15
4.1.15 Echo and stability	15
4.1.15.1 Echo	15
4.1.15.1.1 Echo control devices	15
4.1.15.1.2 Talker echo	15
4.1.15.1.3 Listener echo	15
4.1.15.2 Stability	15
4.2 Interface presentation	15
4.2.1 Connector specification	16
4.2.2 Hardwired presentation	16
4.2.3 Return loss	16
4.2.4 Power feeding	17
4.3 Safety	17
4.4 Overvoltage protection	17
4.5 ElectroMagnetic Compatibility (EMC)	17
4.6 Availability	17

Annex A (normative):	Test methods	18
A.1	General	18
A.1.1	Equipment connection	18
A.1.2	Reference impedance	18
A.1.3	Non-reactive line termination	18
A.1.4	Measurement frequency	19
A.2	Test methods	19
A.2.1	Overall loss	19
A.2.2	Loss/frequency distortion and maximum mean input power	19
A.2.3	Maximum instantaneous power	20
A.2.4	Group delay distortion	21
A.2.5	Amplitude hits	21
A.2.6	Random circuit noise	22
A.2.7	Impulsive noise	22
A.2.8	Phase jitter	23
A.2.9	Total distortion	23
A.2.10	Single tone interference	24
A.2.11	Frequency error	25
A.2.12	Harmonic distortion	25
A.2.13	Stability	26
A.2.14	Return loss	26
A.2.15	Power feeding	28
Annex B (informative):	Weighted return loss measurements	29
B.1	Introduction	29
B.2	Weighting function	29
B.2.1	Calculation (trapezoidal rule)	29
B.2.2	Calculation (tabulated data)	30
Annex C (informative):	Overall loss and quantizing distortion	31
C.1	Introduction	31
C.2	Overall loss	32
C.3	Quantizing distortion	32
Annex D (informative):	Availability	34
D.1	General	34
D.1.1	Unavailability	34
D.1.2	Availability	34
D.2	Definition of unavailability periods	34
D.3	Availability figures	36
Annex E (informative):	Bibliography	37
History	38

Foreword

This European Telecommunication Standard (ETS) has been produced by the Business Telecommunications (BTC) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This ETS resulted from a mandate from the Commission of the European Community (CEC) to provide harmonized standards for support of the Directive on Open Network Provision (ONP) of leased lines (92/44/EEC).

There is another standard directly related to this ETS:

ETS 300 450: "Business Telecommunications (BTC); Ordinary and Special quality voice bandwidth 2-wire analogue leased lines (A2O and A2S); Terminal equipment interface".

This ETS is based on information from ITU-T Recommendations and ETSI publications and the relevant documents are quoted where appropriate.

Transposition dates	
Date of adoption of this ETS:	2 February 1996
Date of latest announcement of this ETS (doa):	31 May 1996
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	30 November 1996
Date of withdrawal of any conflicting National Standard (dow):	30 November 1996

Introduction

The Council Directive on the application of ONP to leased lines (92/44/EEC) concerns the harmonization of conditions for open and efficient access to, and use of, the leased lines provided over public telecommunications networks, and the availability throughout the European Union (EU) of a minimum set of leased lines with harmonized technical characteristics.

The consequence of the Directive is that telecommunications organizations within the EU shall make available a set of leased lines within and between points in these countries with specified connection characteristics and specified interfaces. Under the Second Phase Directive (91/263/EEC) terminal equipment for connection to these leased lines will be required to fulfil certain essential requirements.

CCITT Recommendation M.1020 (1988) is used as the basis for the connection characteristics.

Blank page

1 Scope

This European Telecommunication Standard (ETS) specifies the technical requirements and test principles for the connection characteristics and the physical and electrical characteristics of the network interface presentation of special quality, voice bandwidth, 2-wire, analogue leased lines, provided as part of the minimum set under the Council Directive on the application of Open Network Provision (ONP) to leased lines (92/44/EEC).

A connection is presented via interfaces at Network Termination Points (NTPs) and includes any equipment that may provide the NTP. Signals between terminal equipments are subject to impairments during their transfer over the connection. The limits to these impairments are stated in this ETS although in practice the overall performance may be considerably better.

The leased line provides access to the voice bandwidth (300 Hz to 3 400 Hz) with no restrictions on the use of the frequencies. The requirements of this standard have been chosen primarily for the transmission of data between terminal equipments without equalizers although there is no restriction on the use of the leased line for other types of traffic.

This ETS is applicable to leased lines, including part time leased lines, for which the establishment or release does not require any protocol exchange or other intervention at the NTP.

The tests specified in this ETS cannot be carried out, nor can performance be monitored by the leased line provider, while the leased line is in service, i.e. carrying user's traffic. Thus the tests are designed for bringing into and returning into service although there is no obligation to perform these tests each time the leased line is brought into or returned into service.

This ETS covers the physical, mechanical and electrical characteristics of the network interface and specifies the conformance tests for the connection characteristics and network interface. Some of the tests described in this ETS are not designed to be applied to the interface of an installed leased line; such tests may be applied to equipment of the kind used to provide the interface.

This ETS does not include details concerning the implementation of the tests nor does it include information on any regulations concerning testing.

2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] CCITT Recommendation O.71 (1988): "Impulsive noise measuring equipment for telephone-type circuits".
- [2] CCITT Recommendation O.81 (1988): "Group-delay measuring equipment for telephone-type circuits".
- [3] CCITT Recommendation O.91 (1988): "Phase jitter measuring equipment for telephone-type circuits".
- [4] CCITT Recommendation O.95 (1988): "Phase and amplitude hit counters for telephone-type circuits".
- [5] CCITT Recommendation O.132 (1988): "Quantizing distortion measuring equipment using a sinusoidal test signal".
- [6] EN 28877 (1989): "Information processing systems - Interface connector and contact assignments for ISDN basic access interface located at reference points S and T".

- [7] EN 60950 (1992): "Safety of information technology equipment including electrical business equipment".
- [8] ITU-T Recommendation O.41 (1993): "Psophometer for use on telephone-type circuits".

NOTE: This ETS also contains a number of informative references which have been included to indicate the sources from which material has been derived, hence they do not have an associated normative reference number. Details of these publications are given in Annex E. In some cases the same publication may have been referenced in both a normative and an informative manner.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of this ETS, the following definitions apply:

group delay: A measure of the propagation time through the leased line. For a given frequency it is equal to the first derivative of the phase shift through the leased line, measured in radians, with respect to the angular frequency measured in radians per second.

group delay distortion: The difference between group delay at a given frequency and minimum group delay, in the frequency band of interest.

leased lines: The telecommunications facilities provided by a public telecommunication network that provide defined transmission characteristics between network termination points and that do not include switching functions that the user can control, (e.g. on-demand switching).

Network Termination Point (NTP): All physical connections and their technical access specifications which form part of the public telecommunications network and are necessary for access to and efficient communication through that public network.

reference impedance Z_R : This is a complex impedance made up of a resistance of 270 Ω in series with a parallel combination of 750 Ω and 150 nF. See also subclause A.1.2.

terminal equipment: Equipment intended to be connected to the public telecommunication network; i.e.:

- to be connected directly to the termination of a public telecommunication network; or
- to interwork with a public telecommunication network being connected directly or indirectly to the termination of a public telecommunication network,

in order to send, process, or receive information.

voice bandwidth: The band of frequencies over the range 300 Hz to 3 400 Hz.

3.2 Abbreviations

For the purposes of this ETS, the following abbreviations apply:

a	Return loss in dB
$a(f)$	Return loss at frequency f in dB
a_w	Weighted return loss in dB
$A(f)$	Return loss at frequency f expressed as a ratio
A2S	Special quality voice bandwidth 2-wire analogue leased line
ADPCM	Adaptive Differential Pulse Coded Modulation
EMC	ElectroMagnetic Compatibility
f	frequency
NTP	Network Termination Point
ONP	Open Network Provision

qdu	quantizing distortion unit
rms	root mean square
TNV	Telecommunication Network Voltage (see subclause 3.4 of EN 60950 [7])
Z _R	Reference impedance

4 Requirements

4.1 Connection characteristics

The special quality voice bandwidth 2-wire analogue leased line is a bidirectional line, configured point-to-point, nominally covering the voice bandwidth. The connection is, in general, symmetrical, i.e. each direction of transmission has the same nominal characteristics, although the actual values are independent.

4.1.1 Tabulation of connection characteristics

The parameters defining the characteristics of the connection are given in table 1. These characteristics define the service offered.

Table 1: Network performance characteristics

Description	Nature	Reference subclause
Overall loss	$0 \leq \text{overall loss} \leq 17 \text{ dB}$	4.1.2
Loss/frequency distortion	Table 2, figure 1	4.1.3
Transmission signals		4.1.4
- maximum mean input power	-9 dBm	4.1.4.1
- maximum instantaneous power	+4 dBm	4.1.4.2
- maximum power in a 10 Hz bandwidth	no requirement	4.1.4.3
- maximum input power outside voice band	no requirement	4.1.4.4
Transmission delay		4.1.5
- terrestrial (for distance G in kilometres)	$< (15 + 0,01 G) \text{ ms}$	
- via satellite	$< 350 \text{ ms}$	
Group delay distortion	Table 3, figure 3	4.1.6
Variation of overall loss with time		4.1.7
- amplitude hits	≤ 10 in a 15 minute period	4.1.7.1
- other variations	$\pm 4 \text{ dB}$ of that at 1 020 Hz	4.1.7.2
Random circuit noise	$< -41 \text{ dBm0p}$ (see note)	4.1.8
Impulsive noise	≤ 18 peaks $\geq -21 \text{ dBm0}$ in a 15 minute period (see note)	4.1.9
Phase jitter	$\leq 10^\circ$ peak to peak	4.1.10
Total distortion		4.1.11
- quantizing distortion	$\leq 3 \text{ qdu}$; no ADPCM	4.1.11.1
- total distortion	$> 28 \text{ dB}$ signal to distortion ratio	4.1.11.2
Single tone interference	$\leq -44 \text{ dBm0}$ (see note)	4.1.12
Frequency error	$\leq \pm 5 \text{ Hz}$	4.1.13
Harmonic distortion	$\geq 25 \text{ dB}$ below fundamental	4.1.14
Echo and stability		4.1.15
- Echo control devices	no echo control	4.1.15.1.1
- Talker echo	$> 10 \text{ dB}$	4.1.15.1.2
- Listener echo	$> 20 \text{ dB}$	4.1.15.1.3
- Stability	0 to 4 kHz	4.1.15.2
NOTE:	Where the output relative level is not defined, an alternative value is specified in the reference subclause.	

4.1.2 Overall loss

Requirement: The overall loss, including long term variations, presented to a signal frequency of 1 020 Hz sent at a power level of -9 dBm in each direction of transmission with the line terminated in 600 Ω at each end shall be in the range:

$$0 \leq \text{overall loss} \leq 17 \text{ dB.}$$

NOTE: The overall loss in each direction can be different.

Test: The test shall be conducted according to subclause A.2.1.

4.1.3 Loss/frequency distortion

Requirement: The overall loss relative to that defined in subclause 4.1.2 above for the connection, presented to a signal sent at a power level of -9 dBm with the line terminated in 600 Ω at each end shall lie between the limits given in table 2 and figure 1.

Below 300 Hz and above 3 600 Hz the relative loss shall not be less than -2 dB and 0 dB respectively, but is otherwise unspecified.

Table 2: Limits for loss of the circuit relative to that at 1 020 Hz

Upper limit			Lower limit		
Point (see fig. 1)	Frequency Hz	Relative loss dB	Point (see fig. 1)	Frequency Hz	Relative loss dB
A	300	6	G	500	-2
B	500	6	H	500	-1
C	500	3	I	2 800	-1
D	2 800	3	J	2 800	-2
E	2 800	6	K	3 600	-2
F	3 000	6	L	3 600	0




Figure 1: Limits for loss of the circuit relative to that at 1 020 Hz

Test: The test shall be conducted according to subclause A.2.2.

4.1.4 Transmission signals

4.1.4.1 Maximum mean input power

Requirement: The leased line shall be capable of carrying any signal presented at the input at a one minute mean power level of -9 dBm within a voice bandwidth of 300 Hz to 3 400 Hz with the line terminated in 600 Ω at each end.

Test: The test shall be conducted according to subclause A.2.2.

4.1.4.2 Maximum instantaneous power

Requirement: The leased line shall be capable of carrying a signal at the input having a maximum value equal to an instantaneous power which is 13 dB above the mean value of -9 dBm (i.e. +4 dBm).

NOTE: This value is based upon a provisional ITU-T value. See CCITT Recommendation V.2.

Test: The test shall be conducted according to subclause A.2.3.

4.1.4.3 Maximum power in a 10 Hz bandwidth

There is no requirement for maximum power in a 10 Hz bandwidth.

NOTE: However, there is a corresponding requirement on the terminal equipment specified in ETS 300 450.

4.1.4.4 Maximum input power outside the voice band

NOTE: The leased line interface is not suitable for the handling of signals below 300 Hz and above 3 400 Hz. Out of band signals from the terminal equipment are limited to avoid trouble in the network (see terminal equipment interface requirement in ETS 300 450).

4.1.5 Transmission delay

Requirement: The requirement depends upon whether satellite transmission is involved in the connection or not:

- a) for connections where satellite transmission is not involved the one way end-to-end delay shall be less than $(15 + 0,01 G)$ ms, where G is the geographical distance in kilometres, as shown in figure 2; or
- b) for connections where satellite transmission is involved the one way end-to-end delay shall be less than 350 ms.

NOTE: Requirements a) and b) are based on subclauses 2.2 and 2.3 of ITU-T Recommendation G.114 with suitable adjustment to requirement a) to allow for the possible use of loaded cable.




Figure 2: Upper limit of delay

Test: There is no test. This requirement shall be checked by calculation using information from the network plans.

4.1.6 Group delay distortion

Requirement: The connection shall conform to the limits for group delay distortion given in table 3 and figure 3 in which the limiting values over the frequency band are expressed as values relative to the minimum measured group delay in the 500 Hz to 2 800 Hz frequency band.

NOTE: Figure 3 is based on figure 2 of CCITT Recommendation M.1020.

Table 3: Limits for group delay relative to the minimum measured group delay in the 500 Hz to 2 800 Hz band

Upper limit		
Point (see fig. 3)	Frequency Hz	Group delay distortion ms
A	500	3,0
B	600	3,0
C	600	1,5
D	1 000	1,5
E	1 000	0,5
F	2 600	0,5
G	2 600	3,0
H	2 800	3,0




Figure 3: Limits for group delay relative to the minimum measured group delay in the 500 Hz to 2 800 Hz band

Test: The test shall be conducted according to subclause A.2.4.

4.1.7 Variation of overall loss with time

4.1.7.1 Amplitude hits

Requirement: When measurements are made using an instrument complying with CCITT Recommendation O.95 [4] with the send level set at -9 dBm at a frequency of 1 020 Hz, the number of amplitude hits greater than ± 2 dB shall not exceed 10 in any 15 minute measuring period.

NOTE: Phase or amplitude hits are defined as sudden positive or negative changes in phase or amplitude of an observed test signal which exceed a specified threshold and persist for a period of time greater than a specified duration.

Test: The test shall be conducted according to subclause A.2.5.

4.1.7.2 Other variations

Requirement: For a particular implementation variations with time of the overall loss at 1 020 Hz (including daily and seasonal variations but excluding amplitude hits) shall not exceed ± 4 dB variation from the value established by the test for overall loss, see subclause 4.1.2. Any such variation shall not result in an overall loss greater than the maximum specified in subclause 4.1.2.

Test: There is no test for this but the record of the results of successive tests of overall loss may be used to check compliance. The test shall be conducted according to subclause A.2.1.

4.1.8 Random circuit noise

Requirement: The level of the psophometric noise power at the output of the leased line shall be less than -41 dBm_{0p}. In order that this parameter can be tested, the leased line provider should declare the planned value of the output relative level of the leased line.

Where the output relative level either is not, or cannot be, declared by the leased line provider, the psophometrically weighted random circuit noise level shall be 28 dB below a received test signal which is sent at a level of -9 dBm at a frequency of 1 020 Hz into the far end of the leased line.

Test: The test shall be conducted according to subclause A.2.6.

4.1.9 Impulsive noise

Requirement: With an input signal level of -9 dBm applied at a frequency of 1 020 Hz to the input of the leased line, there shall not be more than 18 impulsive noise peaks exceeding a threshold level of -21 dBm₀ within a period of 15 minutes. In order that this parameter can be tested, the leased line provider should declare the planned value of the output relative level of the leased line.

Where the output relative level either is not, or cannot be, declared by the leased line provider, the threshold level shall be 8 dB below the received signal level. Thus, if a signal level of -9 dBm is applied at the input and the line loss is 17 dB then the received signal level will be -26 dBm and the threshold for impulsive noise peaks will be -34 dBm.

Test: The test shall be conducted according to subclause A.2.7.

4.1.10 Phase jitter

Requirement: The phase jitter shall be less than or equal to 10° peak-to-peak when measured at a frequency of 1 020 Hz.

Test: The test shall be conducted according to subclause A.2.8.

4.1.11 Distortion

4.1.11.1 Quantizing distortion

Requirement: The quantizing distortion shall not exceed 3 quantizing distortion unit (qdu). Moreover, Adaptive Differential Pulse Coded Modulation (ADPCM) systems shall not be used.

NOTE: In some cases (e.g. international leased lines spanning several transit countries, particular network configurations) an allocation of 4 qdu may be needed.

Test: There is no test. This requirement shall be checked by calculation using information from the network plans.

4.1.11.2 Total distortion

Requirement: With an input power level of -9 dBm applied at a frequency of 1 020 Hz to the input of the leased line, the signal to total distortion ratio shall be greater than 28 dB.

Test: The test shall be conducted according to subclause A.2.9.

4.1.12 Single tone interference

Requirement: The power level of single tone interference in the band 300 Hz to 3 400 Hz shall not exceed -44 dBm₀, that is 3 dB less than the permitted noise power level (see subclause 4.1.8). In order that this parameter can be tested, the leased line provider should declare the planned value of the output relative level of the leased line.

Where the output relative level either is not, or cannot be, declared by the leased line provider, the power level of any single tone shall be 31 dB below a received test signal which is sent at a level of -9 dBm at a frequency of 1 020 Hz into the far end of the leased line.

Test: The test shall be conducted according to subclause A.2.10.

4.1.13 Frequency error

Requirement: The frequency error introduced by the connection shall be less than or equal to ± 5 Hz when measured at a frequency of 1 020 Hz.

Test: The test shall be conducted according to subclause A.2.11.

4.1.14 Harmonic distortion

Requirement: When a 700 Hz test frequency of -9 dBm is injected at the input of the leased line, the level of any individual harmonic frequency at the output shall be at least 25 dB below the received level of the fundamental frequency.

Test: The test shall be conducted according to subclause A.2.12.

4.1.15 Echo and stability

4.1.15.1 Echo

4.1.15.1.1 Echo control devices

Requirement: In order to facilitate data transmission, echo control devices shall not be used in the connection.

Test: There is no test. This requirement shall be checked using information from the network plans.

4.1.15.1.2 Talker echo

Requirement: With an input signal level of -9 dBm in the frequency range 300 Hz to 3 600 Hz applied at the interface, with a source impedance of 600 Ω , any composite echo signal received at the near end interface shall be greater than 10 dB below the signal level transmitted into the interface (i.e. < -19 dBm).

Test: There is no test. This requirement shall be checked by calculation using information from the network plans.

4.1.15.1.3 Listener echo

Requirement: With an input signal level of -9 dBm in the frequency range 300 Hz to 3 600 Hz applied at the interface, with a source impedance of 600 Ω , any composite echo signal received at the far end interface shall be greater than 20 dB below the received level of the fundamental signal.

Test: There is no test. This requirement shall be checked by calculation using information from the network plans.

4.1.15.2 Stability

Requirement: Any leased line shall be stable over the frequency range 0 Hz to 4 000 Hz for all terminating conditions.

NOTE: The term "all terminating conditions" includes open and short circuit and high impedance terminations.

Test: The test shall be conducted according to subclause A.2.13.

4.2 Interface presentation

The physical connection arrangements shall normally be by a socket as specified in subclause 4.2.1; however at the specific request of the user the connection arrangements specified in subclause 4.2.2 shall be provided.

4.2.1 Connector specification

Requirement: The network interface shall provide an 8-contact socket of the type specified in EN 28877 [6] and with contact assignments as specified in table 4.

Table 4: Contact assignments

Contact number	Network interface
1	Unused
2	Unused
3	Unused
4 & 5	Pair
6	Unused
7	Unused
8	Unused

Test: There shall be a visual inspection that the socket is of the correct type. The contact assignments are tested indirectly through the tests in Annex A.

4.2.2 Hardwired presentation

Requirement: The network interface shall provide a set of connection contacts (e.g. an insulation displacement connector or a screw terminal block) to which solid conductors with wire diameters in the range 0,4 to 0,6 mm may be connected. The leased line provider shall provide information on the configuration of the connection contacts used for each leased line interface.

Test: There shall be a visual inspection that the connection method provided is suitable for taking solid conductors as defined in the requirement and that information on the configuration is provided.

NOTE: All subsequent tests are carried out via the appropriate connection method.

4.2.3 Return loss

Requirement: The return loss presented by the network interface against the reference impedance, when the far end interface of the connection is terminated by the reference impedance, shall either be:

- greater than 6 dB over the frequency range 300 Hz to 3 400 Hz when measured with a voltage equivalent to a signal power level at the input to the leased line of -9 dBm at 1 020 Hz; or
- if the return loss is not greater than 6 dB at all frequencies, then the weighted return loss against the reference impedance shall be greater than 6 dB over the frequency range 300 Hz to 3 400 Hz, when measured with a voltage equivalent to a signal power at the input to the leased line of -9 dBm at 1 020 Hz.

The weighted return loss a_w shall be given by:

$$a_w = 3,85 - 10 \log \left[\int_{300}^{3400} \frac{A(f)}{f} df \right] \text{dB}$$

where $A(f) = 10^{-a(f)/10}$

and $a(f)$ is the measured return loss at frequency f expressed in dB.

Test: The test shall be conducted according to subclause A.2.14.

4.2.4 Power feeding

Requirement: The network interface shall not feed power to the terminal equipment interface and shall not require power from the terminal equipment interface.

Test: The test for power output from the network interface shall be conducted according to subclause A.2.15. The test for the requirement not to support power feeding from the terminal interface is tested indirectly through the various tests of Annex A since no power is supplied over the network interface from the test equipment.

4.3 Safety

Requirement: The leased line interface presentation shall comply with the requirements for Telecommunication Network Voltage (TNV) circuits and protection against electric shock given in subclause 6.2 of EN 60950 [7].

Test: The test shall be conducted according to subclause 6.2 of EN 60950 [7].

NOTE: The tests associated with the requirements in this subclause are not suitable for use on installed leased lines. Such tests may be applied to equipment of the kind used to provide the interface.

4.4 Overvoltage protection

Requirement: The leased line provider shall provide primary protection in accordance with the general practice adopted in the country in which the leased line is terminated.

NOTE: Secondary protection at the terminal equipment may be necessary to protect the terminal equipment from damage caused by overvoltages.

Test: The test provisions of the applicable national requirements shall apply.

4.5 ElectroMagnetic Compatibility (EMC)

There are no EMC requirements under this ETS.

NOTE: EMC requirements are imposed under the EMC Directive (89/336/EEC). Requirements for conducted emissions and immunity to continuous conducted signals may be added to this ETS when appropriate specifications become available if these requirements are not imposed under the EMC directive.

4.6 Availability

There is no requirement on availability under this ETS.

NOTE 1: Annex D provides information about availability values for analogue leased lines.

NOTE 2: At present some leased line providers include availability performance, defined on an individual basis as a quality of service parameter, as part of the contracted supply conditions for their leased line offerings.

Annex A (normative): Test methods

A.1 General

This annex describes the test principles to be used to determine the compliance of a leased line connection and network interface presentation against the requirements of this ETS.

It is outside the scope of this annex to identify the specific details of the implementation of the tests.

Details of test equipment accuracy and the specification tolerance of the test devices are not included in all cases. Where such details are provided, they shall be complied with, but the way they are expressed shall not constrain the method of implementing the test.

NOTE: Attention is drawn to the issue of measurement uncertainty which may be addressed in future documents. Not all the required test results make allowance for spurious events during testing (e.g. errors due to EMC effects), which may make it necessary to repeat a test.

The test configurations given do not imply a specific realization of the test equipment or test arrangement, or the use of specific test devices. However, any test configuration used shall provide those test conditions specified under "interface state", "stimulus" and "monitor" for each individual test.

The test equipment shall be a device, or group of devices, that is capable of generating a stimulus signal conforming to this ETS and capable of monitoring the signal received from the network interface.

A.1.1 Equipment connection

The leased line interface may be supplied with either a socket or a set of contacts suitable for termination of solid conductors. Testing shall be performed at the socket or contact points as this is the point at which compliance with this ETS is required.

A.1.2 Reference impedance

Where the test defines the use of the reference impedance (Z_R), this shall be a complex impedance made up of a resistance of $270\ \Omega$ in series with a parallel combination of $750\ \Omega$ and $150\ \text{nF}$. This is shown in figure A.1. Specific realizations of the reference impedance required for the performance of the tests shall have a return loss against Z_R of 40 dB over the frequency range 300 Hz to 3 400 Hz.




Figure A.1: Reference impedance Z_R

A.1.3 Non-reactive line termination

For all the tests specified in this annex, except the tests for random circuit noise (subclause A.2.6), single tone interference (subclause A.2.10) and return loss (subclause A.2.14), a non-reactive line termination of $600\ \Omega$ is used. In the test for random circuit noise and the test for single tone interference, both impedances are used as the tests assume non-reactive line terminations in the instrumentation.

Where a line termination of $600\ \Omega$ is specified, this shall be a non-reactive resistance of $600\ \Omega \pm 0,25\ \%$.

A.1.4 Measurement frequency

Many of the requirements specify a test signal frequency of 1 020 Hz. Where this is the case, the specified reference frequency tolerance shall be -7 Hz to +2 Hz (range 1 013 Hz to 1 022 Hz).

A.2 Test methods

A.2.1 Overall loss

Requirement: Subclauses 4.1.2 and 4.1.7.2.

Purpose: To determine the overall loss of the leased line.

Test configuration: A test sender is connected to one interface of the leased line. A level meter is connected to the far end interface of the leased line which is terminated in 600 Ω . See figure A.2.

The test is repeated in the other direction.




Figure A.2: Overall loss

Connection state: Available.

Stimulus: The test sender, with an impedance of 600 Ω , is set to send a single signal frequency 1 020 Hz into a load impedance of 600 Ω at a power level of -9 dBm. The load impedance is then disconnected and the signal applied to one interface of the leased line.

Monitor: The power level is measured at the far end of the leased line with a terminating impedance of 600 Ω .

Result: The overall loss, which is the difference between -9 dBm and the measured output power, shall be as defined in subclause 4.1.2.

NOTE: For the purposes of checking the requirement of subclause 4.1.7.2 the test result may be recorded every time the test is performed during the lifetime of the leased line and the record checked for deviation from the limits set in subclause 4.1.7.2.

A.2.2 Loss/frequency distortion and maximum mean input power

Requirement: Subclauses 4.1.3 and 4.1.4.1.

Purpose: To check the loss/frequency distortion of the leased line over the bandwidth 300 Hz to 3 600 Hz. This test also serves to check the requirement for maximum mean input power handling capacity of the leased line interface over the bandwidth 300 Hz to 3 400 Hz.

Test configuration: A test sender is connected to one interface of the leased line. A test receiver is connected to the far end interface of the leased line which is terminated in 600 Ω . See figure A.3.




Figure A.3: Loss/frequency distortion and maximum mean input power

Connection state: Available.

Stimulus: The test sender, with an impedance of 600 Ω , is set to send a signal at a number of frequencies within the range 300 Hz to 3 600 Hz into a load impedance of 600 Ω at a power level of -9 dBm. At each frequency, in turn, the load impedance is disconnected and the signal applied to one interface of the leased line.

Monitor: The power level is measured at the far end of the leased line with a terminating impedance of 600 Ω .

Result: Relative to the received level measured in subclause A.2.1, the received levels at other frequencies shall be within the limits defined by table 2 and figure 1.

A.2.3 Maximum instantaneous power

Requirement: Subclause 4.1.4.2.

Purpose: To verify that the leased line can carry a signal corresponding to the peak value of a +4 dBm signal at the input. A sine wave of 1 020 Hz, at a level equivalent to +4 dBm, is transmitted into the leased line for a duration of no more than 100 ms. There should be no clipping at the output.

Test configuration: See figure A.4.




Figure A.4: Maximum instantaneous power

Connection state: Available.

Stimulus: The test sender, with an impedance of 600 Ω , is set to send a sine wave of frequency 1 020 Hz, at a level of +4 dBm, into the input of the leased line, with a duration of no more than 100 ms.

Monitor: The signal across a termination impedance of 600 Ω at the far end of the leased line.

Result: There shall be no clipping of the signal at the output of the leased line.

A.2.4 Group delay distortion

Requirement: Subclause 4.1.6.

Purpose: To check group delay distortion of the leased line.

Test configuration: A measuring set to the specification of CCITT Recommendation 0.81 [2] is connected with the transmitter at one end of the connection to be measured, and the receiver is connected to the other end of the connection. See figure A.5.




Figure A.5: Group delay distortion

Connection state: Available.

Stimulus: Modulated, identified, reference and measurement frequency signal, as described in CCITT Recommendation O.81 [2].

Monitor: The group delay.

Result: The group delay shall be within the range specified in subclause 4.1.6.

A.2.5 Amplitude hits

Requirement: Subclause 4.1.7.1

Purpose: To check the leased line for amplitude hits.

Test configuration: Performed using an instrument complying with CCITT Recommendation O.95 [4]. The transmitter (test sender) is connected to one interface of the circuit under test and the receiver is connected to the other interface. See figure A.6.




Figure A.6: Amplitude hits

Connection state: Available.

Stimulus: The transmitter, with an impedance of 600 Ω , is set to send at a power level of -9 dBm at a frequency of 1 020 Hz.

Monitor: The number of amplitude hits greater than ± 2 dB with a duration of 4 ms or greater for a period of 15 minutes. Slow amplitude changes, as defined in CCITT Recommendation O.95 [4], shall not be counted.

Result: The number of amplitude hits shall be within the limits specified in subclause 4.1.7.1.

NOTE: The contribution of the return connection, if any, to the result may be estimated from the results of a number of tests over different leased lines using the same return connection in each case.

A.2.6 Random circuit noise

Requirement: Subclause 4.1.8.

Purpose: To measure the random circuit noise of the leased line connection.

Test configuration: Performed using a psophometer complying with ITU-T Recommendation O.41 [8]. With the far end interface of the leased line terminated with the reference impedance, the psophometer is connected to the near end interface. See figure A.7.




Figure A.7: Random circuit noise

Connection state: Available.

Stimulus: None.

Monitor: The psophometrically weighted noise signal across the 600 Ω termination at the near end interface of the leased line.

NOTE: The psophometer terminates the near end of the line with its own internal 600 Ω termination.

Result: The readings obtained shall be within the limits specified in subclause 4.1.8.

A.2.7 Impulsive noise

Requirements: Subclause 4.1.9.

Purpose: To check the impulsive noise performance of the leased line connection.

Test configuration: Performed using an instrument complying with CCITT Recommendation O.71 [1]. With the far end of the leased line connected to the impulsive noise measuring equipment and the threshold of the measuring equipment adjusted to -21 dBm₀ or, where the output relative level is not declared, 8 dB below the received signal level. The test sender is connected to the near end of the leased line. See figure A.8.




Figure A.8: Impulsive noise

- Connection state:** Available.
- Stimulus:** The test sender is set to send a signal at 1 020 Hz at a power level of -9 dBm.
- Monitor:** The number of impulsive noise peaks exceeding the threshold in a 15 minute measurement period.
- Result:** The number of impulsive noise peaks exceeding the threshold shall be less than the limit specified in subclause 4.1.9.

A.2.8 Phase jitter

- Requirement:** Subclause 4.1.10.
- Purpose:** To check the phase jitter performance of the leased line.
- Test configuration:** Performed with an instrument complying with CCITT Recommendation O.91 [3]. The phase jitter measuring equipment is connected to the leased line interfaces as shown in figure A.9.




Figure A.9: Phase jitter

- Connection state:** Available.
- Stimulus:** A test signal as specified in CCITT Recommendation O.91 [3].
- Monitor:** The phase jitter in degrees peak-to-peak.
- Result:** The phase jitter shall not exceed the limit specified in subclause 4.1.10.

A.2.9 Total distortion

- Requirement:** Subclause 4.1.11.2.
- Purpose:** To check the total distortion of the leased line.
- Test configuration:** Performed using a distortion measuring equipment using a sinusoidal test signal complying with CCITT Recommendation O.132 [5]. See figure A.10.




Figure A.10: Total distortion

- Connection state:** Available.

Stimulus: A test signal complying with CCITT Recommendation O.132 [5] is applied to one interface of the circuit under test at a level of -9 dBm and a frequency of 1 020 Hz.

Monitor: The signal to distortion ratio when measured with the 1 000 Hz to 1 025 Hz test signal reject filter.

Result: The measuring equipment receiver shall indicate a total distortion power level below the power level of the received signal as specified in subclause 4.1.11.2.

A.2.10 Single tone interference

Requirement: Subclause 4.1.12.

Purpose: To check the single tone interference performance of the leased line.

Test configuration: With the far end interface terminated in the reference impedance, a selective level meter with an input impedance of 600 Ω is connected to the near end interface. See figure A.11.




Figure A.11: Single tone interference

Connection state: Available.

Stimulus: None.

Monitor: The frequency band 300 Hz to 3 400 Hz is scanned with a bandwidth of 30 Hz.

Result: No single tone shall exceed the limits specified in subclause 4.1.12.

A.2.11 Frequency error

Requirement: Subclause 4.1.13.

Purpose: To check the frequency error performance of the leased line.

Test configuration: A test sender is connected to one interface of the leased line. A frequency counter is connected to the other interface of the leased line with the line terminated in 600 Ω . See figure A.12.




Figure A.12: Frequency error

Connection state: Available.

Stimulus: The test sender, with an impedance of 600 Ω , is set to send a signal at a frequency of 1 020 Hz into a load impedance of 600 Ω at a level of -9 dBm. The load impedance is then disconnected and the signal applied to one interface of the leased line.

Monitor: The signal frequency at the output of the leased line.

Result: The difference between the measured signal frequency and the input frequency shall be within the limits of ± 5 Hz.

A.2.12 Harmonic distortion

Requirement: Subclause 4.1.14

Purpose: To measure the harmonic distortion performance of the leased line. The test uses a test signal frequency of 700 Hz.

NOTE: The frequency of 700 Hz is chosen because it gives the fundamental and the first three harmonics conveniently spaced within the voice bandwidth.

Test configuration: A test sender is connected to one interface of the leased line. A selective level meter or suitable equivalent is connected to the other interface of the leased line. See figure A.13.




Figure A.13: Harmonic distortion

Connection state: Available.

Stimulus: The test sender, with an impedance of 600Ω , is set to send a signal at a frequency of 700 Hz into an impedance of 600Ω at a level of -9 dBm. The impedance is then disconnected and the signal applied to one interface of the line.

Monitor: The received power in 600Ω measured by the level meter at the far end of the line at the fundamental frequency of 700 Hz and at the three harmonic frequencies of 1 400 Hz, 2 100 Hz and 2 800 Hz.

Result: The received power level of the harmonics of the test signal shall be at least 25 dB below the received level of the test signal.

A.2.13 Stability

Requirement: Subclause 4.1.15.2.

Purpose: To verify the stability of the leased line under open circuit and short circuit conditions.

Test configuration: With the far end interface terminated in turn both open circuit and short circuit, a level meter (or similar device) with an input impedance of $> 100 \text{ k}\Omega$ is connected to the near end interface. See figure A.14.




Figure A.14: Stability

Connection state: Available.

Stimulus: None.

Monitor: The frequency band 20 Hz to 4 000 Hz.


Result: Any signal level shall be $> 22 \text{ dB}$ below the level that would be received if a signal of -9 dBm at a frequency of 1 020 Hz were transmitted into the far end of the leased line.

A.2.14 Return loss

Requirement: Subclause 4.2.3

Purpose: To measure the return loss of the input impedance of the leased line with respect to the reference impedance Z_R .

Test configuration: The leased line interface is connected as shown in figure A.15.



$R_1 = R_2$; between 100 Ω and 800 Ω , preferably 600 Ω , matched to better than 0,2 %
Test sender output impedance < 10 Ω

Figure A.15: Return loss

Connection state: Available.

Stimulus: A sinusoidal signal with a constant voltage is applied to the input of the bridge at various frequencies between 300 Hz and 3 400 Hz. The constant voltage is that required to give a power level of -9 dBm at 1 020 Hz into a reference impedance connected to the output of the bridge. Each measurement frequency shall be spaced by not more than one third of an octave from the next frequency of measurement.

Monitor: The level of voltages V_t and V_o with the leased line input connected to the output of the bridge, as shown in figure A.15.

Result: Either the return loss $a(f)$ or the weighted return loss a_w shall meet the requirement of subclause 4.2.3 across the frequency range; where:

$$a(f) = 20 \log \left| \frac{V_o}{2V_t} \right| \text{ is the measured return loss at frequency } f ,$$

$$a_w = 3,85 - 10 \log \left[\int_{300}^{3400} \frac{A(f)}{f} df \right] \text{ dB , and}$$

$$A(f) = 10^{-a(f)/10}$$

where V_o is the test signal level

and V_t is the level measured across the bridge.

Information on the application of the weighting function is given in annex B.

A.2.15 Power feeding

Requirement: Subclause 4.2.4.

Purpose: To verify that the leased line is not designed for power feeding by measuring the output current from the leased line into an impedance of 300 Ω .

Test configuration: See figure A.16. The termination at the far end of the leased line is undefined.




Figure A.16: Power feeding

Connection state: Available.

Stimulus: None.

Monitor: The current through a resistance of 300 Ω .

Result: The current through 300 Ω shall be less than 1 mA.

Annex B (informative): Weighted return loss measurements

B.1 Introduction

The use of a weighted return loss measurement is allowed within this ETS because a fixed return loss is difficult to meet in some situations. Such situations include long local ends to leased lines and short local ends to leased lines in tandem with loaded cable. The definition of a complex reference impedance solves the problem for long local ends but in the case of lines containing loaded cable the situation is worse. The problem results from the behaviour of the impedance of loaded cable near to the cut-off frequency and it is for this reason that the weighting function has been introduced into the requirement to give more weight to the lower frequencies.

B.2 Weighting function

Limitations are placed on the impedance of the leased line interface in order to control trans-hybrid loss in the terminal equipment. A weighting function which relates to trans-hybrid loss and which is relatively convenient to use is provided for the determination of echo loss in ITU-T Recommendation G.122; this weighting function can also be used for the determination of the weighted return loss.

The weighted return loss a_w is derived from the integral of the power transfer characteristic, $A(f)$, weighted by a negative slope of 3 dB per octave, starting at 300 Hz and extending to 3 400 Hz as follows:

$$a_w = 3,85 - 10 \log \left[\int_{300}^{3400} \frac{A(f)}{f} df \right] \text{ dB} \quad (1)$$

Where $A(f) = 10^{-a(f)/10}$

and $a(f)$ is the measured return loss at frequency f expressed in dB.

B.2.1 Calculation (trapezoidal rule)

In order to calculate the weighted return loss, the weighting function can be approximated by choosing measurement frequencies that are equidistant on a log-frequency scale and using the trapezoidal rule, as described in Annex B of ITU-T Recommendation G.122 (1994). Thus if equidistant measurement frequencies are chosen on a log-frequency scale and the measurement frequencies are spaced by no more than one third of an octave, then the weighted return loss a_w can be represented by:

$$a_w = -10 \log \left[\frac{1}{N} \left(\frac{A_0}{2} + A_1 + A_2 + A_3 + \dots + A_{N-1} + \frac{A_N}{2} \right) \right]$$

where $N+1$ is the number of measurement frequencies

$$A_n = 10^{-a(f_n)/10}, \text{ for } n \text{ from } 0 \text{ to } N$$

and $a(f_n)$ is the measured return loss at frequency f_n expressed in dB.

B.2.2 Calculation (tabulated data)

Where the loss/frequency data are only available at N+1 discrete frequencies, which are non-uniformly spaced on a log-frequency scale, an approximation to the formula for weighted return loss a_w can be given by:

$$a_w = 3,24 - 10 \log \sum_{n=1}^N (A_n + A_{n-1}) (\log f_n - \log f_{n-1}) \quad (3)$$

where N+1 is the number of measurement frequencies

$$A_n = 10^{-a(f_n)/10}, \text{ for } n \text{ from } 0 \text{ to } N$$

and $a(f_n)$ is the measured return loss at frequency f_n expressed in dB.

NOTE 1: The approximation involved is to assume that within the sub-band f_{n-1} to f_n , the power ratio is constant and has the value $A(f) = (A_n + A_{n-1}) / 2$.

NOTE 2: The constant 3,24 in the approximate formula arises from a combination of the constant 3,85 in the definition and other constants produced by the approximation.

The sum of product terms may be conveniently calculated as illustrated by the following example and table B.1.

EXAMPLE: Weighted return loss = $3,24 - 10 \log (0,5050) = 6,21 \text{ dB}$

Table B.1: Example of calculation of weighted return loss

n	f (Hz)	log f _n	log f _n - log f _{n-1}	measured return loss	A _n	A _n + A _{n-1}	(3) x (6)
	(1)	(2)	(3)	(4)	(5)	(6)	(7)
0	300	2,477		5,00	0,316		
1	500	2,699	0,222	6,00	0,251	0,567	0,1259
2	800	2,903	0,204	8,00	0,158	0,410	0,0836
3	1 000	3,000	0,097	7,00	0,200	0,358	0,0347
4	1 500	3,176	0,176	6,00	0,251	0,451	0,0794
5	2 000	3,301	0,125	6,00	0,251	0,502	0,0628
6	2 500	3,398	0,097	6,00	0,251	0,502	0,0487
7	3 000	3,477	0,079	5,80	0,263	0,514	0,0407
8	3 400	3,531	0,054	5,60	0,275	0,538	0,0293
						Total	0,5050

Annex C (informative): Overall loss and quantizing distortion

C.1 Introduction

The purpose of this annex is to provide information for the user on the factors that affect the overall loss and quantizing distortion on a leased line. This annex is given for information only and is not a normative part of the standard. This information is provided because the performance of a leased line is highly dependent on the methods of provision used within the public network and is not related to the distance between the NTP on the customer's premises.

In many cases the leased lines provided in conformance to this standard will provide a level of performance much better than that specified within this standard. Where the actual performance available from a leased line offered under the ONP minimum set does not satisfy the needs of the user, the leased line provider may be able to provide an alternative more suitable type of leased line. Users are advised to discuss with the leased line provider the suitability of a particular leased line for their intended application.

Figure C.1 shows some of the different means by which analogue leased lines may be provided. In most cases, all NTPs on the customer's premises are connected back to the network operators local exchange premises¹ in a star configuration. This local loop is normally provided using copper pairs and may be the main source of loss. In some cases the local loop may use radio technology or fibre optic cables, in which case the transmission would be digital.




Figure C.1: Means of providing analogue leased lines

The means of transmission between the local exchange premises may be one or more of the following:

- Digital transmission on optical fibre, copper cable or microwave radio links, using Time Division Multiplexing (TDM);
- Analogue transmission on copper cable or microwave radio using Frequency Division Multiplexing (FDM);
- Analogue transmission on copper cable without multiplexing, with or without amplification.

In general, the trend is for the analogue transmission equipment in the public networks to be replaced by digital equipment, although it will be a number of years before all the analogue transmission equipment has been withdrawn.

¹ Leased lines are normally provided from the premises that provides the local exchange for the switched network, although the leased lines will not normally be routed through the local exchange switch. In many cases these premises will house special transmission equipment for the connection of the leased lines to other parts of the public network.

C.2 Overall loss

The overall loss of a leased line is frequently of great importance in determining the suitability of a leased line for a particular application. The overall loss can, however, vary significantly between installations due to various factors such as the distance of the termination points of the leased line from the local exchange premises and the general practices adopted by the specific network provider.

The range of losses specified within the minimum set of analogue leased line standards encompasses what is generally available from leased line providers, where the leased lines have been supplied in accordance with the general practice of the network providers.

In most cases, it is not the geographical distance between the ends of the leased line which determines the overall loss, but the different components from which the leased line is constructed. Normally, the main contributor to loss is the copper pair that provides the local loop, whose loss is distance dependent and may be up to some 10 dB, which would equate to a distance of 10-15 km depending on the type of cable. Thus a leased line between two adjacent customers premises may have a high loss in some circumstances. This is shown in figure C.2.




Figure C.2: Example of a short ordinary quality leased line with high loss

The loss between the local exchange premises will be distance dependent only if copper cables without amplification are used. If an analogue or digital transmission system is used, this system will normally introduce a fixed and distance independent loss. Such systems will almost always be used for international leased lines and will frequently be used for long distance national leased lines.

This information shows why a leased line between two closely spaced NTPs that are both at some distance from the local exchange premises may have considerably greater loss than an international leased line between NTPs that are close to the local exchange premises (e.g. in a city centre). An example of a long international leased line with low loss is given in figure C.3.




Figure C.3: Example of a long international leased line with low loss

C.3 Quantizing distortion

Quantizing distortion, is the distortion of a signal that results either from the process of conversion from an analogue to digital form or, the conversion between different digital forms. Quantizing distortion is measured in quantizing distortion units where one unit is defined as the distortion that arises from a conversion from analogue to the normal form of digital encoding in fixed networks (64 kbit/s PCM) and back.

Where there is a need to maximise the number of circuits that can be carried in a given transmission medium, lower bit rates than 64 kbit/s may be used for each circuit, but with the introduction of higher levels of quantizing distortion.

The limit for quantizing distortion is specified at 7,5 qdu (including one ADPCM conversion) for the ordinary quality leased lines, and 3 qdu for the special quality leased lines (although in some cases 4 qdu may be required). Figure C.4 shows an example of how the qdus may be build up within a leased line; the leased line standards do not, however, allocate the qdus to a particular portion of the leased line.




Figure C.4: Example allocation of qdu for ordinary and special quality leased lines

Annex D (informative): Availability

D.1 General

This annex is given for information only and is not a normative part of the standard.

The availability of a leased line should be assessed over a long period of time and cannot be measured using a single test. CCITT Recommendation M.1016, proposes that any observation period should be three calendar months. For the purpose of observing availability, the following terms should be considered:

D.1.1 Unavailability

$$\text{Unavailability} = \frac{\sum \text{Unavailability periods}}{\text{Observation period}}$$

(with unavailability generally expressed as a percentage)

D.1.2 Availability

$$\text{Availability} = \frac{\text{Observation period} - \sum \text{Unavailability periods}}{\text{Observation period}}$$

(with availability generally expressed as a percentage)

D.2 Definition of unavailability periods

The ITU-T, within CCITT Recommendation M.1016, defines an assessment procedure based on fault reports made by users, and planned interruptions, which unacceptably disrupt the user's service.

CCITT Recommendation M.1016 specifies three conditions which should be taken into account when assessing the availability performance of international leased circuits:


- faults, as reported by the user and confirmed by tests and investigations carried out by the leased line provider;
- impairments to normal service, as reported by the user, where the user chooses to continue to use the leased line in a degraded condition;
- planned interruptions to service to enable, for example, permanent repair work to be carried out, maintenance routines to be performed.

Figures D.1 and D.2 determine if, and how, unavailability periods are to be included in the assessment procedure; these principles are as specified in tables A-1 and A-2 of CCITT Recommendation M.1016.

For the purpose of these tables the following definitions of impaired service report and fault report apply:

Impaired service report: the condition reported by the user where the perceived performance of the leased line is degraded but the user has decided that the leased line can still be used.


Fault report: the condition reported by the user where the user has decided that the leased line is unusable.



NOTE 1: If the announced start time is not known to the fault report point, the user report time should be used.

NOTE 2: If the announced end time is not known to the fault report point, the time the service is returned to the user (or first attempt to do so) should be used.

Figure D.1: Unavailability periods as a result of fault reports



NOTE: For fault reports which are received because the announced fault time is exceeded (see figure D.1).

Figure D.2: Unavailability periods as a result planned interruptions of service

If a circuit is unavailable at the beginning of the observation period, the fault or planned interruption of service causing the unavailability is not taken into consideration. However, unavailability is deemed to start at the beginning of the observation period.

If a circuit is unavailable at the end of the observation period, the fault or planned interruption of service causing the unavailability is taken into consideration. The unavailability is deemed to end at the end of the observation period.

D.3 Availability figures

At the time of publication, there are no International or European standards defining requirements for availability for analogue leased lines.

The figures given in table D.1 give some indication of the availability for analogue leased lines; they are based on values given for 2 048 kbit/s digital path elements between customer premises for terrestrial connections up to 5 500 km and satellite connections with access lines of up to 1 375 km. Therefore they should be regarded only as an indication of the availability of analogue leased lines. In practice the availability figures may be considerably better.

Table D.1: Availability figures

Terrestrial		Satellite	
mean	worst case	mean	worst case
97,3 %	94,7 %	undefined	97,0 %

The mean value is the average for all the leased lines of an operator; the worst case value is the value that no leased line should exceed (i.e. be worse than this figure). Customers who require enhanced availability should discuss their particular requirements with the leased line provider.

Annex E (informative): Bibliography

- 89/336/EEC: "Council Directive of 3 May 1989 on the approximation of the laws of Member States relating to electromagnetic compatibility".
- 91/263/EEC: "Council Directive of 29 April 1991 on the approximation of the laws of Member States concerning telecommunications terminal equipment, including the mutual recognition of their conformity".
- 92/44/EEC: "Council Directive of 5 June 1992 on the application of Open Network Provision to leased lines".
- CCITT Recommendation M.1016 (1988): "Assessment of the service availability performance of international leased circuits".
- CCITT Recommendation M.1020 (1988): "Characteristics of Special Quality International Leased Circuits with Special Bandwidth Conditioning".
- CCITT Recommendation V.2 (1988): "Power levels for data transmission over telephone lines".
- ITU-T Recommendation G.114 (1993): "One-way propagation time".
- ITU-T Recommendation G.122 (1993): "Influence of national systems on stability talker echo in international connections".
- ETS 300 450: "Business TeleCommunications (BTC); Ordinary and Special quality voice bandwidth 2-wire analogue leased lines (A2O and A2S); Terminal equipment interface".

History

Document history			
September 1994	Public Enquiry	PE 70:	1994-09-05 to 1994-12-30
November 1995	Vote	V 92:	1995-11-27 to 1996-01-19
February 1996	First Edition		