



**E**UROPEAN  
**T**ELECOMMUNICATION  
**S**TANDARD

**FINAL DRAFT**  
pr **ETS 300 466**

January 1996

---

Source: ETSI TC-RES

Reference: DE/RES-03048

ICS: 33.020, 33.060.50

**Key words:** DECT, GSM

**Radio Equipment and Systems (RES);  
Digital European Cordless Telecommunications/  
Global System for Mobile Communications  
(DECT/GSM) interworking profile;  
General description of service requirements;  
Functional capabilities and information flows**

**ETSI**

European Telecommunications Standards Institute

**ETSI Secretariat**

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

\*

---

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.



## Contents

Foreword .....	5
1 Scope .....	7
2 Normative references .....	7
3 Definitions and abbreviations .....	10
3.1 Definitions .....	10
3.2 Abbreviations .....	12
4 Conformance .....	13
5 Introduction .....	13
6 General .....	13
7 GSM service provision .....	14
7.1 General .....	14
7.1.1 Processing of GSM services not supported .....	14
7.1.2 Bearer service .....	14
7.1.2.1 Exception handling .....	14
7.1.3 Teleservice .....	14
7.1.3.1 Exception handling .....	14
7.1.4 Tones .....	14
7.1.5 Supplementary services .....	14
7.1.5.1 General requirements .....	15
7.1.5.2 Exception handling .....	15
7.1.5.3 Number Identification Supplementary Services (NISS) .....	15
7.1.5.4 Call Offering Supplementary Services (COSS) .....	15
7.1.5.5 Call Completion Supplementary Services (CCSS) .....	15
7.1.5.6 Multi Party Supplementary Services (MPSS) .....	15
7.1.5.7 Community of Interest Supplementary Services (CISS) .....	15
7.1.5.8 Charging Supplementary Services (CSS) .....	15
7.1.5.9 Call Restriction Supplementary Services (CRSS) .....	15
7.1.6 Unstructured Supplementary Services Data (USSD) .....	16
7.1.6.1 Exception handling .....	16
7.2 Functional capabilities and information flows .....	16
7.2.1 Supplementary services .....	16
7.2.1.1 General requirement .....	16
7.2.1.2 Number Identification Supplementary Services (NISS) .....	16
7.2.1.3 Call Offering Supplementary Services (COSS) .....	16
7.2.1.4 Call Completion Supplementary Services (CCSS) .....	16
7.2.1.5 Multi Party Supplementary Services (MPSS) .....	16
7.2.1.6 Community of Interest Supplementary Services (CISS) .....	16
7.2.1.7 Call Restriction Supplementary Services (CRSS) .....	16
7.2.1.8 Charging Supplementary Services (CSS) .....	16
7.2.2 Unstructured Supplementary Services Data (USSD) .....	16
7.2.3 Bearer services .....	17
7.2.4 Teleservices .....	17
8 Portable Part (PP) requirements .....	17
8.1 General .....	17
8.2 Description .....	17
8.2.1 Basic PP features .....	17
8.2.2 Supplementary PP features .....	17
8.2.3 Additional PP features .....	17

8.3	Requirements for implementing PP features .....	17
8.3.1	Basic PP features .....	18
8.3.1.1	Display of called number .....	18
8.3.1.2	Indication of call progress signals .....	18
8.3.1.3	Country/PLMN indication and PLMN selection .....	18
8.3.1.4	Keypad .....	18
8.3.1.5	International Mobile station Equipment Identity (IMEI) and/or International Portable Equipment Identity (IPEI) .....	19
8.3.1.6	International access function .....	19
8.3.1.7	Autocalling restriction capabilities .....	19
8.3.1.8	Emergency calls capabilities .....	19
8.3.1.9	Subscription identity management .....	19
8.3.1.10	Support of DECT encryption .....	19
8.3.1.11	Support of ERMES alphabet .....	19
8.3.2	Supplementary/additional PP features .....	19
8.3.2.1	Support of supplementary services .....	19
8.3.2.2	Abbreviated dialling .....	19
8.3.2.3	Fixed number dialling .....	20
8.3.2.4	Last Numbers Dialed (LND) .....	20
8.4	Man-Machine Interface (MMI) of the PP .....	20
8.4.1	Physical user input features .....	20
8.4.1.1	MMI related to PP features .....	20
8.4.2	Physical output features .....	20
8.4.3	Support of Dual Tone Multi Frequency (DTMF) .....	20
8.4.4	Procedures .....	21
8.4.4.1	Definition of functions .....	21
8.4.4.2	Call Control .....	21
8.5	SIM interfaces .....	21
8.5.1	Entry of PIN and PIN2 .....	21
8.5.2	Change of PIN or PIN2 .....	21
8.5.3	Unblocking of PIN or PIN2 .....	21
8.5.4	Status information - return codes .....	22
8.6	Service access .....	22
9	Fixed Part (FP) requirements .....	22
9.1	Support of GSM Mobile Equipment Identity and Software Version number (IMEISV) .....	22
9.2	Support of MS classmark .....	22
9.3	Support of emergency call capability .....	22
9.4	Support of international access function .....	22
9.5	Support of DTMF .....	23
9.6	Support of ERMES alphabet .....	23
Annex A (normative):	GSM teleservices and supplementary services .....	24
Annex B (informative):	Bibliography .....	25
History	.....	26

## Foreword

This final draft European Telecommunication Standard (ETS) has been produced by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI), and is now submitted for the Voting phase of the ETSI standards approval procedure.

<b>Proposed transposition dates</b>	
Date of latest announcement of this ETS (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Blank page

## 1 Scope

This ETS is a part of the Digital European Cordless Telecommunications/Global System for Mobile Communications (DECT/GSM) interworking profile and specifies requirements needed to ensure that GSM basic services can be provided over the DECT air interface.

To enable DECT terminals to inter-work with DECT systems which are connected to the GSM infrastructure, this ETS specifies the additions to the GAP [46] on which this profile is based. The additions are based on the DECT Common Interface specification given in ETS 300 175 [36] to [43].

From the GSM side this ETS assumes interworking with GSM Public Land Mobile Network (PLMN) phase 2. Interworking with GSM Phase 1 is outside the scope of this ETS.

Interworking requirements are based upon Mobile Switching Centre (MSC) attachment for the DECT Fixed Part (FP) as the FP is using the A-interface towards the GSM MSC in the respect that the FP emulates a GSM Base Station Controller (BSC) with regards to the GSM messages which are relevant to this ETS. The complete interface used between the DECT FP and the GSM MSC is specified in ETS 300 499. Attachment via other interfaces to GSM-networks is outside the scope of this ETS.

The DECT access protocols and FP and Portable Part (PP) interworking/mappings necessary for the support of basic voice telephony service are specified in ETS 300 370 [44]. The interworking/mappings and access requirements for the support of other services of this ETS, will be included in future standards of the DECT/GSM interworking profile.

The whole set of GSM services according to GSM Phase 2 is supported unless it is explicitly stated in the following clauses of this ETS.

The DECT PP has to accept the GSM Subscriber Identification Module (SIM) as well as the DECT Authentication Module (DAM), with a GSM application. The functional separation of the DECT/GSM interworking among DECT FP and PP allows for terminal portability. All roaming scenarios based on SIM roaming as described in GSM specifications are applicable. Additionally subscribers using a SIM or DAM with GSM Application in conjunction with a DECT PP, capable of DECT GSM interworking may also roam among FP's connected to different GSM networks.

Handover among DECT radio access systems and GSM radio access systems as well as handover among DECT cells connected to different Common Control Fixed Parts (CCFP's), which are individually linked to a MSC, is outside the scope of this ETS.

## 2 Normative references

This ETS incorporates, by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] GSM 02.07 (ETS 300 505): "European digital cellular telecommunications system (Phase 2); Mobile Station (MS) features".
- [2] GSM 02.40 (ETS 300 512): "European digital cellular telecommunications system (Phase 2); Procedures for call progress indications".
- [3] GSM 02.11 (ETS 300 507): "European digital cellular telecommunications system (Phase 2); Service accessibility".
- [4] GSM 02.16 (ETS 300 508): "European digital cellular telecommunications system (Phase 2); International Mobile station Equipment Identities (IMEI)".
- [5] GSM 02.30 (ETS 300 511): "European digital cellular telecommunications system (Phase 2); Man Machine Interface (MMI) of the Mobile Station (MS)".

- [6] GSM 02.17 (ETS 300 509): "European digital cellular telecommunications system (Phase 2); Subscriber Identity Modules (SIM); Functional characteristics".
- [7] GSM 03.01 (ETS 300 521): "European digital cellular telecommunications system (Phase 2); Network functions".
- [8] GSM 03.09 (ETS 300 527): "European digital cellular telecommunications system (Phase 2); Handover procedures".
- [9] GSM 03.12 (ETS 300 530): "European digital cellular telecommunications system (Phase 2); Location registration procedures".
- [10] GSM 03.14 (ETS 300 532): "European digital cellular telecommunications system (Phase 2); Support of Dual Tone Multi-Frequency signalling (DTMF) via the GSM system".
- [11] GSM 04.08 (ETS 300 557): "European digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 specification".
- [12] GSM 05.08 (ETS 300 578): "European digital cellular telecommunications system (Phase 2); Radio subsystem link control".
- [13] GSM 11.10 (ETS 300 607): "European digital cellular telecommunications system (Phase 2); Mobile Station (MS) conformity specification".
- [14] GSM 11.11 (ETS 300 608): "European digital cellular telecommunications system (Phase 2); Specification of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface".
- [15] GSM 02.03 (ETS 300 502): "European digital cellular telecommunications system (Phase 2); Teleservices supported by a GSM Public Land Mobile Network (PLMN)".
- [16] GSM 02.04 (ETS 300 503): "European digital cellular telecommunications system (Phase 2); General on supplementary services".
- [17] GSM 03.11 (ETS 300 529): "European digital cellular telecommunications system (Phase 2); Technical realization of supplementary services".
- [18] GSM 04.10 (ETS 300 558): "European digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 Supplementary services specification General aspects".
- [19] GSM 04.80 (ETS 300 564): "European digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 supplementary services specification Formats and coding".
- [20] GSM 02.81 (ETS 300 514): "European digital cellular telecommunications system (Phase 2); Line identification supplementary services - Stage 1".
- [21] GSM 02.82 (ETS 300 515): "European digital cellular telecommunications system (Phase 2); Call Forwarding (CF) supplementary services - Stage 1".
- [22] GSM 02.83 (ETS 300 516): "European digital cellular telecommunications system (Phase 2); Call Waiting (CW) and Call Holding (HOLD) supplementary services - Stage 1".
- [23] GSM 02.84 (ETS 300 517): "European digital cellular telecommunications system (Phase 2); Multi Party (MPTY) supplementary services - Stage 1".



- [24] GSM 02.85 (ETS 300 518): "European digital cellular telecommunications system (Phase 2); Closed User Group (CUG) supplementary services - Stage 1".
- [25] GSM 02.86 (ETS 300 519): "European digital cellular telecommunications system (Phase 2); Advice of charge (AoC) supplementary services - Stage 1".
- [26] GSM 02.24 (ETS 300 510): "European digital cellular telecommunications system (Phase 2); Description of Charge Advice Information (CAI)".
- [27] GSM 02.88 (ETS 300 520): "European digital cellular telecommunications system (Phase 2); Call Barring (CB) supplementary services - Stage 1".
- [28] GSM 03.81 (ETS 300 542): "European digital cellular telecommunications system (Phase 2); Line identification supplementary services - Stage 2".
- [29] GSM 03.82 (ETS 300 543): "European digital cellular telecommunications system (Phase 2); Call Forwarding (CF) supplementary services - Stage 2".
- [30] GSM 03.83 (ETS 300 544): "European digital cellular telecommunications system (Phase 2); Call Waiting (CW) and Call Hold (HOLD) supplementary services - Stage 2".
- [31] GSM 03.84 (ETS 300 545): "European digital cellular telecommunications system (Phase 2); Multi Party (MPTY) supplementary services - Stage 2".
- [32] GSM 03.85 (ETS 300 546): "European digital cellular telecommunications system (Phase 2); Closed User Group (CUG) supplementary services - Stage 2".
- [33] GSM 03.88 (ETS 300 548): "European digital cellular telecommunications system (Phase 2); Call Barring (CB) supplementary services - Stage 2".
- [34] GSM 03.90 (ETS 300 549): "European digital cellular telecommunications system (Phase 2); Unstructured Supplementary Services Data (USSD) - Stage 2".
- [35] GSM 03.86 (ETS 300 547) "European digital cellular telecommunications system (Phase 2); Advice of charge (AoC) supplementary services - Stage 2".
- [36] ETS 300 175-1: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Common Interface (CI); Part 1: Overview".
- [37] ETS 300 175-2: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Common Interface (CI); Part 2: Physical Layer (PHL)".
- [38] ETS 300 175-3: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Common Interface (CI); Part 3: Medium Access Control (MAC) layer".
- [39] ETS 300 175-4: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Common Interface (CI); Part 4: Data Link Control (DLC) layer".
- [40] ETS 300 175-5: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Common Interface (CI); Part 5: Network (NWK) layer".
- [41] ETS 300 175-6: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Common Interface (CI); Part 6: Identities and addressing".

- [42] ETS 300 175-7: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Common Interface (CI); Part 7: Security features".
- [43] ETS 300 175-8: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Common Interface (CI); Part 8: Speech coding and transmission".
- [44] ETS 300 370: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); DECT/GSM interworking profile".
- [45] I-ETS 300 176: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Approval test specification".
- [46] ETS 300 444: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Generic Access Profile (GAP)".
- [47] ETS 300 133: "Paging Systems (PS); European Radio Message System (ERMES), Part 2, Service aspects (annex B)".
- [48] ISO Publication 8859 (1986 E): "Information processing - ISO 7-bit and 8-bit coded character sets".
- [49] GSM 02.02 (ETS 300 501): "European digital cellular telecommunications system (Phase 2); Bearer Services (BS) supported by a GSM Public Land Mobile Network (PLMN)".
- [50] TBR 6: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); General terminal attachment requirements".
- [51] TBR 10: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); General terminal attachment requirements; Telephony applications".
- [52] GSM 02.90 (ETS 300 625): "Description of unstructured Supplementary Service Data (USSD)".
- [53] prETS 300 499: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications/Global System for Mobile Communications (DECT/GSM) interworking profile; Mobile services Switching Centre (MCs) - Fixed Part (FP) interconnection".
- [54] prETS 300 703: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); DECT/GSM interworking profile - GSM Phase 2 supplementary services implementation".

### 3 Definitions and abbreviations

#### 3.1 Definitions

**for the purposes of this ETS, the following definitions apply:**

**attach:** The process whereby a PP within the coverage area of a FP to which it has access rights, notifies this FP that it is operative. The reverse process is detach, which reports the PP as inoperative.

NOTE 1: An operative PP is assumed to be ready to receive calls.

**authentication:** The process whereby a DECT subscriber is positively verified to be a legitimate user of a particular FP.

NOTE 2: Authentication is generally performed at call set-up, but may also be done at any other time (e.g. during a call).

**bearer service:** A type of telecommunication service that provides a defined capability for the transmission of signals between user-network interfaces.

NOTE 3: The DECT user-network interface corresponds to the top of the Network (NWK) layer (layer 3).

**call:** All of the NWK layer processes involved in one NWK layer peer-to-peer association.

NOTE 4: Call may sometimes be used to refer to processes of all layers, since lower layer processes are implicitly required.

**Fixed Part (DECT Fixed Part) (FP):** A physical grouping that contains all of the elements in the DECT network between the local network and the DECT air interface.

NOTE 5: A DECT FP contains the logical elements of at least one Fixed radio Termination (FT), plus additional implementation specific elements.

**Fixed Part GSM PLMN Attachment (DECT Fixed Part Attached To A GSM MSC):** A definition of a functional environment where a DECT system (FP) is attached to an GSM MSC. The MSC in this case refers to a functional entity providing the required Mobility Management (MM) and Call Control (CC) functionality defined in this ETS in order to communicate with the FP.

**Fixed Radio Termination (FT):** A logical group of functions that contains all of the DECT processes and procedures on the fixed side of the DECT air interface.

NOTE 6: A FT only includes elements that are defined in the DECT CI standard. This includes radio transmission elements together with a selection of layer 2 and layer 3 elements.

**handover:** The process of switching a call in progress from one physical channel to another physical channel. These processes can be internal (see internal handover) or external (see external handover).

NOTE 7: There are two physical forms of handover, intra-cell handover and inter-cell handover. Intra-cell handover is always internal. Inter-cell handover can be internal or external.

**incoming call:** A call received at a PP.

**inter-cell handover:** The switching of a call in progress from one cell to another cell.

**internal handover:** Handover processes that are completely internal to one Fixed radio Termination (FT). Internal handover re-connects the call at the lower layers, while maintaining the call at the NWK layer.

NOTE 8: The lower layer reconnection can either be at the Data Link Control (DLC) layer (connection handover) or at the MAC layer (bearer handover).

**inter-operability:** The capability of FPs and PPs, that enable a PP to obtain access to teleservices in more than one location area and/or from more than one operator (more than one service provider).

**inter-operator roaming:** Roaming between FP coverage areas of different operators (different service providers).

**Interworking Unit (IWU):** A unit that is used to interconnect sub-networks.

NOTE 9: The IWU contains the interworking functions necessary to support the required sub-network interworking.

**intra-cell handover:** The switching of a call in progress from one physical channel of one cell to another physical channel of the same cell.

**intra-operator roaming:** Roaming between different FP coverage areas of the same operator (same service provider).

**location area:** The domain in which a PP may receive and/or make calls as a result of a single location registration.

**location registration:** The process whereby the position of a DECT portable termination is determined to the level of one location area, and this position is updated in one or more databases.

NOTE 10: These databases are not included within the DECT FT.

**Medium Access Control (MAC) connection:** An association between one source MAC Multi-Bearer Control (MBC) entity and one destination MAC MBC entity. This provides a set of related MAC services (a set of logical channels), and it can involve one or more underlying MAC bearers.

**outgoing call:** A call originating from a PP.

**Portable Part (DECT Portable Part) (PP):** A physical grouping that contains all elements between the user and the DECT air interface. PP is a generic term that may describe one or several physical pieces.

NOTE 11: A DECT PP is logically divided into one portable termination plus one or more portable applications.

**Portable Radio Termination (PT):** A logical group of functions that contains all of the DECT processes and procedures on the portable side of the DECT air interface.

NOTE 12: A PT only includes elements that are defined in the DECT CI standard. This includes radio transmission elements (layer 1) together with a selection of layer 2 and layer 3 elements.

**Radio Fixed Part (RFP):** One physical sub-group of an FP that contains all the radio end points (one or more) that are connected to a single system of antennas.

**registration:** An ambiguous term, that should always be qualified. See either location registration or subscription registration.

**roaming:** The movement of a PP from one FP coverage area to another FP coverage area, where the capabilities of the FPs enable the PP to make or receive calls in both areas.

NOTE 13: Roaming requires the relevant FPs and PP to be inter-operable.

**subscription registration:** The infrequent process whereby a subscriber obtains access rights to one or more FPs.

NOTE 14: Subscription registration is usually required before a user can make or receive calls.

### 3.2 Abbreviations

For the purposes of this ETS, the following abbreviations apply:

AoCC	Advice of Charge (Charging) (supplementary service)
CC	Call Control
CI	Common Interface
DAM	DECT Authentication Module
DECT	Digital European Cordless Telecommunications
DLC	Data Link Control
DTMF	Dual Tone Multi-Frequency
FP	Fixed Part
FT	Fixed radio Termination
IPEI	International Portable Equipment Identity
IWU	InterWorking Unit
MAC	Medium Access Control
MM	Mobility Management
MS	Mobile Station
MSC	Mobile Switching Centre

NWK	NetWorK
PP	Portable Part
PT	Portable radio Termination. See definition
RFP	Radio Fixed Part
SIM	Subscriber Identification Module

## 4 Conformance

Conformance to this ETS is met by conforming to ETS 300 370 [44] and the references listed in annex A. The procedures contained in ETS 300 370 [44], ETS 300 499 [53], ETS 300 703 [54] and the work item references in annex A fulfil the requirements relevant to the interworking of equipment, in order to provide the services listed in this ETS. Therefore no methods of testing is provided in this ETS.

In order to conform to this ETS, the FT and PT shall satisfy the requirements identified in the relevant Profile ICS proformas listed in annex A.

## 5 Introduction

This ETS is a part of a set of standards for the DECT/GSM interworking profile (IWP) concept that includes:

- general description of service requirements, functional capabilities and information flows, (this ETS);
- access and mapping (protocol/procedure description for 3,1 kHz speech service), (ETS 300 370 [44]);
- GSM-MSC - DECT-FP Fixed Interconnection (ETS 300 499 [53]);
- GSM Phase 2 supplementary services implementation (ETS 300 703 [54]).

Other standards of the DECT/GSM IWP are expected to describe (see Bibliography, annex A):

- implementation of Short message services, Point-to-point and Cell broadcast (DE/RES-03057);
- implementation of bearer services (DE/RES -03071);
- implementation of facsimile group 3 (DE/RES -03072).

This ETS is based on ETS 300 175 [36] to [43] to enable DECT terminals to inter-work in the public and private environment with DECT systems which are connected to a GSM core infrastructure.

In addition, this ETS is based on the DECT Generic Access Profile (GAP) ETS 300 444 [46] to enable the same DECT/GSM terminal to inter-work with a DECT FP complying to the GAP requirements, irrespective of whether this FP provides residential, business or public access services. General attachment requirements and speech attachment requirements are based on TBR 6 [50] and TBR 10 [51].

Further details on the DECT system may be found in ETR 015, ETR 043, and ETR 056 (see Bibliography, annex A), and in I-ETS 300 176 [45].

## 6 General

This ETS specifies the requirements to provide GSM basic services over the DECT air interface.

The clauses that follow describe the teleservices, bearer services and the supplementary services that are supported and the requirements on both the PP and FP.

GSM basic services according to GSM phase 2 shall be supported unless explicitly stated otherwise. The services described in clause 7 is, in general terms, as provided to the user. All cases of non-support of GSM services are explicitly mentioned and appropriate exception handling procedures are described in the relevant subclauses.

The interworking procedures and mappings are defined in ETS 300 370 [44], ETS 300 499 [53], ETS 300 703 [54], and the relevant documents referenced in annex A.

## **7 GSM service provision**

### **7.1 General**

GSM services (tele-, bearer and/or supplementary services) according to GSM Phase 2, shall be supported, unless explicitly stated otherwise. The specific services are described in general terms as provided to the user of the services.

#### **7.1.1 Processing of GSM services not supported**

The DECT FP shall perform the appropriate GSM error handling for all GSM services (tele-, bearer and/or supplementary services) which are not supported by the DECT FP or by the GSM network.

#### **7.1.2 Bearer service**

The bearer services shall be supported as specified in GSM 02.02 (ETS 300 501) [49].

##### **7.1.2.1 Exception handling**

For bearer services the GSM error handling as defined in GSM 04.08 (ETS 300 557) [11] shall be supported.

#### **7.1.3 Teleservice**

The teleservices shall be supported as specified in GSM 02.03 (ETS 300 502) [16]. For information purposes the teleservices in GSM 02.03 (ETS 300 502) [16] are reproduced in annex B.

##### **7.1.3.1 Exception handling**

For teleservices the GSM error handling as defined in GSM 04.08 (ETS 300 557) [11] shall be supported.

#### **7.1.4 Tones**

In order to provide GSM users indication of the progress of their calls, supervisory tones shall be supported as specified in GSM 02.40 (ETS 300 512) [2]. Tones not provided by the GSM network shall be generated in the DECT FP, except the alerting tone which is generated in the PP.

#### **7.1.5 Supplementary services**

The supplementary services shall be supported as specified in GSM 02.04 (ETS 300 503) [16]. For information purposes the supplementary services in GSM 02.04 (ETS 300 503) [16] are reproduced in annex B.

#### **7.1.5.1 General requirements**

All supplementary services shall be provided and withdrawn by arrangement with the Operator.

The exchange of information between the GSM network and the DECT FP shall be according to the supplementary service handling, specified in GSM 03.11 (ETS 300 529) [17], GSM 04.10 (ETS 300 558) [18] and in the specific supplementary service GSM technical specifications.

The GSM MMI procedures as defined in GSM 02.30 (ETS 300 511) [5] shall be supported by the DECT PP using the keypad protocol to convey it to the DECT FP, as described in ETS 300 175-5 [40], subclause 10.2.

GSM network indications and notifications to the user shall be supported by the DECT FP using the DECT keypad protocol to convey it to the DECT PP.

#### **7.1.5.2 Exception handling**

Incorrect user action of a specific supplementary service shall not cause a misoperation in neither the GSM network, nor in the DECT FP or PP.

For supplementary services the GSM error handling as defined in GSM 03.11 (ETS 300 529) [17], GSM 04.10 (ETS 300 558) [18] and GSM 04.80 (ETS 300 564) [19] shall be supported.

#### **7.1.5.3 Number Identification Supplementary Services (NISS)**

These services shall be supported according to GSM 02.81 (ETS 300 514) [20].

#### **7.1.5.4 Call Offering Supplementary Services (COSS)**

These services shall be supported according to GSM 02.82 (ETS 300 515) [21].

#### **7.1.5.5 Call Completion Supplementary Services (CCSS)**

These services shall be supported according to GSM 02.83 (ETS 300 516) [22].

#### **7.1.5.6 Multi Party Supplementary Services (MPSS)**

These services shall be supported according to GSM 02.84 (ETS 300 517) [23].

#### **7.1.5.7 Community of Interest Supplementary Services (CISS)**

These services shall be supported according to GSM 02.85 (ETS 300 518) [24].

The MMI codes for these services are under preparation in an additional standard of the DECT/GSM IWP (see annex A).

#### **7.1.5.8 Charging Supplementary Services (CSS)**

The support of Advice of Charge Charging (AoCC) is outside the scope of this ETS.

NOTE: The PLMN will terminate any call set-up in case the subscriber has subscribed to AoCC and the PP does not support the functionality as required in GSM 02.86 (ETS 300 519) [25] and GSM 02.24 (ETS 300 510) [26].

The support of Advice of Charging Information (AoCI) is under preparation in an additional standard of the DECT/GSM IWP (see annex A).

#### **7.1.5.9 Call Restriction Supplementary Services (CRSS)**

These services according to GSM 02.88 (ETS 300 520) [27] shall be supported.

### **7.1.6 Unstructured Supplementary Services Data (USSD)**

USSD shall be supported as specified in GSM 02.90 (ETS 300 625) [52].

#### **7.1.6.1 Exception handling**

For USSD the GSM error handling as defined in GSM 04.10 (ETS 300 558) [18] and GSM 04.80 (ETS 300 564) [19] shall be supported.

## **7.2 Functional capabilities and information flows**

### **7.2.1 Supplementary services**

The supplementary services shall be supported as specified in GSM 03.11 (ETS 300 529) [17].

#### **7.2.1.1 General requirement**

The DECT FP shall terminate all GSM supplementary services transactions and is supposed to map those transactions to the specified ones for DECT. For this reason, all references to MS in GSM specifications mentioned below shall be applied to the FP instead.

The DECT FP shall convey all information designated for the served mobile user to the DECT PP.

The DECT FP shall convey all information from the DECT PP to the GSM network.

NOTE: The information flows of GSM stage 2 do not include the information exchange between the DECT FP and PP.

#### **7.2.1.2 Number Identification Supplementary Services (NISS)**

These services shall be supported according to GSM 03.81 (ETS 300 542) [28].

#### **7.2.1.3 Call Offering Supplementary Services (COSS)**

These services shall be supported according to GSM 03.82 (ETS 300 543) [29].

#### **7.2.1.4 Call Completion Supplementary Services (CCSS)**

These services shall be supported according to GSM 03.83 (ETS 300 544) [30].

#### **7.2.1.5 Multi Party Supplementary Services (MPSS)**

These services shall be supported according to GSM 03.84 (ETS 300 545) [31].

#### **7.2.1.6 Community of Interest Supplementary Services (CISS)**

These services shall be supported according to GSM 03.85 (ETS 300 546) [32].

#### **7.2.1.7 Call Restriction Supplementary Services (CRSS)**

These services shall be supported according to GSM 03.88 (ETS 300 548) [33].

#### **7.2.1.8 Charging Supplementary Services (CSS)**

These services shall be supported according to GSM 03.86 (ETS 300 547) [35]. For support of these services, see subclause 7.1.5.8.

### **7.2.2 Unstructured Supplementary Services Data (USSD)**

USSD shall be supported as specified in GSM 03.90 (ETS 300 549) [34].



### **7.2.3 Bearer services**

The support of bearer services is under preparation in an additional standard of the DECT/GSM IWP (see annex A).

### **7.2.4 Teleservices**

The support of telephony and emergency calls (GSM teleservices 11, 12) shall be supported as specified in the GSM 03-series of specifications. The interworking procedures and mappings shall meet the requirements of ETS 300 370 [44].

The support of facsimile services (GSM teleservices 61, 62) is under preparation in an additional standard of the DECT/GSM IWP (see annex A).

The support of short message services (GSM teleservices 21, 22, 23) is under preparation in an additional standard of the DECT/GSM IWP (see annex A).

## **8 Portable Part (PP) requirements**

### **8.1 General**

This clause is based on GSM 02.07 (ETS 300 505) [1], with the purpose of defining the PP features required for DECT/GSM interworking. They are also classified according to their type and whether support of them is mandatory or optional.

### **8.2 Description**

An PP feature is defined as a piece of equipment of function which directly relates to the operation of the PP. On this basis, three categories of features can be distinguished:

- basic features;
- supplementary features; and
- additional features.

#### **8.2.1 Basic PP features**

A basic PP feature is directly related to the operation of basic telecommunication services (e.g. key-pad function).

#### **8.2.2 Supplementary PP features**

A supplementary PP feature is directly related to the operation of supplementary services (e.g. display of calling line number).

#### **8.2.3 Additional PP features**

An additional PP feature is a feature which is neither a basic nor a supplementary feature (e.g. abbreviated dialling).

### **8.3 Requirements for implementing PP features**

PP features are qualified as mandatory or optional. Mandatory features shall be implemented as long as they are relevant to the PP type. The method of implementation of all PP features shall be done in accordance with this ETS. Any features additional to those specified in this subclause, shall not cause a mis-operation of the GSM network or DECT (FP, PP).

In tables 1 and 2, the basic, supplementary, and additional PP features are listed. Mandatory features are marked by "M", and optional features are marked by "O".

Additional PP features not listed in table 2 are permitted without the requirement for this table to be amended, provided that these new features do not affect the mandatory interworking requirements.

Unless otherwise stated for a particular feature, the feature supported by the SIM should take priority over the same feature supported by the PP.

### 8.3.1 Basic PP features

The basic PP features are given in table 1.

**Table 1: Basic PP features**

Item no	Name	Mandatory (M) Optional (O)	Note
1	Display of called number	M	1
2	Indication of call progress signals	M	
3	Country/PLMN indication and PLMN selection	M	1
4	Keypad	O	2
5	IMEI/IPEI	M	
6	International Access Function ("+")	M	2
7	Autocalling restriction capabilities	M	3
8	Emergency calls capabilities	M	
9	Subscription identity management	M	
10	Support of DECT encryption	M	
11	Support ERMES alphabet	M	
NOTE 1:	Mandatory where a human interface is provided, i.e. may be inappropriate for PP driven by external equipment.		
NOTE 2:	The physical means of entering the characters 0 - 9, +, * and # may be keypad, voice input device, DTE or others, but it is mandatory that there shall be the means to enter this information.		
NOTE 3:	PPs with capabilities for autocalling shall restrict repeated call attempts according to the procedures described in GSM 02.07 (ETS 300 505) [1].		

#### 8.3.1.1 Display of called number

This feature enables the caller to check before call set-up whether the selected number is correct.

#### 8.3.1.2 Indication of call progress signals

Indications shall be given such as tones, recorded messages or visual display based on signalling information returned from the PLMN.

Call progress indicators shall be supported as specified in GSM 02.40 (ETS 300 512) [2].

#### 8.3.1.3 Country/PLMN indication and PLMN selection

The country/PLMN indicator shows in which GSM PLMN the PP is currently registered.

The network selection procedures and access control classed in the PP, as defined in GSM 02.11 (ETS 300 507) [3] are not fully supported. The requirements in ETS 300 370 [44] however applies. The network selection procedures and access control classes in the PP, as defined in GSM 02.11 (ETS 300 507) [3] are not supported. The user shall have the opportunity to access alternative PLMNs (by re-initialising the locking sequence) and register to the preferred allowed PLMN.

#### 8.3.1.4 Keypad

A physical means of entering numbers, is not required as long as some means of entering "0 - 9", "\*", "# and "+" is provided.

**8.3.1.5 International Mobile station Equipment Identity (IMEI) and/or International Portable Equipment Identity (IPEI)**

The mapping between IPEI and IMEI as well as between IPEI and IMEISV is defined in ETS 300 370 [44].

**8.3.1.6 International access function**

Provision is made in GSM for a direct standard method of gaining international access. For this purpose the PP shall have a means of entering a "+" which shall be transmitted over the air interface and have the effect of generating the international access code in the GSM network. It may be used directly when setting up a call, or entered into the memory for abbreviated dialling.

Users may still place international calls conventionally, using the appropriate international access code.

**8.3.1.7 Autocalling restriction capabilities**

PPs with capabilities for autocalling shall restrict repeated call attempts according to the procedures described in GSM 02.07 (ETS 300 505) [1].

**8.3.1.8 Emergency calls capabilities**

The PP shall support emergency calls without the need for a SIM.

**8.3.1.9 Subscription identity management**

The removal of the SIM detaches the PP, causing a call in progress to be terminated, and preventing the initiation of further calls (except emergency calls).

**8.3.1.10 Support of DECT encryption**

The provision shall be made for support on the PP of no encryption, or support of encryption based on the DECT standard cipher. The DECT cipher key shall be derived from the GSM cipher key, Kc.

**8.3.1.11 Support of ERMES alphabet**

The PP shall be able to transmit, receive and display characters of the Latin alphabet no. 1 and the special character "ˆ" of the Greek alphabet, as specified in ISO 8859 [48].

**8.3.2 Supplementary/additional PP features**

The supplementary PP features are given in table 2.

**Table 2: Supplementary and additional MS features**

NAME	MANDATORY (M) OPTIONAL (O)
2.1 Control of supplementary services	M
2.2 Abbreviated dialling	O
2.3 Fixed number dialling	O
2.4 Selection of directory No in short messages	O
2.5 Last Numbers Dialed (LND)	O

**8.3.2.1 Support of supplementary services**

The user shall be able to control GSM supplementary services using the MMI codes as described in GSM 02.30 (ETS 300 511) [5].

**8.3.2.2 Abbreviated dialling**

If the PP supports abbreviated dialling, it shall be according to GSM 02.07 (ETS 300 505) [1].

### **8.3.2.3 Fixed number dialling**

If the PP supports fixed number dialling, it shall be according to GSM 02.07 (ETS 300 505) [1].

### **8.3.2.4 Last Numbers Dialed (LND)**

If the PP supports LND, it shall be according to GSM 02.07 (ETS 300 505) [1].

## **8.4 Man-Machine Interface (MMI) of the PP**

The purpose of this subclause is to define minimum requirements for MMI for the PP. This includes requirements of the user procedures for Call Control (CC), control of those supplementary services that are supported, and requirements for physical input and output media.

This subclause is based on specification GSM 02.30 (ETS 300 511) [5] and refers to the following GSM technical specifications:

- GSM 02.07 (ETS 300 505) [1];
- GSM 02.11 (ETS 300 507) [3];
- GSM 02.17 (ETS 300 509) [6];
- GSM 02.40 (ETS 300 512) [2];
- GSM 03.01 (ETS 300 521) [7];
- GSM 03.09 (ETS 300 527) [8];
- GSM 03.12 (ETS 300 530) [9];
- GSM 03.14 (ETS 300 532) [10];
- GSM 04.08 (ETS 300 557) [11];
- GSM 05.08 (ETS 300 578) [12];
- GSM 11.10 (ETS 300 607) [13].

### **8.4.1 Physical user input features**

GSM 02.30 (ETS 300 511) [5] specifies the minimum physical requirements for the support of GSM services and features. Where the service is supported in the FP and PP, then the same requirements, or equivalent, in GSM 02.30 (ETS 300 511) [5] shall be supported.

The following subclauses give additional information.

#### **8.4.1.1 MMI related to PP features**

ACCEPT, SEND and END functions:

- the physical means to perform these functions may be keypad, voice input device, DTE or other.

PP shall accept a "+" key in front of the dialled numbers for a call set-up.

#### **8.4.2 Physical output features**

Display that supports the ERMES alphabet.

#### **8.4.3 Support of Dual Tone Multi Frequency (DTMF)**

DTMF shall be supported using the DECT keypad protocol towards the FP.

#### **8.4.4 Procedures**

##### **8.4.4.1 Definition of functions**

The following functions are applicable and mandatory for the logical procedures for PP originated and terminated calls and for the control of supplementary services:

- ACCEPT: acceptance of a mobile terminated call;
- SELECT: entry of information;
- SEND: transmission of the entered information to the network;
- INDICATION: contains indications to the PP users to give them information regarding progress of their calls. Tones that are not generated by the PLMN shall be generated in the FP, except the Ringing Tone;
- END: termination of, or disconnection, from the call. The execution of the END-function may be caused by either party involved in the call by e.g. termination, loss of coverage, invalidation of payment.

##### **8.4.4.2 Call Control**

With the exception of emergency calls, no additional call control is required, in addition to that provided by the DECT specification.

With a PP supporting telephony, it shall be able to place an emergency call by entering 112 followed by SEND in the manner specified in GSM 02.30 (ETS 300 511) [5].

The PP shall support the initiation of an emergency call to the number 112 without a SIM-module present in the PP regardless of the call being accepted or not by the network.

NOTE: In addition to the above procedure, calls to national emergency services may be made in the standard way for the country of the serving PLMN. However, with the exception of code "112", these are not treated within the PLMN as "Teleservice Emergency call", and would require a valid IMSI.

#### **8.5 SIM interfaces**

The DECT PP shall accept IC or plug-in SIM as well as IC or plug-in DAM, with a GSM application.

The following subclauses define the minimum support required when a GSM SIM is inserted into a DECT PP.

The SIM functionality may be included in a standard SIM or a multi-application card supporting both, DAM and SIM functionality (i.e. DECT application and GSM application respectively). The user may select the DECT application or the GSM application of a multi-application card depending on the network attachment of the FP.

##### **8.5.1 Entry of PIN and PIN2**

According to GSM 02.30 (ETS 300 511) [5].

##### **8.5.2 Change of PIN or PIN2**

According to GSM 02.30 (ETS 300 511) [5].

##### **8.5.3 Unblocking of PIN or PIN2**

According to GSM 02.30 (ETS 300 511) [5].

#### 8.5.4 Status information - return codes

The SIM gives status information, as responses to instructions, in two-byte codes (see GSM 11.11 (ETS 300 608) [14], "Status Conditions Returned by the Card"). Some of the possible return codes are deeply related to the user's actions and should therefore be indicated to the user.

It is mandatory to give the user the appropriate indication (respectively) when the following codes appear:

Code	Description
92 40	memory problem (e.g. update impossible)
98 04	Access conditions not fulfilled (e.g. secret code verify rejected)
98 40	unsuccessful CHV verification, no attempt left (e.g. secret code locked)
6F XX	technical problem with no diagnostic given

The status information indication can be a dedicated lamp, text-string or others, as long as it is unambiguously made available to the user via the MMI.

As regards all other codes, it is left to the manufacturers' discretion whether, and how, the user shall be informed.

#### 8.6 Service access

The PLMN selection procedures and access control classes in the PP as defined in GSM 02.11 (ETS 300 507) [3] are not fully supported. The requirements in ETS 300 370 [44] however apply.

The user shall have the opportunity to access alternative PLMNs (by re-initializing the locking sequence) and register to the preferred allowed PLMN.

### 9 Fixed Part (FP) requirements

#### 9.1 Support of GSM Mobile Equipment Identity and Software Version number (IMEISV)

All IMEISV enquiry procedures according to the principles laid down in GSM 02.16 (ETS 300 508) [4] shall be supported by the FP.

#### 9.2 Support of MS classmark

For location registration purpose or call set-up the FP shall provide the following classmark information towards the PLMN:

- revision level: Phase 2 [or higher], Encryption A 5/1 is supported.

#### 9.3 Support of emergency call capability

On reception of a emergency call from the PP, the FP shall map it to a GSM emergency call towards the PLMN.

#### 9.4 Support of international access function

In GSM, two formats may be used, international or open. The Type of Number (TON) may be set to other values if required.

**international format:** This is entered by starting with a "+" followed by country code, even for national calls. Use of this function shall indicate a TON as "International" in the GSM network, see GSM 02.30 (ETS 300 511) [5] and GSM 04.08 (ETS 300 557) [11].

**open format:** This format shall result in the TON of "Unknown" to be indicated to the GSM network when the "+" is not entered, and the number is entered in the normal way for that network.

For PP originated calls on reception of "+" in front of a dialled number the FP shall map this type of number to "international format" towards the PLMN.

For PP originated calls on reception of a dialled number without "+" in front of this dialled number the FP shall map this type of number to "open format".

#### **9.5 Support of DTMF**

The PP shall use the keypad protocol for the transmission of DTMF towards the FP. The FP shall convert this received DTMF keypad information to the appropriate signalling format towards the PLMN.

#### **9.6 Support of ERMES alphabet**

The provision shall be made for the support of the ERMES alphabet, Latin alphabet no 1 and the special character "ˆ" of the Greek alphabet, as specified in ETS 300 133 [47] and ISO 8859 [48].

The FP shall be able to map ERMES characters received from the GSM PLMN into the corresponding 8 bit characters supported by the PP.

## **Annex A (normative): GSM teleservices and supplementary services**

For information, the teleservices in GSM 02.03 (ETS 300 502) [16] include the following:

- telephony (GSM teleservice 11);
- emergency calls (GSM teleservice 12);
- short message service mobile terminated point to point (GSM teleservice 21);
- short message service mobile originated point to point (GSM teleservice 22);
- short message service cell broadcast (GSM teleservice 23);
- alternate speech and facsimile group 3 (T/NT) (GSM teleservice 61);
- automatic facsimile group 3 (T/NT) (GSM teleservice 62).

For information, the supplementary services in GSM 02.04 (ETS 300 503) [16] include the following:

- Calling Line Identification Presentation, CLIP;
- Calling Line Identification Restriction, CLIR;
- Connected Line Identification Presentation, CoLP;
- Connected Line Identification Restriction, CoLR;
  
- Call Forwarding Unconditional, CFU;
- Call Forwarding on Mobile Subscriber Busy, CFB;
- Call Forwarding on No Reply, CFNRy;
- Call Forwarding on Mobile Subscriber Not Reachable, CFNRc;
  
- Call Waiting, CW;
- Call Hold, HOLD;
  
- Multi-Party Service, MPTY;
  
- Closed User Group, CUG;
  
- Advice of Charge Information, AoCI;
- Advice of Charge Charging, AUCC;
  
- Barring of All Outgoing Calls, BAOC;
- Barring of Outgoing International Calls, BOIC;
- Barring of Outgoing International Calls except those directed to the Home PLMN Country, BOIC-exHC;
- Barring of All Incoming Calls, BAIC;
- Barring of Incoming Calls when Roaming outside the Home PLMN Country, BIC-Roam.



## **Annex B (informative): Bibliography**

The references with ETSI work item numbers will be part of the normative references when the relevant documents are approved.

- (DE/RES-03057): "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications/Global System for Mobile Communications (DECT/GSM) Interworking profile, Implementation of Short message services, point to point and Cell broadcast".
- (DE/RES-03071): "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications/Global System for Mobile Communications (DECT/GSM) Interworking profile, Implementation of bearer services".
- (DE/RES-03072): "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications/Global System for Mobile Communications (DECT/GSM) Interworking profile, Implementation of facsimile group 3".
- ETR 015: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Reference document".
- ETR 043: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Common Interface (CI); Services and Facilities requirements specification".
- ETR 056: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); System description document".

## History

Document history			
January 1995	Public Enquiry	PE 77:	1995-01-16 to 1995-05-12
January 1996	Vote	V 96:	1996-01-08 to 1996-03-01