



EUROPEAN
TELECOMMUNICATION
STANDARD

FINAL DRAFT
pr **ETS 300 474-1**

May 1996

Source: ETSI TC-RES

Reference: DE/RES-03043-1

ICS: 33.020, 33.060.50

Key words: DECT, GAP, ICS

**Radio Equipment and Systems (RES);
Digital Enhanced Cordless Telecommunications (DECT);
Generic Access Profile (GAP);
Profile requirement list and profile specific
Implementation Conformance Statement (ICS) proforma;
Part 1: Portable radio Termination (PT)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

*

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1996. All rights reserved.

Contents

Foreword	5
1 Scope	7
2 Normative references	7
3 Definitions abbreviations	8
3.1 Definitions	8
3.2 Abbreviations	8
4 Conformance requirement concerning Profile ICS	8
Annex A (normative): Requirement lists for DECT PT	9
A.1 General	9
A.1.1 Profile Requirement List (profile RL)	9
A.1.2 General conditions	10
A.2 Network (NWK) layer - PT: Profile Requirement List (Profile RL)	10
A.2.1 Major capabilities	10
A.2.1.1 Entities	10
A.2.1.2 CC features	10
A.2.1.3 MM features	12
A.2.1.4 SS features (services)	13
A.2.1.5 LCE features	14
A.2.1.6 Procedures	14
A.2.2 Messages	16
A.2.2.1 Call control messages	16
A.2.2.2 MM messages	22
A.2.2.3 CRSS and CISS messages	27
A.2.2.4 Link Control Entity (LCE) messages	27
A.2.3 Information elements	28
A.2.3.1 Fixed length information element support	28
A.2.3.2 Variable length information element supported	29
A.2.3.3 Escape information elements support	34
A.2.4 Protocol error handling	34
A.3 Data Link Control (DLC) layer - PT: Profile ICS	34
A.3.1 Capabilities	34
A.3.3.1 Services	34
A.3.3.1.1 C-plane services	34
A.3.3.1.2 U-plane services	35
A.3.3.1.2 Management services	35
A.3.3.2 Procedures	35
A.3.3.2.1 Generic signalling procedures	35
A.3.3.2.2 Class A procedures	36
A.3.3.2.3 Broadcast procedures	36
A.3.3.2.4 LU1 procedures	36
A.3.3.2.5 Management procedures	37
A.3.3.3 Parameters	37
A.3.3.3.1 LU1 parameters	37
A.3.3.4 Messages	37
A.3.3.4.1 C-plane PDUs	37
A.4 Medium Access Control (MAC) layer - PT: Profile ICS	38
A.4.1 Major Capabilities	38

A.4.1.1	Services	38
A.4.3.1.1	Connection oriented control services.....	38
A.4.1.1.2	Broadcast control services.....	39
A.4.1.1.3	Multiplexing services.....	39
A.4.1.1.4	Management services.....	40
A.4.1.2	Procedures	40
A.4.1.2.1	Connection setup procedures.....	40
A.4.1.2.2	Connection data transfer procedures.....	41
A.4.1.2.3	Connection handover procedures.....	41
A.4.1.2.4	Connection release procedures.....	41
A.4.1.2.5	Broadcast procedures.....	41
A.4.1.2.6	CSF multiplexing procedures.....	41
A.4.1.2.7	Layer management procedures.....	42
A.4.1.3	Other capabilities.....	42
A.4.2	Messages.....	42
A.4.2.1	A - Field	43
A.4.2.1.1	A - field header - B-field identification	43
A.4.2.2	A - Field Messages.....	43
A.4.2.2.1	Paging tail messages supported.....	43
A.4.2.2.2	PT messages information type	44
A.4.2.2.3	MAC control messages supported.....	44
A.4.2.2.4	Broadcast and connectionless (BCL) messages.....	45
A.5	Physical (PHL) layer - PT: Profile ICS	45
A.5.1	Physical layer procedures	45
Annex B (normative):	GAP Profile-specific ICS proforma for PT	46
B.1	Introduction for completing the Profile-specific ICS proforma	46
B.1.1	Purposes and structure	46
B.1.3	Instructions for completing the Profile specific ICS proforma	48
B.2	Identification of the implementation	48
B.2.1	Date of statement.....	48
B.2.2	Implementation Under Test (IUT) identification	48
B.2.3	System Under Test (SUT) identification.....	48
B.2.4	Product supplier	49
B.2.5	Client identification	49
B.2.6	Contact person identification.....	49
B.3	Identification of the protocol.....	50
B.3.1	Defect report numbers and amendments implemented.....	50
B.3.2	Addenda implemented	50
B.4	Global statement of conformance	50
B.5	Capabilities	51
B.5.1	NWK Profile-specific ICS proforma for PT.....	51
B.5.1.1	General requirements.....	51
B.5.1.2	Application features	51
B.5.1.3	Application Procedures.....	51
B.5.1.4	Management procedures.....	51
B.5.2	DLC Profile-specific ICS proforma for PT	52
B.5.3	MAC Profile-specific ICS proforma for PT	52
B.5.3.1	Services	52
B.5.3.1.2	Extended frequency allocation service.....	52
B.5.4	PH Profile-specific ICS proforma for PT	52
B.5.4.1	Requirements	52
History	53

Foreword

This final draft European Telecommunication Standard (ETS) has been produced by the Radio Equipment and Systems (RES) Technical Committee of the European Telecommunications Standards Institute (ETSI), and is now submitted for the Voting phase of the ETSI standards approval procedure.

The DECT Generic Access Profile (GAP) Profile requirement list and profile specific Implementation Conformance Statement (ICS) proforma standard comprises two parts as follows:

Part 1: "Portable radio Termination (PT)".

Part 2: "Fixed radio Termination (FT)".

Annex A contains the requirement lists for the Portable radio Termination (PT) Generic Access Profile.

Annex B contains the Profile specific ICS proforma for the PT Generic Access Profile.

Proposed transposition dates	
Date of latest announcement of this ETS (doa):	3 months after ETSI publication
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Blank page

1 Scope

This final draft European Telecommunication Standard (ETS) provides the Profile Requirement List and Profile specific Implementation Conformance Statement (Profile ICS) proforma for the Digital Enhanced Cordless Telecommunications (DECT) Generic Access Profile (GAP) at the Portable radio Termination (PT) as defined in ETS 300 444 [1] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [7].

The supplier of an implementation which is claimed to conform to ETS 300 444 [1] is required to complete a copy of the Protocol Implementation Conformance Statement (PICS) proforma ETS 300 476 parts 1, 2, 3 and 7 [2], [3], [4] and [5] with the replacements from annex A of this ETS, as well as, a copy of the and profile specific ICS proforma provided in annex B of this ETS.

2 Normative references

This ETS incorporates, by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- [1] ETS 300 444: "Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Generic Access Profile (GAP)".
- [2] prETS 300 476-1: "Radio Equipment and Systems (RES); Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Protocol Implementation Conformance Statement (PICS); Part 1: Network (NWK) layer - Portable radio Termination (PT)".
- [3] prETS 300 476-2: "Radio Equipment and Systems (RES); Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Protocol Implementation Conformance Statement (PICS); Part 2: Data Link Control (DCL) layer - Portable radio Termination (PT)".
- [4] prETS 300 476-3: "Radio Equipment and Systems (RES); Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Protocol Implementation Conformance Statement (PICS); Part 3: Medium Access Control (MAC) layer - Portable radio Termination (PT)".
- [5] prETS 300 476-7: "Radio Equipment and Systems (RES); Digital Enhanced Cordless Telecommunications (DECT); Common Interface (CI); Protocol Implementation Conformance Statement (PICS); Part 7: Physical (PHL) layer".
- [6] ISO/IEC 9646-1 (1995): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework -Part 1: General concepts". (See also X.290 (1991)).
- [7] ISO/IEC 9646-7 (1995): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".

3 Definitions abbreviations

3.1 Definitions

For the purposes of this ETS, the following terms and definitions apply:

- a) the terms defined in ISO/IEC 9646-7 [7];
- b) the definitions in ETS 300 444 [1]; and
- c) the following terms defined in ISO/IEC 9646-1 [6]:
 - PICS proforma;
 - Profile Implementation Conformance Statement (Profile ICS).

3.2 Abbreviations

For the purposes of this ETS, the abbreviations defined in ISO/IEC 9646-1 [6], the abbreviations defined in ETS 300 444 [1] apply.

4 Conformance requirement concerning Profile ICS

The supplier of a protocol implementation which is claimed to conform to the portable termination specific requirements of ETS 300 444 [1] shall verify that his protocol implementation meets the profile Requirements Lists (RLs) for each DECT protocol layer, contained in annex A of this standard, and shall complete a copy of the Profile specific ICS proforma provided in annex B and shall provide the information necessary to identify both the supplier and the implementation.

Annex A (normative): Requirement lists for DECT PT

A.1 General

The supplier of a protocol implementation which is claimed to conform to the portable termination specific requirements of ETS 300 444 [1] shall verify that his particular Network (NWK), Data Link Control (DLC), Medium Access Control (MAC) and PHL layer protocol implementation meets the profile RL for this layer. For this, he shall complete a copy of the corresponding layer PICS proforma contained in annex A of ETS 300 476 Parts 1, 2, 3 and 7 [2], [3], [4] and [5] updated with the requirements from this annex.

A.1.1 Profile Requirement List (profile RL)

The profile Requirement List (profile RL) for the NWK, DLC, MAC and PHL layers as defined in this annex is based on ETS 300 476 Parts 1, 2, 3 and 7 [2], [3], [4] and [5]. For every capability listed in ETS 300 476 Parts 1, 2, 3 and 7 [2], [3], [4] and [5], the profile requirements are expressed by restriction upon allowed support answers in ETS 300 476 Parts 1, 2, 3 and 7 [2], [3], [4] and [5]. The profile RL is produced by copying selected tables from ETS 300 476 Parts 1, 2, 3 and 7 [2], [3], [4] and [5], removing the column(s) to be completed by the supplier, and adding a new set of columns giving the new profile requirements, both in terms of the status and allowed values. The tables are referenced by preceding it with ETS 300 476 Parts "[2]", "[3]", or "[4]" as relevant.

Profile status column

The standardised symbols for the status column are as follows:

m or M	mandatory - the capability is required to be supported;
o or O	optional - the capability may be supported or not;
n/a or N/A	not applicable - in the given context, it is impossible to use the capability;
x or X	prohibited (excluded) - there is a requirement not to use this capability in the given context;
o.i or O.i	qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table;
ci or Ci	conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table or which is defined in the general condition table below;
i or I	out-of-scope - this capability is outside the scope of the given specification, and hence irrelevant and not subject to conformance testing. This status is in particular applicable for data fields which are reserved for future use. The structure of such fields has to be supported, but the value is undefined and thus to be ignored.

Reference column

The reference column gives reference to ETS 300 444 [1], except where explicitly stated otherwise.

A.1.2 General conditions

Table A.1:General condition table

Condition identifier	Condition definition
c01	IF A.7/41 THEN m ELSE i
NOTE A:	The status of the relevant item is exactly as the status of this item in ETS 300 476 Parts 1, 2, 3 and 7 [2], [3], [4] and [5]. The item has been included as the Profile reference column include reference to the profile that describes the item more in details.

A.2 Network (NWK) layer - PT: Profile Requirement List (Profile RL)

A.2.1 Major capabilities

A.2.1.1 Entities

To express the profile requirements of ETS 300 444 [1], the following table A.2 indicates the change of status for support of entities.

Table A.2: ETS 300 476-1 [2] Table A.12 Entity supported

Item	Entity name	Profile reference	Profile status
1	Call Control (CC)	6.2	m
2	Call Independent Supplementary Services (CISS)	-	i
3	Connection Oriented Message Services (COMS)	-	i
4	ConnectionLess Message Services (CLMS)	-	i
5	Mobility Management (MM)	6.2	m
6	Link Control Entity (LCE)	6.2	m
7	Management (LLME)	13	m

A.2.1.2 CC features

To express the profile requirements of ETS 300 444 [1], the following table A.3 indicates the change of status for support of features.

Table A.3: ETS 300 476-1 [2] Table A.13 CC features supported

Item	Feature name	Profile reference	Profile status
1	Bell off (Alerting)	6.2	m
2	Bell on (Alerting)	6.2	m
3	Control of supervisory tones	-	i
4	Dial tone detection indication	-	i
5	Dialled digits (basic)	6.2	m
6	Dialled digits additional	-	i
7	Dialling delimiter	-	i
8	Dialling delimiter request	-	i
9	Display control characters	6.2	o
10	Emergency service access request	-	i
11	External Handover (inter-cell)	-	i
12	Fixed part/portable part capability exchange	-	i
13	Go to DTMF (infinite tone length)	6.2	o
14	Go to DTMF signalling (defined tone length)	6.2	m
15	Go to Pulse	6.2	o
16	Group address	-	i
17	Incoming call	6.2	m
18	Internal call	6.2	o
19	Off hook	6.2	m
20	On hook (full release)	6.2	m
21	Outgoing call	6.2	m
22	Packet mode	-	i
23	Partial release	6.2	o
24	Pause (dialling pause)	6.2	m
25	Register recall	6.2	m
26	Signalling of display characters	6.2	o
27	Selection of bearer service	-	i
28	Service call	6.2	o
29	Service change	-	i

A.2.1.3 MM features

To express the profile requirements of ETS 300 444 [1], the following table A.4 indicates the change of status for support of MM features.

Table A.4: ETS 300 476-1 [2] Table A.14 MM features supported

Item	Feature name	Prof. ref.	Prof. status
1	Authentication of FT	6.2	o
2	Authentication of PT	6.2	m
3	Authentication of user	6.2	m
4	Encryption activation FT initiated	6.2	m
5	Encryption activation PT initiated	6.2	o
6	Encryption deactivation FT initiated	6.2	o
7	Encryption deactivation PT initiated	6.2	o
8	Identification of PP	6.2	m
9	Inter-operator roaming registration	-	i
10	Location de-registration	-	i
11	Location registration	6.2	m
12	Multiple subscription registration	6.6	m
13	On air key allocation	6.2	m
14	Service class indication/assignment	6.2	m
15	Silent polling	-	i
16	Subscription registration procedure on-air	6.2	m
17	Subscription registration user procedure with DECT authentication module	-	i
18	Subscription registration user procedures keypad (digit entry only)	-	i
19	Terminate access rights FT initiated	6.2	m
20	Terminate access rights PT initiated	-	i
21	ZAP	6.2	m
22	MM Partial release (Link control)	6.2	m
23	Temporary identity assign	-	i

A.2.1.4 SS features (services)

To express the profile requirements of ETS 300 444 [1], the following table A.5 indicates the change of status for support of supplementary services.

Table A.5: ETS 300 476-1 [2] Table A.15 SS features (services) supported

Item	Feature name	Prof. ref.	Prof. status
1	Advice of charge (AOC)	-	i
2	Advice of tariff request	-	i
3	Call Deflection (CD)	-	i
4	Call Forwarding Busy (CFB)	-	i
5	Call Forwarding No Reply (CFNR)	-	i
6	Call Forwarding Unconditional (CFU)	-	i
7	Call Waiting (CW)	-	i
8	Calling Line Identification Presentation (CLIP)	6.2	o
9	Calling Line Identification Restriction (CLIR)	-	i
10	Closed User Group (CUG)	-	i
11	Completion of Calls to Busy Subscriber (CCBS)	-	i
12	Call HOLD (HOLD)	-	i
13	CONference call add-on (CONF)	-	i
14	COConnected Line identification Presentation (COLP)	-	i
15	COConnected Line identification Restriction (COLR)	-	i
16	Control of echo control functions	-	i
17	Cost information	-	i
18	Credit agency public access service	-	i
19	Credit public access service	-	i
20	Debit public access service	-	i
21	Direct Dialling In (DDI)	-	i
22	Explicit Call Transfer (ECT)	-	i
23	Forced re-connection of held call	-	i
24	FreePHone (FPH)	-	i
25	Hold call (FT to PT)	-	i
26	Hold call (PT to FT)	-	i
27	Indication of teleservice available request	-	i
28	Indication of teleservices available	-	i
29	Malicious Call Identification (MCID)	-	i
30	Multiple Subscriber Number (MSN)	-	i
31	On-demand (hot bill) public access service- CRSS	-	i
32	Queue management	-	i
33	Re-connection of held call (FT to PT)	-	i
34	Re-connection of held call (PT to FT)	-	i
35	Request for indication of temporary subscriber number- CRSS	-	i
36	Selection of required teleservice	-	i
37	Single step Call Transfer (SCT)	-	i
38	Specific trunk carrier selection	-	i
39	SUBaddressing (SUB)	-	i
40	Terminal Portability (TP)	-	i
41	Tree ParTY (3TPY)	-	i
42	User to User Signalling UUS	-	i
43	CISS Partial release	-	i
44	Feature key	-	i
45	Indication of subscriber number	-	i
46	Register recall	-	i
47	Specific line selection	-	i
48	External handover switch	-	i

A.2.1.5 LCE features

To express the profile requirements of ETS 300 444 [1], table A.6 indicates the change of status for support of LCE features.

Table A.6: ETS 300 476-1 [2] Table A.16 LCE features supported

Item	Feature name	Profile reference	Profile status
1	Connection oriented Link control (Link control)	6.2	m
2	Connectionless oriented Link control	-	i

A.2.1.6 Procedures

To express the profile requirements of ETS 300 444 [1], table A.7 to A.11 indicates the change of status for support of the procedures.

Table A.7: ETS 300 476-1 [2] Table A.18 CC procedures supported

Item	Procedure name	Profile reference	Profile status
1	cc_outgoing_normal_call_request	8.2	m
4	cc_outgoing_selection_of_lower_layer_resources	-	i
5	cc_outgoing_connection_of_U_plane	8.3, 8.4, 8.5, 8.6	m
6	cc_outgoing_overlap_sending	8.3	m
7	cc_outgoing_call_proceeding	8.4	m
8	cc_outgoing_call_confirmation	8.5	m
9	cc_outgoing_call_connection	8.6	m
10	cc_incoming_call_request	8.12	m
11	cc_incoming_selection_of_lower_layer_resources	-	i
12	cc_incoming_connection_of_U_plane	8.15	m
13	cc_incoming_overlap_receiving	-	i
14	cc_incoming_call_proceeding	-	i
15	cc_incoming_call_confirmation	8.13	m
16	cc_incoming_call_connection	8.15	m
17	cc_sending_terminal_capability	-	i
18	cc_sending_keypad_info	8.10	m
19	cc_call_information	8.10	m
20	cc_normal_call_release	8.7	m
21	cc_partial_release	8.9	note A
22	cc_abnormal_call_release	8.8	m
23	cc_release_collisions	8.7.2.1	m
31	cc_timer_p_cc_02_mgt	8.7	m
32	cc_timer_p_cc_03_mgt	8.2	m
33	cc_timer_p_cc_04_mgt	-	i
34	cc_timer_p_cc_05_mgt	8.15	m
35	cc_internal_call_setup	8.18	note A
36	cc_service_call_setup	8.20	note A
38	cc_service_call_keypad	8.21	note A
39	cc_internal_call_keypad	8.19	note A
40	pt_alerting	8.14	m
41	display	8.16	note A

Table A.8: ETS 300 476-1 [2] Table A.19 MM procedures supported

Item	Procedure name	Profile reference	Profile status
1	mm_identification_of_pt	8.22	m
2	mm_temporary_identity_assignment	-	i
3	mm_authentication_of_pt	8.24	m
4	mm_authentication_of_user	8.25	m
5	mm_authentication_of_ft	8.23	note A
6	mm_location_registration	8.28	m
8	mm_location_update	8.29	m
9	mm_obtain_access_rights	8.30	m
10	mm_pt_init_terminate_access_rights	-	i
11	mm_ft_init_terminate_access_rights	8.31	m
12	mm_key_allocation	8.32	m
13	mm_pt_init_parameter_retrieval	-	i
14	mm_ft_init_parameter_retrieval	-	i
15	mm_pt_init_cipher_switching	8.34	note A
16	mm_ft_init_cipher_switching	8.33	m
17	mm_zap_increment	8.26	m
18	mm_dck_storing	8.27	m
19	mm_dck_sending	-	i
20	mm_service_class_mgt	8.30, 8.24	m
21	mm_partial_release	8.39	m
23	mm_timer_p_mm_access_1_mgt	8.30.1.1	m
24	mm_timer_p_mm_access_2_mgt	-	i
25	mm_timer_p_mm_auth_1_mgt	8.32.1.2	m
26	mm_timer_p_mm_cipher_2_mgt	8.34.1.1	note A
27	mm_timer_p_mm_locate_1_mgt	8.28.1.1	m
28	mm_timer_p_mm_wait_mgt	-	i

Table A.9: ETS 300 476-1 [2] Table A.20 SS protocols supported

Item	SS protocol name	Profile reference	Profile status
1	crss_keypad_protocol	8.10	m
2	crss_feature_key_mgt_protocol	-	i
3	crss_functional_protocol_smc	-	i
4	ciss_keypad_protocol	-	i
5	ciss_feature_key_mgt_protocol	-	i
6	ciss_partial_release	-	i
7	crss_functional_protocol_ciec	-	i
8	ciss_functional_protocol_ciec	-	i

Table A.10: ETS 300 476-1 [2] Table A.23 LCE procedures supported

Item	Procedure name	Profile reference	Profile status
1	lce_direct_pt_init_link_establishment	8.36	m
2	lce_indirect_ft_init_link_establishment	8.35	m
3	lce_direct_ft_init_link_establishment	-	i
5	lce_link_suspend	-	i
6	lce_link_resume	-	i
7	lce_link_release	8.37, 8.38	m
8	lce_link_partial_release	8.39	m
9	lce_cl_message_routing	-	i
10	lce_cl_broadcast_announce	-	i
11	lce_timer_lce_01_mgt	8.37.1.1	m
12	lce_timer_lce_02_mgt	8.39.1.1	m
13	lce_timer_lce_04_mgt	-	i

Table A.11: ETS 300 476-1 [2] Table A.24 LLME procedures supported

Item	Procedure name	Profile reference	Profile status
1	mgt_prioritised_list_negotiation	-	i
2	mgt_exchanged_attribute_negotiation	-	i
3	mgt_operating_parameter_negotiation	-	i
4	mgt_service_modification	-	i
5	mgt_mm_procedures_priority_mgt	13.1	m
6	mgt_mm_cc_coexistence	6.9.6	m
7	mgt_mm_coms_coexistence	-	i
9	mgt_external_handover	-	i
10	mgt_test_call_back	-	i
11	mgt_test_hook_control	-	i
12	mgt_upper_tester	-	i

A.2.2 Messages

To express the profile requirements of ETS 300 444 [1], tables A.12 to A.29 indicate the change of status for support of messages.

A.2.2.1 Call control messages

Table A.12: ETS 300 476-1 [2] Table A.25 CC sending (P to F) messages supported

Item	CC sending (P to F) Message name	Profile reference	Profile status
1	CC-SETUP	8.2	m
2	CC-INFORMATION	8.10	m
5	CC-ALERTING	8.13	m
6	CC-CONNECT	8.15	m
8	CC-RELEASE	8.7, 8.9	m
9	CC-RELEASE-COMplete	8.7, 8.8	m
14	IWU-INFORMATION	-	i

Table A.13: ETS 300 476-1 [2] Table A.26 CC receiving (F to P) messages supported

Item	CC receiving (F to P) Message name	Profile reference	Profile status
1	CC-SETUP	8.2	m
2	CC-INFORMATION	8.16	m
3	CC-SETUP-ACKnowledge	8.3	m
4	CC-CALL-PROceeding	8.4	m
5	CC-ALERTING	8.5	m
6	CC-CONNECT	8.6	m
7	CC-CONNECT-ACKnowledge	8.15	m
8	CC-RELEASE	8.7, 8.9	m
9	CC-RELEASE-COMplete	8.7, 8.8	m
13	CC-NOTIFY	6.9.6	m
14	IWU-INFORMATION	-	i

Table A.14: ETS 300 476-1 [2] Table A.27 CC-SETUP sending (P to F) supported

Item	CC-SETUP sending (P to F) Information element name	Profile reference	Profile status
5	IWU attributes	-	i
6	Repeat indicator "prioritised list"	-	i
7	Call attributes 1	-	i
8	Call attributes 2	-	i
9	Call attributes 3	-	i
10	Repeat indicator "prioritised list"	-	i
11	Connection attributes 1	-	i
12	Connection attributes 2	-	i
13	Connection attributes 3	-	i
14	Cipher info	-	i
15	Connection identity	-	i
16	Facility	-	i
19	Keypad	-	i
21	Feature Activate	-	i
23	Network parameter	-	i
24	Terminal capability	-	i
25	End-to-end compatibility	-	i
26	Rate parameters	-	i
27	Transit delay	-	i
28	Window size	-	i
29	Calling party number	-	i
30	Called party number	-	i
31	Called party subaddress	-	i
32	Sending complete	-	i
33	IWU-to-IWU	-	i
34	IWU-PACKET	-	i

Table A.15: ETS 300 476-1 [2] Table A.28 CC-SETUP receiving (F to P) supported

Item	CC-SETUP receiving (F to P) Information element name	Profile reference	Profile status
5	IWU attributes	-	i
6	Repeat indicator "prioritised list"	-	i
7	Call attributes 1	-	i
8	Call attributes 2	-	i
9	Call attributes 3	-	i
10	Repeat indicator "prioritised list"	-	i
11	Connection attributes 1	-	i
12	Connection attributes 2	-	i
13	Connection attributes 3	-	i
14	Cipher info	-	i
15	Connection identity	-	i
16	Facility	-	i
17	Progress Indicator	-	i
18	Display	8.16	c01
20	Signal	8.14	m
22	Feature Indicate	-	i
25	End-to-end compatibility	-	i
26	Rate parameters	-	i
27	Transit delay	-	i
28	Window size	-	i
29	Calling party number	-	i
30	Called party number	-	i
31	Called party subaddress	-	i
32	Sending complete	-	i
33	IWU-to-IWU	-	i
34	IWU-PACKET	-	i

Table A.16: ETS 300 476-1 [2] Table A.29 CC-INFO sending (P to F) supported

Item	CC-INFO sending (P to F) Information element name	Profile reference	Profile status
2	Location area	-	i
3	NWK assigned identity	-	i
4	Facility	-	i
7	Keypad	8.10	m
9	Feature activate	-	i
11	Network parameter	-	i
12	Called party number	-	i
13	Called party subaddress	-	i
14	Sending complete	-	i
16	IWU-to-IWU	-	i
17	IWU-packet	-	i

Table A.17: ETS 300 476-1 [2] Table A.30 CC-INFO receiving (F to P) supported

Item	CC-INFO receiving (F to P) Information element name	Profile reference	Profile status
4	Facility	-	i
5	Progress Indicator	-	i
6	Display	8.16	c01
8	Signal	8.14	m
10	Feature indicate	-	i
12	Called party number	-	i
13	Called party subaddress	-	i
14	Sending complete	-	i
15	Test hook control	-	i
16	IWU-to-IWU	-	i
17	IWU-packet	-	i

Table A.18: ETS 300 476-1 [2] Table A.31 CC-SETUP-ACK receiving (F to P) supported

Item	CC-SETUP-ACK receiving (F to P) Information element name	Profile reference	Profile status
2	Info type	-	i
3	Portable identity	-	i
4	Fixed identity	-	i
5	Location area	-	i
6	Call attributes	-	i
7	Connection identity	-	i
8	Facility	-	i
9	Progress indicator	8.3	m
10	Display	8.16	c01
11	Signal	-	i
12	Feature indicate	-	i
13	Transit delay	-	i
14	Window size	-	i
15	Delimiter request	-	i

Table A.19: ETS 300 476-1 [2] Table A.32 CC-CALL-PROC receiving (F to P) supported

Item	CC-CALL-PROC receiving (F to P) Information element name	Profile reference	Profile status
2	Call attributes	-	i
3	Connection identity	-	i
4	Facility	-	i
5	Progress indicator	8.4	m
6	Display	8.16	c01
7	Signal	-	i
8	Feature indicate	-	i
9	Transit delay	-	i
10	Window size	-	i
11	IWU-to-IWU	-	i
12	IWU-PACKET	-	i

Table A.20: ETS 300 476-1 [2] Table A.33 CC-ALERTING sending (P to F) supported

Item	CC-ALERTING sending (P to F) Information element name	Profile reference	Profile status
2	Call attributes	-	i
3	Connection identity	-	i
9	Terminal capability	-	i
10	Transit delay	-	i
11	Window size	-	i
12	IWU-to-IWU	-	i
13	IWU-PACKET	-	i

Table A.21: ETS 300 476-1 [2] Table A.34 CC-ALERTING receiving (F to P) supported

Item	CC-ALERTING receiving (F to P) Information element name	Profile reference	Profile status
2	Call attributes	-	i
3	Connection identity	-	i
4	Facility	-	i
5	Progress Indicator	8.4	m
6	Display	8.16	c01
7	Signal	-	i
8	Feature indicate	-	i
10	Transit delay	-	i
11	Window size	-	i
12	IWU-to-IWU	-	i
13	IWU-PACKET	-	i

Table A.22: ETS 300 476-1 [2] Table A.35 CC-CONNECT sending (P to F) supported

Item	CC-CONNECT sending (P to F) Information element name	Profile reference	Profile status
2	Call attributes	-	i
3	Connection identity	-	i
4	Facility	-	i
9	Terminal capability	-	i
10	Transit delay	-	i
11	Window size	-	i
12	IWU-to-IWU	-	i
13	IWU-PACKET	-	i

Table A.23: ETS 300 476-1 [2] Table A.36 CC-CONNECT receiving (F to P) supported

Item	CC-CONNECT receiving (F to P) Information element name	Profile reference	Profile status
2	Call attributes	-	i
3	Connection identity	-	i
4	Facility	-	i
5	Progress indicator	-	i
6	Display	8.16	c01
7	Signal	-	i
8	Feature indicate	-	i
10	Transit delay	-	i
11	Window size	-	i
12	IWU-to-IWU	-	i
13	IWU-PACKET	-	i

Table A.24: ETS 300 476-1 [2] Table A.37 CC-CONNECT-ACK receiving (F to P) supported

Item	CC-CONNECT-ACK receiving (F to P) Information element name	Profile reference	Profile status
2	Display	8.16	c01
3	Feature indicate	-	i
4	IWU-to-IWU	-	i
5	IWU-PACKET	-	i

Table A.25: ETS 300 476-1 [2] Table A.38 CC-RELEASE sending (P to F) supported

Item	CC-RELEASE sending (P to F) Information element name	Profile reference	Profile status
2	Release reason	8.9	cp2501
6	IWU-to-IWU	-	i
7	IWU-PACKET	-	i

cp2501: IF A.7/21 THEN m ELSE i.

Table A.26: ETS 300 476-1 [2] Table A.39 CC-RELEASE receiving (F to P) supported

Item	CC-RELEASE receiving (F to P) Information element name	Profile reference	Profile status
2	Release reason	8.9	cp2601
3	Facility	-	i
4	Display	8.16	c01
5	Feature indicate	-	i
6	IWU-to-IWU	-	i
7	IWU-PACKET	-	i

cp2601: IF A.7/21 THEN m ELSE i.

Table A.27: ETS 300 476-1 [2] Table A.40 CC-RELEASE-COM sending (P to F) supported

Item	CC-RELEASE-COM sending (P to F) Information element name	Profile reference	Profile status
2	Release reason	8.9	cp2701
5	IWU attributes	-	i
10	IWU-to-IWU	-	i
11	IWU-PACKET	-	i

cp2701: IF A.7/21 THEN m ELSE i.

Table A.28: ETS 300 476-1 [2] Table A.41 CC-RELEASE-COM receiving (F to P) supported

Item	CC-RELEASE-COM receiving (F to P) Information element name	Profile reference	Profile status
2	Release reason	8.9	cp2801
3	Identity type	-	i
4	Location area	-	i
5	IWU attributes	-	i
6	Facility	-	i
7	Display	8.16	c01
8	Feature indicate	-	i
9	Network parameter	-	i
10	IWU-to-IWU	-	i
11	IWU-PACKET	-	i

cp2801: IF A.7/21 THEN m ELSE i.

Table A.29: ETS 300 476-1 [2] Table A.48 CC-NOTIFY receiving (F to P) supported

Item	CC-NOTIFY receiving (F to P) Information element name	Profile reference	Profile status
2	Timer restart	6.9.6	m

A.2.2.2 MM messages

Table A.30: ETS 300 476-1 [2] Table A.51 MM message sending (P to F) supported

Item	MM message sending (P to F) Information element name	Profile reference	Profile status
3	ACCESS-RIGHTS-REQUEST	8.30	m
4	ACCESS-RIGHTS-TERMINATE-ACCEPT	8.31	m
5	ACCESS-RIGHTS-TERMINATE-REJECT	8.31.2.1	m
6	ACCESS-RIGHTS-TERMINATE-REQUEST	-	i
7	AUTHENTICATION-REJECT	8.23.2.1, 8.32.2.4	m
8	AUTHENTICATION-REPLY	8.24, 8.25	m
9	AUTHENTICATION-REQUEST	8.32, 8.23	m
10	CIPHER-REJECT	8.33.2.1	m
12	CIPHER-SUGGEST	8.34	note A
13	DETACH	-	i
14	IDENTITY-REPLY	8.22	m
19	LOCATE-REQUEST	8.28	m
22	MM-INFO-REQUEST	-	i
25	TEMPORARY-IDENTITY-ASSIGN-ACKNOWLEDGE	8.28	m
26	TEMPORARY-IDENTITY-ASSIGN-REJECT	8.28.2.3	m

Table A.31: ETS 300 476-1 [2] Table A.52 MM message receiving (F to P) supported

Item	MM message receiving (F to P) Information element name	Profile reference	Profile status
1	ACCESS-RIGHTS-ACCEPT	8.30	m
2	ACCESS-RIGHTS-REJECT	8.30.2.1	m
4	ACCESS-RIGHTS-TERMINATE-ACCEPT	-	i
5	ACCESS-RIGHTS-TERMINATE-REJECT	-	i
6	ACCESS-RIGHTS-TERMINATE-REQUEST	8.31	m
7	AUTHENTICATE-REJECT	8.32.2.3, 8.23.2.1	m
8	AUTHENTICATE-REPLY	8.23, 8.32	m
9	AUTHENTICATE-REQUEST	8.24, 8.25, 8.26, 8.27	m
10	CIPHER-REJECT	8.34.2.1	m
11	CIPHER-REQUEST	8.33	m
15	IDENTITY-REQUEST	8.22	m
16	KEY-ALLOCATE	8.32	m
17	LOCATE-ACCEPT	8.28	m
18	LOCATE-REJECT	8.28.2.1	m
20	MM-INFO-ACCEPT	-	i
21	MM-INFO-REJECT	-	i
23	MM-INFO-SUGGEST	8.29	m
24	TEMPORARY-IDENTITY-ASSIGN	-	i

Table A.32: ETS 300 476-1 [2] Table A.53 ACCESS-RIGHTS-ACCEPT receiving (F to P) supported

Item	ACCESS-RIGHTS-ACCEPT receiving (F to P) Information element name	Profile reference	Profile status
3	Repeat indicator "non-prioritised"	-	i
5	Fixed identity (PARK) 2	-	i
6	Fixed identity (PARK) 3	-	i
7	Fixed identity (PARK) 4	-	i
8	Fixed identity (PARK) 5	-	i
9	Location area	-	i
10	Auth-type	-	i
11	Cipher-info	-	i
12	ZAP field	8.30	m
13	Service class	8.30	m
14	IWU-to-IWU	-	i

Table A.33: ETS 300 476-1 [2] Table A.54 ACCESS-RIGHTS-REJECT receiving (F to P) supported

Item	ACCESS-RIGHTS-REJECT receiving (F to P) Information element name	Profile reference	Profile status
2	Reject reason	-	i
3	Duration	-	i

Table A.34: ETS 300 476-1 [2] Table A.55 ACCESS-RIGHTS-REQUEST sending (P to F) supported

Item	ACCESS-RIGHTS-REQUEST sending (P to F) Information element name	Profile reference	Profile status
3	Auth-type	8.30	m
4	Cipher-info	-	i
5	Terminal Capability	8.30	m
6	IWU-to-IWU	-	i

Table A.35: ETS 300 476-1 [2] Table A.58 ACCESS-RIGHTS-TERMINATE-REJECT sending (P to F) supported

Item	ACCESS-RIGHTS-TERMINATE-REJECT sending (P to F) Information element name	Profile reference	Profile status
2	Reject reason	-	i

Table A.36: ETS 300 476-1 [2] Table A.61 ACCESS-RIGHTS-TERMINATE-REQUEST receiving (F to P) supported

Item	ACCESS-RIGHTS-TERMINATE-REQUEST receiving (F to P) Information element name	Profile reference	Profile status
3	Repeat indicator "non-prioritised"	-	i
4	Fixed identity (PARK) 1	8.31	m
5	Fixed identity (PARK) 2	-	i
6	Fixed identity (PARK) 3	-	i
7	IWU-to-IWU	-	i

Table A.37: ETS 300 476-1 [2] Table A.62 AUTHENTICATE-REJECT sending (P to F) supported

Item	AUTHENTICATE-REJECT sending (P to F) Information element name	Profile reference	Profile status
2	Repeat indicator "prioritised"	-	i
3	Auth-type 1	-	i
4	Auth-type 2	-	i
5	Auth-type 3	-	i
6	Reject reason	-	i

Table A.38: ETS 300 476-1 [2] Table A.63 AUTHENTICATE-REJECT receiving (F to P) supported

Item	AUTHENTICATE-REJECT receiving (F to P) Information element name	Profile reference	Profile status
2	Repeat indicator "prioritised"	-	i
3	Auth-type 1	-	i
4	Auth-type 2	-	i
5	Auth-type 3	-	i
6	Reject reason	-	i

Table A.39: ETS 300 476-1 [2] Table A.64 AUTHENTICATE-REPLY sending (P to F) supported

Item	AUTHENTICATE-REPLY sending (P to F) Information element name	Profile reference	Profile status
4	ZAP field	8.24	note A
5	Service class	8.24	note A
6	Key	-	i
7	IWU-to-IWU	-	i

Table A.40: ETS 300 476-1 [2] Table A.65 AUTHENTICATE-REPLY receiving (F to P) supported

Item	AUTHENTICATE-REPLY receiving (F to P) Information element name	Profile reference	Profile status
7	IWU-to-IWU	-	i

Table A.41: ETS 300 476-1 [2] Table A.66 AUTHENTICATE-REQUEST sending (P to F) supported

Item	AUTHENTICATE-REQUEST sending (P to F) Information element name	Profile reference	Profile status
6	Cipher info	-	i
7	IWU-to-IWU	-	i

Table A.42: ETS 300 476-1 [2] Table A.67 AUTHENTICATE-REQUEST receiving (F to P) supported

Item	AUTHENTICATE-REQUEST receiving (F to P) Information element name	Profile reference	Profile status
6	Cipher info	-	i
7	IWU-to-IWU	-	i

Table A.43: ETS 300 476-1 [2] Table A.68 CIPHER-REJECT sending (P to F) supported

Item	CIPHER-REJECT sending (P to F) Information element name	Profile reference	Profile status
2	Repeat indicator "prioritised"	-	i
3	Cipher info 1	-	i
4	Cipher info 2	-	i
5	Cipher info 3	-	i
6	Reject reason	-	i

Table A.44: ETS 300 476-1 [2] Table A.69 CIPHER-REJECT receiving (F to P) supported

Item	CIPHER-REJECT receiving (F to P) Information element name	Profile reference	Profile status
2	Repeat indicator "prioritised"	-	i
3	Cipher info 1	-	i
4	Cipher info 2	-	i
5	Cipher info 3	-	i
6	Reject reason	-	i

Table A.45: ETS 300 476-1 [2] Table A.70 CIPHER-REQUEST receiving (F to P) supported

Item	CIPHER-REQUEST receiving (F to P) Information element name	Profile reference	Profile status
3	Call identity	-	i
4	Connection identity	-	i
5	IWU-to-IWU	-	i

Table A.46: ETS 300 476-1 [2] Table A.71 CIPHER-SUGGEST sending (P to F) supported

Item	CIPHER-SUGGEST sending (P to F) Information element name	Profile reference	Profile status
3	Call identity	-	i
4	Connection identity	-	i
5	IWU-to-IWU	-	i

Table A.47: ETS 300 476-1 [2] Table A.73 IDENTITY-REPLY sending (P to F) supported

Item	IDENTITY-REPLY sending (P to F) Information element name	Profile reference	Profile status
2	Repeat Indicator "non-prioritised"	-	i
3	Portable identity 1	8.22	m
4	Portable identity 2	-	i
5	Portable identity 3	-	i
6	Repeat Indicator "non-prioritised"	-	i
7	Fixed identity 1	8.22	m
8	Fixed identity 2	-	i
9	Fixed identity 3	-	i
10	Repeat Indicator "non-prioritised"	-	i
11	NWK assigned identity 1	-	i
12	NWK assigned identity 2	-	i
13	NWK assigned identity 3	-	i
14	IWU-to-IWU	-	i

Table A.48: ETS 300 476-1 [2] Table A.81 IDENTITY-REQUEST receiving (F to P) supported

Item	IDENTITY-REQUEST receiving (F to P) Information element name	Profile reference	Profile status
2	Repeat indicator	-	i
4	Identity type 2	-	i
5	Identity type 3	-	i
6	IWU-to-IWU	-	i

Table A.49: ETS 300 476-1 [2] Table A.76 LOCATE-ACCEPT receiving (F to P) supported

Item	LOCATE-ACCEPT receiving (F to P) Information element name	Profile reference	Profile status
4	NWK assigned identity	-	i
5	Duration	-	i
6	IWU-to-IWU	-	i

Table A.50: ETS 300 476-1 [2] Table A.77 LOCATE-REJECT receiving (F to P) supported

Item	LOCATE-REJECT receiving (F to P) Information element name	Profile reference	Profile status
2	Reject reason	-	i
3	Duration	-	i

Table A.51: ETS 300 476-1 [2] Table A.78 LOCATE-REQUEST sending (P to F) supported

Item	LOCATE-REQUEST sending (P to F) Information element name	Profile reference	Profile status
5	NWK assigned identity	-	i
6	Cipher info	-	i
7	Setup capability	-	i
8	Terminal capability	8.28	m
9	IWU-to-IWU	-	i

Table A.52: ETS 300 476-1 [2] Table A.82 MM-INFO-SUGGEST receiving (F to P) supported

Item	MM-INFO-SUGGEST receiving (F to P) Information element name	Profile reference	Profile status
3	Fixed identity	-	i
4	Location area	-	i
5	NWK assigned identity	-	i
6	Network parameter	-	i
7	IWU-to-IWU	-	i

Table A.53: ETS 300 476-1 [2] Table A.85 TEMPORARY-IDENTITY-ASSIGN-REJECT sending (P to F) supported

Item	TEMPORARY-IDENTITY-ASSIGN-REJECT sending (P to F) Information element name	Profile reference	Profile status
2	Reject reason	-	i

A.2.2.3 CRSS and CISS messages

Table A.54: ETS 300 476-1 [2] Table A.86 CRSS and CISS messages sending (P to F) supported

Item	CRSS and CISS messages sending (P to F) Message name	Profile reference	Profile status
1	FACILITY	-	i
2	HOLD	-	i
3	HOLD-ACKnowledge	-	i
4	HOLD-REJECT	-	i
5	RETRIEVE	-	i
6	RETRIEVE-ACKnowledge	-	i
7	RETRIEVE-REJECT	-	i
8	CISS-REGISTER	-	i
9	CISS-RELEASE-COMplete	-	i

Table A.55: ETS 300 476-1 [2] Table A.87 CRSS and CISS messages receiving (F to P) supported

Item	CRSS and CISS messages receiving (F to P) Message name	Profile reference	Profile status
1	FACILITY	-	i
2	HOLD	-	i
3	HOLD-ACKnowledge	-	i
4	HOLD-REJECT	-	i
5	RETRIEVE	-	i
6	RETRIEVE-ACKnowledge	-	i
7	RETRIEVE-REJECT	-	i
8	CISS-REGISTER	-	i
9	CISS-RELEASE-COMplete	-	i

A.2.2.4 Link Control Entity (LCE) messages

Table A.56: ETS 300 476-1 [2] Table A.126 LCE message sending (P to F) supported

Item	LCE message sending (P to F) Information element name	Profile reference	Profile status
1	LCE-PAGE-RESPONSE	8.35	m

Table A.57: ETS 300 476-1 [2] Table A.127 LCE message receiving (F to P) supported

Item	LCE message receiving (F to P) Information element name	Profile reference	Profile status
2	LCE-PAGE-REJECT	8.35.2.1	m
3	LCE-REQUEST-PAGE short	8.35	m
4	LCE-REQUEST-PAGE long	-	i

Table A.58: ETS 300 476-1 [2] Table A.128 LCE-PAGE-RESPONSE sending (P to F) supported

Item	LCE-PAGE-RESPONSE sending (P to F) Information element name	Profile reference	Profile status
3	Fixed identity	8.35	m
4	NWK assigned identity	-	i
5	Cipher info	-	i

Table A.59: ETS 300 476-1 [2] Table A.129 LCE-PAGE-REJECT receiving (F to P) supported

Item	LCE-PAGE-REJECT receiving (F to P) Information element name	Profile reference	Profile status
4	Fixed identity	-	i
5	Reject reason	-	i

A.2.3 Information elements

To express the profile requirements of ETS 300 444 [1], tables A.60 to A.87 indicate the change of status for support of information elements.

A.2.3.1 Fixed length information element support

Table A.60: ETS 300 476-1 [2] Table A.136 Type of service class in basic service supported

Item	Type of service class in basic service	Profile reference	Profile status
1	Basic service "Normal call set-up"	8.2	m
2	Basic service "Internal call set-up"	8.2, 8.18	note A
3	Basic service "Emergency call set-up"	-	i
4	Basic service "Service call set-up"	8.2, 8.20	note A
5	Basic service "External handover call set-up"	-	i

Table A.61: ETS 300 476-1 [2] Table A.137 Basic service - Normal call set-up supported

Item	Basic service - Normal call set-up Name of field	Profile reference	Profile status	Profile value allowed
3	Basic service	8.2	m	'0000'B

Table A.62: ETS 300 476-1 [2] Table A.138 Basic service - Internal call set-up supported

Item	Basic service - Internal call set-up Name of field	Profile reference	Profile status	Profile value allowed
3	Basic service	8.2	m	'0000'B

Table A.63: ETS 300 476-1 [2] Table A.140 Basic service - Service call set-up supported

Item	Basic service - Service call set-up Name of field	Profile reference	Profile status	Profile value allowed
3	Basic service	8.2	m	'0000'B

Table A.64: ETS 300 476-1 [2] Table A.142 Single display supported

Item	Single display	Profile reference	Profile status	Profile value allowed
1	Single display	-	i	-

Table A.65: ETS 300 476-1 [2] Table A.143 Single-keypad supported

Item	Single keypad	Profile reference	Profile status	Profile value allowed
1	Single keypad	-	i	-

Table A.66: ETS 300 476-1 [2] Table A.144 Release-reason supported

Item	Release-reason Name of field	Profile reference	Profile status	Profile value allowed
2	Release reason code	8.9	m	0EH

Table A.67: ETS 300 476-1 [2] Table A.145 Signal supported

Item	Signal Name of field	Profile reference	Profile status	Profile value allowed
2	Signal value	8.14	m	'01000000'B '01000111'B '01001000'B '01001111'B

A.2.3.2 Variable length information element supported

Table A.68: ETS 300 476-1 [2] Table A.206 Allocation type supported

Item	Allocation type Name of field	Profile reference	Profile status	Profile value allowed
4	User Authentication Key (UAK) number	8.32	m	'1000'B
5	Authentication Code (AC) number	8.32	m	'1000'B

Table A.69: ETS 300 476-1 [2] Table A.208 Auth-type supported

Item	Auth-type Name of field	Profile reference	Profile status	Profile value allowed
2	Length of Contents (L)	8.23, 8.24, 8.25, 8.26, 8.27, 8.30, 8.32	m	0, 4
3	Authentication algorithm identifier	8.23, 8.24, 8.25, 8.26, 8.27, 8.30, 8.32	m	'00000001'B
4	Proprietary algorithm identifier	8.23, 8.24, 8.25, 8.26, 8.27, 8.30, 8.32	x	-
6	Authentication key number	8.23, 8.24, 8.25, 8.26, 8.27, 8.30, 8.32	m	'1000'B
7	TXC number	-	m	i
10	Cipher key number	8.23, 8.24, 8.25, 8.26, 8.27, 8.30, 8.32	o	'1000'B

Table A.70: ETS 300 476-1 [2] Table A.214 Cipher info supported

Item	Cipher info Name of field	Profile reference	Profile status	Profile value allowed
4	Cipher algorithm identifier	8.33	m	'0000001'B
5	Proprietary algorithm identifier	8.33	x	-
6	Cipher key type	8.33	m	'1001'B
7	Cipher key number	8.33	m	'1000'B

Table A.71: ETS 300 476-1 [2] Table A.241 Class Fixed identity supported

Item	Class Fixed identity	Profile reference	Profile status
1	Fixed identity class A	8.22, 8.28, 8.30	m
2	Fixed identity class B	8.22, 8.28, 8.30	m
3	Fixed identity class C	8.22, 8.28, 8.30	m
4	Fixed identity class D	-	i

Table A.72: ETS 300 476-1 [2] Table A.250 Identity type supported

Item	Identity types	Profile reference	Profile status
1	Identity type "Portable identity"	8.22	m
2	Identity type "NWK assigned identity"	-	i
3	Identity type "Fixed identity"	8.22	m
4	Identity type "Proprietary"	-	i

Table A.73: ETS 300 476-1 [2] Table A.255 Info type supported

Item	Info type Name of field	Profile reference	Profile status	Profile value allowed
2	Length of Contents (L)	8.29	m	0, 1
3	Oct3_ext_bit	8.29	m	'0'B
4	Parameter coding	8.29	m	'0000000'B
5	Ext_bit and Parameter coding (group of octets)	8.29	i	-

Table A.74: ETS 300 476-1 [2] Table A.260 Location area info types supported

Item	Location area info types	Profile reference	Profile status
1	Location area "No ELI"	8.28	m
2	Location area "With ELI no GSM info indicated"	-	i
3	Location area "No ELI GSM info indicated"	-	i

Table A.75: ETS 300 476-1 [2] Table A.264 Multi-display - DECT standard characters supported

Item	Multi-display - DECT standard characters Name of field	Profile reference	Profile status	Profile value allowed
3	Display information (group of octets)	8.16	m	len_o: 1 .. 61 val: 0CH, 20H, 23H, 2AH, 30H .. 39H

Table A.76: ETS 300 476-1 [2] Table A.264 Multi-display - DECT control characters supported

Item	Multi-display - DECT control characters Name of field	Profile reference	Profile status	Profile value allowed
3	Display information (group of octets)	8.16	m	len_o: 1 .. 61 val: 08H .. 0BH, 0DH

Table A.77: ETS 300 476-1 [2] Table A.265 Multi-keypad supported - dialling pause

Item	Multi-keypad - dialling pause Name of field	Profile reference	Profile status	Profile value allowed
3	Keypad information (group of octets)	8.10	m	len_o: 1 val: 05H

Table A.78: ETS 300 476-1 [2] Table A.265 Multi-keypad - Go to pulse supported

Item	Multi-keypad - Go to pulse Name of field	Profile reference	Profile status	Profile value allowed
3	Keypad information (group of octets)	8.10	m	len_o: 1 val: 12H

Table A.79: ETS 300 476-1 [2] Table A.265 Multi-keypad - Go to DTMF defined tone length supported

Item	Multi-keypad - Go to DTMF defined tone length Name of field	Profile reference	Profile status	Profile value allowed
3	Keypad information (group of octets)	8.10	m	len_o: 1 val: 14H

Table A.80: ETS 300 476-1 [2] Table A.265 Multi-keypad - register recall supported

Item	Multi-keypad - register recall Name of field	Profile reference	Profile status	Profile value allowed
3	Keypad information (group of octets)	8.10	m	len_o: 1 val: 15H

Table A.81: ETS 300 476-1 [2] Table A.265 Multi-keypad - Go to DTMF infinite tone length supported

Item	Multi-keypad - Go to DTMF infinite tone length Name of field	Profile reference	Profile status	Profile value allowed
3	Keypad information (group of octets)	8.10	m	len_o: 1 val: 16H

Table A.82: ETS 300 476-1 [2] Table A.265 Multi-keypad - internal call supported

Item	Multi-keypad - internal call Name of field	Profile reference	Profile status	Profile value allowed
3	Keypad information (group of octets)	8.10	m	len_o: 1 val: 17H

Table A.83: ETS 300 476-1 [2] Table A.265 Multi-keypad - service call supported

Item	Multi-keypad - service call Name of field	Profile reference	Profile status	Profile value allowed
3	Keypad information (group of octets)	8.10	m	len_o: 1 val: 18H

Table A.84: ETS 300 476-1 [2] Table A.265 Multi-keypad - dialled digit basic supported

Item	Multi-keypad - dialled digit basic Name of field	Profile reference	Profile status	Profile value allowed
3	Keypad information (group of octets)	8.10	m	len_o: 1 .. 61 val: 23H, 2AH, 30H .. 39H

Table A.85: ETS 300 476-1 [2] Table A.272 Type of portable identity supported

Item	Type of portable identity Identity name	Profile reference	Profile status
1	IPEI	8.30	m
2	IPUI-N	8.30	m
3	IPUI-S	8.30	m
4	IPUI-O	8.30	m
5	IPUI-T	8.30	m
6	IPUI-P	8.30	m
7	IPUI-Q	8.30	m
8	IPUI-U	8.30	m
9	IPUI-R	8.30	m
10	TPUI-default	8.30, 8.28	m
11	TPUI-assigned individual	8.30, 8.28	m
12	TPUI-assigned call group	-	i
13	TPUI-assigned connectionless group	-	i

Table A.86: ETS 300 476-1 [2] Table A.285 Progress indicator supported

Item	Progress indicator Name of field	Profile reference	Profile status	Profile value allowed
5	Progress description	8.3, 8.4, 8.5	m	'0001000'B

Table A.87: ETS 300 476-1 [2] Table A.297 Terminal capability supported

Item	Terminal capability Name of field	Profile reference	Profile status	Profile value allowed
2	Length of contents (L)	8.17, C.2.5	m	0, 3..255
3	Oct3_ext_bit	8.17, C.2.5	m	'1'B
4	Tone capability	8.17, C.2.5	m	'000'B .. '100'B
5	Display capability	8.17, C.2.5	m	'0000'B .. '0101'B
6	Oct3b_ext_bit	-	i	-
7	Echo param	-	i	-
8	N-rej	-	i	-
9	A-vol	-	i	-
10	Oct3c_ext_bit	-	i	-
11	slot type capability	-	i	-
12	Oct3d_ext_bit	-	i	-
13	Number of stored display characters (MS)	-	i	-
14	Oct3e_ext_bit	-	i	-
15	Number of stored display characters (LS)	-	i	-
16	Oct3f_ext_bit	-	i	-
17	Number of lines in (physical) display	-	i	-
18	Oct3g_ext_bit	-	i	-
19	Number of characters per line	-	i	-
20	Oct3h_ext_bit	-	i	-
21	Scrolling behaviour field	-	i	-
22	Oct4_ext_bit	8.17, C.2.5	m	'1'B
23	Profile indicator_1	8.17, C.2.5	m	'xxxxx1x'B
24	Oct4a_ext_bit	-	i	-
25	Profile indicator_2	-	i	-
26	Oct5_ext_bit	8.17, C.2.5	m	'1'B
27	Oct5_spare	8.17, C.2.5	m	'0000'B
28	Control Codes	8.17, C.2.5	m	'000'B .. '100'B
29	Oct5a_ext_bit	-	i	-
30	Escape to 8 bit character sets_1	-	i	-

A.2.3.3 Escape information elements support

All the escape information elements are out of scope for all GAP only equipment.

A.2.4 Protocol error handling

The supplier of the implementation shall state the support of the implementation for each of the following protocol error and exception handling procedures, in the table below.

Table A.88: ETS 300 476-1 [2] Table A.313 Error and exception handling procedures supported

Item	Error and exception handling procedures Procedure name	Prof. ref.	Prof. status
1	eeh_protocol_discriminator_error	6.9.4	m
2	eeh_message_too_short	6.9.4	m
3	eeh_unsupported_transaction_identity_error	6.9.4	m
4	eeh_unknown_active_cc_call	6.9.4	m
5	eeh_unknown_active_ciss_call	-	i
6	eeh_unknown_active_coms_call	-	i
7	eeh_unknown_active_clms_call	-	i
8	eeh_unknown_active_mm_transaction	6.9.4	m
9	eeh_cc_message_error	6.9.4	m
10	eeh_ciss_message_error	-	i
11	eeh_coms_message_error	-	i
12	eeh_clms_message_error	-	i
13	eeh_mm_message_error	6.9.4	m
14	eeh_info_element_out_of_sequence	6.9.4	m
15	eeh_duplicated_info_elements	6.9.4	m
16	eeh_mandatory_info_element_missing_in_cc_message	6.9.4	m
17	eeh_mandatory_info_element_content_error_in_cc_message	6.9.4	m
18	eeh_mandatory_info_element_missing_in_coms_message	-	i
19	eeh_mandatory_info_element_missing_in_clms_message	-	i
20	eeh_mandatory_info_element_error_in_mm_message	6.9.4	m
21	eeh_unrecognised_info_element	6.9.4	m
22	eeh_non-mandatory_info_element_content_error	6.9.4	m
23	eeh_data_link_reset	-	i
24	eeh_data_link_failure	-	i

A.3 Data Link Control (DLC) layer - PT: Profile ICS

A.3.1 Capabilities

A.3.3.1 Services

To express the profile requirements of ETS 300 444 [1], table A.89 indicates the change of status for support of data link services.

Table A.89: ETS 300 444 [1] Table A.9 Data link services

Item	Data link services	Prof. Ref.	Prof. Status
1	C-plane services	5.1	m
2	U-plane services	5.1	m

A.3.3.1.1 C-plane services

To express the profile requirements of ETS 300 444 [1], table A.90 indicates the change of status for support of C-plane services.

Table A.90: ETS 300 444 [1] Table A.10 C-plane services

Item	C-plane services	Prof. Ref.	Prof. Status
1	Class U service	-	i
2	Class A service (LAPC class A service and Lc; Cs channel fragmentation and recommendation)	5.1	m
3	Class B service	-	i
4	Broadcast service (Broadcast Lb service)	5.1	m

A.3.3.1.2 U-plane services

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of U-plane services.

Table A.91: ETS 300 444 [1] Table A.11 U-plane services

Item	U-plane services	Prof. Ref.	Prof. Status
1	LU1 - Transparent Unprotected service	5.1	m
2	LU2 - Frame Relay service (FREL)	-	i
3	LU3 - Frame Switching service (FSWI)	-	i
4	LU4 - Forward error correction service (FEC)	-	i
5	LU5 - Basic Rate Adaptation (BRAT) protected service	-	i
6	LU5 - Basic Rate Adaptation (BRAT) unprotected service	-	i
7	LU6 - Secondary Rate Adaptation service (SRAT)	-	i
8	LU7 - 64kbit/s data bearer service	-	i
9	LU16 - Escape for non-standard family (ESC)	-	i

A.3.3.1.2 Management services

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of management services.

Table A.92: ETS 300 444 [1] Table A.12 Management services

Item	Management services	Prof. Ref.	Prof. Status
4	Connection handover management	5.1	Intra-cell: m
	(Intracell/intercell voluntary)	5.1	Inter-cell: m
5	Connection ciphering management	5.1	Encryption activation: m
	(Encryption activation/deactivation)	5.1	Encryption deactivation: c9201

c9201: IF A.4/5 OR A.4/7 THEN m ELSE i

A.3.3.2 Procedures

A.3.3.2.1 Generic signalling procedures

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of Generic signalling procedures.

Table A.93: ETS 300 444 [1] Table A.13 Generic signalling procedures

Item	Generic signalling procedures	Prof. Ref.	Prof. Status
1	Segmentation of NWK information	9.2.3	o
2	C _S channel fragmentation and recombination	9.5	m
3	C _F channel fragmentation and recombination	-	i

A.3.3.2.2 Class A procedures

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of Class A procedures.

Table A.94: ETS 300 444 [1] Table A.14 Class A procedures

Item	Class A procedures	Prof. Ref.	Prof. Status
1	Class A link establishment	9.1	m
2	Class A acknowledged information transfer	9.2	m
3	Class A link release	9.3	m
4	Class A link re-establishment	9.4	m
5	Class A (basic) connection handover	9.7	m

A.3.3.2.3 Broadcast procedures

To express the profile requirements of ETS 300 444 [1], tableA.95 indicates the change of status for support of Broadcast procedures.

Table A.95: ETS 300 444 [1] Table A.16 Broadcast procedures

Item	Broadcast procedures	Prof. Ref.	Prof. Status
1	Normal operation (broadcast)	9.6	m
2	Expedited operation	-	i

A.3.3.2.4 LU1 procedures

To express the profile requirements of ETS 300 444 [1], table A.96 indicates the change of status for support of LU1 procedures.

Table A.96: ETS 300 444 [1] Table A.17 LU1 procedures

Item	LU1 procedures	Prof. Ref.	Prof. Status
1	U plane Class 0/min_delay	9.9	m
2	U plane Class 0	-	i
3	FU1 frame operation	9.10	note A

A.3.3.2.5 Management procedures

To express the profile requirements of ETS 300 444 [1], table A.97 indicates the change of status for support of Management procedures.

Table A.97: ETS 300 444 [1] Table A.28 Management procedures

Item	Management procedures	Prof. Ref.	Prof. Status
1	MAC connection management	9.1.1.4	m
3	DLC U-plane management	9.9.1.1	m
4	Connection handover management	9.7.2.1	m
5	Connection ciphering management (Encryption switching)	9.8	m

Table A.98: ETS 300 444 [1] Table A.29 MAC connection management procedures

Item	MAC connection management procedures	Prof. Ref.	Prof. Status
5	Selection of logical channels (only Cs) (Cs channel fragmentation and recommendation)	9.5	m

Table A.99: ETS 300 444 [1] Table A.32 Connection ciphering management procedures

Item	Connection ciphering management procedures	Prof. Ref.	Prof. Status
1	Providing a key to the MAC layer	9.8.1.1	note A
2	Starting the ciphering	9.8	note A
3	Stopping the ciphering	9.8	note A
4	Connection handover of ciphered connection	9.8.2.2	note A

A.3.3.3 Parameters

A.3.3.3.1 LU1 parameters

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of LU1 Connection types.

Table A.100: ETS 300 444 [1] Table A.38 LU1 Connection types

Item	Connection types	Prof. Ref.	Prof. Status
1	IN / min delay - Half slot (10 octets)	-	i
2	IN / normal delay - Half slot (10 octets)	-	i
3	IN / min delay - Full slot (40 octets)	9.10	m
4	IN / normal delay - Full slot (40 octets)	-	i
5	IN / min delay - Double slot (100 octets)	-	i
6	IN / normal delay - Double slot (100 octets)	-	i

A.3.3.4 Messages

A.3.3.4.1 C-plane PDUs

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of Broadcast service frame structure (Receipt F to P).

Table A.101: ETS 300 444 [1] Table A.54 Broadcast service frame structure (Receipt F to P)

Item	Frame elements	Prof. Ref.	Prof. Status
1	Short frame format (3 octets)	9.6	m
2	Long frame format (5 octets)	-	i

A.4 Medium Access Control (MAC) layer - PT: Profile ICS

A.4.1 Major Capabilities

A.4.1.1 Services

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of services.

Table A.102: ETS 300 476-3 [4] Table A.9 Service groups supported

Item	Name of service	Prof. Ref.	Prof. Status
1	Connection oriented control	5.2	m
2	Broadcast control	5.2	m
3	Connectionless control	-	i
4	Multiplexing (General)	5.2, 10.1	note A
5	Management (General)	5.2, 10.1	note A

A.4.3.1.1 Connection oriented control services

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of connection oriented services.

Table A.103: ETS 300 476-3 [4] Table A.10 Connection oriented control services

Item	Connection oriented control services	Prof. Ref.	Prof. Status
1	Basic connections	5.2	m
2	Advanced symmetric connections	-	i
3	Advanced asymmetric connections	-	i

Table A.104: ETS 300 476-3 [4] Table A.11 Connection services

Item	Connection services	Prof. Ref.	Prof. Status
1	Connection setup (Basic connections)	5.2	note A
3	Connection data transfer (Basic connections)	5.2	note A
4	Connection handover (intra-cell, inter-cell)	5.2	m
5	Connection release (Basic connections)	5.2	note A

Table A.105: ETS 300 476-3 [4] Table A.12 Symmetric connection oriented services

Item	Symmetric connection oriented services	Prof. Ref.	Prof. Status
1	Type 1 IN_minimum_delay (General)	5.2, 10.1	m
2	Type 2 IN_normal_delay	-	i
3	Type 3 IP_error_detection	-	i
4	Type 4 IP_error_correction	-	i

Table A.106: ETS 300 476-3 [4] Table A.14 C-plane connection services

Item	C-plane connection services	Prof. Ref.	Prof. Status
1	Only Cs channel supported (Cs higher layer signalling)	5.2	m
2	Cs and Cf channels supported	-	i
3	Only Cf channel supported	-	i

A.4.1.1.2 Broadcast control services

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of Broadcast services.

Table A.107: ETS 300 476-3 [4] Table A.15 Broadcast control services

Item	Broadcast services	Prof. Ref.	Prof. Status
1	Continuous broadcast	5.2	note A
2	Non-continuous broadcast	-	i
3	Paging broadcast	5.2	m

A.4.1.1.3 Multiplexing services

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of Multiplexing services.

Table A.108: ETS 300 476-3 [4] Table A.19 CSF multiplexing services

Item	CSF multiplexing services	Prof. Ref.	Prof. Status
1	D-MAP (General)	5.2, 10.1	note A
2	A-MAP (General)	5.2, 10.1	note A
3	B-MAP (General)	5.2, 10.1	m
4	T-MUX (General)	5.2, 10.1	note A
5	E/U-MUX (General)	5.2, 10.1	m
6	C-MUX (General)	5.2, 10.1	i
7	Encryption activation	5.2	m
8	Encryption deactivation	5.2	c10801
9	Scrambling (General)	5.2, 10.1	note A
10	Error control R-CRC (General)	5.2, 10.1	m
11	Error control X-CRC (General)	5.2, 10.1	m

c10801: IF A.4/7 THEN m ELSE i.

Table A.109: ETS 300 476-3 [4] Table A.20 D-MAP services

Item	D-MAP	Prof. Ref.	Prof. Status
1	D-field MAP D80	-	i
2	D-field MAP D32 (General)	5.2, 10.1	m
3	D-field MAP D08	-	i
4	D-field MAP D00 (General)	5.2, 10.1	m

Table A.110: ETS 300 476-3 [4] Table A.21 B-MAP services

Item	B-MAP	Prof. Ref.	Prof. Status
1	B-field MAP unprotected format (General)	5.2, 10.1	m
2	B-field MAP protected format	-	i

Table A.111: ETS 300 476-3 [4] Table A.22 E/U mux services

Item	E/U MUX	Prof. Ref.	Prof. Status
1	E/U-mux E type	-	i
2	E/U-mux U type (General)	5.2, 10.1	m

Table A.112: ETS 300 476-3 [4] Table A.23 C mux mapping services

Item	Time multiplexers - C mux	Prof. Ref.	Prof. Status
1	C-mux double slot	-	i
2	C-mux full slot (General)	5.2, 10.1	i
3	C-mux half slot	-	i

A.4.1.1.4 Management services

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of Management services.

Table A.113: ETS 300 476-3 [4] Table A.24 Management services

Item	Management services	Prof. Ref.	Prof. Status
5	In-connection quality control (Quality control)	5.2	note A
9	SARI support	5.2	m

Table A.114: Handover services management

Item	Handover services	Prof. Ref.	Prof. Status
1	Connection handover	5.2	intra-cell: m
	(intra/inter cell)	5.2	inter-cell: m
2	Bearer handover	5.2	intra-cell: m
	(intra/inter cell)	5.2	inter-cell: o

A.4.1.2 Procedures

A.4.1.2.1 Connection setup procedures

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of Connection setup procedures.

Table A.115: ETS 300 476-3 [4] Table A.25 C/O single bearer setup procedures

Item	Name of procedure	Prof. Ref.	Prof. Status
1	Basic setup, single bearer basic connection of known service (Setup of basic connection, basic bearer setup (A-field))	10.4	m
2	Normal setup, single bearer duplex connection known service	-	i
3	Fast setup, single bearer duplex connection known service	-	i

Table A.116: ETS 300 476-3 [4] Table A.28 C/O bearer setup procedures

Item	Name of procedure	Prof. Ref.	Prof. Status
1	Basic bearer setup	10.4	m

A.4.1.2.2 Connection data transfer procedures

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of C/O data transfer procedures.

Table A.117: ETS 300 476-3 [4] Table A.30 C/O data transfer procedures

Item	Name of procedure	Prof. Ref.	Prof. Status
2	Cs - channel data	10.8	m
3	Q1/Q2 setting for sliding collision / A-,B-field check (FT to PT) (Sliding collision detection)	10.12	o
4	Antenna diversity (React on Q1 bit in direction PT to FT)	10.11	i
5	Q2 bit settings	10.9	m
6	Q1 bit settings	10.11	m

A.4.1.2.3 Connection handover procedures

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of connection handover procedures.

Table A.118: ETS 300 476-3 [4] Table A.31 C/O connection handover procedures

Item	Name of procedure	Prof. Ref.	Prof. Status
1	Connection handover (request)	10.7	m
2	Duplex bearer handover (request)	10.6	m
3	Double simplex bearer handover	-	i

A.4.1.2.4 Connection release procedures

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of connection release procedures.

Table A.119: ETS 300 476-3 [4] Table A.32 C/O connection release procedures

Item	Name of procedure	Prof. Ref.	Prof. Status
1	Unacknowledged bearer release (Connection/bearer release)	10.5	m

A.4.1.2.5 Broadcast procedures

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of broadcast procedures.

Table A.120: ETS 300 476-3 [4] Table A.33 Broadcast procedures

Item	Name of procedure	Prof. Ref.	Prof. Status
1	Normal paging (Paging broadcast)	10.3	m
2	Fast paging	-	i
3	Downlink broadcast	10.2	m

A.4.1.2.6 CSF multiplexing procedures

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of CSF multiplexing procedures.

Table A.121: ETS 300 476-3 [4] Table A.36 CSF multiplexing procedures

Item	CSF multiplexing procedures	Prof. Ref.	Prof. Status
1	Encryption	10.13	Encryption process - initialisation and synchronisation: m
		10.14	Encryption mode control: m
		10.15	Handover encryption process: m
2	Scrambling (General)	10.1	m
3	R-CRC generation (General)	10.1	m
4	R-CRC checking (General)	10.1	m
5	X-CRC generation (General)	10.1	m
6	X-CRC checking (General)	10.1	m

A.4.1.2.7 Layer management procedures

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of Layer management procedures.

Table A.122: ETS 300 476-3 [4] Table A.37 Layer management procedures

Item	Name of procedure	Prof. Ref.	Prof. Status
1	Extended system information PP request	-	i
3	Double simplex bearer physical channel selection	-	i
4	Simplex bearer physical channel selection	-	i
5	RFPI handshake	10.10	note A
7	RFP idle receiver scan sequence (General)	10.1	m
8	Test message procedures	-	i

A.4.1.3 Other capabilities

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of extended RF carriers.

Table A.123: ETS 300 476-3 [4] Table A.38 Extended RF carriers supported

Item	Extended RF Carriers	Prof. Ref.	Prof. Status
1	Extended RF carriers (Extended frequency allocation)	10.16	m

Table A.124: ETS 300 476-3 [4] Table A.39 Operation modes in Idle_locked state supported

Item	Operation mode	Prof. Ref.	Prof. Status
2	High duty cycle Idle_locked mode	-	i
3	Normal cycle Idle_locked mode (General)	10.1	m
4	Low cycle Idle_locked mode	-	i

A.4.2 Messages

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of messages.

A.4.2.1 A - Field

A.4.2.1.1 A - field header - B-field identification

Table A.125: ETS 300 476-3 [4] Table A.50 B-field identification (Sending P to F)

Item	B-field identification	Prof. Ref.	Prof. Status
1	U-type, IN, SIN or IP packet number 0	10.1	m
2	U-type, IP error detect or IP packet number 1	-	i
3	E-type, all CF or CLF, packet number 0	-	i
4	E-type, all CF, packet number 1	-	i
5	E-type, not all CF or CLF; packet number 0	-	i
6	E-type, not all CF; CF packet number 1	-	i
7	E-type, all MAC control (unnumbered)	-	i
8	No B-field	10.1	i

Table A.126: ETS 300 476-3 [4] Table A.51 B-field identification (Receipt F to P)

Item	B-field identification	Prof. Ref.	Prof. Status
1	U-type, IN, SIN or IP packet number 0	10.1	m
2	U-type, IP error detect or IP packet number 1	-	i
3	E-type, all CF or CLF, packet number 0	-	i
4	E-type, all CF, packet number 1	-	i
5	E-type, not all CF or CLF; packet number 0	-	i
6	E-type, not all CF; CF packet number 1	-	i
7	E-type, all MAC control (unnumbered)	-	i
8	No B-field	10.1	m

A.4.2.2 A - Field Messages

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of A - field messages.

A.4.2.2.1 Paging tail messages supported

Table A.127: ETS 300 476-3 [4] Table A.57 Paging tail (P_T) messages (Receipt F to P)

Item	Paging tail messages	Prof. Ref.	Prof. Status
1	Full page format	-	i
2	Long page format	-	i
3	Short page format	10.3.1	m
4	Zero length page format	10.3.2	m

A.4.2.2.2 P_T messages information typeTable A.128: ETS 300 476-3 [4] Table A.58 P_T messages information supported (Receipt F to P)

Item	P_T messages information type	Prof. Ref.	Prof. Status
1	0000 - fill bits	10.3.3	i
2	0001 - blind full slot	10.3.3	m
3	0010 - other bearer	-	m
4	0011 - recommended other bearer	-	i
5	0100 - good RFP bearer	-	i
6	0101 - dummy or C/L bearer position	-	m
7	0110 - RFP identity	-	i
8	0111 - escape	-	i
9	1000 - dummy or C/L bearer marker	-	i
10	1001 - bearer handover information	-	m
11	1010 - RFP status	-	i

A.4.2.2.3 MAC control messages supported

Table A.129: ETS 300 476-3 [4] Table A.59 MAC control (M_T) messages (Sending P to F)

Item	MAC control (M_T) messages	Prof. Ref.	Prof. Status
1	Basic connection control	10.4	m
2	MAC layer test messages	-	i
3	Advanced connection control	-	i
4	Quality control	-	i
5	Broadcast and connectionless services	10.2	m
6	Encryption control	10.14	m
7	B-field setup, first PT transmission	-	i
8	MAC control escape	-	i
9	TARI	-	i

Table A.130: ETS 300 476-3 [4] Table A.60 MAC control (M_T) messages (Receipt F to P)

Item	MAC control (M_T) messages	Prof. Ref.	Prof. Status
1	Basic connection control	10.4	m
2	MAC layer test messages	-	i
3	Advanced connection control	-	i
4	Quality control	-	i
5	Broadcast and connectionless services	10.2	m
6	Encryption control	10.14	m
7	B-field setup, first PT transmission	-	i
8	MAC control escape	-	i
9	TARI	-	i

A.4.2.2.4 Broadcast and connectionless (BCL) messages

Table A.131: ETS 300 476-3 [4] Table A.69 Broadcast and connectionless (BCL) messages (Sending P to F)

Item	MAC control (M _T) messages - Broadcast and connectionless services	Prof. Ref.	Prof. Status
7	C/L single transmissions, no CF or CLS	-	i
8	CLS service, first transmissions	-	i
9	change dummy bearer position	-	i
10	extended system info., A-field procedure	-	i
11	extended system info., B-field procedure	-	i

Table A.132: ETS 300 476-3 [4] Table A.70 Broadcast and connectionless (BCL) messages (Receipt F to P)

Item	MAC control (M _T) messages - Broadcast and connectionless services	Prof. Ref.	Prof. Status
10	extended system info., A-field procedure	-	i
11	extended system info., B-field procedure	-	i

Table A.133: ETS 300 476-3 [4] Table A.72 Encryption control (EC) messages (Sending P to F)

Item	MAC control (M _T) messages - Encryption control	Prof. Ref.	Prof. Status
4	Encryption stop request	11.14	o
5	Encryption stop confirm	11.14	o
6	Encryption stop grant	11.14	o

Table A.134: ETS 300 476-3 [4] Table A.73 Encryption control (EC) messages (Receipt F to P)

Item	MAC control (M _T) messages - Encryption control	Prof. Ref.	Prof. Status
4	Encryption stop request	11.14	o
5	Encryption stop confirm	11.14	o
6	Encryption stop grant	11.14	o

A.5 Physical (PHL) layer - PT: Profile ICS

A.5.1 Physical layer procedures

To express the profile requirements of ETS 300 444 [1], the following table indicates the change of status for support of procedures.

Table A.135: ETS 300 476-7 [5] Table Q.12 Physical layer procedures

Item	Procedure name	Profile reference	Profile status R/B/P
2	Addition of Z-field	11.4	m
4	Receipt of Z-field	11.4	m
9	Basic physical channel R32 management	10.1, 11.1	m
10	The low-rate physical channel R08j management	10.1, 11.1	i
11	The high capacity physical channel R80 management	10.1, 11.1	i
12	Sliding collision detection	11.5	m

Annex B (normative): GAP Profile-specific ICS proforma for PT

Notwithstanding the provisions of the copyright clause related to the text of the present ETS (see front page), ETSI grants users of this ETS to freely reproduce the Profile ICS Proforma in this annex so that it can be used for its intended purposes and may further publish the completed Profile ICS.

B.1 Introduction for completing the Profile-specific ICS proforma

B.1.1 Purposes and structure

The purpose of this PICS proforma is to provide a mechanism whereby a supplier of an implementation of the portable termination specific requirements of ETS 300 444 [1]: DECT: Generic Access Profile (GAP) may provide information about the implementation in a standardised manner.

The Profile-specific ICS proforma is subdivided into subclauses for the following categories of information:

- instructions for completing the ICS proforma;
- identification of the implementation;
- identification of the ETS 300 444 [1]: DECT: Generic Access Profile (GAP);
- ICS proforma tables:
 - global statement of conformance;
 - functional groups and procedures;
 - timers and protocol parameters;
 - messages;
 - information elements;
 - negotiation capabilities;
 - protocol error handling;
 - multilayer dependencies.

The ICS proforma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [7].

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Status column

The following notations, defined in ISO/IEC 9646-7 [7], are used for the status column:

m or M	mandatory - the capability is required to be supported;
o or O	optional - the capability may be supported or not;
n/a or N/A	not applicable - in the given context, it is impossible to use the capability;
x or X	prohibited (excluded) - there is a requirement not to use this capability in the given context;
o.i or O.i	qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies a unique group of related optional items and the logic of their selection which is defined immediately following the table;
ci or Ci	conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table or which is defined in the general condition table below;
i or I	out-of-scope - this capability is outside the scope of the given specification, and hence irrelevant and not subject to conformance testing. This status is in particular applicable for data fields which are reserved for future use. The structure of such fields has to be supported, but the value is undefined and thus to be ignored.

Reference column

The reference column gives reference to ETS 300 444 [1], except where explicitly stated otherwise.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [7], are used for the support column:

Y or y	supported by the implementation;
N or n	not supported by the implementation;
N/A, n/a or	no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status).

In each context, the kind of "non-support" which is implemented at the receipt may be additionally indicated such as:

- Err the item is treated as a protocol error;
- lg the item is received and ignored (i.e. processed syntactically, but not semantically);
- rj the item is received and rejected.

NOTE: As stated in ISO/IEC 9646-7 [7], support for a PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Values allowed column

The values allowed column contains the values or the ranges of values allowed.

Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line before a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

B.1.3 Instructions for completing the Profile specific ICS proforma

The supplier of the implementation shall complete the Profile specific ICS proforma in each of the spaces provided using the notation described in subclause B.1.2. Specific instruction is provided in the text which precedes each table.

B.2 Identification of the implementation

B.2.1 Date of statement

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

Table B.1: Date of statement

Date of statement		
Day	Month	Year

B.2.2 Implementation Under Test (IUT) identification

The supplier of the implementation shall enter information necessary to uniquely identify the IUT in the table below.

Table B.2: IUT identification

IUT identification	
IUT name	
IUT version	

B.2.3 System Under Test (SUT) identification

The supplier of the implementation shall enter information necessary to uniquely identify the SUT in the table below.

Table B.3: SUT identification

SUT identification	
SUT name	International Portable Equipment Identity (IPEI):
Hardware configuration	

B.2.4 Product supplier

Table B.4 : Product supplier

Product supplier	
Name	
Address	
Phone No.	
Fax No.	
E-mail address	
Additional information	

B.2.5 Client identification

The product supplier information and client information should both be filled in if they are different.

Table B.5 : Client identification

Client	
Name	
Address	
Phone No.	
Fax No.	
E-mail address	
Additional information	

B.2.6 Contact person identification

A person who can answer queries regarding information supplied in the Profile ICS should be named as the contact person.

Table B.6: Contact person identification

Contact person	
Name	
Address	
Phone No.	
Fax No.	
E-mail address	
Additional information	

B.3 Identification of the protocol

The supplier of the implementation shall enter the title, reference number and date of the publication of the ETS DECT-GAP Specification to which conformance is claimed, in the box below.

Table B.7: Identification of protocol

Identification of profile	
Title of specification	Radio Equipment and Systems (RES); Digital European Cordless Telecommunications (DECT); Generic Access Profile (GAP)
Reference no.	ETS 300 444 [1]
Date of Publication	

B.3.1 Defect report numbers and amendments implemented

The supplier of the implementation shall enter the reference number of implementation defect reports or corresponding amendment documents which modify the specification to ETS 300 444 [1], in the table below.

Table B.8: Defect report and amendments number

Modification of specification	
Defect report no.	Amendment no.

B.3.2 Addenda implemented

The supplier of the implementation shall enter the titles and the reference number of implemented addenda to ETS 300 444 [1], in the table below.

Table B.9: Addenda implemented

Addenda implemented	
Title	Reference no.

B.4 Global statement of conformance

An explicit answer shall be entered, in each of the support or supported column boxes provided, using the notation described in subclause B.1.2.

Table B.10: Global statement of conformance

Global statement of conformance	
Are all mandatory capabilities implemented?	

NOTE: Answering "No" to this question indicates non-conformance to the <reference specification type> specification. Non-supported mandatory capabilities are to be identified in the ICS, with an explanation of why the implementation is non-conforming, on pages attached to the ICS proforma.

B.5 Capabilities

B.5.1 NWK Profile-specific ICS proforma for PT

B.5.1.1 General requirements

Table B.11: General requirements supported

Item	Requirement	Profile reference	Profile status	Support
1	Transaction identifier assignment	6.9.2	m	
2	Length of NWK layer message	6.9.3	m	
3	Handling of error and exception conditions	6.9.4	m	
4	Codings of information elements	6.9.7	m	

B.5.1.2 Application features

The supplier of the implementation shall state the support of the implementation for all of the following application features, in the table below.

Table B.12: Application features supported

Item	Name of feature	Profile reference	Profile status	Support
1	AC_bitstring_mapping	6.6	m	
2	Multiple subscription registration	6.6	m	
3	Manual entry of the PARK	6.6	o	

B.5.1.3 Application Procedures

The supplier of the implementation shall state the support of the implementation for all of the following procedures, in the table below.

Table B.13: Application procedures supported

Item	Name of procedure	Profile reference	Profile status	Support
1	Subscription control	14.1	m	
2	AC to bitstring mapping	14.2	m	
3	Manual entry of the PARK	14.3	cp1301	

cp1301: IF B.12/3 THEN m ELSE n/a.

B.5.1.4 Management procedures

The supplier of the implementation shall state the support of the implementation for all of the following management procedures, in the table below.

Table B.14: Management procedure support

Item	Name of procedure	Profile reference	Profile status	Support
1	Location registration initiation	13.2	m	
2	Assigned individual TPUI management	13.3	m	
3	PMID management	13.4	m	
4	Broadcast attributes management	13.6	m	
5	Storage of subscription related data	13.7	m	
6	DCK management	13.5	m	

B.5.2 DLC Profile-specific ICS proforma for PT

The supplier of the implementation shall state the support of the implementation for all of the following requirements, in the table below.

Table B.15: Generic signalling procedures

Item	Generic signalling procedures	Prof. Ref.	Prof. Status
1	Receipt of segmented NWK information according to GAP	9.2.3	c1501

c1501: IF A.93/1 THEN n/a ELSE m

B.5.3 MAC Profile-specific ICS proforma for PT**B.5.3.1 Services****B.5.3.1.2 Extended frequency allocation service**

The supplier of the implementation shall state the support of the implementation for all of the following requirements, in the table below.

Table B.16: Extended frequency allocation supported

Item	Service	Profile reference	Profile status	Support
1	Extended frequency allocation	5.2	m	

B.5.4 PH Profile-specific ICS proforma for PT**B.5.4.1 Requirements**

The supplier of the implementation shall state the support of the implementation for all of the following requirements, in the table below.

Table B.17: GAP specific PH requirements

Item	Requirement	Profile reference	Profile status R/B/P	Sp.	Allowed values	Sp. values
1	Full Slots shall be used	11.1, 12.1	m		n/a	
2	Minimum Normal Transmit Power (NTP)	11.2	m		> 80 mW per simultaneously active transmitter	
3	Radio receiver sensitivity	11.3	m		at least - 86 dBm	
4	Physical channel availability	11.6	m		n/a	
5	Synchronisation window (synchronised reference timer)	11.7	m		at least \pm 4 bits	
6	Synchronisation window (not synchronised reference timer)	11.7	m		at least \pm 10 bits	
7	User controlled volume control	12.2	m		RLR _H decrease < 6dB	

History

Document history			
June 1995	Public Enquiry	PE 85:	1995-06-05 to 1995-09-29
May 1996	Vote	V 102:	1996-05-06 to 1996-08-09