



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 504

September 1995

Second Edition

Source: ETSI TC-SMG

Reference: RE/SMG-010206P

ICS: 33.060.50

Key words: European digital cellular telecommunications system, Global System for Mobile communications (GSM)

**European digital cellular telecommunications system (Phase 2);
Types of Mobile Stations (MS)
(GSM 02.06)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1995. All rights reserved.

Contents

Foreword	5
1 Introduction.....	7
1.1 Scope.....	7
1.2 Normative references	7
1.3 Definitions and abbreviations.....	7
2 General.....	7
3 Mobile Station attributes.....	7
3.1 MS service access configuration	7
3.2 MS access capability	8
3.2.1 Frequency Bands	8
3.2.2 Full Rate/Half Rate Services	8
3.3 Definition of a hand-held MS.....	8
3.4 Definition of a vehicular mounted MS	8
4 Mobile station output and power control.....	9
5 Configuration possibilities.....	9
History.....	10

Blank page

Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) Technical Committee (TC) of the European Telecommunications Standards Institute (ETSI).

This ETS defines typical attributes of different types of Mobile Stations (MS) used with GSM and DCS1800 PLMNs within the European digital cellular telecommunications system (Phase 2). This ETS corresponds to GSM technical specification GSM 02.06 version 4.3.0.

The specification from which this ETS has been derived was originally based on CEPT documentation, hence the presentation of this ETS may not be entirely in accordance with the ETSI/PNE rules.

Reference is made within this ETS to GSM-TSs (NOTE).

NOTE: TC-SMG has produced documents which give the technical specifications for the implementation of the European digital cellular telecommunications system. Historically, these documents have been identified as GSM Technical Specifications (GSM-TSs). These TSs may have subsequently become I-ETTs (Phase 1), or ETSS (Phase 2), whilst others may become ETSI Technical Reports (ETRs). GSM-TSs are, for editorial reasons, still referred to in GSM ETSS.

Transposition dates	
Date of adoption of this ETS:	30 September 1995
Date of latest announcement of this ETS (doa):	31 December 1995
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	30 June 1996
Date of withdrawal of any conflicting National Standard (dow):	30 June 1996

Blank page

1 Introduction

1.1 Scope

The purpose of this ETS is to describe typical attributes of different types of Mobile Stations (MS) to be used on GSM and DCS 1800 PLMNs.

Manufacturers and customers may choose any appropriate combination of these attributes in order to fulfil their need while utilizing the services offered through a GSM or a DCS 1800 PLMN. This is not an exhaustive list of attributes or types of Mobile Station. Type approval of Mobile Stations is addressed in GSM 11.10.

1.2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] GSM 01.04 (ETR 100): "European digital cellular telecommunication system (Phase 2); Abbreviations and acronyms".
- [2] GSM 04.03 (ETS 300 552): "European digital cellular telecommunication system (Phase 2); Mobile Station - Base Station System (MS-BSS) interface Channel structures and access capabilities".
- [3] GSM 04.08 (ETS 300 557): "European digital cellular telecommunication system (Phase 2); Mobile radio interface layer 3 specification".
- [4] GSM 05.05 (ETS 300 577): "European digital cellular telecommunication system (Phase 2); Radio transmission and reception".
- [5] GSM 11.10 (ETS 300 607): "European digital cellular telecommunication system (Phase 2); Mobile Station (MS) conformity specification".

1.3 Definitions and abbreviations

Abbreviations used in this document are listed in GSM 01.04.

2 General

The term Mobile Station is taken to mean equipment necessary to access GSM PLMN telecommunication services. It includes the mobile termination and also may include Terminal Equipments and Terminal Adaptors. Some of the characteristics of the configuration in use at any time will be reflected in the Mobile Station Class Mark (see GSM 04.08). A Mobile Station is characterised by a set of attributes defined in Section 3.

3 Mobile Station attributes

The list of Mobile Station attributes is as follows:

- MS service access configuration;
- MS access capability;
- Modes of Use.

3.1 MS service access configuration

Service access configuration must suit the requirements of the customer and will depend on the combination of tele-, bearer and supplementary services to be used. The actual configuration will depend on the manufacturers' implementation and may comprise a single unit or a mobile termination unit with additional Terminal Equipment and/or Terminal Adaptors.

3.2 MS access capability

The Mobile Station access capability is defined in GSM 04.03 Channel Structures and Access Capability, and describes the limitation put on the simultaneous provision at a given time of tele- or bearer services.

3.2.1 Frequency Bands

Three frequency bands are defined:

- i) Standard GSM Band;
- ii) Extended GSM Band (includes standard band);
- iii) DCS1800 Band.

Mobile Stations may support one or more of these bands.

If the MS is capable of both GSM and DCS-1800 operation, then it shall provide internally either a manual or automatic procedure to select the type of network to be used. Once the network type has been selected, the MS shall comply with all specifications relevant to that network. Use of GSM and DCS-1800 modes simultaneously is not supported.

NOTE: The network does not provide any functionality to manage dual mode GSM and DCS-1800 MS.

3.2.2 Full Rate/Half Rate Services

Both Full Rate and Half Rate services are specified. For each basic service, they may be supported by a mobile station on full rate, full and half rate, or not at all. MSs supporting services using signalling modes only are also permitted.

3.3 Definition of a hand-held MS

In this standard, a handheld station is an MS where the used antenna is directly attached to the portion of the equipment containing the acoustic transducers for speech (this condition applies only to speech mobile stations).

3.4 Definition of a vehicular mounted MS

In this standard, a vehicular mounted MS is an MS where the used antenna is physically mounted to the outside of a vehicle. Vehicles include, for example, trucks, buses, trains and ships.

4 Mobile station output and power control

GSM and DCS MS are categorized into classes according to their maximum output power as defined in GSM 05.05. The mean output power for each of these classes is as follows:

MS class	Nominal maximum mean power (milliwatts)	
	Full rate	Half rate
GSM class 2	960	500
GSM class 3	600	312
GSM class 4	240	125
GSM class 5	96	50
DCS class 1	120	62
DCS class 2	30	16
DCS class 3	480	250

GSM and DCS 1800 Mobile stations must be capable of reducing transmitter output power on command from a base station. See GSM 05.05.

5 Configuration possibilities

Any given configuration will be a combination of attributes mentioned in Section 3 above and may include additional features e.g. payphones.

A GSM handheld MS shall only be of GSM class 4 or 5. A DCS handheld MS shall only be DCS of class 1 or 2.

A DCS MS of DCS class 3 shall only be vehicular mounted.

History

Document history	
October 1993	Public Enquiry PE 51: 1993-11-01 to 1994-02-25
May 1994	Vote V 59: 1994-06-27 to 1994-09-02
September 1994	First Edition
May 1995	Unified Approval Procedure UAP 29: 1995-05-22 to 1995-09-15
September 1995	Second Edition
November 1995	Converted into Adobe Acrobat Portable Document Format (PDF)