



AMENDMENT

ETS 300 511

A1

March 1995

Source: ETSI TC-SMG

Reference: RE/SMG-010230P

ICS: 33.060.20

Key words: European digital cellular communications system, Global System for Mobile communications (GSM)

**This amendment A1 modifies
the European Telecommunication Standard ETS 300 511 (1994)**

**European digital cellular telecommunications system (Phase 2);
Man Machine Interface (MMI) of the Mobile Station (MS);
(GSM 02.30)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1995. All rights reserved.

Foreword

This Amendment to ETS 300 511 (1994) has been produced by the Special Mobile Group (SMG) Technical Committee of the European Telecommunications Standards Institute (ETSI).

This Amendment to ETS 300 511 (1994) corresponds to the changes to GSM Technical Specification (GSM-TS) 02.30 from version 4.11.1 to version 4.12.0, as approved by TC-SMG.

This Amendment modifies pages 15 and 19 of ETS 300 511 (1994).

Amendments

Page 15, subclause 4.5.3.2.

Action by the MS, item b), delete the paragraph:

"it shall be interpreted by the MS as Unstructured SS Data and sent transparently towards the network".

Insert the paragraph:

"it shall be interpreted by the MS as Unstructured SS Data and sent transparently towards the network, unless the MS is not engaged in a call and the first digit of the two character entry, followed by SEND, is a "1". In this case the MS shall transmit this as a call set-up request".

Page 19, subclause 4.7.

Replace the existing subclause 4.7 with the following new subclause 4.7:

4.7. Presentation of IMEI

The following procedure shall instruct the ME to display its IMEI:

*#06#

The procedure shall be accepted and performed with and without an inserted SIM. The ME shall then display the 14 digits of the IMEI (not including the spare digit), the Check Digit and optionally the Software Version Number as defined in GSM 02.16 (as a single string, in that order).

History

Document history	
September 1994	First Edition
March 1995	Amendment 1 to First Edition of ETS 300 511
November 1995	Converted into Adobe Acrobat Portable Document Format (PDF)