



**E**UROPEAN  
**T**ELECOMMUNICATION  
**S**TANDARD

**ETS 300 526**

September 1994

---

Source: ETSI TC-SMG

Reference: GSM 03.08

ICS: 33.060.30

**Key words:** European digital cellular telecommunications system, Global System for Mobile communications (GSM)

**European digital cellular telecommunications system (Phase 2);  
Organisation of subscriber data  
(GSM 03.08)**

**ETSI**

European Telecommunications Standards Institute

**ETSI Secretariat**

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

---

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1994. All rights reserved.



## Contents

Foreword .....		5
0	General.....	7
	0.1 Scope.....	7
	0.2 Normative references .....	7
	0.3 Definitons and abbreviations.....	8
1	Introduction.....	8
	1.1 Definition .....	8
	1.2 Storage facilities.....	9
	1.3 Subscriber data in functional units other than the HLR & the VLR .....	9
2	Definition of subscriber data.....	9
	2.1 Data related to identification and numbering .....	9
	2.1.1 International mobile subscriber identity (IMSI) .....	9
	2.1.2 Mobile Station International ISDN Number (MSISDN).....	9
	2.1.3 MSISDNs for multinumering option.....	9
	2.1.3.1 The Basic MSISDN Indicator.....	9
	2.1.3.2 The MSISDN-Alert Indicator.....	9
	2.1.4 Temporary mobile subscriber identity (TMSI) .....	10
	2.1.5 Local Mobile Station Identity (LMSI).....	10
	2.2 Data related to Mobile Station types .....	10
	2.2.1 Mobile Station Category .....	10
	2.3 Data related to authentication and ciphering .....	10
	2.3.1 Random Number (RAND), Signed Response (SRES) and Ciphering Key (Kc).....	10
	2.3.2 The Ciphering Key Sequence Number (CKSN) .....	10
	2.4 Data related to roaming .....	10
	2.4.1 Mobile Station Roaming Number (MSRN) .....	10
	2.4.2 Location Area Identification (LAI) .....	10
	2.4.3 VLR number .....	11
	2.4.4 MSC number .....	11
	2.4.5 HLR number .....	11
	2.4.6 Subscription restriction .....	11
	2.4.7 Regional Subscription Information .....	11
	2.4.7.1 RSZI lists .....	12
	2.4.7.2 Zone Code List .....	12
	2.4.8 MSC area restricted flag.....	12
	2.4.9 LA not allowed flag .....	12
	2.4.10 Service restriction data induced by roaming .....	12
	2.4.10.1 ODB-induced barring data .....	13
	2.4.10.2 Roaming restriction due to unsupported feature .....	13
	2.5 Data related to basic services.....	13
	2.5.1 Provision of bearer service.....	13
	2.5.2 Provision of teleservice .....	13
	2.5.3 Bearer capability allocation.....	13
	2.6 Data related to supplementary services.....	14
	2.7 Mobile station status data .....	14
	2.7.1 IMSI detached flag .....	14
	2.7.2 Restoration flags .....	14
	2.7.2.1 Radio Confirmation Indicator .....	14
	2.7.2.2 Subscriber Data Confirmed by HLR indicator.....	14
	2.7.2.3 Location Information Confirmed in HLR Indicator .....	14
	2.7.2.4 Check supplementary services Indicator .....	14
	2.7.3 MS purged flag .....	15
	2.8 Data related to operator determined barring.....	15

2.8.1	Subscriber status.....	15
2.8.2	Operator determined barring general data .....	15
2.8.2.1	Barring of outgoing calls .....	15
2.8.2.2	Barring of incoming calls.....	15
2.8.2.3	Barring of roaming .....	15
2.8.2.4	Barring of premium rate calls.....	16
2.8.2.5	Barring of supplementary services management .....	16
2.8.3	Operator determined barring PLMN-specific data.....	16
2.9	Data related to handover.....	16
2.9.1	Handover number.....	16
2.10	Data related to short message support.....	16
2.10.1	Messages Waiting Data (MWD).....	16
2.10.2	Mobile Station Not Reachable Flag (MNRF) .....	16
2.10.3	Memory Capacity Exceeded Flag (MCEF) .....	17
3	Summary of data stored in location registers .....	17
4	Accessing subscriber data.....	17
	History.....	19

## Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) Technical Committee (TC) of the European Telecommunications Standards Institute (ETSI).

This ETS defines the organisation of subscriber data for the European digital cellular telecommunications system (Phase 2). This ETS corresponds to GSM Technical Specification (GSM-TS) GSM 03.08 version 4.7.1.

The specification from which this ETS has been derived was originally based on CEPT documentation, hence the presentation of this ETS may not be entirely in accordance with the ETSI/PNE rules.

Reference is made within this ETS to GSM-TSs (NOTE).

NOTE: TC-SMG has produced documents which give the technical specifications for the implementation of the European digital cellular telecommunications system. Historically, these documents have been identified as GSM Technical Specifications (GSM-TSs). These TSs may have subsequently become I-ETTs (Phase 1), or ETTs (Phase 2), whilst others may become ETSI Technical Reports (ETRs). GSM-TSs are, for editorial reasons, still referred to in GSM ETTs.

Blank page

## 0 General

### 0.1 Scope

The scope of this Recommendation is to provide details concerning information to be stored in home location registers and visitor location registers concerning mobile subscriber.

Section 2 contains all details concerning the definition of the parameters, often given by reference to other specifications, and where the parameter is to be stored.

Table 1 in section 3 gives a summary overview and section 4 identifies the reference information required for accessing the information.

### 0.2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] GSM 01.04 (ETR 100): "European digital cellular telecommunications system (Phase 2); Abbreviations and acronyms".
- [2] GSM 02.02 (prETS 300 501): "European digital cellular telecommunications system (Phase 2); Bearer Services (BS) supported by a GSM Public Land Mobile Network (PLMN)".
- [3] GSM 02.03 (prETS 300 502): "European digital cellular telecommunications system (Phase 2); Teleservices supported by a GSM Public Land Mobile Network (PLMN)".
- [4] GSM 02.04 (prETS 300 503): "European digital cellular telecommunications system (Phase 2); General on supplementary services".
- [5] GSM 03.03 (prETS 300 523): "European digital cellular telecommunications system (Phase 2); Numbering, addressing and identification".
- [6] GSM 03.07 (prETS 300 525): "European digital cellular telecommunications system (Phase 2); Restoration procedures".
- [7] GSM 03.09 (prETS 300 527): "European digital cellular telecommunications system (Phase 2); Handover procedures".
- [8] GSM 03.12 (prETS 300 530): "European digital cellular telecommunications system (Phase 2); Location registration procedures".
- [9] GSM 03.15 (prETS 300 533): "European digital cellular telecommunications system (Phase 2); Technical realization of operator determined barring".
- [10] GSM 03.20 (prETS 300 534): "European digital cellular telecommunications system (Phase 2); Security related network functions".
- [11] GSM 03.40 (prETS 300 536): "European digital cellular telecommunications system (Phase 2); Technical realization of the Short Message Service (SMS) Point to Point (PP)".
- [12] GSM 03.81 (prETS 300 542): "European digital cellular telecommunications system (Phase 2); Line identification supplementary services - Stage 2".

- [13] GSM 03.82 (prETS 300 543): "European digital cellular telecommunications system (Phase 2); Call Forwarding (CF) supplementary services - Stage 2".
- [14] GSM 03.83 (prETS 300 544): "European digital cellular telecommunications system (Phase 2); Call Waiting (CW) and Call Hold (HOLD) supplementary services - Stage 2".
- [15] GSM 03.84 (prETS 300 545): "European digital cellular telecommunications system (Phase 2); MultiParty (MPTY) supplementary services - Stage 2".
- [16] GSM 03.85 (prETS 300 546): "European digital cellular telecommunications system (Phase 2); Closed User Group (CUG) supplementary services - Stage 2".
- [17] GSM 03.86 (prETS 300 547): "European digital cellular telecommunications system (Phase 2); Advice of Charge (AoC) supplementary services - Stage 2".
- [18] GSM 03.88 (prETS 300 548): "European digital cellular telecommunications system (Phase 2); Call Barring (CB) supplementary services - Stage 2".
- [19] GSM 03.90 (prETS 300 549): "European digital cellular telecommunications system (Phase 2); Unstructured supplementary services operation - Stage 2".
- [20] GSM 04.08 (prETS 300 557): "European digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 specification".
- [21] GSM 09.02 (prETS 300 599): "European digital cellular telecommunications system (Phase 2); Mobile Application Part (MAP) specification".
- [22] GSM 09.07 (prETS 300 604): "European digital cellular telecommunications system (Phase 2); General requirements on interworking between the Public Land Mobile Network (PLMN) and the Integrated Services Digital Network (ISDN) or Public Switched Telephone Network (PSTN)".
- [23] GSM 12.03 (prETS 300 614): "European digital cellular telecommunications system (Phase 2); Security management".
- [24] CCITT Recommendation Q.763: "Specifications of Signalling System No.7; Formats and codes".

### **0.3 Definitons and abbreviations**

Abbreviations used in this specification are listed in GSM 01.04.

## **1 Introduction**

### **1.1 Definition**

The term subscriber data is used to designate all information associated with a subscription which is required for service provisions, identification, authentication, routing, call handling, charging, operation and maintenance purposes. Some subscriber data are referred to as permanent subscriber data, i.e. they can only be changed by administration means. Other data are temporary subscriber data which may change as a result of normal operation of the system.

Unless shown to be conditional, all data items are considered to be mandatory.



## 1.2 Storage facilities

This Technical Specification considers subscriber data stored in two types of functional unit:

- Home location register (HLR) which contains all permanent subscriber data and all relevant temporary subscriber data for all mobile subscribers permanently registered in the HLR.
- Visitor location register (VLR) which contains all subscriber data required for call handling and other purposes for mobile subscribers currently located in the area controlled by the VLR.

## 1.3 Subscriber data in functional units other than the HLR & the VLR

The individual Subscriber Authentication Key Ki defined in Technical Specification GSM 03.20 is stored in the Authentication Centre AuC; it is also stored in the SIM and therefore available in the MS. Version numbers of algorithms A3 and A8 may also be stored in the AuC.

NOTE: It is for further study whether or not other types of functional units containing mobile subscriber parameters are to be included in this Recommendation. Such units could include encryption key distribution centres, maintenance centres, etc.

## 2 Definition of subscriber data

### 2.1 Data related to identification and numbering

#### 2.1.1 International mobile subscriber identity (IMSI)

International mobile subscriber identity (IMSI) is defined in TS GSM 03.03.

IMSI is permanent subscriber data. IMSI is stored in both HLR and VLR.

#### 2.1.2 Mobile Station International ISDN Number (MSISDN)

Mobile Station International ISDN Number (MSISDN) is defined in TS GSM 03.03.

The MSISDN number is permanent subscriber data and is stored in both HLR and VLR.

If the multinumnering option applies, the MSISDN stored in the VLR is the Basic MSISDN, see section 2.1.3.1.

#### 2.1.3 MSISDNs for multinumnering option

If the HPLMN allocates different MSISDNs for different Basic Services (see TS GSM 09.07), these numbers are conditionally stored as permanent data in the HLR.

##### 2.1.3.1 The Basic MSISDN Indicator

The Basic MSISDN is defined in TS GSM 03.12. The Basic MSISDN indicator marks the MSISDN to be used as Basic MSISDN.

It is permanent subscriber data stored conditionally in the HLR.

##### 2.1.3.2 The MSISDN-Alert Indicator

The MSISDN-Alert is defined in TS GSM 03.40. The MSISDN-Alert indicator marks the MSISDN to be used as MSISDN-Alert.

It is permanent subscriber data stored conditionally in the HLR.

#### **2.1.4 Temporary mobile subscriber identity (TMSI)**

Temporary mobile subscriber identity (TMSI) is defined in TS GSM 03.03.

The TMSI is temporary subscriber data and is conditionally stored in the VLR.

#### **2.1.5 Local Mobile Station Identity (LMSI)**

Local Mobile Station Identity (LMSI) is defined in TS GSM 03.03. The LMSI is temporary subscriber data. The LMSI may be stored in the VLR; if it is received in the HLR it must be stored there.

### **2.2 Data related to Mobile Station types**

#### **2.2.1 Mobile Station Category**

Mobile Station Category has a structure identical to that of "Calling Party's Category" defined in ISUP (CCITT Recommendation Q.763).

The following values of category shall be supported:

- ordinary subscriber.

The category is assigned per IMSI.

Mobile Station Category is permanent subscriber data and is stored in HLR and VLR.

### **2.3 Data related to authentication and ciphering**

#### **2.3.1 Random Number (RAND), Signed Response (SRES) and Ciphering Key (Kc)**

Random Number (RAND), Signed Response (SRES) and Ciphering Key (Kc) form a triplet of vectors used for authentication and encryption as defined in TS GSM 03.20.

A set of up to 5 triplet values is calculated in the AuC (see TS GSM 12.03), provided to and stored in the HLR and sent to the VLR on request. These data are temporary subscriber data stored in the HLR and the VLR.

#### **2.3.2 The Ciphering Key Sequence Number (CKSN)**

The Ciphering Key Sequence Number (CKSN) is used to ensure authentication information (Kc) consistency between the MS and the VLR.

CKSN and its handling are defined in TSs GSM 04.08 and GSM 03.20. It is a temporary subscriber data and is stored in the VLR.

### **2.4 Data related to roaming**

#### **2.4.1 Mobile Station Roaming Number (MSRN)**

Mobile Station Roaming Number (MSRN) is defined in TS GSM 03.03.

NOTE: There may be more than one MSRN simultaneously per IMSI.

The MSRN is short-lived temporary subscriber data stored in the VLR.

#### **2.4.2 Location Area Identification (LAI)**

Location Area Identification (LAI) is defined in TS GSM 03.03.

The LAI is temporary subscriber data and is stored in the VLR.

### **2.4.3 VLR number**

VLR number is defined in TS GSM 03.03.

The VLR number is temporary subscriber data and is stored in the HLR. Absence of the VLR number indicates that the mobile station is deregistered in the HLR.

### **2.4.4 MSC number**

MSC number is defined in TS GSM 03.03.

The MSC number is temporary subscriber data and is stored in the HLR and conditionally in the VLR.

### **2.4.5 HLR number**

HLR number is defined in TS GSM 03.03.

The HLR number may be stored in the VLR. It is received as a mandatory parameter in the updating location accepted message. This data may be needed to retrieve subscribers to be restored after HLR reset.

The HLR number is temporary subscriber data and may optionally be stored in the VLR.

### **2.4.6 Subscription restriction**

Subscription restriction is a parameter indicating whether or not certain restrictions apply to the subscription. The parameter takes either of the following values (see also Technical Specification GSM 02.13):

accessible area for service:

- all GSM PLMNs,
- one national and all foreign GSM PLMNs,
- regionally restricted (part of a GSM PLMN in one country),
- regionally restricted plus all other GSM PLMNs.

The HLR associates location updating information with subscription restriction. It deregisters the MS if the PLMN is not allowed and sets the MSC area restricted flag if the MSC area is not allowed, see section 2.4.8.

Handling of Regionally Restricted Subscription is defined in section 2.4.7. By operator agreement, regional restriction in parts of different GSM PLMNs is also possible.

The subscription restriction is permanent subscriber data and is stored in the HLR.

### **2.4.7 Regional Subscription Information**

If a mobile subscriber has a regional subscription, the HLR shall store a list of up to ten Regional Subscription Zone Identities (RSZIs) per Network Destination Code (NDC) of the PLMN involved. The structure of RSZI is defined in Technical Specification GSM 03.03; since it is composed of the PLMN identification (CC NDC) and the Zone Code it is sufficient to store the Zone Code List per CC NDC.

On updating the VLR, the HLR identifies the VPLMN and NDC given by the VLR number and transfers the pertaining Zone Code List to the VLR. The VLR derives from the Zone Code List the allowed and not allowed MSC areas and location areas; it sets the "LA not allowed flag" should the target LAI of the mobile station be excluded, and it informs the HLR should the MSC area be excluded. Signalling of cause value "location area not allowed" towards the mobile station is defined in Technical Specifications GSM 09.02 and GSM 04.08.

#### **2.4.7.1 RSZI lists**

The RSZI lists are permanent subscriber data stored conditionally in the HLR.

#### **2.4.7.2 Zone Code List**

The VLR shall store as permanent and conditional subscriber data at least those Zone Codes by which it is affected.

#### **2.4.8 MSC area restricted flag**

MSC area restricted flag is a parameter which can take either of the following values:

- MSC area restricted;
- MSC area not restricted.

The parameter is set in the HLR during updating of the VLR. Handling of unsupported services and information received from the VLR based on national roaming or regionally restricted subscription (section 2.4.7) determine its value. The parameter contributes to the "MS Not Reachable" state for handling of terminating traffic in the HLR. The default value is "MSC area not restricted".

The MSC area restricted flag is temporary subscriber data and is contained in the HLR.

#### **2.4.9 LA not allowed flag**

The LA not allowed flag is set in the VLR depending on National Roaming, Regionally Restricted Subscription and Roaming Restriction Due To UnSupported Feature, see TS GSM 09.02. It is applied to restrict service on a location area basis.

The LA not allowed flag is temporary subscriber data stored in the VLR.

#### **2.4.10 Service restriction data induced by roaming**

If in the course of roaming or at updating of the VLR the HLR is informed that the VLR does not support certain sensitive services or features, the HLR takes appropriate measures to restrict service for the mobile station in that VLR by setting and sending network induced replacing services such as barring programs or the roaming restriction for the MSC area.

These network-induced data have to be kept separate in the HLR, and where possible as discussed below in the VLR, from the permanent subscriber data of the call barring supplementary services, from the barring related data that can be modified by the subscriber or from the permanent regional subscription data. The network induced data take precedence over the subscriber data of the user where they are in conflict. If, in the course of roaming, restrictions caused by a service are lifted, the original subscriber data have to be re-installed both in HLR and in VLR, regarding any remaining restrictions due to other service replacements.

All network-induced restriction data are temporary subscriber data.

For ODB, TS GSM 03.15 recommends mainly barring programs to replace this feature. The replacing barring data are conditionally stored in the HLR and VLR. In the VLR they cannot be distinguished from the permanent supplementary services data with the available signalling means, and no additional storage is needed. Interrogation shall reflect in both HLR and VLR the valid setting of the replacing temporary data; to prevent interference with Subscriber Controlled Input and to inform the customer on the restriction, the "control of barring services" subscription option is also temporarily set to the value "by the service provider".

CUG is also replaced by Outgoing Call Barring as described in TS GSM 03.85.

Roaming restriction in the MSC area due to unsupported features is used to replace AoCC, see TS GSM 03.86, and Zone Codes for regional subscription, see section 2.4.7 and TS GSM 09.02. A flag in

HLR and VLR, see section 2.4.10.2, collects the sources of network-induced roaming restriction which are also kept separate by the HLR.

#### **2.4.10.1 ODB-induced barring data**

ODB-induced barring data are temporary data stored conditionally in the HLR; they include the necessary replacing barring programs for outgoing and incoming calls depending on the ODB profile. The subscription option "control of barring services" is set to "by the service provider". The corresponding barring supplementary services for outgoing calls are set by the HLR and sent to the VLR.

#### **2.4.10.2 Roaming restriction due to unsupported feature**

Roaming restriction due to unsupported feature is a parameter which indicates that one or several services or features are not supported by the MSC, resulting in roaming restriction in the MSC area. It can take either of the following values:

- roaming restricted;
- roaming not restricted.

The parameter governs the "LA not allowed flag" in the VLR (see section 2.4.9) and the "MSC area restricted flag" in the HLR (see section 2.4.8), see TS GSM 09.02.

The flag "roaming restriction due to unsupported feature" is temporary subscriber data stored in the VLR and in the HLR.

### **2.5 Data related to basic services**

#### **2.5.1 Provision of bearer service**

Provision of bearer service is a parameter identifying whether a bearer service is provisioned to the mobile subscriber or not. This provision can be achieved through subscription of the mobile subscriber or the bearer service can be generally available. The parameter "provision of bearer service" must be set for the bearer service defined in Technical Specification GSM 02.02 for which a subscription is required.

Provision of bearer service is permanent subscriber data and is stored in the HLR and VLR.

#### **2.5.2 Provision of teleservice**

Provision of teleservice is a parameter identifying whether a teleservice is provisioned to the mobile subscriber or not. This provision can be achieved through subscription of the mobile subscriber or the teleservice can be generally available. The parameter "provision of teleservice" must be set for the teleservices defined in Technical Specification GSM 02.03 for which a subscription is required.

Provision of teleservice is permanent subscriber data and is stored in the HLR and VLR.

#### **2.5.3 Bearer capability allocation**

Bearer capability allocation is a parameter stored against each ISDN number in the case when the Home PLMN allocates one directory number per teleservice and bearer service. In this case it is used to permit the establishment of the correct bearer capability on the connection to the MS. (See Technical Specification GSM 09.07). The bearer capability allocation is not required when the Home PLMN only allocates one directory number per subscriber for all bearer services and teleservices. It is permanent data stored conditionally in both HLR and VLR.

## **2.6 Data related to supplementary services**

Subscriber data related to supplementary services are contained in the GSM 03.8x and 03.9x series of Technical Specifications, that is GSM 03.81 and following describing the network functionality of supplementary services.

There is no data type which is mandatory for all supplementary services; note that the provision status is mandatory for all supplementary services except CUG, TS GSM 03.85. All other data are conditional depending on the provision. The data settable but by O&M are the permanent data while the temporary data are those that can be modified by subscriber control in the mobile station.

## **2.7 Mobile station status data**

### **2.7.1 IMSI detached flag**

IMSI detached flag is a parameter indicating that the MS is in the IMSI detached state, i.e. the subscriber is no longer reachable. For definition and handling see TS GSM 03.12 and TS GSM 09.02. The parameter takes the following values:

- IMSI detached;
- IMSI attached.

The parameter is temporary subscriber data and is stored conditionally in the VLR.

### **2.7.2 Restoration flags**

In the case of VLR or HLR failure, location register data have to be restored as described in Technical Specification GSM 03.07 and GSM 09.02. The following flags are used for this purpose.

#### **2.7.2.1 Radio Confirmation Indicator**

Radio Confirmation Indicator is a restoration indicator defined in Technical Specification GSM 03.07.

It is temporary subscriber data, stored in the VLR.

#### **2.7.2.2 Subscriber Data Confirmed by HLR indicator**

Subscriber Data Confirmed by HLR indicator is a restoration indicator defined in Technical Specification GSM 03.07.

It is temporary subscriber data, stored in the VLR.

#### **2.7.2.3 Location Information Confirmed in HLR Indicator**

Location Information Confirmed in HLR Indicator is a restoration indicator defined in Technical Specification GSM 03.07.

It is temporary subscriber data, stored in the VLR.

#### **2.7.2.4 Check supplementary services Indicator**

Check supplementary services Indicator is a restoration indicator defined in Technical Specification GSM 03.07.

It is temporary subscriber data and is stored in the HLR.

### **2.7.3 MS purged flag**

MS purged flag is set in the HLR per IMSI record in order to indicate that the subscriber data for the MS concerned have been purged in the VLR. The parameter takes the following values:

- MS purged;
- MS not purged.

The default value is "MS not purged". The parameter is temporary subscriber data, stored in the HLR.

## **2.8 Data related to operator determined barring**

### **2.8.1 Subscriber status**

Subscriber status is a flag which indicates whether the subscriber is subject to operator determined barring.

It is permanent subscriber data, and is conditionally stored in the HLR and the VLR.

### **2.8.2 Operator determined barring general data**

#### **2.8.2.1 Barring of outgoing calls**

Barring of outgoing calls indicates which one of the following categories of operator determined barring of outgoing calls applies to the subscriber:

- No barring of outgoing calls;
- Barring of all outgoing calls;
- Barring of all outgoing international calls;
- Barring of all outgoing international calls except those directed to the home PLMN country.

It is permanent data, and is stored conditionally in the HLR and the VLR.

#### **2.8.2.2 Barring of incoming calls**

Barring of incoming calls indicates which one of the following categories of operator determined barring of incoming calls applies to the subscriber:

- No barring of incoming calls;
- Barring of all incoming calls;
- Barring of all incoming calls when roaming outside the home PLMN country.

It is permanent data, and is stored conditionally in the HLR.

#### **2.8.2.3 Barring of roaming**

Barring of roaming indicates which one of the following categories of operator determined barring of roaming applies to the subscriber:

- No barring of roaming;
- Barring of roaming outside the home PLMN;
- Barring of roaming outside the home PLMN country.

It is permanent data, and is stored conditionally in the HLR.

#### **2.8.2.4 Barring of premium rate calls**

Barring of premium rate calls indicates which one of the following categories of operator determined barring of premium rate calls applies to the subscriber:

- No barring of premium rate calls;
- Barring of premium rate (information) calls;
- Barring of premium rate (entertainment) calls;
- Barring of premium rate (information) calls and premium rate (entertainment) calls.

It is permanent subscriber data, and is stored conditionally in the HLR and the VLR.

#### **2.8.2.5 Barring of supplementary services management**

Barring of supplementary services management is a flag which indicates whether the subscriber is subject to operator determined barring of supplementary services management.

It is permanent subscriber data, and stored conditionally in the HLR and the VLR.

#### **2.8.3 Operator determined barring PLMN-specific data**

Operator determined barring PLMN-specific data indicates which of the following categories of operator specific barring, in any combination, applies to the subscriber:

- Operator specific barring (type 1);
- Operator specific barring (type 2);
- Operator specific barring (type 3);
- Operator specific barring (type 4).

It is permanent subscriber data. It is stored conditionally in the HLR, and in the VLR when the subscriber is registered in the home PLMN.

### **2.9 Data related to handover**

#### **2.9.1 Handover number**

Handover number is defined in TS GSM 03.03 and its use is specified in TS GSM 03.09.

The Handover Number is short-lived subscriber data and is stored in the VLR.

### **2.10 Data related to short message support**

#### **2.10.1 Messages Waiting Data (MWD)**

Messages Waiting Data (MWD) is defined in TS GSM 03.40.

The MWD is temporary subscriber data, and is conditionally stored in the HLR.

#### **2.10.2 Mobile Station Not Reachable Flag (MNRF)**

Mobile Station Not Reachable Flag (MNRF) is defined in TS GSM 03.40.

The MNRF is temporary data. It is stored in the VLR and conditionally stored in the HLR.



### 2.10.3 Memory Capacity Exceeded Flag (MCEF)

Memory Capacity Exceeded Flag (MCEF) is defined in TS GSM 03.40.

The MCEF is temporary subscriber data and is conditionally stored in the HLR.

## 3 Summary of data stored in location registers

Table 1 gives an overview of data that may be stored in location registers. In the Table M = mandatory means that this parameter is stored for all subscribers and C = conditional means that the parameter is subject to some condition (e.g. subscription, reception of optional message or short-lived data). The type indication indicates whether the subscriber data is temporary (T) or permanent (P) data, where permanent data can be set and modified but by the operator, whereas the temporary data are set and changed automatically by network functions.

## 4 Accessing subscriber data

It shall be possible to retrieve or store subscriber data concerning a specific MS from the HLR by use of each of the following references:

- International Mobile Subscriber Identity (IMSI);
- Mobile Station ISDN Number (MSISDN).

It shall be possible to retrieve or store subscriber data concerning a specific MS from the VLR by use of each of the following references:

- International Mobile Subscriber Identity (IMSI);
- Temporary Mobile Subscriber Identity (TMSI).

Table 1: Overview of data stored in location registers

PARAMETER	SECTION	HLR	VLR	TYPE	
IMSI	2.1.1	M	M	P	
International MS ISDN number	2.1.2	M	M	P	
multinumbering MSISDNs	2.1.3	C	-	P	
Basic MSISDN indicator	2.1.3.1	C	-	P	
MSISDN-Alert indicator	2.1.3.2	C	-	P	
TMSI	2.1.4	-	C	T	
LMSI	2.1.5	C	C	T	Note
Mobile Station Category	2.2.1	M	M	P	
RAND/SRES and Kc	2.3.2	M	M	T	
Ciphering Key Sequence Number	2.3.3	-	M	T	
MSRN	2.4.1	-	C	T	Note
Location Area Identity	2.4.2	-	M	T	
VLR number	2.4.3	M	-	T	Note
MSC number	2.4.4	M	C	T	
HLR number	2.4.5	-	C	T	
Subscription restriction	2.4.6	C	-	P	
RSZI lists	2.4.7.1	C	-	P	
Zone Code List	2.4.7.2	-	C	P	
MSC area restricted flag	2.4.8	M	-	T	
LA not allowed flag	2.4.9	-	M	T	
ODB-induced barring data	2.4.10.1	C	-	T	
Roam. restr. due to unsupported feature	2.4.10.2	M	M	T	
Provision of bearer service	2.5.1	M	M	P	
Provision of teleservice	2.5.2	M	M	P	
BC allocation	2.5.3	C	C	P	
IMSI detached flag	2.7.1	-	C	T	
Radio Confirmation Indicator	2.7.2.1	-	M	T	
Subscriber Data Cnf by HLR Indicator	2.7.2.2	-	M	T	
Location Info Cnf in HLR Indicator	2.7.2.3	-	M	T	
Check Suppl. Services Indicator	2.7.2.4	M	-	T	
MS purged flag	2.7.3	M	-	T	
Subscriber Status	2.8.1	C	C	P	
Barring of outgoing calls	2.8.2.1	C	C	P	
Barring of incoming calls	2.8.2.2	C	-	P	
Barring of roaming	2.8.2.3	C	-	P	
Barring of premium rate calls	2.8.2.4	C	C	P	
Barring of supplementary service management	2.8.2.5	C	C	P	
Operator determined barring PLMN-specific data	2.8.3	C	C	P	
Handover Number	2.9.1	-	C	T	
Messages Waiting Data	2.10.1	C	-	T	
Mobile Station Not Reachable Flag	2.10.2	C	M	T	
Memory Capacity Exceeded Flag	2.10.3	C	-	T	

See section 3 for explanation of M,C,T and P in table 1.

NOTE: For special conditions of storage, see in the indicated section.

## History

Document history	
September 1994	First Edition
October 1995	Converted into Adobe Acrobat Portable Document Format (PDF)