

**E**UROPEAN  
**T**ELECOMMUNICATION  
**S**TANDARD

**ETS 300 553**

September 1994

---

Source: ETSI TC-SMG

Reference: GSM 04.04

ICS: 33.060.30

**Key words:** European digital cellular telecommunications system, Global System for Mobile communications (GSM)

**European digital cellular telecommunications system (Phase 2);  
Layer 1  
General requirements  
(GSM 04.04)**

**ETSI**

European Telecommunications Standards Institute

**ETSI Secretariat**

**Postal address:** F-06921 Sophia Antipolis CEDEX - FRANCE

**Office address:** 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

**X.400:** c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

---

**Copyright Notification:** No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1994. All rights reserved.



## Contents

Foreword.....	5
1 General.....	7
1.1 Scope .....	7
1.2 Normative references .....	7
1.3 Definitions and abbreviations.....	9
2 Interfaces to the physical layer.....	10
2.1 Interface to the Data Link Layer .....	10
2.2 Interface to radio resource management.....	10
2.3 Interface to other functional units.....	10
3 Service of the physical layer.....	11
3.1 Service Access Point.....	11
3.2 Service of the physical layer.....	12
3.2.1 Specific services of the physical layer in the MS .....	12
4 Primitives of the physical layer.....	13
4.1 Generic names of primitives between layers 1 and 2 for the transfer of layer 2 frames:..	13
4.2 Generic names of primitives between layer 1 and the RR- management entity of layer 3	13
4.3 Primitive types .....	14
4.4 Parameter definition .....	15
5 Physical layer procedures .....	16
5.1 States of the physical layer .....	16
5.2 Control procedures.....	16
5.3 Physical layer interface procedures .....	17
6 Physical layer protocol header.....	17
6.1 Physical layer protocol fields and procedures .....	17
7 Block transmission.....	18
7.1 SACCH downlink block format.....	18
7.2 SACCH uplink block format .....	19
7.3 FACCH/SDCCH/CCCH/BCCH/CBCH downlink block format .....	20
7.4 FACCH/SDCCH uplink block format .....	21
7.5 Order of bit transmission .....	22
8 Vocabulary .....	22
History .....	23

Blank page

## Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) Technical Committee (TC) of the European Telecommunications Standards Institute (ETSI).

This ETS defines the services offered by the physical layer (layer 1) of the Mobile Station - Base Station System (MS - BSS) interface within the European digital cellular telecommunications system (Phase 2).

This ETS corresponds to GSM technical specification, GSM 04.04 version 4.0.4.

The specification from which this ETS has been derived was originally based on CEPT documentation, hence the presentation of this ETS may not be entirely in accordance with the ETSI/PNE rules.

Reference is made within this ETS to GSM Technical Specifications (GSM-TSs) (NOTE).

Reference is also made within this ETS to GSM 0x.xx. series. The specifications in the series can be identified, with their full title, within the normative reference Clause of this ETS by the first two digits of their GSM reference number e.g. GSM 09.xx series, refers to GSM 09.01, GSM 09.02 etc.

NOTE: TC-SMG has produced documents which give the technical specifications for the implementation of the European digital cellular telecommunications system. Historically, these documents have been identified as GSM Technical Specifications (GSM-TS). These TSs may have subsequently become I-ETTs (Phase 1), or ETSS (Phase 2), whilst others may become ETSI Technical Reports (ETRs). GSM-TSs are, for editorial reasons, still referred to in GSM ETSS.

Blank page

## 1 General

### 1.1 Scope

This Technical Specification defines the service offered by the physical layer (GSM 05-series of Technical Specifications) of the MS-BS interface (GSM 05- and 04-series of Technical Specifications). Its main objective is to be a guidance for the interface between the GSM Technical Specifications in the 05-series and the 04-series. It also specifies the format of signalling channels and the order of bit transmission.

When the mention for "further study" or "FS" or "FFS" is present throughout this document this means this is not relevant for ETSI-GSM phase 1 standard.

As far as possible, this Technical Specification makes use of the layering principles of the Reference Model for Open System Interconnection (OSI) as contained in CCITT Recommendations X.200 and X.210.

### 1.2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] GSM 01.04 (ETR 100): "European digital cellular telecommunications system (Phase 2); Abbreviations and acronyms".
- [2] GSM 02.11 (prETS 300 507): "European digital cellular telecommunications system (Phase 2); Service accessibility".
- [3] GSM 03.13 (prETS 300 531): "European digital cellular telecommunications system (Phase 2); Discontinuous Reception (DRX) in the GSM system".
- [4] GSM 03.20 (prETS 300 534): "European digital cellular telecommunications system (Phase 2); Security related network functions".
- [5] GSM 04.01 (prETS 300 550): "European digital cellular telecommunications system (Phase 2); Mobile Station - Base Station System (MS - BSS) interface General aspects and principles".
- [6] GSM 04.02 (prETS 300 551): "European digital cellular telecommunications system (Phase 2); GSM Public Land Mobile Network (PLMN) access reference configuration".
- [7] GSM 04.03 (prETS 300 552): "European digital cellular telecommunications system (Phase 2); Mobile Station - Base Station System (MS - BSS) interface Channel structures and access capabilities".
- [8] GSM 04.05 (prETS 300 554): "European digital cellular telecommunications system (Phase 2); Data Link (DL) layer General aspects".
- [9] GSM 04.06 (prETS 300 555): "European digital cellular telecommunications system (Phase 2); Mobile Station - Base Station System (MS - BSS) interface Data Link (DL) layer specification".
- [10] GSM 04.07 (prETS 300 556): "European digital cellular telecommunications system (Phase 2); Mobile radio interface signalling layer 3 General aspects".
- [11] GSM 04.08 (prETS 300 557): "European digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 specification".

- [12] GSM 04.10 (prETS 300 558): "European digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 Supplementary services specification General aspects".
- [13] GSM 04.11 (prETS 300 559): "European digital cellular telecommunications system (Phase 2); Point-to-Point (PP) Short Message Service (SMS) support on mobile radio interface".
- [14] GSM 04.12 (prETS 300 560): "European digital cellular telecommunications system (Phase 2); Short Message Service Cell Broadcast (SMSCB) support on the mobile radio interface".
- [15] GSM 04.13 (prETS 300 561): "European digital cellular telecommunications system (Phase 2); Performance requirements on mobile radio interface".
- [16] GSM 04.21 (prETS 300 562): "European digital cellular telecommunications system (Phase 2); Rate adaption on the Mobile Station - Base Station System (MS - BSS) interface".
- [17] GSM 04.22 (prETS 300 563): "European digital cellular telecommunications system (Phase 2); Radio Link Protocol (RLP) for data and telematic services on the Mobile Station - Base Station System (MS - BSS) interface and the Base Station System - Mobile-services Switching Centre (BSS - MSC) interface".
- [18] GSM 04.80 (prETS 300 564): "European digital cellular telecommunications system (Phase 2); Mobile radio interface layer 3 supplementary services specification Formats and coding".
- [19] GSM 04.81 (prETS 300 565): "European digital cellular telecommunications system (Phase 2); Line identification supplementary services - Stage 3".
- [20] GSM 04.82 (prETS 300 566): "European digital cellular telecommunications system (Phase 2); Call Forwarding (CF) supplementary services - Stage 3".
- [21] GSM 04.83 (prETS 300 567): "European digital cellular telecommunications system (Phase 2); Call Waiting (CW) and Call Hold (HOLD) supplementary services - Stage 3".
- [22] GSM 04.84 (prETS 300 568): "European digital cellular telecommunications system (Phase 2); MultiParty (MPTY) supplementary services - Stage 3".
- [23] GSM 04.85 (prETS 300 569): "European digital cellular telecommunications system (Phase 2); Closed User Group (CUG) supplementary services - Stage 3".
- [24] GSM 04.86 (prETS 300 570): "European digital cellular telecommunications system (Phase 2); Advice of Charge (AoC) supplementary services - Stage 3".
- [25] GSM 04.88 (prETS 300 571): "European digital cellular telecommunications system (Phase 2); Call Barring (CB) supplementary services - Stage 3".
- [26] GSM 04.90 (prETS 300 572): "European digital cellular telecommunications system (Phase 2); Unstructured supplementary services operation - Stage 3".
- [27] GSM 05.01 (prETS 300 573): "European digital cellular telecommunications system (Phase 2); Physical layer on the radio path General description".
- [28] GSM 05.02 (prETS 300 574): "European digital cellular telecommunications system (Phase 2); Multiplexing and multiple access on the radio path".



- [29] GSM 05.03 (prETS 300 575): "European digital cellular telecommunications system (Phase 2); Channel coding".
- [30] GSM 05.04 (prETS 300 576): "European digital cellular telecommunications system (Phase 2); Modulation".
- [31] GSM 05.05 (prETS 300 577): "European digital cellular telecommunications system (Phase 2); Radio transmission and reception".
- [32] GSM 05.08 (prETS 300 578): "European digital cellular telecommunications system (Phase 2); Radio subsystem link control".
- [33] GSM 05.10 (prETS 300 579): "European digital cellular telecommunications system (Phase 2); Radio subsystem synchronisation".
- [34] GSM 05.90 (ETR 108): "European digital cellular telecommunications system (Phase 2); GSM Electro Magnetic Compatibility (EMC) considerations".
- [35] CCITT Recommendation X.200: "Reference Model of Open Systems Interconnection for CCITT Applications".
- [36] CCITT Recommendation X.210: "Open Systems Interconnection layer service definition conventions".

### 1.3 Definitions and abbreviations

Abbreviations used in this specification are listed in GSM 01.04.

## 2 Interfaces to the physical layer

The physical layer (layer 1) is the lowest layer in the OSI Reference Model and it supports all functions required for the transmission of bit streams on the physical medium. These bit streams are transferred on traffic and control channels as defined in TS GSM 04.03.

NOTE: For GSM application the physical layer may also be referred to as the radio subsystem. However, the radio subsystem supports functions additional to those described in this Technical Specification.

The physical layer interfaces the Data Link Layer and the supported functional units of the application (figure 2.1).




Figure 2.1: Interfaces with the Physical Layer

### 2.1 Interface to the Data Link Layer

The physical layer interfaces the data link layer. On this interface control channels are supported. The data link layer is specified in TS GSM 04.05 and 04.06. Communication between the Physical Layer and the Data Link Layer is in an abstract way performed by means of PH-primitives defined do not constrain implementations.

NOTE: The terms physical layer and layer 1, and data link layer and layer 2, will be used synonymously in this Technical Specification.

The PH-primitives exchanged between the physical layer and the data link layer are used for the transfer of layer 2 frames. They are also used to indicate the establishment of channels to layer 2.

### 2.2 Interface to radio resource management

The physical layer interfaces the radio resource management (RR-management) entity of layer 3 in the MS and in the network.

Communication is performed in an abstract way by means of MPH-primitives. They do not constrain implementations.

The primitives exchanged with the RR-management entity are related to the assignment of channels, physical layer system information (including measurement results), etc...

### 2.3 Interface to other functional units

The physical layer interfaces other functional units in the MS and in the network for supporting traffic channels. These interfaces are described in the 06 and 07 series of Technical Specifications.

### 3 Service of the physical layer

The physical layer supports transfer of bit streams on the radio medium according to the Technical Specifications of the 05-series. The scope of the 05-series of Technical Specifications is the definition of a framework for operation on the radio medium. The application of this framework on the radio medium results in a transmission service. General characteristics of the service obtained by applying the framework of the 05-series at the operation on the radio medium are described in this section.

#### 3.1 Service Access Point

In the Reference Model for Open System Interconnection, Service Access Points (SAPs) of a layer are defined as gates through which services are offered to an adjacent higher layer (figure 3.1). Through a SAP the physical layer offers a service to the data link layer. The SAP is used both for the control of the service providing entity (in case this is the physical layer; commands related to the establishment and release of channels) and the transfer of data (in case of the physical layer; the transfer of bits). The physical layer service access points defined in this Technical Specification differ from the OSI physical layer Service Access Points; the layer 3 RR-management instead of the data link layer controls the SAPs (establishment and release of channels).



Figure 3.1: Service Access Point principle

On the physical layer of the GSM system a SAP is defined between the physical layer and the data link layer for each control channel (figure 3.2). The characteristics of SAPs (channels) are listed in TS GSM 04.03.




Figure 3.2: SAPs between the physical layer and the data link layer in the MS

### 3.2 Service of the physical layer

#### \* Access capabilities:

The physical layer offers a transmission service on a limited set of logical channels. The BS and MS access capabilities and the characteristics of logical channels (SAPs) are defined in TS GSM 04.03.

NOTE: Between TS GSM 04.03 and the 05-series there is a slight difference in terminology. The 'channels' mentioned in 04.03 are 'logical channels' according to the 05-series (especially 05.02). The 'CCCH', a channel name commonly used in the 04-series, covers the logical channels of the type RACH, PCH and AGCH.

Logical channels are multiplexed on physical channels. Physical channels are the units scheduled on the radio medium. Some are reserved by the network for common use (a combination of CCCH and BCCH), others are assigned to connections with MSs (dedicated physical channels). In time the combination of logical channels used on an assigned dedicated physical channel may change. Allowed combinations of logical channels on a dedicated physical channel are defined in TS GSM 04.03. Data on SAPs of control channels is exchanged in discrete blocks with a size of 23 or 21 (SACCH) octets. Synchronisation between layer 1 and layer 2 is provided for piggy-backing of RR (receive ready) frames, and the starting of timers (T200). See also TS GSM 04.06.

#### \* Error detection:

The physical layer offers an error protected transmission service, it includes error detection functions and to a lower level, error correction functions. Erroneous received frames are not offered to the data link layer. The probability of one or more errors in a physical block transferred by the physical layer is defined in TS GSM 05.03. Due to not specified methods of quality detection, the probability of residual errors in transferred blocks may vary between implementations.

#### \* Encryption:

Security related functions implemented at the physical layer are described in TS GSM 03.20.

An overview of the functions specified in the 05-series which create the service of the physical layer can be found in TS GSM 05.01.

#### 3.2.1 Specific services of the physical layer in the MS

The access capability service of the physical layer in the MS is different for dedicated physical channels than for BCCH/CCCHs;

#### \* Establishment of dedicated physical channels:

Establishment of dedicated physical channels on the physical layer is controlled by the radio resources management of layer 3 (TS GSM 04.08). During operation on a dedicated physical channel, the physical layer measures the signals of neighbouring base stations and the signal quality of the used dedicated physical channel. Measurements are transferred to layer 3, measurement control information is offered by layer 3.

#### \* cell/PLMN selection in idle mode:

In idle mode the physical layer selects the best cell with its BCCH/CCCH in close co-operation with layer 3, meeting requirements for PLMN selection specified in TS GSM 02.11. The idle mode procedures are not modelled within this Technical Specification. Examples of procedures for cell selection are described in TS GSM 05.08. The physical layer performs automatic crossover.

## 4 Primitives of the physical layer

The Physical layer interacts with other entities as illustrated in figure 2.1. The interactions with the data link layer of Dm channels are shown in terms of primitives where the primitives represent the logical exchange of information and control between the physical layer and adjacent layers. They do not specify or constrain implementations. The interactions between the physical layer and layer 1 entities for Bm/Lm channels are for further study. For the physical layer two sets of primitives are defined:

### \* Primitives between layer 1 and 2:

PH - Generic name - Type: Parameters

### \* Primitives between layer 1 and the RR-management layer 3 entity:

MPH - Generic name - Type: Parameters

#### 4.1 Generic names of primitives between layers 1 and 2 for the transfer of layer 2 frames:

The following primitive generic names are defined on the SAPs between the physical layer and the data link layer:

- a) PH-DATA:  
The PH-DATA primitives are used on a SAP to pass message units containing frames used for data link layer peer-to-peer communications to and from the physical layer.
- b) PH-RANDOM ACCESS:  
The PH-RANDOM ACCESS (PH-RA) primitives are used on the SAP of the RACH to request and confirm (in the MS) the sending of a random access frame and to indicate (in the network) the arrival of a random access frame. The random access protocol is specified TS GSM 04.08.
- c) PH-CONNECT:  
The PH-CONNECT primitive is used on a SAP to indicate that the physical connection on the corresponding control channel has been established.
- d) PH-READY-TO-SEND:  
The PH-READY-TO-SEND primitive is used by the physical layer to trigger if applicable piggy backing, the start of timer for layer 2 and the forwarding a data unit to layer 1. It is passed to layer 2 just before a new physical block is transmitted.
- e) PH-EMPTY-FRAME:  
The PH-EMPTY-FRAME primitive can be used by the data link layer to indicate that no frame has to be transmitted after receiving the PH-READY-TO-SEND primitive. It enables polling of several layer 2 entities by layer 1 and support DTX.

#### 4.2 Generic names of primitives between layer 1 and the RR- management entity of layer 3

The following primitive generic name is defined between layer 1 and the RR-management entity of layer 3:

- MPH-INFORMATION:  
MPH-INFORMATION (MPH-INFO) primitives are used for the control of the physical layer by the RR-management of layer 3. This information activates and deactivates, configures and deconfigures, throughconnects and disconnects physical and logical channels. It is also used for the transfer of measurements and measurement control information from layer 1 to layer 3.

### 4.3 Primitive types

The primitive types defined in this Technical Specification are:

- a) **REQUEST:**  
The REQUEST primitive type is used when a higher layer is requesting a service from a lower layer.
- b) **INDICATION:**  
The INDICATION primitive type is used by a layer providing a service to notify the next higher layer of activities in the layer. This activities are directly related to the occurrence of a REQUEST primitive on the peer-protocol side.
- c) **RESPONSE:**  
The RESPONSE primitive type is used by a layer to acknowledge receipt from the INDICATION primitive type.
- d) **CONFIRM:**  
The CONFIRM primitive type is used by the layer providing the requested service to confirm that the activity has been completed.

#### 4.4 Parameter definition

Primitives contain a variable amount of parameters. The primitives with included parameters are listed in table 4.1.

**Table 4.1: Primitives of the physical layer**

primitive	entity	direction	message unit				
			dedicated channel control parameters	idle mode system information	absolute frame No.	measurements	
MPH-INFO-REQ	MS/BS	RR (L3) ->L1	x	x			
MPH-INFO-CON	MS/BS	L1->RR (L3)	x	x			
MPH-INFO-IND	MS/BS	L1->RR (L3)	x	x		x	
PH-CONNECT-IND	MS/BS	L1->L2	x				
PH-DATA-REQ	MS/BS	L2->L1	x	x			
PH-DATA-IND	MS/BS	L1->L2	x	x			
PH-RA-REQ	MS	L2->L1	x				
PH-RA-IND	BS	L1->L2	x			x	
PH-RA-CON	MS	L1->L2	x			x	

Parameters involved in the primitive exchange with the physical layer are:

- a) **Message unit:**  
The message unit contains peer-to-peer information of a layer. It is transferred by the physical layer to the peer layer.
- b) **Dedicated channel control parameters:**  
These parameters contain information for channel control, specified in TS GSM 04.08.
- c) **Idle mode system information:**  
This information is exchanged in the cell/PLMN selection procedures. It may also contain control information for DRX (sleep mode, see TS GSM 03.13).
- d) **Absolute Frame Number:**  
The absolute frame number is used (in combination with a random access identifier) to uniquely identify a random access.
- e) **Measurements:**  
This parameter is used to report the quality of a dedicated physical channel (MS and network) and to report the quality of surrounding BCCH carriers (MS only).

## 5 Physical layer procedures

The main body of physical layer procedures is specified in TS GSM 04.08 and 05.08.

### 5.1 States of the physical layer

In the physical layer of the MS the following states are defined:

NULL	: the equipment is switched off;
SEARCHING BCH	: the physical layer tracks the best BCCH;
BCH	: the physical layer listens to a BCCH/CCCH and is able to do random access;
TUNING DCH	: the physical layer seizes on a dedicated physical channel;
DCH	: the physical layer has seized a dedicated physical channel and may establish and throughconnect logical channels.

NOTE: BCH = Bch/ccch physical CHannel,  
DCH = Dedicated physical CHannel.

Figure 5.1 gives a general state diagram of the physical layer. All state transitions of the physical layer are controlled by MPH-INFORMATION primitives.




Figure 5.1: States of the physical layer in the MS

The states of the physical layer in the network are not specified. The states in the network will reflect the other characteristics of operation on channels.

### 5.2 Control procedures

Requirements and examples of procedures for idle mode operation of the MS are specified in TS GSM 02.11 and 05.08. In the idle mode procedures the physical layer tracks the best cell and may tune on their BCCH in order to enable layer 3 to read the system information of the BCCH. This system information of the BCCH is used in the selection process.



### 5.3 Physical layer interface procedures

Three types of primitives are defined for the communication between the physical layer and the data link layer both in the MS and the network. When a control channel is being established, a PH-CONNECT-INDICATION is offered to the data link layer on the corresponding SAP. On an established full duplex control channel (DCCHs) in both MS and network or on the established BCCH/CCCH in the MS, physical blocks received correctly are offered on the corresponding SAP in PH-DATA-INDICATION primitives. On a full duplex control channel (DCCHs) or on the BCCH/CCCH in the network, the data link layer will offer physical blocks to be transmitted in PH-DATA-REQUEST primitives. In the MS in idle mode, random accesses can be offered in PH-RANDOM ACCESS-REQUEST primitives. The physical layer of the MS will perform a random access as soon as possible. The physical layer of the MS will confirm the data link layer the transmission of the random access attempt in a PH-RANDOM ACCESS-CONFIRM. This confirmation contains the absolute frame number in which the random access is transmitted. The physical layer of the BS offers correctly received random accesses to the data link layer in a PH-RANDOM ACCESS-INDICATION. This indication contains the absolute frame number in which the random access is received.

## 6 Physical layer protocol header

The physical layer implements a peer-to-peer protocol for the control of timing advance and power control at the operation on dedicated physical channels. For this purpose a two octet physical header is defined on all blocks transferred via the SACCH, a logical channel always present on a dedicated physical channel.

### 6.1 Physical layer protocol fields and procedures


Procedures for handling the ordered and actual power level fields are specified in Technical Specifications GSM 05.05 and 05.08. The ordered MS power level field and the actual MS power level field are coded as the binary representation of the "power control level", see GSM 05.05.

Procedures for handling the ordered and actual timing advance fields are specified in TS GSM 05.10. The numbers corresponding to the timing advance steps in TS GSM 05.10 are included binary coded in the 6 bit ordered and actual timing advance fields of the physical layer header. The bit pattern "111111" indicates that the field does not contain a timing advance value. All other bit combinations (64 to 126 decimal) are reserved.

## 7 Block transmission

### 7.1 SACCH downlink block format

The originally 23 octets of SACCH blocks are used downlink in the following way:




**Figure 7.1: SACCH downlink block format**

NOTE: The numbering convention specified in TS GSM 04.06 applies.

**7.2 SACCH uplink block format**

The originally 23 octets of SACCH blocks are used uplink in the following way:



**Figure 7.2: SACCH uplink block format**

NOTE: The numbering convention specified in TS GSM 04.06 applies.

7.3 FACCH/SDCCH/CCCH/BCCH/CBCH downlink block format

The originally 23 octets blocks are used downlink in the following way:





Figure 7.3: FACCH/SDCCH/BCCH/CCCH/CBCH downlink block format

NOTE: The numbering convention specified in TS GSM 04.06 and 04.12 applies.

#### 7.4 FACCH/SDCCH uplink block format

The originally 23 octets blocks are used uplink in the following way:



**Figure 7.4: FACCH/SDCCH uplink block format**

NOTE: The numbering convention specified in TS GSM 04.06 applies.

## 7.5 Order of bit transmission

On channels for normal burst transmission the 23 octets are mapped onto 184 bits,  $d(0)$  to  $d(183)$ , defined in TS GSM 05.03 section 4 as follows:

bit  $m$  of octet  $n$  shall be transmitted as bit  $d((n-1)*8+m-1)$  with  $m=(1..8)$  and  $n=(1..23)$ .

For transmission which does not follow the normal burst transmission (refer e.g. to CHANNEL REQUEST message, HANDOVER ACCESS message and SYNCHRONISATION CHANNEL INFORMATION message defined in TS GSM 04.08) this rule applies accordingly:

Bit  $m$  of octet  $n$  shall be transmitted as bit  $d((n-1)*8+m-1)$  with  $m=(1..x)$  and  $n=(1..y)$  where  $x$  and  $y$  are given by the definition of the respective layer 3 information in TS GSM 04.08.

## 8 Vocabulary

The terminology used in this Technical Specification is as follows:

- Idle mode:  
In this mode the MS is not allocated any dedicated physical channel; it listens to the CCCH and the BCCH.
- Dedicated mode:  
In this mode the MS is allocated a dedicated physical channel, at least containing two logical channels, only one of them being a SACCH.
- Physical block:  
The physical block is the minimal unit which can be transferred by the physical layer.

## History

Document history	
September 1994	First Edition
October 1995	Converted into Adobe Acrobat Portable Document Format (PDF)