



EUROPEAN
TELECOMMUNICATION
STANDARD

DRAFT
pr **ETS 300 641**

August 1995

Source: ETSI TC-SMG

Reference: DE/SMG-091112Q

ICS: 33.060.50

Key words: European digital cellular telecommunications system, Global System for Mobile communications (GSM)

**European digital cellular telecommunications system (Phase 2);
Specification of the 3 Volt Subscriber Identity Module
- Mobile Equipment (SIM - ME) interface
(GSM 11.12)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 92 94 42 00 - Fax: +33 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1995. All rights reserved.

Contents

Foreword		5
1	Scope	7
2	Normative references	7
3	Definitions, abbreviations and symbols	7
	3.1 Definitions	7
	3.2 Abbreviations	7
	3.3 Symbols	7
4	3V technology	8
	4.1 3V technology SIM	8
	4.2 3V technology impact	8
	4.3 3V technology SIM Identification	8
	4.4 3V technology ME	8
	4.5 3V Only ME	8
	4.6 Activation and deactivation	8
	4.7 Supply voltage switching	9
	4.8 Cross compatibility	9
	4.9 Outlook	9
5	Electrical specifications of the SIM - ME interface	9
	Annex A (informative): Cross compatibility aspects	11
	History	12

Blank page

Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) Technical Committee (TC) of the European Telecommunications Standards Institute (ETSI), and is now submitted for the Public Enquiry phase of the ETSI standards approval procedure.

This ETS defines the aspects of the SIM - ME interface which are based on 3V technology to be used in the Mobile Station (MS) within the European digital cellular telecommunications system (Phase 2).

This ETS corresponds to GSM technical specification GSM 11.12 version 4.0.0.

Proposed transposition dates	
Date of adoption of this ETS:	date of ETSI adoption
Date of latest announcement of this ETS (doa):	3 months after ETSI adoption
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	6 months after doa
Date of withdrawal of any conflicting National Standard (dow):	6 months after doa

Blank page

1 Scope

This European Telecommunication Standard (ETS) defines the aspects of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface which are based on 3V technology to be used in the Mobile Station (MS). It specifies the electrical and logical requirements necessary for the operation of the 3V SIM - ME interface where it differs from GSM 11.11 (ETS 300 608) [1]. For all aspects of the SIM - ME interface which are not covered by this ETS, GSM 11.11 (ETS 300 608) [1] applies.

2 Normative references

This ETS incorporates by dated and non-dated reference, provisions from other publications. This normative reference is cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For non-dated references the latest edition of the publication referred to applies.

- [1] GSM 11.11 (ETS 300 608): "European digital cellular telecommunications system (Phase 2); Specification of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface".

3 Definitions, abbreviations and symbols

3.1 Definitions

For the purposes of this ETS the following definitions apply.

3V technology SIM: A SIM operating at $3V \pm 10\%$ and $5V \pm 10\%$.

3V technology ME: An ME operating the SIM - ME interface at $3V \pm 10\%$ according to this ETS and $5V \pm 10\%$ according to GSM 11.11 (ETS 300 608) [1].

3V only ME: An ME only operating the SIM - ME interface at $3V \pm 10\%$ according to this ETS.

3.2 Abbreviations

For the purposes of this ETS the following abbreviations apply.

ATR	Answer To Reset
CLK	Clock
IC	Integrated Circuit
I/O	Input/Output
ME	Mobile Equipment
MS	Mobile Station
RST	Reset
SIM	Subscriber Identity Module

3.3 Symbols

For the purposes of this ETS the following symbols apply.

t_F	fall time
t_R	rise time
V_{IH}	Input Voltage (high)
V_{IL}	Input Voltage (low)
V_{OH}	Output Voltage (high)
V_{OL}	Output Voltage (low)

4 3V technology

4.1 3V technology SIM

The SIM shall operate on both $5V \pm 10\%$ according to GSM 11.11 (ETS 300 608) [1], and on $3V \pm 10\%$ according to this ETS. If the ME supplies 5V to the SIM, both the ME and the SIM shall operate according to GSM 11.11 (ETS 300 608) [1]. The logical operation of the 3V technology SIM shall be as defined in GSM 11.11 (ETS 300 608) [1].

Clock stop mode shall be supported by the SIM. The SIM shall indicate "Clock Stop Allowed" in the file characteristics of the status information as specified in GSM 11.11 (ETS 300 608) [1].

4.2 3V technology impact

When supplied with the supply voltage as specified in this ETS the SIM shall be operated with a clock frequency of 1 to 4 MHz.

4.3 3V technology SIM Identification

The 3V technology SIM shall contain an identification. The identification is coded on bit 5 in byte 14 of the status information as follows:

"0" : 5V only SIM;

"1" : 3V technology SIM.

In the case that the ME offers full compatibility by being able to operate the SIM interface at both 3V and 5V, then bit 5 in byte 14 of the status information, when set to "1", indicates that the SIM may be operated at 3V.

The procedure for deriving the identification bit shall be performed by the ME immediately after the Answer To Reset (ATR) and before issuing any other command. The procedure consists of the two commands "SELECT GSM" and "STATUS/GET RESPONSE"

4.4 3V technology ME

The 3V technology ME shall initially activate the SIM with 5V according to GSM 11.11 (ETS 300 608) [1]. If the SIM indicates 3V operation as defined in subclause 4.3, the ME may switch to 3V operation as defined in subclause 4.7. If switching is performed it shall take place before issuing any further commands.

4.5 3V Only ME

The 3V only ME activates the SIM at 3V.

If the ME is able to detect a 5V only SIM according to the procedure in subclause 4.3, or if the procedure cannot be completed, the ME shall deactivate and reject the SIM immediately (maximum of 5s) without issuing any further command. This rejection ensures that a SIM which appears to operate successfully during these early procedures is not allowed to continue further into the GSM session where it may subsequently give unreliable operation at 3V.

If an ATR is corrupted or not received by the ME, error handling according to clause 5.10 of GSM 11.11 (ETS 300 608) [1] shall apply.

4.6 Activation and deactivation

The ME shall connect, activate and deactivate the SIM in accordance with the operating procedures specified in GSM 11.11 (ETS 300 608) [1] taking into account the electrical characteristics specified in clause 5 of this ETS. In particular, Vcc is powered when it has a value between 2,7 V and 3,3 V.

4.7 Supply voltage switching

MEs supporting both 3V and 5V operation may switch between the two supply voltages. Switching shall always be performed by deactivating the SIM and activating it at the new supply voltage. Activation and deactivation of the SIM with 5V shall be according to GSM 11.11 (ETS 300 608) [1], whereas activation and deactivation of the SIM with 3V shall be according to this ETS.

4.8 Cross compatibility

Cross compatibility means that the ME supports 3V and 5V operation. This is, however, optional for the ME. In case of the 3V technology ME, full cross compatibility is provided, whereas, a 3V only ME requires a 3V technology SIM for operation. However, the 3V technology SIM (see definitions) ensures full cross compatibility.

4.9 Outlook

Due to technology development it is possible in the future, when sub-micron technology is introduced, that Integrated Circuits (ICs) used in MEs may not withstand the 5V supply voltage. This may, in particular, be the case for ICs operating in the power supply range of 1,5V to 3,6V. It may therefore be necessary in the future to specify a low voltage only SIM interface.

NOTE: When a low voltage only SIM is inserted into an ME when it is supplying 5V, the SIM may be destroyed which in some cases could cause permanent damage to the ME. Precautions should be taken by the IC manufacturers to prevent the low voltage ICs from being damaged at 5V.

5 Electrical specifications of the SIM - ME interface

The electrical specification given in this ETS covers the supply voltage range from 2,7V to 3,3V. The supply voltage range from 4,5V to 5,5V is specified in GSM 11.11 (ETS 300 608) [1]. Current direction is specified to be positive (+) into the SIM or the ME interface, whichever is tested. Vpp is not supported by the 3V technology ME or the 3V technology SIM.

When the SIM is in idle state the current consumption of the card shall not exceed 200 μ A at 1 MHz at +25°C. When the SIM is in clock stop mode the current consumption shall not exceed 100 μ A at +25 °C.

The ME shall source the maximum current as defined in table 4. It shall also be able to counteract spikes in the current consumption of the card up to a maximum charge of 12 nAs with no more than 400 ns duration and an amplitude of at most 60 mA, ensuring that the supply voltage stays in the specified range.

The clock duty cycle shall be between 40 % and 60 % of the period during stable operation. A clock cycle is defined at 50% of Vcc from rising to rising edge or falling to falling edge. When switching clock frequencies MEs shall ensure that no pulse is shorter than 100 ns which is 40 % of the shortest allowed period.

The ME need not provide contact C6 (Vpp). Contact C6 shall not be connected in the ME if provided.

Table 1. Electrical characteristics of I/O under normal operating conditions

Symbol	Conditions	Minimum	Maximum	Unit
V_{IH}	$I_{IHmax} = \pm 20 \mu A$ (Note 2)	$0,7 \times V_{cc}$	$V_{cc}+0,3$	V
V_{IL}	$I_{ILmax} = + 1 \text{ mA}$	- 0,3	$0,2 \times V_{cc}$	V
V_{OH} (Note 1)	$I_{OHmax} = + 20 \mu A$	$0,7 \times V_{cc}$	V_{cc} (Note 3)	V
V_{OL}	$I_{OLmax} = - 1 \text{ mA}$	0 (Note 3)	0,4	V
$t_R t_F$	$C_{in} = C_{out} = 30 \text{ pF}$		1	μs
NOTE 1:	It is assumed that a pull-up resistor is used on the interface device (recommended value: 20 k Ω).			
NOTE 2:	During static conditions (idle state) only the positive value can apply. Under dynamic operating conditions (transmissions) short term voltage spikes on the I/O line may cause a current reversal.			
NOTE 3:	To allow for overshoot the voltage on I/O shall remain between -0,3V and $V_{cc}+0,3V$ during dynamic operation.			

Table 2. Electrical characteristics of Clock (CLK) under normal operating conditions

Symbol	Conditions	Minimum	Maximum	Unit
V_{OH}	$I_{OHmax} = + 20 \mu A$	$0,7 \times V_{cc}$	V_{cc} (Note)	V
V_{OL}	$I_{OLmax} = - 20 \mu A$	0 (Note)	$0,2 \times V_{cc}$	V
$t_R t_F$	$C_{in} = C_{out} = 30 \text{ pF}$		50	ns
NOTE:	To allow for overshoot the voltage on CLK should remain between -0,3V and $V_{cc}+0,3V$ during dynamic operations.			

Table 3. Electrical characteristics of RESET (RST) under normal operating conditions

Symbol	Conditions	Minimum	Maximum	Unit
V_{OH}	$I_{OHmax} = + 20 \mu A$	$0,8 \times V_{cc}$	V_{cc} (Note)	V
V_{OL}	$I_{OLmax} = -200 \mu A$	0 (Note)	$0,2 \times V_{cc}$	V
$t_R t_F$	$C_{in} = C_{out} = 30 \text{ pF}$		400	μs
NOTE:	To allow for overshoot the voltage on RST should remain between -0,3V and $V_{cc} +0,3V$ during dynamic operations.			

Table 4. Electrical characteristics of Vcc under normal operating conditions

Symbol	Minimum	Maximum	Unit
V_{cc}	2,7	3,3	V
I_{cc}		6 (Note)	mA
NOTE:	The supply current at 3,3V refers to a clock frequency of 4 MHz.		

Annex A (informative): Cross compatibility aspects

Table A.1 shows the impacts of selecting different start-up scenarios between different technology SIMs and MEs. The table also takes into account possible future migration to new technology.

Table A.1

ME	5V	3V --> 5V Note 1	5V --> 3V Note 2	3V	3V --> Future	Future Note 3
SIM						
5V Only	OK	Working at 5V	OK	Not Working	Not Working	Not Working
3V&5V	OK	OK	OK	OK	OK	Not Working
3V Only Note 4	Not Working (Damage?)	OK	OK (Damage?)	OK	OK	Not Working
3V&Future	Damaged?	OK	Damaged?	OK	OK	OK
Future Note 3	Destroyed?	Unknown	Destroyed?	Unknown	OK ?	OK

NOTE 1: An ME supporting both 3V and 5V is not allowed to power up the SIM initially at 3V. The column is only for information what effects starting up initially at 3V would have.

NOTE 2: The ME starts up the SIM by first applying 5V to the SIM and if a 3V technology SIM is identified the ME may restart the SIM at 3V.

NOTE 3: The Future technology might be 1-2V.

NOTE 4: 3V only SIMs will not be used for the time being.

History

Document history	
August 1995	Public Enquiry PE 89: 1995-08-07 to 1995-12-01
April 1996	Converted into Adobe Acrobat Portable Document Format (PDF)