



EUROPEAN
TELECOMMUNICATION
STANDARD

ETS 300 944

September 1997

Second Edition

Source: ETSI SMG

Reference: RE/SMG-030413QR

ICS: 33.020

Key words: Digital cellular telecommunications system, Global System for Mobile communications (GSM)



**Digital cellular telecommunications system (Phase 2+);
Performance requirements on the mobile radio interface
(GSM 04.13 version 5.1.1)**

ETSI

European Telecommunications Standards Institute

ETSI Secretariat

Postal address: F-06921 Sophia Antipolis CEDEX - FRANCE

Office address: 650 Route des Lucioles - Sophia Antipolis - Valbonne - FRANCE

X.400: c=fr, a=atlas, p=etsi, s=secretariat - **Internet:** secretariat@etsi.fr

Tel.: +33 4 92 94 42 00 - Fax: +33 4 93 65 47 16

Copyright Notification: No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 1997. All rights reserved.

Contents

Foreword	5
1 Scope	7
2 Normative references	7
3 Abbreviations and definitions	7
3.1 Abbreviations	7
3.2 Definitions	8
4 Default conditions	8
5 Requirements	8
5.1 General requirements	8
5.1.1 Response to layer 3 message	8
5.1.2 Response to an erroneous layer 3 message	8
5.2 Layer 3 Radio Resource signalling	8
5.2.0 Paging	8
5.2.1 Paging and cell reselection after channel release	9
5.2.2 Paging commands and immediate assignment rejection (Timer T3122)	9
5.2.3 Immediate assignment (Timer T3101)	9
5.2.4 Channel assignment	9
5.2.5 Channel mode modify	9
5.2.6 Handover access	9
5.2.6.1 Fully, pseudo and pre synchronized cases	9
5.2.6.2 Non synchronized case	10
5.2.7 Encryption	11
5.2.8 Classmark change	11
5.2.9 Classmark interrogation	11
5.2.10 Release (Timer T3110)	11
5.2.11 Early sending of the CLASSMARK CHANGE message	11
5.3 Layer 3 Mobility Management signalling	11
5.3.1 Periodic location updating timer	11
5.3.2 Identification	11
5.3.3 Authentication	11
5.3.4 T3240 expiry	11
5.3.5 TMSI reallocation	12
5.3.6 IMSI detach	12
5.3.7 Location updating with random access failure	12
5.3.8 Follow on call	12
5.4 Layer 3 Call Control signalling	12
5.4.1 Time to send SETUP message	12
5.4.2 Response times to CC messages	12
5.4.3 User alerting	13
5.4.4 Call establishment	13
5.4.5 Call reestablishment	13
5.4.6 In call modification	14
5.4.7 DTMF	14
5.5 Supplementary service signalling	14
5.5.1 Advice of Charge Charging (AoCC)	14
5.6 Short Message Services Point-to-Point	14
5.6.1 CP-DATA	14
5.6.2 RP-DATA	14
History	15

Blank page

Foreword

This European Telecommunication Standard (ETS) has been produced by the Special Mobile Group (SMG) of the European Telecommunications Standards Institute (ETSI).

This ETS provides a mechanism giving reliable transfer of signalling messages within the digital cellular telecommunications system (Phase 2+).

The contents of this ETS is subject to continuing work within SMG and may change following formal SMG approval. Should SMG modify the contents of this ETS, it will be resubmitted for OAP by ETSI with an identifying change of release date and an increase in version number as follows:

Version 5.x.y

where:

- y the third digit is incremented when editorial only changes have been incorporated in the specification;
- x the second digit is incremented for all other types of changes, i.e. technical enhancements, corrections, updates, etc.

The specification from which this ETS has been derived was originally based on CEPT documentation, hence the presentation of this ETS may not be entirely in accordance with the ETSI drafting rules.

Transposition dates	
Date of adoption:	5 September 1997
Date of latest announcement of this ETS (doa):	31 December 1997
Date of latest publication of new National Standard or endorsement of this ETS (dop/e):	30 June 1998
Date of withdrawal of any conflicting National Standard (dow):	30 June 1998

Blank page

1 Scope

This European Telecommunication Standard (ETS) specifies measurable performance requirements for signalling aspects of Mobile Stations (MS)s. To allow implementation flexibility it has been chosen to specify requirements on the whole Mobile Station rather than to specify requirements on each "OSI layer". As a consequence the performance requirements do not fit conveniently in specifications such as GSM 04.08 [4] (layer 3 only) or GSM 04.06 [3] (layer 2 only).

The main aim of this ETS is to provide the justification for testing of requirements that are not included in other GSM specifications. Where specific requirements are included in other GSM specifications they are not duplicated here.

MSs have to perform a wide variety of functions. As a consequence most performance measurements have to be made under a set of defined conditions: where necessary, these are included in this ETS.

Where necessary certain assumptions are made about the interaction times between the mobile equipment and the SIM. If the (test) SIM does not respond within the assumed time then appropriate allowances shall be made.

Additionally, it is intended that this ETS should contain sufficient requirements to enable some undefined network timers in GSM 04.08 [4] to be calculated.

2 Normative references

This ETS incorporates by dated and undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this ETS only when incorporated in it by amendment or revision. For undated references, the latest edition of the publication referred to applies.

- [1] GSM 01.04 (ETR 350): "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [2] GSM 03.22 (ETS 300 930): "Digital cellular telecommunications system; Functions related to Mobile Station (MS) in idle mode and group receive mode".
- [3] GSM 04.06 (ETS 300 938): "Digital cellular telecommunications system; Mobile Station - Base Station System (MS - BSS) interface Data Link (DL) layer specification".
- [4] GSM 04.08 (ETS 300 940): "Digital cellular telecommunications system (Phase 2+); Mobile radio interface layer 3 specification".
- [5] GSM 04.86 (ETS 300 955): "Digital cellular telecommunications system; Advice of Charge (AoC) supplementary services - Stage 3".
- [6] GSM 05.02 (ETS 300 908): "Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path".
- [7] GSM 05.08 (ETS 300 911): "Digital cellular telecommunications system (Phase 2+); Radio subsystem link control".

3 Abbreviations and definitions

3.1 Abbreviations

Abbreviations used in this ETS are listed in GSM 01.04 [1].

3.2 Definitions

For the purposes of this ETS, the following definition applies:

ready to transmit: In this ETS the phrase "ready to transmit the message before time x" is defined to mean that the MS shall transmit part of that message no later than the first burst of the first TCH or control channel block that occurs after time x.

4 Default conditions

Unless otherwise stated, throughout this ETS the following conditions are associated with the requirements:

- ideal radio link with an insignificant bit error rate;
- no other signalling is in progress on the main DCCH;
- messages sent by the network are correctly formed;
- the only established data link (or the only data link to be established) is on SAPI 0;
- any Starting Time IE that is included in a message sent by the network does not require the action to be delayed;
- cells are not barred and all access classes are allowed;
- the layer 2 performance of the network shall satisfy the "System Performance Requirements" of subclause 5.9 of GSM 04.06 [3];
- messages sent by the network may contain any set of optional IEs, and any permitted set of conditional IEs;
- the mobile has a valid SIM inserted, is powered on, and the SIM's update status is "updated"; and
- on the CCCH, the Page Mode IE is not set to "paging reorganization" or "same as before".

5 Requirements

5.1 General requirements

5.1.1 Response to layer 3 message

The requirements of subclause 5.1.1 apply if there are no specific requirements for a layer 3 message in other parts of clause 5.

If the last timeslot of the message block containing a network command occurs at time T, then the MS shall be ready to transmit the response before time T + 500 ms.

5.1.2 Response to an erroneous layer 3 message

If the last timeslot of the message block containing an erroneous RR, MM or CC message occurs at time T and if GSM 04.08 [4] requires a status message to be returned to the network then the MS shall be ready to transmit the RR-STATUS or MM-STATUS or STATUS message before T + 500 ms.

5.2 Layer 3 Radio Resource signalling

5.2.0 Paging

If access to the network is allowed and the MS has been camped on a suitable cell for at least 2 seconds and if the last timeslot of the message block containing a PAGING REQUEST message addressing the MS occurs at time T, then the MS shall be ready to transmit the CHANNEL REQUEST message before T + 0,7 seconds.

5.2.1 Paging and cell reselection after channel release

If the last timeslot of the message block containing a CHANNEL RELEASE message occurs at time T the MS shall respond to PAGING REQUEST messages sent later than $T + 1,0$ seconds.

5.2.2 Paging commands and immediate assignment rejection (Timer T3122)

If the last timeslot of the message block containing an IMMEDIATE ASSIGNMENT REJECT message is sent at time T and contains a Wait Indication of W seconds then the MS shall at least respond to PAGING REQUEST messages sent later than $T + (W + 1)$ seconds.

5.2.3 Immediate assignment (Timer T3101)

If the last timeslot of the message block containing an IMMEDIATE ASSIGNMENT (or IMMEDIATE ASSIGNMENT EXTENDED) message is transmitted at time T then, the MS shall be ready to transmit the SABM frame with its information field before $T + 25$ ms. This requirement shall apply for assignment to TCH/F, TCH/H and SDCCH.

5.2.4 Channel assignment

If the last timeslot of the message block containing an ASSIGNMENT COMMAND occurs at time T, then the MS shall be ready to transmit the ASSIGNMENT COMPLETE message before $T + 600$ ms.

If the last timeslot of the message block containing an ASSIGNMENT COMMAND occurs at time T and this ASSIGNMENT COMMAND is such that the MS tries but fails to establish a layer 2 link on the new channel and thus reverts to the old channel, then the MS shall be ready to transmit the ASSIGNMENT FAILURE message on the old channel before $T + 2$ seconds.

If the last timeslot of the message block containing an ASSIGNMENT COMMAND occurs at time T and this ASSIGNMENT COMMAND is such that the MS shall not attempt to establish a layer 2 link on the new channel, then the MS shall be ready to transmit any ASSIGNMENT FAILURE message on the old channel before $T + 500$ ms.

5.2.5 Channel mode modify

If the last timeslot of the message block containing a CHANNEL MODE MODIFY message occurs at time T, then the MS shall be ready to transmit the CHANNEL MODE MODIFY ACKNOWLEDGE message before $T + 300$ ms. In the case that the call is a voice group or voice broadcast call the MS shall be ready to transmit the CHANNEL MODE ACKNOWLEDGE message before $T + 50$ ms.

5.2.6 Handover access

5.2.6.1 Finally, pseudo and pre synchronized cases

If the last timeslot of the message block containing a HANDOVER COMMAND message to a full rate TCH occurs at time T, then the MS shall be ready to transmit the HANDOVER COMPLETE message before $T + 650$ ms.

If the last timeslot of the message block containing a HANDOVER COMMAND message to a half rate TCH occurs at time T, then the MS shall be ready to transmit the HANDOVER COMPLETE message before $T + 900$ ms.

If the last timeslot of the message block containing a HANDOVER COMMAND message to an SDCCH occurs at time T, then the MS shall be ready to transmit the HANDOVER COMPLETE message before $T + 1,5$ seconds.

If the last timeslot of the message block containing a HANDOVER COMMAND to a full rate TCH occurs at time T and this HANDOVER COMMAND is such that the MS tries but fails to establish a layer 2 link on the new channel and thus reverts to the old channel, then the MS shall be ready to transmit the HANDOVER FAILURE message on the old full rate TCH before $T + 2$ seconds.

If the last timeslot of the message block containing a HANDOVER COMMAND to a full rate TCH occurs at time T and this HANDOVER COMMAND is such that the MS tries but fails to establish a layer 2 link on the new channel and thus reverts to the old channel, then the MS shall be ready to transmit the HANDOVER FAILURE message on the old SDCCH before T + 2,5 seconds.

If the last timeslot of the message block containing a HANDOVER COMMAND to a half rate TCH occurs at time T and this HANDOVER COMMAND is such that the MS tries but fails to establish a layer 2 link on the new channel and thus reverts to the old channel, then the MS shall be ready to transmit the HANDOVER FAILURE message on the old half rate TCH before T + 3 seconds.

If the last timeslot of the message block containing a HANDOVER COMMAND to a half rate TCH occurs at time T and this HANDOVER COMMAND is such that the MS tries but fails to establish a layer 2 link on the new channel and thus reverts to the old channel, then the MS shall be ready to transmit the HANDOVER FAILURE message on the old SDCCH before T + 3 seconds.

If the last timeslot of the message block containing a HANDOVER COMMAND to an SDCCH occurs at time T and this HANDOVER COMMAND is such that the MS tries but fails to establish a layer 2 link on the new channel and thus reverts to the old channel, then the MS shall be ready to transmit the HANDOVER FAILURE message on the old SDCCH before T + 5 seconds.

If the last timeslot of the message block containing a HANDOVER COMMAND occurs at time T and this HANDOVER COMMAND is such that the MS shall not attempt to establish a layer 2 link on the new channel, then the MS shall be ready to transmit any HANDOVER FAILURE message on the old channel before T + 500 ms.

5.2.6.2 Non synchronized case

If the last timeslot of the message block containing the (one and only) PHYSICAL INFORMATION message occurs at time T, then on a full rate TCH the MS shall be ready to transmit the HANDOVER COMPLETE message before T + 500 ms.

If the last timeslot of the message block containing the (one and only) PHYSICAL INFORMATION message occurs at time T, then on a half rate TCH the MS shall be ready to transmit the HANDOVER COMPLETE message before T + 750 ms.

If the last timeslot of the message block containing the (one and only) PHYSICAL INFORMATION message occurs at time T, then on an SDCCH the MS shall be ready to transmit the HANDOVER COMPLETE message before T + 1,5 seconds.

If the last timeslot of the message block containing a HANDOVER COMMAND to either a full rate or a half rate TCH occurs at time T and this HANDOVER COMMAND is such that the MS tries but fails to establish a layer 2 link on the new channel and thus reverts to the old channel, then the MS shall be ready to transmit the HANDOVER FAILURE message on the old TCH before T + 1,1 seconds.

If the last timeslot of the message block containing a HANDOVER COMMAND to an SDCCH occurs at time T and this HANDOVER COMMAND is such that the MS tries but fails to establish a layer 2 link on the new channel and thus reverts to the old channel, then the MS shall be ready to transmit the HANDOVER FAILURE message on the old SDCCH before T + 2 seconds.

If the last timeslot of the message block containing a HANDOVER COMMAND to either a full rate or a half rate TCH occurs at time T and this HANDOVER COMMAND is such that the MS tries but fails to establish a layer 2 link on the new channel and thus reverts to the old channel, then the MS shall be ready to transmit the HANDOVER FAILURE message on the old SDCCH before T + 1,7 seconds.

If the last timeslot of the message block containing a HANDOVER COMMAND occurs at time T and this HANDOVER COMMAND is such that the MS shall not attempt to establish a layer 2 link on the new channel, then the MS shall be ready to transmit any HANDOVER FAILURE message on the old channel before T + 500 ms.

5.2.7 Encryption

If the last timeslot of the message block containing a CIPHERING MODE COMMAND message occurs at time T , then the MS shall be ready to transmit the CIPHERING MODE COMPLETE message before $T + 500$ ms.

5.2.8 Classmark change

While the MS has an active RR connection, any change in the MS's capabilities that are indicated in the Mobile Station Classmark 2 or 3 IEs shall cause a CLASSMARK CHANGE message to be sent to the network. The MS shall be ready to transmit the CLASSMARK CHANGE message not later than 1 second after the change in capabilities.

5.2.9 Classmark interrogation

If the last timeslot of the message block containing a CLASSMARK ENQUIRY message occurs at time T , then the MS shall be ready to transmit the CLASSMARK CHANGE message before $T + 300$ ms.

5.2.10 Release (Timer T3110)

If the last timeslot of the message block carrying the CHANNEL RELEASE message occurs at time T , then the MS shall cease transmissions on all channels before $T + 500$ ms.

5.2.11 Early sending of the CLASSMARK CHANGE message

During a contention resolution procedure, if the last timeslot of the block containing a Layer 2 UA frame, occurs at time T , then the MS shall be ready to transmit the CLASSMARK CHANGE message, if applicable (see GSM 04.06 [3] and GSM 04.08 [4]), before $T + 40$ ms.

5.3 Layer 3 Mobility Management signalling

5.3.1 Periodic location updating timer

When the T3212 time-out value is set to the non-zero value P and the last timeslot of the message block containing a CHANNEL RELEASE message is transmitted at time T then, assuming the next event shall be the periodic location update, the next CHANNEL REQUEST message shall be transmitted between time $T + P$ decihours - 15 seconds and time $T + P$ decihours + 15 seconds.

5.3.2 Identification

If the last timeslot of the message block containing an IDENTITY REQUEST message occurs at time T , then the MS shall be ready to transmit the IDENTITY RESPONSE message before $T + 600$ ms. This requirement assumes that the ME has to wait less than 100 ms to obtain any necessary responses from the SIM.

5.3.3 Authentication

If the last timeslot of the message block containing an AUTHENTICATION REQUEST message occurs at time T , then the MS shall be ready to transmit the AUTHENTICATION RESPONSE message before $T + 1$ second. This requirement assumes that the ME has to wait less than 500 ms to obtain any necessary responses from the SIM.

5.3.4 T3240 expiry

If the last timeslot of the message block containing an AUTHENTICATION REJECT message; or a LOCATION UPDATING ACCEPT message (without a Follow On Proceed IE); or a LOCATION UPDATING REJECT message; or a CM SERVICE REJECT message (and no other MM connection is active) occurs at time T , and the network does not send a CHANNEL RELEASE message but does maintain the RR connection, then the MS shall cease transmission on all channels before $T + 12$ seconds.

5.3.5 TMSI reallocation

If the last timeslot of the message block containing either a TMSI REALLOCATION COMMAND, or a LOCATION UPDATING ACCEPT with a TMSI in the Mobile Identity IE, occurs at time T, then the MS shall be ready to transmit the TMSI REALLOCATION COMPLETE message before T + 500 ms.

5.3.6 IMSI detach

The requirements of this subclause only apply if the network indicates on the BCCH that IMSI detach shall be used.

If it is possible to switch the mobile off, or if it is possible to remove the SIM whilst the mobile is powered on, then when such an action is performed in idle mode at time T, the first CHANNEL REQUEST message for the IMSI Detach procedure shall be transmitted before T + 2 seconds.

If it is possible to switch the mobile off, or if it is possible to remove the SIM whilst the mobile is powered on, then when such an action is performed in the Active (U10) state of a call at time T, the MS shall be ready to transmit the IMSI DETACH INDICATION message before T + 1 second.

If the last timeslot in which the IMSI DETACH message is sent occurs at time T then the MS shall cease transmission on all channels before T + 6 seconds.

5.3.7 Location updating with random access failure

In an environment with only one suitable cell (see GSM 03.22 [2] for the definition of a "suitable cell"), if a location updating attempt suffers a random access failure (see GSM 04.08 [4]) with the last CHANNEL REQUEST message being transmitted at time T, then the first re-attempt shall result in a CHANNEL REQUEST message being transmitted before T + 15 seconds.

5.3.8 Follow on call

If the last timeslot of the message block containing a LOCATION UPDATING ACCEPT message with a Follow on Proceed IE occurs at time T and the MS has a CM application request pending, then the MS shall be ready to the CM SERVICE REQUEST message before T + 500 ms.

5.4 Layer 3 Call Control signalling

5.4.1 Time to send SETUP message

In the case of a MS originated call, if the last timeslot of the message block containing a CM SERVICE ACCEPT message occurs at time T then the MS shall be ready to transmit the SETUP message before T + 500 ms. In the case that the call is a voice group or voice broadcast call the MS shall be ready to transmit the SETUP message before T + 50 ms.

In the case of a MS originated call, if the last timeslot of the message block containing a CIPHERING MODE COMMAND message occurs at time T, then the MS shall be ready to transmit the SETUP message before T + 750 ms. In the case that the call is a voice group or voice broadcast call the MS shall be ready to transmit the SETUP message before T + 50 ms.

In the case of a MS originated call, if the last timeslot of the message block containing a MM GO ON message occurs at time T, then the MS shall be ready to transmit the SETUP message before T + 50 ms. In the case that the call is a voice group or voice broadcast call the MS shall be ready to transmit the SETUP message before T + 50 ms.

5.4.2 Response times to CC messages

For the commands and responses listed in table 1, the following shall apply:

- if the last timeslot of the message block in which the "command" message is sent occurs at time T, then the MS shall be ready to transmit any one of the possible "responses" before time T + W.

In table 1, the second figure, where provided, represents the time that must be achieved in the case of a voice group or voice broadcast call.

Table 1: Call Control message response times

command (network --> MS)	response(s) (MS --> network)	W
CONNECT	CONNECT ACKNOWLEDGE	500 ms, 50 ms
SETUP	(as first response message) CALL CONFIRMED or ALERTING or CONNECT or RELEASE COMPLETE	1 second, 50 ms
SETUP	(as second response message) ALERTING or CONNECT or DISCONNECT	2 seconds
SETUP	(as third response message) CONNECT	no requirement
DISCONNECT	RELEASE	500 ms
RELEASE	RELEASE COMPLETE	500 ms
STATUS ENQUIRY	STATUS	500 ms

5.4.3 User alerting

If the MS has some form of user alerting and if for a mobile terminating call the MS sends the ALERTING message before the CONNECT message then:

- if the last timeslot carrying a SETUP message containing the Signal IE occurs at time T, the user alerting shall be initiated before time T + 1 second.

5.4.4 Call establishment

If the MS's service indication indicates that service is available (see GSM 03.22 [2]) and after the entry of suitable number digits, then if the "SEND" or "Emergency SEND" function on the MS is activated at time T, the first CHANNEL REQUEST message shall be transmitted before time T + 2 second.

5.4.5 Call reestablishment

The requirement of this subclause relates to the following environment and conditions:

- the MS is the active (U10) state of a speech call on cell A;
- the NCC of cell B is indicated as permitted in the SYSTEM INFORMATION messages of cell A, but cell B may be in a different location area;
- cells A and B are the only cells which have C1 > 0 (see GSM 05.08 [7]);
- cell B is in at least the BA(SACCH) list of cell A;
- cell B allows call reestablishment.

If the transmissions from cell A are disrupted such that the MS shall detect a radio link failure at time T then the MS shall transmit a CHANNEL REQUEST message to cell B before time T + 3 second.

5.4.6 In call modification

For network originated in call modification, if the MS transmits the last timeslot of the message block containing the MODIFY message at time T then the MS shall be ready to transmit the MODIFY COMPLETE message before time T + 500 ms.

5.4.7 DTMF

This requirement applies when the MS's DTMF function is not disabled.

When the first number key is pressed on the MS during the Active (U10) state of a call at time T, then the MS shall be ready to transmit the START DTMF message before time T + 500 ms.

5.5 Supplementary service signalling

5.5.1 Advice of Charge Charging (AoCC)

The following requirements only apply to mobile stations that support the Advice of Charge Charging supplementary service defined in GSM 04.86 [5].

If the last timeslot of the message block in which a Call Control message with a Facility information element containing the operation ForwardChargeAdvice with the SS code set to AoCC occurs at time T, then the MS shall be ready to transmit a message with a Facility information element containing a Return result with the same Invoke ID before time T + 1 second.

5.6 Short Message Services Point-to-Point

These requirements relate to signalling using SAPI 3.

5.6.1 CP-DATA

If the last timeslot of the message block containing a CP-DATA message occurs at time T, then the MS shall be ready to transmit the CP-ACK message before T + 500 ms.

5.6.2 RP-DATA

If the last timeslot of the message block containing a RP-DATA message which will be stored in the ME and for which the ME has storage room available occurs at time T, then the MS shall be ready to transmit the RP-ACK message before time T + 1 second.

If the last timeslot of the message block containing a RP-DATA message whose destination is the SIM and for which the SIM has storage room available occurs at time T, then the ME shall start to send the short message on the ME - SIM interface before time T + 250 ms.

If the last timeslot of the message block containing a RP-DATA message whose destination is the TE occurs at time T, then the ME shall start to send the short message on the ME - TE interface before time T + 250 ms.

In the case of a short message supplied to the SIM, if the response from the SIM that triggers the sending of the RP-ACK message is completed on the SIM-ME interface at time T, then the MS shall be ready to transmit the RP-ACK message before time T + 250 ms.

In the case of a short message supplied to the TE, if the response from the TE that triggers the sending of the RP-ACK message is completed on the TE-ME interface at time T, then the MS shall be ready to transmit the RP-ACK message before time T + 250 ms.

History

Document history	
May 1996	Publication of GSM 04.13 version 5.0.0
November 1996	Unified Approval procedure UAP 59: 1996-11-25 to 1997-03-21
May 1997	One-step Approval Procedure OAP 9735: 1997-05-02 to 1997-08-29 (Second Edition)
September 1997	Second Edition