ETSI TR 122 903 V17.0.0 (2022-04)



Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE;

Study on Videotelephony teleservice (3GPP TR 22.903 version 17.0.0 Release 17)



Reference RTR/TSGS-0122903vh00 Keywords GSM,LTE,UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from: http://www.etsi.org/standards-search

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx

If you find errors in the present document, please send your comment to one of the following services: https://portal.etsi.org/People/CommiteeSupportStaff.aspx

If you find a security vulnerability in the present document, please report it through our Coordinated Vulnerability Disclosure Program:

https://www.etsi.org/standards/coordinated-vulnerability-disclosure

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022. All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (https://ipr.etsi.org/).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECTTM, **PLUGTESTS**TM, **UMTS**TM and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP**TM and **LTE**TM are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M**TM logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM**[®] and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Report (TR) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Modal verbs terminology

In the present document "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the ETSI Drafting Rules (Verbal forms for the expression of provisions).

"must" and "must not" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

Intell	ectual Property Rights	2
Lega	1 Notice	2
Mod:	al verbs terminology	2
	word	
1	Scope	5
2	References	5
3	Definitions, symbols and abbreviations	5
3.1	Definitions	5
3.2	Abbreviations	
4	Overview of CS videotelephony support in 3GPP specifications up to Release 6	6
4.1	Codec	
4.2	Charging	<i>6</i>
4.3	Supplementary services	
5	Requirements for videotelephony service	7
5.1	Charging	
5.2	Codec negotiation	
5.3	Security	8
5.4	Privacy	8
5.5	Supplementary service support	
5.6	Fall back to speech and in-call modification	9
5.7	Subscription	9
5.8	Handover	9
5.9	Emergency calls support	
5.10	Notifications to the User	9
6	Backwards compatibility requirements	10
6.1	General description of functionalities that are supported in a videotelephony call to a pre Rel-7	
- 0	videotelephony	
6.2	Interoperability with fixed videotelephony service	
7	International calls and roaming	12
8	Conclusions	12
Anno	ex A: Existing requirements for videotelephony	14
Anno	ex B: Change history	15
Histo	orv	16

Foreword

This Technical Report has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document intends to analyse the introduction of additional functionalities for the videotelephony service in addition to what is provided in the 3GPP specifications up to Release 6. The functionalities will include but are not limited to codec negotiation, charging principles, supplementary services support. The approach followed is to evaluate how functionalities which are applicable to existing teleservices can be replicated for videotelephony.

The document will analyse how the new functionalities will impact the backwards compatibility with the existing CS multimedia service and will whether it is beneficial to create a videotelephony teleservice.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- 3GPP TR 21.905: "Vocabulary for 3GPP specifications".
 3GPP TS 22.004: "General on Supplementary Services".
 3GPP TS 22 101: "Service Principles".
 3GPP TS 26.110: "Codec for circuit switched multimedia telephony service".
 3GPP TS 26.111: "Modification to H.324".
 3GPP TS 21.133: "3G security; Security threats and requirements".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply.

Teleservice: Is a type of telecommunication service that provides the complete capability, including terminal equipment functions, for communication between users according to standardised protocols and transmission capabilities established by agreement between operators.

Videotelephony: a instance of bidirectional multimedia communications between two parties where a speech component and a video component are transmitted and received.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

VT Video Telephony UE User Equipment

Further abbreviations are given in 3GPP TR 21.905 [1].

4 Overview of CS videotelephony support in 3GPP specifications up to Release 6

The CS Multimedia telephony is a Bearer Service, which is using the basic bearer service BS30 in the Core Network. On the air interface the BS30 is mapped to the Radio Access Bearer (RAB) using the traffic class "Conversational" with 64kbps CS in UL and DL direction.

4.1 Codec

ITU-T has specified that Recommendation H.324 should be used for video telephony in circuit switched connection. The 3GPP-variant of H.324 is named 3G-324M and the corresponding 3GPP specification is the [4] TS 26.110 " Codec for circuit switched multimedia telephony service" and [5] TS 26.111 " Modification to H.324". 3G-324M terminals provide real-time video, audio, or data, in any combination over 3GPP circuit-switched radio networks.

4.2 Charging

The RAB and the corresponding BS30 is not only for video telephony, data transfer is also possible. The user is able to select via terminal, depending on terminal capabilities, which service they prefer, but the CN may not be able to distinguish between video telephony and data transfer unless the UE provides such indication. This also applies to changes during call set-up and in-call modification of the requested service. That means the current charging architecture may not be able to support e.g. two different pricing models for video telephony and data transfer.

4.3 Supplementary services

The BS30 is a general synchronous bearer service with support of supplementary services. [2] TS 22.004 includes an overview of the supplementary services which are supported and which are not supported by the BS30 bearer as shown in the table below:

Su	pplementary Service	Support by BS30				
eMLPP	enhanced Multi-Level	Yes				
	Precedence and Pre-emption					
CD	Call Deflection	Yes				
CLIP	Calling Line Identification	Yes				
	Presentation					
CLIR	Calling Line Identification	Yes				
	Restriction					
COLP						
	Presentation Connected Line Identification					
COLR	Yes					
	Restriction					
CFU	Call Forwarding Unconditional	Yes				
CFB	Call Forwarding on Mobile	Yes				
	Subscriber Busy					
CFNRy	Call Forwarding on No Reply	Yes				
CFNRc	Call Forwarding on Mobile	Yes				
	Subscriber Not Reachable					
CW	Call Waiting	Yes				
HOLD	Call Hold	No				
MPTY	Multi Party Service	No				
CUG	Closed User Group	Yes				
AoCI	Advice of Charge (Information)	Yes				
AoCC	Advice of Charge (Charging)	Yes				
UUS	User-to-user signalling	Yes				
BAOC	Barring of All Outgoing Calls	Yes				
BOIC	Barring of Outgoing	Yes				
	International Calls					
BOIC-exHC	Barring of Outgoing	Yes				
	International Calls except					
	those directed to the Home					
510	PLMN Country	.,				
BIC	Barring of All Incoming Calls	Yes				
BIC-Roam	Barring of Incoming Calls	Yes				
	when Roaming Outside the					
FOT	Home PLMN Country	NI-				
ECT Explicit Call Transfer CCBS Completion of calls to busy		No Var				
CCBS	Completion of calls to busy subscribers	Yes				
SPNP	Support of Private Numbering	Yes				
	Plan					
CNAP	Calling Name Presentation	No				
MSP	Multiple Subscriber Profiles	Yes				
MC	Multicall	Yes				

5 Requirements for videotelephony service

5.1 Charging

It should be possible for the network to identify when a videotelephony is established so that accurate charging can be realised. All the events related to the videotelephony call such as modifications of the service type (e.g. speech call to videotelephony call modification, fall back to speech), modification of the codecs and so on should be recorded.

5.2 Codec negotiation

It should be possible for terminals to perform codec negotiation during videotelephony call set up. This should result in reduced call set up time for videotelephony calls and may allow new and more efficient video codecs to be introduced

easily within mobile networks. This should be realised in the same fashion as speech call where the calling terminal presents to the recipient a list of supported codecs alongside the preferred one.

5.3 Security

The user shall be able to use and access the VT service in a secure manner. It shall be possible to deny access to the VT service to unauthorized users. An authorization may be based on the identity of the originating and/or destination user/device.

The "Security Threats and Requirements" specified in [6] shall not be compromised.

5.4 Privacy

It shall be possible to prevent exchange of user's identity during call setup (e.g., by using CLIR/COLR). In addition, to protect user privacy it shall be possible to:

- enable/disable video camera during the call.
- accept a video call in audio mode only.
- enable/disable audio during the call (mute/unmute).

A recipient shall be informed of the identity of the sender in case the sender has not restricted his identity to be transmitted.

Optional support for ciphering user audio/video/data sessions should be considered.

Note: this may be in conflict with lawful intercept if the encrypting in this case is user to user and the network is not able to recover the keys.

5.5 Supplementary service support

At least the following supplementary services should be supported for videotelephony, which are already available for BS30:

- eMLPP (enhanced Multi-Level Precedence and Pre-emption)
- CD (Call Delfection)
- CLIP (Calling Line Identification Presentation)
- CLIR (Calling Line Identification Restriction)
- COLP (Connected Line Identification Presentation)
- COLR (Connected Line Identification Restriction)
- all the call forwarding types (CFU, CFB, CFNRy, CFNRc)
- CW (Call Waiting)
- CUG (Closed User Group)
- AoCI (Advice of Charge Information) and AoCC (Advice of Charge Charging)
- UUS (User-to-user signalling)
- all types of barring (BAOC, BOIC, BOIC -exHC, BIC, BIC-Roam)
- CCBS (Call Completion to Busy Subscriber)
- SPNP (Support of Private Numbering Plan)
- MSP (Multiple Subscriber Profiles)

- MC (Multicall)

Furthermore following supplementary services should be supported:

- HOLD:
- CNAP (calling name presentation)

The support of multiparty is for further study.

5.6 Fall back to speech and in-call modification

When the radio access network of the calling party or of the called party cannot support any longer the video media, or the interconnection between networks does not or no longer support videotelephony, the videotelephony call should be downgraded to a speech call. The transition from videotelephony to speech should be realised with minimum (ideally without) interruptions.

When the videotelephony call can be supported again the downgraded call, i.e.the speech call, may be upgraded to a videotelephony call. The transition from speech to videotelephony should be realised with minimum (ideally without) interruptions.

The fall back from videotelephony to speech and the upgrade from speech to videotelephony should be supported when requested by either party.

The user should be able to deny a service change from speech to videotelephony.

It should be possible to accept a videotelephony call with downgrading to speech, which means the user should be able to request a downgrade of an incoming videotelephony call before the call is answered resulting in establishing a speech call only.

5.7 Subscription

It should be possible for the mobile operator to control the access to the videotelephony service by means of a subscription to the service.

5.8 Handover

Inter-system handover between UMTS and GSM is not supported for 64 kbps UDI calls. In the case of a user moving out of 3G coverage, the video call will be released. The user has to establish a voice call either manually or the handset provides a voice call set up automatically. In the early days of UMTS this is an especially likely scenario. Therefore, the handover from 3G to 2G linked with a downgrade from video to voice is a desirable functionality.

Handover of VT between UMTS and I-WLAN should be available if the network is available and if the terminal has this functionality.

5.9 Emergency calls support

The capability of establishing a videotelephony call towards an emergency number should not be mandatory. If a user attempts to establish a videotelephony call to an emergency service, which is not equipped to handle video telephony calls, the UE or the network should be able to transform it to an emergency speech call (TS12) set up request.

5.10 Notifications to the User

A network should provide notifications to the user(s) if needed, e.g., if the call set-up is unsuccessful or modified (e.g., by applying supplementary services).

Notifications can consist of audible (e.g. announcement) and / or of visible (e.g. picture or video) and / or textual information.

6 Backwards compatibility requirements

Taking into account that there is already a large population of UEs and networks that support videotelephony services using the BS30 multimedia call bearer service, a new videotelephony teleservice (if specified) shall provide interworking and interoperability with the BS30 multimedia call bearer service. Moreover, the specification of a videotelephony teleservice shall have no negative impact on the interworking and interoperability of videotelephony services provided based on the BS30 multimedia call bearer service specified in 3GPP releases prior to Rel-7.

It shall be possible for a videotelephony teleservice capable UE to initiate and terminate a call towards a UE supporting BS30 multimedia calls. In other words, it is required that a videotelephony capable UE behaves towards a BS30 multimedia call capable network and/or UE as a BS30 multimedia call capable UE.

The following table provides an overview of the backwards compatibility requirements for a new videotelephony teleservice:

			UE feature support			
			New Videotelephony Teleservice	BS 30 Multimedia Call Bearer		
ıt	New Videotelephony Teleservice	HPLMN	Out of scope of this study	Backwards Compatibility Required		
ure support		VPLMN	Out of scope of this study	Backwards Compatibility Required		
Network feature	BS 30 HPLN Multimedia Call Bearer		Backwards Compatibility Required	Out of scope of this study		
Ne		VPLMN	Backwards Compatibility Required	Out of scope of this study		

Figure 6.1: Overview of backwards compatibility requirements for a new videotelephony teleservice

Backwards compatibility between a new videotelephony teleservice (if specified) and videotelephony services using the BS30 multimedia call bearer service shall be provided for all roaming and intra and inter-PLMN call connection scenarios from the perspectives of the UE, HPLMN, VPLMN and interconnection network capabilities. As a minimum, if a new videotelephony teleservice is specified by 3GPP backwards compatibility shall be provided for the following scenarios:

- General

- Support of videotelephony services for a UE supporting videotelephony services using the BS30 multimedia call bearer service within PLMNs that support the new videotelephony teleservice
- Support of videotelephony services for a UE supporting the new videotelephony teleservice within PLMNs that support only the BS30 multimedia call bearer service

- Roaming

 Support of videotelephony services for a UE supporting the new videotelephony teleservice roaming in a VPLMN that does not support the new videotelephony teleservice but supports the BS30 multimedia call bearer service - Support of videotelephony services for a UE supporting videotelephony services using the BS30 multimedia call bearer service roaming in a VPLMN that supports the new videotelephony teleservice

- Intra-PLMN connection

- Intra-HPLMN connection between a UE supporting the new videotelephony teleservice and a UE supporting videotelephony services using the BS30 multimedia call bearer service

Note 1: In the following scenarios the HPLMN and VPLMN is the same network.

- Intra-PLMN connection between a UE supporting the new videotelephony teleservice roaming within a VPLMN that supports the new videotelephony service and a UE supporting videotelephony services using the BS30 multimedia call bearer service within its HPLMN
- Intra-PLMN connection between a UE supporting the new videotelephony teleservice roaming within a VPLMN that does not support the new videotelephony service and a UE supporting videotelephony services using the BS30 multimedia call bearer service within its HPLMN

- Inter-PLMN connection

Note 2: In the following scenarios the HPLMNs are different networks and may be in different countries.

- Inter-HPLMN connection between a UE supporting the new videotelephony teleservice within its HPLMN and a UE supporting videotelephony services using the BS30 multimedia call bearer within its HPLMN that does not support the new videotelephony teleservice
- Inter-HPLMN connection between a UE supporting the new videotelephony teleservice within its HPLMN and a UE supporting videotelephony services using the BS30 multimedia call bearer within its HPLMN that supports the new videotelephony teleservice
- Note 3: In the following scenarios the HPLMN and VPLMN are different networks and may be in different countries.
 - Inter-PLMN connection between a UE supporting the new videotelephony teleservice within its HPLMN and a UE supporting videotelephony services using the BS30 multimedia call bearer roaming in a VPLMN that does not support the new videotelephony teleservice
 - Inter-PLMN connection between a UE supporting the new videotelephony teleservice within its HPLMN and a UE supporting videotelephony services using the BS30 multimedia call bearer roaming in a VPLMN that supports the new videotelephony teleservice

Note 3: In the following scenarios the VPLMNs are different networks and may be in different countries.

- Inter-PLMN connection between a UE supporting the new videotelephony teleservice roaming in a VPLMN that supports the new videotelephony teleservice and a UE supporting videotelephony services using the BS30 multimedia call bearer roaming within a VPLMN that does not support the new videotelephony teleservice
- Inter-PLMN connection between a UE supporting the new videotelephony teleservice roaming in a VPLMN that does not support the new videotelephony teleservice and a UE supporting videotelephony services using the BS30 multimedia call bearer roaming within a VPLMN that also does not support the new videotelephony teleservice
- Inter-PLMN connection between a UE supporting the new videotelephony teleservice roaming in a VPLMN that supports the new videotelephony teleservice and a UE supporting videotelephony services using the BS30 multimedia call bearer service roaming within a VPLMN that also supports the new videotelephony teleservice
- Inter-PLMN connection between a UE supporting the new videotelephony teleservice roaming in a VPLMN that does not support the new videotelephony teleservice and a UE supporting videotelephony services using the BS30 multimedia call bearer service roaming within a VPLMN that supports the new videotelephony teleservice

6.1 General description of functionalities that are supported in a videotelephony call to a pre Rel-7 videotelephony

6.2 Interoperability with fixed videotelephony service

Similar to the BS30 multimedia call bearer service the new videotelephony teleservice (if specified) should support interconnection with CS videotelephony services provided by PSTN and ISDN fixed networks.

7 International calls and roaming

As Video Telephony depends on the 64kbps UDI bearer, for national as well as international and roaming calls, such a bearer must be provided by all carriers used for this specific connection. Presently many long distance carriers do not guarantee this functionality. If the 64kbit/s UDI bearer is not provided end to end, this may lead to SS7 signalling issues.

Note: This issue is FFS.

8 Conclusions

This study has identified the enhancements needed for videotelephony services including:

- Call setup time improvements
- Additional support of supplementary services
- Charging improvements
- Improved in call modification
- More efficient emergency videotelephony call support
- User notification

These enhancements can be provided by either:

- 1. standardising a new videotelephony teleservice.
- 2. improving the existing videotelephony service that is based on BS30

For both alternatives backwards compatibility with existing videotelephony services using the BS30 Multimedia Call Bearer Service is essential.

Some of the possible advantages for defining a videotelephony teleservice are:

- ability to negotiate the codecs used in the VT call using already standardised mechanisms available today for teleservices
- ability to differentiate the charging between videotelephony and data transfers using BS30
- simplification of handling of call modification for network operators compared to videotelephony services provided using the BS30 Multimedia Call Bearer Service
- simplification of downgrading the service to speech in case of changing from 3G to 2G and vice versa compared to videotelephony services provided using the BS30 Multimedia Call Bearer Service
- the same handling of supplementary services as other teleservices
- unique subscription for videotelephony services including unique definition within roaming agreements which may improve interoperator charging

possible definition of a unique emergency videotelephony teleservice (if required)

These need to be balanced against possible disadvantages of defining two alternative solutions for providing videotelephony services.

Annex A:

Existing requirements for videotelephony

Annex B: Change history

	Change history										
TSG SA#	SA Doc.	SA1 Doc	Spec	CR	Rev	Rel	Cat	Subject/Comment	Old	New	WI
2005-04			22.903					Initial draft	0.0.0	0.1.0	
2005-05			22.903					Output of SWG May2005	0.1.0	0.2.0	
2005-07			22.903					Output of SWG July 2005	0.2.0	1.0.0	
2005-10			22.903					Output of SWG October 2005	1.0.0	1.1.0	
2005-10			22.903					Output of SA1 October 2005	1.1.0	2.0.0	
SP-30	SP-050757	S1-051242	22.903			Rel-7		Approved for Rel-7 at SA #30	2.0.0	7.0.0	MITE
SP-42	-	-				Rel-8		Updated from Rel-7 to Rel-8	7.0.0	8.0.0	
SP-46	-	-	-	-	-	-	-	Updated to Rel-9 by MCC	8.0.0	9.0.0	
2011-03	-	-	-	-	-	-	-	Update to Rel-10 version (MCC)	9.0.0	10.0.0	
2012-09	-	-	-	-	-	-	-	Updated to Rel-11 by MCC	10.0.0	11.0.0	
2014-10								Updated to Rel-12 by MCC	11.0.0	12.0.0	
2015-12	-	-	-	-	-	-	-	Updated to Rel-13 by MCC	12.0.0	13.0.0	
2017-03	-	-	-	-	-	-	-	Updated to Rel-14 by MCC	13.0.0	14.0.0	
2018-06	-	-	-	-	-	-	-	Updated to Rel-15 by MCC	14.0.0	15.0.0	
SA#88e	-	-	-	-	-	-	-	Updated to Rel-16 by MCC	15.0.0	16.0.0	
2022-03	-	-	-	-	-	-	-	Updated to Rel-17 by MCC	16.0.0	17.0.0	

History

Document history						
V17.0.0	April 2022	Publication				