

ETSI TR 136 913 V17.0.0 (2022-05)



LTE;
**Requirements for further advancements for Evolved Universal
Terrestrial Radio Access (E-UTRA) (LTE-Advanced)**
(3GPP TR 36.913 version 17.0.0 Release 17)



Reference

RTR/TSGR-0036913vh00

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Report (TR) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions, symbols and abbreviations	5
3.1 Definitions	5
3.2 Symbols.....	5
3.3 Abbreviations	5
4 Introduction	5
5 Objective	6
6 General requirements	7
7 Capability-related requirements	8
7.1 Peak Data Rate	8
7.2 Latency	8
7.2.1 C-plane latency	8
7.2.1.1 C-plane capacity.....	8
7.2.2 U-Plane latency.....	9
8 System performance requirements	9
8.1 Spectrum efficiency.....	9
8.1.1 Peak spectrum efficiency	9
8.1.2 Average spectrum efficiency	9
8.1.3 Cell edge user throughput	10
8.1.4 VoIP capacity.....	10
8.2 Mobility.....	10
8.3 Coverage.....	11
8.4 Further Enhanced MBMS	11
8.5 Network synchronization	11
9 Deployment-related requirements	11
9.1 Deployment scenarios	11
9.2 Spectrum flexibility	11
9.3 Spectrum deployment.....	12
9.4 Co-existence and interworking with legacy RATs.....	12
10 Requirements for E-UTRAN architecture and migration	12
11 Radio Resource Management requirements.....	12
12 Complexity requirements	12
13 Cost-related requirements.....	13
14 Service-related requirements.....	13
Annex A (informative): System performance evaluation model.....	14
A.1 System performance evaluation model	14
Annex B (informative): Change history	15
History	16

Foreword

This Technical Report has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

This document contains requirements for the further advancements for E-UTRA/E-UTRAN.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] (void)
- [2] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [3] 3GPP TR 25.913: "Requirements for Evolved UTRA (E-UTRA) and Evolved UTRAN (E-UTRAN)".
- [4] ITU-R Circular Letter 5/LCCE/2 on IMT-Advanced
- [5] 3GPP TR 25.912: "Feasibility study for evolved Universal Terrestrial Radio Access (UTRA) and Universal Terrestrial Radio Access Network (UTRAN)".

3 Definitions, symbols and abbreviations

3.1 Definitions

Void

3.2 Symbols

Void

3.3 Abbreviations

For the purposes of the present document, the abbreviations defined in 3GPP TS 21.905 [2] and the following apply:

4 Introduction

At the 3GPP TSG RAN #39 meeting, the Study Item description on "Further Advancements for E-UTRA (LTE-Advanced)" was approved (RP-080137).

The justification of the Study Item was as follows;

IMT-Advanced is entering the phase of the process in ITU-R addressing the development of the terrestrial radio interface recommendations. To announce this stage of the process for IMT-Advanced, ITU-R has issued a Circular Letter(CL) to invite submission of candidate Radio Interface Technologies (RITs) or a set of RITs (SRITs) for IMT-Advanced. The key features of IMT-Advanced delineated in the CL are:

- a high degree of commonality of functionality worldwide while retaining the flexibility to support a wide range of services and applications in a cost efficient manner;
- compatibility of services within IMT and with fixed networks;
- capability of interworking with other radio access systems;
- high quality mobile services;
- user equipment suitable for worldwide use;
- user-friendly applications, services and equipment;
- worldwide roaming capability; and
- enhanced peak data rates to support advanced services and applications (100 Mbit/s for high and 1 Gbit/s for low mobility were established as targets for research) .

The base line requirements for IMT-Advanced will be concluded in ITU-R WP 5D #2 (June 2008) and communicated in an Addendum to the Circular Letter in the July 2008 timeframe.

In the WRC07, the following spectrum bands were proposed as additions to the prior identified bands, and the parts of the existing and new bands are globally or regionally identified for IMT, which is the new root term to encompass both IMT-2000 and IMT-Advanced.

- 450 MHz band
- UHF band (698-960 MHz)
- 2.3 GHz band
- C-band(3400-4200 MHz)

In 3GPP, E-UTRA should be further evolved for the future releases in accordance with:

- 3GPP operator requirements for the evolution of E-UTRA
- The need to meet/exceed the IMT-Advanced capabilities.

Considering the above, 3GPP TSG-RAN should study further advancements for E-UTRA (LTE-Advanced) toward meeting:

- Requirements for IMT-Advanced and provide ITU-R with proposals of RITs or SRITs according to the defined ITU-R time schedule provided in the Circular Letter and its Addendums.
- 3GPP operators requirements for the evolution of E-UTRA

5 Objective

The objective of Further Advancements for E-UTRA is as follows;

- A) Define a framework for further advancements of E-UTRA and E-UTRAN (to be referred to as Advanced E-UTRA and Advanced EUTRAN considering:
 - The time schedule of ITU-R
 - That the work on Advanced E-UTRA and Advanced E-UTRAN must not introduce any delay to the completion of the Release 8 specification of E-UTRA and E-UTRAN
 - That the general enhancements of specifications for Release 8 E-UTRA and E-UTRAN are maintained and progressed in a focused and efficient manner.
- B) Define requirements for Advanced E-UTRA and Advanced E-UTRAN based on the ITU-R requirements for IMT-Advanced as well as 3GPP operators own requirements for advancing Release 8 E-UTRA AND E-UTRAN considering:

- E-UTRA radio technology and architecture improvements
 - Support for all radio modes of operation
 - Interworking with legacy RATs (scenarios and performance requirements)
 - Backward compatibility of Advanced E-UTRA and Advanced E-UTRAN with Release 8 E-UTRA and E-UTRAN i.e.
 - an Release 8 E-UTRA terminal can work in an Advanced E-UTRAN,
 - an Advanced E-UTRA terminal can work in an Release 8 E-UTRAN and
 - non-backward compatible elements could be considered based on RAN decision
 - Newly identified frequency bands and existing frequency bands, and their advantages and limitations, in particular, the consideration of the WRC-07 conclusions, to ensure that Advanced E-UTRA can accommodate radio channel bandwidths commensurate with the availability in parts of the world of wideband channels in the spectrum allocations (above 20 MHz) and at the same time being mindful on the need to accommodate those parts of the world where the spectrum allocations will not have availability of wideband channels
- C) Identify potential solutions, technologies for the Advanced E-UTRA and Advanced E-UTRAN. The study areas include:
- Physical layer
 - Radio interface layer 2 and RRC
 - E-UTRAN architecture
 - RF, including Aspects of wider channel bandwidth than 20 MHz
 - Advanced system concepts
- D) To develop documents that will serve as a basis for the documentation to be submitted to ITU-R to provide the 3GPP proposals for IMT-Advanced:
- 1) An "Early Proposal" submission that would be sent to ITU-R, to be agreed at RAN #41 (9-12 September 2008), for submission to WP 5D #3 (8-15 October 2008).
 - 2) A "Complete Technology" submission that would be sent to ITU-R, to be agreed at RAN #44 (26-29 May 2009), for submission to WP 5D #5 (planned for 10-17 June 2009).
 - 3) A "Final" submission to incorporate updates, additional specific details or feature additions, *and* the required self-evaluation that would be sent to ITU-R, to be agreed at RAN #45 (22-25 September 2009), for submission to WP 5D #6 (planned for 13-20 Oct 2009).
- 3GPP should take note, that by ITU-R convention, the formal submission deadline for ITU-R meetings has been established as 16:00 hours UTC, seven calendar days prior to the start of the meeting.
- E) Make recommendations for future WIs
- F) For reference, the Circular Letter as received from the ITU-R (and future Addendums to the same) are annexed to this Work Item and should become an integral part of the WI.

6 General requirements

The following general requirements are valid for Advanced E-UTRA and Advanced E-UTRAN

- Advanced E-UTRA and Advanced E-UTRAN shall be an evolution of Release 8 E-UTRA and E-UTRAN
- All relevant requirement in [3] are valid also for Advanced E-UTRA and Advanced E-UTRAN

- Advanced E-UTRA and Advanced E-UTRAN shall meet or exceed IMT-Advanced requirements within the ITU-R time plan

The expectancy is that Advanced E-UTRA should provide substantially higher performance compared to what is expected to be the IMT-Advanced requirements in ITU-R. The values provided in clauses 7 and 8 have been expressed as preferred performance of Advanced E-UTRA. These values are recognised as being very ambitious, especially in light of the ITU-R time plan, and the performance evaluation results generated for LTE R8, but are adopted as long term target for Advanced E-UTRA"

7 Capability-related requirements

7.1 Peak Data Rate

The peak data rate is the maximum data rate to be supported from a system requirement viewpoint (i.e. not from radio performance requirement viewpoint) regardless of radio interface parameters such as the transmission bandwidth and antenna configuration.

Advanced E-UTRA should support significantly increased instantaneous peak data rates.

At a minimum, Advanced E-UTRA should support the key feature of IMT-Advanced which is stated in the Circular Letter from the ITU-R as "enhanced peak data rates to support advanced services and applications (100 Mbit/s for high and 1 Gbit/s for low mobility were established as targets for research)"

The system should target a downlink peak data rate of 1 Gbps and an uplink peak data rate of 500 Mbps.

7.2 Latency

7.2.1 C-plane latency

The overall C-Plane latency shall be significantly decreased compared to EPS Rel-8. The C-Plane latency takes into account RAN and CN latencies (excluding the transfer latency on the S1 interface) in unloaded conditions.

The target for transition time from Idle mode (with IP address allocated) to Connected mode is less than 50 ms including the establishment of the user plane (excluding the S1 transfer delay).

The target for the transition from a "dormant state" in Connected Mode (i.e. DRX substate in Connected Mode in E-UTRAN) is less than 10 ms (excluding the DRX delay).




Figure 7.1: Requirements for state transitions

7.2.1.1 C-plane capacity

The system should be able to support at least 300 active users without DRX in a 5 MHz bandwidth. The same number of RRC connections with DRX as in Release 8 E-UTRA and E-UTRAN (16k) is expected.

7.2.2 U-Plane latency

Advanced E-UTRA and Advanced E-UTRAN should allow for reduced U-plane latency compared to Release 8 E-UTRA and E-UTRAN, specifically in situations where:

- The UE does not have a valid scheduling assignment
- The UE needs to synchronise and obtain a scheduling assignment

The U-Plane latency is defined as the minimum achievable user plane latency with the system configurations optimized for latency

8 System performance requirements

8.1 Spectrum efficiency

In this section, the target for peak spectrum efficiency, the average spectrum efficiency, and cell edge spectrum efficiency are defined. The target for average spectrum efficiency and the cell edge user throughput efficiency should be given a higher priority than the target for peak spectrum efficiency and VoIP capacity.

The target for average spectrum efficiency and the cell edge spectrum efficiency should be achieved simultaneously.

8.1.1 Peak spectrum efficiency

The peak spectrum efficiency is the highest data rate normalised by overall cell bandwidth assuming error-free conditions, when all available radio resources for the corresponding link direction are assigned to a single UE.

The system target to support downlink peak spectrum efficiency of 30 bps/Hz and uplink peak spectrum efficiency of 15 bps/Hz.

Assumption of antenna configuration is 8x8 or less for DL and 4x4 or less for UL

8.1.2 Average spectrum efficiency

Average spectrum efficiency is defined as the aggregate throughput of all users (the number of correctly received bits over a certain period of time) normalized by the overall cell bandwidth divided by the number of cells. The average spectrum efficiency is measured in b/s/Hz/cell.

Advanced E-UTRA should target the average spectrum efficiency to be as high as possible, given a reasonable system complexity.

The expectation at the end of the study item is that the values of all the targets (of the different configurations) will be made available, but currently the evaluation for the blanked out boxes in the table below, are a lower priority.

Advanced E-UTRA should target the average spectrum efficiencies in different environments below.

Table 8.1 Targets for average spectrum efficiency

Radio env.		Case 1 [bps/Hz/cell]	Micro	Indoor	Rural/ High speed
Ant. Config	UL				
	DL				
	1x2	1.2			
	2x4	2.0			
	2x2	2.4			
	4x2	2.6			
	4x4	3.7			

NOTE: There is a need to define all the cases in the tables. Case 1 is defined in Annex A. Case 1 is included to permit 3GPP to compare Advanced E-UTRA to Release 8 E-UTRA. 3GPP should consider that the other environments would be based on the ITU-R environments (these are currently designated as High Speed, Base Coverage Urban, Microcellular, & Indoor). These environments are defined in Recommendation/Reports [IMT.TECH] and [IMT.EVAL] which are expected to be concluded in ITU-R WP 5D in early July 2008. Such definitions would ensure consistency with developing submissions to ITU-R for IMT-Advanced and for consistency with performing simulations, etc. Thus 3GPP would have 5 environments Case 1 plus the 4 ITU-R environments.

8.1.3 Cell edge user throughput

The cell edge user throughput is defined as the 5% point of CDF of the user throughput normalized with the overall cell bandwidth.

Advanced E-UTRA should target the cell edge user throughput to be as high as possible, given a reasonable system complexity.

A more homogeneous distribution of the user experience over the coverage area is highly desirable and therefore a special focus should be put on improving the cell edge performance.

The expectation at the end of the study item is that the values of all the targets (of the different configurations) will be made available, but currently the evaluation for the blanked out boxes in the table below, are a lower priority.

Advanced E-UTRA should target the cell edge user throughput below in different environments

Table 8.2 Targets for cell edge throughput

Radio env.		Case 1 [bps/Hz/cell/user*]	Micro	Indoor	Rural/ High speed
Ant. Config	UL				
	DL				
	1x2	0.04			
	2x4	0.07			
	2x2	0.07			
	4x2	0.09			
	4x4	0.12			

* 10 users uniform-randomly dropped in the cell

NOTE: There is a need to define all the cases in the tables. Case 1 is defined in Annex A. Case 1 is included to permit 3GPP to compare Advanced E-UTRA to Release 8 E-UTRA. 3GPP should consider that the other environments would be based on the ITU-R environments (these are currently designated as High Speed, Base Coverage Urban, Microcellular, & Indoor). These environments are defined in Recommendation/Reports [IMT.TECH] and [IMT.EVAL] which are expected to be concluded in ITU-R WP 5D in early July 2008. Such definitions would ensure consistency with developing submissions to ITU-R for IMT-Advanced and for consistency with performing simulations, etc. Thus 3GPP would have 5 environments Case 1 plus the 4 ITU-R environments.

8.1.4 VoIP capacity

VoIP capacity should be improved relative to that shown in the evaluation for E-UTRA and E-UTRAN in [5] for all antenna configurations.

8.2 Mobility

The system shall support mobility across the cellular network for various mobile speeds up to 350km/h (or perhaps even up to 500km/h depending on the frequency band).

System performance shall be enhanced for 0 to 10km/h and preferably enhanced but at least no worse than E-UTRA and E-UTRAN for higher speeds

8.3 Coverage

Requirements for Coverage in Release 8 E-UTRA and E-UTRAN [3] are applicable for Advanced E-UTRA and Advanced E-UTRAN.

8.4 Further Enhanced MBMS

The targets for MBMS in Advanced E-UTRA and Advanced E-UTRAN should be better than those studied in Release 8 E-UTRA and E-UTRAN [3]. Specifically, the target spectrum efficiency for MBMS in Advanced E-UTRA should be better than that in Release 8 E-UTRA.

8.5 Network synchronization

Requirements for Network synchronization in Release 8 E-UTRA and E-UTRAN [3] are applicable for Advanced E-UTRA and Advanced E-UTRAN.

9 Deployment-related requirements

9.1 Deployment scenarios

Advanced E-UTRA and Advanced E-UTRAN will be deployed as an evolution of Release 8 E-UTRA and E-UTRAN and on new bands. Advanced E-UTRA and Advanced E-UTRAN shall be backwards compatible with Release 8 E-UTRA and E-UTRAN in the sense that

- a Release 8 E-UTRA terminal can work in an Advanced E-UTRAN,
- an Advanced E-UTRA terminal can work in an Release 8 E-UTRAN

However, non-backward compatible element might be considered if significant gain or benefit can be achieved.

It should be expected to have increased deployment of indoor eNB and HNB in Advanced E-UTRAN.

In addition to the deployment scenario in Release 8 E-UTRA and E-UTRAN, the system shall be considered in indoor scenario.

9.2 Spectrum flexibility

The initial identified bands in addition to the already allocated bands in E-UTRA are follows:

- 450–470 MHz band,
- 698–862 MHz band,
- 790–862 MHz band,
- 2.3–2.4 GHz band,
- 3.4–4.2 GHz band, and
- 4.4–4.99 GHz band.

Advanced E-UTRA shall operate in spectrum allocations of different sizes including wider spectrum allocations than those of Release 8 E-UTRA to achieve higher performance and the target peak data rate, e.g. up to 100 MHz.

Main focus for wider bandwidth solution than 20MHz should be on consecutive spectrum, but Aggregation of the spectrum for Advanced E-UTRA should be supported considering reasonable UE complexity

FDD and TDD should be supported for existing paired and unpaired band, respectively

For new identified band, duplex mode should be studied considering, e.g. delay, spectrum efficiency, operation, BS and UE complexity and overall co-existence aspects especially on adjacent channels

9.3 Spectrum deployment

Advanced E-UTRA is required to cope with following scenarios:

- a) Co-existence in the same geographical area and co-location with GERAN/UTRA/E-UTRA on adjacent channels.
- b) Co-existence in the same geographical area and co-location between operators on adjacent channels.
- c) Co-existence on overlapping and/or adjacent spectrum at country borders.
- d) Advanced E-UTRA shall be possible to operate standalone, i.e. there is no need for any other carrier to be available.
- e) All frequency bands should be allowed following release independent frequency band principles
- f) Operation of Release 8 E-UTRA and Advanced E-UTRA in the same spectrum

9.4 Co-existence and interworking with legacy RATs

Following features already supported in previous releases are a pre-requisite for being supported by Advanced E-UTRAN:

- Handovers with legacy RATs
- Network sharing

The same inter-RAT interworking capabilities with at least same performance as in Release 8 E-UTRAN shall be supported.

Intra-RAT handover performance shall be same or better than Release 8 E-UTRAN.

HO requirements for Release 8 E-UTRAN – Advanced E-UTRAN shall be same as intra-Advanced E-UTRAN HO performance.

10 Requirements for E-UTRAN architecture and migration

Advanced E-UTRAN architecture should be based on Release 8 E-UTRAN architecture.

New architecture should be considered in Advanced E-UTRAN if significant benefit can be expected.

11 Radio Resource Management requirements

Radio resource management requirements of Release 8 E-UTRA and E-UTRAN [3] are applicable for Advanced E-UTRA and Advanced E-UTRAN.

12 Complexity requirements

Complexity requirements of Release 8 E-UTRA and E-UTRAN [3] are applicable for Advanced E-UTRA and Advanced E-UTRAN.

13 Cost-related requirements

- Low cost of the infrastructure deployment and terminal for Advanced E-UTRA and Advanced E-UTRAN shall be an essential element
- Power efficiency in the infrastructure and terminal shall be an essential element
- Backhauling shall minimize cost per bit
- Advanced E-UTRA and Advanced E-UTRAN should allow backhaul using LTE spectrum
- Further enhancements of SON and self configuration shall be an essential element, e.g.:
 - Special care with respect to SON shall be taken for special deployment scenarios like network sharing
 - Special care with respect to SON shall be taken for mass deployment scenarios like in the case of home eNBs, i.e. for In and Outbound Mobility for home eNode B and problems caused by incorrect behaviour of home eNBs.
 - Avoiding need for drive tests
 - Impact to UE complexity and power consumption needs to be taken into account
- Operation and maintenance tasks shall be minimized to the maximum possible extent. Where needed it should be based on open interfaces
- eNode B implementation cost efficiency and flexibility for multi-vendor deployments should be considered, such as RF requirements in specific scenarios or base station modularity aspects with e.g. remote radio units and open interfaces
- All the interfaces specified shall be open for multi-vendor equipment interoperability.

14 Service-related requirements

Service related requirements of Release 8 E-UTRA and E-UTRAN [3] are applicable for Advanced E-UTRA and Advanced E-UTRAN.

Annex A (informative): System performance evaluation model

A.1 System performance evaluation model

One of the system performance evaluation models in Advanced E-UTRA (Case 1) is the same as the model used for E-UTRA. The carrier frequency (CF), Inter-site distance (ISD), operating bandwidth (BW), penetration loss (P_{Loss}) and UE speed are given in Table A.1-1.

Table A.1-1 – 3GPP Case 1 model

Simulation	CF	ISD	BW	P_{Loss}	Speed
Cases	(GHz)	(meters)	(MHz)	(dB)	(km/h)
1	2.0	500	10	20	3

Annex B (informative): Change history

Change history					
Date	TSG #	TSG Doc.	Subject/Comment	Old	New
2008-05	RAN#40	RP-080445	Submitted for approval at TSG RAN #40		1.0.0
2008-06			Report approved at TSG-RAN and placed under change control	1.0.0	8.0.0
2009-06			Minor editorial correction to title, keywords, logo, layout	8.0.0	8.0.1
2009-12	RP-46	-	Upgrade to the Release 9 - no technical change	8.0.1	9.0.0
2011-03	RP-51	-	Upgrade to the Release 10 - no technical change	9.0.0	10.0.0
2012-09	RP-57	-	Upgrade to the Release 11 - no technical change	10.0.0	11.0.0
2014-09	RP-65	-	Upgrade to the Release 12 - no technical change	11.0.0	12.0.0
2015-12	RP-70	-	Upgrade to the Release 13 - no technical change	12.0.0	13.0.0
2017-03	RP-75	-	Upgrade to the Release 14 - no technical change	13.0.0	14.0.0
2018-06	RP-80	-	Upgrade to the Release 15 - no technical change	14.0.0	15.0.0
2020-07	RP-88e	-	Upgrade to the Release 16 - no technical change	15.0.0	16.0.0
2022-03	RP-95e	-	Upgrade to the Release 17- no technical change	16.0.0	17.0.0

History

Document history		
V17.0.0	May 2022	Publication