



**5G;
NR;**

**Derivation of test points for radio transmission and reception
User Equipment (UE) conformance test cases
(3GPP TR 38.905 version 17.4.0 Release 17)**



Reference

RTR/TSGR-0538905vh40

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Report (TR) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope	6
2 References	6
3 Definitions, symbols and abbreviations	6
3.1 Definitions	6
3.2 Symbols.....	7
3.3 Abbreviations	7
4 Test coverage analysis.....	7
4.1 Test point analysis for FR1 test cases in TS 38.521-1.....	7
4.1.1 Test point analysis per test case	7
4.1.1.1 FR1 single carrier, NR CA and UL MIMO test cases.....	7
4.1.1.2 FR1 SUL test cases	13
4.1.1.3 FR1 V2X test cases	15
4.1.2 Test point analysis per NS value.....	16
4.1.2.1 A-MPR, A-SEM and A-SE FR1 test cases for single carrier and UL MIMO.....	16
4.1.2.2 A-MPR test cases for FR1 UL CA.....	19
4.1.3 Test point analysis per NR CA configuration.....	19
4.1.3.2 Spurious emissions test cases for FR1 UL CA.....	22
4.2 Test point analysis for FR2 test cases in TS 38.521-2.....	23
4.2.2 Test point analysis per NS value.....	26
4.2.2.1 A-MPR and A-SE FR2 test cases for single carrier	26
4.2.3 Test point analysis per NR CA configuration.....	26
4.2.3.1 Reference Sensitivity test cases for FR2 NR CA	26
4.3 Test point analysis for test cases in TS 38.521-3.....	27
4.3.1 Test point analysis per test case	27
4.3.1.1 EN-DC test cases	27
4.3.1.2 V2X test cases.....	32
4.3.2 Test point analysis per NS value.....	32
4.3.2.1 A-MPR and A-SE test cases for EN-DC.....	32
4.3.3 Test point analysis per EN-DC configuration.....	32
4.3.3.1 Reference sensitivity test cases for EN-DC	32
4.3.3.2 Spurious emissions test cases for EN-DC	40
Annex A: Derivation documents.....	44
Annex B: Principles for test point selection for NR CA reference sensitivity test cases	45
B.1 General	45
B.2 Test case structure	45
B.3 Test Environment	46
B.4 Test Frequencies selection.....	46
B.5 Test Channel Bandwidth selection.....	47
B.6 Modulation selections.....	47
B.7 Examples	47
B.8 Current test completion status per CA configuration	48
B.9 Reference Sensitivity checklist for CA	48
B.9.1 Checklist for two bands.....	48

B.9.2	Checklist for three bands	49
B.9.3	Checklist for four bands and five bands	49
Annex C:	Principles for test point selection for FR2 NR CA reference sensitivity test cases	50
Annex D:	Principles for test point selection for EN-DC reference sensitivity test cases.....	51
D.1	General	51
D.2	Requirements.....	51
D.2.1	Defined EN-DC configurations	51
D.2.2	Definition of exception requirements	52
D.2.3	Reference sensitivity	52
D.2.4	Rx requirements other than reference sensitivity	53
D.2.5	Test case structure and test coverage.....	53
D.2.6	EN-DC configurations to test	54
D.2.6.1	Lower order fallbacks	54
D.2.6.2	EN-DC configurations requiring testing and max number of CCs	55
D.2.6.3	Test coverage	55
D.2.7	Test Environment	59
D.2.8	Test Frequencies selections for EN-DC	59
D.2.9	Test EN-DC channel bandwidth.....	63
D.2.9.1	Test point selection EN-DC configuration without exception	63
D.2.9.2	Test point selection EN-DC configuration with exception	63
D.2.10	RB allocation and RB location selections	63
D.2.10.1	Test point selection EN-DC configuration without exception	63
D.2.10.2	Test point selection EN-DC configuration with exception when exception applies	63
D.2.10.3	Test point selection EN-DC configuration with exception when exception does not apply	63
D.2.11	Modulation scheme selections	64
D.2.12	Current test completion status per EN-DC configuration	64
Annex B:	Change history	65
History		77

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies and contains the derivation of Test Points for NR RF test cases, thereby 3GPP TSG RAN WG5 will have a way of storing the input contributions provided. The test cases are described in TS38.521-1[2], TS38.521-2[3] and TS38.521-3[4],

The test cases which have been analysed to determine Test Points are included as .zip files.

The present document is applicable from Release 15 up to the release indicated on the front page of the present Terminal conformance specifications.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 38.521-1: "NR; UE conformance specification; Radio transmission and reception; Part 1: NR range 1".
- [3] 3GPP TS 38.521-2: "NR; UE conformance specification; Radio transmission and reception; Part 2: NR range 2".
- [4] 3GPP TS 38.521-3: "NR; UE conformance specification; Radio transmission and reception; Part 3: NR interworking between NR range1 + NR range2 and between NR and LTE".
- [5] 3GPP TS 38.101-1: "NR; User Equipment (UE) radio transmission and reception; Part 1: Range 1 Standalone".
- [6] 3GPP TS 38.101-2: "NR; User Equipment (UE) radio transmission and reception; Part 2: Range 2 Standalone".
- [7] 3GPP TS 38.101-3: "NR; User Equipment (UE) radio transmission and reception; Part 3: Range 1 and Range 2 Interworking operation with other radios".
- [8] 3GPP TS 36.101: Evolved Universal Terrestrial Radio Access (E-UTRA); User Equipment (UE) radio transmission and reception".
- [9] R5-206841: "Discussion on test points in Receiver test cases for EN-DC configurations with exception requirements".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

Other definitions used in the present document are listed in 3GPP TS 38.521-1 [2], 3GPP TS 38.521-2 [3] or 3GPP TS 38.521-3 [4].

Editor's note: intended to capture definitions

3.2 Symbols

Symbols used in the present document are listed in 3GPP TR 21.905 [1], 3GPP TS 38.521-1 [2], 3GPP TS 38.521-2 [3] or 3GPP TS 38.521-3 [4].

Editor's note: intended to capture definitions

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

Other abbreviations used in the present document are listed in 3GPP TS 38.521-1 [2], or 3GPP, 3GPP TS 38.521-1 [2], 3GPP TS 38.521-2 [3] or 3GPP TS 38.521-3 [4].

A-SE	Additional spurious emissions
A-SEM	Spectrum Emission Mask

4 Test coverage analysis

This clause contains information on test point analysis and test point selection for RX and TX test configuration tables in [2], [3] and [4]. The test point analysis should include selection of:

- Test environment
- Test frequencies
- Test channel bandwidth
- Test Subcarrier Spacing (SCS)
- Downlink configuration including modulation and RB allocation
- Uplink configuration including modulation and RB allocation
- Number of test points

4.1 Test point analysis for FR1 test cases in TS 38.521-1

4.1.1 Test point analysis per test case

4.1.1.1 FR1 single carrier, NR CA and UL MIMO test cases

This clause contains information on test point analysis and test point selection for single carrier, NR CA and UL MIMO test cases in [2] clause 6 and 7 with information about transmitting test point selection for FR1 listed in table 4.1.1.1-1 and receiver test point selection in table 4.1.1.1-2.

Table 4.1.1.1-1: NR UE transmitter test point selection for FR1

Subclause	Number of test points	Justification in attachment	Comments
6.2.1 UE maximum output power	540	"38.521-1_TPanalysis_6.2.1_MaxOP_v3.zip"	RAN5#89-e
6.2.2 Maximum Power Reduction (MPR)	contiguous allocation: 920 (1040 ¹ ,1000 ^{2,3}) almost contiguous allocation: 120	"38.521-1_TPanalysis_6.2.2_MPR_6.5.2.2_SEM_6.5.2.4.1_N R_ACLR_v3.zip"	RAN5#92-e
6.2.3 UE A-MPR	See clause 4.1.2.1	See clause 4.1.2.1	See clause 4.1.2.1
6.2.4 Configured Transmitted Power	30	"38.521-1_TPanalysis_6.2.4_ConfigTP_v1.zip"	RAN5#91-e
6.2A.1.1 UE maximum output power for CA (2UL CA)	240	"38.521-1_TPanalysis_6.2A.1_MOP"	RAN5#83
6.2A.2 Maximum power reduction (MPR) for CA	For inter-band CA:1440 For intra-band contiguous CA: 720 (contiguous RB allocation) 720 (non-contiguous RB allocation) For intra-band non-contiguous CA: 2520	"38.521-1_TPanalysis_6.2A.2_MPR_v2.zip"	RAN5#94-e
6.2A.4 Configured transmitted power for CA	Inter-band CA:20 Intra-band contiguous CA (contiguous RB allocation): 20	"38.521-1_TPanalysis_6.2A.4_ConfigTP_v1.zip"	RAN5#88-e
6.2C.1 Configured UE transmitted Output Power	270	"38.521-1_TPanalysis_6.2C.1_ConfigOPSUL.zip"	RAN5#80
6.2D.1 UE maximum output power for UL-MIMO	UL MIMO with ULFPTx: 540 UL MIMO with 2-layer: 0	"38.521-1_TPanalysis_6.2.1_MaxOP_v3.zip"	RAN5#89-e
6.2D.2 Maximum Power Reduction (MPR)	power class 3: 400 power class 2: 400	"38.521-1_TPanalysis_6.2.2_MPR_v3.zip"	RAN5#85
6.2D.3 UE additional maximum output power reduction for UL-MIMO	Table 4.1.2.1-1	Table 4.1.2.1-1	See Table 4.1.2.1-1
6.2D.4 Configured Transmitted Power for UL-MIMO	15	"38.521-1_TPanalysis_6.2.4_ConfigTP_v1.zip"	RAN5#91-e
6.3.1 Minimum output power	45	"38.521-1_TPanalysis_6.3.1_MinOP_v3.zip"	RAN5#5-5G-NR Adhoc
6.3.3.2 General ON/OFF time mask	TBD	"38.521-1_TPanalysis_6.3.3.2_OnOff_M_v2.zip"	RAN5#5-5G-NR Adhoc
6.3.3.6 SRS time mask	30	"38.521-1_TPanalysis_6.3.3.3_SRS.zip"	RAN5#82
6.3.4.2 Absolute power tolerance	6	"38.521-1_TPanalysis_6.3.4.2_AbsPtol_v2.zip"	RAN5#83
6.3.4.3 Relative power tolerance	TBD	"38.521-1_TPanalysis_6.3.4.3_RelPtol_v2.zip"	RAN5#83
6.3.4.4 Aggregate power tolerance	PUCCH: 6 PUSCH: 6	"38.521-1_TPanalysis_6.3.4.4_AggPtol_v2.zip"	RAN5#83
6.3A.1.1 Minimum output power for CA (2UL CA)	20	38.521-1_TPanalysis_6.3A.1.1_MinOP_CA.zip	RAN5#83

6.3A.3.1 Transmit ON/OFF time mask for CA (2UL CA)	40	"38.521-1_TPanalysis_6.3A.3.1_OnOff_M_CA.zip"	RAN5#83
6.3A.3.1_1 Time mask for switching between two uplink carriers	1	"38.521-1_TPanalysis_6.3A.3.1_1_TxSwitch_M.zip"	RAN5#90-e
6.3A.4.1 Absolute power tolerance for CA (2UL CA)	Intra-band contiguous CA:4 Intra-band non-contiguous CA:2	"38.521-1_TPanalysis_6.3A.4.1_Abs_PToI_CA_v2.zip"	RAN5#94-e
6.3A.4.2 Relative power tolerance for CA (2UL CA)	TBD	"38.521-1_TPanalysis_6.3A.4.2_Rel_PToI_CA_v1.zip"	RAN5#92-e
6.3A.4.3 Aggregate power tolerance for CA (2UL CA)	PUCCH:4 PUSCH:4	"38.521-1_TPanalysis_6.3A.4.3_Agg_PToI_CA_v1.zip"	RAN5#92-e
6.3D.1 Minimum output power for UL-MIMO	45	"38.521-1_TPanalysis_6.3.1_MinOP_v3.zip"	RAN5#5-5G-NR Adhoc
6.3D.3 Transmit ON/OFF time mask for UL-MIMO	TBD	"38.521-1_TPanalysis_6.3.3.2_OnOff_M_v2.zip"	RAN5#5-5G-NR Adhoc
6.3D.4.1 Absolute Power tolerance for UL-MIMO	6	"38.521-1_TPanalysis_6.3.4.2_AbsPtoI_v2.zip"	RAN5#83
6.3D.4.2 Relative Power Tolerance for UL-MIMO	TBD	"38.521-1_TPanalysis_6.3.4.3_RelPtoI_v2.zip"	RAN5#83
6.3D.4.3 Aggregate Power tolerance for UL-MIMO	PUCCH: 6 PUSCH: 6	"38.521-1_TPanalysis_6.3.4.4_AggPtoI_v2.zip"	RAN5#83
6.4.1 Frequency error	5	"38.521-1_TPanalysis_6.4.1_FreqErr_v3.zip"	RAN5#84
6.4.2.1 Error Vector Magnitude	PUSCH: 252 PUCCH: 36 PRACH: 36	"38.521-1_TPanalysis_6.4.2.1_EVM_v3.zip"	RAN5#94-e
6.4.2.1a Error Vector Magnitude including symbols with transient period	PUSCH: 36	"38.521-1_TPanalysis_6.4.2.1_EVM_v3.zip"	RAN5#94e
6.4.2.2 Carrier leakage	3	"38.521-1_TPanalysis_6.4.2.2_CarrLeak_v2.zip"	RAN5#84
6.4.2.3 In-band emissions	36	"38.521-1_TPanalysis_6.4.2.3_IE_2.zip"	RAN5#84
6.4.2.4 EVM equalizer spectrum flatness	90	"38.521-1_TPanalysis_6.4.2.4_EVMequalizerSpectrumFlatness_v3.zip"	RAN5#84
6.4.2.5 EVM equalizer spectrum flatness for Pi/2 BPSK	9	"38.521-1_TPanalysis_6.4.2.5_EVMequalizerSpectrumFlatness_BPSK_v2.zip"	RAN5#92-e
6.4A.1.1 Frequency error for CA (2UL CA)	5	"38.521-1_TPanalysis on 6.4A.1.1_FreqErr.zip"	RAN5#82
6.4A.2.1.1 Error Vector Magnitude for CA (2UL CA)	168	"38.521-1_TPanalysis on 6.4A.2.1.1_EVM.zip"	RAN5#82
6.4A.2.2.1 Carrier leakage for CA (2UL CA)	2	"38.521-1_TPanalysis on 6.4A.2.2.1_CarrLeak.zip"	RAN5#82
6.4A.2.3.1 In-band emissions for CA (2UL CA)		"38.521-1_TPanalysis on 6.4A.2.2.1_IBE.zip"	RAN5#82
6.4D.1 Frequency error	5	"38.521-1_TPanalysis_6.4.1_FreqErr_v3.zip"	RAN5#84
6.4D.2.1 Error Vector Magnitude for UL MIMO	PUSCH: 108	"38.521-1_TPanalysis on 6.4.2.1_EVM_v3.zip"	RAN5#94-e
6.4D.2.2 Carrier leakage for UL MIMO	3	"38.521-1_TPanalysis on 6.4.2.2_CarrLeak_v2.zip"	RAN5#84

6.4D.2.3 In-band emissions for UL MIMO	18	"38.521-1_TPanalysis_6.4.2.3_IE_2.zip"	RAN5#84
6.4D.2.4 EVM equalizer spectrum flatness for UL MIMO	45	"38.521-1_TPanalysis_6.4.2.4_EVMequalizerSpectrumFlatness_v3.zip"	RAN5#84
6.4D.3 Time alignment error for UL-MIMO	6	"38.521-1_TPanalysis_6.4D.3_TAE_MIMO.zip"	RAN5#82
6.5.1 Occupied bandwidth	10	"38.521-1_TPanalysis_6.5.1_OccBW_v3.zip"	RAN5#92-e
6.5.2.2 Spectrum Emission Mask	contiguous allocation: 144 (168 ¹ , 160 ^{2,3}) almost contiguous allocation: 24	"38.521-1_TPanalysis_6.2.2_MPR_6.5.2.2_SEM_6.5.2.4.1_NR_ACLR_v3.zip"	RAN5#92-e
6.5D.2.3 Additional spectrum emission mask for UL-MIMO	Table 4.1.2.1-1	Table 4.1.2.1-1	See Table 4.1.2.1-1
6.5.2.4.1 NR Adjacent channel leakage ratio	contiguous allocation: 920 (1040 ¹ , 1000 ^{2,3}) almost contiguous allocation: 120	"38.521-1_TPanalysis_6.2.2_MPR_6.5.2.2_SEM_6.5.2.4.1_NR_ACLR_v3.zip"	RAN5#92-e
6.5.2.4.2 UTRA ACLR	Same as NS_3U, NS_5U, NS_43U, and NS_100 in Table 4.1.1.1-1	"38.521-1_TPanalysis_6.5.2.4.2_UTRA_ACLR_v3.zip"	RAN5#91-e
6.5.3.1 General spurious emissions	27	"38.521-1_TPanalysis_6.5.3.1_TX_Spurious_Emission_v1.zip"	RAN5#89-e
6.5.3.2 Spurious emissions for UE co-existence	27	"38.521-1_TPanalysis_6.5.3.1_TX_Spurious_Emission_v1.zip"	RAN5#89-e
6.5.3.3 Additional spurious emissions	See Table 4.1.2.1-1	See Table 4.1.2.1-1	See Table 4.1.2.1-1
6.5.4 Transmit intermodulation	8	"38.521-1_TPanalysis_6.5.4_TxIm.zip"	RAN5#80
6.5A.1.1 Occupied bandwidth for CA (2UL CA)	Inter-band: 2 Intra-band contiguous: 1 Intra-band non-contiguous: 1	"38.521-1_TPanalysis_6.5A.1.1_OccBW_v2.zip"	RAN5#92-e
6.5A.2.2.1 Spectrum emission mask for CA (2UL CA)	Inter-band CA:112 Intra-band CA:72	"38.521-1_TPanalysis on 6.5A.2.2.1_SEM_v1.zip"	RAN5#94-e
6.5A.2.4.1.1 NR ACLR for CA (2UL CA)	840	"38.521-1_TPanalysis on 6.5A.2.4.1.1_NR_ACLR_v1.zip"	RAN5#94-e
6.5A.2.4.2.1 UTRA ACLR for CA (2UL CA)	840	"38.521-1_TPanalysis on 6.5A.2.4.2.1_UTRA_ACLR.zip"	RAN5#82
6.5A.3.1.1 General spurious emissions for CA (2UL CA)	12	"38.521-1_TPanalysis on 6.5A.3.1.1_Spurious_v1.zip"	RAN5#90
6.5A.3.2.1 Spurious emissions for UE co-existence for CA (2UL CA)	See table 4.1.3.2-1	"38.521-1_TPanalysis on 6.5A.3.2.1_SECoex_v1.zip"	RAN5#91-e
6.5A.4.1 Transmit intermodulation for CA (2UL CA)	840	"38.521-1_TPanalysis on 6.5A.4.1_TxIM.zip"	RAN5#82
6.5D.1 Occupied bandwidth for UL-MIMO	10	38.521-1_TPanalysis_6.5.1_OBW_v3.zip	RAN5#92-e
6.5D.1_1 Occupied bandwidth for UL MIMO (Rel-16 onward)	10	38.521-1_TPanalysis_6.5.1_OBW_v3.zip	RAN5#92

6.5D.2.4.1 NR ACLR for UL-MIMO		"38.521-1_TPanalysis_6.5.2.4_ACLR_v3.zip"	RAN5#82
6.5D.2.4.2 UTRA ACLR for UL-MIMO	96 for NS_3U	"38.521-1_TPanalysis_6.5D.2.4.2_UTRA ALCR_NS_3U_v1.zip" "38.521-1_TPanalysis_6.5.2.4.2_UTRA ACLR_v3.zip"	RAN5#5-5G-NR Adhoc
6.5D.2.4.2 UTRA ACLR for UL MIMO (Rel-16 onward)	216 for NS_3U	"38.521-1_TPanalysis_6.5D.2.4.2_UTRA ALCR_NS_3U_v1.zip" "38.521-1_TPanalysis_6.5.2.4.2_UTRA ACLR_v3.zip"	RAN5#90-e
6.5D.3.1 General spurious emissions	27	"38.521-1_TP analysis_6.5.3.1_TX_Spurious_Emission_v1.zip"	RAN5#89-e
6.5D.3.2 Spurious emissions for UE co-existence for UL-MIMO	27	"38.521-1_TP analysis_6.5.3.1_TX_Spurious_Emission_v1.zip"	RAN5#89-e
6.5D.3.3 Additional spurious emissions for UL-MIMO	Table 4.1.2.1-1	Table 4.1.2.1-1	RAN5#5-5G-NR Adhoc
6.5D.3.1.1 General spurious emissions (Rel-16 onward)	27	"38.521-1_TP analysis_6.5.3.1_TX_Spurious_Emission_v1.zip"	RAN5#89-e
6.5D.3.1.2 Spurious emissions for UE co-existence for UL-MIMO (Rel-16 onward)	27	"38.521-1_TP analysis_6.5.3.1_TX_Spurious_Emission_v1.zip"	RAN5#89-e
6.5D.3.1.3 Additional spurious emissions for UL-MIMO (Rel-16 onward)	Table 4.1.1.1-1	Table 4.1.1.1-1	RAN5#89-e
6.5D.4 Transmit intermodulation for UL-MIMO		"38.521-1_TPanalysis_6.5.4_TxIm_v2.zip"	RAN5#82
NOTE 1: For power class 3 UE operating in bands n40, n41, n77, n78 and n79. NOTE 2: UE operating in FDD mode, or in TDD mode in bands other than n40, n41, n77, n78 and n79, or in TDD mode the IE powerBoostPi2BPSK is set to 0 for bands n40, n41, n77, n78 and n79. NOTE 3: UEs supporting pi/2 BPSK DMRS and the corresponding IE [DMRSPi2BPSK] is set to 1. NOTE 4: The maximum number of test point is 24 if only default points are applied.			

Table 4.1.1.1-2: NR UE receiver test point selection for FR1

Subclause	Number of test points	Justification in attachment	Comments
7.3 Reference sensitivity power level	45	"38.521-1_TPanalysis_7.3_RefSense_v3.zip"	RAN5#5-5G-NR Adhoc
7.3A Reference sensitivity for CA	See clause 4.1.3	See clause 4.1.3	See clause 4.1.3
7.3D.2 Reference sensitivity power level for UL-MIMO		"38.521-1_TPanalysis_7.3_RefSense_v2.zip"	RAN5#82
7.4 Maximum input level	6	"38.521-1_TPanalysis_7.4_Maximun input level_v2.zip"	RAN5#82
7.4A Maximum input level for CA	2CC:2 3CC:2	"38.521-1_TPanalysis_7.4A_maxIL for CA_v1.zip"	RAN5#89-e
7.4D Maximum input level for UL-MIMO		"38.521-1_TPanalysis_7.4_Maximun input level_v2.zip"	RAN5#82
7.5 Adjacent Channel Selectivity	3	"38.521-1_TPanalysis_7.5_ACS_v2.zip"	RAN5#82
7.5A Adjacent channel selectivity for DL CA	intra-band contiguous CA: 2 inter-band CA: 1	"38.521-1_TPanalysis_7.5A.1_ACS_2CA.zip"	RAN5#83
7.5D Adjacent Channel Selectivity for UL-MIMO		"38.521-1_TPanalysis_7.5_ACS_v2.zip"	RAN5#82
7.6.2 In Band Blocking	3	"38.521-1_TPanalysis_7.6.2_InB_Block_v2.zip"	RAN5#5-5G-NR Adhoc
7.6.3 Out-of-band blocking	3	"38.521-1_TPanalysis_7.6.3_OobBlocking_v2.zip"	RAN5#5-5G-NR Adhoc
7.6.4 Narrow band blocking	3	"38.521-1_TPanalysis_7.6.4_NarrowbBlocking_v2.zip"	RAN5#5-5G-NR Adhoc
7.6A.2 Inband blocking for CA 2CC: 3CC:1	1	"38.521-1_TPanalysis_7.6A.2 IBB for CA_v1.zip"	RAN5#89-e
7.6A.3 Out-of-band blocking for CA	1	"38.521-1_TPanalysis_7.6A.3 Out-of-band blocking for CA_v1.zip"	RAN5#86-e
7.6A.4 Narrow band blocking for CA	1	"38.521-1_TPanalysis_7.6A.4 Narrow band blocking for CA_v1.zip"	RAN5#86-e
7.6D.2 Inband blocking for UL-MIMO	3	"38.521-1_TPanalysis_7.6.2_InB_Block_v2.zip"	RAN5#5-5G-NR Adhoc
7.6D.3 Out-of-band blocking for UL-MIMO	3	"38.521-1_TPanalysis_7.6.3_OobBlocking_v2.zip"	RAN5#5-5G-NR Adhoc
7.6D.4 Narrow band blocking for UL-MIMO	3	"38.521-1_TPanalysis_7.6.4_NarrowbBlocking_v2.zip"	RAN5#5-5G-NR Adhoc
7.7 Spurious response	3	"38.521-1_TPanalysis_7.7_Spurious response.zip"	RAN5#4-5G-NR Adhoc
7.7D Spurious response for UL-MIMO	3	"38.521-1_TPanalysis_7.6.3_OobBlocking_v2.zip"	RAN5#83
7.8.2 Wide band Intermodulation	3	"38.521-1_TPanalysis_7.8.2_WidebandIntermod_v2.zip"	RAN5#5-5G-NR Adhoc
7.8A Wide band Intermodulation for CA	1	"38.521-1_TPanalysis_7.8A Wide band Intermodulation for CA_v1.zip"	RAN5#86-e
7.8D.2 Wide band Intermodulation for UL-MIMO	3	"38.521-1_TPanalysis_7.8.2_WidebandIntermod_v2.zip"	RAN5#5-5G-NR Adhoc
7.9 Spurious emissions	3	"38.521-1_TPanalysis_7.9_RxSpurious.zip"	RAN5#81

4.1.1.2 FR1 SUL test cases

This section contains information on test point selection for SUL test cases in [2]. The basic principle is following the same rules for test point selection in single carrier test cases. In these SUL test cases, there are default test points to be used unless SUL configuration specific test points are over-ruling.

Basic rules for Tx SUL test cases:

For Test environment: Adopt the same selection of test environment in corresponding single carrier test cases.

For Test frequency: Considering that Non-SUL carrier should have no impact on SUL carrier testing results, for any SUL configurations, Mid range is chosen as default for Non-SUL carrier. Select the same test frequency in corresponding single carrier test cases for SUL carrier.

For Test SCS: Considering only 15 kHz SCS is supported for SUL bands, it's reasonable to select 15 kHz SCS for SUL carrier and Non-SUL carrier regardless of SUL configurations.

For Test channel bandwidths: Under the limit of 15 kHz SCS, only the lowest channel bandwidth is supported for current Non-SUL bands in SUL configurations, which are band n78 and n79. Select the lowest channel bandwidth that support 15kHz SCS for Non-SUL carrier. Select the same test channel bandwidths as in corresponding single carrier test cases for SUL carrier.

For waveform, modulation and RB allocations: Adopt the same selection of test configurations as in corresponding single carrier test cases for SUL carrier.

Basic rules for Rx SUL test cases:

In Rx testing for SUL, test point selection in clause 7.3C and 7.6C need to be defined. Considering the focus of Rx test cases is testing DL bands, the configuration of SUL carrier shall be selected to ensure the test coverage without costing too much testing time. The configuration of Non-SUL carrier shall be selected based on the same principle as single carrier test cases. The basic test point selection rule for Rx SUL test cases is specified as below:

For Test environment: Adopt the same selection of test environment in corresponding single carrier test cases.

For Test frequency: The Non-SUL carrier should select the same test frequency as corresponding single carrier test cases. Select Mid range as default for SUL carrier.

For Test SCS: Since the REFSENS requirement for SUL is specified for 15 kHz SCS for SUL band and the test point selection of clause 7.6C is also based on that of clause 7.3C, 15 kHz SCS should be selected for SUL carrier. For the Non-SUL carrier the SCS should be selected following the same rule as single carrier testing.

For test channel bandwidths: Highest channel bandwidth when SCS =15 kHz for SUL shall be selected for SUL carrier. For the Non-SUL carrier the channel bandwidth should be selected following the same rule as single carrier testing.

For waveform, modulation and RB allocations: Adopt the same selection of test configurations as single carrier test cases for Non-SUL carrier. SUL carrier select DFT-s-OFDM QPSK. The RB allocation of SUL carrier shall fulfill the requirement in clause 7.3C.0 in TS 38.521-1.

Number of test points for SUL test cases in FR1 are listed in table 4.1.1.2-1 and table 4.1.1.2-2.

Table 4.1.1.2-1: Number of test points for SUL test cases in FR1 (NR UE Transmitter test)

Subclause	Number of test points	Comments
6.2C.1 Configured transmitted power for SUL	30	RAN5#86e
6.2C.3 UE maximum output power for SUL	270	RAN5#86e
6.2C.4 UE maximum output power reduction for SUL	460 (500 ¹)	RAN5#90e
6.2C.5 UE additional maximum output power reduction for SUL	Table 4.1.1.1-1	RAN5#87e
6.3C.1 Minimum output power for SUL	45	RAN5#87e
6.3C.3 Transmit ON/OFF time mask for SUL	45	RAN5#87e
6.3C.4.1 Absolute power tolerance for SUL	3	RAN5#87e
6.3C.4.2 Power Control Relative power tolerance for SUL	TBD	RAN5#87e
6.3C.4.3 Aggregate power tolerance for SUL	PUCCH: 3 PUSCH: 3	RAN5#87e
6.4C.1 Frequency error for SUL	5	RAN5#86e
6.4C.2.1 Error Vector Magnitude for SUL	PUSCH: 84 PUCCH: 24 PRACH: 12	RAN5#86e
6.4C.2.2 Carrier leakage for SUL	3	RAN5#90e
6.4C.2.3 In-band emissions for SUL	36	RAN5#90e
6.4C.2.4 EVM equalizer spectrum flatness for SUL	90	RAN5#90e
6.4C.2.5 EVM equalizer spectrum flatness for Pi/2 BPSK for SUL	9	RAN5#90e
6.5C.1 Occupied bandwidth for SUL	18	RAN5#86e
6.5C.2.2 Spectrum Emission Mask for SUL	72 (80 ¹)	RAN5#90e
6.5C.2.3 Additional spectrum emission mask for SUL	27	RAN5#86e
6.5C.2.4.1 NR ACLR for SUL	460 (500 ¹)	RAN5#90e
6.5C.2.4.2 UTRA ACLR for SUL	Table 4.1.1.1-1	RAN5#86e
6.5C.3.1 General spurious emissions for SUL	27	RAN5#86e
6.5C.3.2 Spurious emission for UE co-existence for SUL	27	RAN5#86e
6.5C.3.3 Additional spurious emissions for SUL	115 for NS_05 28 for NS_43	RAN5#87e
6.5C.4 Transmit intermodulation for SUL	4	RAN5#86e
NOTE 1: UEs supporting pi/2 BPSK DMRS and the corresponding IE [DMRSPi2BPSK] is set to 1.		

Table 4.1.1.2-2: Number of test points for SUL test cases in FR1 (NR UE Receiver test)

Subclause	Number of test points	Comments
7.3C.2 Reference sensitivity power level for SUL	General test points:45 SUL configuration specific test points: SUL_n78-n80: 2	RAN5#90e
7.6C.2 Inband Blocking for SUL	3	RAN5#87e
7.6C.3 Out-of-band blocking for SUL	3	RAN5#87e

4.1.1.3 FR1 V2X test cases

This section contains information on test point selection for V2X test cases 6.2E, 6.3E, 6.4E, 6.5E, 7.3E, 7.4E, 7.5E, 7.6E, 7.7E and 7.8E in [2].

Number of test points for V2X test cases in FR1 are listed in table 4.1.1.3-1 and table 4.1.1.3-2.

Table 4.1.1.3-1: Number of test points for V2X test cases in FR1 (NR UE Transmitter test)

Subclause	Number of test points	Justification in attachment	Comments
6.2E.2 UE maximum output power reduction for V2X	440	'38.521-1_TP analysis_V2X_6.2E.2_MPR_6.5E.2.2_SEM_6.5E.2.4_ACLR_v2'	RAN5#94-e
6.3E.1 Minimum output power for V2X	360	'38.521-1_TP analysis_V2X_6.3E.1_MinOP_v1.zip'	RAN5#92-e
6.5E.2.2 Spectrum emission mask for V2X	440	'38.521-1_TP analysis_6.2E.2_MPR_6.5E.2.2_SEM_6.5E.2.4_ACLR_V2X.zip'	RAN5#91-e
6.5E.2.4 Adjacent channel leakage ratio for V2X	88	'38.521-1_TP analysis_6.2E.2_MPR_6.5E.2.2_SEM_6.5E.2.4_ACLR_V2X.zip'	RAN5#91-e

Table 4.1.1.3-2: Number of test points for V2X test cases in FR1 (NR UE Receiver test)

Subclause	Number of test points	Justification in attachment	Comments
FFS			

4.1.2 Test point analysis per NS value

4.1.2.1 A-MPR, A-SEM and A-SE FR1 test cases for single carrier and UL MIMO

This section contains information on test point selection for single carrier test cases 6.2.3, Additional Maximum Power Reduction (A-MPR), 6.5.2.3 Additional spectrum emission mask (A-SEM) and 6.5.3.3 Additional spurious emissions (A-SE); and for correspondent UL-MIMO test cases in 6.2D.3 and 6.5D.3.3 in [2].

Selection of test points should include some possible worst combinations based on the A-MPR characteristics specified for each NS value and these shall be selected so that they match with corresponding spectrum emission requirements test points. The number of test points should be realistic.

For $\pi/2$ BPSK with Rel-16 DMRS, the correspondent A-MPR requirements are the same as that for Rel-15 DMRS but the PAPR is lower. Given the UE can pass the requirements using Rel-15 DMRS, it can be expected that the UE can pass the requirements using Rel-16 DMRS. Therefore there is no need to additionally test A-MPR, A-SEM and A-SE for Rel-16 DMRS.

Table 4.1.2.1-1 lists number of test points for A-MPR, A-SEM and A-SE single carrier test cases and for different NS values.

Table 4.1.2.1-1: NS value specific test points for A-MPR, A-SEM and A-SE single carrier

NS label	Number of test points for A-MPR	Number of test points A-SEM	Number of test points A-SE	Justification	Comments
NS_03	6.2.3: 80 40 for SUL testing			"38.521-1_TPanalysis_6.2.3_AMPR_NS_03.zip"	RAN5#85
NS_04	6.2.3: 120 6.2D.3: 112 6.5D.3.3:112			"38.521-1_TPanalysis_6.2.3_AMPR_NS_04_v3.zip"	RAN5#93-e
NS_05	6.5.3.3: 432			"38.521-1_TP analysis_6.5.3.3_TX_Additional_Spurious_Emission_NS_05.zip"	RAN5#87-e
NS_05, NS_05U	6.2.3: 288			"38.521-1_TPanalysis_6.2.3_AMPR_NS_05_v2.zip"	RAN5#86
NS_06	6.2.3: PC1 160 PC3 144			"38.521-1_TPanalysis_6.2.3_AMPR_NS_06_v2.zip"	RAN5#92-e
NS_12	48			"38.521-1_TPanalysis_6.2.3_AMPR_NS_12_13_14_15.zip"	RAN5#90-e
NS_13	21			"38.521-1_TPanalysis_6.2.3_AMPR_NS_12_13_14_15.zip"	RAN5#90-e
NS_14	50			"38.521-1_TPanalysis_6.2.3_AMPR_NS_12_13_14_15.zip"	RAN5#90-e
NS_15	102			"38.521-1_TPanalysis_6.2.3_AMPR_NS_12_13_14_15.zip"	RAN5#90-e
NS_17	6.5.3.3: 4			"38.521-1_TPanalysis_6.5.3.3_TX_Additional_Spurious_Emission_NS_17_v2.zip"	RAN5#92-e
NS_18	88 6.2.3: 108 6.5.3.3: 54			"38.521-1_TPanalysis_6.2.3_AMPR_6.5.3.3_ASE_NS_18_v3.zip"	RAN5#89-e
NS_21	180			"38.521-1_TPanalysis_6.2.3_AMPR_NS_21.zip"	RAN5#89-e
NS_24	6.2.3: 300			"38.521-1_TPanalysis_6.2.3_AMPR_NS_24.zip"	RAN5#87
NS_27	6.2.3: 252			"38.521-1_TPanalysis_6.2.3_AMPR_NS_27_v2.zip"	RAN5#93-e
NS_35	6.2.3: 144 6.2.3: 72			"38.521-1_TPanalysis_6.2.3_AMPR_NS_35_v2.zip"	RAN5#5-5G-NR-Adhoc
NS_37	6.2.3: 48			"38.521-1_TPanalysis_6.2.3_AMPR_NS_37.zip"	RAN5#86
NS_38	6.2.3: 96			"38.521-1_TPanalysis_6.2.3_AMPR_NS_38.zip"	RAN5#86
NS_39	6.2.3: 54			"38.521-1_TPanalysis_6.2.3_AMPR_NS_39.zip"	RAN5#86
NS_40	6.2.3: 24			"38.521-1_TPanalysis_6.2.3_AMPR_NS_40.zip"	RAN5#87
NS_41	6.2.3: 72			"38.521-1_TPanalysis_6.2.3_AMPR_NS_41.zip"	RAN5#87
NS_42	6.2.3: 108			"38.521-1_TPanalysis_6.2.3_AMPR_NS_42.zip"	RAN5#87
NS_43	6.2.3: 28			"38.521-1_TPanalysis_6.2.3_AMPR_NS_43_v2.zip"	RAN5#86
	6.5.3.3: 81			"38.521-1_TP analysis_6.5.3.3_TX_Additional_Spurious_Emission_NS_43.zip"	RAN5#87-e
NS_43U	6.2.3: 72			"38.521-1_TPanalysis_6.2.3_AMPR_NS_43U.zip"	RAN5#85
NS_44	360	N/A	180	"38.521-1_TPanalysis_6.2.3_AMPR_6.5.3.3_ASE_NS_44.zip"	RAN5#90-e
NS_45	24			"38.521-1_TPanalysis_6.2.3_AMPR_NS_45.zip"	RAN5#89-e
NS_46	176			"38.521-1_TPanalysis_6.2.3_AMPR_NS_46.zip"	RAN5#89-e
NS_47	70			"38.521-1_TPanalysis_6.2.3_AMPR_NS_47.zip"	RAN5#87
NS_48	192	N/A	96	"38.521-1_TPanalysis_6.2.3_AMPR_6.5.3.3_ASE_NS_48_v1.zip"	RAN5#90-e

NS_49	224	N/A	112	"38.521-1_TPanalysis_6.2.3_AMPR_6.5.3.3_ASE_NS_49.zip"	RAN5#90-e
NS_56	175		175	38.521-1_TPanalysis_6.2.3_AMPR_6.5.3.3_ASE_NS_56.zip	RAN5#93-e
NS_100	72			"38.521-1_TPanalysis_6.2.3_AMPR_NS_100.zip"	RAN5#85

4.1.2.2 A-MPR test cases for FR1 UL CA

This section contains information on test point selection for test case 6.2A.3.1 in [2], UE additional maximum output power reduction for CA.

TS 38.101 [3] specifies band dependent NS-values, which in the inter-band UL CA test cases become a combination of two NS-values. Testing all possible combinations would lead to too excessive testing and the combinations that are realistic should therefore be prioritized. This selection is documented in table 4.1.1.1-1.

Table 4.1.2.2-1: A-MPR test coverage per CA configuration for inter-band CA with 2 CC

CA config with UL CA support (Note 1)	NS values in same order as Uplink CA Configuration column		Number of test points	Applicable test case	Justification	Comment
CA_n3-n78 CA_n8-n78	NS_100	NS_01	24	N/A	"38.521-1_TPanalysis 6.2A.3 NS_100+NS_01.zip"	RAN5#87-e
CA_n8-n78	NS_43	NS_01	12	N/A	"38.521-1_TPanalysis 6.2A.3 NS_43+NS_01.zip"	RAN5#88-e
CA_n8-n78	NS_43U	NS_01	12	N/A	"38.521-1_TPanalysis 6.2A.3 NS_43U+NS_01.zip"	RAN5#88-e
CA_n41A-n79A	NS_47	NS_01	3	N/A	"38.521-1_TPanalysis_6.2A.3_NS_47+NS_01.zip"	RAN5#94-e
Note 1: As per TS 38.101.						

The analyses are performed per NS-value and are stored as zip-files as defined in annex A. The general principle for selection of test points is:

- Test the minimum Total power backoff value
- Test the maximum Total power backoff value
- Test the maximum unbalanced Total power backoff among CCs (max $P_{\text{CMAX},c}$ difference).

Where the Total power backoff value means: MAX[MPR, A-MPR]

4.1.3 Test point analysis per NR CA configuration

4.1.3.1 Reference Sensitivity test cases for FR1 NR CA

Editor's note:

- Not all CA configurations completed in TS 38.521-1 refsens test cases are listed in Table 4.1.3.1-1 through Table 4.1.3.1-5.

This clause contains information on test point analysis, test frequency selection and status for FR1 NR CA test cases in TS 38.521-1 [2] clause 7. The analyses are performed per CA configuration in Table 4.1.3.1-1 through Table 4.1.3.1 4. The principles for selection of reference sensitivity test points for NR CA is given in Annex B including a test point analysis check list in B.9.

Table 4.1.3.1-1: Reference Sensitivity test cases per CA configuration (single band)

CA config	Single band refsens exception, victim band (Note 2)	Requirement coverage (Note 2)	Test point analysis updated
CA_n41C	–	NE	RAN5#89-e
CA_n48B	–	NE	RAN5#94-e
CA_n66B	–	NE	RAN5#86-e
CA_n66(2A)	–	NE	RAN5#86-e
CA_n71(2A)	–	NE	RAN5#94-e
CA_n78C	–	NE	RAN5#87-e
NOTE 1: Void. NOTE 2: Notations used: NE: Non-exception as defined in TS 38.101-1 [5], meaning single carrier NR requirements apply. HD: UL Harmonic Distortion, as defined in TS 38.101-1 [5], 7.3A.4 HM: RX Harmonic Mixing, as defined in TS 38.101-1 [5], 7.3A.4 IMD: Intermodulation Distortion, as defined in TS 38.101-1 [5], 7.3A.5 CBI: Cross Band Isolation, as defined in TS 38.101-1 [5], 7.3A.6			

Table 4.1.3.1-2: Reference Sensitivity test cases per CA configuration (two bands)

CA config	Two band refsens exception, victim band (Note 1)	Requirement coverage (Note 1)	Test point analysis updated
CA_n1A-n3A	n1 (IMD3)	IMD	RAN5#94-e
CA_n1A-n77A	n77 (HD2)	HD	RAN5#89-e
CA_n1A-n78A	n1 (IMD4)	IMD	RAN5#94
CA_n3A-n77A	n78 (HD2)	HD	RAN5#84
CA_n3A-n78A	n3 (IMD2 fn78-fn3) n3 (IMD4 fn78-3*fn3) n78 (HD2)	HD, IMD	RAN5#87-e
CA_n5A-n78A	n78 (HD2)	HD	RAN5#94-e
CA_n7A-n78A	n7 and n78 (CBI)	CBI	RAN5#94-e
CA_n8A-n78A	n8 (IMD4 fn78-3*fn8) n78 (HD4)	HD, IMD	RAN5#87-e
CA_n26A-n66A	n26 (IMD2)	IMD	RAN5#94-e
CA_n26A-n70A	n26 (IMD2)	IMD	RAN5#94-e
CA_n28A-n41A	–	NE	RAN5#91-e
CA_n28A-n79A	–	NE	RAN5#91-e
CA_n29A-n66A	–	NE	RAN5#94-e
CA_n29A-n70A	–	NE	RAN5#94-e
CA_n41A-n79A	–	NE	RAN5#83
CA_n48A-n66A	n48 (HD2), n66 (IMD5)	HD, IMD	RAN5#94-e
CA_n48A-n70A	n70 (IMD2)	IMD	RAN5#94-e
CA_n48A-n71A	–	NE	RAN5#94-e
CA_n66A-n70A	–	NE	RAN5#94-e
CA_n66A-n71A	n66 (IMD4)	IMD	RAN5#87-e
CA_n70A-n71A	n70 (HD3), n70 (IMD4)	HD, IMD	RAN5#85
NOTE 1: Notations used NE: Non-exception as defined in TS 38.101-1 [5], meaning single carrier NR requirements apply. HD: UL Harmonic Distortion, as defined in TS 38.101-1 [5], 7.3A.4 HM: RX Harmonic Mixing, as defined in TS 38.101-1 [5], 7.3A.4 IMD: Intermodulation Distortion, as defined in TS 38.101-1 [5], 7.3A.5 CBI: Cross Band Isolation, as defined in TS 38.101-1 [5], 7.3A.6			

Table 4.1.3.1-3: Reference Sensitivity test cases per CA configuration (three bands)

CA config	Three band refsens exception, victim band (Note 1)	Requirement coverage (Note 1)	Test point analysis updated
CA_n26A-n66A-n70A	–	NE	RAN5#94-e
CA_n29A-n66A-n70A	–	NE	RAN5#89-e
CA_n66A-n70A-n71A	–	NE	RAN5#87-e
NOTE 1: Notations used NE: Non-exception as defined in TS 38.101-1 [5], meaning single carrier NR requirements apply. HD: UL Harmonic Distortion, as defined in TS 38.101-1 [5], 7.3A.4 HM: RX Harmonic Mixing, as defined in TS 38.101-1 [5], 7.3A.4 IMD: Intermodulation Distortion, as defined in TS 38.101-1 [5], 7.3A.5 CBI: Cross Band Isolation, as defined in TS 38.101-1 [5], 7.3A.6			

Table 4.1.3.1-4: Reference Sensitivity test cases per CA configuration (four bands)

CA config	Four band refsens exception, victim band (Note 1)	Requirement coverage (Note 1)	Test point analysis updated
TBD	–	TBD	TBD
NOTE 1: No exceptions can occur for four bands.			

Table 4.1.3.1-5: Reference Sensitivity test cases per CA configuration (five bands)

CA config	Five band refsens exception, victim band (Note 1)	Requirement coverage (Note 1)	Test point analysis updated
TBD	–	TBD	TBD
NOTE 1: No exceptions can occur for five bands.			

Table 4.1.3.1-6: Test frequency selection per band pair for UL harmonics exception

Band pair (Note 2)	Frequency	Channel BW [MHz]	Comment
n1A / n77A	Mid / Low	Highest/Highest	Non-exception. To be used in test cases 7.3A.1 to 7.3A.4
	Mid / 3900	20/ Highest	Exception Note 2 of TS 38.101 table 7.3A.4-1
	Mid / 3870	20/20	Exception Note 3 of TS 38.101 table 7.3A.4-1
n3A / n77A	TBD/TBD	Highest/Highest	Non-exception. To be used in test cases 7.3A.1 to 7.3A.4
	TBD/TBD	Highest/Highest	Exception Note 2 of TS38.101 table 7.3A.4-1
	TBD/TBD	20/20	Exception Note 3 of TS38.101 table 7.3A.4-1
n3A / n78A	Mid/High	Highest/Highest	Non-exception. To be used in test cases 7.3A.1 to 7.3A.4
	Mid/3495 MHz	Highest/Highest	Exception Note 2 of TS38.101 table 7.3A.4-1
	Mid/3465 MHz	20/20	Exception Note 3 of TS38.101 table 7.3A.4-1
n5A / n78A	Mid/High	Highest/Highest	Non-exception. To be used in test cases 7.3A.1 to 7.3A.4 in TS 38.521-1 [2]
	Mid/3346 MHz	Highest/Highest	Exception Note 4 of TS 38.101 [5] table 7.3A.4-1
	Mid/3316 MHz	20/20	Exception Note 5 of TS 38.101 [5] table 7.3A.4-1
n8A / n78A	Mid/High	Highest/Highest	Non-exception. To be used in test cases 7.3A.1 to 7.3A.4
	Mid/3590 MHz	Highest/Highest	Exception Note 5 of TS38.101 table 7.3A.4-1
n70A / n71A	Mid/High	Highest/Highest	Non-exception. To be used in test cases 7.3A.1 to 7.3A.4
	Low/Low	Highest / 10	Exception Note 9 of TS38.101 table 7.3A.4-1 n71 UL RB allocation 20@10
	Low/Low	5 / 5	Exception Note 9 of TS38.101 table 7.3A.4-1 n71 UL RB allocation 8@10
NOTE 1: This selection is used in test case 7.3A.1_1 unless otherwise stated.			
NOTE 2: Aggressor band in bold.			

4.1.3.2 Spurious emissions test cases for FR1 UL CA

In this case, it is sufficient to verify the minimum requirements in frequency ranges affected by 2nd and 3rd order intermodulation products. The frequency ranges and UL RB allocations used in the test are calculated here.

The analyses are performed per CA configuration and are stored as zip-files as defined in annex A.

Table 4.1.3.2-1: Frequency range analysis availability per CA configuration

CA config	Number of test point	Justification	Comments
CA_n1A-n78A	5	38.521-1_TpAnalysisSpur(CA_n1A-n78A)v2.zip	Added at RAN5#88e
CA_n3A-n78A	3	TpAnalysisSpur(n3A-n78A).zip	Added at RAN5#82
CA_n8A-n78A	4	TpAnalysisSpur(n8A-n78A).zip	Added at RAN5#82
CA_n28A-n41A	4	38.521-1_TpAnalysisSpur(CA_n28A-n41A).zip	Added at RAN5#91e
CA_n41A-n79A	7	TpAnalysisSpur(n41A-n79A).zip	Added at RAN5#83

4.2 Test point analysis for FR2 test cases in TS 38.521-2

4.2.1 Test point analysis per test case

4.2.1.1 FR2 single carrier, NR CA and UL MIMO test cases

This clause contains information on test point analysis and test point selection for single carrier, NR CA and UL MIMO test cases in [3] clause 6 and 7 with information about transmitting test point selection for FR2 listed in table 4.2.1.1-1 and receiver test point selection in table 4.2.1.1-2.

Table 4.2.1.1-1: NR UE transmitter test point selection for FR2

Subclause	Number of test points	Justification in attachment	Comments
6.2.1 UE maximum output power	x	"38.521-2_TPanalysis_6.2.1_MOP_v3.zip"	RAN5#94-e
6.2.2 UE maximum output power reduction	power class 1: 90 power class 2&3&4: 84	"38.521-2_TPanalysis_6.2.2_MPR_6.5.2.1_SEM_6.5.2.3_NR_ACLR_v4.zip"	RAN5#94-e
6.2A.1.1 UE maximum output power - EIRP and TRP for CA	TRP: 4 EIRP: 20	"38.521-2_TPanalysis_6.2A.1.x_MOP_Spherical Coverage_CA_v1"	RAN5#84
6.2A.1.2 UE maximum output power - Spherical coverage for CA	20	"38.521-2_TPanalysis_6.2A.1.x_MOP_Spherical Coverage_CA_v1"	RAN5#84
6.2A.2 UE maximum output power reduction for CA	FFS	"38.521-2_TPanalysis_6.2A.2_MPR for CA"	RAN5#84
6.2D.1 UE maximum output power for UL MIMO	x	"38.521-2_TPanalysis_6.2.1_MOP_v3.zip"	RAN5#94-e
6.2D.2 UE maximum output power reduction for UL MIMO	x	"38.521-2_TPanalysis_6.2.2_MPR_6.5.2.1_SEM_6.5.2.3_NR_ACLR_v4.zip"	RAN5#94-e
6.3.1 Minimum output power	9	"38.521-2_TPanalysis_6.3.1_MinOP_v2.zip"	RAN5#84
6.3.2 Transmit OFF power	3	"38.521-2_TPanalysis_6.3.2_Tx_OFF_power"	RAN5#83
6.3.3.2 General ON/OFF time mask	9	"38.521-2_TPanalysis_6.3.3.2_OnOff.zip"	RAN5#92-e
6.3.4.2 Absolute power tolerance	8	"38.521-2_TPanalysis_6.3.4.2_AbsPtol.zip"	RAN5#91-e
6.3.4.3 Relative power tolerance	Ramp up: 1 Ramp down: 1 Alternating: 1	"38.521-2_TPanalysis_6.3.4.3_RelPtol_v3.zip"	RAN5#82 RAN5#91-e RAN5#93-e
6.3.4.4 Aggregate power tolerance	PUCCH: 6 PUSCH: 6	"38.521-2_TPanalysis_6.3.4.4_AggPtol_2.zip"	RAN5#82 RAN5#91-e
6.3A.1.1 Minimum output power for CA (2UL CA)	4	"38.521-2_TPanalysis_6.3A.1.1_MinOP.zip"	RAN5#83
6.3A.2.1 Transmit OFF power for CA (2UL CA)	3	"38.521-2_TPanalysis_6.3A.2.1_Tx_OFF_Power_CA.zip"	RAN5#88-e

6.3A.4.2.1 Absolute power tolerance for CA (2UL CA)	6	38.521-2_TPanalysis_6.3A.4.2.1_AbsPCTol_CA.zip	RAN5#85
6.3A.4.2.2 Absolute power tolerance for CA (3UL CA)	6	38.521-2_TPanalysis_6.3A.4.2.1_AbsPCTol_CA.zip	RAN5#85
6.3A.4.2.3 Absolute power tolerance for CA (4UL CA)	6	38.521-2_TPanalysis_6.3A.4.2.1_AbsPCTol_CA.zip	RAN5#85
6.3A.4.2.4 Absolute power tolerance for CA (5UL CA)	6	38.521-2_TPanalysis_6.3A.4.2.1_AbsPCTol_CA.zip	RAN5#85
6.3A.4.2.5 Absolute power tolerance for CA (6UL CA)	6	38.521-2_TP analysis_6.3A.4.2.1_AbsPCTol_CA.zip	RAN5#85
6.3A.4.2.6 Absolute power tolerance for CA (7UL CA)	6	38.521-2_TP analysis_6.3A.4.2.1_AbsPCTol_CA.zip	RAN5#85
6.3A.4.2.7 Absolute power tolerance for CA (8UL CA)	6	38.521-2_TPanalysis_6.3A.4.2.1_AbsPCTol_CA.zip	RAN5#85
6.3A.4.4 Aggregate power tolerance for CA	1	38.521-2_TPanalysis_6.3A.4.4_Aggregate power tolerance for CA.zip	RAN5#92-e
6.3D.1 Minimum output power for UL MIMO	9	"38.521-2_TPanalysis_6.3.1_MinOP_v2.zip"	RAN5#84
6.3D.3.4 SRS time mask for UL-MIMO	18	"38.521-2_TPanalysis_6.3.3.2_SRS_M_UL-MIMO.zip"	RAN5#85
6.4.1 Frequency error	1	"38.521-2_TPanalysis_6.4.1_FreqErr.zip"	RAN5#80
6.4.2.1 Error Vector Magnitude	PUSCH: 168 PUCCH: 24 PRACH: 24	"38.521-2_TPanalysis_6.4.2.1_EVM.zip"	RAN5#3-5G-NR Adhoc
6.4.2.2 Carrier leakage	3	"38.521-2_TPanalysis_6.4.2.2_CarrLeak_v3.zip"	RAN5#93-e
6.4.2.3 In-band emissions	PUSCH: 36 PUCCH: 18	"38.521-1_TPanalysis_6.4.2.3_IE_v2.zip"	RAN5#89-e
6.4.2.4 EVM equalizer spectrum flatness	18	"38.521-2_TP analysis_6.4.2.4_6.4.2.5_EVMequalizerSpectrumFlatness.zip"	RAN5#3-5G-NR Adhoc
6.4.2.5 EVM spectral flatness for pi/2 BPSK modulation with spectrum shaping	9	"38.521-2_TP analysis_6.4.2.4_6.4.2.5_EVMequalizerSpectrumFlatness.zip"	RAN5#3-5G-NR Adhoc
6.4A.1 Frequency error for CA	N (1 test point per UL carrier)	"38.521-2_TPanalysis_6.4A.1_FreqErr_CA_v2.zip"	RAN5#87-e RAN5#90-e
6.4A.2.1 Error Vector Magnitude for CA	224	"38.521-2_TPanalysis_6.4A.2.1_EVM_CA.zip"	RAN5#91-e

6.4A.2.2 Carrier leakage for CA	2	"38.521-2_TPanalysis_6.4A.2.2_CarrLeak_CA_v3.zip"	RAN5#93-e
6.4D.3 Time alignment error for UL MIMO	6	"38.521-2_TPanalysis_6.4D.3_TAE_MIMO.zip"	RAN5#92-e
6.5.1 Occupied Bandwidth	12	"38.521-2_TPanalysis_6.5.1_OccBW_v3.zip"	RAN5#89-e RAN5#91-e
6.5.2.1 Spectrum Emission Mask	90	"38.521-2_TPanalysis_6.2.2_MPR_6.5.2.1_SEM_6.5.2.3_NR_ACLR_v4.zip"	RAN5#2-5G-NR Adhoc RAN5#79 RAN5#80 RAN5#89-e RAN5#90-e RAN5#91-e RAN5#92-e
6.5.2.3 Adjacent Channel Leakage Ratio	TBD	"38.521-2_TPanalysis_6.2.2_MPR_6.5.2.1_SEM_6.5.2.3_NR_ACLR_v4.zip"	RAN5#2-5G-NR Adhoc RAN5#89-e RAN5#90-e RAN5#91-e RAN5#92-e
6.5.3.1 Spurious emissions	4	"38.521-2_TPanalysis_6.5.3_TxSpurious_v3.zip"	RAN5#94-e
6.5.3.2 Spurious emissions UE band co-existence	4	"38.521-2_TPanalysis_6.5.3_TxSpurious_v3.zip"	RAN5#94-e
6.5.3.3 Additional spurious emission	NS202: 4 NS203: 4	"38.521-2_TPanalysis_6.2.3_AMPR_NS_202.zip" "38.521-2_TPanalysis_6.2.3_AMPR_NS_203.zip"	RAN5#90-e
6.5A.2.1 Spectrum Emission Mask for CA	30	"38.521-2_TPanalysis_6.5A.2.1_SEM_CA.zip"	RAN5#89-e
6.5A.2.2 Adjacent channel leakage ratio for CA	52	"38.521-2_TPanalysis_6.5A.2.2_ACLR_CA.zip"	RAN5#89-e
6.5A.3.1 Spurious emissions for CA	4	38.521-2_TPanalysis_6.5A.3_Spur_CA.zip	RAN5#91-e
6.5A.3.2 Spurious emissions for CA	4	38.521-2_TPanalysis_6.5A.3_SpurCoEx_CA.zip	RAN5#93-e
6.5D.1 Occupied Bandwidth for UL MIMO	12	"38.521-2_TPanalysis_6.5.1_OccBW_v3.zip"	RAN5#91-e
6.5D.2.1 Spectrum Emission Mask for UL MIMO	x	"38.521-2_TPanalysis_6.2.2_MPR_6.5.2.1_SEM_6.5.2.3_NR_ACLR_v4.zip"	RAN5#92-e
6.5D.2.2 Adjacent channel leakage ratio for UL MIMO	x	"38.521-2_TPanalysis_6.2.2_MPR_6.5.2.1_SEM_6.5.2.3_NR_ACLR_v4.zip"	RAN5#92-e
6.5D.3.1 Transmitter Spurious emissions for UL MIMO	4	"38.521-2_TPanalysis_6.5.3_TxSpurious_v3.zip"	RAN5#94-e
6.5D.3.2 Spurious emission band UE co-existence for UL MIMO	4	"38.521-2_TPanalysis_6.5.3_TxSpurious_v3.zip"	RAN5#94-e
6.5D.3.3 Additional spurious emissions for UL MIMO	NS202: 4 NS203: 4	"38.521-2_TPanalysis_6.2.3_AMPR_NS_202.zip" "38.521-2_TPanalysis_6.2.3_AMPR_NS_203.zip"	RAN5#94-e
6.6 Beam Correspondence	6	"38.521-2_TPanalysis_6.6_Beam_Correspond_v1.zip"	RAN5#85

Table 4.2.1.1-2: NR UE receiver test point selection for FR2

Subclause	Number of test points	Justification in attachment	Comments
7.3 Reference sensitivity	9	"38.521-2_TPanalysis_7.3_RefSense.zip"	RAN5#80
7.3A Reference sensitivity for CA	9	"38.521-2_TPanalysis_7.3A_RefSenseCA.zip"	RAN5#86-e
7.4 Maximum input level	6	"38.521-2_TPanalysis_7.4_Maximum input level v1.zip"	RAN5#93-e
7.4A Maximum input level for CA	2	"38.521-2_TPanalysis_7.4A_Maximum input level for CA v1.zip"	RAN5#93-e
7.5 Adjacent channel selectivity	3	"38.521-2_TPanalysis_7.5_ACS_v1.zip"	RAN5#83
7.6.2 In Band Blocking	3	"38.521-2_TPanalysis_7.6.2 InB_Block_v1.zip"	RAN5#83

4.2.2 Test point analysis per NS value

4.2.2.1 A-MPR and A-SE FR2 test cases for single carrier

This section contains information on test point selection for test case 6.2.3 in [3] Additional Maximum Power Reduction (A-MPR) as well as the related spectrum emissions test case 6.5.3.3 in [3] Additional Spurious emission (A-SE). Selection of test points should include some possible worst combinations based on the A-MPR and spectrum emissions characteristics specified for each NS value. The number of test points should be realistic.

Since A-MPR is defined by RAN4 together with A-Spurious requirements, a combined analysis is required. In general, the following non-compliant UE behaviours need to be checked:

- a) UE apply too much A-MPR (more than RAN4 allow)
- b) UE apply to little A-MPR (causing too much spectrum emissions)

Case A can be verified in A-MPR test case

Case B can be verified in A-SE test case if it is ensured that the same test point is tested inside A-MPR test. Therefore, the test points in spectrum emissions test case must be a subset of the test points in the A-MPR test case.

Note: Even if there are identical test points in the MPR test case the A-MPR test case is still needed to verify UE output power when NS-value is signalled.

Table 4.2.2.1-1: NS value specific test points for A-MPR single carrier

NS label	Number of test points	Justification	Comments
NS_202	6.2.3: 3 6.5.3.3: 3	"38.521-2_TPanalysis_6.2.3_AMPR_NS_202_v2.zip"	RAN5#93-e
NS_203	6.2.3: 3 6.5.3.3: 3	"38.521-2_TPanalysis_6.2.3_AMPR_NS_203_v2.zip"	RAN5#93-e

4.2.3 Test point analysis per NR CA configuration

4.2.3.1 Reference Sensitivity test cases for FR2 NR CA

Editor's note: TP analyses for FR2 NR CA will be added to this clause.

4.3 Test point analysis for test cases in TS 38.521-3

4.3.1 Test point analysis per test case

4.3.1.1 EN-DC test cases

Table 4.3.1.1-1: NR UE transmitter test point selection for EN-DC

Subclause	Number of test points	Justification in attachment	Comments
6.2B.1.1 UE Maximum Output Power for Intra-Band Contiguous EN-DC	20	"38.521-3_TPanalysis_6.2B.1.1_MOP_Intra_B_contig_v4.zip"	RAN5#88-e
6.2B.1.2 UE Maximum Output Power for Intra-Band Non-Contiguous EN-DC	40	"38.521-3_TPanalysis_6.2B.1.2_MOP_Intra_B_non-contig_v2.zip"	RAN5#87-e
6.2B.1.3 UE Maximum Output Power for Inter-Band EN-DC	600	"38.521-3_TPanalysis_6.2B.1.3_MOP_Inter_B_Config_v2.zip"	RAN5#86-e
6.2B.2.1 UE Maximum Output Power reduction for Intra-Band Contiguous EN-DC	1880	"38.521-3_TPanalysis_6.2B.2.1_MPR_6.5B.2.1_SEM_6.5B.2.1.3_ACLR.zip"	RAN5#87-e
6.2B.2.2 UE Maximum Output Power reduction for Intra-Band Non-Contiguous EN-DC	1140	"38.521-3_TPanalysis_6.2B.2.2_MPR_6.5B.2.2.1_SEM_6.5B.2.2.3_ACLR_v1.zip"	RAN5#93-e
6.2B.2.3 UE Maximum Output Power reduction for Inter-Band EN-DC within FR1	Same as Table 4.1.1-1, test case 6.5.2	Same as Table 4.1.1.1-1, test case 6.5.2.	RAN5#3-5G-NR Adhoc
6.2B.2.4 UE Maximum Output Power reduction for Inter-Band EN-DC including FR2	Same as Table 4.1.1-1, test case 6.2.2	Same as Table 4.1.1.1-1, test case 6.2.2	RAN5#5-5G-NR-Adhoc
6.2B.3.1 UE Additional Maximum Output Power reduction for Intra-band contiguous EN-DC	340	"38.521-3_TPanalysis_6.2B.3.1_AMPR_NS_04_v3.zip"	RAN5#81
	8	"38.521-3_TPanalysis_6.2B.3.1_AMPR_NS_35.zip"	RAN5#3-5G-NR Adhoc
6.2B.4.1.1 Configured Output Power Level for Intra-Band Contiguous EN-DC	-UE not supporting DPS: 90 -UE supporting DPS: 120	"38.521-3_TPanalysis_6.2B.4.1.1_ConfiguredTP_Intra_B_Contig_v2.zip"	RAN5#86-e
6.2B.4.1.2 Configured Output Power for Intra-Band Non-Contiguous EN-DC	-UE not supporting DPS: 70 -UE supporting DPS: 100	"38.521-3_TPanalysis_6.2B.4.1.2_ConfiguredTP_Intra_B_Non-contig_v2.zip"	RAN5#86-e
6.2B.4.1.3 Configured Output Power for Inter-Band EN-DC within FR1	-UE not supporting DPS: 90 -UE supporting DPS: 140	"38.521-3_TPanalysis_6.2B.4.1.3_ConfiguredTP_Inter_B_within_FR1_v2.zip"	RAN5#86-e
6.4B.2.1.3 In-band emissions for intra-band contiguous EN-DC	36	"38.521-3_TPanalysis_6.4B.2.1.3_IBE_Intra_B_contig_v1.zip"	RAN5#92-e
6.5B.1.1 Occupied bandwidth for Intra-Band Contiguous EN-DC	X= intra-band ENDC channel BWs supported by UE	"38.521-3_TPanalysis_6.5B.1.1_OBW_Intra_B_contig.zip"	RAN5#3-5G-NR adhoc
6.5B.2.1.1 Spectrum emissions mask for intra-band contiguous EN-DC	304	"38.521-3_TPanalysis_6.2B.2.1_MPR_6.5B.2.1_SEM_6.5B.2.1.3_ACLR.zip"	RAN5#87-e
6.5B.2.1.3 Adjacent channel leakage ratio for intra-band contiguous EN-DC	2160	38.521-3_TPanalysis_6.2B.2.1_MPR_6.5B.2.1_SEM_6.5B.2.1.3_ACLR.zip""	RAN5#87-e
6.5B.2.2.1 Spectrum emissions mask for intra-band non-contiguous EN-DC	228	38.521-3_TPanalysis_6.2B.2.2_MPR_6.5B.2.2.1_SEM_6.5B.2.2.3_ACLR_v1.zip	RAN5#93-e

6.5B.2.2.3 Adjacent channel leakage ratio for intra-band non-contiguous EN-DC	1140	38.521-3_TPanalysis_6.2B.2.2_MPR_6.5B.2.2.1_SEM_6.5B.2.2.3_ACLR_v1.zip	RAN5#93-e
6.5B.3.1.2 Spurious emission band UE co-existence for intra-band contiguous EN-DC	8	"38.521-3_TPanalysis_6.5B.3_TX_SpurEmission_Intra_B_EN-DC"	RAN5#91-e
6.5B.3.2.2 Spurious emission band UE co-existence for intra-band non-contiguous EN-DC	8	"38.521-3_TPanalysis_6.5B.3_TX_SpurEmission_Intra_B_EN-DC"	RAN5#91-e
6.5B.3.3.1 General spurious emissions for Inter-band EN-DC within FR1	12	"38.521-3_TPanalysis_6.5B.3.3.1_TX_SpurEmission_Inter_B_EN-DC.zip"	RAN5#91-e
6.5B.3.3.2 Spurious Emissions band UE co-existence for Inter-band within FR1	Note 1	"38.521-3_TPanalysis_6.5B.3.3.2_TX_SpurEmission_Inter_B_EN-DC"	RAN5#91-e
Note 1: The maximum number of test point is 2 if only default points are applied.			

Table 4.3.1.1-2: NR UE receiver test point selection for EN-DC

Subclause	Number of test points	Justification in attachment	Comments
7.3B Reference sensitivity for EN-DC		"38.521-3_TPanalysis_7.3B_RxSense_EN-DC with FR1_v2.zip"	RAN5#89-e
7.4B.1 Maximum Input Level for Intra-Band Contiguous EN-DC	6	"38.521-3_TPanalysis_7.4B.1.1_MaxIL_Intra_B_contig.zip"	RAN5#82
7.4B.2 Maximum Input Level for Intra-Band Non-Contiguous EN-DC	6	"38.521-3_TPanalysis_7.4B.2_MaxIL_Intra_B_noncontig.zip"	RAN5#82
7.5B.1 Adjacent Channel Selectivity for intra-band contiguous EN-DC (2 CCs)	2	"38.521-3_TPanalysis_7.5B.1_ACS_Intra_B_contig.zip"	RAN5#94-e
7.5B.2 Adjacent Channel Selectivity for intra-band non-contiguous EN-DC (2 CCs)	2	Same as Table 4.1.1-1, test case 7.5	RAN5#94-e
7.5B.3 Adjacent Channel Selectivity for inter-band EN-DC (1 NR CC)	3	Same as Table 4.1.1-1, test case 7.5	RAN5#94-e
7.6B.2.1 Inband blocking for intra-band contiguous EN-DC in FR1 (2 CCs)	2	"38.521-3_TPanalysis_7.6B.2.1_IBB_Intra_B_contig.zip"	RAN5#87-e
7.6B.2.2 Inband blocking for intra-band non-contiguous EN-DC in FR1 (2 CCs)	1	"38.521-3_TPanalysis_7.6B.2.2_IBB_Intra_B_non-contig.zip"	RAN5#87-e
7.6B.2.3 Inband blocking for inter-band EN-DC within FR1 (2 CCs)	Same as Table 4.1-2, test case 7.6.2.	Same as Table 4.1-2, test case 7.6.2.	RAN5#87-e
7.6B.3.1 Out-of-band blocking for intra-band contiguous EN-DC in FR1 (2 CCs)	1	"38.521-3_TPanalysis_7.6B.3.1_OOBB_Intra_B_contig.zip"	RAN5#87-e
7.6B.3.2 Out-of-band blocking for intra-band non-contiguous EN-DC in FR1 (2 CCs)	1	"38.521-3_TPanalysis_7.6B.3.2_OOBB_Intra_B_non-contig.zip"	RAN5#87-e
7.6B.3.3 Out-of-band blocking for inter-band EN-DC within FR1 (2 CCs)	1	"38.521-3_TPanalysis_7.6B.3.3_OOBB_Inter_B_within FR1.zip"	RAN5#87-e
7.6B.4.1 Narrow band blocking for intra-band contiguous EN-DC in FR1 (2 CCs)	2	"38.521-3_TPanalysis_7.6B.4.1_NBB_Intra_B_contig.zip"	RAN5#87-e
7.6B.4.2 Narrow band blocking for intra-band non-contiguous EN-DC in FR1 (2 CCs)	1	"38.521-3_TPanalysis_7.6B.4.2_NBB_Intra_B_non-contig.zip"	RAN5#87-e
7.6B.4.3 Narrow band blocking for inter-band EN-DC within FR1 (2 CCs)	Same as Table 4.1-2, test case 7.6.4.	Same as Table 4.1-2, test case 7.6.4.	RAN5#87-e
7.7B.1 Spurious Response for intra-band contiguous EN-DC in FR1 (2 CCs)	Same as Table 4.3-2, test case 7.6B.3.1.	Same as Table 4.3-2, test case 7.6B.3.1.	RAN5#87-e
7.7B.2 Spurious Response for intra-band non-contiguous EN-DC in FR1 (2 CCs)	Same as Table 4.3-2, test case 7.6B.3.2.	Same as Table 4.3-2, test case 7.6B.3.2.	RAN5#87-e

7.7B.3 Spurious Response for inter-band EN-DC within FR1 (2 CCs)	Same as Table 4.3-2, test case 7.6B.3.3.	Same as Table 4.3-2, test case 7.6B.3.3.	RAN5#87-e
7.8B.2.3 Wideband Intermodulation for inter-band EN-DC within FR1	Same as Table 4.1-2, test case 7.8.2.	Same as Table 4.1-2, test case 7.8.2.	RAN5#81
7.9A.1 Spurious emission for 2DL CA	3	"38.521-1_TPanalysis_7.9A_Spurious Emission_DL CA.zip"	RAN5#82
7.9B.3 Spurious Emissions for inter-band EN-DC within FR1	Same as Table 4.1-2, test case 7.9.	Same as Table 4.1-2, test case 7.9.	RAN5#81

4.3.1.2 V2X test cases

Table 4.3.1.2-1: UE transmitter test point selection for E-UTRA-NR V2X

Subclause	Number of test points	Justification in attachment	Comments
6.2E.1 UE Maximum Output Power for V2X	Intra-band contiguous V2X: N/A Intra-band non-contiguous V2X: N/A Inter-band con-current V2X: 20	"38.521-3_TPanalysis_V2X_6.2E.1_MOP.zip"	RAN5#93-e
6.2E.2 UE maximum output power reduction for V2X	Intra-band contiguous V2X: N/A Intra-band non-contiguous V2X: N/A Inter-band con-current V2X: - 80 for E-UTRA Uu + NR SL - 220 for NR Uu + E-UTRA SL	"38.521-3_TPanalysis_V2X_6.2E.2_MPR_6.5E.2.1_SEM_6.5E.2.3_ACLR.zip"	RAN5#93-e
6.5E.2.1 Spectrum emission mask for V2X	Intra-band contiguous V2X: N/A Intra-band non-contiguous V2X: N/A Inter-band con-current V2X: - 8 for E-UTRA Uu + NR SL - 28 for NR Uu + E-UTRA SL	"38.521-3_TPanalysis_V2X_6.2E.2_MPR_6.5E.2.1_SEM_6.5E.2.3_ACLR.zip"	RAN5#93-e
6.5E.2.3 Adjacent channel leakage ratio for V2X	Intra-band contiguous V2X: N/A Intra-band non-contiguous V2X: N/A Inter-band con-current V2X: - 80 for E-UTRA Uu + NR SL - 220 for NR Uu + E-UTRA SL	"38.521-3_TPanalysis_V2X_6.2E.2_MPR_6.5E.2.1_SEM_6.5E.2.3_ACLR.zip"	RAN5#93-e

4.3.2 Test point analysis per NS value

4.3.2.1 A-MPR and A-SE test cases for EN-DC

FFS

4.3.3 Test point analysis per EN-DC configuration

4.3.3.1 Reference sensitivity test cases for EN-DC

This clause contains information on test point analysis and status for FR1 EN-DC test cases in TS 38.521-3 [4] clause 7. The analyses are performed per EN-DC configuration in Table 4.3.3.1-1, Table 4.3.3.1-2 and Table 4.3.3.1-3.

Table 4.3.3.1-1: Reference Sensitivity test cases per EN-DC configuration (2CC)

Band or band configuration	Single UL	Refsens exception, victim band (NOTE 2)	Requirement coverage (NOTE 2)	Comments
DC_(n)XAA				
5	Only single UL requirements defined	5	Exception	Added at RAN5#92-e
12	Only single UL requirements defined	12	Exception	Added at RAN5#92-e
38	Only single UL requirements defined	N/A	NE	Added at RAN5#88-e
41	Yes	N/A	NE	Added at RAN5#88-e
48	Only single UL requirements defined	N/A	NE	Added at RAN5#88-e
71	Yes	71	Exception	Added at RAN5#88-e
DC_XA_nXA				
DC_2A_n2A	Only single UL requirements defined	N/A	NE	Added at RAN5#88-e
DC_3A_n3A	Yes	3	Exception	Added at RAN5#88-e
DC_5A_n5A	Only single UL requirements defined	N/A	NE	Added at RAN5#88-e
DC_7A_n7A	Only single UL requirements defined	N/A	NE	Added at RAN5#88-e
DC_41A_n41A	Only single UL requirements defined	N/A	NE	Added at RAN5#88-e
DC_48A_n48A	Only single UL requirements defined	N/A	NE	Added at RAN5#88-e
DC_66A_n66A	Only single UL requirements defined	N/A	NE	Added at RAN5#88-e
DC_71A_n71A	Only single UL requirements defined	N/A	NE	Added at RAN5#92-e
DC_XA-nYA (NOTE 1)				
DC_1A_n3A	Yes	1 (IMD3) CBI	NE IMD3 CBI, CBI avoid	Added at RAN5#89-e
DC_1A-n5A	No	1 (IMD4)	NE IMD4	Added at RAN5#94-e
DC_1A-n7A	No	N/A	NE	Added at RAN5#94-e
DC_1A_n78A	No	1 (IMD4)	NE IMD4	Added at RAN5#88-e
DC_2A_n66A	No	3 (IMD3) n66 (IMD5)	NE IMD3 IMD5	Added at RAN5#94-e
DC_2A_n71A	No	2 (HD3) n71 (HM)	NE HD HM	Added at RAN5#93-e
DC_2A_n77A	No	n77 (HD) 2 (HM) 2 (IMD2) 2 (IMD4) 2 (IMD5)	NE HD, HD avoid HM, HM avoid IMD2 PC2&PC3 IMD4 PC2&PC3 IMD5 PC3	Added at RAN5#94-e
DC_2A_n78A	No	n78 (HD2) 2 (IMD2) 2 (IMD4)	NE HD IMD2 IMD4	Added at RAN5#94-e
DC_3A_n1A	Yes	1 (IMD3) CBI	NE IMD3 CBI, CBI avoid	Added at RAN5#89-e
DC_3A_n5A	Yes	3 (IMD4) n5 (IMD2)	NE IMD2 IMD4	Added at RAN5#94-e
DC_3A_n78A	Yes	3 (IMD2) 3 (IMD4) 3 (HD) n78 (HM)	NE IMD2 PC2&PC3 IMD4 PC2&PC3 HD HM, HM avoid	Added at RAN5#89-e
DC_5A_n66A	Yes	5 (IMD2)	NE (anchor agnostic) IMD2	Added at RAN5#93-e

DC_5A_n77A	No	n77 (HD) 5 (IMD4) 5 (IMD5)	NE HD, HD avoid IMD4 PC2&PC3 IMD5 PC3	Added at RAN5#94-e
DC_7A_n1A	No	N/A	NE	Added at RAN5#90-e
DC_7A_n3A	No	7 (IMD4 3*fB3-1*fB7)	NE, IMD4	Added at RAN5#90-e
DC_7A_n5A	Yes	n5 (IMD3)	NE, IMD3	Added at RAN5#94-e
DC_7A_n28A	No	N/A	NE	Added at RAN5#94-e
DC_7A_n78A	No	CBI	NE, CBI	Added at RAN5#94-e
DC_8A_n1A	No	n1 (IMD4 2*fB1-2*fB8)	NE, IMD4	Added at RAN5#90-e
DC_8A_n3A	No	8 (IMD4 3*fB8-1*fB3), n3 (IMD5 4*fB8-1*fB3)	NE, IMD4, IMD5	Added at RAN5#90-e
DC_8A_n20A	Yes	8 (IMD3) n20 (IMD3)	NE IMD3	Added at RAN5#94-e
DC_8A_n77A	No	8 (HD4), 8 (IMD4)	NE HD, HD avoid IMD4	Added at RAN5#92-e
DC_11A_n77A	No	N/A	NE	Added at RAN5#91-e
DC_11A_n78A	No	N/A	NE	Added at RAN5#91-e
DC_11A_n79A	No	11 (HM)	NE HM, HM avoid	Added at RAN5#92-e
DC_13A_n77A	No	n77 (HD) 13 (HM) 13 (IMD5)	NE HD, HD avoid HM, HM avoid IMD5 PC2&PC3	Added at RAN5#94-e
DC_19A_n79A	No	19 (HM 5*fB19DL-1*fB79),	NE, HM, HM avoid	Added at RAN5#90-e
DC_20A_n1A	No	N/A	NE	Added at RAN5#90-e
DC_20A_n3A	No	n3 (IMD4), 20 (IMD4)	NE IMD4	Added at RAN5#89-e
DC_20A_n7A	DC_20_n7	20 (IMD3)	NE IMD3	Added at RAN5#94-e
DC_20A_n78A	No	20 (IMD4), n78 (HD)	NE IMD4, HD, HD avoid	Added at RAN5#88-e
DC_25A_n41A	No	N/A	NE	Added at RAN5#91-e
DC_26A_n41A	No	n41 (HD3), 26 (IMD3)	NE HD, HD avoid IMD	Added at RAN5#92-e
DC_26A_n77A	No	n77 (HD4), 26 (IMD4)	NE HD, HD avoid IMD	Added at RAN5#92-e
DC_26A_n78A	No	n78 (HD4), 26 (IMD4)	NE HD, HD avoid IMD	Added at RAN5#92-e
DC_26A_n79A	No	26 (HM 4*fB26DL-1*fB79)	NE HM, HM avoid	Added at RAN5#92-e
DC_28A_n5A	No	CBI	NE CBI, CBI avoid	Added at RAN5#94-e
DC_28A_n7A	No	N/A	NE	Added at RAN5#94-e
DC_28A_n77A	No	n77 (HD), n77 (HM), 28 (IMD5)	NE (HD avoid), HD, HM, IMD5	Added at RAN5#92-e
DC_28A_n78A	No	n78 (HD), 28 (IMD5)	NE (HD avoid), HD, IMD5	Added at RAN5#92-e
DC_40A_n1A	No	N/A	NE	Added at RAN5#89-e
DC_40A_n78A	No	40 (HM)	NE HM, HM avoid	Added at RAN5#89-e
DC_40A_n79A	No	N/A	NE	Added at RAN5#94-e

DC_41A_n77A (NOTE 3)	No	41 (HM 3*fB41DL- 2*fB77), 41 (CBI), n77 (CBI)	NE HM CBI	Added at RAN5#92-e
DC_41A_n78A (NOTE 3)	No	41 (HM 3*fB41DL- 2*fB77), 41 (CBI), n78 (CBI)	NE HM CBI	Added at RAN5#92-e
DC_42A_n77A	Only single UL requirements defined	N/A	NE	Added at RAN5#91-e
DC_48A_n66A	No	48 (HD2) 66 (IMD5)	NE (anchor agnostic) HD2 IMD5	Added at RAN5#92-e
DC_66A_n2A	DC_66_n2	n2 (IMD3) 66 (IMD5)	NE (anchor agnostic) IMD3 IMD5	Added at RAN5#93-e
DC_66A_n71A	No	66 (IMD4)	NE (anchor agnostic) IMD4	Added at RAN5#93-e
DC_66A_n77A	No	n77 (HD) 66 (IMD2) 66 (IMD5)	NE HD, HD avoid IMD2 PC2&PC3 IMD5 PC2&PC3	Added at RAN5#94-e
DC_66A_n78A	No	n78 (HD2) 66 (IMD5)	NE (anchor agnostic) HD2 IMD5	Added at RAN5#93-e
NOTE 1: If single UL is allowed in a DC_XA_nYA configuration the IMD requirements does not apply for UEs supporting UE capability <i>singleUL-Transmission</i>. NOTE 2: Notations used NE: Non-exception as defined in TS 38.101-3 [7], meaning standalone LTE in TS 36.101 [8] and NR in 38.101-1 [5] requirements apply. HD: UL Harmonic Distortion, as defined in TS 38.101-3 [7], 7.3B.2.3.1 HM: RX Harmonic Mixing, as defined in TS 38.101-3 [7], 7.3B.2.3.2 IMD: Intermodulation Distortion, as defined in TS 38.101-3 [7], 7.3B.2.3.5 CBI: Cross Band Isolation, as defined in TS 38.101-3 [7], 7.3B.2.3.4 HD avoid: single carrier requirements apply with aggressor of UL Harmonic Distortion active. HM avoid: single carrier requirements apply with aggressor of RX Harmonic Mixing active. CBI avoid: single carrier requirements apply with aggressor of Cross Band Isolation active. NOTE 3: HM cannot be avoided with aggressor still active since CBI exception always exists. Therefore, no HM avoid test point is added.				

Table 4.3.3.1-2: Reference Sensitivity test cases per EN-DC configuration (3CC)

Band or band configuration	Single UL	UL config	Refsens exception, victim band	Requirement coverage (NOTE 2)	Fallback DC configurations	Comments
DC_(n)XCA						
41	Yes	DC_(n)41AA	N/A	NE	DC_(n)41AA DC_41A_n41A	Added at RAN5#89-e
41	Yes	DC_41A_n41A	N/A	NE	DC_(n)41AA DC_41A_n41A	Added at RAN5#89-e
48	Only single UL requirements defined	DC_(n)48AA	N/A	NE	DC_(n)48AA DC_48A_n48A	Added at RAN5#89-e
48	Only single UL requirements defined	DC_48A_n48A	N/A	NE	DC_(n)48AA DC_48A_n48A	Added at RAN5#89-e
DC_XA_nYC						
DC_3A_n78C	Yes	DC_3A_n78A	N/A	NE		Added at RAN5#93-e
DC_XA_nY(2A)						
FFS						
DC_XA_nYA-nZA						
DC_1A_n28A-n78A	No	DC_1A_n28A	n78 (3 band IMD3)	NE, IMD3		Added at RAN5#92-e
	No	DC_1A_n78A	n28 (3 band IMD5)	NE, IMD5		Added at RAN5#92-e
DC_3A_n28A-n78A	No	DC_3A_n28A	n78 (3 band IMD5)	NE, IMD5		Added at RAN5#92-e
	Yes	DC_3A_n78A	No 3CC exception	No test required		
DC_7A_n5A-n78A	Yes	DC_7A_n5A	No 3CC exception	No test required		Added at RAN5#94-e
	No	DC_7A_n78A	No 3CC exception	No test required		Added at RAN5#94-e
DC_7A_n28A-n78A	No	DC_7A_n28A	n78 (3 band IMD2)	NE, IMD2		Added at RAN5#92-e
	No	DC_7A_n78A	n28 (3 band IMD2)	NE, IMD2		
DC_20A_n28A-n78A	No	DC_20A_n28A	n78 (3 band IMD4)	NE, IMD4		Added at RAN5#93-e
	No	DC_20A_n78A	n28 (3 band IMD4)	NE, IMD4		Added at RAN5#93-e
DC_28A_n7A-n78A	No	DC_28A_n7A	n78 (3 band IMD2)	NE, IMD2		Added at RAN5#94-e
	No	DC_28A_n78A	n7 (3 band IMD2)	NE, IMD2		Added at RAN5#94-e
DC_XA-YA_nZA						
DC_1A-3A_n28A	No	DC_1A_n28A	3 (3 band IMD5)	IMD5		Added at RAN5#92-e
	No	DC_3A_n28A	1 (3 band IMD4)	IMD4		Added at RAN5#92-e
DC_1A-7A_n3A	Yes	DC_1A_n3A	No 3CC exception	No test required		
	No	DC_7A_n3A				
DC_1A-7A_n28A	No	DC_1A_n28A	7 (3 band IMD2)	IMD2		Added at RAN5#92-e
	No	DC_7A_n28A	No 3 band exception	No test required		Added at RAN5#92-e
DC_1A-7A_n78A	No	DC_1A_n78A	7 (IMD4 [3*FB1-1*FB78])	IMD4		
	No	DC_7A_n78A	1 (IMD4 [2*FB7-2*FB78])	IMD4		
DC_1A-8A_n3A	Yes	DC_1A_n3A	No 3CC exception	No test required		
	No	DC_8A_n3A				
DC_1A-20A_n3A	Yes	DC_1A_n3A	No 3CC exception	No test required		
	No	DC_20A_n3A				
DC_1A-20A_n28A	No	DC_1A_n28A	No 3CC exception	No test required		Added at RAN5#93-e

	No	DC_20A_n28A	No 3CC exception	No test required		Added at RAN5#93-e
DC_1A-20A_n78A	No	DC_1A_n78A	20 (IMD5	IMD5		
	No	DC_20A_n78A	1 (IMD3	IMD3		
DC_1A-28A_n3A	Yes	DC_1A_n3A	1 (3 band IMD4)	IMD4	Yes	Added at RAN5#90-e
	No	DC_28A_n3A	No 3CC exception	-	No	
DC_1A-28A_n78A	No	DC_1A_n78A	28 (3 band IMD3)	IMD3		Added at RAN5#92-e
	No	DC_28A_n78A	1 (3 band IMD5)	IMD5	DC_28A_n78A	
DC_3A-7A_n1A	Yes	DC_3A_n1A	No 3CC exception	No test required		Added at RAN5#90-e
	No	DC_7A_n1A	No 3CC exception			
DC_3A-7A_n28A	No	DC_3A_n28A	7 (3 band IMD3)	IMD3		Added at RAN5#92-e
	No	DC_7A_n28A	3 (3 band IMD2)	IMD2		Added at RAN5#92-e
DC_3A-20A_n1	Yes	DC_3A_n1A	No 3CC exception	No test required		
	No	DC_20A_n1A				
DC_3A-20A_n28A	No	DC_3A_n28A	No 3CC exception	No test required		Added at RAN5#92-e
	No	DC_20A_n28A	3 (3 band IMD4)	IMD4		Added at RAN5#92-e
DC_3A-20A_n78	Yes	DC_3A_n78A	No 3CC exception			
	No	DC_20A_n78A	3 (3 band IMD3)	IMD3		
DC_3A-28A_n78A	Yes	DC_3A_n78A	No 3CC exception		DC_3A_n78A	Added at RAN5#92-e
	No	DC_28A_n78A	3 (3 band IMD3)	IMD3	DC_28A_n78A	
DC_3A-40A_n1A	Yes	DC_3A_n1A	40 (3 band IMD5)	IMD5 if UE supporting dual UL		
	No	DC_40A_n1A	No 3CC exception			
DC_7A-20A_n1A	No	DC_20A_n1A	20 (3 band IMD5)	IMD5		Added at RAN5#90-e
	No	DC_7A_n1A	No 3CC exception	-		
DC_7A-20A_n3A	No	DC_7A_n3A	20 (IMD2 1*FB7-1*FB3)	NE, IMD2		
	No	DC_20A_n3A	7 (IMD2 1*FB3+1*FB20)	NE, IMD2		
DC_7A-20A_n28A	No	DC_7A_n28A	No 3CC exception	No test required		Added at RAN5#92-e
	No	DC_20A_n28A	7 (3 band IMD5)	IMD 5		
DC_7A-20A_n78A	No	DC_7A_n78A	20 (3 band IMD2)	IMD2, IMD5		
	No	2 DC_0A_n78A	7 (3 band IMD2)	IMD2		
DC_7A-28A_n3A	No	DC_7A_n3A	28 (3 band IMD2)	IMD2		Added at RAN5#90-e
	No	DC_28A_n3A	7 (3 band IMD3)	IMD3		
DC_7A-28A_n78A	No	DC_7A_n78A	28 (3 band IMD2)	IMD2, IMD5		Added at RAN5#92-e
	No	DC_28A_n78A	7 (3 band IMD2)	IMD2	DC_28A_n78A	
DC_(n)XAA-nYA						
FFS						
DC_XA_nXA_nYA						
FFS						

NOTE 1:	If single UL is allowed in a DC_XA_nYA configuration the IMD requirements does not apply for UEs supporting UE capability <i>singleUL-Transmission</i> .
NOTE 2:	Notations used
	NE: Non-exception as defined in TS 38.101-3 [7], meaning standalone LTE in TS 36.101 [8] and NR in 38.101-1 [5] requirements apply.
	HD: UL Harmonic Distortion, as defined in TS 38.101-3 [7], 7.3B.2.3.1
	HM: RX Harmonic Mixing, as defined in TS 38.101-3 [7], 7.3B.2.3.2
	IMD: Intermodulation Distortion, as defined in TS 38.101-3 [7], 7.3B.2.3.5
	CBI: Cross Band Isolation, as defined in TS 38.101-3 [7], 7.3B.2.3.4

Table 4.3.3.1-3: Reference Sensitivity test cases per EN-DC configuration (4CC)

Band or band configuration	Single UL	UL config	Refsens exception, victim band	Requirement coverage (NOTEote 2)	Fallback DC configurations	Comments
DC_(n)XDA						
41	Yes	DC_(n)41AA	N/A	NE	DC_(n)41CA DC_41C_n41A	Added at RAN5#89-e
41	Yes	DC_41A_n41A	N/A	NE	N/A	Added at RAN5#89-e
48	Only single UL requirements defined	DC_(n)48AA	N/A	NE	DC_(n)48CA DC_48C_n48A	Added at RAN5#89-e
48	Only single UL requirements defined	DC_48A_n48A	N/A	NE	N/A	Added at RAN5#89-e
DC_XA_nY(2A)-nZA						
FFS						
DC_XA_nYA-nZC						
FFS						
NOTE 1:	If single UL is allowed in a DC_XA_nYA configuration the IMD requirements does not apply for UEs supporting UE capability <i>singleUL-Transmission</i> .					
NOTE 2:	Notations used					
	NE: Non-exception as defined in TS 38.101-3 [7], meaning standalone LTE in TS 36.101 [8] and NR in 38.101-1 [5] requirements apply.					
	HD: UL Harmonic Distortion, as defined in TS 38.101-3 [7], 7.3B.2.3.1					
	HM: RX Harmonic Mixing, as defined in TS 38.101-3 [7], 7.3B.2.3.2					
	IMD: Intermodulation Distortion, as defined in TS 38.101-3 [7], 7.3B.2.3.5					
	CBI: Cross Band Isolation, as defined in TS 38.101-3 [7], 7.3B.2.3.4					

4.3.3.2 Spurious emissions test cases for EN-DC

In this case, it is sufficient to verify the minimum requirements in frequency ranges affected by 2nd and 3rd order intermodulation products. The frequency ranges and UL RB allocations used in the test are calculated here.

The analyses are performed per EN-DC configuration and are stored as zip-files as defined in annex A.

Table 4.3.3.2-1: Frequency range analysis availability per EN-DC configuration

EN-DC config	Justification	Comments
DC 1A n3A	38.521-3 TpAnalysisSpur(DC 1A-n3A).zip	Added at RAN5#89-e
DC 1A n5A	38.521-3 TpAnalysisSpur(DC 1A n5A).zip	Added at RAN5#94-e
DC 1A n7A	38.521-3 TpAnalysisSpur(DC 1A n7A).zip	Added at RAN5#94-e
DC 1A n28A	38.521-3 TpAnalysisSpur(DC 1A n28A).zip	Added at RAN5#92-e
DC 1A n77A	38.521-3 TpAnalysisSpur(DC 1A n77A).zip	Added at RAN5#92-e
DC 1A n78A	38.521-3 TpAnalysisSpur(DC 1A n78A) v1.zip	Added at RAN5#92-e
DC 1A n79A	38.521-3 TpAnalysisSpur(DC 1A n79A).zip	Added at RAN5#92-e
DC 2A n5A	38.521-3 TpAnalysisSpur(DC 2A n5A).zip	Added at RAN5#89-e
DC 2A n41A	38.521-3 TpAnalysisSpur(DC 2A n41A).zip	Added at RAN5#90-e
DC 2A n66A	38.521-3 TpAnalysisSpur(DC 2A n66A).zip	Added at RAN5#88-e
DC 2A n71A	38.521-3 TpAnalysisSpur(DC 2A n71A) v2.zip	Added at RAN5#92-e
DC 2A n77A	38.521-3 TpAnalysisSpur(DC 2A n77A).zip	Added at RAN5#94-e
DC 2A n78A	38.521-3 TpAnalysisSpur(DC 2A n78A).zip	Added at RAN5#88-e
DC 3A n1A	38.521-3 TpAnalysisSpur(DC 3A n1A).zip	Added at RAN5#88-e
DC 3A n5A	38.521-3 TpAnalysisSpur(DC 3A n5A).zip	Added at RAN5#94-e
DC 3A n7A	38.521-3 TpAnalysisSpur(DC 3A n7A) v1.zip	Added at RAN5#91-e
DC 3A n28A	38.521-3 TpAnalysisSpur(DC 3A n28A).zip	Added at RAN5#92-e
DC 3A n41A	38.521-3 TpAnalysisSpur(DC 3A n41A) v3.zip	Added at RAN5#94-e
DC 3A n77A	38.521-3 TpAnalysisSpur(DC 3A n77A).zip	Added at RAN5#92-e
DC 3A n78A	38.521-3 TpAnalysisSpur(DC 3A n78A) v1.zip	Added at RAN5#91-e
DC 3A n79A	38.521-3 TpAnalysisSpur(DC 3A-n79A) v1.zip	Added at RAN5#83
DC 5A n2A	38.521-3 TpAnalysisSpur(DC 5A n2A).zip	Added at RAN5#92-e
DC 5A n66A	38.521-3 TpAnalysisSpur(DC 5A n66A) v2.zip	Added at RAN5#92-e
DC 5A n77A	38.521-3 TpAnalysisSpur(DC 5A n77A).zip	Added at RAN5#94-e
DC 5A n78A	38.521-3 TpAnalysisSpur(DC 5A n78A) v2.zip	Added at RAN5#92-e
DC 7A n1A	38.521-3 TpAnalysisSpur(DC 7A n1A).zip	Added at RAN5#88-e
DC 7A n3A	38.521-3 TpAnalysisSpur(DC 7A n3A).zip	Added at RAN5#90-e
DC 7A 5A	38.521-3 TpAnalysisSpur(DC 7A n5A).zip	Added at RAN5#94-e
DC 7A n28A	38.521-3 TpAnalysisSpur(DC 7A n28A).zip	Added at RAN5#92-e
DC 7A n66A	38.521-3 TpAnalysisSpur(DC 7A n66A).zip	Added at RAN5#88-e
DC 7A n78A	38.521-3 TpAnalysisSpur(DC 7A n78A) v1.zip	Added at RAN5#92-e
DC 8A n1A	38.521-3 TpAnalysisSpur(DC 8A n1A).zip	Added at RAN5#88-e
DC 8A n3A	38.521-3 TpAnalysisSpur(DC 8A n3A) v1.zip	Added at RAN5#94-e
DC 8A n20A	38.521-3 TpAnalysisSpur(DC 8A n20A).zip	Added at RAN5#94-e
DC 8A n41A	38.521-3 TpAnalysisSpur(DC 8A n41A) v3.zip	Added at RAN5#94-e
DC 8A n77A	38.521-3 TpAnalysisSpur(DC 8A n77A) v1.zip	Added at RAN5#91-e
DC 8A n78A	38.521-3 TpAnalysisSpur(DC 8A n78A) v1.zip	Added at RAN5#93-e
DC 11A n77A	38.521-3 TpAnalysisSpur(DC 11A n77A) v1.zip	Added at RAN5#92-e
DC 11A n78A	38.521-3 TpAnalysisSpur(DC 11A n78A) v1.zip	Added at RAN5#92-e
DC 11A n79A	38.521-3 TpAnalysisSpur(DC 11A n79A) v1.zip	Added at RAN5#92-e
DC 12A n66A	38.521-3 TpAnalysisSpur(DC 12A n66A) v1.zip	Added at RAN5#91-e
DC 12A n78A	38.521-3 TpAnalysisSpur(DC 12A n78A) v1.zip	Added at RAN5#92-e
DC 13A n2A	38.521-3 TpAnalysisSpur(DC 13A n2A) v1.zip	Added at RAN5#92-e
DC 13A n66A	38.521-3 TpAnalysisSpur(DC 13A n66A).zip	Added at RAN5#89-e
DC 13A n77A	38.521-3 TpAnalysisSpur(DC 13A n77A).zip	Added at RAN5#94-e
DC 14A n2A	38.521-3 TpAnalysisSpur(DC 14A n2A) v3.zip	Added at RAN5#93-e
DC 14A n66A	38.521-3 TpAnalysisSpur(DC 14A n66A) v3.zip	Added at RAN5#93-e
DC 19A n1A	38.521-3 TpAnalysisSpur(DC 19A n1A).zip	Added at RAN5#94-e
DC 19A n77A	38.521-3 TpAnalysisSpur(DC 19A n77A).zip	Added at RAN5#92-e
DC 19A n78A	38.521-3 TpAnalysisSpur(DC 19A n78A).zip	Added at RAN5#92-e
DC 19A n79A	38.521-3 TpAnalysisSpur(DC 19A n79A).zip	Added at RAN5#92-e
DC 20A n1A	38.521-3 TpAnalysisSpur(DC 20A-n1A).zip	Added at RAN5#90-e
DC 20A n3A	38.521-3 TpAnalysisSpur(DC 20A-n3A) v1.zip	Added at RAN5#94-e
DC 20A n7A	38.521-3 TpAnalysisSpur(DC 20A n7A).zip	Added at RAN5#94-e
DC 20A n78A	38.521-3 TpAnalysisSpur(DC 20A n78A).zip	Added at RAN5#92-e
DC 20A n28A	38.521-3 TpAnalysisSpur(DC 20A n28A).zip	Added at RAN5#92-e
DC 21A n1A	38.521-3 TpAnalysisSpur(DC 21A n1A).zip	Added at RAN5#94-e
DC 21A n77A	38.521-3 TpAnalysisSpur(DC 21A n77A).zip	Added at RAN5#92-e
DC 21A n78A	38.521-3 TpAnalysisSpur(DC 21A n78A).zip	Added at RAN5#92-e
DC 21A n79A	38.521-3 TpAnalysisSpur(DC 21A n79A).zip	Added at RAN5#92-e
DC 25A n41A	38.521-3 TpAnalysisSpur(DC 25A n41A) v2.zip	Added at RAN5#94-e
DC 26A n41A	38.521-3 TpAnalysisSpur(DC 26A n41A) v2.zip	Added at RAN5#94-e
DC 26A n77A	38.521-3 TpAnalysisSpur(DC 26A n77A) v1.zip	Added at RAN5#92-e
DC 26A n78A	38.521-3 TpAnalysisSpur(DC 26A n78A) v1.zip	Added at RAN5#92-e

DC_26A_n79A	38.521-3_TpAnalysisSpur(DC_26A_n79A)_v1.zip	Added at RAN5#91-e
DC_28A_n3A	38.521-3_TpAnalysisSpur(DC_28A_n3A)_v1.zip	Added at RAN5#92-e
DC_28A_n5A	38.521-3_TpAnalysisSpur(DC_28A_n5A).zip	Added at RAN5#94-e
DC_28A_n7A	38.521-3_TpAnalysisSpur(DC_28A_n7A).zip	Added at RAN5#94-e
DC_28A_n78A	38.521-3_TpAnalysisSpur(DC_28A_n78A).zip	Added at RAN5#92-e
DC_28A_n77A	38.521-3_TpAnalysisSpur(DC_28A_n77A).zip	Added at RAN5#92-e
DC_28A_n79A	38.521-3_TpAnalysisSpur(DC_28A_n79A).zip	Added at RAN5#92-e
DC_30A_n5A	38.521-3_TpAnalysisSpur(DC_30A_n5A)_v1.zip	Added at RAN5#91-e
DC_39A_n41A	38.521-3_TpAnalysisSpur(DC_39A_n41A)_v2.zip	Added at RAN5#94-e
DC_39A_n79A	38.521-3_TpAnalysisSpur(DC_39A_n79A)_v1.zip	Added at RAN5#92-e
DC_40A_n1A	38.521-3_TpAnalysisSpur(DC_40A_n1A)_v1.zip	Added at RAN5#92-e
DC_40A_n41A	38.521-3_TpAnalysisSpur(DC_40A_n41A)_v2.zip	Added at RAN5#94-e
DC_40A_n78A	38.521-3_TpAnalysisSpur(DC_40A_n78A)_v1.zip	Added at RAN5#92-e
DC_40A_n79A	38.521-3_TpAnalysisSpur(DC_40A_n79A).zip	Added at RAN5#94-e
DC_41A_n77A	38.521-3_TpAnalysisSpur(DC_41A_n77A)_v1.zip	Added at RAN5#92-e
DC_41A_n78A	38.521-3_TpAnalysisSpur(DC_41A_n78A)_v1.zip	Added at RAN5#92-e
DC_41A_n79A	38.521-3_TpAnalysisSpur(DC_41A_n79A)_v1.zip	Added at RAN5#92-e
DC_42A_n77A	38.521-3_TpAnalysisSpur(DC_42A_n77A).zip	Added at RAN5#92-e
DC_48A_n5A	38.521-3_TpAnalysisSpur(DC_48A_n5A).zip	Added at RAN5#90-e
DC_48A_n66A	38.521-3_TpAnalysisSpur(DC_48A_n66A).zip	Added at RAN5#90-e
DC_66A_n2A	38.521-3_TpAnalysisSpur(DC_66A_n2A).zip	Added at RAN5#88-e
DC_66A_n5A	38.521-3_TpAnalysisSpur(DC_66A_n5A)_v1.zip	Added at RAN5#92-e
DC_66A_n41A	38.521-3_TpAnalysisSpur(DC_66A_n41A).zip	Added at RAN5#90-e
DC_66A_n71A	38.521-3_TpAnalysisSpur(DC_66A_n71A)_v1.zip	Added at RAN5#92-e
DC_66A_n77A	38.521-3_TpAnalysisSpur(DC_66A_n77A).zip	Added at RAN5#94-e
DC_66A_n78A	38.521-3_TpAnalysisSpur(DC_66A_n78A)_v2.zip	Added at RAN5#92-e

Annex A: Derivation documents

The documents and spreadsheets used to give the background for the selected test points for each test case are included in the present document as zip files.

The name of the zip shall:

- Include a prefix allowing easier grouping of files, e.g. “38.521-1_TPanalysis”, “38.521-2_TPanalysis” or “38.521-3_TPanalysis”.les in the same area, e.g. .
- Include Test Case Number(s) and an abbreviation Test Case Name, e.g. “6.2.1_MOP”, “7.6.2.InB_Block” or “6.2.1_MOP+6.2.2_MPR”.
- In cases where multiple analysis is needed per test cases, e.g. for different CA configurations, include the CA band combination applicable in the parentheses, e.g. add “(1A-3A)” for CA_1A-3A.

Concatenated example file name: “38.521-1_TPanalysis_6.2.1_MOP.zip”.

If there is an update of test points for a test case the old corresponding zip file shall be replaced with a new zip file with a version stepping in the file name. e.g. “nnn_v2.zip”. The aim is to provide a reference to completed test cases, so that test points for similar test cases can be selected on a common basis.

For cases when no spreadsheet is used then the principles for selecting reference sensitivity test points are described in Annex B, C or D.

Annex B: Principles for test point selection for NR CA reference sensitivity test cases

B.1 General

From TS 38.521-1 [2] (Table 7.3.2.4.1-1), the initial conditions used for NR RX reference sensitivity is given below.

Initial Conditions				
Test Environment as specified in TS 38.508-1 [5] subclause 4.1			Normal, TL/VL, TL/VH, TH/VL, TH/VH	
Test Frequencies as specified in TS 38.508-1 [5] subclause 4.3.1			Low range, Mid range, High range (NOTE 4)	
Test Channel Bandwidths as specified in TS 38.508-1 [5] subclause 4.3.1			Lowest, Mid, Highest (NOTE 4) Lowest UL / Lowest DL, Lowest UL / Highest DL (NOTE 3)	
Test SCS as specified in Table 5.3.5-1			Lowest	
Test Parameters				
Test ID	Downlink Configuration		Uplink Configuration	
	Modulation	RB allocation	Modulation	RB allocation
1	CP-OFDM QPSK	Full RB (NOTE 1)	DFT-s-OFDM QPSK	REFERENCE SENSITIVITY (NOTE 2)
NOTE 1: Full RB allocation shall be used per each SCS and channel BW as specified in Table 7.3.2.4.1-2.				
NOTE 2: REFERENCE SENSITIVITY refers to Table 7.3.2.4.1-3 which defines uplink RB configuration and start RB location for each SCS, channel BW and NR band.				
NOTE 3: According to asymmetric channel bandwidths specified in clause 5.3.6.				
NOTE 4: For n70, in addition to default test configurations, additional configurations shall be used to verify reference sensitivity requirements with the UE TX-RX frequency separation of 295MHz (table 5.4.4-1):				
5 MHz CH BW with DL @ low range, UL @ mid range				
5 MHz CH BW with DL @ mid range, UL @ high range				
10 MHz CH BW with DL @ low range, UL @ high range				

For reference, the initial test condition for E-UTRA-CA (inter-band DL CA and UL CA) is listed below: (Table 7.3B.4.1-1 in TS 38.521-1 [2])

Initial Conditions									
Test Environment as specified in TS 36.508[7] subclause 4.1				NC, TL/VL, TL/VH, TH/VL, TH/VH					
Test Frequencies as specified in TS36.508 [7] subclause 4.3.1 for different CA bandwidth classes, and PCC and SCCs are mapped onto physical frequencies according to Table 7.1-2				B: Low range, High range C: Low range, High range (Note 4)					
Test CC Combination setting (N _{RB_agg}) as specified in subclause 5.4.2A.1 for the CA Configuration across bandwidth combination sets supported by the UE.				Lowest N _{RB_agg} , Highest N _{RB_agg} (Notes 3, 4)					
Test Parameters for CA Configurations									
CA Configuration / N _{RB_agg}		DL Allocation		UL Allocation					
PCC N _{RB}	SCCs N _{RB}	CC MOD	PCC & SCC RB allocation	CC MOD	N _{RB_alloc}	PCC & SCC RB allocations (L _{CRB} @ RB _{start})			
6	25	QPSK	6+25	QPSK	6	P_6@0	-	-	-
15	50	QPSK	15+50	QPSK	15	P_15@0	-	-	-
25	25	QPSK	25+25	QPSK	20	P_20@0	-	-	-

B.2 Test case structure

This approach which is described in this clause is relying on certain properties of the RAN4 CA requirements and applies to both NR CA and EN-DC.

1. For E-UTRA, fallbacks are skipped unless there is a documented exception in TS36.521-2. This may cause that a fallback is skipped even if no technical analysis has been made leading to insufficient testing of demanding CA configurations. For NR fallback can only be skipped if there has been a technical analysis performed in TR 38.905.
2. The RAN4 decision to only specify the affected (aggressor and victim) bands for an exception enables a different approach than in E-UTRA that in most cases makes fallback analysis redundant. This is not entirely true for requirements under clause 7.3A.5 and 7.3A.6 of TS38.101-1 [5] but it is assumed that the same approach can be used also in those cases as it greatly simplifies test cases.
3. Test cases can be split into *default* and *additional* test cases where default test cases only test where there is no exception (single carrier requirements apply), and additional only test the exceptions in TS 38.101-1 [5] clause 7.3A.
4. *Default* test cases need to be defined from 2 up to 5 CCs. Since they cover no exception, no fallback analysis is required, and the applicability rule should say that only highest CC number is required (similar to other Rx tests).
5. As the *default* test cases are not covering any CA exceptions, there is no need to configure UL CA in these test cases. Single UL configuration is sufficient to fulfil the test purpose.
6. *Additional* test cases only need to be defined for 2CC (and for intermodulation also 3CC) since this is sufficient for testing the exception. Adding more CCs is not considered to affect the test result and does not add any value.
7. *Additional* test cases only need to consider pure inter-band configurations since requirements are the same for intra-band contiguous or non-contiguous, and the essential aspect to test is the interference between bands.
8. It is important for sufficient test coverage to ensure that all band combinations with the highest number of CCs supported in the UE can always be tested.
9. The highest supported CC number may be with a band including an exception that can be avoided by setting a different test frequency (e.g. harmonic interference). In such cases, there is a need to include test points in the *default* test case so that this CA configuration can be tested without an exception (see example 1 below).
10. The highest supported CC number may be with a band including an exception that cannot be avoided by setting a different test frequency (e.g. cross band isolation). In this case the test requirements of the *default* test that are normally general for any CA config need to include this specific exception requirement. In addition, one fallback configuration needs to be tested to ensure test coverage of the single carrier requirement for the victim band that applies in this case. In order to simplify test applicability this fallback configuration will be specified inside the higher order test case (see example 2 below).
11. The highest supported CC number may be with a band including a limitation that is not present in the lower order fallback (e.g. UL is not possible in one of the bands). In this case, one fallback configuration needs to be tested to ensure test coverage of the single carrier requirement with UL active in the band. In order to simplify test applicability this fallback configuration will be specified inside the higher order test case.
12. To ensure that it has been checked that the CA configuration has been fully analysed with regard to test configuration and fallback testing, the CA configuration is listed in TR 38.905.

B.3 Test Environment

Reference sensitivity is one of the critical test cases for NR. Considering NR CA testing scenario is very similar to E-UTRA_CA test case, similar Test Environment shall be used for NR CA testing, i.e. NC, TL/VL, TL/VH, TH/VL, TH/VH.

B.4 Test Frequencies selection

In E-UTRA DL CA and UL CA reference sensitivity testing, Low range and High range are selected for intra-band CA testing. Mid range is selected for inter band E-UTRA CA testing.

Considering NR CA testing scenario is very similar to E-UTRA_CA test case, similar Test Frequencies should be used for NR CA default case.

It is proposed that Low and High Range are tested as default for intra-band and mid range for inter-band. For CA combinations containing intra-band configuration in an inter-band CA configuration it is proposed that low and high range are tested for intra-band CA and mid channel for inter-band without intra-band component. It is also proposed that the fallback configurations from intra-band configuration to single carrier component do not need to be tested even if the test frequency would differ (e.g. XA-YC -> XA-YA fallback does not need to be tested even if YC is tested with low/high frequency and YA would be tested with mid frequency).

For CA configurations affected by exceptions the test frequency cannot be freely chosen. One test frequency per exception requirement is sufficient to test the requirement, in addition to testing the case where the exception is avoided. This is indicated in table 2.3-2. Exceptions in TS 38.101-1 [5] clause 7.3A.5 (2UL intermodulation) are not specified since the test frequency and channel bandwidth is already specified in TS 38.101-1 [5].

Table B.4-1: Void

Proposal 2a: Low range and high range for intra band CA and mid range for inter-band CA shall be selected for NR in *default* test cases 7.3A.1 to 7.3A.4 in general, but final selection is band dependent. For CA combinations containing intra-band configuration in an inter-band CA configuration low and high range shall be selected for intra-band CA and mid channel for inter-band without intra-band component. The fallback configurations from intra-band configuration to single carrier component do not need to be tested even if the test frequency would differ.

Proposal 2b: In the *additional* test case, one test frequency per exception is selected.

B.5 Test Channel Bandwidth selection

The objective is how to verify the NR CA reference sensitivity. In intra-band E-UTRA CA reference sensitivity testing, two extreme bandwidth combinations corresponding to Lowest NRB_agg Highest NRB_agg are selected. Highest NRB_agg is selected for inter band E-UTRA CA testing.

As a simplification the highest aggregated channel bandwidth is proposed to test NR CA reference sensitivity.

Proposal 3: Highest aggregated channel bandwidth combinations shall be selected for NR CA reference sensitivity measurement. (Highest NRB_agg).

B.6 Modulation selections

QPSK is used for both uplink and downlink modulations for E-UTRA reference sensitivity measurement which is the same as for E-UTRA standalone reference sensitivity testing. There is no particular reason to deviate from current E-UTRA configurations of modulation scheme selection. NR modulations shall also follow what is selected in standalone NR testing.

B.7 Examples

Example 1 (highest CC number has an exception that can be avoided):

- UE supports CA_XA-YA-ZA-RA (4DL CA)
 - CA_X-Y has an exception if testing Low+Low freq
 - CA_X-Y has no exception if testing Mid+Mid freq
 - Other bands pairs have no exception

Applicable Test cases for the example:

7.3A.1 2CC non-exception/“default”

Skip test (no fallback analysis required)

7.3B 3CC non-exception/“default”

Skip test (no fallback analysis required)

7.3A.3 4CC non-exception/“default”

Test CA_XA-YA-ZA-RA in Mid+Mid freq in bands X and Y respectively avoiding the exception

7.3A.1_1 2CC exception/“additional”

Test CA_X-Y in Low+Low freq

Example 2 (highest CC number has an exception that cannot be avoided):

- UE supports CA_XA-YA-ZA-RA (4DL CA)
 - CA_X-Y has an exception always (e.g. cross band isolation) with band Y being the victim
 - Other bands pairs have no exception

Applicable Test cases for the example:

7.3A.1 2CC non-exception/“default”

Skip test (no fallback analysis required)

7.3A.2 3CC non-exception/“default”

Skip test (no fallback analysis required)

7.3A.3 4CC non-exception/“default”

Test CA_XA-YA-ZA-RA and add exception in test requirements

Add test points for 3CC fallback avoiding the exception CA_YA-ZA-RA

7.3A.1_1 2CC exception/“additional”

Test CA_X-Y

B.8 Current test completion status per CA configuration

The completion status per EN-DC configuration is documented in clause 4.3.3.1.

B.9 Reference Sensitivity checklist for CA

The purpose of this annex is to facilitate the reference sensitivity test point analysis in TR 38.905 for NR CA configurations.

B.9.1 Checklist for two bands

- 1) Check if the 2 DL band configuration has reference sensitivity exceptions in the tables listed below:
 - UL Harmonic Distortion (HD), as defined in TS 38.101-1 [5], Table 7.3A.4-1.
 - RX Harmonic Mixing (HM), as defined in TS 38.101-1 [5], Table 7.3A.4-4 to Table 7.3A.4-4a.
 - Intermodulation Distortion (IMD), as defined in TS 38.101-1 [5], Table 7.3A.5-1 to Table 7.3A.5-1a.
 - Cross Band Isolation (CBI), as defined in TS 38.101-1 [5], Table 7.3A.6-1 to Table 7.3A.6-1b.

2) If reference sensitivity exceptions are found for two bands above:

- Then add the result from the check to Table 4.1.3.1-2 for 2CC if they do not already exist.
- Add test frequencies for HD, HM and CBI to Table 4.1.3.1-6 if a new 2CC band pair was added to Table 4.1.3.1-2.

Add two band test points to test case in TS 38.521-1 [2] Table 7.3A.1_1.4.1-1.

B.9.2 Checklist for three bands

1) Check all three band fallback configurations in accordance to B.9.1.

2) Check for any 3DL/2UL IMD reference sensitivity exceptions in TS 38.101-1 [5], Table 7.3A.5-2 to Table 7.3A.5-2a.

3) If exceptions are found for three bands above:

- Then add the result from the check to Table 4.1.3.1-3: for three bands if they do not already exist.
- Add three band test points to test case in TS 38.521-1 [2] Table FFS.

B.9.3 Checklist for four bands and five bands

1) Check all two band and three band fall backs in accordance to B.9.1 and B.9.2 above.

No reference sensitivity exceptions exists for four bands and five bands in TS 38.101-1 [5].

Annex C: Principles for test point selection for FR2 NR CA reference sensitivity test cases

FFS

Annex D: Principles for test point selection for EN-DC reference sensitivity test cases

D.1 General

The purpose of this Annex is to describe the test point selection of NR and E-UTRA carriers for RX sensitivity testing within FR1. Considering the high number of EN-DC band combinations, the procedure has been developed to carefully reduce the number of test points. Since the objective of TS 38.521-3 [4] specification is providing conformance testing requirement for NR in the case of EN-DC scenarios, the number of E-UTRA test points can be reduced.

TS 38.521-3 [4] include exception test cases and non-exception test cases for inter-band EN-DC with FR1. The exceptional test cases must be tested as per configurations defined in TS 38.521-3 [4]. The procedure covers selection of both non-exceptional case and exception cases.

When no NR or E-UTRA exception or additional requirements exist, the E-UTRA anchor is configured such that it does not interfere with NR operation (based on TS 38.101-3 [7] clause 6.1 and 7.1). The EN-DC testing is performed in E-UTRA anchor-agnostic mode. NR is tested but in SA as per TS 38.521-1 [2].

General initial conditions to be used for NR RX sensitivity testing are:

Table D.1-1: Initial test condition for standalone NR RX sensitivity

Initial Conditions				
Test Environment as specified in TS 38.508-1 [5] subclause 4.1			Normal, TL/VL, TL/VH, TH/VL, TH/VH	
Test Frequencies as specified in TS 38.508-1 [5] subclause 4.3.1			Low range, Mid range, High range	
Test Channel Bandwidths as specified in TS 38.508-1 [5] subclause 4.3.1			Lowest, Mid, Highest	
Test SCS as specified in Table 5.3.5-1			Lowest supported SCS per test channel BW	
Test Parameters				
Test ID	Downlink Configuration		Uplink Configuration	
	Modulation	RB allocation	Modulation	RB allocation
1	CP-OFDM QPSK	Full RB (Note 1)	DFT-s-OFDM QPSK	REFERENCE SENSITIVITY (Note 2)

D.2 Requirements

D.2.1 Defined EN-DC configurations

Downlink EN-DC configurations in 38.101-3 V16.5.0 clause 5.5B are:

Currently defined downlink EN-DC configurations in 38.101-3 [7] V16.6.0 clause 5.5B are:

- Intra-band contiguous EN-DC configurations within a single band includes max 2 NR CCs and max 3 E-UTRA CC, but in total max 4 CCs.
- Intra-band non-contiguous EN-DC configurations within a single band does not include NR CA (max 1NR CC), only E-UTRA CA (max 3 E-UTRA CC)
- Inter-band EN-DC configurations include up to 6 bands and 8 CCs but for NR the maximum is:
 - 2 NR CCs in 1 band (nXC or nX(2A))
 - 4 NR CCs in 2 bands (nXA-nYA, nXA-nYC, nXA-nY(2A), nX(2A)-nY(2A))
- Combinations of intra-band contiguous EN-DC + inter-band E-UTRA/NR CA.
- Combinations of intra-band non-contiguous EN-DC + inter-band E-UTRA/NR CA.

Currently defined uplink EN-DC configurations in TS 38.101-3 [7] V16.6.0 clause 5.5B are:

- The UL configuration contains at least 1 E-UTRA CC and 1 NR CC, meaning 2 UL CC.
- 3 UL CC configurations are also defined only with intra-band contiguous CA on either E-UTRA or NR (DC_XA-nYC or DC_XC-nYA).

D.2.2 Definition of exception requirements

Before going into the test case details, the term “exception” needs to be clarified since it is different for EN-DC compared to SA. We can have the following situations:

1. EN-DC config without exception
 - a. Anchor agnostic, only need to be tested for UE not supporting SA
2. EN-DC config with exception when the exception applies
 - b. Need to be tested for all EN-DC UEs
3. EN-DC config with exception when the exception does not apply (single carrier requirement applies)
 - c. Need to be tested for some exception types. Which exception types that need to this test coverage is defined in clause D.2.10.3.
 - d. In some cases, it is not possible to avoid the exception.
 - e. Anchor agnostic approach shall not be followed. It is important that E-UTRA aggressor is active to test performance when the interferer falls outside of the victim carrier

D.2.3 Reference sensitivity

Intra-band

Unlike for standalone NR, there are exceptions for intra-band operation, currently limited to band 3 for non-contiguous operation and band 71 for contiguous operation.

The exceptions in band 3 is due to 2UL intermodulation interference making it similar to the corresponding inter-band intermodulation case. This scenario did not happen in standalone NR mode due to that there is no UL CA defined for CA_n3(2A).

It can therefore be treated in the same way as inter-band intermodulation and added in the “additional” test case.

The intra-band contiguous exceptions are not expected to be very common. Currently only band 71 is affected, which can be added in the “additional” test case.

Inter-band

For both SA and NSA there are 4 different types of interference related to inter-band operation that results in refsens exception if the frequency relation of the exception is fulfilled.

Table D.2.3-1: Exception types for inter-band (2 bands)

Exception types	Aggressor	Victim	Frequency relation
UL harmonic interference (HD)	Low band UL	High band DL	$a \cdot f_{UL_LB} = f_{DL_HB}$
Receiver Harmonic Mixing (HM)	Low band DL LO and High band UL	Low band DL	$b \cdot f_{DL_LB} + c \cdot f_{UL_HB} = f_{DL_LB}$
Intermodulation due to Dual uplink (IMD)	Low band UL and High band UL	DL	$a \cdot f_{UL_LB} + c \cdot f_{UL_HB} = f_{DL_LB}$ or $a \cdot f_{UL_LB} + c \cdot f_{UL_HB} = f_{DL_HB}$
Cross band isolation (CBI)	UL on other than victim band	DL	

The exception requirements for dual uplink intermodulation apply only for a specified test frequency setting per UL configuration in TS 38.101-3 [7].

More details on how the exception requirements were derived can be found in TR 37.863 (Rel-15), TR 37.716 (Rel-16) and TR 37.817 (Rel-17). These TRs can be used to identify all the applicable requirements for a certain EN-DC configuration which are otherwise spread out over multiple sections in TS 38.101-3 [7]. Additionally, the TRs specify exactly which aggressors that contribute to the exception for IMD which is not defined in the TS. Some terminology from the mentioned TRs are re-used here to calculate test frequency for avoiding the exceptions, namely:

BW_{INT} : Effective bandwidth of the interference falling into the victim band.

f_{INT} : Interference centre frequency. If $|f_{INT}| \geq (BW_{INT} + BW_{victim})/2$ the interference is not overlapping the victim carrier and exception requirements do not apply.

It has been agreed that for SA tests all the interference types except intermodulation can be tested with 1UL. Doing the same for NSA would simplify the test cases and would also mean that the main interferer (the aggressor) can be tested with higher power.

Most other Rx requirements than reference sensitivity in intra-band contiguous EN-DC configuration require a configuration with 2UL however, meaning the “default” test cases need to be tested with 2UL active in this scenario

There are combinations of intra-band contiguous/non-contiguous EN-DC + inter-band E-UTRA/NR CA which are listed in the inter-band EN-DC configuration tables of TS 38.101-3 [7]. These configurations do not add any exception requirements and are therefore proposed not to be tested unless they contain maximum number of NR CCs supported by the UE.

D.2.4 Rx requirements other than reference sensitivity

The requirements are in some cases referring back to standalone requirements in TS 36.101/ TS 38.101-1. In other cases, specific exceptions for EN-DC are defined in TS 38.101-3 [7]. This is summarized in Table 2.1.3-1.

Table D.2.4-1: Rx requirements

Clause	Title	Requirement		
		Intra-band contiguous	Intra-band non-contiguous	Inter-band
7.4B	Max input level	Exception with 2UL	Standalone	Standalone
7.5B	ACS	Exception with 2UL	Standalone	Standalone
7.6B.2	IBB	Exception with 2UL	Standalone	Standalone
7.6B.3	OBBB	Exception with 2UL	Standalone	Standalone (only 2 band needed)
7.6B.4	NBB	Exception with 2UL	Standalone	Standalone
7.7B	Spurious response	Exception with 2UL	Standalone	Standalone (only 2 band needed)
7.8B	Intermodulation	Exception with 2UL	Standalone	Standalone
7.9B	Rx spurious	Standalone	Standalone	Standalone

D.2.5 Test case structure and test coverage

As seen above, the EN-DC requirements are similar to the SA requirements from a structure point of view. Therefore, the same test case structure as for SA where test cases are separated into “default” and “additional” test cases can be considered for EN-DC which can greatly reduce complexity in TS 38.521-3[4] as well as reducing the need to complicated fallback test analysis. However, the additional complexity of EN-DC requirements means that a clear separation between exception (“additional”) test cases and “default” test cases is not as straightforward.

The following principles are suggested for EN-DC Rx test cases:

1. Let the 2CC test cases cover all reference sensitivity exceptions. Include test coverage of reference sensitivity when exception is avoided.
2. The 2CC test cases always need to be tested even for UE supporting more CCs since some of the exceptions are not covered in >2CC test cases.

3. Let the 3CC-5CC test cases cover mainly non-exception testing (anchor agnostic), including EN-DC not affected by exceptions and EN-DC affected by exceptions. 2UL 3 band intermodulation exceptions are tested in the 3CC test. Exceptions that 2CC fallback cannot cover are tested in 3CC test.
4. Highest number of NR CCs per band combination supported in the UE need to be tested. Anchor agnostic testing unless the EN-DC configuration has an exception requirement. Only 1 E-UTRA CC need to be tested for intra-band non-contiguous EN-DC and inter-band EN-DC. Maximum number of E-UTRA CCs need to be tested for intra-band contiguous EN-DC (1 band). This is further explained in clause 3.2.6.
5. Since requirements for 3UL and 2UL for the Rel-16 EN-DC configurations are the same there is no technical reason to test receiver requirements with 3UL configured. This may change in Rel-17 but will not have an impact on structure if we can add 3UL as new test points in existing tests.
6. The test configuration shall be with 1UL or 2UL active depending on the exception type as indicated in Table D.2.5-1.

Table D.2.5-1: UL configuration to test

Exception type	Intra-band contiguous EN-DC	Intra-band non-contiguous EN-DC	Inter-band EN-DC
Intra-band contiguous (band 71)	2UL ¹	-	-
Intra-band non-contiguous (band 3)	-	2UL ¹	-
UL harmonics, Rx mixing, cross band isolation	-	-	1UL
2UL Intermodulation	-	-	2UL ¹
EN-DC config w/o exception	2UL ²	1UL (anchor agnostic) ³	1UL (anchor agnostic)
NOTE 1: Exception requirements apply only with 2UL and apply only for one test frequency/BW setting. NOTE 2: Other than refsens requirements in this configuration mandate 2UL NOTE 3: Requirements in this configuration mandate 2UL (TS 38.101-3, 7.1) unless UE supports only single UL. However, there is no Rel-16 configuration w/o exception where 2UL is supported meaning only 1UL is configured in the test case			

7. Void
8. Other than reference sensitivity test cases should use the MSD=0 test points defined in reference sensitivity test case, or minimum achievable MSD. This is currently ensured by using anchor agnostic configuration for inter-band EN-DC, but other solutions are not precluded.
9. Test cases need to be defined from 2 up to 5 CCs for Rel-16. The number of CCs may increase in Rel-17. The reason for not needing more than 5CC is that it is sufficient to test max number of NR CCs as well as all defined exceptions.

D.2.6 EN-DC configurations to test

D.2.6.1 Lower order fallbacks

In E-UTRA specifications, the lower order CA fallback cases are important in the test point analysis. If requirements are the same in the lower order fallback, then the fallback can be skipped to save test time. The same principle can be applied for EN-DC, but there is a need to keep in mind that this is only for CA fallback and not EN-DC fallback. Additionally, lower order CA fallbacks can be split into E-UTRA CA fallbacks and NR CA fallbacks.

EN-DC fallback

EN-DC fallback does not need to be handled since this would mean falling back to pure E-UTRA operation, which is covered by TS 36.521-1 test cases.

E-UTRA CA fallback

Since it has been agreed to use anchor agnostic approach for EN-DC test cases (TS 38.521-3 [4], clause 4.6), it is enough to test with 1 E-UTRA CC unless more CCs are needed to test an exception requirement in TS 38.101-3 [7].

There are exception requirements in TS 38.101-3 [7] for intra-band-contiguous EN-DC (not reference sensitivity, but other Rx requirements as shown in clause D.2.3) meaning the maximum number of E-UTRA CCs need to be tested in this scenario.

E-UTRA CA fallback in intra-band contiguous EN-DC can result in change of EN-DC config from contiguous to non-contiguous (e.g. DC_(n)41DA -> DC_41C_n41A). This change means requirements are different, but since the non-contiguous requirement is same as the standalone requirement it does not need to be tested.

E-UTRA CA fallback in inter-band contiguous EN-DC can result in change of EN-DC config to intra-band contiguous (e.g. DC_1A-(n)41AA->DC_(n)41AA). This change means requirements are different, implying that both EN-DC config types may need to be tested. See clause D.2.6.2.

NR CA fallback

As shown in clause D.2.1, the maximum number of NR CCs for Rel-16 is 4, which only occurs in inter-band EN-DC (2 NR bands). The fallback to 2-3 NR CCs (2 bands) don't need to be tested since requirements are still the same. The fallback to single NR band with 1CC may need to be tested in the cases where the 2CC configuration had a reference sensitivity exception that is avoided in the higher order case.

Table D.2.6.1-1: EN-DC configurations requiring testing and max number of CCs

Clause number	Title	Requirement coverage	EN-DC configuration type		
			Intra-band cont EN-DC	Intra-band non-cont EN-DC	Inter-band EN-DC
7.3B.2.1	Reference sensitivity for Intra-band Contiguous EN-DC (2 CCs)	1. Band n71 exceptions 2. standalone NR requirements	Yes	-	-
7.3B.2.2	Reference sensitivity for Intra-band non-contiguous EN-DC (2 CCs)	1. Band n3 exceptions 2. standalone NR requirements	-	Yes	-
7.3B.2.3	Reference sensitivity for Inter-band EN-DC within FR1 (2 CCs)	1. UL harmonics, harmonic mixing, cross band isolation, 2UL intermodulation (2 band) 2. standalone NR requirements	-	-	Yes
7.3B.2.3_1.1	Reference sensitivity for EN-DC within FR1 (3 CCs)	1. standalone NR requirements, 2. 2UL intermodulation (3 band)	Yes (2E-UTRA+1NR, Note 1)	-	Yes (1E-UTRA+2NR, 2E-UTRA+1NR, Note 2)
7.3B.2.3_1.2	Reference sensitivity for EN-DC within FR1 (4 CCs)	standalone NR requirements	Yes (3E-UTRA+1NR, Note 1)	-	Yes (1E-UTRA+3NR, Note 4)
7.3B.2.3_1.2	Reference sensitivity for EN-DC within FR1 (5 CCs)	standalone NR requirements	-	-	Yes (1E-UTRA+4NR, Note 4)
NOTE 1: This is needed for other than refsens Rx test case that refers back to refsens test config table					
NOTE 2: For EN-DC configs affected by 2UL intermodulation, 2E-UTRA+1NR may need to be tested when E-UTRA CC1 is aggressor and E-UTRA CC2 is victim or when E-UTRA CC1 and CC2 are aggressors and NR CC is victim)					
NOTE 3: Void					
NOTE 4: Test of max number of NR CCs. Anchor agnostic testing.					

D.2.6.2 EN-DC configurations requiring testing and max number of CCs

There is an issue in only requiring highest CC number to be tested, since this rule can only be applied within one EN-DC configuration type. For example, if the UE supports 3E-UTRA+1NR intra-band contiguous EN-DC and 1E-UTRA+2NR inter-band EN-DC, both configurations need to be tested for sufficient test coverage of core requirements. Another problem is that highest CC number to test within Inter-band EN-DC is not easy to determine it shall include 1 or 2 E-UTRA CCs, not more.

D.2.6.3 Test coverage

As explained in clause D.2.1 only certain configurations are specified in TS 38.101-3 [7].

Additionally, some configurations may not need to be tested for reasons like:

- 1) To test an exception, it is sufficient to test with fewer CCs (“No test needed” in tables below)
- 2) No exception requirement exists (“N/A” in tables below)
- 3) No such configuration is defined in TS 38.101-3[7] clause 5.5B (“N/A” in tables below)

For configurations that need to be tested, anchor agnostic approach can be used for E-UTRA when testing a non-exception requirement. In other cases, the E-UTRA carrier need to be fully configured.

The different cases that may happen for 3CC and 4CC configurations, and the proposed test coverage are listed in the tables below where the following general rules have been applied:

- Harmonic exceptions are only tested in the 2CC test and need not be considered in >2CC test cases. 2CC test cases are always run.
- Any inter-band EN-DC configuration with more than 2 E-UTRA bands will not be tested.
- Any inter-band EN-DC configuration with more than 1 E-UTRA CC per band will not be tested.

Table D.2.6.3-1: 3CC test coverage

EN-DC type	E-UTRA CA	NR CA	Notation	Test coverage		
				Non-exception test points (NOTE 4)	Exception test points (NOTE 5)	
				No exception	UL harmonics, harmonic mixing, cross band isolation	2UL intermodulation

Intra-band contiguous EN-DC (1 band)	No	Yes	DC_(n)XAB	N/A	N/A	N/A
	Yes	No	DC_(n)XCA	Test needed due to other than refsens exception in intra-band EN-DC	N/A	N/A
Intra-band non-contiguous EN-DC (1 band)	Yes (cont)	No	DC_XC_nXA	No test needed. Only 2CC need to be tested	N/A	N/A
	Yes (non-cont)	No	DC_XA-XA_nXA DC_XA_(n)XAA	No test needed. Only 2CC need to be tested	N/A	N/A
	No	Yes (cont)	Note 1	N/A	N/A	N/A
	No	Yes (non-cont)	Note 1	N/A	N/A	N/A
Inter-band EN-DC	No	Yes (intra-cont)	DC_XA_nYC	Test needed (if max NR CC) – anchor agnostic	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested
	No	Yes (intra-non-cont)	DC_XA_nY(2A)	Test needed (if max NR CC) – anchor agnostic	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested
	No	Yes (inter)	DC_XA_nYA-nZA	Test needed (if max NR CC) – anchor agnostic	Test needed (if exception involving 2 NR bands). 2CC need to be tested	Test needed (if IMD 3 band). 2CC need to be tested
	Yes (intra-cont)	No	DC_XC_nYA	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested
	Yes (intra-non-cont)	No	DC_XA-XA_nYA	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested
	Yes (inter)	No	DC_XA-YA_nZA	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested	Test needed if IMD(3 band). 2CC need to be tested.
Inter-band + Intra-band contiguous EN-DC (2 band)	No	Yes	DC_(n)XAA-nYA	Test needed (if max NR CC) – anchor agnostic	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested
	Yes	No	DC_XA-(n)YAA	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested
Inter-band + Intra-band non-contiguous EN-DC (2 band)	No	Yes	DC_XA_nXA-nYA	Test needed (if max NR CC) – anchor agnostic	Test needed (if exception involving 2 NR bands). 2CC need to be tested	No test needed. Only 2CC need to be tested
	Yes	No	DC_XA-YA_nYA	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested

NOTE 1: No such config in TS 38.101-3 [7] V16.5.0

NOTE 2: CC BW class C is indicated in the table. The same rules apply to BW class B

NOTE 3: Different test coverage is indicated by colour coding in this table.

NOTE 4: Applicable to both EN-DC configurations not affected by any exception and EN-DC configurations affected by exceptions, corresponding to Table 7.3B.2.3_1.1.4.1-0 in TS 38.521-3.

NOTE 5: Only applicable to EN-DC configurations affected by exceptions, including UL harmonics, harmonic mixing, cross band isolation and 2UL intermodulation, corresponding to Table 7.3B.2.3_1.1.4.1-1 in TS 38.521-3.

Table D.2.6.3-2: 4CC test coverage

EN-DC type	E-UTRA CA	NR CA	Notation	Test coverage	
				Non-exception test points (NOTE 4)	Exception test points (NOTE 5)

				No exception	UL harmonics, harmonic mixing, cross band isolation	2UL intermodulation
Intra-band contiguous EN- DC (1 band)	No	Yes	NOTE 1	N/A	N/A	N/A
	Yes	No	DC_(n)XDA	Test needed due to other than refsens exception in intra- band EN-DC	N/A	N/A
Intra-band non- contiguous EN- DC (1 band)	Yes (cont)	No	DC_XD_nXA	No test needed. Only 2CC need to be tested	N/A	N/A
	Yes (non- cont)	No	NOTE 1	N/A	N/A	N/A
	No	Yes (cont)	NOTE 1	N/A	N/A	N/A
	No	Yes (non- cont)	NOTE 1	N/A	N/A	N/A
Inter-band EN- DC	No	Yes (cont)	NOTE 1	N/A	N/A	N/A
	No	Yes	DC_XA_nY(2A)-nZA	Test needed (if max NR CC) – anchor agnostic	No test needed. Only 2CC need to be tested	No test needed. 2CC need to be tested. 3CC need to be tested if IMD(3 band)
	No	Yes	DC_XA_nYA-nZC	Test needed (if max NR CC) – anchor agnostic	No test needed. Only 2CC need to be tested	No test needed. 2CC need to be tested. 3CC need to be tested if IMD(3 band)
	Yes (all types)	No	DC_XD_nYA, DC_XA-YC_nZA, DC_XA-XA-YA_nZA, DC_XA-YA-ZA_nRA	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested	No test needed. 2CC need to be tested. 3CC need to be tested if IMD(3 band)
	Yes (all types)	Yes (cont)	DC_XC_nYC, DC_XA-XA_nYC, DC_XA-YA_nYC	No test needed. 3CC need to be tested if max NR CC	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested
		Yes (non- cont)	DC_XC_nY(2A), DC_XA-YA_nY(2A)	No test needed. 3CC need to be tested if max NR CC	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested
		Yes (inter)	DC_XC_nYA-nZA, DC_XA-XA_nYA- nZA, DC_XA-YA_nZA- nRA	No test needed. 3CC need to be tested if max NR CC	No test needed. Only 2CC need to be tested	No test needed. 2CC need to be tested. 3CC need to be tested if IMD(3 band)
Inter-band + Intra-band contiguous EN- DC (2-3 band)	No	Yes	NOTE 1	N/A	N/A	N/A
	Yes	No	DC_XA-YA_(n)ZAA, DC_XC_(n)YAA	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested
	Yes	Yes	DC_(n)XCA-nYA	No test needed. 3CC need to be tested if max NR CC	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested
Inter-band + Intra-band non- contiguous EN- DC (2-3 band)	No	Yes	NOTE 1	N/A	N/A	N/A
	Yes	No	DC_XA-YA-ZA_nZA	No test needed. Only 2CC need to be tested	No test needed. Only 2CC need to be tested	No test needed. 2CC need to be tested. 3CC need to be tested if IMD(3 band)
	Yes	Yes	DC_XA-YA_nYA-nZA	No test needed. 3CC need to be tested if max NR CC	No test needed. Only 2CC need to be tested	No test needed. 2CC need to be tested. 3CC need to be tested if IMD(3 band)

NOTE 1: No such config in TS 38.101-3 [7] V16.5.0

NOTE 2: 2CC BW class C is indicated in the table. The same rules apply to BW class B

NOTE 3: Different test coverage is indicated by colour coding in this table.

NOTE 4: Applicable to both EN-DC configurations not affected by any exception and EN-DC configurations affected by exceptions, corresponding to Table 7.3B.2.3_1.2.4.1-1.

NOTE 5: Only applicable to EN-DC configurations affected by exceptions, including UL harmonics, harmonic mixing, cross band isolation and 2UL intermodulation.

D.2.7 Test Environment

The test environment for FR1 EN-DC RX sensitivity measurement is Normal, TL/VL, TL/VH, TH/VL, TH/VH (same as for NR CA).

D.2.8 Test Frequencies selections for EN-DC

In E-UTRA DL CA and UL CA reference sensitivity testing, Low range and High range are selected for intra-band CA testing. Mid-range is selected for inter band E-UTRA CA testing.

In standalone NR CA reference sensitivity testing, Low and High Range are tested as default for intra-band and Mid-range for inter-band. For CA combinations containing intra-band configuration in an inter-band CA configuration, low and high range are tested for intra-band CA and mid channel for inter-band without intra-band component.

The same principle shall apply for EN-DC testing.

For EN-DC configurations affected by exceptions, the test frequency cannot be freely chosen. One test frequency per exception requirement is sufficient to test the requirement. This is indicated in Table D.2.8-1 following the frequency relation formulas defined in clause D.2.3. Exceptions in TS 38.101-3 clause 7.3A.5 (2UL intermodulation) are not specified since the test frequency and channel bandwidth is already specified in TS 38.101-1.

Table D.2.8-1: Test frequency selection per band pair for exceptions avoidable by test frequency setting (UL harmonics, Rx mixing, cross band isolation)

Band set (Note 2)	Frequency	Channel BW [MHz]	Exception type	Comments
1A / n3A	Mid/Mid	Highest/Highest	-	Non-Exception.
	Low/High	20 / 40	Cross band isolation	Exception in TS 38.101-3 table 7.3B.2.3.4-1
2A/71A	DL1980 MHz/ UL665.5 MHz	20/5	UL Harmonic Interference	Exception Note 11 of TS 38.101-3 table 7.3B.2.3.1-1
	DL1980 MHz/ UL673 MHz	20/10	UL Harmonic Interference	Exception Note 12 of TS 38.101-3 table 7.3B.2.3.1-1
	UL1881 MHz/UL Low	20/20	Receiver Harmonic Mixing	Exception Note 4 in TS 38.101-3 Table 7.3B.2.3.2-1
2A/n77A	UL 1860 MHz / DL 3720 MHz	20/100	UL Harmonic Interference	Exception Note 2, 13 of TS 38.101-3 table 7.3B.2.3.1-1
	UL 1860 MHz / DL 3700 MHz	20/20	UL Harmonic Interference	Exception Note 3 of TS 38.101-3 table 7.3B.2.3.1-1
	DL Mid (1960) / UL 3920	20/100	Receiver harmonic mixing HM2	Receiver Harmonic Mixing Exception in TS38.101-3 Table 7.3B.2.3.2-1
	UL 1860 MHz / DL 3400 MHz			HD avoid
	DL 1950 / UL 4000	20/100		HM avoid
2A/78A	DL 3740 MHz/ UL 1870 MHz	Highest (20 MHz) / Highest (100 MHz)	UL Harmonic Interference HD2	Exception Note 2, 13 of TS38.101-3 table 7.3B.2.3.1-1
	DL 3740 MHz/ UL 1885 MHz	20 MHz) / Highest (20 MHz)	UL Harmonic Interference HD2	Exception Note 3 of TS38.101-3 table 7.3B.2.3.1-1
3A / n1A	Mid/Mid	Highest/Highest	-	Non-Exception.
	High/Low	20 / 20	Cross band isolation	Exception in TS 38.101-3 table 7.3B.2.3.4-1
3A / n41A				CMCC CR R5-205929
3A / n78A	Mid/High	Highest/Highest	-	Non-Exception.
	Mid/3495	Highest/Highest	UL Harmonic Interference	Exception Note 2 of TS 38.101-3 table 7.3B.2.3.1-1
	Mid/3525	20/20	UL Harmonic Interference	Exception Note 3 of TS 38.101-3 table 7.3B.2.3.1-1
	Mid /3685	20/20	Receiver Harmonic Mixing	Receiver Harmonic Mixing Exception in TS 38.101-3 Table 7.3B.2.3.2-1
5A/n77A	UL 829 MHz / DL 3316 MHz	10/100	UL Harmonic Interference	Exception Note 6, 7, 17 of TS 38.101-3 table 7.3B.2.3.1-1
	UL 829 MHz / DL 4145 MHz	10/100	UL Harmonic Interference	Exception Note 4, 5, 17 of TS 38.101-3 table 7.3B.2.3.1-1
	UL 840 MHz/DL 3600 MHz	10/100		HD avoid
7A / n78A	High/Low	20/100	Cross band isolation	Exception in TS 38.101-3 table 7.3B.2.3.4-1
8A / n77A	Mid (UL 897.5 MHz) / 3590	Highest (10 MHz) / Highest (100 MHz)	UL Harmonic Interference HD4	Exception Note 7 of TS38.101-3 table 7.3B.2.3.1-1
	Mid (UL 897.5 MHz) / 3520	Highest (10 MHz) / Highest (100 MHz)		Non-Exception. Not overlapping interference since $BW_{INT}=40$ MHz, $F_{INT} = (40+100)/2 = 70$
11A / n79A	Mid (DL 1485.9 MHz) / 4457.7	Highest (10 MHz) / Highest (100 MHz)	Receiver Harmonic Mixing HM3	Receiver Harmonic Mixing Exception in TS38.101-3 Table 7.3B.2.3.2-1
	Mid (DL 1485.9 MHz) / 4512.7 MHz	Highest (10 MHz) / Highest (100 MHz)		Non-Exception. Not overlapping interference since $BW_{INT}=100$ MHz, $F_{INT} = (100+10)/2 = 55$
13A/n77A	UL 782 MHz / DL 3910 MHz	10/100	UL Harmonic Interference	Exception Note 4, 5 of TS 38.101-3 table 7.3B.2.3.1-1
	DL Mid (751) / UL 3755	10/100	Receiver harmonic mixing	Receiver Harmonic Mixing Exception in TS38.101-3 Table 7.3B.2.3.2-1
	UL 782 MHz /DL 3600 MHz	10/100		HD avoid
	DL 751 / UL 3950	10/100		HM avoid

19A / n79A	DL 884 MHz / Low (4420.02 MHz)	10 MHz / 40 MHz	Receiver Harmonic Mixing HM3	Receiver Harmonic Mixing Exception in TS38.101-3 Table 7.3B.2.3.2-1
	DL 884 MHz / Low (4445.02 MHz)	10 MHz / 40 MHz		Non-Exception. Not overlapping interference since $BW_{INT}=40$ MHz, $F_{INT} = (40+10)/2 = 25$
20A / n78A	Mid/Mid	Highest/Highest	-	Non-Exception.
	Mid/3388	Highest/Highest	UL Harmonic Interference	Exception Note 7 of TS 38.101-3 table 7.3B.2.3.1-1
26A / n41A	High (UL 841.5 MHz) / 2524.5 MHz	Highest (15 MHz) / 50 MHz	UL Harmonic Interference HD3	Exception Note 9 of TS38.101-3 table 7.3B.2.3.1-1
	High (UL 841.5 MHz) / 2572 MHz	Highest (15 MHz) / 50 MHz		Non-Exception. Not overlapping interference since $BW_{INT}=45$ MHz, $F_{INT} = (45+50)/2 = 47.5$
26A / n77A 26A / n78A	High (UL 841.5 MHz) / 3366 MHz	Highest (15 MHz) / Highest (100 MHz)	UL Harmonic Interference HD4	Exception Note 7 of TS38.101-3 table 7.3B.2.3.1-1
	High (UL 841.5 MHz) / 3446 MHz	Highest (15 MHz) / Highest (100 MHz)		Non-Exception. Not overlapping interference since $BW_{INT}=60$ MHz, $F_{INT} = (60+100)/2 = 80$
26A / n79A	High (DL 886.5 MHz) / 4432.5 MHz	Highest (15 MHz) / 60 MHz	Receiver Harmonic Mixing HM5	Receiver Harmonic Mixing Exception in TS38.101-3 Table 7.3B.2.3.2-1
	High (DL 886.5 MHz) / 4470.5 MHz	Highest (15 MHz) / 60 MHz		Non-Exception. Not overlapping interference since $BW_{INT}=60$ MHz, $F_{INT} = (60+15)/2 = 37.5$
40A / n78A	Low/Mid	Highest/Highest	-	Non-Exception.
	Mid/3525	20/20	Receiver Harmonic Mixing	Receiver Harmonic Mixing Exception Note 8 in TS38.101-3 Table 7.3B.2.3.2-1
41A / n77A 41A / n78A	Low (DL 2593 MHz) / 3750 MHz	Highest (20 MHz) / Highest (100 MHz)	Receiver Harmonic Mixing HM4	Receiver Harmonic Mixing Exception in TS38.101-3 Table 7.3B.2.3.2-1
	Mid (DL 2593 MHz) / 3974.5 MHz	Highest (20 MHz) / Highest (100 MHz)	Cross band isolation	Not overlapping HM interference since $BW_{INT}=240$ MHz, $F_{INT} = (240+100)/2 = 170$
	Mid / Mid	Highest / Highest	-	Non-Exception only possible with 1UL in band 41
48A/n66A	DL 3557.6 MHz/ UL 1778.8 MHz	Highest (20 MHz) / Highest (400 MHz)	UL Harmonic Interference HD2	Exception Note 2, 13 of TS38.101-3 table 7.3B.2.3.1-1
	DL 3581.0 MHz/ UL 1777.5 MHz	Highest (20 MHz) / Highest (400 MHz)	UL Harmonic Interference HD2	Exception Note 3 of TS38.101-3 table 7.3B.2.3.1-1
66A/n77A	UL 1720 MHz / DL 3440 MHz	20/100	UL Harmonic Interference	Exception Note 2, 13 of TS38.101-3 table 7.3B.2.3.1-1
	UL 1720 MHz / DL 3420 MHz	20/20	UL Harmonic Interference	Exception Note 3 of TS38.101-3 table 7.3B.2.3.1-1
	UL 1720 MHz / DL 3600 MHz	20/100		HD avoid
66A/n78A	DL 3510 MHz/ UL 1755 MHz	Highest (20 MHz) / Highest (100 MHz)	UL Harmonic Interference HD2	Exception Note 2, 13 of TS38.101-3 table 7.3B.2.3.1-1
	DL 3480 MHz/ UL 1755 MHz	Highest (20 MHz) / Highest (100 MHz)	UL Harmonic Interference HD2	Exception Note 3 of TS38.101-3 table 7.3B.2.3.1-1
NOTE 1: This selection is used in test case 7.3B.2.3 unless otherwise stated				
NOTE 2: Aggressor band in bold				

For EN-DC configurations affected by IMD exceptions where the exception is avoided, the test frequency and bandwidth are FFS.

D.2.9 Test EN-DC channel bandwidth

D.2.9.1 Test point selection EN-DC configuration without exception

Follow similar arguments for frequency selection, for regular inter-band EN-DC and intra-band non-contiguous testing, the NR channel bandwidths shall follow what is specified in SA scenario. Since the objective is to test NR performance, it is sufficient to select 5 MHz channel bandwidth for E-UTRA carrier, which is common for all E-UTRA bands.

For intra-band contiguous EN-DC testing, the highest bandwidth is selected for E-UTRA carrier and NR carrier, respectively.

D.2.9.2 Test point selection EN-DC configuration with exception

For inter-band EN-DC configuration with exception requirement due to UL harmonics, Rx mixing and cross band isolation, the highest channel bandwidth shall be tested for E-UTRA and NR carrier.

For inter-band EN-DC configuration with exception requirement due to 2UL intermodulation, the test channel bandwidth selection for both NR and E-UTRA are EN-DC combo dependent. There are fixed channel bandwidth pairs required for these exceptional test scenarios.

For intra-band EN-DC configuration with exception requirement, the test channel bandwidth selection for both NR and E-UTRA are EN-DC combo dependent. There are fixed channel bandwidth pairs required for these exceptional test scenarios.

Only 5 MHz channel bandwidth shall be employed by E-UTRA band, Lowest, Mid, Highest channel bandwidth shall be selected for NR carrier for EN-DC non- exceptional testing.

D.2.10 RB allocation and RB location selections

D.2.10.1 Test point selection EN-DC configuration without exception

Following the E-UTRA anchor-agnostic proposed in R5-185916 [6], E-UTRA operation does not interfere with NR connection, 0 RB were proposed for both UL and DL channels for non-exceptional test scenarios.

There is no reason to deviate from current NR configurations for RB allocation selection employed in standalone testing.

D.2.10.2 Test point selection EN-DC configuration with exception when exception applies

For EN-DC inter-band and intra-band EN-DC exceptional test scenarios, the RB allocation for both NR and E-UTRA are selected as specified in TS 38.101-3 [7] for the EN-DC band combination.

Based on the E-UTRA anchor-agnostic approach, 0 RB shall be used for both UL and DL channels for non-exceptional test scenarios. RB allocation for NR carrier in inter-band EN-DC non- exceptional testing shall follow what is selected for standalone testing.

D.2.10.3 Test point selection EN-DC configuration with exception when exception does not apply

According to the test principle outlined in clause D.2.5, there is a need to verify the UE performance when the exception is avoided and MSD=0 dB applies. Detailed background can be found in [9].

The calculation of test frequency for avoiding exceptions is presented in clause 2.5. The UL configuration also need to be determined and may be with one or two simultaneous UL CCs depending on the scenario.

For HD and HM exceptions when the victim band is TDD there is no need from an interference point of view to have UL active on the victim band, meaning this can be verified with 1UL. The same can apply for EN-DC configurations

where single switched Tx is allowed. In the case of FDD victim band when 2UL is mandatory, both UL CCs should be active since this represents the worst case.

For CBI exceptions the requirements are defined in two different ways depending on the EN-DC configuration:

1. Exception applies for any frequency separation as long as aggressor UL is active. In this case, the only way to avoid the exception is to not have UL active on the aggressor band. The test point then becomes very similar to the standalone test and then does not need to be tested for a SA and NSA capable UE. Therefore, CBI exception avoiding could not be tested for this kind of combinations.
2. Exception applies only if separation is small. Just like for HD and HM exceptions, the exception can be avoided by configuring a larger separation with aggressor signal still active.

For 2-band IMD exceptions, the exception is avoided by changing the frequency of one of the CCs such that the intermodulation does not overlap with the victim CC anymore. In the case of multiple IMD affecting the same victim band, only the worst case IMD may be tested. However, in TS 38.101-3[7], there is no general criteria in which REFSENS can be fulfilled with MSD=0 for the EN-DC combinations which have MSD exceptions due to IMD interference (2 UL active). The 2-band IMD exception avoiding testing is still FFS in TS 38.521-3[4].

For 3-band IMD exceptions there are a separate set of IMD depending on the UL configuration (selecting 2UL among 3 bands gives two cases). Within a UL configuration, the same test point selection as for 2-band IMD can be used.

D.2.11 Modulation scheme selections

The modulation scheme for both non-exceptional and exceptional EN-DC intra-band and inter-band test scenarios are selected as:

- For E-UTRA: QPSK (same as used for E-UTRA reference sensitivity testing in TS 36-521-1 [9])
- For NR: Use same modulation scheme as used for NR standalone testing.

D.2.12 Current test completion status per EN-DC configuration

The completion status per EN-DC configuration is documented in clause 4.3.3.1.

Annex B: Change history

Change history							
Date	Meeting	TDoc	CR	R ev	Cat	Subject/Comment	New version
2017-09	RAN5#76	R5-174704	-	-	-	Draft skeleton TR 38.905	0.0.1
2018-04	RAN5#2-5G-NR Adhoc	R5-181954	-	-	-	Agreed Text Proposal in RAN5#2-5G-NR Adhoc: R5-181889, " TP to update TR 38.905 with information on test point analysis " Agreed Test Point Analysis in RAN5#78: R5-180885, "Discussion on test point selection for NR Occupied Bandwidth in FR1" R5-180886, "Discussion on test point selection for NR SEM in FR1" R5-180887, "Discussion on test point selection for NR ACLR in FR1" R5-181524, "Discussion on test point selection for Absolute Power Tolerance in FR1" R5-181525, "Discussion on test point selection for Aggregate Power Tolerance in FR1" Agreed Test Point Analysis in RAN5#2-5G-NR Adhoc: R5-182019, "Discussion of NR FR1 Test Point for TX Spurious Emission test cases " R5-182024, "Discussion on test point selection for NR Frequency Error in FR1" R5-181830, "Discussion on test point selection for Maximum Output Power in FR1" R5-181831, "Discussion on test point selection for Minimum Output Power in FR1" R5-181832, "Discussion on test point selection for General ON/OFF Time Mask in FR1" R5-181879, "Discussion on test point selection for NR In-Band in FR1" R5-181880, "Discussion on test point selection for NR ACS in FR1" R5-182025, "Discussion on test point selection for NR Frequency Error in FR1" R5-181905, "Discussion on test point selection for NR Occupied Bandwidth in FR2" R5-182030, "Discussion on test point selection for NR ACLR in FR2" R5-182042, "Discussion on test point selection for NR In-Band blocking in FR2" R5-182044, "Discussion on test point selection for NR ACS in FR2"	0.1.0
2018-05	RAN5#79	R5-183078	-	-	-	Document title corrected. Agreed Text Proposal in RAN WG5#79: R5-183963, "Test Point analysis for FR1 RefSens test case"	0.2.0
2018-08	RAN5#80	R5-185134	-	-	-	R5-184923, "Test Point analysis for FR2 RefSense test case" R5-184961, "TP for updating TR 38.905 with FR2 Frequency Error test point analysis" R5-185307, "TP for updating TR38.905 with FR1 AMPR test point analyses with NS_35" R5-185309, "Test Point analysis for FR1 Configured Output Power for SUL" R5-185311, "TP for updating TR 38.905 with FR1 Carrier Leakage test point analysis" R5-185314, "TP for updating TR 38.905 with FR1 EVM equalizer spectrum flatness test point analysis" R5-185316, "TP for updating TR 38.905 with FR1 Frequency Error test point analysis" R5-185412, "TP for updating TR 38.905 with EVM test point analysis" R5-185491, "Test Point analysis for FR2 TxSpurious test case" R5-185215, "TP for updating TR 38.905 with FR2 SEM test point analysis" R5-185334, "Discussion of LTE Test point selection for EN-DC with FR1 Tx Spurious emission Test" R5-185301, "Discussion on test point selection for NR Out-of-band in FR1" R5-185423, "Discussion on Uplink configuration for NR Transmit Intermodulation in FR1" R5-185216, "TP for updating TR38.905 with UE AMPR for NS_04 Intra-band contiguous EN-DC" R5-185319, "TP for updating TR 38.905 with FR1 In-band Emissions test point analysis"	1.0.0
2018-09	RAN#81	-	-	-	-	raised to v15.0.0 with editorial changes only	15.0.0
2018-12	RAN#82	R5-186454	0016	-	F	TP analysis for test case 6.5.2.4.2	15.1.0
2018-12	RAN#82	R5-186455	0017	-	F	TP analysis for EN-DC test case 6.2B.2.3	15.1.0

2018-12	RAN#82	R5-186609	0018	-	F	TP_analysis for TX spurious emission UE co-existence for intra-band contiguous EN-DC with FR1	15.1.0
2018-12	RAN#82	R5-186610	0019	-	F	TP analysis for Reference sensitivity for Intra-band Contiguous EN-DC with FR1	15.1.0
2018-12	RAN#82	R5-186611	0020	-	F	TP analysis for Reference sensitivity for Inter-band EN-DC with FR1	15.1.0
2018-12	RAN#82	R5-186674	0021	-	F	Test point analysis for AMPR Intra-band contiguous EN-DC in FR1 for NS_35	15.1.0
2018-12	RAN#82	R5-186710	0022	-	F	TP analysis for test case 6.2B.2.4, UE Maximum Output Power reduction for Inter-Band EN-DC including FR2	15.1.0
2018-12	RAN#82	R5-186791	0028	-	F	TP analysis OBW intraband contiguous EN-DC	15.1.0
2018-12	RAN#82	R5-186792	0029	-	F	TP analysis SEM intraband contiguous EN-DC	15.1.0
2018-12	RAN#82	R5-187035	0031	-	F	Update test points analysis for multiple FR1 test cases	15.1.0
2018-12	RAN#82	R5-187396	0037	-	F	Update of TR 38.905 with SA FR1 A-MPR test point analyses, NS_04	15.1.0
2018-12	RAN#82	R5-188240	0039	1	F	Update of TR 38.905 with EN-DC A-MPR test point analyses, NS_04	15.1.0
2018-12	RAN#82	R5-188227	0041	1	F	Test Point analysis for FR2 Maximum Output Power	15.1.0
2018-12	RAN#82	R5-187489	0042	-	F	TP analysis for FR1 test case 6.3.4.3, relative power tolerance	15.1.0
2018-12	RAN#82	R5-187582	0043	-	F	Discussion on test point selection for EVM in FR2	15.1.0
2018-12	RAN#82	R5-187583	0044	-	F	Discussion on test point selection for Carrier Leakage in FR2	15.1.0
2018-12	RAN#82	R5-187584	0045	-	F	Update of test point selection for EVM equalizer spectrum flatness in FR1	15.1.0
2018-12	RAN#82	R5-187587	0046	-	F	Discussion on test point selection for In-band Emissions in FR2	15.1.0
2018-12	RAN#82	R5-187589	0047	-	F	Discussion on test point selection for EVM equalizer spectrum flatness in FR2	15.1.0
2018-12	RAN#82	R5-187593	0048	-	F	Discussion on test point selection for EVM equalizer spectrum flatness for Pi/2 BPSK in FR1	15.1.0
2018-12	RAN#82	R5-187806	0023	1	F	Test Point analysis for FR1 7.4 Maximum input level	15.1.0
2018-12	RAN#82	R5-187808	0035	1	F	TP analysis for receiver spurious emission tests for FR1 SA	15.1.0
2018-12	RAN#82	R5-187809	0036	1	F	TP analysis for wideband intermodulation tests for FR1 SA	15.1.0
2018-12	RAN#82	R5-187817	0033	1	F	TP analysis for receiver spurious emission tests for FR1 inter-band EN-DC	15.1.0
2018-12	RAN#82	R5-187818	0034	1	F	TP analysis for wideband intermodulation tests for FR1 inter-band EN-DC	15.1.0
2018-12	RAN#82	R5-187836	0025	1	F	Test Point analysis for FR2 7.4 Maximum input level	15.1.0
2018-12	RAN#82	R5-187907	0024	1	F	Test Point analysis for FR1 MPR test case	15.1.0
2019-03	RAN#83	R5-191257	0077	-	F	Test Point analysis for TC 6.3.3.4 PRACH time mask in FR1	15.2.0
2019-03	RAN#83	R5-191260	0078	-	F	Test Point analysis for NR Narrow band in FR1	15.2.0
2019-03	RAN#83	R5-191261	0079	-	F	Test Point analysis for NR spurious response in FR1	15.2.0
2019-03	RAN#83	R5-191337	0081	-	F	Adding test case 6.2B.2.1 to 38.905	15.2.0
2019-03	RAN#83	R5-191678	0086	-	F	Addition of TP analysis of FR2 6.3.1 Minimum output power	15.2.0
2019-03	RAN#83	R5-191811	0087	-	F	Test Point analysis update for FR2 TxSpurious test case	15.2.0
2019-03	RAN#83	R5-191855	0091	-	F	TP_analysis_38.905_6.5.3.1_TX_SpurEmission	15.2.0
2019-03	RAN#83	R5-192002	0104	-	F	Adding test case 7.4B.1 to 38.905	15.2.0
2019-03	RAN#83	R5-192003	0105	-	F	Adding test case 7.4B.2 to 38.905	15.2.0
2019-03	RAN#83	R5-192007	0106	-	F	Adding test case 6.2B.1.1 to 38.905	15.2.0
2019-03	RAN#83	R5-192008	0107	-	F	Adding test case 6.2B.1.2 to 38.905	15.2.0
2019-03	RAN#83	R5-192009	0108	-	F	Adding test case 6.2B.1.3 to 38.905	15.2.0
2019-03	RAN#83	R5-192239	0116	-	F	TP analysis of FR1 time alignment error for UL MIMO	15.2.0
2019-03	RAN#83	R5-192401	0085	1	F	Addition of TP analysis of FR1 6.2.4 Configured transmitted power	15.2.0
2019-03	RAN#83	R5-192404	0099	1	F	TP analysis for FR1 6.5A.2.4.1.1 NR ACLR for CA (2UL CA)	15.2.0
2019-03	RAN#83	R5-192405	0100	1	F	TP analysis for FR1 6.5A.2.4.2.1 UTRA ACLR for CA (2UL CA)	15.2.0
2019-03	RAN#83	R5-192406	0103	1	F	TP analysis for FR1 6.5A.4.1 Transmit intermodulation for CA (2UL CA)	15.2.0
2019-03	RAN#83	R5-192410	0110	1	F	Update of TP analysis of FR1 6.3.1 Minimum Output Power	15.2.0
2019-03	RAN#83	R5-192444	0113	1	F	Addition of TP analysis for EN-DC 6.2B.4.1.3 Configured transmitted power inter-band within FR1	15.2.0
2019-03	RAN#83	R5-192449	0080	1	F	Adding FR2 test case 6.3.4.3 to 38.905	15.2.0
2019-03	RAN#83	R5-192546	0082	1	F	Test Point analysis for FR1 6.3.3.6 SRS time mask	15.2.0
2019-03	RAN#83	R5-192568	0095	1	F	TP analysis for FR1 6.4A.2.1.1 Error Vector Magnitude for CA (2UL CA)	15.2.0
2019-03	RAN#83	R5-192569	0094	1	F	TP analysis for FR1 6.4A.1.1 Frequency error for CA (2UL CA)	15.2.0
2019-03	RAN#83	R5-192571	0096	1	F	TP analysis for FR1 6.4A.2.2.1 Carrier leakage for CA (2UL CA)	15.2.0
2019-03	RAN#83	R5-192572	0097	1	F	TP analysis for FR1 6.4A.2.3.1 In-band emissions for CA (2UL CA)	15.2.0
2019-03	RAN#83	R5-192573	0098	1	F	TP analysis for FR1 6.5A.2.2.1 Spectrum emission mask for CA (2UL CA)	15.2.0
2019-03	RAN#83	R5-192574	0101	1	F	TP analysis for FR1 6.5A.3.1.1 General spurious emissions for CA (2UL CA)	15.2.0
2019-03	RAN#83	R5-192575	0102	1	F	TP analysis for FR1 6.5A.3.2.1 Spurious emissions for UE co-existence for CA (2UL CA)	15.2.0
2019-03	RAN#83	R5-192582	0109	1	F	Add Tp analysis statements for MIMO tests	15.2.0
2019-03	RAN#83	R5-192599	0084	1	F	Update of TP analysis of FR1 6.2.1 MOP	15.2.0
2019-03	RAN#83	R5-192624	0115	1	F	TP_analysis_38.905_6.5B.3_TX_SpurEmission	15.2.0

2019-03	RAN#83	R5-192647	0092	1	F	Addition of Test Point analysis of FR2 6.3.4.4 Aggregate power tolerance	15.2.0
2019-03	RAN#83	R5-192684	0073	1	F	TP analysis for FR1 Rx 7.9A.1 Spurious Emission for 2DL CA	15.2.0
2019-03	RAN#83	R5-192691	0111	1	F	Additional of TP analysis for EN-DC 6.2B.4.1.1 Configured transmitted power Intra-band contiguous	15.2.0
2019-03	RAN#83	R5-192692	0112	1	F	Addition of TP analysis for EN-DC 6.2B.4.1.2 Configured transmitted power Intra-band non-contiguous	15.2.0
2019-03	RAN#83	R5-192846	0114	2	F	Introduction of new section for TP analysis of Tx spurious	15.2.0
2019-06	RAN#84	R5-193543	0137	-	F	Additional TT analysis for 38.521-3 MPR intra-band contiguous	15.3.0
2019-06	RAN#84	R5-193808	0147	-	F	Addition of TP analysis for power control for UL-MIMO	15.3.0
2019-06	RAN#84	R5-193916	0148	-	F	Update of TP analysis of 6.2D.3 A-MPR for UL-MIMO	15.3.0
2019-06	RAN#84	R5-193919	0149	-	F	Add SA FR1 RF 6.5D.2.4.2 to 38.905	15.3.0
2019-06	RAN#84	R5-194010	0151	-	F	Test Point analysis update for FR2 TxSpurious UE coexistence test case	15.3.0
2019-06	RAN#84	R5-194168	0152	-	F	Updating Annex A; Derivation documents	15.3.0
2019-06	RAN#84	R5-194169	0153	-	F	Update of test points analysis for NS_35 A-MPR FR1 test case	15.3.0
2019-06	RAN#84	R5-194170	0154	-	F	Test point analysis for A-MPR Intra-band contiguous EN-DC; NS_04	15.3.0
2019-06	RAN#84	R5-194257	0155	-	F	TP analysis for Asymmetric CH BWs in Reference Sensitivity Requirements in FR1	15.3.0
2019-06	RAN#84	R5-194402	0158	-	F	Test Point analysis for EN-DC In-band emissions for intra-band contiguous	15.3.0
2019-06	RAN#84	R5-194459	0160	-	F	Update to TP analysis for FR2 Maximum Output Power	15.3.0
2019-06	RAN#84	R5-194904	0142	1	F	Addition of TP analysis for 38.521-1 7.6D.3	15.3.0
2019-06	RAN#84	R5-194907	0163	1	F	Addition of TP analysis for 38.521-1 6.3A.3	15.3.0
2019-06	RAN#84	R5-194909	0164	1	F	Addition of TP analysis for 38.521-1 6.3A.1 FR1	15.3.0
2019-06	RAN#84	R5-194913	0165	-	F	Addition of TP analysis for ACS for 2DL CA in FR1	15.3.0
2019-06	RAN#84	R5-194914	0166	-	F	Addition of TP analysis for FR1 MOP for CA	15.3.0
2019-06	RAN#84	R5-194927	0162	1	F	Addition of test frequency selection of spurious co-existence inter-band for DC 3-n79	15.3.0
2019-06	RAN#84	R5-194931	0141	1	F	Addition of TP analysis for 38.521-1 7.6D.2	15.3.0
2019-06	RAN#84	R5-194932	0143	1	F	Addition of TP analysis for 38.521-1 7.6D.4	15.3.0
2019-06	RAN#84	R5-194933	0144	1	F	Addition of TP analysis for 38.521-1 7.8D.2	15.3.0
2019-06	RAN#84	R5-194959	0167	-	F	Addition of TP analysis for UL-MIMO cases of 6.3D.1 and 6.3D.3	15.3.0
2019-06	RAN#84	R5-194961	0157	1	F	TP analysis for FR2 Tx 6.3A.1.1 Minimum output power for CA 2UL CA	15.3.0
2019-06	RAN#84	R5-194963	0161	1	F	Update SCS test points for FR2 ACS and Inband blocking test cases	15.3.0
2019-06	RAN#84	R5-195146	0138	1	F	Addition of TP analysis for SA FR2 6.2.2	15.3.0
2019-06	RAN#84	R5-195148	0139	1	F	Addition of TP analysis for SA FR2 6.3.2	15.3.0
2019-06	RAN#84	R5-195190	0145	1	F	TPanalysis of 7.7D Spurious response for UL-MIMO	15.3.0
2019-06	RAN#84	R5-193730	0146	-	F	Addition of test frequency selection of 6.5A.3.2 for Rel-16 CA_n41A-n79A	16.0.0
2019-06	RAN#84	R5-195055	0150	1	F	Addition of test frequency selection of 6.5B.3.3.2 spurious co-existence inter-band for Rel-16 DC configurations	16.0.0
2019-09	RAN#85	R5-196435	0184	-	F	Update of TP analysis of FR2 minimum output power to add UL MIMO	16.1.0
2019-09	RAN#85	R5-196445	0185	-	F	Correction of 4.5 to add DC_3A-n41	16.1.0
2019-09	RAN#85	R5-197315	0175	1	F	Addition of TP analysis for FR1 MPR for CA	16.1.0
2019-09	RAN#85	R5-197317	0176	1	F	Addition of TP analysis for FR1 ConfigTP for CA	16.1.0
2019-09	RAN#85	R5-197320	0179	1	F	Addition of TP analysis of FR1 6.4D.2.1 EVM for UL MIMO	16.1.0
2019-09	RAN#85	R5-197322	0180	1	F	Addition of TP analysis of FR1 6.4D.2.2 Carrier leakage for UL MIMO	16.1.0
2019-09	RAN#85	R5-197323	0181	1	F	Addition of TP analysis of FR1 6.4D.2.3 Inband emission for UL MIMO	16.1.0
2019-09	RAN#85	R5-197325	0182	1	F	Addition of TP analysis of FR1 6.4D.2.4 EVM equalizer spectrum flatness for UL MIMO	16.1.0
2019-09	RAN#85	R5-197326	0186	1	F	Test Point analysis for Occupied bandwidth for 2UL CA in FR1	16.1.0
2019-09	RAN#85	R5-197524	0187	1	F	TP_analysis_38.905_7.3A_CA_ref_sensitivity	16.1.0
2019-09	RAN#85	R5-197589	0168	1	F	New addition of TP analysis for MOP & MOP Spherical Coverage for UL CA in SA FR2	16.1.0
2019-09	RAN#85	R5-197590	0169	1	F	New addition of TP analysis for Carrier leakage for UL CA in SA FR2	16.1.0
2019-09	RAN#85	R5-197591	0170	1	F	Adding test case 6.5B.2.1.3 to 38.905	16.1.0
2019-09	RAN#85	R5-197592	0173	1	F	Addition of TP analysis of FR2 6.6 Beam Correspondence	16.1.0
2019-09	RAN#85	R5-197593	0174	1	F	Test Point analysis update for FR2 Tx Spurious test case	16.1.0
2019-09	RAN#85	R5-197594	0177	1	F	Addition of TP analysis of FR1 Maximum input level for CA	16.1.0
2019-09	RAN#85	R5-197595	0178	1	F	Addition of TP analysis of FR1 6.4D.1 Frequency error for UL MIMO	16.1.0
2019-09	RAN#85	R5-197596	0183	1	F	Addition of TP analysis of FR2 6.2A.2 MPR for 2 UL CA	16.1.0
2019-09	RAN#85	R5-197597	0191	1	F	Addition of TP analysis for FR2 AMPR with NS_201	16.1.0
2019-09	RAN#85	R5-197628	0192	2	F	Updates of TP analysis for EN-DC MPR test case 6.2.B.2.1	16.1.0
2019-12	RAN#86	R5-198384	0203		F	Addition of TP analysis of FR2 6.6 Beam Correspondence v1	16.2.0
2019-12	RAN#86	R5-198392	0205		F	Addition of TP analysis of FR2 6.3D.3.4 SRS time mask for UL-MIMO	16.2.0
2019-12	RAN#86	R5-198490	0206		F	TPanalysis of TC 7.5B.1 ACS for intra-band contiguous EN-DC 2CCs	16.2.0

2019-12	RAN#86	R5-198523	0208		F	Test points analysis for NS_03 A-MPR FR1 test case	16.2.0
2019-12	RAN#86	R5-198527	0210		F	Test points analysis for NS_43 and NS_43U A_MPR FR1 test case	16.2.0
2019-12	RAN#86	R5-199326	0209	1	F	Test points analysis for NS_05 and NS_05U A_MPR FR1 test case	16.2.0
2019-12	RAN#86	R5-199327	0211	1	F	Test points analysis for NS_100 A_MPR FR1 test case	16.2.0
2019-12	RAN#86	R5-199328	0200	1	F	Addition of test point analysis for SA FR1 TC 7.6A.3 Out-of-band blocking for CA	16.2.0
2019-12	RAN#86	R5-199372	0197	1	F	Update of test point analysis for SA FR2 TC 6.2.2	16.2.0
2019-12	RAN#86	R5-199410	0199	1	F	Update of test point analysis for SA FR1 TC 6.2.2 to add almost contiguous allocation test points	16.2.0
2019-12	RAN#86	R5-199487	0202	1	F	Addition of test point analysis for SA FR1 TC 7.8A Wide band Intermodulation for CA	16.2.0
2019-12	RAN#86	R5-199488	0201	1	F	Addition of test point analysis for SA FR1 TC 7.6A.4 Narrow band blocking for CA	16.2.0
2019-12	RAN#86	R5-199489	0207	1	F	Addition of TP analysis for ACS for 3DL CA in FR1	16.2.0
2019-12	RAN#86	R5-199501	0198	1	F	Update of test point analysis for SA FR1 TC 6.5.2.4.2	16.2.0
2019-12	RAN#86	R5-199507	0196	1	F	TP analysis for test case 6.2B.2.2, UE Maximum Output Power reduction for Intra-Band Non-Contiguous EN-DC	16.2.0
2019-12	RAN#86	R5-199509	0194	1	F	TP analysis for MOP for EN-DC	16.2.0
2019-12	RAN#86	R5-199549	0204	1	F	Addition to TP analysis of FR2 TC 6.3A.4.2.1 Absolute Power Control for CA	16.2.0
2020-03	RAN#87	R5-200402	0215	-	F	Updating TP of MOP for inter-band EN-DC	16.3.0
2020-03	RAN#87	R5-200412	0221	-	F	Editorial change of replacing zip file of FR2 6.3.1 by v2	16.3.0
2020-03	RAN#87	R5-200419	0222	-	F	Update of test point analysis for 7.6A.3 Out-of-band blocking for CA	16.3.0
2020-03	RAN#87	R5-200459	0223	-	F	Update of test point analysis for 7.6A.4 Narrow band blocking for CA	16.3.0
2020-03	RAN#87	R5-200460	0224	-	F	Update of test point analysis for 7.8A Wide band Intermodulation for CA	16.3.0
2020-03	RAN#87	R5-200574	0226	-	F	Addition of Test point selection for FR1 in SUL test cases	16.3.0
2020-03	RAN#87	R5-200603	0227	-	F	Test Point analysis for FR2 ref sens for CA	16.3.0
2020-03	RAN#87	R5-200758	0229	-	F	Correction of NS_05 test points analysis	16.3.0
2020-03	RAN#87	R5-200762	0231	-	F	Test points analysis for NS_38 A-MPR FR1 test case	16.3.0
2020-03	RAN#87	R5-200764	0232	-	F	Test points analysis for NS_39 A-MPR FR1 test case	16.3.0
2020-03	RAN#87	R5-200766	0233	-	F	Test points analysis for NS_43 A-MPR FR1 test case	16.3.0
2020-03	RAN#87	R5-200768	0234	-	F	Test points analysis for NS_43U A-MPR FR1 test case	16.3.0
2020-03	RAN#87	R5-200799	0236	-	F	Updated test point analysis for FR2 A-MPR test case	16.3.0
2020-03	RAN#87	R5-200815	0237	-	F	Update of Test Point Analysis for UE Coexistence for DC_3A-n41A and DC_8A-n41A	16.3.0
2020-03	RAN#87	R5-200990	0238	1	F	Addition of TP analysis for FR1 In-band blocking for CA	16.3.0
2020-03	RAN#87	R5-201182	0216	1	F	Updating TP of configured output power for inter-band EN-DC	16.3.0
2020-03	RAN#87	R5-201184	0218	1	F	Updating TP of configured output power for intra-band contiguous EN-DC	16.3.0
2020-03	RAN#87	R5-201186	0220	1	F	Updating TP of configured output power for intra-band non-contiguous EN-DC	16.3.0
2020-03	RAN#87	R5-201237	0230	1	F	Test points analysis for NS_37 A-MPR FR1 test case	16.3.0
2020-03	RAN#87	R5-201239	0235	1	F	Test points analysis for NS_18 A-MPR FR1 test case	16.3.0
2020-06	RAN#88	R5-201746	0242	-	F	Addition of Number of test points for FR1 in SUL test cases	16.4.0
2020-06	RAN#88	R5-201747	0243	-	F	Addition of TP analysis for FR1 A-MPR for CA	16.4.0
2020-06	RAN#88	R5-201765	0246	-	F	Test points analysis for NS_27 A_MPR FR1 test case	16.4.0
2020-06	RAN#88	R5-201767	0247	-	F	Test points analysis for NS_40 A_MPR FR1 test case	16.4.0
2020-06	RAN#88	R5-201773	0250	-	F	Test points analysis for NS_47 A_MPR FR1 test case	16.4.0
2020-06	RAN#88	R5-201871	0253	-	F	Update of test points analysis in UE co-existence for inter-band EN-DC	16.4.0
2020-06	RAN#88	R5-201872	0254	-	F	Update of Test Point Analysis for UE Co-existence for DC_5A-n66A	16.4.0
2020-06	RAN#88	R5-201873	0255	-	F	Update of Test Point Analysis for UE Co-existence for DC_5A-n78A	16.4.0
2020-06	RAN#88	R5-201874	0256	-	F	Update of Test Point Analysis for UE Co-existence for DC_66A-n5A	16.4.0
2020-06	RAN#88	R5-201875	0257	-	F	Update of Test Point Analysis for UE Co-existence for DC_66A-n78A	16.4.0
2020-06	RAN#88	R5-201929	0258	-	F	Cleanup in 38.905	16.4.0
2020-06	RAN#88	R5-201931	0260	-	F	Combined TP analysis for MPR, ACLR and SEM intra-band contiguous EN-DC test cases	16.4.0
2020-06	RAN#88	R5-202029	0261	-	F	Introduction of test point analysis for 2CCs EN-DC TCs in FR1 in 7.6B Blocking characteristics for DC and 7.7B Spurious response for DC	16.4.0
2020-06	RAN#88	R5-202111	0262	-	F	NS_24 TP analysis to TR 38.905	16.4.0
2020-06	RAN#88	R5-202524	0267	-	F	TP_analysis_6.5.3.3_TX_Additional_SpurEmission_NS_43	16.4.0
2020-06	RAN#88	R5-202755	0248	1	F	Test points analysis for NS_41 A_MPR FR1 test case	16.4.0
2020-06	RAN#88	R5-202756	0249	1	F	Test points analysis for NS_42 A_MPR FR1 test case	16.4.0
2020-06	RAN#88	R5-202757	0264	1	F	TP_analysis_6.5.3.3_TX_Additional_SpurEmission_NS_05	16.4.0
2020-06	RAN#88	R5-202918	0239	1	F	Test Point analysis for FR2 Frequency Error for CA	16.4.0
2020-06	RAN#88	R5-202926	0266	1	F	Addition of TPanalysis 6.5A.3.2.1_SECoex for CA_n1A-n78A	16.4.0
2020-06	RAN#88	R5-202932	0244	1	F	Addition of TP analysis for FR1 Maximum input level for 3DL CA	16.4.0
2020-06	RAN#88	R5-202933	0245	1	F	Addition of TP analysis for FR1 In-band blocking for 3DL CA	16.4.0
2020-06	RAN#88	R5-202952	0251	1	F	Updating TP of MOP for intra-band contiguous EN-DC	16.4.0

2020-06	RAN#88	R5-202953	0252	1	F	Updating TP of MOP for intra-band non-contiguous EN-DC	16.4.0
2020-06	RAN#88	R5-202954	0259	1	F	Combined TP analysis for MPR, NR ACLR and SEM FR1 test cases	16.4.0
2020-06	RAN#88	R5-202955	0263	1	F	Updated TP analysis for 7.3A Reference sensitivity for CA	16.4.0
2020-09	RAN#89	R5-203642	0269	-	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_40A_n1A	16.5.0
2020-09	RAN#89	R5-203643	0270	-	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_40A_n78A	16.5.0
2020-09	RAN#89	R5-203751	0275	-	F	Editorial correction to references to EN-DC configurations	16.5.0
2020-09	RAN#89	R5-204720	0299	1	F	Add_TP_analysis_table for TX_spurious_emission	16.5.0
2020-09	RAN#89	R5-204726	0278	1	F	Addition of test point analysis in Tx spurious emissions	16.5.0
2020-09	RAN#89	R5-204727	0273	1	F	Updating TP analysis for 6.2A.2-MPR for CA	16.5.0
2020-09	RAN#89	R5-204728	0279	1	F	Update of test point analysis of MOP for intra-band contiguous EN-DC	16.5.0
2020-09	RAN#89	R5-204789	0271	1	F	Update of TP analysis for NS_43 and NS_01 in FR1 A-MPR for CA	16.5.0
2020-09	RAN#89	R5-204790	0272	1	F	Update of TP analysis for NS_43U and NS_01 in FR1 A-MPR for CA	16.5.0
2020-09	RAN#89	R5-204791	0280	1	F	Updating test point analysis for DC_1A-n78A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204792	0281	1	F	Updating test point analysis for DC_2A-n66A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204793	0282	1	F	Updating test point analysis for DC_2A-n78A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204794	0283	1	F	Updating test point analysis for DC_3A-n7A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204795	0284	1	F	Updating test point analysis for DC_3A-n78A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204796	0285	1	F	Updating test point analysis for DC_7A-n78A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204797	0292	1	F	Correction to test point analysis for spurious emissions UE co-existence for a few inter-band EN-DC configurations	16.5.0
2020-09	RAN#89	R5-204817	0286	1	F	Updating test point analysis for DC_3A-n1A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204818	0287	1	F	Updating test point analysis for DC_7A-n1A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204819	0288	1	F	Updating test point analysis for DC_7A-n66A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204820	0289	1	F	Updating test point analysis for DC_8A-n1A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204821	0290	1	F	Updating test point analysis for DC_12A-n78A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204822	0291	1	F	Updating test point analysis for DC_28A-n3A for spurious emissions UE co-existence	16.5.0
2020-09	RAN#89	R5-204829	0293	1	F	Addition of test point analysis for AMPR NS_48	16.5.0
2020-09	RAN#89	R5-204838	0274	1	F	Updating TP analysis for 6.2A.4-Configured output power for CA	16.5.0
2020-09	RAN#89	R5-204948	0295	1	F	Addition of Test Point analysis for FR2 Transmit OFF Power for CA	16.5.0
2020-09	RAN#89	R5-204949	0298	1	F	TP analysis 6.5B.3 TX SpurEmission EN-DC V2	16.5.0
2020-09	RAN#89	R5-204950	0300	1	F	Updated TP analysis for 7.3B Reference sensitivity for EN-DC in FR1	16.5.0
2020-09	RAN#89	R5-204959	0301	1	F	Update of TP analysis 6.5A.3.2.1_SECoex for CA_n1A-n78A	16.5.0
2020-09	RAN#89	R5-204963	0276	1	F	Update test point analysis for A-MPR NS_18 with CBW being 30MHz	16.5.0
2020-09	RAN#89	R5-204964	0294	1	F	Addition of test point analysis for additional spurious emission with NS_17	16.5.0
2020-09	RAN#89	R5-204982	0268	2	F	Updated TP analysis for 7.3A	16.5.0
2020-12	RAN#90	R5-205264	0303	-	F	Addition of Test Point analysis for 6.3A.4.1	16.6.0
2020-12	RAN#90	R5-205265	0304	-	F	Addition of Test Point analysis for 6.3A.4.2	16.6.0
2020-12	RAN#90	R5-205267	0305	-	F	Addition of Test Point analysis for 6.3A.4.3	16.6.0
2020-12	RAN#90	R5-205558	0309	-	F	Adding test point analysis for A-MPR test of band n30 with NS_21	16.6.0
2020-12	RAN#90	R5-205619	0312	-	F	Addition of TP Analysis for TC 6.5A.2.1 Spectrum Emission Mask for CA in FR2	16.6.0
2020-12	RAN#90	R5-205630	0313	-	F	Addition of TP Analysis for TC 6.5A.2.2 Adjacent channel leakage ratio for CA in FR2	16.6.0
2020-12	RAN#90	R5-205780	0318	-	F	Addition of test point analysis for DC_2A_n5A in Tx spurious emissions cases	16.6.0
2020-12	RAN#90	R5-205781	0319	-	F	Addition of test point analysis for DC_8A_n78A in Tx spurious emissions cases	16.6.0
2020-12	RAN#90	R5-205782	0320	-	F	Addition of test point analysis for DC_12A_n66A in Tx spurious emissions cases	16.6.0
2020-12	RAN#90	R5-205783	0321	-	F	Addition of test point analysis for DC_30A_n5A in Tx spurious emissions cases	16.6.0
2020-12	RAN#90	R5-205785	0322	-	F	Addition of test point analysis for DC_13A_n66A in Tx spurious emissions cases	16.6.0
2020-12	RAN#90	R5-205885	0329	-	F	Addition of test point analysis for A-MPR NS_46	16.6.0

2020-12	RAN#90	R5-206037	0333	-	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_20A_n3A	16.6.0
2020-12	RAN#90	R5-206729	0332	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_1A_n3A	16.6.0
2020-12	RAN#90	R5-206752	0302	1	F	Addition of test point analysis for A-MPR NS_45	16.6.0
2020-12	RAN#90	R5-206769	0325	1	F	Update of test point analysis for Tx spurious emissions in NR FR1	16.6.0
2020-12	RAN#90	R5-206853	0328	1	F	Update to test point analysis for A-MPR NS_18 with 30MHz	16.6.0
2020-12	RAN#90	R5-206854	0314	1	F	Updating TP analysis for OBW for CA	16.6.0
2020-12	RAN#90	R5-206855	0316	1	F	Updating TP analysis for Maximum input level for 3DL CA	16.6.0
2020-12	RAN#90	R5-206856	0317	1	F	Updating TP analysis for Inband blocking for 3DL CA	16.6.0
2020-12	RAN#90	R5-206857	0323	1	F	Update of test point analysis for MPR, SEM and ACLR in NR FR1	16.6.0
2020-12	RAN#90	R5-206858	0324	1	F	Update of test point analysis for MOP in FR1	16.6.0
2020-12	RAN#90	R5-206873	0310	1	F	Restructuring of TR 38.905.	16.6.0
2020-12	RAN#90	R5-206874	0311	1	F	Combined TP analysis for FR2 test cases MPR, ACLR and SEM	16.6.0
2020-12	RAN#90	R5-206875	0331	1	F	Update of TPA for in-band emission and carrier leakage TCs	16.6.0
2020-12	RAN#90	R5-206876	0336	1	F	Update of test point analysis for occupied bandwidth in FR2	16.6.0
2020-12	RAN#90	R5-206893	0315	1	F	Updating TP analysis for REFSENS for CA	16.6.0
2020-12	RAN#90	R5-206917	0330	1	F	Updated TP analysis for 7.3B Reference sensitivity for EN-DC in FR1	16.6.0
2021-03	RAN#91	R5-210383	0343	-	F	Correct a typo of 6.3A.4.2	16.7.0
2021-03	RAN#91	R5-210512	0344	-	F	Introduction of test point analysis for SA FR2 7.4A Maximum input level for CA	16.7.0
2021-03	RAN#91	R5-210740	0347	-	F	Updating TP analysis of FR1 A-MPR for NS_48	16.7.0
2021-03	RAN#91	R5-210742	0348	-	F	Adding TP analysis of FR1 A-MPR for NS_49	16.7.0
2021-03	RAN#91	R5-210743	0349	-	F	Resubmitting TP analysis of FR1 A-MPR for NS_44	16.7.0
2021-03	RAN#91	R5-210791	0353	-	F	Adding TP selection for 6.4C.2 Transmit modulation quality for SUL	16.7.0
2021-03	RAN#91	R5-210900	0354	-	F	Updating TP analysis for Spurious Emissions for CA in FR1	16.7.0
2021-03	RAN#91	R5-210905	0356	-	F	Updating TP analysis for FR1 REFSENS for SUL testing	16.7.0
2021-03	RAN#91	R5-210963	0362	-	F	Spur emission TP analysis R16 DC_5A_n2A	16.7.0
2021-03	RAN#91	R5-211018	0368	-	F	TP analysis for test case 6.5D.2_1.4.2, UTRA ACLR for UL MIMO (Rel-16 onward)	16.7.0
2021-03	RAN#91	R5-211134	0380	-	F	TP analysis for ULFP Tx in MPR test case	16.7.0
2021-03	RAN#91	R5-211230	0389	-	F	NS_12, NS_13, NS_14, NS_15 TP analysis to 38.905	16.7.0
2021-03	RAN#91	R5-211733	0340	1	F	Updated TP analysis for 7.3B Reference sensitivity for EN-DC in FR1	16.7.0
2021-03	RAN#91	R5-211734	0341	1	F	TP analysis for 38.521-3 test case 6.5B.2.2.1 SEM Intra-band non-contiguous	16.7.0
2021-03	RAN#91	R5-211735	0342	1	F	TP analysis for 38.521-3 test case 6.5B.2.2.3 ACLR Intra-band non-contiguous	16.7.0
2021-03	RAN#91	R5-211736	0345	1	F	Update of test point analysis for FR2 UL CA frequency error test cases	16.7.0
2021-03	RAN#91	R5-211737	0369	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_8A_n77A	16.7.0
2021-03	RAN#91	R5-211738	0370	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_11A_n77A	16.7.0
2021-03	RAN#91	R5-211739	0371	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_11A_n78A	16.7.0
2021-03	RAN#91	R5-211740	0372	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_11A_n79A	16.7.0
2021-03	RAN#91	R5-211741	0373	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_25A_n41A	16.7.0
2021-03	RAN#91	R5-211742	0374	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_26A_n41A	16.7.0
2021-03	RAN#91	R5-211743	0375	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_26A_n77A	16.7.0
2021-03	RAN#91	R5-211744	0376	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_26A_n78A	16.7.0
2021-03	RAN#91	R5-211745	0377	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_26A_n79A	16.7.0
2021-03	RAN#91	R5-211746	0378	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_41A_n77A	16.7.0
2021-03	RAN#91	R5-211747	0379	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_41A_n78A	16.7.0
2021-03	RAN#91	R5-211748	0388	1	F	Test Point analysis update for FR2 Tx additional spurious emission test case	16.7.0
2021-03	RAN#91	R5-211774	0337	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_7A_n3A	16.7.0
2021-03	RAN#91	R5-211775	0338	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_8A_n3A	16.7.0
2021-03	RAN#91	R5-211776	0339	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_20A_n1A	16.7.0
2021-03	RAN#91	R5-211777	0361	1	F	Spur emission TP analysis R16 DC_2A_n41A	16.7.0
2021-03	RAN#91	R5-211778	0363	1	F	Spur emission TP analysis R16 DC_13A_n2A	16.7.0

2021-03	RAN#91	R5-211779	0364	1	F	Spur emission TP analysis R16 DC_48A_n5A	16.7.0
2021-03	RAN#91	R5-211780	0365	1	F	Spur emission TP analysis R16 DC_48A_n66A	16.7.0
2021-03	RAN#91	R5-211781	0366	1	F	Spur emission TP analysis R16 DC_66A_n41A	16.7.0
2021-03	RAN#91	R5-211809	0350	1	F	Adding TP analysis for Rel-16 DMRS in A-MPR test case	16.7.0
2021-03	RAN#91	R5-211810	0351	1	F	Update of TP analysis for EVM equalizer spectrum flatness for half Pi BPSK	16.7.0
2021-03	RAN#91	R5-211811	0352	1	F	Update of TP analysis for FR1 SUL test cases	16.7.0
2021-03	RAN#91	R5-211893	0346	1	F	Update of test point analysis for FR2 MPR, SEM and ACLR test cases	16.7.0
2021-03	RAN#91	R5-211894	0359	1	F	Addition of reference sensitivity test point analyses for FR1 NR CA and EN-DC	16.7.0
2021-03	RAN#91	R5-211895	0360	1	F	Moving of principles for reference sensitivity test point selection from attachments to annexes	16.7.0
2021-03	RAN#91	R5-211897	0382	1	F	TP analysis for DC_8A_n77A	16.7.0
2021-03	RAN#91	R5-211898	0383	1	F	TP analysis for DC_11A_n79A	16.7.0
2021-03	RAN#91	R5-211899	0384	1	F	TP analysis for DC_26A_n41A	16.7.0
2021-03	RAN#91	R5-211900	0385	1	F	TP analysis for DC_26A_n77A and DC_26A_n78A	16.7.0
2021-03	RAN#91	R5-211901	0386	1	F	TP analysis for DC_26A_n79A	16.7.0
2021-03	RAN#91	R5-211902	0387	1	F	TP analysis for DC_41A_n77A and DC_41A_n78A	16.7.0
2021-03	RAN#91	R5-211906	0390	1	F	Reference sensitivity TP analysis for DC_1A-28A_n3A	16.7.0
2021-03	RAN#91	R5-211907	0391	1	F	Reference sensitivity analysis for DC_3A-7A_n1A	16.7.0
2021-03	RAN#91	R5-211908	0392	1	F	Reference sensitivity TP analysis for DC_7A-20A_n1A	16.7.0
2021-03	RAN#91	R5-211909	0393	1	F	Reference sensitivity TP analysis for DC_7A-28A_n3A	16.7.0
2021-03	RAN#91	R5-211914	0358	1	F	Adding TP analysis for NR test case-Time mask for UL carrier switching	16.7.0
2021-03	RAN#91	-	-	-	-	Administrative release upgrade to match the release of TS 38.508-1, TS 38.508-2 and TS 38.521-1 which were upgraded at RAN#91 to Rel-17 due to Rel-17 relevant CRs	17.0.0
2021-06	RAN#92	R5-212519	0397	-	F	Update of test point analysis for FR2 Occupied Bandwidth for UL MIMO test case	17.1.0
2021-06	RAN#92	R5-212524	0400	-	F	Spurious emission TP analysis for Rel-15 EN-DC configuration DC_66A_n71A	17.1.0
2021-06	RAN#92	R5-212929	0405	-	F	Addition of TP analysis of V2X MPR, SEM and ACLR non-concurrent	17.1.0
2021-06	RAN#92	R5-212930	0406	-	F	Addition of TP analysis of 6.3E.1 V2X minimum output power non-concurrent	17.1.0
2021-06	RAN#92	R5-212982	0407	-	F	Addition of TP analysis for CA_n28A-n41A in Tx Spurious Emission cases	17.1.0
2021-06	RAN#92	R5-212990	0409	-	F	Updating TP analysis for UTRA ACLR MIMO testing for band n1	17.1.0
2021-06	RAN#92	R5-213024	0411	-	F	Correction to test points selection for intra-band EN-DC spurious emissions testing	17.1.0
2021-06	RAN#92	R5-213053	0421	-	F	TP analysis for 6.2.4 updated for eMIMO	17.1.0
2021-06	RAN#92	R5-213114	0428	-	F	Correction of test coverage clause numbering	17.1.0
2021-06	RAN#92	R5-213946	0396	1	F	Introduction of test point analysis for FR2 CA Error Vector Magnitude test case	17.1.0
2021-06	RAN#92	R5-213947	0401	1	F	Spurious emission TP analysis for Rel-15 EN-DC configuration DC_2A_n71A	17.1.0
2021-06	RAN#92	R5-213948	0403	1	F	Addition of test points analysis for NS_06 FR1 test cases	17.1.0
2021-06	RAN#92	R5-213949	0413	1	F	Correction to test points selection for inter-band EN-DC co-existence spurious emissions testing	17.1.0
2021-06	RAN#92	R5-213950	0414	1	F	Update of TP analysis for general spurious emissions for DC_3A_n7A	17.1.0
2021-06	RAN#92	R5-213951	0415	1	F	Update of TP analysis for general spurious emissions for DC_3A_n78A	17.1.0
2021-06	RAN#92	R5-213952	0416	1	F	Update of TP analysis for general spurious emissions for DC_8A_n77A	17.1.0
2021-06	RAN#92	R5-213953	0417	1	F	Update of TP analysis for general spurious emissions for DC_12A_n66A	17.1.0
2021-06	RAN#92	R5-213954	0418	1	F	Update of TP analysis for general spurious emissions for DC_26A_n41A	17.1.0
2021-06	RAN#92	R5-213955	0419	1	F	Update of TP analysis for general spurious emissions for DC_26A_n79A	17.1.0
2021-06	RAN#92	R5-213956	0420	1	F	Update of TP analysis for general spurious emissions for DC_30A_n5A	17.1.0
2021-06	RAN#92	R5-213957	0422	1	F	Update of test point analysis for FR2 MPR SEM and ACLR UL-MIMO test cases	17.1.0
2021-06	RAN#92	R5-213958	0423	1	F	TP analysis for DC_11A_n77A	17.1.0
2021-06	RAN#92	R5-213959	0424	1	F	TP analysis for DC_11A_n78A	17.1.0
2021-06	RAN#92	R5-213960	0425	1	F	TP analysis for DC_25A_n41A	17.1.0
2021-06	RAN#92	R5-213961	0426	1	F	TP analysis for DC_42A_n77A	17.1.0
2021-06	RAN#92	R5-213962	0427	1	F	General TP analysis update for NR CA refsens	17.1.0
2021-06	RAN#92	R5-214070	0402	1	F	Correction of power control in 38.905	17.1.0
2021-06	RAN#92	R5-214071	0429	1	F	Test Point analysis for FR2 Tx spurious emission CA test case	17.1.0

2021-06	RAN#92	R5-214073	0398	1	F	Spurious emission TP analysis for Rel-16 EN-DC configuration DC_14A_n2A	17.1.0
2021-06	RAN#92	R5-214074	0399	1	F	Spurious emission TP analysis for Rel-16 EN-DC configuration DC_14A_n66A	17.1.0
2021-06	RAN#92	R5-214093	0412	1	F	Correction to test points selection for inter-band EN-DC general spurious emissions testing	17.1.0
2021-09	RAN#93	R5-214245	0431	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_1A_n77A	17.2.0
2021-09	RAN#93	R5-214246	0432	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_1A_n79A	17.2.0
2021-09	RAN#93	R5-214247	0433	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_3A_n28A	17.2.0
2021-09	RAN#93	R5-214248	0434	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_3A_n77A	17.2.0
2021-09	RAN#93	R5-214249	0435	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_7A_n28A	17.2.0
2021-09	RAN#93	R5-214250	0436	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_19A_n77A	17.2.0
2021-09	RAN#93	R5-214251	0437	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_19A_n78A	17.2.0
2021-09	RAN#93	R5-214252	0438	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_19A_n79A	17.2.0
2021-09	RAN#93	R5-214253	0439	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_20A_n28A	17.2.0
2021-09	RAN#93	R5-214255	0441	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_21A_n77A	17.2.0
2021-09	RAN#93	R5-214256	0442	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_21A_n78A	17.2.0
2021-09	RAN#93	R5-214257	0443	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_21A_n79A	17.2.0
2021-09	RAN#93	R5-214258	0444	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_28A_n77A	17.2.0
2021-09	RAN#93	R5-214260	0446	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_28A_n79A	17.2.0
2021-09	RAN#93	R5-214261	0447	-	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_42A_n77A	17.2.0
2021-09	RAN#93	R5-214262	0448	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_1A_n78A	17.2.0
2021-09	RAN#93	R5-214263	0449	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_3A_n79A	17.2.0
2021-09	RAN#93	R5-214264	0450	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_5A_n66A	17.2.0
2021-09	RAN#93	R5-214265	0451	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_5A_n78A	17.2.0
2021-09	RAN#93	R5-214266	0452	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_7A_n78A	17.2.0
2021-09	RAN#93	R5-214267	0453	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_11A_n77A	17.2.0
2021-09	RAN#93	R5-214268	0454	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_11A_n78A	17.2.0
2021-09	RAN#93	R5-214269	0455	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_11A_n79A	17.2.0
2021-09	RAN#93	R5-214271	0457	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_26A_n77A	17.2.0
2021-09	RAN#93	R5-214272	0458	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_26A_n78A	17.2.0
2021-09	RAN#93	R5-214273	0459	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_39A_n79A	17.2.0
2021-09	RAN#93	R5-214274	0460	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_41A_n77A	17.2.0
2021-09	RAN#93	R5-214275	0461	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_41A_n78A	17.2.0
2021-09	RAN#93	R5-214276	0462	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_41A_n79A	17.2.0
2021-09	RAN#93	R5-214277	0463	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_66A_n5A	17.2.0
2021-09	RAN#93	R5-214278	0464	-	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_66A_n78A	17.2.0
2021-09	RAN#93	R5-214315	0465	-	F	Update of spurious emission TP analysis for Rel-16 EN-DC configuration DC_40A_n1A	17.2.0
2021-09	RAN#93	R5-214316	0466	-	F	Update of spurious emission TP analysis for Rel-16 EN-DC configuration DC_40A_n78A	17.2.0
2021-09	RAN#93	R5-214385	0467	-	F	Introduction of NR FR2 Test Points For Aggregate power tolerance for CA	17.2.0

2021-09	RAN#93	R5-214721	0468	-	F	Adding TP analysis for test case 6.5D.1_1	17.2.0
2021-09	RAN#93	R5-214907	0469	-	F	Introduction of test point analysis for FR2 Time alignment error for UL MIMO test case	17.2.0
2021-09	RAN#93	R5-215076	0473	-	F	Addition of TP analysis of V2X MPR, SEM and ACLR non-concurrent with SL-MIMO	17.2.0
2021-09	RAN#93	R5-215077	0474	-	F	Addition of TP analysis of V2X minimum output power for non-concurrent with SL-MIMO	17.2.0
2021-09	RAN#93	R5-215164	0475	-	F	Addition of test points analysis for NS_06 power class 1 test cases	17.2.0
2021-09	RAN#93	R5-215219	0479	-	F	Update of TP analysis for general spurious emissions for DC_12A_n78A	17.2.0
2021-09	RAN#93	R5-215220	0480	-	F	Update of TP analysis for general spurious emissions for DC_28A_n3A	17.2.0
2021-09	RAN#93	R5-215229	0483	-	F	Correction to TP analysis for in-band emission for intra-band contiguous EN-DC	17.2.0
2021-09	RAN#93	R5-215236	0484	-	F	Addition of reference sensitivity TP analysis for DC_1A_n28A-n78A	17.2.0
2021-09	RAN#93	R5-215237	0485	-	F	Addition of reference sensitivity TP analysis for DC_1A-3A_n28A	17.2.0
2021-09	RAN#93	R5-215238	0486	-	F	Addition of reference sensitivity TP analysis for DC_1A-7A_n28A	17.2.0
2021-09	RAN#93	R5-215239	0487	-	F	Addition of reference sensitivity TP analysis for DC_3A-7A_n28A	17.2.0
2021-09	RAN#93	R5-215293	0492	-	F	Updating Test point analysis for DC_3A-20A_n28A	17.2.0
2021-09	RAN#93	R5-215302	0495	-	F	Updating TP analysis for Relative power tolerance for CA	17.2.0
2021-09	RAN#93	R5-215304	0496	-	F	Updating TP analysis for Aggregate power tolerance for CA	17.2.0
2021-09	RAN#93	R5-215306	0497	-	F	Updating TP analysis for Occupied bandwidth for CA	17.2.0
2021-09	RAN#93	R5-215327	0498	-	F	TP analysis for FR2 General ON OFF time mask	17.2.0
2021-09	RAN#93	R5-215336	0499	-	F	Correction to TP analysis for FR1 A-SPR with NS_17	17.2.0
2021-09	RAN#93	R5-215543	0502	-	F	Update_TP_analysis for Rel_16_DC_14A_n2A	17.2.0
2021-09	RAN#93	R5-215545	0503	-	F	Update_TP_analysis for Rel_16_DC_13A_n2A	17.2.0
2021-09	RAN#93	R5-215547	0504	-	F	Update_TP_analysis for Rel_15_DC_2A_n71A	17.2.0
2021-09	RAN#93	R5-215550	0505	-	F	Update_TP_analysis for Rel_15_DC_66A_n71A	17.2.0
2021-09	RAN#93	R5-215919	0440	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_20A_n78A	17.2.0
2021-09	RAN#93	R5-215920	0456	1	F	Update of spurious emission TP analysis for Rel-15 EN-DC configuration DC_25A_n41A	17.2.0
2021-09	RAN#93	R5-215921	0471	1	F	Addition of TP analysis for spurious emissions for DC_28A_n78A	17.2.0
2021-09	RAN#93	R5-216014	0430	1	F	Introduction of spurious emission TP analysis for Rel-15 EN-DC configuration DC_1A_n28A	17.2.0
2021-09	RAN#93	R5-216017	0477	1	F	Update of TP analysis for general spurious emissions for DC_3A_n41A	17.2.0
2021-09	RAN#93	R5-216018	0481	1	F	Update of TP analysis for general spurious emissions for DC_39A_n41A	17.2.0
2021-09	RAN#93	R5-216019	0482	1	F	Update of TP analysis for general spurious emissions for DC_40A_n41A	17.2.0
2021-09	RAN#93	R5-216020	0507	1	F	Update of spurious emission TP analysis for Rel-16 EN-DC configuration DC_8A_n41A	17.2.0
2021-09	RAN#93	R5-216056	0472	1	F	Addition of TP for REFSENS for inter-band EN-DC 2CC and 3CC combos	17.2.0
2021-09	RAN#93	R5-216057	0488	1	F	Correction to TP analysis for reference sensitivity per EN-DC configuration	17.2.0
2021-09	RAN#93	R5-216058	0489	1	F	Correction to Annex D Principles for test point selection for EN-DC reference sensitivity test cases	17.2.0
2021-09	RAN#93	R5-216059	0490	1	F	Updating Test point analysis for DC_3A_n28A-n78A	17.2.0
2021-09	RAN#93	R5-216060	0491	1	F	Updating Test point analysis for DC_7A_n28A-n78A	17.2.0
2021-09	RAN#93	R5-216061	0493	1	F	Updating Test point analysis for DC_7A-20A_n28A	17.2.0
2021-09	RAN#93	R5-216062	0501	1	F	Defining TP analysis for MPR, SEM and ACLR for FR2 UL MIMO	17.2.0
2021-09	RAN#93	R5-216064	0500	1	F	Update_TP_analysis for Rel_16_DC_14A_n66A	17.2.0
2021-09	RAN#93	R5-216068	0494	1	F	Updating TP analysis for Absolute power tolerance for CA	17.2.0
2021-09	RAN#93	R5-216109	0506	1	F	TP analysis for ref sensitivity DC_48A_n66A	17.2.0
2021-09	RAN#93	R5-216142	0476	1	F	Correction to IE and UE capability for low PAPR DMRS in test point analysis	17.2.0
2021-12	RAN#94	R5-216513	0508	-	F	TP analysis update for FR1 6.2.3 AMPR NS_27	17.3.0
2021-12	RAN#94	R5-216516	0509	-	F	TP analysis update for IBNC EN-DC 6.2B.2.2_MPR 6.5B.2.2.1_SEM 6.5B.2.2.3_ACLR	17.3.0
2021-12	RAN#94	R5-216547	0511	-	F	TP analysis for FR2 DL 256QAM to Maximum input level	17.3.0
2021-12	RAN#94	R5-216548	0512	-	F	TP analysis for FR2 DL 256QAM to Maximum input level for CA	17.3.0
2021-12	RAN#94	R5-217164	0515	-	F	TP analysis for ref sensitivity for DC_66A_n2A	17.3.0
2021-12	RAN#94	R5-217165	0516	-	F	TP analysis for ref sensitivity for DC_66A_n78A	17.3.0
2021-12	RAN#94	R5-217166	0517	-	F	TP analysis for ref sensitivity for DC_66A_n71A	17.3.0
2021-12	RAN#94	R5-217190	0520	-	F	Test Point analysis for FR2 Tx spur emission coex CA test case	17.3.0
2021-12	RAN#94	R5-217301	0521	-	F	Addition of reference sensitivity TP analysis for DC_1A-20A_n28A	17.3.0
2021-12	RAN#94	R5-217302	0522	-	F	Addition of reference sensitivity TP analysis for DC_3A_n78C	17.3.0
2021-12	RAN#94	R5-217303	0523	-	F	Addition of reference sensitivity TP analysis for DC_20A_n28A-n78A	17.3.0
2021-12	RAN#94	R5-217306	0524	-	F	Editorial correction to Annex 2.10.3 test point selection EN-DC reference sensitivity	17.3.0

2021-12	RAN#94	R5-217307	0525	-	F	Update of TP analysis for general spurious emissions for DC_8A_n78A	17.3.0
2021-12	RAN#94	R5-217561	0526	-	F	Update of test point analysis for carrier leakage in FR2	17.3.0
2021-12	RAN#94	R5-217604	0527	-	F	Addition of TP analysis of V2X MOP 6.2E.1.x	17.3.0
2021-12	RAN#94	R5-218200	0532	-	F	TP analysis for ref sensitivity for DC_41A_n77A and DC_41A_n78A	17.3.0
2021-12	RAN#94	R5-218276	0513	1	F	Update TP analysis for Rel_16_DC_14A_n2A	17.3.0
2021-12	RAN#94	R5-218277	0514	1	F	Update TP analysis for Rel_16_DC_14A_n66A	17.3.0
2021-12	RAN#94	R5-218306	0528	1	F	Addition of TP analysis of V2X MPR 6.2E.2.x	17.3.0
2021-12	RAN#94	R5-218364	0510	1	F	Addition of TP analysis of A-MPR and ASE for NS_56	17.3.0
2021-12	RAN#94	R5-218409	0531	1	F	Update of test point analysis for relative power tolerance in FR2	17.3.0
2021-12	RAN#94	R5-218445	0518	1	F	TP analysis for ref sensitivity for DC_2A_n71A	17.3.0
2021-12	RAN#94	R5-218446	0519	1	F	TP analysis for ref sensitivity for DC_5A_n66A	17.3.0
2021-12	RAN#94	R5-218447	0530	1	F	TP analysis update for A-MPR and A-Spurious test cases	17.3.0
2021-12	RAN#94	R5-218487	0529	1	F	Update of TR 38.905 with EN DC A MPR test point analyses, NS_04	17.3.0
2022-03	RAN#95	R5-220321	0537	-	F	Adding Reference sensitivity Test point analysis for Rel-16 inter-band EN-DC FR1 two band combinations	17.4.0
2022-03	RAN#95	R5-220363	0541	-	F	Update TP analysis for Rel-17 DC_2A_n77A	17.4.0
2022-03	RAN#95	R5-220364	0542	-	F	Update TP analysis for Rel-17 DC_5A_n77A	17.4.0
2022-03	RAN#95	R5-220365	0543	-	F	Update TP analysis for Rel-17 DC_13A_n77A	17.4.0
2022-03	RAN#95	R5-220366	0544	-	F	Update TP analysis for Rel-17 DC_66A_n77A	17.4.0
2022-03	RAN#95	R5-220377	0545	-	F	Introduction of reference sensitivity test point analysis for DC_1A-n7A	17.4.0
2022-03	RAN#95	R5-220378	0546	-	F	Introduction of reference sensitivity test point analysis for DC_28A_n7A	17.4.0
2022-03	RAN#95	R5-220379	0547	-	F	Introduction of reference sensitivity test point analysis for DC_1A_n5A	17.4.0
2022-03	RAN#95	R5-220381	0548	-	F	Introduction of reference sensitivity test point analysis for DC_3A_n5A	17.4.0
2022-03	RAN#95	R5-220383	0549	-	F	Introduction of reference sensitivity test point analysis for DC_7A-n5A	17.4.0
2022-03	RAN#95	R5-220385	0550	-	F	Introduction of reference sensitivity test point analysis for DC_7A_n28A	17.4.0
2022-03	RAN#95	R5-220388	0552	-	F	Introduction of reference sensitivity test point analysis for DC_7A_n5A-n78A	17.4.0
2022-03	RAN#95	R5-220389	0553	-	F	Introduction of reference sensitivity test point analysis for DC_28A_n7A-n78A	17.4.0
2022-03	RAN#95	R5-221748	0555	1	F	Addition of Test Point analysis for FR1 Spurious emission for UE co-existence for DC_19_n1	17.4.0
2022-03	RAN#95	R5-221749	0556	1	F	Addition of Test Point analysis for FR1 Spurious emission for UE co-existence for DC_21_n1	17.4.0
2022-03	RAN#95	R5-220794	0558	-	F	TP analysis for 6.2D.1 for ULFPtx	17.4.0
2022-03	RAN#95	R5-220982	0561	-	F	Update of test point analysis for Adjacent Channel Selectivity for EN-DC within FR1	17.4.0
2022-03	RAN#95	R5-221115	0562	-	F	Updating TP analysis for FR1 AMPR for CA_n41A-n79A testing	17.4.0
2022-03	RAN#95	R5-221123	0563	-	F	Updating TP analysis for FR1 MPR for intra-band CA test case	17.4.0
2022-03	RAN#95	R5-221125	0564	-	F	Updating TP analysis for FR1 Absolute power tolerance CA test case	17.4.0
2022-03	RAN#95	R5-221127	0565	-	F	Updating TP analysis for FR1 ACLR for intra-band CA test case	17.4.0
2022-03	RAN#95	R5-221129	0566	-	F	Updating TP analysis for FR1 SEM for intra-band CA test case	17.4.0
2022-03	RAN#95	R5-221313	0573	-	F	TP analysis for ref sensitivity for DC_2A_n78A	17.4.0
2022-03	RAN#95	R5-221320	0575	-	F	TP analysis for ref sensitivity for 4 Rel-17 ENDC combos	17.4.0
2022-03	RAN#95	R5-221327	0577	-	F	TP analysis for ref sensitivity for DC_2A_n66A	17.4.0
2022-03	RAN#95	R5-221602	0580	-	F	Correction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_8A_n3A	17.4.0
2022-03	RAN#95	R5-221603	0581	-	F	Correction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_20A_n3A	17.4.0
2022-03	RAN#95	R5-221631	0583	-	F	Update of spurious emission TP analysis for DC_3A_n41A	17.4.0
2022-03	RAN#95	R5-221632	0584	-	F	Update of spurious emission TP analysis for DC_8A_n41A	17.4.0
2022-03	RAN#95	R5-221633	0585	-	F	Update of spurious emission TP analysis for DC_25A_n41A	17.4.0
2022-03	RAN#95	R5-221634	0582	-	F	Update of spurious emission TP analysis for DC_26A_n41A	17.4.0
2022-03	RAN#95	R5-221635	0586	-	F	Update of spurious emission TP analysis for DC_39A_n41A	17.4.0
2022-03	RAN#95	R5-221636	0587	-	F	Update of spurious emission TP analysis for DC_40A_n41A	17.4.0
2022-03	RAN#95	R5-221750	0574	1	F	Update TP analysis for EVM	17.4.0
2022-03	RAN#95	R5-221751	0576	1	F	Test Point analysis for FR2 Tx spur emission UL MIMO tests	17.4.0
2022-03	RAN#95	R5-221752	0578	1	F	Addition of reference sensitivity checklist for CA reference sensitivity test point analysis	17.4.0
2022-03	RAN#95	R5-221753	0579	1	F	Modification of test point analysis clause for FR1 NR CA	17.4.0
2022-03	RAN#95	R5-221774	0533	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_8A_n20A	17.4.0
2022-03	RAN#95	R5-221775	0534	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_20A_n7A	17.4.0
2022-03	RAN#95	R5-221776	0535	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_28A_n5A	17.4.0

2022-03	RAN#95	R5-221777	0536	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_40A_n79A	17.4.0
2022-03	RAN#95	R5-221778	0551	1	F	Introduction of reference sensitivity test point analysis for DC_7A_n78A	17.4.0
2022-03	RAN#95	R5-221779	0567	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_1A_n5A	17.4.0
2022-03	RAN#95	R5-221780	0568	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_1A_n7A	17.4.0
2022-03	RAN#95	R5-221781	0569	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_3A_n5A	17.4.0
2022-03	RAN#95	R5-221782	0570	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_7A_n5A	17.4.0
2022-03	RAN#95	R5-221783	0571	1	F	Introduction of spurious emission TP analysis for Rel-16 EN-DC configuration DC_28A_n7A	17.4.0
2022-03	RAN#95	R5-221829	0557	1	F	TP analysis for 6.2E.2.2 MPR for concurrent operation	17.4.0
2022-03	RAN#95	R5-221841	0559	1	F	TP analysis for 6.2D.2 for ULFP Tx	17.4.0

History

Document history		
V17.4.0	May 2022	Publication