

ETSI TS 100 963 V4.1.0 (2001-06)

Technical Specification

Digital cellular telecommunications system (Phase 2); Comfort Noise Aspects for Full Rate Speech Traffic Channels (3GPP TS 06.12 version 4.1.0 GSM Phase 2)



Reference

DTS/TSGS-040612P

Keywords

GSM

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at <http://www.etsi.org/tb/status/>

If you find errors in the present document, send your comment to:
editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2001.

All rights reserved.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under www.etsi.org/key.

Contents

Foreword	4
Introduction.....	4
0.1 Scope	5
0.2 References	5
0.3 Definitions and abbreviations	5
1 General.....	5
2 Functions on the transmit side	6
2.1 Background acoustic noise evaluation	6
2.2 SID-frame encoding	6
3 Functions on the receive side.....	6
3.1 Comfort noise generation and updating	7
Annex A (informative): Change history.....	8

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

This TS specifies the comfort noise aspect for full rate speech traffic channels for the Digital cellular telecommunications system GSM (Phase 2).

0.1 Scope

This technical specification gives the detailed requirements for the correct operation of the background acoustic noise evaluation, noise parameter encoding/decoding and comfort noise generation in GSM Mobile Stations and Base Station Systems during Discontinuous Transmission (DTX) on full rate speech traffic channels.

The requirements described in this technical specification are mandatory for implementation in all GSM Mobile Stations. The receiver requirements are mandatory for implementation in all GSM Base Station Systems, the transmitter requirements only for those where downlink DTX will be used.

0.2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] GSM 01.04 (ETR 100): "European digital cellular telecommunication system (Phase 2); Definitions, abbreviations and acronyms".
- [2] GSM 05.03 (ETS 300 575): "European digital cellular telecommunication system (Phase 2); Channel coding".
- [3] GSM 06.10 (ETS 300 580-2): "European digital cellular telecommunication system (Phase 2); Full rate speech transcoding".
- [4] GSM 06.31 (ETS 300 580-5): "European digital cellular telecommunication system (Phase 2); Discontinuous Transmission (DTX) for full rate speech traffic channel".

0.3 Definitions and abbreviations

Definitions and abbreviations used in this specification are listed in GSM 01.04.

1 General

The definitions of terms used in this technical specification can be found in GSM 06.31.

The overall operation of Discontinuous Transmission is described in GSM 06.31.

A basic problem when using DTX is that the background acoustic noise, which is transmitted together with the speech, would disappear when the radio transmission is cut, resulting in a modulation of the background noise. Since the DTX switching can take place rapidly, it has been found that this effect can be very annoying for the listener - especially in a car environment with high background noise levels. In bad cases the speech may be hardly intelligible.

This technical specification specifies the way to overcome this problem by generating on the receive side synthetic noise similar to the transmit side background noise. The parameters of this so called comfort noise are estimated on the transmit side and transmitted to the receive side before the radio transmission is cut and at a regular low rate afterwards. This allows the comfort noise to adapt to the changes of the noise on the transmit side.

2 Functions on the transmit side

The comfort noise evaluation algorithm uses the unquantized block amplitude and Log Area Ratio (LAR) parameters of the full rate speech encoder, defined in section 4.2.15 and 4.2.6 of GSM 06.10. These parameters give information on the level and the spectrum of the background noise, respectively.

The evaluated comfort noise parameters are encoded into a special frame, called a SID (Silence Descriptor) frame, for transmission to the receive side.

The SID frame also serves to initiate the comfort noise generation on the receive side, as a SID frame is always sent at the end of a speech burst, ie before the radio transmission is cut.

The scheduling of SID or speech frames on the radio path is described in GSM 06.31.

2.1 Background acoustic noise evaluation

The comfort noise parameters to be encoded into a SID frame are calculated over $N=4$ consecutive frames marked with $VAD=0$, as follows:

The Log Area Ratio parameters shall be averaged according to the equation:

$$\text{mean (LAR}(i)) = 1/N \text{ SUM [n=1 to N] LAR[j-n]}(i) \quad i = 1,2..8$$

where $\text{LAR}[j](i)$ is the i 'th Log Area Ratio coefficient of the current frame j and $j-n$ indicates the previous frames.

The block amplitude parameter shall be averaged according to the equation:

$$\text{mean (xmax)} = 1/(4N) \text{ SUM [n=1 to N] SUM [i=1 to 4] xmax[j-n]}(i)$$

where $\text{xmax}[j](i)$ is the block amplitude in subsegment i of the current frame. The SID frame containing these averaged parameters is passed to the Radio Subsystem instead of frame number j .

2.2 SID-frame encoding

The SID-frame encoding algorithm exploits the fact that only some of the 260 bits in a frame are needed to code the comfort noise parameters. The other bits can then be used to mark the SID-frame by means of a fixed bit pattern, called the SID code word.

The log area ratio coefficients are replaced by the mean $\text{(LAR}(i))$ values defined above and encoded as described in GSM 06.10.

The block amplitude values are replaced by the mean (xmax) value defined above, repeated four times inside the frame and encoded as described in GSM 06.10.

The SID code word consists of 95 bits which are all zero. The bits of the SID code word are inserted in the SID field defined as the positions of those 95 bits of the encoded RPE-pulses X_{mc} , which are in the error protection class I (see GSM 05.03, table 2).

The remaining bits in the SID frame are set to zero. The use of these bits is for further study.

3 Functions on the receive side

The situations in which comfort noise shall be generated on the receive side are defined in GSM 06.31. Generally speaking, the comfort noise generation is started or updated whenever a valid SID frame is received.

3.1 Comfort noise generation and updating

The comfort noise generation procedure uses the RPE-LTP speech decoder algorithm defined in GSM 06.10.

When comfort noise is to be generated, then the various encoded parameters are set as follows:

The RPE pulses (X_{mcr}) are replaced by a locally generated random integer sequence, uniformly distributed between 1 and 6.

Also the grid position parameters (M_{cr}) are set to random integer values, uniformly distributed between 0 and 3.

The LTP gain values (b_{cr}) are set to 0.

The LTP lag values (N_{cr}) of the 4 subsegments are set to 40, 120, 40 and 120 respectively.

The 4 block amplitude values (X_{maxcr}) used are those received in the SID frame.

The log area ratio parameters (LAR_{cr}) used are those received in the SID frame.

With these parameters, the speech decoder now performs the standard operations described in GSM 06.10 and synthesizes comfort noise.

Updating of the comfort noise parameters occurs each time a valid SID frame is received, as described in GSM 06.31.

When updating the comfort noise, the parameters above should preferably be interpolated over a few frames to obtain smooth transitions.

Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2001-06	12	SP-010304	A001		Corrections of the formula for averaging Xmax	4.0.4	4.1.0

History

Document history		
V4.1.0	June 2001	Publication