# ETSITS 101 376-1-2 V2.2.1 (2005-03)

Technical Specification


**GEO-Mobile Radio Interface Specifications (Release 2)** 

**General Packet Radio Service;** 

Part 1: General specifications;

Sub-part 2: Introduction to the GMR-1 family;

**GMPRS-1 01.201** 



#### Reference

#### RTS/SES-00222-1-2

#### Keywords

GMPRS, GMR, GPRS, GSM, GSO, MES, mobile, MSS, radio, satellite, S-PCN

#### **ETSI**

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

#### Important notice

Individual copies of the present document can be downloaded from: <u>http://www.etsi.org</u>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<a href="http://portal.etsi.org/tb/status/status.asp">http://portal.etsi.org/tb/status/status.asp</a></a>

#### **Copyright Notification**

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005.
All rights reserved.

**DECT**<sup>TM</sup>, **PLUGTESTS**<sup>TM</sup> and **UMTS**<sup>TM</sup> are Trade Marks of ETSI registered for the benefit of its Members. **TIPHON**<sup>TM</sup> and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members. **3GPP**<sup>TM</sup> is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

## Contents

Intell	lectual Property Rights	4
	word	
[ntro	duction	5
1	Scope	6
2	References	6
3 3.1 3.2	Definitions and abbreviations.  Definitions	6
4 4.1 4.2 4.3 4.4 4.5	GEO mobile radio interface specifications (GMR-1) Scope of the GMR-1 family of specifications GMR-1 Release 1 and Release 2 Contents of the GMR-1 document series Numbering of GMR-1 specifications Contents of GMR-1 family of specifications	7 7 7
5	Terminology cross reference	8
Anne	ex A (informative): Contents of Release 1 of the GMR-1 family	9
<b>A</b> .1	Contents of the 01-series	9
A.2	Contents of the 02-series	9
A.3	Contents of the 03-series	10
A.4	Contents of the 04-series	11
A.5	Contents of the 05-series	12
A.6	Contents of the 06-series	12
<b>A</b> .7	Contents of the 07-series	12
Anno	ex B (informative): Contents of Release 2 of the GMR-1 family (GMPRS-1)	13
B.1	Contents of the 01-series	13
B.2	Contents of the 02-series	13
B.3	Contents of the 03-series	13
B.4	Contents of the 04-series	14
B.5	Contents of the 05-series	14
B.6	Contents of the 07-series	14
B.7	Contents of the 08-series	14
B.8	Contents of the 09-series	15
Histo	n <b>rv</b>	16

### Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

#### **Foreword**

This Technical Specification (TS) has been produced by ETSI Technical Committee Satellite Earth Stations and Systems (SES).

The contents of the present document are subject to continuing work within TC-SES and may change following formal TC-SES approval. Should TC-SES modify the contents of the present document it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version 2.m.n

where:

- the third digit (n) is incremented when editorial only changes have been incorporated in the specification;
- the second digit (m) is incremented for all other types of changes, i.e. technical enhancements, corrections, updates, etc.

The present document is part 1, sub-part 2 of a multi-part deliverable covering the GEO-Mobile Radio Interface Specifications, as identified below:

```
Part 1: "General specifications":
```

```
Sub-part 1:
                     "Abbreviations and acronyms";
     Sub-part 2:
                     "Introduction to the GMR-1 family";
     Sub-part 3:
                     "General System Description";
Part 2:
           "Service specifications";
Part 3:
           "Network specifications";
Part 4:
           "Radio interface protocol specifications";
Part 5:
           "Radio interface physical layer specifications";
Part 6:
           "Speech coding specifications";
Part 7:
           "Terminal adaptor specifications".
```

#### Introduction

GMR stands for GEO (Geostationary Earth Orbit) Mobile Radio interface, which is used for mobile satellite services (MSS) utilizing geostationary satellite(s). GMR is derived from the terrestrial digital cellular standard GSM and supports access to GSM core networks.

The present document is part of the GMR Release 2 specifications. Release 2 specifications are identified in the title and can also be identified by the version number:

- Release 1 specifications have a GMR-1 prefix in the title and a version number starting with "1" (V1.x.x.).
- Release 2 specifications have a GMPRS-1 prefix in the title and a version number starting with "2" (V2.x.x.).

The GMR release 1 specifications introduce the GEO-Mobile Radio interface specifications for circuit mode mobile satellite services (MSS) utilizing geostationary satellite(s). GMR release 1 is derived from the terrestrial digital cellular standard GSM (phase 2) and it supports access to GSM core networks.

The GMR release 2 specifications add packet mode services to GMR release 1. The GMR release 2 specifications introduce the GEO-Mobile Packet Radio Service (GMPRS). GMPRS is derived from the terrestrial digital cellular standard GPRS (included in GSM Phase 2+) and it supports access to GSM/GPRS core networks.

Due to the differences between terrestrial and satellite channels, some modifications to the GSM standard are necessary. Some GSM specifications are directly applicable, whereas others are applicable with modifications. Similarly, some GSM specifications do not apply, while some GMR specifications have no corresponding GSM specification.

Since GMR is derived from GSM, the organization of the GMR specifications closely follows that of GSM. The GMR numbers have been designed to correspond to the GSM numbering system. All GMR specifications are allocated a unique GMR number. This GMR number has a different prefix for Release 2 specifications as follows:

- Release 1: GMR-n xx.zyy.
- Release 2: GMPRS-n xx.zyy.

#### where:

- xx.0yy (z = 0) is used for GMR specifications that have a corresponding GSM specification. In this case, the numbers xx and yy correspond to the GSM numbering scheme.
- xx.2yy (z = 2) is used for GMR specifications that do not correspond to a GSM specification. In this case, only the number xx corresponds to the GSM numbering scheme and the number yy is allocated by GMR.
- n denotes the first (n = 1) or second (n = 2) family of GMR specifications.

A GMR system is defined by the combination of a family of GMR specifications and GSM specifications as follows:

• If a GMR specification exists it takes precedence over the corresponding GSM specification (if any). This precedence rule applies to any references in the corresponding GSM specifications.

NOTE: Any references to GSM specifications within the GMR specifications are not subject to this precedence rule. For example, a GMR specification may contain specific references to the corresponding GSM specification.

• If a GMR specification does not exist, the corresponding GSM specification may or may not apply. The applicability of the GSM specifications is defined in the present document.

### 1 Scope

The present document gives a general introduction to the GEO Mobile Radio interface (GMR) specifications in the GMR-1 family.

The present document introduces both the Release 1 and the Release 2 specifications.

The GMR-1 specifications are organized into series that correspond to the organization of the ETSI GSM technical specifications. Clause 4 of the present document defines the contents of each GMR-1 series and shows how the individual GMR-1 specifications relate to their GSM counterparts. Clause 5 of the present document defines the relationship between GMR-1 terminology and the GSM terminology.

#### 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication and/or edition number or version number) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <a href="http://docbox.etsi.org/Reference">http://docbox.etsi.org/Reference</a>.

[1] GMPRS-1 01.004 (ETSI TS 101 376-1-1): "GEO-Mobile Radio Interface Specifications (Release 2); General Packet Radio Service; Part 1: General specifications; Sub-part 1: Abbreviations and acronyms".

[2] GMR-1 03.001 (ETSI TS 101 376-3-1): "GEO-Mobile Radio Interface Specifications; Part 3: Network specifications; Sub-part 1: Network Functions".

NOTE: This is a reference to a GMR-1 Release 1 specification. See the introduction for more details.

### 3 Definitions and abbreviations

#### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**GSM applies:** this feature is identical to GSM and hence the associated GSM specification applies

GMR specific: this GMR specification describes a new GMR feature that has no equivalent feature in GSM

Replaces GSM: the GMR specification is a replacement for the associated GSM specification

NOTE: The GMR specification may make reference to the associated GSM specification.

#### 3.2 Abbreviations

For the purposes of the present document, the abbreviations defined in GMPRS-1 01.004 [1] apply.

## 4 GEO mobile radio interface specifications (GMR-1)

#### 4.1 Scope of the GMR-1 family of specifications

The GEO-Mobile Radio Interface Specifications (GMR-1) is a family of specifications which specify the requirements for implementing the GMR-1 radio interface for Mobile Earth Stations (MESs) communicating using Geosynchronous Earth Orbit satellites and interworking into a GSM core network. The MES may be a handheld, mobile or fixed terminal.

The GMR-1 specifications are based upon the GSM (Global System for Mobile Communications) specifications. The GMR specifications define the differences (i.e. the modifications) relative to the GSM specifications that deal with the different system requirements such as the path losses and delays associated with satellite communications using a Geosynchronous Earth Orbit (GEO) satellite.

#### 4.2 GMR-1 Release 1 and Release 2

The GMR-1 family of specifications is organized into two releases:

**Release 1 specifications.** This release of specifications defines the GMR-1 circuit mode services, which are based on the GSM phase 2 circuit mode services. The contents of the Release 1 family of specifications are defined in annex A.

**Release 2 specifications**. This release of specifications define the GMR-1 packet mode services (GMPRS-1) which are based on the GSM phase 2+ packet mode services (GPRS). The contents of the Release 2 family of specifications are defined in annex B.

#### 4.3 Contents of the GMR-1 document series

The GMR-1 family of specifications are organized in document series that correspond the GSM document structure as follows:

- 01-series; General specifications.
- 02-series; Service specifications.
- 03-series; Network specifications.
- 04-series; Radio interface protocol specifications.
- 05-series; Radio interface physical layer specifications.
- 06-series; Speech coding specifications.
- 07-series; Terminal adaptor specifications.

### 4.4 Numbering of GMR-1 specifications

The GMR-1 specifications follow the GMR numbering rules as described in the Introduction clause to the present document. The GMR document numbering is based on the GSM numbering, except that the GMR documents use a 3-digit document number after the 2-digit series number.

With the exception of GMR-1 specific documents (i.e. those for which no equivalent GSM specification exists) the GMR document numbers within each series are aligned with the equivalent GSM document numbers and this means that these GMR-1 specifications can be directly associated with the corresponding GSM specification. For example, GMR-1 03.001 [2] is associated with GSM 03.01.

#### 4.5 Contents of GMR-1 family of specifications

The complete contents of the GMR-1 Release 1 specifications are given in annex A.

The complete contents of the GMR-1 Release 2 (GMPRS) specifications are given in annex B.

Where appropriate the GMR-1 specifications include references to the corresponding GSM specifications. The relationship between the GMR-1 specifications and the corresponding GSM specifications is defined in annexes A and B using the terminology defined below.

Table 1: GMR-1 specifications

Terminology	Definition
GSM applies	This feature is identical to GSM and hence the associated GSM specification applies.
GMR specific	This GMR specification describes a new GMR feature that has no equivalent feature in GSM.
Replaces GSM	The GMR specification is a replacement for the associated GSM specification. The GMR
	specification may make reference to the associated GSM specification.

NOTE 1: The associated GSM specification (if any) is directly indicated by the document number as described in clause 4.3.

NOTE 2: In the case of "GSM applies" or "Replaces GSM" the terminology translation defined in clause 5 should be applied when reading the associated GSM specification.

## 5 Terminology cross reference

This clause provides a terminology cross-reference table that provides a cross-reference between a series of common GSM terms and the equivalent terms that are used in the GMR-1 specifications.

The terminology translations defined in this table should be applied when reading any of the associated GSM specifications (as defined in clause 4) or when reading any GSM specifications that are referenced directly or indirectly by a GMR-1 specification.

GSM term	GMR-1 term
BSC (Base Station Controller)	GSC (Gateway Station Controller)
BSS (Base Station System)	Release 1: GSS (Gateway Station System)
	Release 2: BSS (same as GSM)
BTS (Base Transceiver Station)	GTS (Gateway Transceiver Station)
Cell	Spot beam
GSM	GMR-1
GSM PLMN	GMR PLMN
GSM GPRS	GMPRS
ME (Mobile Equipment)	MES-ME (Mobile Earth Station - Mobile
	Equipment). (See note.)
MS (Mobile Station)	MES-MS (Mobile Earth Station - Mobile
	Station). (See note.)
MSC (Mobile Switching Centre)	GSS-MSC (Gateway Station Subsystem-Mobile
	Switching Centre)
	ES-MS are specific terms that indicate a terminal without tively. In cases where this distinction is not required, the

## Annex A (informative): Contents of Release 1 of the GMR-1 family

### A.1 Contents of the 01-series

GMR number	ETSI number	GSM number	Short title	Comment
01.004	TS 101 376-1-1		Abbreviations and acronyms	Replaces GSM
01.201	TS 101 376-1-2		Introduction to the GMR-1 family	GMR specific
01.202	TS 101 376-1-3		General System Description	GMR specific

## A.2 Contents of the 02-series

GMR number	ETSI number	GSM number	Short title	Comment
		02.01	Principles of Telecommunication Services Supported by a GSM Public Land Mobile Network (PLMN)	GSM applies
		02.02	Bearer Services (BS) Supported by a GSM Public Land Mobile Network (PLMN)	GSM applies
		02.03	Teleservices Supported by a GSM Public Land Mobile Network (PLMN)	GSM applies
		02.04	General on Supplementary Services	GSM applies
		02.09	Security Aspects	GSM applies
02.011	TS 101 376-2-1		Service Accessibility	Replaces GSM
		02.16	International Mobile Station Equipment Identities (IMEI)	GSM applies
		02.17	Subscriber Identity Modules, Functional Characteristics	GSM applies
		02.40	Procedures for Call Progress Indications	GSM applies
		02.41	Operator Determined Barring	GSM applies
		02.81	Line Identification Supplementary Services- Stage 1	GSM applies
		02.82	Call Forwarding (CF) Supplementary Services - Stage 1	GSM applies
		02.83	Call Waiting (CW) and Call Hold (HOLD) Supplementary Services - Stage 1	GSM applies
		02.84	MultiParty (MPTY) Supplementary Services - Stage 1	GSM applies
		02.85	Closed User Group (CUG) Supplementary Services - Stage 1	GSM applies
		02.88	Call Barring (CB) Supplementary Services - Stage 1	GSM applies
		02.90	Stage 1 Decision of Unstructured Supplementary Service Data (USSD)	GSM applies

# A.3 Contents of the 03-series

GMR number	ETSI number	GSM number	Short title	Comment
03.001	TS 101 376-3-1		Network Functions	Replaces GSM
03.002	TS 101 376-3-2		Network Architecture	Replaces GSM
03.003	TS 101 376-3-3		Numbering, addressing and identification	Replaces GSM
		03.04	Signalling Requirements Relating to Routing of Calls to Mobile Subscribers	GSM applies
		03.07	Restoration Procedures	GSM applies
03.008	TS 101 376-3-4		Organization of Subscriber Data	Replaces GSM
		03.10	GMR network connection types	GSM applies
03.011	TS 101 376-3-5		Technical realization of supplementary services	Replaces GSM
03.012	TS 101 376-3-6		Location registration and position identification procedures	Replaces GSM
03.013	TS 101 376-3-7		Discontinuous Reception (DRX) in the GMR-1 system	Replaces GSM
03.014	TS 101 376-3-8		Support of Dual Tone Multi-Frequency signalling (DTMF) via the GMR-1 system	Replaces GSM
		03. 15	Technical Realization of Operator Determined Barring	GSM applies
		03.16	Subscriber Data Management	GSM applies
03.020	TS 101 376-3-9		Security related network functions	Replaces GSM
03.022	TS 101 376-3-10		Functions Related to the Mobile Earth Station (MES) in Idle Mode	Replaces GSM
		03.38	Alphabets and Language Specific Information for GSM	GSM applies
03.040	TS 101 376-3-11		Technical realization of the Short Message Service (SMS) Point-to-Point (PP)	Replaces GSM
03.041	TS 101 376-3-12		Technical realization of the Short Message Service Cell Broadcast (SMSCB)	Replaces GSM
03.045	TS 101 376-3-13		Technical realization of group 3 facsimile using transparent mode of transmission	Replaces GSM
03.050	TS 101 376-3-14		Transmission planning aspects of the speech service in the GMR-1 system	Replaces GSM
		0370	Routing of Calls to/from Public Data Networks (PDN)	GSM applies
03.081	TS 101 376-3-15		Line identification supplementary services - Stage 2	Replaces GSM
		03.82	Call Forwarding (CF) Supplementary Services - Stage 2	GSM applies
		03.83	Call Waiting (CW) and Call Hold (HOLD) Supplementary Services - Stage 2	GSM applies
		03.84	Multi Party (MPTY) Supplementary Services - Stage 2	GSM applies
		03.85	Closed user Group (CUG) Supplementary Services - Stage 2	GSM applies
03.088	TS 101 376-3-16		Call Barring (CB) supplementary services - Stage 2	Replaces GSM
03.090	TS 101 376-3-17		Unstructured Supplementary Service Data (USSD) - Stage 2	Replaces GSM
03.296	TS 101 376-3-18		Terminal to Terminal Calls - Stage 2	GMR specific
03.297	TS 101 376-3-19		Technical realization of optimal routing	GMR specific
03.298	TS 101 376-3-20		Technical realization of high-penetration alerting	GMR specific
03.299	TS 101 376-3-21		Position reporting services: Stage 2 service description	GMR specific

# A.4 Contents of the 04-series

GMR number	ETSI number	<b>GSM</b> number	Short title	Comment
04.001	TS 101 376-4-1		Mobile Station - Base Station System (MS -	Replaces GSM
			BSS) Interface General Aspects and Principles	
04.002	TS 101 376-4-2		GSM Public Land Mobile Network (PLMN)	Replaces GSM
			Access Reference Configuration	
04.003	TS 101 376-4-3		Mobile Station - Base Station System (MS -	Replaces GSM
			BSS) Interface Channel Structures and Access	
0.4.00.4	TO 101 070 1 1		Capabilities	5 1 0014
04.004	TS 101 376-4-4		Layer 1 - General Requirements	Replaces GSM
04.005	TS 101 376-4-5		Data Link (DL) Layer General Aspects	Replaces GSM
04.006	TS 101 376-4-6		Mobile Station - Base Stations System (MS -	Replaces GSM
			BSS) Interface Data Link (DL) Layer	
	<b></b>		Specification	
04.007	TS 101 376-4-7		Mobile Radio Interface Signalling Layer 3 - General Aspects	Replaces GSM
04.008	TS 101 376-4-8		Mobile Radio Interface - Layer 3 Specification	Replaces GSM
04.000	10 101 070 40	04.10	Mobile Radio Interface Layer 3 -	GSM applies
		04.10	Supplementary Services Specification -	GOW applies
			General Aspects	
		04.11	Point-to-Point (PP) Short Message Service	GSM applies
		0	(SMS) Support on Mobile Radio Interface	Com applico
		04.12	Short Message Service Cell Broadcast	GSM applies
		02	(SMSCB) Support on the Mobile Radio	Com applico
			Interface	
04.013	TS 101 376-4-9		Performance Requirements on Mobile Radio	Replaces GSM
			Interface	
04.021	TS 101 376-4-10		Rate Adaptation on the Mobile Station - Base	Replaces GSM
			Station System (MS-BSS) Interface	•
04.022	TS 101 376-4-11		Radio Link Protocol (RLP) for Data and	Replaces GSM
			Telematic Services on the (MS-BSS) Interface	
			and the Base Station System - Mobile-services	
			Switching Centre (BSS-MSC) Interface	
		04.80	Mobile Radio Interface Layer 3 -	GSM applies
			Supplementary Services Specification Formats	
			and Coding	
		04.81	Line Identification Supplementary Services - Stage 3	GSM applies
		04.82	Call Forwarding (CF) Supplementary Services -	GSM applies
			Stage 3	pp
		04.83	Call Waiting (CW) and Call Hold (HOLD)	GSM applies
			Supplementary Services - Stage 3	11
		04.84	Multi Party (MPTY) Supplementary Services -	GSM applies
			Stage 3	
		04.85	Closed User Group (CUG) Supplementary	GSM applies
			Services - Stage 3	• •
		04.88	Call Barring (CB) Supplementary Services -	GSM applies
			Stage 3	
		04.90	Unstructured Supplementary Service Data	GSM applies
			(USSD)	• •

## A.5 Contents of the 05-series

GMR number	ETSI number	GSM number	Short title	Comment
05.001	TS 101 376-5-1		Physical Layer on the Radio Path (General	Replaces GSM
			Description)	
05.002	TS 101 376-5-2		Multiplexing and Multiple Access on the Radio	Replaces GSM
			Path	
05.003	TS 101 376-5-3		Channel Coding	Replaces GSM
05.004	TS 101 376-5-4		Modulation	Replaces GSM
05.005	TS 101 376-5-5		Radio Transmission and Reception	Replaces GSM
05.008	TS 101 376-5-6		Radio Subsystem Link Control	Replaces GSM
05.010	TS 101 376-5-7		Radio Subsystem Synchronization	Replaces GSM

## A.6 Contents of the 06-series

GMR number	ETSI number	GSM number	Short title	Comment
06.001	TS 101 376-6-1		Speech Processing Functions	Replaces GSM
06.010	TS 101 376-6-2		Vocoder: Speech Transcoding	Replaces GSM
06.011	TS 101 376-6-3		Vocoder: Substitution and Muting of Lost	Replaces GSM
			Frames	
06.012	TS 101 376-6-4		Vocoder: Comfort Noise Aspects	Replaces GSM
06.031	TS 101 376-6-5		Vocoder: Discontinuous Transmission (DTX)	Replaces GSM
06.032	TS 101 376-6-6		Vocoder: Voice Activity Detection (VAD)	Replaces GSM

## A.7 Contents of the 07-series

GMR number	ETSI number	GSM number	Short title	Comment
07.001	TS 101 376-7-1		General on Terminal Adaptation Functions (TAF) for Mobile Earth Stations (MES)	Replaces GSM
07.002	TS 101 376-7-2		Terminal Adaptation Functions (TAF) for Services Using Asynchronous Bearer Capabilities	Replaces GSM
07.003	TS 101 376-7-3		Terminal Adaptation Functions (TAF) for Services Using Synchronous Bearer Capabilities	Replaces GSM

## Annex B (informative): Contents of Release 2 of the GMR-1 family (GMPRS-1)

### B.1 Contents of the 01-series

GMR number	ETSI number	GSM number	Short title	Comment	
01.004	TS 101 376-1-1	01.04	Abbreviations and acronyms	GSM applies + GMPRS specific	
				(see note)	
01.201	TS 101 376-1-2		Introduction to the GMR-1 family	GMPRS specific	
		01.60	GPRS Requirements	GSM applies	
		01.61	GPRS Ciphering Algorithm Requirements	GSM applies	
NOTE: GMPRS-1 specific abbreviations are contained in GMPRS-1 01.004 (Release 2 specification).					

### B.2 Contents of the 02-series

GMR number	ETSI number	GSM number	Short title	Comment
		02.09	Security Aspects	GSM applies
		02.16	International Mobile Station Equipment Identities	GSM applies
			(IMEI)	
		02.17	Subscriber Identity Modules, Functional	GSM applies
			Characteristics	
		02.60	General Packet Radio Service Stage 1	GSM applies
			Description	

## B.3 Contents of the 03-series

<b>GMR</b> number	ETSI number	GSM number	Short title	Comment
		03.01	Network functions	GSM applies
		03.02	Network architecture	GSM applies
03.003	TS 101 376-3-3		Numbering, addressing and identification	Replaces GSM
		03.20	Security related network functions	GSM applies
03.022	TS 101 376-3-10		Functions Related to the Mobile Earth Station (MES) in Idle Mode	Replaces GSM
		03.60	General Packet Radio Service (GPRS) Service description; Stage 2	GSM applies
03.064	TS 101 376-3-22		General Packet Radio Service (GPRS); Overall description of the GPRS radio interface; Stage 2	Replaces GSM
03.297	TS 101 376-3-19		Optimal Routing technical realization	GMR specific

### B.4 Contents of the 04-series

GMR number	ETSI number	GSM number	Short title	Comment
04.007	TS 101 376-4-7		Mobile Radio Interface Signalling Layer 3 -	Replaces GSM
			General Aspects	
04.008	TS 101 376-4-8		Mobile Radio Interface - Layer 3 Specification	Replaces GSM
04.060	TS 101 376-4-12		General Packet Radio Service (GPRS); Mobile	Replaces GSM
			Station (MS) - Base Station System (BSS)	
			interface; Radio Link Control/ Medium Access	
			Control (RLC/MAC) protocol	
		04.64	General Packet Radio Service (GPRS); Mobile	GSM applies
			Station - Serving GPRS Support Node (MS-SGSN)	
			Logical Link Control (LLC) layer specification	
		04.65	General Packet Radio Service (GPRS); Mobile	GSM applies
			Station (MS) - Serving GPRS Support Node	
			(SGSN); Subnetwork Dependent Convergence	
			Protocol (SNDCP)	

## B.5 Contents of the 05-series

GMR number	ETSI number	GSM number	Short title	Comment
05.002	TS 101 376-5-2		Multiplexing and Multiple Access on the Radio	Replaces GSM
			Path	
05.003	TS 101 376-5-3		Channel Coding	Replaces GSM
05.004	TS 101 376-5-4		Modulation	Replaces GSM
05.005	TS 101 376-5-5		Radio Transmission and Reception	Replaces GSM
05.008	TS 101 376-5-6		Radio Subsystem Link Control	Replaces GSM
05.010	TS 101 376-5-7		Radio Subsystem Synchronization	Replaces GSM

## B.6 Contents of the 07-series

GMR number	ETSI number	GSM number	Short title	Comment
		07.60	General Packet Radio Service (GPRS); Mobile	GSM applies
			Station (MS) supporting GPRS	

## B.7 Contents of the 08-series

<b>GMR</b> number	ETSI number	<b>GSM</b> number	Short title	Comment
		08.14	General Packet Radio Service (GPRS); Base	GSM applies
			Station System (BSS) - Serving GPRS Support	
			Node (SGSN) interface; Gb Interface Layer 1	
		08.16	General Packet Radio Service (GPRS); Base	GSM applies
			Station System (BSS) - Serving GPRS Support	
			Node (SGSN) Interface; Network Service	
		08.18	General Packet Radio Service (GPRS); Base	GSM applies
			Station System (BSS) - Serving GPRS Support	
			Node (SGSN); BSS GPRS Protocol	

## B.8 Contents of the 09-series

GMR number	ETSI number	GSM number	Short title	Comment
		09.60	General Packet Radio Service (GPRS); GPRS	GSM applies
			Tunnelling Protocol GPT) across the Gn and Gp	
			Interface	

# History

Document history			
V2.1.1	March 2003	Publication	
V2.2.1	March 2005	Publication	