

ETSI TS 102 222 V11.0.0 (2018-07)



**Integrated Circuit Cards (ICC);  
Administrative commands  
for telecommunications applications  
(Release 11)**

---

**Reference**RTS/SCP-Tv110000

---

**Keywords**GSM, smart card, UMTS

---

**ETSI**

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

---

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

---

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M** logo is protected for the benefit of its Members.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

# Contents

|   |    |
|---|----|
| Intellectual Property Rights .....                              | 5  |
| Foreword.....   | 5  |
| Modal verbs terminology.....                                    | 5  |
| 1 Scope .....   | 6  |
| 2 References .....  | 6  |
| 2.1 Normative references .....                                  | 6  |
| 2.2 Informative references.....                                 | 7  |
| 3 Definitions, symbols and abbreviations .....                  | 7  |
| 3.1 Definitions.....  | 7  |
| 3.2 Symbols.....  | 8  |
| 3.3 Abbreviations .....   | 8  |
| 4 Mapping principles.....                                       | 8  |
| 5 Security architecture.....                                    | 8  |
| 6 Description of the functions and commands .....               | 9  |
| 6.0 Overview .....  | 9  |
| 6.1 Coding of the commands.....                                 | 9  |
| 6.2 TLV objects.....  | 9  |
| 6.3 CREATE FILE.....  | 9  |
| 6.3.1 Definition and scope .....                                | 9  |
| 6.3.2 Command message .....                                     | 10 |
| 6.3.2.0 Command coding .....                                    | 10 |
| 6.3.2.1 Parameters P1 and P2.....                               | 10 |
| 6.3.2.2 Data field sent in the command message .....            | 11 |
| 6.3.2.2.1 Creating a DF/ADF .....                               | 11 |
| 6.3.2.2.2 Creating an EF.....                                   | 13 |
| 6.3.3 Response message .....                                    | 15 |
| 6.3.3.1 Data field returned in the response message .....       | 15 |
| 6.3.3.2 Status conditions returned in the response message..... | 16 |
| 6.4 DELETE FILE .....   | 16 |
| 6.4.1 Definition and scope .....                                | 16 |
| 6.4.2 Command message .....                                     | 17 |
| 6.4.2.0 Command coding .....                                    | 17 |
| 6.4.2.1 Parameters P1 and P2.....                               | 17 |
| 6.4.2.2 Data field sent in the command message .....            | 17 |
| 6.4.3 Response message .....                                    | 17 |
| 6.4.3.1 Data field returned in the response message .....       | 17 |
| 6.4.3.2 Status conditions returned in the response message..... | 18 |
| 6.5 DEACTIVATE FILE .....                                       | 18 |
| 6.6 ACTIVATE FILE.....  | 18 |
| 6.7 TERMINATE DF.....   | 18 |
| 6.7.1 Definition and scope .....                                | 18 |
| 6.7.2 Command message .....                                     | 19 |
| 6.7.2.0 Command coding .....                                    | 19 |
| 6.7.2.1 Parameters P1 and P2.....                               | 19 |
| 6.7.2.2 Data field sent in the command message .....            | 19 |
| 6.7.3 Response message .....                                    | 19 |
| 6.7.3.1 Data field returned in the response message .....       | 19 |
| 6.7.3.2 Status conditions returned in the response message..... | 19 |
| 6.8 TERMINATE EF .....  | 20 |
| 6.8.1 Definition and scope .....                                | 20 |
| 6.8.2 Command message .....                                     | 20 |
| 6.8.2.0 Command coding .....                                    | 20 |
| 6.8.2.1 Parameters P1 and P2.....                               | 20 |

|  |   |           |
|--|---|-----------|
| 6.8.2.2  | Data field sent in the command message .....            | 20        |
| 6.8.3  | Response message .....                                  | 20        |
| 6.8.3.1  | Data field returned in the response message .....       | 20        |
| 6.8.3.2  | Status conditions returned in the response message..... | 21        |
| 6.9  | TERMINATE CARD USAGE.....                               | 21        |
| 6.9.1  | Definition and scope .....                              | 21        |
| 6.9.2  | Command message .....                                   | 21        |
| 6.9.2.0  | Command coding .....                                    | 21        |
| 6.9.2.1  | Parameters P1 and P2.....                               | 22        |
| 6.9.2.2  | Data field sent in the command message .....            | 22        |
| 6.9.3  | Response message .....                                  | 22        |
| 6.9.3.1  | Data field returned in the response message .....       | 22        |
| 6.9.3.2  | Status conditions returned in the response message..... | 22        |
| 6.10   | RESIZE FILE.....  | 22        |
| 6.10.1   | Definition and scope .....                              | 22        |
| 6.10.2   | Command message .....                                   | 24        |
| 6.10.2.0   | Command coding .....                                    | 24        |
| 6.10.2.1   | Data field sent in the command message .....            | 24        |
| 6.10.3   | Response message .....                                  | 26        |
| 6.10.3.1   | Data field returned in the response message .....       | 26        |
| 6.10.3.2   | Status conditions returned in the response message..... | 26        |
| 7  | Administrative files .....                              | 27        |
| 7.1  | EF <sub>S</sub> UME (SetUpMenu Elements) .....          | 27        |
| 7.2  | EF <sub>R</sub> MA (Remote Management Actions) .....    | 28        |
| <b>Annex A (informative): Change history .....</b> |   | <b>29</b> |
| History .....                                      |   | 31        |

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Smart Card Platform (SCP).

The contents of the present document are subject to continuing work within TC SCP and may change following formal TC SCP approval. If TC SCP modifies the contents of the present document, it will then be republished by ETSI with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 0 early working draft;
  - 1 presented to TC SCP for information;
  - 2 presented to TC SCP for approval;
  - 3 or greater indicates TC SCP approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document defines functions and syntax of a set of administrative commands for a telecommunication card.

The commands defined in the present document are compliant to the commands defined in the ISO/IEC 7816 [i.2] series where corresponding commands in ISO/IEC are available. The commands described in the present document are using parts of the functionality of the commands described in ISO/IEC 7816-3 [i.1]. The present document does not cover the internal implementation within the UICC and/or the external equipment.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

- In the case of a reference to a TC SCP document, a non specific reference implicitly refers to the latest version of that document in the same Release as the present document.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- |     |  |
|-----|--|
| [1] | Void.  |
| [2] | ISO/IEC 7816-4: "Identification cards - Integrated circuit cards - Part 4: Organisation, security and commands for interchange". |
| [3] | Void.  |
| [4] | Void.  |
| [5] | ETSI TS 102 221: "Smart cards; UICC-Terminal interface; Physical and logical characteristics (Release 6)".                       |
| [6] | Void.  |
| [7] | ETSI TS 101 220: "Smart cards; ETSI numbering system for telecommunication application providers (Release 6)".                   |
| [8] | ETSI TS 102 223: "Smart cards; Card Application Toolkit (CAT) (Release 6)".  |
| [9] | Void.  |

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

- In the case of a reference to a TC SCP document, a non specific reference implicitly refers to the latest version of that document in the same Release as the present document.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ISO/IEC 7816-3: "Identification cards -- Integrated circuit cards -- Part 3: Cards with contacts -- Electrical interface and transmission protocols".
- [i.2] ISO/IEC 7816 (all parts): "Identification cards -- Integrated circuit cards".

---

## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

**Access Conditions (AC):** set of security attributes associated to a file

**ADMInistrative (ADM):** access condition to an EF which is under the control of the authority which creates this file

**administrative command:** command modifying the internal properties of the file system of an UICC

**current directory:** latest directory (MF, DF or ADF) selected in the UICC

**current EF:** latest Elementary File (EF) selected in the UICC

**current file:** current EF, if an EF is selected, else the current directory

**Dedicated File (DF):** file containing Access Conditions (AC) and allocable memory

NOTE: It may be the parent of Elementary Files (EF) and/or Dedicated Files (DF).

**directory:** general name for MF, DF or ADF

**Elementary File (EF):** file containing Access Conditions (AC) and data

NOTE: It cannot be the parent of another file.

**File Identifier (ID):** each file (MF, DF, ADF or EF) has a file identifier consisting of 2 bytes

**Master File (MF):** mandatory unique DF representing the root of the file structure and containing Access Conditions (AC) and allocable memory

NOTE: It may be the parent of elementary files and/or dedicated files.

**record:** string of bytes handled as a whole by the UICC and terminal and referenced by a record number or a record pointer

**record number:** sequential and unique number within an EF, which identifies a record within an EF

NOTE: It is managed by the UICC.

**record pointer:** pointer, which addresses one record in an EF

**telecommunication card:** UICC mainly used for telecommunication applications

## 3.2 Symbols

For the purposes of the present document, the following symbols apply:

|                           |  |
|---------------------------|--|
| '                         | Single quotation is used to indicate hexadecimal notation. |
| '0' to '9' and 'A' to 'F' | The sixteen hexadecimal digits                             |
| b8 ... b1                 | Bits of one byte. b8 is the MSB, b1 the LSB                |

## 3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

|         |  |
|---------|--|
| AC      | Access Condition   |
| ADF     | Application Dedicated File                                 |
| AID     | Application IDentifier                                     |
| AM      | Access Mode  |
| AM_DO   | Access Mode Data Object                                    |
| APDU    | Application Protocol Data Unit                             |
| ATR     | Answer To Reset  |
| BER     | Basic Encoding Rule  |
| CLA     | CLAss  |
| DF      | Dedicated File (abbreviation formerly used for Data Field) |
| DO      | Data Object  |
| EF      | Elementary File  |
| FCP     | File Control Parameters                                    |
| FID     | File IDentifier  |
| ICC     | Integrated Circuit Card                                    |
| ID      | IDentifier   |
| IEC     | International Electrotechnical Commission                  |
| INS     | INstruction  |
| ISO     | International Organization for Standardization             |
| LCSI    | Life Cycle Status Information                              |
| LSB     | Least Significant Bit                                      |
| M       | Mandatory  |
| MF      | Master File  |
| MSB     | Most Significant Bit                                       |
| O       | Optional   |
| PIN     | Personal Identification Number                             |
| RFU     | Reserved for Future Use                                    |
| SFI     | Short (elementary) File Identifier                         |
| SIM     | Subscriber Identity Module                                 |
| SM      | Secure Messaging   |
| SW1/SW2 | Status Word 1/Status Word 2                                |
| TLV     | Tag Length Value   |

---

## 4 Mapping principles

UICC Cards compliant to the present document shall follow the rules of ETSI TS 102 221 [5] in clauses 7 and 10.

---

## 5 Security architecture

The general coding of security attributes assigned to files by use of the CREATE FILE command is as described in ETSI TS 102 221 [5].



## 6 Description of the functions and commands

### 6.0 Overview

A UICC supporting the command set based on the present document shall support the command as defined in the present document. However, it is up to the UICC to provide more functionality than described in the present document.

This clause gives a functional description of the commands, their respective responses, associated status conditions, error codes and their coding.

### 6.1 Coding of the commands

**Table 1: Coding of the commands**

| Command              | CLA  | INS  |
|----------------------|------|------|
| CREATE FILE          | '0X' | 'E0' |
| DELETE FILE          | '0X' | 'E4' |
| DEACTIVATE FILE      | '0X' | '04' |
| ACTIVATE FILE        | '0X' | '44' |
| TERMINATE DF         | '0X' | 'E6' |
| TERMINATE EF         | '0X' | 'E8' |
| TERMINATE CARD USAGE | '0X' | 'FE' |
| RESIZE FILE          | '8X' | 'D4' |

The coding of the value X for the CLA-bytes in table 1 shall be according to ISO/IEC 7816-4 [2].

All bytes specified as RFU shall be set to '00' and all bits specified as RFU shall be set to 0.

These are the basic commands under the assumption of no Secure Messaging (SM). If SM is used, the Lc and data field shall be adopted.

Other commands may be needed in order to execute the commands listed above (e.g. EXTERNAL AUTHENTICATE). If such commands are necessary, they shall be coded according to ISO/IEC 7816-4 [2].

### 6.2 TLV objects

All TLVs described in the present document are BER-TLVs as described in ETSI TS 101 220 [7] and shall be supported by the UICC.

The sequence of mandatory TLV objects within the data field of any command specified in the present document shall be as in the description of the command.

According to the requirements of the application, the mandatory list of TLVs may be appended by one of the Tags '85' (Proprietary Information Primitive, see ISO/IEC 7816-4 [2]) or 'A5' (Proprietary Information Constructed, see ISO/IEC 7816-4 [2]).

Tag '85' or Tag 'A5' may be appended by other TLVs described in the present document or by any ISO/IEC or application dependent optional TLV object if necessary for a particular application.

### 6.3 CREATE FILE

#### 6.3.1 Definition and scope

This function allows the creation of a new file under the current directory. The access condition for the CREATE FILE function of the current directory shall be fulfilled.

When creating an EF with linear fixed or cyclic structure the UICC shall directly create as many records as allowed by the requested file size.

After the creation of a DF, the current directory shall be on the newly created file. In case of an EF creation, the current EF shall be on the newly created file and the current directory is unchanged. After creation of an EF with linear fixed structure, the record pointer is not defined. After creation of an EF with cyclic structure, the current record pointer is on the last created record. After creation of an EF with BER TLV structure, the current tag pointer is undefined.

The memory space allocated shall be reserved for the created file.

If an ADF is created, some instance has to take care of the administration of the application, e.g. updating the EF<sub>DIR</sub> with the application ID. The CREATE FILE command does not take care of this administration by its own. The DF Name tag shall only provide in the command, if an ADF is created.

The CREATE FILE command shall initialize newly created EFs with 'FF'. The content of the whole newly created EF shall consist of bytes of this value. If, for another application, other default values are required, this default behaviour can be overwritten by specifying an appropriate TLV in the application dependent data TLV (tag '85' or 'A5') of the CREATE FILE command.

## 6.3.2 Command message

### 6.3.2.0 Command coding

The CREATE FILE command message is coded according to table 2.

**Table 2: CREATE FILE command message**

| Code       | Value                               |
|------------|-------------------------------------|
| CLA        | See table 1                         |
| INS        | See table 1                         |
| P1         | '00'                                |
| P2         | '00'                                |
| Lc         | Length of the subsequent data field |
| Data field | Data sent to the UICC               |
| Le         | Not present                         |

### 6.3.2.1 Parameters P1 and P2

P1 and P2 are set to '00' indicating: FileID and file parameters encoded in data.

### 6.3.2.2 Data field sent in the command message

#### 6.3.2.2.1 Creating a DF/ADF

**Table 3: Coding of the data field of the CREATE FILE command (in case of creation of a DF/ADF)**

| Value   | M/O/C        | Description  | Length             |
|---|--------------|--|--------------------|
| '62'  | M            | Tag: FCP Template  | 1 byte             |
| LL  |              | Length of FCP Template (next byte to the end)  | 1 or 2 bytes       |
| '82'  | M            | Tag: File Descriptor<br>File Descriptor byte followed by Data Coding Byte            | 1 byte             |
| '02'  |              | Length of File Descriptor  | 1 byte             |
|   |              | File Descriptor Byte indicating DF or ADF  | 1 byte             |
| '21'  |              | Data Coding Byte   | 1 byte             |
| '83'  | M            | Tag: File ID   | 1 byte             |
| '02'  |              | Length of File ID  | 1 byte             |
|   |              | File ID  | 2 bytes            |
| '84'  | C (see note) | Tag: DF Name (AID)   | 1 byte             |
| LL  |              | Length of DF Name (AID)  | 1 byte             |
|   |              | DF Name (AID)  | 1 byte to 16 bytes |
| '8A'  | M            | Life Cycle Status Information (LCSI)   | 1 byte             |
| '01'  |              | Length of the LCSI   | 1 byte             |
|   |              | Life Cycle Status Information  | 1 byte             |
| '8C'<br>'AB'<br>'8B'  | M            | Tag: Security Attributes: one of the following:<br>Compact<br>Expanded<br>Referenced | 1 byte             |
| LL  |              | Length of Security Attributes  | 1 byte             |
|   |              | Data for the Security Attributes   | W bytes            |
| '81'  | M            | Tag: Total File Size   | 1 byte             |
| LL, LL ≥ 2  |              | Length of Total File Size  | 1 byte             |
|   |              | Total File Size  | X bytes            |
| 'C6'  | M            | Tag: PIN Status Template DO  | 1 byte             |
| LL  |              | Length of PIN Status Template DO   | 1 byte             |
|   |              | PIN Status Template DO   | Y bytes            |
| '85' or<br>'A5'   | O            | Tag: Proprietary, application dependent  | 1 byte             |
| LL  |              | Length of application dependent data   | 1 byte             |
|   |              | Application dependent data   | Z bytes            |
| NOTE: Tag '84' shall only be present for an ADF, otherwise it is not present. |              |  |                    |

#### Tag '8C', Tag 'AB' or Tag '8B': Security Attributes

Exactly one of the tags shall be present.

At least the key references that are used to allow access during the operational phase of the UICC shall be supplied in the Security Attributes.

#### Tag '81': Total File Size

Amount of physical memory allocated for the DF or ADF. The amount of memory specifies, how much memory will be available within the currently created DF or ADF to create EFs or other DFs. It shall include the memory needed for structural information for these EFs and DFs. The size of the structural information for the created DF/ADF shall not be included.

Some card implementations support dynamic allocation of memory (memory is allocated for the whole UICC), and therefore will ignore this TLV object.

By specifying a value other than '0000' it is possible, to indicate the requested amount of physical memory for the content of a DF or an ADF. This amount is taken from the memory allocated for the current DF.

The behaviour of the UICC for a value equal to '0000' is for further study.

**Tag '82': File Descriptor with Data Coding Byte**

The File Descriptor Byte shall be coded as defined in ETSI TS 102 221 [5].

The data coding byte can be used differently according to ISO/IEC 7816-4 [2]. For the present document, the value '21' (proprietary) shall be used and shall not be interpreted by the UICC.

**Tag '84': DF Name**

The DF Name is a string of bytes which is used to uniquely identify an application dedicated file (ADF) in the card.

**Tag '8A': Life Cycle Status Information (LCSI)**

The Life Cycle Status Information shall be coded according to ETSI TS 102 221 [5].

This TLV specifies the status of the file after creation.

The initialization state can be used to set the file into a specific security environment for administrative purposes. See ACTIVATE FILE command.

**Tag 'C6': PIN Status Template DO**

The PIN Status Template DO shall be coded according to ETSI TS 102 221 [5].

## 6.3.2.2.2 Creating an EF

**Table 4: Coding of the data field of the CREATE FILE command (in case of the creation of an EF)**

| Value          | M/O/C             | Description   | Length            |
|----------------|-------------------|---|-------------------|
| '62'           | M                 | Tag: FCP Template   | 1 byte            |
| LL             |                   | Length of FCP Template (next byte to the end)   | 1 byte or 2 bytes |
| '82'           | M                 | Tag: File Descriptor<br>File Descriptor Byte followed by Data Coding Byte<br>or<br>File Descriptor Byte followed by Data Coding Byte and record length,<br>coded on 2 bytes | 1 byte            |
| '02' or '04'   |                   | Length of File Descriptor   | 1 byte            |
|                |                   | File Descriptor Byte  | 1 byte            |
| '21'           |                   | Data Coding Byte  | 1 byte            |
|                | C<br>(see note 1) | Record length   | 2 bytes           |
| '83'           | M                 | Tag: File ID  | 1 byte            |
| '02'           |                   | Length of File ID   | 1 byte            |
|                |                   | File ID   | 2 bytes           |
| '8A'           | M                 | Life Cycle Status Information (LCSI)  | 1 byte            |
| '01'           |                   | Length of the LCSI  | 1 byte            |
|                |                   | Life Cycle Status Information   | 1 byte            |
| '8C' 'AB' '8B' | M                 | Tag: Security Attributes: one of the following:<br>Compact<br>Expanded<br>Referenced  | 1 byte            |
| LL             |                   | Length of Security Attributes related data  | 1 byte            |
|                |                   | Data for the Security Attributes  | X bytes           |
| '80'           | M                 | Tag: File Size (Reserved File Size)   | 1 byte            |
| LL             |                   | Length of File Size   | 1 byte            |
|                |                   | File Size   | Y bytes           |
| '88'           | O                 | Tag: Short File Identifier  | 1 byte            |
| '00' or '01'   |                   | Length of Short File Identifier   | 1 byte            |
|                |                   | Short File Identifier   | 0 or 1 byte       |
| 'A5' or '85'   | C<br>(see note 2) | Tag proprietary, application dependent  | 1 byte            |
| LL             |                   | Length of application dependent data  | 1 byte or 2 bytes |
|                |                   | Application dependent data (see below for tag 'A5')   | Z bytes           |

NOTE 1: Mandatory for linear fixed and cyclic files, otherwise it is not applicable.  
NOTE 2: Tag 'A5' is mandatory for BER TLV structured EFs, otherwise it is optional.

**Tag '80': File Size (Reserved File Size)**

File Size indicates the number of bytes allocated for the body of the file (i.e. it does not include structural information) and cannot be allocated by any other entity.

In the case of an EF with linear or cyclic structure, it is the record length multiplied by the number of records of the EF.

In case of a BER-TLV structured EF, the File Size indicates the number of bytes allocated for the body of the file. The value shall include administrative overhead (if any) that is required to store TLV objects, but not the structural information for the file itself. This value shall be returned in the FCP information provided in a response to a SELECT APDU command and labelled "Reserved File Size".

**Tag '82': File Descriptor**

The File Descriptor Byte shall be coded as defined in ETSI TS 102 221 [5].

The data coding byte can be used differently according to ISO/IEC 7816-4 [2]. For the present document, the value '21' (proprietary) shall be used and shall not be interpreted by the UICC.

The record length shall be present if a record structured file (i.e. for linear fixed or cyclic files) is created. In this case it indicates the length of the records coded on 2 bytes. Most significant byte comes first in the value field.

**Tag '8A': Life Cycle Status Information (LCSI)**

The Life Cycle Status Information shall be coded as defined in ETSI TS 102 221 [5].

This TLV specifies the status of the file after creation.

The initialization state can be used to set the file into a specific security environment for administrative purposes. See ACTIVATE FILE command.

**Tag '88': Short File Identifier**

The following 3 cases shall be supported by the UICC if the ATR indicates that the UICC supports selection by SFI:

- Tag '88' is missing in the CREATE FILE command: The lower five bits of the file ID are used as the Short File Identifier by the EF.
- Tag '88' is available in the CREATE FILE command, there is no value part in the TLV: Short File Identifier is not supported by the EF.
- Tag '88' is available in the CREATE FILE command, there is a Short File Identifier value in the TLV: The Short File Identifier is coded from bits b8 to b4. Bits b3,b2,b1 = 000.

**Tag 'A5': Proprietary, application dependent**

This is a constructed TLV object.

The following TLV objects are defined for the proprietary template (tag 'A5'). Additional private TLV objects (bits b7 and b8 of the first byte of the tag set to '1') may be present after the TLV objects defined in this clause.

**Table 4a: TLV objects**

| Value | M/O/C             | Description   | Length            |
|-------|-------------------|---|-------------------|
| 'C0'  | O                 | Tag: Special File Information (File Status Byte)                                    | 1 byte            |
| '01'  |                   | Length of Special File Information  | 1 byte            |
|       |                   | Special File Information (File Status Byte)   | 1 byte            |
| 'C1'  | O<br>(see note 1) | Tag: Filling Pattern  | 1 byte            |
| LL    |                   | Length of Filling Pattern   | 1 byte or 2 bytes |
|       |                   | Filling Pattern Value   | W bytes           |
| 'C2'  | O<br>(see note 1) | Tag: Repeat Pattern   | 1 byte            |
| LL    |                   | Length of the Repeat Pattern  | 1 byte or 2 bytes |
|       |                   | Length of Repeat Pattern Value  | X bytes           |
| '86'  | O<br>(see note 2) | Tag: Maximum File Size  | 1 byte            |
| LL    |                   | Length of Maximum File Size   | 1 byte            |
|       |                   | Maximum File Size   | Y bytes           |
| '84'  | C<br>(see note 3) | Tag: File Details   | 1 byte            |
| '01'  |                   | Length of File Details  | 1 byte            |
| '01'  |                   | File Details value as defined for the BER TLV structured EFs in ETSI TS 102 221 [5] | 1 byte            |
|       |                   | Additional private TLV objects  | Z bytes           |

NOTE 1: Tag 'C1' and Tag 'C2' shall not be both present within the same command. Tag 'C1' and 'C2' are not applicable in case of BER TLV structured EF.

NOTE 2: Tag '86' shall only be present for BER TLV structured EFs, for which it is optional.

NOTE 3: Tag '84' shall only be present for BER TLV structured EFs, for which it is mandatory.

Tag 'C0': Special File Information (File Status Byte) within the proprietary TLV (tag 'A5')

**Table 5: Coding of the Special File Information**

| b8              | b7 | b6 | b5 | b4 | b3 | b2 | b1 | Meaning                                    |
|-----------------|----|----|----|----|----|----|----|--|
| 0               | x  | 0  | 0  | 0  | 0  | 0  | 0  | Low update activity                        |
| 1               | x  | 0  | 0  | 0  | 0  | 0  | 0  | High update activity                       |
| x               | 0  | 0  | 0  | 0  | 0  | 0  | 0  | Not readable or updatable when deactivated |
| x               | 1  | 0  | 0  | 0  | 0  | 0  | 0  | Readable and updatable when deactivated    |
| Any other value |    |    |    |    |    |    |    | RFU  |

Tag 'C1': Filling Pattern within the proprietary TLV (tag 'A5')

The Filling Pattern may have any length  $W > 0$  and shall be used as follows:

The first  $W-1$  bytes of the transparent EF or the first  $W-1$  bytes of each record of a record oriented EF shall be initialized with the first  $W-1$  bytes of the Filling Pattern. All remaining bytes (if any) shall be initialized with the value of the last byte of the Filling Pattern. If the file or record length is shorter than the Filling Pattern, the Filling Pattern shall be truncated accordingly.

Tag 'C2': Repeat Pattern within the proprietary TLV (tag 'A5')

The Repeat Pattern may have any length  $X$  and shall be used as follows:

The first  $X$  bytes of the transparent EF or the first  $X$  bytes of each record of a record oriented EF shall be initialized with the  $X$  bytes of the Repeat Pattern. This shall be repeated consecutively for all remaining blocks of  $X$  bytes of data in the file or in a record. If necessary, the Repeat Pattern shall be truncated at the end of the file or at the end of each record to initialize the remaining bytes.

Tag '86': Maximum File Size within the proprietary TLV (tag 'A5')

In the case of an EF with transparent, linear or cyclic structure, this TLV shall not be present in the command.

In case of a BER TLV structured EF, the Maximum File Size indicates the maximum number of bytes that may be allocated for the body of the file and shall not be exceeded when new objects are created. The value shall include administrative overhead (if any) that is required to store TLV objects, but not the structural information for the file itself. This value shall be returned in the FCP information provided in a response to a SELECT APDU command and labelled "Maximum file size".

If the TLV is not present, no Maximum File Size is defined for the file and all available memory of the UICC can be allocated to that file.

### 6.3.3 Response message

#### 6.3.3.1 Data field returned in the response message

The data field of the response message is not present.

### 6.3.3.2 Status conditions returned in the response message

The following status conditions shall be returned by the UICC.

**Table 6: CREATE FILE status conditions**

| SW1                      | SW2  | Meaning   |
|--------------------------|------|---|
| <b>Normal Processing</b> |      |   |
| '90'                     | '00' | - normal ending of the command  |
| '63'                     | '0X' | - command successful but after using an internal update retry routine 'X' times |
| <b>Errors</b>            |      |   |
| '62'                     | '83' | - in contradiction with activation status                                       |
| '65'                     | '81' | - memory problem  |
| '67'                     | '00' | - incorrect length field  |
| '69'                     | '00' | - command not allowed (no information given)                                    |
| '69'                     | '82' | - security status not satisfied   |
| '6A'                     | '80' | - incorrect parameters in the data field  |
| '6A'                     | '84' | - not enough memory space   |
| '6A'                     | '89' | - file ID already exists  |
| '6A'                     | '8A' | - DF Name already exists  |
| '6B'                     | '00' | - incorrect parameter P1 or P2  |
| '6D'                     | '00' | - instruction code not supported or invalid                                     |
| '6E'                     | '00' | - class not supported   |
| '6F'                     | '00' | - technical problem with no diagnostic given                                    |
| '6F'                     | 'XX' | - technical problem, XX (proprietary) provides diagnostic except for SW2 = '00' |

## 6.4 DELETE FILE

### 6.4.1 Definition and scope

This command initiates the deletion of a referenced EF immediately under the current DF, or a DF with its complete subtree.

If a file is indicated as not-shareable as defined in ETSI TS 102 221 [5] and is the current file of one application, then another application cannot delete it.

If a file is indicated as shareable as defined in ETSI TS 102 221 [5], then it can be deleted by one application independently of whether or not the file is the current file of any other application.

NOTE 1: If another application is using concurrently the deleted file, the processing by the application may fail.

NOTE 2: If a DF is shareable and an application, having the appropriate rights, requests to delete it, the whole DF including all EFs can be deleted whatever shareable status they have.

If an EF is to be deleted, the access condition "DELETE FILE" of the EF to be deleted shall be fulfilled. After successful completion the current directory is unchanged and no EF is selected. If the EF that is successfully deleted is the current file of another application, the current directory of this application is unchanged and no EF is selected.

If a DF is to be deleted, the access condition "DELETE FILE (self)" of the DF to be deleted shall be fulfilled. After successful completion the parent directory is selected and no EF is selected.

If an ADF is to be deleted, the access condition "DELETE FILE (self)" of the ADF to be deleted shall be fulfilled and the ADF is not currently selected on another logical channel. After successful completion the MF is selected and no EF is selected.

The access conditions "DELETE FILE" and "DELETE FILE (self)" shall be coded as specified in ISO/IEC 7816-4 [2]. The access condition "DELETE FILE (child)" shall not be used.



After successful completion of this command, the deleted file can no longer be selected. The resources held by the file shall be released and the memory used by this file shall be set to the logical erased state. It shall not be possible to interrupt this process in such a way that the data can become recoverable.

If an ADF is deleted, some instance has to take care of the administration of the application, e.g. deleting the application ID entry in the EF<sub>DIR</sub>. The DELETE FILE command does not take care of this administration by its own.

## 6.4.2 Command message

### 6.4.2.0 Command coding

The DELETE FILE command message is coded according to table 7.

**Table 7: DELETE FILE command message**

| Code       | Value                               |
|------------|-------------------------------------|
| CLA        | See table 1                         |
| INS        | See table 1                         |
| P1         | '00'                                |
| P2         | '00'                                |
| Lc         | Length of the subsequent data field |
| Data field | Data sent to the UICC               |
| Le         | Not present                         |

#### 6.4.2.1 Parameters P1 and P2

P1 and P2 are set to '00', indicating the selection by file identifier as defined in ISO/IEC 7816-4 [2] for SELECT FILE command.

#### 6.4.2.2 Data field sent in the command message

**Table 8: Coding of the data field of the DELETE FILE command**

| Value | BytesM/O | Description | Length  |
|-------|----------|-------------|---------|
|       | M        | File ID     | 2 bytes |

## 6.4.3 Response message

### 6.4.3.1 Data field returned in the response message

The data field of the response message is not present.

### 6.4.3.2 Status conditions returned in the response message

The following status conditions shall be returned by the UICC.

**Table 9: DELETE FILE status conditions**

| SW1                      | SW2  | Meaning   |
|--------------------------|------|---|
| <b>Normal Processing</b> |      |   |
| '90'                     | '00' | - normal ending of the command  |
| <b>Errors</b>            |      |   |
| '63'                     | '0X' | - command successful but after using an internal update retry routine 'X' times |
| '65'                     | '81' | - memory problem  |
| '67'                     | '00' | - incorrect length field  |
| '69'                     | '00' | - command not allowed (no information given)                                    |
| '69'                     | '82' | - security status not satisfied   |
| '6A'                     | '82' | - file not found  |
| '6B'                     | '00' | - incorrect parameter P1 or P2  |
| '6D'                     | '00' | - instruction code not supported or invalid                                     |
| '6E'                     | '00' | - class not supported   |
| '6F'                     | '00' | - technical problem with no diagnostic given                                    |
| '6F'                     | 'XX' | - technical problem, XX (proprietary) provides diagnostic except for SW2 = '00' |

## 6.5 DEACTIVATE FILE

The support of this command is mandatory for an UICC compliant to the present document.

Refer to ETSI TS 102 221 [5] for the specification of the command.

## 6.6 ACTIVATE FILE

The support of this command is mandatory for an UICC compliant to the present document.

Refer to ETSI TS 102 221 [5] for the specification of the command.

This command initiates the transition of a file from:

- the initialization state; or
- the operational state (deactivated).

To the operational state (activated).

## 6.7 TERMINATE DF

### 6.7.1 Definition and scope

The TERMINATE DF command initiates the irreversible transition of the currently selected DF/ADF into the termination state (coding see LCSi coding in ISO/IEC 7816-4 [2]).

After a successful completion of the command, the DF/ADF is in terminated state and the DF/ADF shall no longer be available for any command except for the SELECT and the DELETE FILE command. All other commands on the terminated DF/ADF shall return the status code '6900' (command not allowed, no information given). Any files in the subtree of the DF/ADF are no longer accessible for any commands. If a file in the subtree of the DF/ADF is selected by another application, all commands that make a reference to this file shall return the status code '6900' (command not allowed, no information given). If the DF/ADF is selected the warning status SW1/SW2='6285' (selected file in termination state) shall be returned.

The command can be performed only if the security status satisfies the Security Attributes defined for this command.

NOTE 1: An appropriate security rule is to be setup and fulfilled in order to execute this command.

If a DF is indicated as not-shareable as defined in ETSI TS 102 221 [5] and is the current DF of one application, then another application cannot terminate it. If a DF is indicated as shareable as defined in ETSI TS 102 221 [5], then it can be terminated by an application independently of whether or not the DF is the current file of any other application.

NOTE 2: If another application is using concurrently the terminated DF, the processing by this application may fail.

## 6.7.2 Command message

### 6.7.2.0 Command coding

The TERMINATE DF command message is coded according to table 10.

**Table 10: TERMINATE DF command message**

| Code       | Value       |
|------------|-------------|
| CLA        | See table 1 |
| INS        | See table 1 |
| P1         | '00'        |
| P2         | '00'        |
| Lc         | Not present |
| Data field | Not present |
| Le         | Not present |

#### 6.7.2.1 Parameters P1 and P2

P1 and P2 are set to '00'.

#### 6.7.2.2 Data field sent in the command message

The data field of the command message is not present.

## 6.7.3 Response message

### 6.7.3.1 Data field returned in the response message

The data field of the response message is not present.

### 6.7.3.2 Status conditions returned in the response message

The following status conditions shall be returned by the UICC.

**Table 11: TERMINATE DF status conditions**

| SW1                      | SW2  | Meaning   |
|--------------------------|------|---|
| <b>Normal Processing</b> |      |   |
| '90'                     | '00' | - normal ending of the command  |
| <b>Errors</b>            |      |   |
| '65'                     | '81' | - memory problem  |
| '67'                     | '00' | - incorrect length field  |
| '69'                     | '82' | - security status not satisfied   |
| '69'                     | '00' | - command not allowed (no information given)  |
| '69'                     | '85' | - condition of use not satisfied:<br>- not-shareable file selected by another application |
| '6B'                     | '00' | - incorrect parameter P1 or P2  |
| '6D'                     | '00' | - instruction code not supported or invalid   |
| '6E'                     | '00' | - class not supported   |
| '6F'                     | '00' | - technical problem with no diagnostic given  |
| '6F'                     | 'XX' | - technical problem, XX (proprietary) provides diagnostic except for SW2 = '00'           |

## 6.8 TERMINATE EF

### 6.8.1 Definition and scope

The TERMINATE EF command initiates the irreversible transition of the currently selected EF into the termination state (coding see LCSI coding in ISO/IEC 7816-4 [2]).

The command can be performed only if the security status satisfies the Security Attributes defined for this command.

After a successful completion of the command, the EF is in terminated state and the EF shall no longer be available for any command except for the SELECT and the DELETE FILE commands. All other commands on the terminated EF shall return the status code '6900' (command not allowed, no information given). If the EF is selected the warning status SW1/SW2='6285' (selected file in termination state) shall be returned.

If an EF is indicated as not-shareable as defined in ETSI TS 102 221 [5] and is the current EF of one application, then another application cannot terminate it. If an EF is indicated as shareable as defined in ETSI TS 102 221 [5], then it can be terminated by an application independently of whether or not the EF is the current file of any other application.

NOTE: If another application is using concurrently the terminated EF, the processing by this application may fail.

### 6.8.2 Command message

#### 6.8.2.0 Command coding

The TERMINATE EF command message is coded according to table 12.

**Table 12: TERMINATE EF command message**

| Code       | Value       |
|------------|-------------|
| CLA        | See table 1 |
| INS        | See table 1 |
| P1         | '00'        |
| P2         | '00'        |
| Lc         | Not present |
| Data field | Not present |
| Le         | Not present |

#### 6.8.2.1 Parameters P1 and P2

P1 and P2 are set to '00'.

#### 6.8.2.2 Data field sent in the command message

The data field of the command message is not present.

### 6.8.3 Response message

#### 6.8.3.1 Data field returned in the response message

The data field of the response message is not present.

### 6.8.3.2 Status conditions returned in the response message

The following status conditions shall be returned by the UICC.

**Table 13: TERMINATE EF status conditions**

| SW1                      | SW2  | Meaning   |
|--------------------------|------|---|
| <b>Normal Processing</b> |      |   |
| '90'                     | '00' | - normal ending of the command  |
| <b>Errors</b>            |      |   |
| '65'                     | '81' | - memory problem  |
| '67'                     | '00' | - incorrect length field  |
| '69'                     | '82' | - security status not satisfied   |
| '69'                     | '85' | - condition of use not satisfied:<br>- not-shareable file selected by another application |
| '69'                     | '00' | - command not allowed (no information given)  |
| '69'                     | '86' | - command not allowed (no EF selected)  |
| '6B'                     | '00' | - incorrect parameter P1 or P2  |
| '6D'                     | '00' | - instruction code not supported or invalid   |
| '6E'                     | '00' | - class not supported   |
| '6F'                     | '00' | - technical problem with no diagnostic given  |
| '6F'                     | 'XX' | - technical problem, XX (proprietary) provides diagnostic except for SW2 = '00'           |

## 6.9 TERMINATE CARD USAGE

### 6.9.1 Definition and scope

The TERMINATE CARD USAGE command initiates the irreversible transition of the UICC into the termination state. Use of this command gives an implicit selection of the MF.

The termination state should be indicated in the ATR (see ISO/IEC 7816-4 [2]) using the coding shown in ISO/IEC 7816-4 [2].

Following a successful completion of the command, no other than the STATUS command shall be supported by the UICC.

The intend of UICC termination is generally to make the UICC unusable by the cardholder.

The command can be performed only if the security status satisfies the Security Attributes defined for this command.

NOTE: An appropriate security rule is to be setup and fulfilled in order to execute this command.

### 6.9.2 Command message

#### 6.9.2.0 Command coding

The TERMINATE CARD USAGE command message is coded according to table 14.

**Table 14: TERMINATE CARD USAGE command message**

| Code       | Value       |
|------------|-------------|
| CLA        | See table 1 |
| INS        | See table 1 |
| P1         | '00'        |
| P2         | '00'        |
| Lc         | Not present |
| Data field | Not present |
| Le         | Not present |

### 6.9.2.1 Parameters P1 and P2

P1 and P2 are set to '00'.

### 6.9.2.2 Data field sent in the command message

The data field of the command message is not present.

## 6.9.3 Response message

### 6.9.3.1 Data field returned in the response message

The data field of the response message is not present.

### 6.9.3.2 Status conditions returned in the response message

The following status conditions may be returned by the UICC.

**Table 15: TERMINATE CARD USAGE status conditions**

| SW1                      | SW2  | Meaning   |
|--------------------------|------|---|
| <b>Normal Processing</b> |      |   |
| '90'                     | '00' | - normal ending of the command  |
| <b>Errors</b>            |      |   |
| '65'                     | '81' | - memory problem  |
| '67'                     | '00' | - incorrect length field  |
| '69'                     | '82' | - security status not satisfied   |
| '6B'                     | '00' | - incorrect parameter P1 or P2  |
| '6D'                     | '00' | - instruction code not supported or invalid                                     |
| '6E'                     | '00' | - class not supported   |
| '6F'                     | '00' | - technical problem with no diagnostic given                                    |
| '6F'                     | 'XX' | - technical problem, XX (proprietary) provides diagnostic except for SW2 = '00' |

## 6.10 RESIZE FILE

### 6.10.1 Definition and scope

This command allows to modify the memory space allocated to the MF, a DF/ADF, a transparent file or a linear fixed file or a BER TLV structured EF under the current directory (MF, DF/ADF). This command shall not be allowed for a cyclic file.

If the RESIZE FILE command is used for an ADF, this ADF can only be the ADF of the current active application on this logical channel.

If a file is indicated as not-shareable as defined in ETSI TS 102 221 [5] and is the current file of one application, then another application cannot resize it. If a file is indicated as shareable as defined in ETSI TS 102 221 [5], then it can be resized by an application independently of whether or not the file is the current file of any other application.

If the card cannot provide the requested memory, the error status SW1/SW2="6A84' (not enough memory space) shall be returned.

MF or DF/ADF resizing may be not allowed for a card implementing dynamic allocation of memory (memory is allocated for the whole UICC). If not allowed, the error status SW1/SW2="6985' (condition of use not satisfied) shall be returned.

The access condition for the RESIZE FILE command shall be fulfilled for the file to be resized.

The RESIZE FILE access condition is indicated in the access rules using AM\_DO tag '84'. Tag '84' indicates that the INS code for the RESIZE FILE command is indicated as the value in the TLV object (instruction code 'D4'). The

RESIZE FILE command can only be used on files that refer to an access rule where this INS code is indicated as part of the rule.

In case of successful execution of the command, the EF or directory on which the command was applied is selected.

If the RESIZE FILE command was performed on a linear fixed file the record pointer shall be undefined, if it pointed to a record which no longer exists. Otherwise it shall be unchanged. This applies to all applications having a record pointer set to the resized file.

If the RESIZE FILE command was performed, on a BER TLV structured EF the tag pointer shall be undefined if the data object it pointed to was deleted due to the RESIZE command. Otherwise it shall be unchanged. This applies to all applications having a tag pointer set to the resized file.

NOTE: If another application is using concurrently the resized file, the processing by the application may fail.

After an unsuccessful execution of the command, the current file shall remain the same as prior to the execution. If in this case the RESIZE FILE command was performed on a linear fixed file the record pointer shall not be changed, on a BER TLV structured EF the tag pointer shall not be changed.

After a successful execution of the command, the Total File Size, if applicable, and the File Size TLVs defined in the FCP template of the modified file shall be updated accordingly.

The allocated memory space is updated according to the new data size.

For a linear fixed file, the RESIZE FILE command modifies the number of records but does not change the record length.

In case the size of a linear fixed or transparent EF is increased:

- the extension data shall be appended to the end of the existing data (e.g. if 3 records are added to a linear fixed EF with 2 records, these 2 records remain the record 1 and 2 in the increased file, and the 3 new records will become the records 3, 4 and 5); and
- the data contained in the previously allocated memory space shall not be modified by the RESIZE FILE command (e.g. if 3 records are added to a linear fixed EF with 2 records, the content of the 2 initially allocated records shall be identical before and after the execution of the RESIZE FILE command); and
- the newly allocated memory space shall be initialized with 'FF'. The content of the whole newly allocated memory space shall consist of bytes of this value. If, for some applications, other default values are required, this default behaviour can be overwritten by specifying an appropriate TLV in the application dependent data TLV (tag '85' and 'A5') of the RESIZE FILE command.

In case the size of a linear fixed or transparent EF is decreased:

- the removed data shall be deleted and removed from the end of the existing data (e.g. if 3 bytes are removed from a transparent EF with 5 bytes, the bytes 3, 4 and 5 shall be removed from the file); and
- the remaining data already contained in the previously allocated memory space shall not be modified by the RESIZE FILE command (e.g. if 3 bytes are removed from a transparent EF with 5 bytes, the content of the 2 remaining bytes shall be identical before and after the execution of the RESIZE FILE command).

For a BER TLV structured EF, the Reserved File Size or the Maximum File Size or both can be resized. If the Maximum File Size is decreased and the new size conflicts with the used size, then depending on the mode chosen the command is rejected or all objects in the file are deleted.

If the File Size of the MF or a DF/ADF is increased its content is unchanged.

The size of the MF or a DF/ADF can only be decreased if the current amount of memory (including structural information) allocated to the child EFs and DFs is lower or equal to the new requested size. Otherwise, the command is not allowed and the error status SW1/SW2='6985' (condition of use not satisfied) shall be returned.

## 6.10.2 Command message

### 6.10.2.0 Command coding

The RESIZE FILE command message is coded according to table 16.

**Table 16: RESIZE command message**

| Code       | Value                               |
|------------|-------------------------------------|
| CLA        | See table 1                         |
| INS        | See table 1                         |
| P1         | See table 16A                       |
| P2         | '00'                                |
| Lc         | Length of the subsequent data field |
| Data Field | Data sent to the ICC                |
| Le         | Not present                         |

**Table 16a: Coding of P1 for a BER TLV structured EF**

| b8              | b7 | b6 | b5 | b4 | b3 | b2 | b1 | Meaning |
|-----------------|----|----|----|----|----|----|----|---------|
| 0               | 0  | 0  | 0  | 0  | 0  | 0  | 0  | Mode 0  |
| 0               | 0  | 0  | 0  | 0  | 0  | 0  | 1  | Mode 1  |
| Any other value |    |    |    |    |    |    |    | RFU     |

For other file types, P1 shall be set to '00'.

### 6.10.2.1 Data field sent in the command message

**Table 17: Coding of the data field of the RESIZE FILE command**

| Value        | M/O/C | Description   | Length            |
|--------------|-------|---|-------------------|
| '62'         | M     | Tag: FCP Template                                   | 1 byte            |
| LL           |       | Length of FCP Template (next byte to the end)       | 1 byte or 2 bytes |
| '83'         | M     | Tag: File ID  | 1 byte            |
| '02'         |       | Length of the File ID                               | 1 byte            |
|              |       | File ID   | 2 bytes           |
| '80'         | O     | Tag: File Size (Reserved File Size)                 | 1 byte            |
| LL           |       | Length of the File Size                             | 1 byte            |
|              |       | File Size (New File Size)                           | X bytes           |
| '81'         | O     | Tag: Total File Size                                | 1 byte            |
| LL           |       | Length of Total File Size                           | 1 byte            |
|              |       | Total File Size (New Total File Size)               | Y bytes           |
| '85' or 'A5' | O     | Tag proprietary, application dependent data         | 1 byte            |
| LL           |       | Length of application dependent data                | 1 byte or 2 bytes |
|              |       | Application dependent data (see below for tag 'A5') | Z bytes           |

There is at most one occurrence of the following Tags.

#### **Tag '83': File ID**

Contains the FID of the MF, ADF, DF or EF to be resized. In order to specify the ADF of the currently selected application on this logical channel, the FID '7FFF' shall be used.

#### **Tag '80': File Size (Reserved File Size)**

This TLV shall only be provided if an EF is resized. It contains the New File Size for this EF.

This size is the new number of bytes allocated for the body of the EF (i.e. it does not include structural information).



In the case of an EF with linear fixed structure, the File Size shall be the record length multiplied by the number of records of the EF; otherwise the command is rejected. The New File Size shall contain at least one record.

For transparent files, if this size is set to '00', all the content of the EF is removed but the EF is not deleted (it is then exactly as if the EF was created with a size set to '00') and the structural information is still available.

For BER TLV structured EF, if File Size is present, it indicates the minimum number of bytes reserved for the body of the file. The value shall include administrative overhead (if any) that is required to store TLV objects, but not the structural information for the file itself. The content of the file shall not be altered whatever is the new reserved file size value.

#### Tag '81': Total File Size

This TLV shall only be provided if the MF or a DF/ADF is resized. It contains the New Total File Size for the MF or this DF/ADF.

This size is the new amount of physical memory allocated for the MF or a DF/ADF (i.e. it does not include structural information) for card not implementing dynamic allocation of memory.

The amount of EFs or DFs which may be created is implementation dependent.

The MF or DF/ADF can be resized to '00' only if it does not contain any file. In this case, the structural information is still available for the MF or DF/ADF. For an ADF, the resizing to '00' does not affect EF<sub>DIR</sub> and any other information necessary to administer an application.

#### Tag 'A5' Proprietary, application dependent

This is a constructed TLV object.

The following TLV objects are defined for the proprietary template (tag 'A5'). Additional private TLV objects (bits b7 and b8 of the first byte of the tag set to '1') may be present after the TLV objects defined in this clause.

**Table 18**

| Value  | M/O/C             | Description   | Length            |
|--|-------------------|---|-------------------|
| 'C1'   | O<br>(see note 1) | Tag: Filling Pattern                                | 1 byte            |
| LL   |                   | Length of Filling Pattern                           | 1 byte or 2 bytes |
|  |                   | Filling Pattern Value                               | W bytes           |
| 'C2'   | O<br>(see note 1) | Tag: Repeat Pattern                                 | 1 byte            |
| LL   |                   | Length of the Repeat Pattern                        | 1 byte or 2 bytes |
|  |                   | Repeat Pattern Value                                | X bytes           |
| '86'   | C<br>(see note 2) | Tag: Maximum File Size (New Maximum File Size)      | 1 byte            |
| LL   |                   | Length of Maximum File Size (New Maximum File Size) | 1 byte            |
|  |                   | Maximum File Size (New Maximum File Size)           | Y bytes           |
|  |                   | Additional private TLV objects                      | Z bytes           |
| NOTE 1: Tag 'C1' and Tag 'C2' shall not be both present within the same command. In the case the size of a MF/DF/ADF of EF is decreased these Tags shall be ignored. Tag 'C1' and 'C2' are not applicable in case of a BER-TLV structured EF and in case the command is performed on a MF/DF or ADF. |                   |   |                   |
| NOTE 2: Tag '86' shall only be present for BER TLV structured EFs, for which it is optional.   |                   |   |                   |

#### Tag 'C1': Filling Pattern within the proprietary TLV (tag 'A5')

The Filling Pattern may have any length  $W > 0$  and shall be used as follows:

The first  $W-1$  bytes of the newly allocated memory space of the transparent EF or the first  $W-1$  bytes of each newly created record shall be initialized with the first  $W-1$  bytes of the Filling Pattern. All remaining bytes (if any) shall be initialized with the value of the last byte of the Filling Pattern. If the newly allocated memory space or record length is shorter than the Filling Pattern, the Filling Pattern shall be truncated accordingly.

**Tag 'C2': Repeat Pattern within the proprietary TLV (tag 'A5'):**

The Repeat Pattern may have any length X and shall be used as follows:

The first X bytes of the newly allocated memory space of the transparent EF or the first X bytes of each newly created record shall be initialized with the X bytes of the Repeat Pattern. This shall be repeated consecutively for all remaining blocks of the new X bytes of data in the file or in the new records. If necessary, the Repeat Pattern shall be truncated at the end of the file or at the end of each new record to initialize the remaining bytes.

**Tag '86': Maximum File Size within the proprietary TLV (tag 'A5')**

This TLV may only be provided if a BER-TLV structured EF is resized.

Maximum File Size indicates the new maximum number of bytes that can be allocated for the body of the file. The value shall include administrative overhead (if any) that is required to store TLV objects, but not the structural information for the file itself.

In case the New Maximum File Size is decreased and the size used by the existing TLV is greater than the New Maximum File Size:

- If P1 indicates Mode 0, all existing TLV objects shall be deleted. The file itself shall not be deleted. The New Maximum File Size is assigned to the file.
- If P1 indicates Mode 1, no action is performed and the error status SW1/SW2='6985' (condition of use not satisfied) shall be returned.

### 6.10.3 Response message

#### 6.10.3.1 Data field returned in the response message

The data field of the response message is not present.

#### 6.10.3.2 Status conditions returned in the response message

The following status conditions shall be returned by the ICC.

**Table 19: RESIZE FILE status conditions**

| SW1                      | SW2  | Meaning   |
|--------------------------|------|---|
| <b>Normal Processing</b> |      |   |
| '90'                     | '00' | - normal ending of the command  |
| '63'                     | '0X' | - command successful but after using an internal update retry routine 'X' times   |
| <b>Errors</b>            |      |   |
| '65'                     | '81' | - memory problem  |
| '67'                     | '00' | - incorrect length field  |
| '69'                     | '00' | - command not allowed (no information given)  |
| '69'                     | '81' | - command incompatible with file structure  |
| '69'                     | '82' | - security status not satisfied   |
| '69'                     | '84' | - referenced data invalidated   |
| '69'                     | '85' | - condition of use not satisfied: <ul style="list-style-type: none"> <li>- command not allowed on MF/DF/ADF</li> <li>- new MF/DF/ADF size lower than current MF/DF/ADF content size</li> <li>- new maximum size is lower than current BER-TLV EF content size.</li> </ul> |
| '6A'                     | '80' | - incorrect parameters in the data field  |
| '6A'                     | '82' | - file not found  |
| '6A'                     | '84' | - not enough memory space   |
| '6B'                     | '00' | - incorrect parameter P1 or P2  |
| '6D'                     | '00' | - instruction code not supported or invalid   |
| '6E'                     | '00' | - class not supported   |
| '6F'                     | '00' | - technical problem with no diagnostic given  |
| '6F'                     | 'XX' | - technical problem, X (proprietary) provides diagnostic  |

## 7 Administrative files

### 7.1 EF<sub>SUME</sub> (SetUpMenu Elements)

This file is located under DF<sub>TELECOM</sub> ('7F10').

This EF contains COMPREHENSION TLVs related to the menu title to be used by a UICC when issuing a SET UP MENU proactive command.

| Identifier: '6F 54'            | Structure: transparent | Optional |         |
|--------------------------------|------------------------|----------|---------|
| File size: X + Y + Z + P bytes | Update activity: low   |          |         |
| Access Conditions:             |                        |          |         |
| READ                           | ADM                    |          |         |
| UPDATE                         | ADM                    |          |         |
| DEACTIVATE                     | ADM                    |          |         |
| ACTIVATE                       | ADM                    |          |         |
| Bytes                          | Description            | M/O      | Length  |
| 1 to X                         | Title Alpha Identifier | M        | X bytes |
| X + 1 to X + Y                 | Title Icon Identifier  | O        | Y bytes |
| X + Y + 1 to X + Y + Z         | Title Text Attribute   | O        | Z bytes |
| X + Y + Z + 1 to X + Y + Z + P | 'FF' Padding           | O        | P bytes |

- Title Alpha Identifier

Contents: this field contains the Alpha Identifier COMPREHENSION TLV defining the menu title text.

Coding: according to ETSI TS 102 223 [8].

- Title Icon Identifier

Contents: this field contains the Icon Identifier COMPREHENSION TLV defining the menu title icon.

Coding: according to ETSI TS 102 223 [8].

- Title Text Attribute

Contents: this field contains the Text Attribute COMPREHENSION TLV defining the menu title text attribute.

Coding: according to ETSI TS 102 223 [8].

## 7.2 EF<sub>RMA</sub> (Remote Management Actions)

This file is located under DF<sub>TELECOM</sub> ('7F10').

This EF contains records with COMPREHENSION TLVs of proactive commands used in remote management.

| Identifier: '6F 53'  |                                       | Structure: linear fixed |                      | Optional |  |
|--|---------------------------------------|-------------------------|----------------------|----------|--|
| Record length: R bytes   |                                       |                         | Update activity: low |          |  |
| Access Conditions:   |                                       |                         |                      |          |  |
| READ   |                                       | ADM                     |                      |          |  |
| UPDATE   |                                       | ADM                     |                      |          |  |
| DEACTIVATE   |                                       | ADM                     |                      |          |  |
| ACTIVATE   |                                       | ADM                     |                      |          |  |
| <b>Format of each record that can be referenced by a remote management script:</b> |                                       |                         |                      |          |  |
| Bytes  | Description                           | M/O                     | Length               |          |  |
| 1 to X   | Length of next field                  | M                       | X bytes              |          |  |
| X + 1 to X + Y   | Set of COMPREHENSION-TLV data objects | M                       | Y bytes              |          |  |
| X + Y + 1 to R   | Padding (value undefined)             | O                       | R - X - Y bytes      |          |  |

- Length of next field

Contents: length of the list of COMPREHENSION-TLV data objects.

Coding: as defined for BER TLVs in ETSI TS 101 220 [7].

- Set of COMPREHENSION-TLV data objects

Contents: a set of COMPREHENSION-TLV data objects constituting a proactive command.

Coding: according to ETSI TS 102 223 [8].

## Annex A (informative): Change history

The table below indicates all changes that have been incorporated into the present document since it was created by TC SCP.

| Change history |         |             |     |     |     |   |       |       |
|----------------|---------|-------------|-----|-----|-----|---|-------|-------|
| Date           | Meeting | TC SCP Doc. | CR  | Rev | Cat | Subject/Comment   | Old   | New   |
| 2000-05        | SCP-01  | 9-00-0149   | -   |     | -   | Final draft approved for publication  |       | 3.0.0 |
| 2000-11        | SCP-03  | 9-00-0437   | 002 |     | F   | Alignments with ETSI TS 102 221 regarding CREATE FILE command. Note that CR 002 includes corrections which had originally been agreed in CR 001 in T3-000347. | 3.0.0 | 3.1.0 |
|                |         | 9-00-0438   | 003 |     | F   | Alignments with ETSI TS 102 221 regarding access conditions   |       |       |
|                |         | 9-00-0439   | 004 |     | F   | Alignments with ETSI TS 102 221 concerning editorial changes  |       |       |
|                |         | 9-00-0436   | 005 |     | F   | Administrative command: proprietary information added   |       |       |
| 2001-05        | SCP-05  | SCP-010120  | 006 |     | F   | Correction of the annex applying to the SIM   | 3.1.0 | 3.2.0 |
|                |         | SCP-010144  | 007 |     | F   | Allocation of memory for a file   |       |       |
| 2001-10        | SCP-07  | SCP-010305  | 008 |     | F   | Correction of the CREATE FILE command   | 3.2.0 | 3.3.0 |
| 2002-09        | SCP-11  | SCP-020256  | 009 |     | F   | Clarification of the SFI management by the CREATE FILE command  | 3.3.0 | 3.4.0 |
| 2003-01        | SCP-12  | SCP-030020  | 011 |     | F   | Correction of return status conditions in case of technical problem.  | 3.4.0 | 6.0.0 |
|                |         | SCP-030075  | 012 | 1   | D   | Suppression of duplicated information with ETSI TS 102 221  |       |       |
|                |         | SCP030079   | 010 | 1   | D   | Reference ETSI TS 101 220 for definition of TLV   |       |       |
| 2003-05        | SCP-13  | SCP-030122  | 014 |     | B   | Additional Status Words for CREATE FILE and DELETE FILE command   | 6.0.0 | 6.1.0 |
| 2003-09        | SCP-14  | SCP-030224  | 016 |     | F   | Alignment of ETSI TS 102 222 with TC SCP specifications   | 6.1.0 | 6.2.0 |
| 2003-12        | SCP-15  | SCP2-030253 | 015 | 1   | B   | Addition of the RESIZE Command  | 6.2.0 | 6.3.0 |
|                |         | SCP2-030260 | 017 |     | C   | Clarification of DELETE FILE command  |       |       |
| 2004-02        | SCP-16  | SCP-040091  | 021 | 2   | B   | Addition of a filling pattern TLV in the CREATE FILE command for an EF  | 6.3.0 | 6.4.0 |
|                |         | SCP-040042  | 022 |     | D   | Deletion of two empty references  |       |       |
|                |         | SCP-040042  | 023 |     | C   | Description of deletion of a shareable file   |       |       |
|                |         | SCP-040090  | 024 | 1   | B   | Addition of a filling pattern TLV in the RESIZE command in case the size of an EF is increased.   |       |       |
|                |         | SCP-040042  | 025 |     | B   | Add "command not allowed" status condition in TERMINATE EF command  |       |       |
|                |         | SCP-040070  | 027 | 1   | B   | Introduction of EF <sub>SUME</sub> File   |       |       |
| 2004-05        | SCP-17  | SCP-040218  | 031 |     | D   | Renaming of Resize command to Resize File   | 6.4.0 | 6.5.0 |
|                |         | SCP-040218  | 028 |     | B   | Add "incorrect parameters in the data field" status condition in RESIZE command   |       |       |
|                |         | SCP-040218  | 029 |     | B   | Authorize Create File and Resize File on any channel  |       |       |
|                |         | SCP-040218  | 030 |     | B   | Addition of text attribute for the menu title   |       |       |
| 2004-09        | SCP-18  | SCP-040346  | 032 |     | F   | Correction of CLA byte for Create/Delete/Resize/Activate/Deactivate   | 6.5.0 | 6.6.0 |
|                |         | SCP-040346  | 033 |     | F   | Alignment with ETSI TS 102 221 terminology in status conditions   |       |       |
|                |         | SCP-040368  | 034 | 1   | B   | Add support for BER-TLV structure EF administration (Create and Resize)   |       |       |
| 2004-12        | SCP-19  | SCP-040415  | 038 |     | A   | Clarification of the interpretation of non specific references to other specifications  | 6.6.0 | 6.7.0 |
|                |         | SCP-040415  | 039 |     | C   | Allow Terminate commands on any logical channels  |       |       |
|                |         | SCP-040415  | 040 |     | F   | Change presence of proprietary tag of CREATE FILE to conditional and clarify presence of Maximum File Size tag of RESIZE command                              |       |       |
|                |         | SCP-040415  | 041 |     | F   | Correction of length coding of FCP template   |       |       |
|                |         | SCP-040415  | 042 |     | F   | Correction and clarifications   |       |       |
|                |         | SCP-040415  | 043 |     | D   | Editorial modifications linked to BER TLV file introduction   |       |       |

| Change history |         |             |     |     |     |  |        |        |
|----------------|---------|-------------|-----|-----|-----|--|--------|--------|
| Date           | Meeting | TC SCP Doc. | CR  | Rev | Cat | Subject/Comment  | Old    | New    |
| 2005-01        |         | SCPt040586  | 045 |     | F   | Missing modifications related to TERMINATE on all logical channels | 6.7.0  | 6.8.0  |
|                |         | SCPt040588  | 046 |     | F   | Clarification of DELETE FILE in case of concurrent EF file access  |        |        |
| 2005-09        | SCP-22  | SCP-050245  | 047 |     | F   | Remove DELETE without FID  | 6.8.0  | 6.9.0  |
|                |         | SCP-050275  | 048 |     | F   | Clarify definition of "current file"                               |        |        |
|                |         | SCP-050228  | 052 |     | A   | Modifications due to revision of ISO/IEC 7816 series               |        |        |
| 2005-12        | SCP-23  | SCP-050461  | 055 |     | F   | Clarification on RESIZE Command for shareable/non shareable files  | 6.9.0  | 6.10.0 |
| 2006-03        | SCP-25  | SCP-060141  | 056 |     | F   | Correction of a reference to a table for RESIZE command            | 6.10.0 | 6.11.0 |
| 2006-07        | SCP-26  | SCP-060281  | 054 | 3   | B   | Clarification on TERMINATE EF and TERMINATE DF Commands            | 6.11.0 | 7.0.0  |
| 2007-01        | SCP-29  | SCP-070054  | 056 |     | B   | EF for Action Commands   | 7.0.0  | 7.1.0  |
| 2018-07        | SCP#84  |             |     |     |     | Upgrade to Rel-8   | 7.1.0  | 8.0.0  |
| 2018-07        | SCP#84  |             |     |     |     | Upgrade to Rel-9   | 8.0.0  | 9.0.0  |
| 2018-07        | SCP#84  |             |     |     |     | Upgrade to Rel-10  | 9.0.0  | 10.0.0 |
| 2018-07        | SCP#84  |             |     |     |     | Upgrade to Rel-11  | 10.0.0 | 11.0.0 |

---

# History

| <b>Document history</b> |           |             |
|-------------------------|-----------|-------------|
| V11.0.0                 | July 2018 | Publication |
|                         |           |             |
|                         |           |             |
|                         |           |             |
|                         |           |             |