



**Intelligent Transport Systems (ITS);
Testing;
Conformance test specifications for GeoNetworking ITS-G5;
Part 1: Test requirements and Protocol Implementation
Conformance Statement (PICS) pro forma**

Reference

RTS/ITS-00343

Keywords

ITS, network, PICS, testing

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2015.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Contents

Intellectual Property Rights	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope	5
2 References	5
2.1 Normative references	5
2.2 Informative references.....	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	5
4 Conformance requirement concerning PICS.....	6
Annex A (normative): GEONETW PICS pro forma (Media independent)	7
A.1 Partial cancellation of copyright.....	7
A.2 Guidance for completing the ICS pro forma	7
A.2.1 Purposes and structure.....	7
A.2.2 Abbreviations and conventions	7
A.2.3 Instructions for completing the ICS pro forma.....	9
A.3 Identification of the implementation	9
A.3.1 Introduction	9
A.3.2 Date of the statement	9
A.3.3 Implementation Under Test (IUT) identification	9
A.3.4 System Under Test (SUT) identification	10
A.3.5 Product supplier.....	10
A.3.6 Client (if different from product supplier).....	10
A.3.7 ICS contact person.....	11
A.4 Identification of the protocol.....	11
A.5 Global statement of conformance.....	11
A.6 Tables	12
A.6.1 Introduction	12
A.6.2 Media independent	12
A.6.2.1 Introduction.....	12
A.6.2.2 GeoNetworking packet structure	12
A.6.2.3 Basic Header	12
A.6.2.4 Common Header.....	13
A.6.2.5 Extended Header.....	14
A.6.2.5.1 GUC packet.....	14
A.6.2.5.2 TSB packet.....	14
A.6.2.5.3 SHB packet	14
A.6.2.5.4 GBC/GAC packet	14
A.6.2.5.5 BEACON packet.....	14
A.6.2.5.6 LS Request header.....	15
A.6.2.5.7 LS Reply header.....	15
A.6.2.6 Common elements	15
A.6.2.6.1 Lifetime	15
A.6.2.6.2 Position	15
A.6.2.6.3 LongPositionVector	15
A.6.2.6.4 ShortPositionVector	16
A.6.2.6.5 GN_Addr.....	16
A.6.2.7 Protocol operation.....	16
A.6.2.8 Protocol constants	18
History	20

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Intelligent Transport Systems (ITS).

The present document is part 1 of a multi-part deliverable covering Conformance test specifications for Geonetworking ITS-G5 as identified below:

- Part 1: "**Test requirements and Protocol Implementation Conformance Statement (PICS) pro forma**";
- Part 2: "Test Suite Structure and Test Purposes (TSS & TP)";
- Part 3: "Abstract Test Suite (ATS) and Protocol Implementation eXtra Information for Testing (PIXIT)".

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

1 Scope

The present document provides the Protocol Implementation Conformance Statement (PICS) pro forma for Conformance test specifications for Geonetworking ITS-G5 as defined in ETSI EN 302 636-4-1 [1] in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [3].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <http://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI EN 302 636-4-1 (V1.2.1): "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 4: Geographical addressing and forwarding for point-to-point and point-to-multipoint communications; Sub-part 1: Media-Independent Functionality".
- [2] ISO/IEC 9646-1 (1994): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 1: General concepts".
- [3] ISO/IEC 9646-7 (1995): "Information technology - Open Systems Interconnection - Conformance testing methodology and framework - Part 7: Implementation Conformance Statements".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the reference document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

Not applicable.

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in ETSI EN 302 636-4-1 [1], ISO/IEC 9646-1 [2] and ISO/IEC 9646-7 [3] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BTP-A	Basic Transport Protocol A
BTP-B	Basic Transport Protocol B
CBF	Contention-Based Forwarding

DE_PV	Destination Position Vector
ELIP	Ellipse
GAC	Geographically-Scoped Anycast
GBC	Geographically-Scoped Broadcast
GUC	Geo Unicast
HST	Header Subtype
HT	Header Type
ICS	Implementation Conformance Statement
ITS	Intelligent Transportation Systems
ITS-G5	5 GHz wireless communication
IUT	Implementation Under Test
LS	Location Service
LT	Lifetime
MHL	Maximum Hop Limit
MID	MAC ID
NH	Next Header
PAI	Position Accuracy Indicator
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
PL	Payload Length
RHL	Remaining Hop Limit
SCC	Station Country Code
SHB	Single Hop Broadcast
SN	Sequence Number
SO_PV	Source Position Vector
ST	Station Type
SUT	System Under Test
TC	Test Case
TSB	Topology Scoped Broadcast
TST	Timestamp

4 Conformance requirement concerning PICS

If it claims to conform to the present document, the actual PICS pro forma to be filled in by a supplier shall be technically equivalent to the text of the PICS pro forma given in annex A, and shall preserve the numbering, naming and ordering of the pro forma items.

An ICS which conforms to the present document shall be a conforming PICS pro forma completed in accordance with the instructions for completion given in clause A.2

Annex A (normative): GEONETW PICS pro forma (Media independent)

A.1 Partial cancellation of copyright

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the GEONETW PICS pro forma in this annex so that it can be used for its intended purposes and may further publish the completed GEONETW PICS.

A.2 Guidance for completing the ICS pro forma

A.2.1 Purposes and structure

The purpose of this PICS pro forma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in ETSI EN 302 636-4-1 [1] may provide information about the implementation in a standardized manner.

The PICS pro forma is subdivided into clauses for the following categories of information:

- guidance for completing the ICS pro forma;
- identification of the implementation;
- identification of the ETSI EN 302 636-4-1 [1];
- global statement of conformance;
- PICS pro forma tables.

A.2.2 Abbreviations and conventions

The ICS pro forma contained in this annex is comprised of information in tabular form in accordance with the guidelines presented in ISO/IEC 9646-7 [3].

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g. parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Status column

The following notations, defined in ISO/IEC 9646-7 [3], are used for the status column:

m	mandatory - the capability is required to be supported.
o	optional - the capability may be supported or not.
n/a	not applicable - in the given context, it is impossible to use the capability.
x	prohibited (excluded) - there is a requirement not to use this capability in the given context.
o.i	qualified optional - for mutually exclusive or selectable options from a set. "i" is an integer which identifies an unique group of related optional items and the logic of their selection which is defined immediately following the table.
c.i	conditional - the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying an unique conditional status expression which is defined immediately following the table.
i	irrelevant (out-of-scope) - capability outside the scope of the reference specification. No answer is requested from the supplier.

NOTE 1: This use of "i" status is not to be confused with the suffix "i" to the "o" and "c" statuses above.

Reference column

The reference column makes reference to ETSI EN 302 636-4-1 [1], except where explicitly stated otherwise.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in ISO/IEC 9646-7 [3], are used for the support column:

Y or y	supported by the implementation.
N or n	not supported by the implementation.
N/A, n/a or -	no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status).

NOTE 2: As stated in ISO/IEC 9646-7 [3], support for a received PDU requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Values allowed column

The values allowed column contains the type, the list, the range, or the length of values allowed. The following notations are used:

- range of values: <min value> .. <max value>
example: 5 .. 20
- list of values: <value1>, <value2>, ..., <valueN>
example: 2, 4, 6, 8, 9
example: '1101'B, '1011'B, '1111'B
example: '0A'H, '34'H, '2F'H
- list of named values: <name1>(<val1>), <name2>(<val2>), ..., <nameN>(<valN>)
example: reject(1), accept(2)
- length: size (<min size> .. <max size>)
example: size (1 .. 8)

Values supported column

The values supported column shall be filled in by the supplier of the implementation. In this column, the values or the ranges of values supported by the implementation shall be indicated.

References to items

For each possible item answer (answer in the support column) within the ICS pro forma a unique reference exists, used, for example, in the conditional expressions. It is defined as the table identifier, followed by a solidus character "/", followed by the item number in the table. If there is more than one support column in a table, the columns are discriminated by letters (a, b, etc.), respectively.

EXAMPLE 1: A.5/4 is the reference to the answer of item 4 in table 5 of annex A.

EXAMPLE 2: A.6/3b is the reference to the second answer (i.e. in the second support column) of item 3 in table 6 of annex A.

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

A.2.3 Instructions for completing the ICS pro forma

The supplier of the implementation shall complete the ICS pro forma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support or supported column boxes provided.

If necessary, the supplier may provide additional comments in space at the bottom of the tables or separately.

More detailed instructions are given at the beginning of the different clauses of the ICS pro forma.

A.3 Identification of the implementation

A.3.1 Introduction

Identification of the Implementation Under Test (IUT) and the system in which it resides (the System Under Test (SUT)) shall be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information shall both be filled in if they are different.

A person who can answer queries regarding information supplied in the ICS shall be named as the contact person.

A.3.2 Date of the statement

.....

A.3.3 Implementation Under Test (IUT) identification

IUT name:

.....

.....

IUT version:

.....

A.3.4 System Under Test (SUT) identification

SUT name:

.....
.....

Hardware configuration:

.....
.....
.....

Operating system:

.....

A.3.5 Product supplier

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

A.3.6 Client (if different from product supplier)

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

A.3.7 ICS contact person

(A person to contact if there are any queries concerning the content of the ICS)

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

.....

A.4 Identification of the protocol

This ICS pro forma applies to the following standard:

ETSI EN 302 636-4-1 [1]: "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 4: Geographical addressing and forwarding for point-to-point and point-to-multipoint communications; Sub-part 1: Media independent functionalities".

A.5 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No)

NOTE: Answering "No" to this question indicates non-conformance to the GEONET standard specification. Non-supported mandatory capabilities are to be identified in the ICS, with an explanation of why the implementation is non-conforming, on pages attached to the ICS pro forma.

A.6 Tables

A.6.1 Introduction

Unless stated otherwise, the column references of all tables below indicates the clause numbers of ETSI EN 302 636-4-1 [1].

A.6.2 Media independent

A.6.2.1 Introduction

This clause of the ICS pro forma applies to the following standard: ETSI EN 302 636-4-1 [1]: "Intelligent Transport Systems (ITS); Vehicular Communications; GeoNetworking; Part 4: Geographical addressing and forwarding for point-to-point and point-to-multipoint communications; Sub-part 1: Media-Independent Functionality".

A.6.2.2 GeoNetworking packet structure

Table A.1: GeoNetworking packet structure

Item	Name of field	Reference	Status	Support
1	Basic Header	8.3	m	
2	Common Header	8.3	m	
3	Extended Header	8.3	m	
4	Payload	8.2.2	o	

Table A.2: GeoNetworking secured packet structure

Item	Name of field	Reference	Status	Support
1	Basic Header	8.4	m	
2	Secured packet	8.4	m	

A.6.2.3 Basic Header

Table A.3: Basic Header

Prerequisite: A.1/1 or A.2/1					
It.	Name of field	Ref.	Status	Support	Value allowed
1	version	8.6	m		0 .. 255
2	next Header (NH)	8.6	m		0 .. 255, Any unspecified (0), Unsecured packet (1), Secured packet (2)
3	reserved	8.6	m		8-bit unsigned integer (0)
4	Lifetime (LT)	8.6	m		Lifetime (Table A.14)
5	hop Limit (RHL)	8.6	m		8-bit unsigned integer

A.6.2.4 Common Header

Table A.4: Common Header

Prerequisite: A.1/2					
It.	Name of field	Ref.	Status	Support.	Value allowed
1	next Header (NH)	8.7	m		0 .. 255, Any unspecified (0), BTP-A (1), BTP-B (2), IPV6 (3)
2	reserved	8.7	m		4 bit unsigned integer
3	header Type (HT)	8.7	m		HeaderType (Table A.5)
4	header Subtype (HST)	8.7	m		HeaderSubtype (Table A.6)
5	traffic Class (TC)	8.7	m		0 .. 255
6	flags	8.7	m		Bitstring size (8) Bit 0 to 5: Reserved (0) Bit 6: Type of ITS station Bit 7: Reserved (0)
7	payload Length (PL)	8.7	m		16-bit unsigned integer
8	Maximum Hop Limit (MHL)	8.7	m		8-bit unsigned integer
9	reserved	8.7	m		8-bit unsigned integer (0)

Table A.5: HeaderType

Prerequisite: A.4/3					
It.	Name of field	Ref.	Status	Support	Value allowed
1	type	8.7.4	m		4 bit unsigned integer: ANY (0), BEACON (1), GEOUNICAST (2), GEOANYCAST (3), GEOBROADCAST (4), TSB (5), LS (6)

Table A.6: HeaderSubtype

Prerequisite: A.4/4					
It.	Name of field	Ref.	Status	Support	Value allowed
1	type	8.7.4	m		Bitstring size (4) values: c.601
c.601:					
IF A.4/3 == GEOANYCAST (3)		THEN	value == CIRCLE (0), RECT (1), ELIP (2)		
ELSE					
IF A.4/3 == GEOBROADCAST (4)		THEN	value == CIRCLE (0), RECT (1), ELIP (2)		
ELSE					
IF A.4/3 == TSB (5)		THEN	value == SINGLE_HOP (0), MULTI_HOP (1)		
ELSE					
IF A.4/3 == LS (6)		THEN	value == REQUEST (0), REPLY (1)		
ELSE			value == Unspecified (0)		

A.6.2.5 Extended Header

A.6.2.5.1 GUC packet

Table A.7: GUC Header

Prerequisite: A.1/3					
It.	Name of field	Ref.	Status	Support	Value allowed
1	Sequence Number (SN)	8.8.2	m		16-bit unsigned integer
2	Reserved	8.8.2	m		16-bit unsigned integer (0)
3	Source Position Vector (SO_PV)	8.8.2	m		LongPositionVector (Table A.16)
4	Destination Position Vector (DE_PV)	8.8.2	m		ShortPositionVector (Table A.17)

A.6.2.5.2 TSB packet

Table A.8: TSB Header

Prerequisite: A.1/3					
It.	Name of field	Ref.	Status	Support	Value allowed
1	Sequence Number (SN)	8.8.3	m		16-bit unsigned integer.
2	Reserved	8.8.3	m		16-bit unsigned integer (0)
3	Source Position Vector (SO_PV)	8.8.3	m		LongPositionVector (Table A.16)

A.6.2.5.3 SHB packet

Table A.9: SHB Header

Prerequisite: A.1/3					
It.	Name of field	Ref.	Status	Support	Value allowed
1	Source Position Vector (SO_PV)	8.8.4	m		LongPositionVector (Table A.16)
2	Reserved	8.8.4	m		32-bit unsigned integer (0)

A.6.2.5.4 GBC/GAC packet

Table A.10: GBC/GAC Header

Prerequisite: A.1/3					
It.	Name of field	Ref.	Status	Support	Value allowed
1	Sequence Number (SN)	8.8.5	m		16-bit unsigned integer
2	Reserved	8.8.5	m		16-bit unsigned integer (0)
3	Source Position Vector (SO_PV)	8.8.5	m		LongPositionVector (Table A.16)
4	GeoAreaPos	8.8.5	m		Position (Table A.15)
5	Distance a	8.8.5	m		16-bit unsigned integer
6	Distance b	8.8.5	m		16-bit unsigned integer
7	Angle	8.8.5	m		16-bit unsigned integer
8	Reserved	8.8.5	m		16-bit unsigned integer

A.6.2.5.5 BEACON packet

Table A.11: BEACON Header

Prerequisite: A.1/3					
It.	Name of field	Ref.	Status	Support.	Value allowed
1	Source Position Vector (SO_PV)	8.8.6	m		LongPositionVector (Table A.16)

A.6.2.5.6 LS Request header

Table A.12: LS Request header

Prerequisite: A.1/3					
It.	Name of field	Ref.	Status	Support	Value allowed
1	Sequence Number (SN)	8.8.7	m		16-bit unsigned integer
2	Reserved	8.8.7	m		16-bit unsigned integer (0)
3	Source Position Vector (SO_PV)	8.8.7	m		LongPositionVector (Table A.16)
4	Request	8.8.7	m		GN_Addr (Table A.18)

A.6.2.5.7 LS Reply header

Table A.13: LS Reply header

Prerequisite: A.1/3					
It.	Name of field	Ref.	Status	Support	Value allowed
1	Sequence Number (SN)	8.8.8	m		16-bit unsigned integer
2	Reserved	8.8.8	m		16-bit unsigned integer (0)
3	Source Position Vector (SO_PV)	8.8.8	m		LongPositionVector (Table A.16)
4	Destination Position Vector (DE_PV)	8.8.8	m		ShortPositionVector (Table A.17)

A.6.2.6 Common elements

A.6.2.6.1 Lifetime

Table A.14: Lifetime

Prerequisite: A.3/2					
It.	Name of field	Ref.	Status	Support.	Value allowed
1	multiplier	8.6.4	m		Bitstring size (6) == (0 .. 63)
2	base	8.6.4	m		Bitstring size (2) value 50 ms (0), 1 s (1), 10 s (2), 100 s (3)

A.6.2.6.2 Position

Table A.15: Position

Prerequisite: A.10/4 or A.16/3 or A.17/3					
It.	Name of field	Ref.	Status	Support.	Value allowed
1	Latitude (Lat)	8.5.2.2 8.8.5.2	m		32-bit signed integer
2	Longitude (Long)	8.5.2.2 8.8.5.2	m		32-bit signed integer.

A.6.2.6.3 LongPositionVector

Table A.16: LongPositionVector

Prerequisite: A.7/3 or A.8/3 or A.9/1 or A.10/3 or A.11/1 or A.12/3 or A.13/3					
It.	Name of field	Ref.	Status	Support	Value allowed
1	GeoNetworking address (GN_Addr)	8.5.2	m		GN_Addr (Table A.18)
2	Time Stamp (TST)	8.5.2	m		32-bit unsigned integer
3	Latitude/Longitude	8.5.2	m		Position (Table A.15)
4	Position accuracy (PAI)	8.5.2	m		1-bit unsigned integer
5	Speed (S)	8.5.2	m		15-bit signed integer
6	Heading (H)	8.5.2	m		16-bit unsigned integer

A.6.2.6.4 ShortPositionVector

Table A.17: ShortPositionVector

Prerequisite: A.7/4 or A.13/4					
It.	Name of field	Ref.	Status	Support	Value allowed
1	GeoNetworking address (GN_Addr)	8.5.3	m		GN_Addr (Table A.18)
2	Time Stamp (TST)	8.5.3	m		32-bit unsigned integer
3	Latitude/Longitude	8.5.3	m		Position (Table A.15)

A.6.2.6.5 GN_Addr

Table A.18: GN_Addr

Prerequisite: A.12/4 or A.16/1 or A.17/1					
It.	Name of field	Ref.	Status	Support	Value allowed
1	Configuration (M)	6.3	m		1 bit unsigned integer 1 = the address is manually configured 0 = otherwise
2	ITS Station Type (ST)	6.3	m		4 bits unsigned integer 0 Unknown 1 Pedestrian 2 Cyclist 3 Moped 4 Motorcycle 5 Passenger Car 6 Bus 7 Light Truck 8 Heavy Truck 9 Trailer 10 Special Vehicle 11 Tram 15 Road Side Unit
3	ITS Station Country Code (SCC)	6.3	m		10 bits unsigned integer
4	LL_ADDR (MID)	6.3	m		48 bits unsigned integer

A.6.2.7 Protocol operation

Table A.19: Protocol operation

Item	Name of field	Reference	Status	Support
1	Network management	9.2	m	
2	Packet handling	9.3	m	

Table A.20: Network management

Prerequisite: A.19/1				
Item	Name of field	Reference	Status	Support
1	Address configuration	9.2.1	m	
2	Local position vector and time update	9.2.2	m	
3	Beaconing	9.2.3	m	
4	Location service	9.2.4	m	

Table A.21: Address configuration

Prerequisite: A.201				
Item	Name of field	Reference	Status	Support
1	Auto-address configuration	9.2.1.2	m	
2	Managed address configuration	9.2.1.3	m	
3	Anonymous address configuration	9.2.1.4	m	
4	Duplicate address detection	9.2.1.5	m	

Table A.22: Managed address configuration

Prerequisite: A.21/2				
Item	Name of field	Reference	Status	Support
1	Initial address configuration	9.2.1.3.1	m	
2	Address update	9.2.1.3.2	m	

Table A.23: Local position and time update

Prerequisite: A.202				
Item	Name of field	Reference	Status	Support
1	Local position vector update	9.2.2.2	m	
2	Time update	9.2.2.3	m	

Table A.24: Packet handling

Prerequisite: A.19/2				
Item	Name of field	Reference	Status	Support
1	Basic Header field settings	9.3.2	m	
2	Basic Header processing	9.3.3	m	
3	Common Header field settings	9.3.4	m	
4	Common Header processing	9.3.5	m	
5	Beacon packet handling	9.3.6	m	
6	Location service packet handling	9.3.7	m	
7	GUC packet handling	9.3.8	m	
8	TSB packet handling	9.3.9	m	
9	SHB packet handling	9.3.10	m	
10	GBC packet handling	9.3.11	m	
11	GAC packet handling	9.3.12	m	

Table A.25: Beacon packet handling

Prerequisite: A.24/5				
Item	Name of field	Reference	Status	Support
1	Source operations	9.3.6.2	m	
2	Receiver operations	9.3.6.3	m	

Table A.26: Location service packet handling

Prerequisite: A.24/6				
Item	Name of field	Reference	Status	Support
1	Source operation for initial LS Request	9.3.7.1.2	m	
2	Source operation for LS Request re-transmission	9.3.7.1.3	m	
3	Source operation for LS Reply	9.3.7.1.4	m	
4	Forwarder operations	9.3.7.2	m	
5	Destination operations	9.3.7.3	m	

Table A.27: GUC Packet handling

Prerequisite: A.24/7				
Item	Name of field	Reference	Status	Support
1	Source operations	9.3.8.2	m	
2	Forwarder operations	9.3.8.3	m	
3	Destination operations	9.3.8.4	m	

Table A.28: TSB Packet handling

Prerequisite: A.24/8				
Item	Name of field	Reference	Status	Support
1	Source operations	9.3.9.2	m	
2	Forwarder and receiver operations	9.3.9.3	m	

Table A.29: SHB Packet handling

Prerequisite: A.24/9				
Item	Name of field	Reference	Status	Support
1	Source operations	9.3.10.2	m	
2	Receiver operations	9.3.10.3	m	

Table A.30: GBC Packet handling

Prerequisite: A.24/10				
Item	Name of field	Reference	Status	Support
1	Source operations	9.3.11.2	m	
2	Forwarder and receiver operations	9.3.11.3	m	

Table A.31: GAC Packet handling

Prerequisite: A.24/11				
Item	Name of field	Reference	Status	Support
1	Source operations	9.3.12.2	m	
2	Forwarder and receiver operations	9.3.12.3	m	

A.6.2.8 Protocol constants

Table A.32: Protocol constants

Item	Constant	Ref.	Status	Value allowed	Value
1	itsGnLocalGnAddr	Annex G	m	0 .. 2 ⁴⁸ -1	
2	itsGnLocalAddrConfMethod	Annex G	m	Auto (0) Managed (1) Anonymous (2)	
3	itsGnProtocolVersion	Annex G	m	V1.2.1 (0)	
4	itsGnStationType	Annex G	m	Unknown (0) Pedestrian (1) Cyclist (2) Moped (3) Motorcycle (4) PassengerCar (5) Bus (6) LightTruck (7) HeavyTruck (8) Trailer (9) SpecialVehicles (10) Tram (11) RoadSideUnit (15)	
5	itsGnIsMobile	Annex G	m	Stationary (0) Mobile (1)	
6	itsGnIfType	Annex G	m	Unspecified (0) ITS-G5 (1)	
7	itsGnMinimumUpdateFrequencyLPV	Annex G	m	0 .. 65 635	
8	itsGnPaiInterval	Annex G	m	0 .. 100	
9	itsGnMaxSduSize	Annex G	m	0 .. 65 635	
10	itsGnMaxGeoNetworkingHeaderSize	Annex G	m	0 .. 65 635	
11	itsGnLifetimeLocTE	Annex G	m	0 .. 65 635	

Item	Constant	Ref.	Status	Value allowed	Value
12	itsGnSecurity	Annex G	m	DISABLED (0) ENABLED (1)	
13	itsGnSnDecapResultHandling	Annex G	m	STRICT (0) NON-STRICT (1)	
14	itsGnLocationServiceMaxRetrans	Annex G	m	0 .. 255	
15	itsGnLocationServiceRetransmitTimer	Annex G	m	0 .. 65 635	
16	itsGnLocationServicePacketBufferSize	Annex G	m	0 .. 65 635	
17	itsGnBeaconServiceRetransmitTimer	Annex G	m	0 .. 65 635	
18	itsGnBeaconServiceMaxJitter	Annex G	m	itsGnMaxPacketLifetime / 4	
19	itsGnDefaultHopLimit	Annex G	m	0 .. 255	
20	itsGnMaxPacketLifetime	Annex G	m	0 .. 6 300	
21	itsGnDefaultPacketLifetime	Annex G	m	0 .. 6 300	
22	itsGnMaxPacketDataRate	Annex G	m	0 .. 65 635	
23	itsGnMaxPacketDataRateEmaBeta	Annex G	m	0 .. 65 635	
24	itsGnMaxGeoAreaSize	Annex G	m	0 .. 65 635	
25	itsGnMinPacketRepetitionInterval	Annex G	m	0 .. 1 000	
26	itsGnGeoUnicastForwardingAlgorithm	Annex G	m	UNSPECIFIED (0) GREEDY (1) CBF (2)	
27	itsGnGeoBroadcastForwardingAlgorithm	Annex G	m	UNSPECIFIED (0) SIMPLE (1) CBF(2) ADVANCED (3)	
28	itsGnGeoUnicastCbfMinTime	Annex G	m	0 .. 65 635	
29	itsGnGeoUnicastCbfMaxTime	Annex G	m	0 .. 65 635	
30	itsGnGeoBroadcastCbfMinTime	Annex G	m	0 .. 65 635	
31	itsGnGeoBroadcastCbfMaxTime	Annex G	m	0 .. 65 635	
32	itsGnDefaultMaxCommunicationRange	Annex G	m	0 .. 65 635	
33	itsGnBroadcastCBFDefSectorAngle	Annex G	m	0 .. 360	
34	itsGnUnicastCBFDefSectorAngle	Annex G	m	0 .. 360	
35	itsGnGeoAreaLineForwarding	Annex G	m	DISABLED (0) ENABLED (1)	
36	itsGnUcForwardingPacketBufferSize	Annex G	m	0 .. 255	
37	itsGnBcForwardingPacketBufferSize	Annex G	m	0 .. 65 635	
38	itsGnCbfPacketBufferSize	Annex G	m	0 .. 65 635	
39	itsGnDefaultTrafficClass	Annex G	m	0 .. 255	

History

Document history		
V1.1.1	June 2011	Publication
V1.2.1	April 2014	Publication
V1.3.1	June 2015	Publication