

ETSI TS 103 572 V1.3.1 (2021-08)



**HDR Signalling and Carriage of Dynamic Metadata
for Colour Volume Transform;
Application #1**

EBU

Reference

RTS/JTC-061

Keywordsbroadcasting, content, distribution, HDR, HDTV,
UHDTV, video**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2021.

© European Broadcasting Union 2021.

All rights reserved.

Contents

Intellectual Property Rights	4
Foreword.....	4
Modal verbs terminology.....	4
Introduction	5
1 Scope	6
2 References	6
2.1 Normative references	6
2.2 Informative references.....	6
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	7
3.2.1 Arithmetic operators	7
3.2.2 Relational operators	7
3.2.3 Assignment operators	8
3.2.4 Mathematical functions.....	8
3.3 Abbreviations	8
4 ST2094-10_data() structure definition	9
4.1 Introduction	9
4.2 ST2094-10_data() structure syntax	9
4.3 ST2094-10_data() structure semantics	10
Annex A (informative): SMPTE ST 2094-10 HDR Dynamic Metadata in MPEG-2 TS for DVB Systems	15
A.1 Introduction	15
History	16

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This Technical Specification (TS) has been produced by Joint Technical Committee (JTC) Broadcast of the European Broadcasting Union (EBU), Comité Européen de Normalisation ELECTrotechnique (CENELEC) and the European Telecommunications Standards Institute (ETSI).

NOTE: The EBU/ETSI JTC Broadcast was established in 1990 to co-ordinate the drafting of standards in the specific field of broadcasting and related fields. Since 1995 the JTC Broadcast became a tripartite body by including in the Memorandum of Understanding also CENELEC, which is responsible for the standardization of radio and television receivers. The EBU is a professional association of broadcasting organizations whose work includes the co-ordination of its members' activities in the technical, legal, programme-making and programme-exchange domains. The EBU has active members in about 60 countries in the European broadcasting area; its headquarters is in Geneva.

European Broadcasting Union
CH-1218 GRAND SACONNEX (Geneva)
Switzerland
Tel: +41 22 717 21 11
Fax: +41 22 717 24 81

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

SMPTE ST 2094-10 [4] HDR dynamic metadata provides and describes dynamic information about the video signal. The usage of this information can be employed by the display to adapt the delivered HDR imagery to the capability of the display device. The information conveyed in the SEI or VSEI messages carrying SMPTE ST 2094-10 [4] HDR dynamic metadata is adequate for purposes corresponding to the use of Society of Motion Picture and Television Engineers SMPTE ST 2094-1 [3] and SMPTE ST 2094-10 [4].

1 Scope

The present document specifies the format of the SEI or VSEI messages for the carriage of SMPTE ST 2094-10 [4] HDR dynamic metadata.

The present document includes references for the carriage and signalling the presence of SMPTE ST 2094-10 [4] HDR dynamic metadata (carried in SEI messages defined in the present document) for DVB systems, as defined in ETSI TS 101 154 [i.3], ETSI TS 103 285 [9] and ETSI EN 300 468 [i.2].

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] SMPTE ST 2084: "High Dynamic Range Electro-Optical Transfer Function of Mastering Reference Displays".
- [2] SMPTE ST 2086: "Mastering Display Color Volume Metadata Supporting High Luminance and Wide Color Gamut Images".
- [3] SMPTE ST 2094-1: "Dynamic Metadata for Color Volume Transform - Core Components".
- [4] SMPTE ST 2094-10: "Dynamic Metadata for Color Volume Transform - Application #1".
- [5] Recommendation ITU-T H.265 | ISO/IEC 23008-2: "Information technology -- High efficiency coding and media delivery in heterogeneous environments -- Part 2: High efficiency video coding".
- [6] Void.
- [7] Void.
- [8] Void.
- [9] Void.
- [10] Void.
- [11] Recommendation ITU-T H.274 (08-2020) "Versatile supplemental enhancement information messages for coded video bitstreams".

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] Recommendation ITU-R BT.2246-2: "The present state of ultra-high definition television".
- [i.2] ETSI EN 300 468: "Digital Video Broadcasting (DVB); Specification for Service Information (SI) in DVB systems".
- [i.3] ETSI TS 101 154: "Digital Video Broadcasting (DVB); Specification for the use of Video and Audio Coding in Broadcast and Broadband Applications".
- [i.4] ETSI TS 103 285: "Digital Video Broadcasting (DVB); MPEG-DASH Profile for Transport of ISO BMFF Based DVB Services over IP Based Networks".

3 Definition of terms, symbols and abbreviations

3.1 Terms

For the purposes of the present document, the following terms apply:

display mapping: adapting the signal to the dynamic range and the colour gamut of the target display

dynamic range: ratio of the maximum light intensity to the minimum light intensity [i.1]

NOTE: In digital cameras the dynamic range is normally measured in terms of stops, which describe the total light range by power of 2.

extended display mapping metadata: subset of the ST2094_data() structure

high dynamic range: typically, a dynamic range of more than 10 stops is referred to as high dynamic range

standard dynamic range: typically, a dynamic range of up to 10 stops is referred to as standard dynamic range

Supplemental Enhancement Information (SEI) message: carriage mechanism defined in Recommendation ITU-T H.265 [5] and in Recommendation ITU-T H.274 [11] that is intended to assist in processes related to decoding, display or other purposes

3.2 Symbols

3.2.1 Arithmetic operators

For the purposes of the present document, the following arithmetic operators apply:

+	Addition
-	Subtraction (as a two-argument operator) or negation (as a unary prefix operator)
×	Multiplication, including matrix multiplication
÷	Used to denote division in mathematical equations where no truncation or rounding is intended
/	Integer division with truncation of the result toward zero

EXAMPLE: $7/4$ and $-7/-4$ are truncated to 1 and $-7/4$ and $7/-4$ are truncated to -1.

3.2.2 Relational operators

For the purposes of the present document, the following relational operators apply:

>	Greater than
>=	Greater than or equal to
<	Less than
<=	Less than or equal to
==	Equal to

!= Not equal to

3.2.3 Assignment operators

For the purposes of the present document, the following assignment operators apply:

=	Assignment operator
++	Increment, i.e. x is equivalent to $x = x + 1$; when used in an array index, evaluates to the value of the variable prior to the increment operation
--	Decrement, i.e. $x-$ is equivalent to $x = x - 1$; when used in an array index, evaluates to the value of the variable prior to the decrement operation
+=	Increment by amount specified, i.e. $x += 4$ is equivalent to $x = x + 4$, and $x += (-4)$ is equivalent to $x = x + (-4)$
-=	Decrement by amount specified, i.e. $x -= 4$ is equivalent to $x = x - 4$, and $x -= (-4)$ is equivalent to $x = x - (-4)$

3.2.4 Mathematical functions

For the purposes of the present document, the following mathematical functions apply:

$$\text{Abs}(x) = \begin{cases} x & ; \quad x \geq 0 \\ -x & ; \quad x < 0 \end{cases}$$

$$\text{Clip3}(x, y, z) = \begin{cases} x & ; \quad z < x \\ y & ; \quad z > y \\ z & ; \quad \textit{otherwise} \end{cases}$$

Floor(x) the largest integer less than or equal to x .

$$\text{Round}(x) = \text{Sign}(x) * \text{Floor}(\text{Abs}(x) + 0.5)$$

$$\text{Sign}(x) = \begin{cases} 1 & ; \quad x > 0 \\ 0 & ; \quad x = 0 \\ -1 & ; \quad x < 0 \end{cases}$$

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CVS	Coded Video Sequence
EN	European Standard
HDR	High Dynamic Range
HEVC	High Efficiency Video Coding
ITU-R	International Telecommunications Union - Radiocommunications standardization sector
ITU-T	International Telecommunications Union - Telecommunications standardization sector
MPEG	Moving Picture Expert Group
PQ	Perceptual Quantizer

NOTE: As defined in SMPTE ST 2084 [1].

SEI	Supplemental Enhancement Information
SI	Service Information
SMPTE	Society of Motion Pictures and Television Engineers
ST	STandard
UHDTV	Ultra High Definition TeleVision
VVC	Versatile Video Coding
VSEI	Versatile Supplemental Enhancement Information

4 ST2094-10_data() structure definition

4.1 Introduction

This clause specifies the syntax and semantics of ST2094-10_data() structure.

Clause 4.2 defines the syntax of the ST2094-10_data() structure.

Clause 4.3 defines the semantics of the ST2094-10_data() structure.

The metadata elements of the ST2094-10_data() structure are defined according to the SMPTE ST 2086 [2], SMPTE ST 2094-1 [3] and SMPTE ST 2094-10 [4].

4.2 ST2094-10_data() structure syntax

The parsing process of each syntax element by the descriptor u(n) is described in Recommendation ITU-T H.265 [5] for HEVC and VSEI [11] for VVC.

Table 1: ST2094-data() syntax

ST2094-10_data () {	Descriptor
app_identifier	ue(v)
app_version	ue(v)
metadata_refresh_flag	u(1)
if(metadata_refresh_flag) {	
num_ext_blocks	ue(v)
if(num_ext_blocks) {	
while(!byte_aligned())	
dm_alignment_zero_bit	f(1)
for(i = 0; i < num_ext_blocks; i ++) {	
ext_dm_data_block(i)	
}	
}	
while(!byte_aligned())	
dm_alignment_zero_bit	f(1)
}	

Table 2: ext_dm_data_block() syntax

ext_dm_metadata_block(i) {	Descriptor
ext_block_length [i]	ue(v)
ext_block_level [i]	u(8)
ext_dm_data_block_payload(ext_block_length[i], ext_block_level [i])	
}	

Table 3: ext_dm_data_block_payload() syntax

ext_dm_data_block_payload(ext_block_length, ext_block_level) {	Descriptor
ext_block_len_bits = 8 * ext_block_length	
ext_block_use_bits = 0	
if(ext_block_level == 1) {	
min_PQ	u(12)
max_PQ	u(12)
avg_PQ	u(12)
ext_block_use_bits += 36	
}	
if(ext_block_level == 2) {	
target_max_PQ	u(12)
trim_slope	u(12)
trim_offset	u(12)
trim_power	u(12)
trim_chroma_weight	u(12)
trim_saturation_gain	u(12)
ms_weight	i(13)
ext_block_use_bits += 85	
}	
if(ext_block_level == 3) {	
min_PQ_offset	u(12)
max_PQ_offset	u(12)
avg_PQ_offset	u(12)
ext_block_use_bits += 36	
}	
if(ext_block_level == 4) {	
TF_PQ_mean	u(12)
TF_PQ_stdev	u(12)
ext_block_use_bits += 24	
}	
if(ext_block_level == 5) {	
active_area_left_offset	u(13)
active_area_right_offset	u(13)
active_area_top_offset	u(13)
active_area_bottom_offset	u(13)
ext_block_use_bits += 52	
}	
while(ext_block_use_bits++ < ext_block_len_bits)	
ext_dm_alignment_zero_bit	f(1)
}	

4.3 ST2094-10_data() structure semantics

app_identifier identifies an application and shall be set equal to 1 according to constraints of the section 5 of SMPTE ST 2094-10 [4].

app_version specifies the application version in the application and shall be set equal to 0 according to constraints of the section 5 of SMPTE ST 2094-10 [4].

metadata_refresh_flag when set equal to 1 cancels the persistence of any previous extended display mapping metadata in output order and indicates that extended display mapping metadata follows. The extended display mapping metadata persists from the coded picture to which the SEI message containing ST2094-10_data() is associated (inclusive) to the coded picture to which the next SEI message containing ST2094-10_data() and with **metadata_refresh_flag** set equal to 1 in output order is associated (exclusive) or (otherwise) to the last picture in the CVS (inclusive). When set equal to 0 this flag indicates that the extended display mapping metadata does not follow.

num_ext_blocks specifies the number of extended display mapping metadata blocks. The value shall be in the range of 1 to 254, inclusive.

dm_alignment_zero_bit shall be equal to 0.

ext_block_length[i] is used to derive the size of the i-th extended display mapping metadata block payload in bytes. The value shall be in the range of 0 to 1 023, inclusive.

ext_block_level[i] specifies the level of payload contained in the i-th extended display mapping metadata block. The value shall be in the range of 0 to 255, inclusive. The corresponding extended display mapping metadata block types are defined in Table 4. Values of **ext_block_level**[i] that are reserved shall not be present in the bitstreams conforming to this version of the present document. Blocks using reserved values shall be ignored:

- When the value of **ext_block_level**[i] is set equal to 1, the value of **ext_block_length**[i] shall be set equal to 5.
- When the value of **ext_block_level**[i] is set equal to 2, the value of **ext_block_length**[i] shall be set equal to 11.
- When the value of **ext_block_level**[i] is set equal to 3, the value of **ext_block_length**[i] shall be set equal to 5.
- When the value of **ext_block_level**[i] is set equal to 4, the value of **ext_block_length**[i] shall be set equal to 3.
- When the value of **ext_block_level**[i] is set equal to 5, the value of **ext_block_length**[i] shall be set equal to 7.

Table 4: Definition of extended display mapping metadata block type

ext_block_level	extended display mapping metadata block type
0	Reserved
1	Level 1 Metadata - Content Range
2	Level 2 Metadata - Trim Pass
3	Level 3 Metadata - Content Range Offsets
4	Level 4 Metadata - Temporally Filtered Image Level
5	Level 5 Metadata - Active Area
6...255	Reserved

When an extended display mapping metadata block with **ext_block_level** equal to 5 is present, the following constraints shall apply:

- An extended display mapping metadata block with **ext_block_level** equal to 5 shall be preceded by at least one extended display mapping metadata block with **ext_block_level** equal to 1, 2, 3 or 4.
- Between any two extended display mapping metadata blocks with **ext_block_level** equal to 5, there shall be at least one extended display mapping metadata block with **ext_block_level** equal to 1, 2, 3 or 4.
- No extended display mapping metadata block with **ext_block_level** equal to 1, 2, 3 or 4 shall be present after the last extended display mapping metadata block with **ext_block_level** equal to 5.
- The metadata of an extended display mapping metadata block with **ext_block_level** equal to 1, 2, 3 or 4 shall be applied to the active area specified by the first extended display mapping metadata block with **ext_block_level** equal to 5 following this block.
- When the active area defined by the current extended display mapping metadata block with **ext_block_level** equal to 5 overlaps with the active area defined by preceding extended display mapping metadata blocks with **ext_block_level** equal to 5, all metadata of the extended display mapping metadata blocks with **ext_block_level** equal to 1, 2, 3 or 4 associated with the current extended display mapping metadata block with **ext_block_level** equal to 5 shall be applied to the pixel values of the overlapping area.

min_PQ specifies the minimum luminance value of the current picture in 12-bit PQ encoding. The value shall be in the range of 0 to 4 095, inclusive. Note that the 12-bit **min_PQ** value with full range is calculated as follows:

$$\text{min_PQ} = \text{Clip3}(0, 4\,095, \text{Round}(\text{Min} \times 4\,095)) \quad (1)$$

where **Min** is **MinimumPqencodedMaxrgb** as defined in clause 6.1.3 of SMPTE ST 2094-10 [4].

max_PQ specifies the maximum luminance value of current picture in 12-bit PQ encoding. The value shall be in the range of 0 to 4 095, inclusive. Note that the 12-bit max_PQ value with full range is calculated as follows:

$$\text{max_PQ} = \text{Clip3}(0, 4\,095, \text{Round}(\text{Max} \times 4\,095)) \quad (2)$$

where Max is MaximumPqencodedMaxrgb as defined in clause 6.1.5 of SMPTE ST 2094-10 [4].

avg_PQ specifies the midpoint luminance value of current picture in 12-bit PQ encoding. The value shall be in the range of 0 to 4 095, inclusive. Note that the 12-bit avg_PQ value with full range is calculated as follows:

$$\text{avg_PQ} = \text{Clip3}(0, 4\,095, \text{Round}(\text{Avg} \times 4\,095)) \quad (3)$$

where Avg is AveragePqencodedMaxrgb as defined in section 6.1.4 of SMPTE ST 2094-10 [4].

target_max_PQ specifies the maximum luminance value of a target display in 12-bit PQ encoding. The value shall be in the range of 0 to 4 095, inclusive. The target_max_PQ is the PQ encoded value of TargetedSystemDisplayMaximumLuminance as defined in clause 10.4 of SMPTE ST 2094-1 [3].

If there is more than one extended display mapping metadata block with ext_block_level equal to 2, those blocks shall have no duplicated target_max_PQ.

trim_slope specifies the slope metadata. The value shall be in the range of 0 to 4 095, inclusive. If trim_slope is not present, it shall be inferred to be 2 048. Note that the 12-bit slope value is calculated as follows:

$$\text{trim_slope} = \text{Clip3}(0, 4\,095, \text{Round}((S - 0,5) \times 4\,096)) \quad (4)$$

where S is the ToneMappingGain as defined in clause 6.2.3 of SMPTE ST 2094-10 [4].

trim_offset specifies the offset metadata. The value shall be in the range of 0 to 4 095, inclusive. If trim_offset is not present, it shall be inferred to be 2 048. Note that the 12-bit offset value is calculated as follows:

$$\text{trim_offset} = \text{Clip3}(0, 4\,095, \text{Round}((O + 0,5) \times 4\,096)) \quad (5)$$

where O is the ToneMappingOffset as defined in clause 6.2.2 of SMPTE ST 2094-10 [4].

trim_power specifies the power metadata. The value shall be in the range of 0 to 4 095, inclusive. If trim_power is not present, it shall be inferred to be 2 048. Note that the 12-bit power value is calculated as follows:

$$\text{trim_power} = \text{Clip3}(0, 4\,095, \text{Round}((P - 0,5) \times 4\,096)) \quad (6)$$

where P is the ToneMappingGamma as defined in clause 6.2.4 of SMPTE ST 2094-10 [4].

trim_chroma_weight specifies the chroma weight metadata. The value shall be in the range of 0 to 4 095, inclusive. If trim_chroma_weight is not present, it shall be inferred to be 2 048. Note that the 12-bit chroma weight value is calculated as follows:

$$\text{trim_chroma_weight} = \text{Clip3}(0, 4\,095, \text{Round}((CW + 0,5) \times 4\,096)) \quad (7)$$

where CW is the ChromaCompensationWeight as defined in clause 6.3.1 of SMPTE ST 2094-10 [4].

trim_saturation_gain specifies the saturation gain metadata. The value shall be in the range of 0 to 4 095, inclusive. If trim_saturation_gain is not present, it shall be inferred to be 2 048. Note that the 12-bit saturation gain value is calculated as follows:

$$\text{trim_saturation_gain} = \text{Clip3}(0, 4\,095, \text{Round}((SG + 0,5) \times 4\,096)) \quad (8)$$

where SG is the SaturationGain as defined in clause 6.3.2 of SMPTE ST 2094-10 [4].

ms_weight this field is reserved for future specification. This 13-bit signed integer shall be 0x1fff (-1).

min_PQ_offset specifies a creative adjustment to **min_PQ**. The value shall be in the range of 0 to 4 095, inclusive. This integer range encodes the normalized PQ value range [-1.0, 1.0] inclusive, as specified in section 6.1.6 of SMPTE ST 2094-10 [4].

If min_PQ_offset is not present, it shall be inferred to be 2 048. This default value corresponds to the encoded normalized PQ value of 0.0 as specified in section 6.1.6 of SMPTE ST 2094-10 [4].

The 12-bit `min_PQ_offset` value is calculated as follows:

$$\text{min_PQ_offset} = \text{Clip3}(0, 4\,095, \text{Round}((\text{Min_Offset} + 1) \times 2\,048)) \quad (9)$$

where `Min_Offset` is `MinimumPqencodedMaxrgbOffset` as defined in section 6.1.6 of SMPTE ST 2094-10 [4].

max_PQ_offset specifies a creative adjustment to **max_PQ**. The value shall be in the range of 0 to 4 095, inclusive. This integer range encodes the normalized PQ value range [-1.0, 1.0] inclusive, as specified in section 6.1.8 of SMPTE ST 2094-10 [4].

If `max_PQ_offset` is not present, it shall be inferred to be 2 048. This default value corresponds to the encoded normalized PQ value of 0.0 as specified in section 6.1.8 of SMPTE ST 2094-10 [4].

The 12-bit `max_PQ_offset` value is calculated as follows:

$$\text{max_PQ_offset} = \text{Clip3}(0, 4\,095, \text{Round}((\text{Max_Offset} + 1) \times 2\,048)) \quad (10)$$

where `Max_Offset` is `MaximumPqencodedMaxrgbOffset` as defined in section 6.1.8 of SMPTE ST 2094-10 [4].

avg_PQ_offset specifies a creative adjustment to **avg_PQ**. The value shall be in the range of 0 to 4 095, inclusive. This integer range encodes the normalized PQ value range [-1.0, 1.0] inclusive, as specified in section 6.1.7 of SMPTE ST 2094-10 [4].

If `avg_PQ_offset` is not present, it shall be inferred to be 2 048. This default value corresponds to the encoded normalized PQ value of 0.0 as specified in section 6.1.7 of SMPTE ST 2094-10 [4].

The 12-bit `avg_PQ_offset` value is calculated as follows:

$$\text{avg_PQ_offset} = \text{Clip3}(0, 4\,095, \text{Round}((\text{Avg_Offset} + 1) \times 2\,048)) \quad (11)$$

where `Avg_Offset` is `AveragePqencodedMaxrgbOffset` as defined in section 6.1.7 of SMPTE ST 2094-10 [4].

TF_PQ_mean specifies the temporally filtered mean of the maximum RGB value of the current frame. The value shall be in the range of 0 to 4 095, inclusive. Note that the 12-bit `TF_PQ_mean` value for i^{th} frame `TF_PQ_meani` is calculated as follows:

$$\text{TF_PQ_norm_mean}_i = \text{TF_PQ_norm_mean}_{i-1} * (1 - \alpha) + \text{mean}(\text{PQ}(\text{maxRGB}_i)) * \alpha \quad (12)$$

where `maxRGB` is defined in section 4.1.1 of SMPTE ST 2094-1 [3] and in the range [0, 1], and:

$$\alpha = \min(1, \min(1, (SC * |\text{mean}(\text{PQ}(\text{maxRGB}_i)) - \text{mean}(\text{PQ}(\text{maxRGB}_{i-1}))| * 8 + 0,1) * 24/\text{framerate})) \quad (13)$$

The value of `SC` is set to 1 at a scene boundary; otherwise the value of `SC` is set to 0:

$$\text{TF_PQ_mean}_i = \text{Clip3}(0, 4\,095, \text{Round}(\text{TF_PQ_norm_mean}_i \times 4\,095)) \quad (14)$$

NOTE 1: For an initial frame where there is no $i-1$ frame, a default value for `TF_PQ_mean` of 1 474 (0,36) may be used.

TF_PQ_stdev specifies the temporally filtered standard deviation of the maximum RGB value of the current frame. The value shall be in the range of 0 to 4 095, inclusive. Note that the 12 bit - value for i^{th} frame `TF_PQ_stdevi` is calculated as follows:

$$\text{TF_PQ_norm_stdev}_i = \text{TF_PQ_norm_stdev}_{i-1} * (1 - \alpha) + \text{stdev}(\text{PQ}(\text{maxRGB}_i)) * \alpha \quad (15)$$

where `maxRGB` is defined in section 4.1.1 of SMPTE ST 2094-1 [3] and in the range [0, 1], and:

$$\alpha = \min(1, \min(1, (SC * |\text{mean}(\text{PQ}(\text{maxRGB}_i)) - \text{mean}(\text{PQ}(\text{maxRGB}_{i-1}))| * 8 + 0.1) * 24/\text{framerate})) \quad (16)$$

The value of `SC` is set to 1 at a scene boundary; otherwise the value of `SC` is set to 0:

$$\text{TF_PQ_stdev}_i = \text{Clip3}(0, 4\,095, \text{Round}(\text{TF_PQ_norm_stdev}_i \times 4\,095)) \quad (17)$$

NOTE 2: For an initial frame where there is no $i-1$ frame, a default value for `TF_PQ_stdev` of 0 may be used.

NOTE 3: The alpha value is calculated to ensure a smooth transition between scenes. The scene boundary can be determined by an appropriate mechanism, such as in the encoder.

active_area_left_offset, active_area_right_offset, active_area_top_offset, active_area_bottom_offset specify the selected pixels of the current picture, in terms of a rectangular region specified in picture coordinates for active area. The values shall be in the range of 0 to 8 191, inclusive. See also ProcessingWindow definitions in SMPTE ST 2094-10 [4].

active_area_left_offset, active_area_right_offset, active_area_top_offset, active_area_bottom_offset represent the coordinates of UpperLeftCorner and LowerRightCorner constrained in clause 7.1 of SMPTE ST 2094-10 [4] as follows:

$$\begin{aligned} \text{UpperLeftCorner} &= (\text{active_area_left_offset}, \text{active_area_top_offset}) \\ \text{LowerRightCorner} &= (\text{XSize} - 1 - \text{active_area_right_offset}, \text{YSize} - 1 - \text{active_area_bottom_offset}) \end{aligned} \quad (18)$$

where Xsize is the horizontal resolution of the current picture and Ysize is the vertical resolution of the current picture.

ext_dm_alignment_zero_bit shall be equal to 0.

Annex A (informative): SMPTE ST 2094-10 HDR Dynamic Metadata in MPEG-2 TS for DVB Systems

A.1 Introduction

This annex was removed as the carriage and signalling of SMPTE ST 2094-10 [4] HDR dynamic metadata in DVB systems compliant streams has now been defined in ETSI TS 101 154 [i.3], ETSI TS 103 285 [9] and ETSI EN 300 468 [i.2].

History

Document history		
V1.1.1	March 2018	Publication
V1.1.2	July 2018	Publication
V1.2.1	October 2020	Publication
V1.3.1	August 2021	Publication