



**Core Network and Interoperability Testing (INT);  
VoLTE/ViLTE interoperability test description over  
4G/early 5G in physical/virtual environments;  
(3GPP™ Release 15);**  
**Part 3: Abstract Test Suite (ATS) and partial Protocol  
Implementation eXtra Information for Testing (PIXIT)  
for VoLTE/ViLTE interoperability**

---

Reference

DTS/INT-00159-3

---

Keywords

ATS, interoperability, PIXIT, ViLTE, VoLTE

***ETSI***

---

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

***Important notice***

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.  
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

---

***Copyright Notification***

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.  
All rights reserved.

**DECT™, PLUGTESTS™, UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and  
of the 3GPP Organizational Partners.

**oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and  
of the oneM2M Partners.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

## Contents

Intellectual Property Rights .....	4
Foreword.....	4
Modal verbs terminology.....	4
1 Scope .....	5
2 References .....	5
2.1 Normative references .....	5
2.2 Informative references.....	6
3 Definition of terms, symbols and abbreviations.....	7
3.1 Terms.....	7
3.2 Symbols.....	7
3.3 Abbreviations .....	7
4 Abstract Test Method (ATM).....	7
4.1 Introduction .....	7
4.2 Test architecture .....	7
4.3 Interconnection of TS and SUT.....	10
4.4 Implementation of TS.....	10
4.5 Test Adapter .....	12
<b>Annex A (normative):      VoLTE/ViLTE interoperability over 4G/early 5G in physical/virtual environments Partial PIXIT pro forma.....</b>	<b>13</b>
A.1 The right to copy .....	13
A.2 Identification summary.....	13
A.3 ATS summary .....	13
A.4 Test laboratory.....	13
A.5 Client identification.....	13
A.6 SUT .....	14
A.7 Protocol layer information.....	14
A.8 PIXIT items .....	14
A.8.1 Introduction .....	14
A.8.2 PIXIT items for the Gm Interface .....	14
A.8.3 PIXIT items for the Ic Interface .....	15
A.8.4 PIXIT items for the Mw Interface .....	15
A.8.5 PIXIT items for the ISC Interface .....	15
A.8.6 PIXIT items for the Cx Interface.....	15
A.8.7 PIXIT items for the Gx Interface.....	16
A.8.8 PIXIT items for the Rx Interface .....	16
A.8.9 PIXIT items for the S6a Interface .....	16
A.8.10 PIXIT items for the S9 Interface .....	16
A.8.11 PIXIT items for the Sh Interface .....	17
A.8.12 Interface independent PIXIT items.....	17
A.8.13 LibCommon items.....	17
<b>Annex B (normative):      Abstract Test Suite (ATS) .....</b>	<b>18</b>
B.1 The TTCN-3 Module.....	18
<b>Annex C (informative):      Bibliography .....</b>	<b>19</b>
History .....	20

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Core Network and Interoperability Testing (INT).

The present document is part 3 of a multi-part deliverable. Full details of the entire series can be found in part 1 [11].

---

## Modal verbs terminology

In the present document "shall", "shall not", "should", "should not", "may", "need not", "will", "will not", "can" and "cannot" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"must" and "must not" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# 1 Scope

The present document specifies the Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) pro forma for the VoLTE/VoLTE interoperability test description over 4G/early 5G in physical/virtual environments in compliance with the relevant requirements and in accordance with the relevant guidance given in ISO/IEC 9646-7 [i.3] and ETSI ETS 300 406 [i.4].

The test notation used in the ATS is TTCN-3 (see ETSI ES 201 873-1 [i.5]).

The following test specification and design considerations can be found in the body of the present document:

- the overall test suite structure;
- the testing architecture;
- the test methods and port definitions;
- the test configurations;
- TTCN styles and conventions;
- the partial PIXIT pro forma;
- the modules containing the TTCN-3 ATS.

Annex A provides the Partial Implementation Extra Information for Testing (PIXIT) pro forma.

Annex B provides the Abstract Test Suite (ATS) part of the ATS.

---

## 2 References

### 2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found at <https://docbox.etsi.org/Reference/>.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are necessary for the application of the present document.

- [1] ETSI TS 124 229: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; 5G; IP multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3 (3GPP TS 24.229 Release 15)".
- [2] ETSI TS 129 165: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; 5G; Inter-IMS Network to Network Interface (NNI) (3GPP TS 29.165 Release 15)".
- [3] ETSI TS 129 228: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; IP Multimedia (IM) Subsystem Cx and Dx Interfaces; Signalling flows and message contents (3GPP TS 29.228 Release 15)".
- [4] ETSI TS 129 229: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Cx and Dx interfaces based on the Diameter protocol; Protocol details (3GPP TS 29.229 Release 15)".

- [5] ETSI TS 129 214: "Universal Mobile Telecommunications System (UMTS); LTE; 5G; Policy and charging control over Rx reference point (3GPP TS 29.214 Release 15)".
- [6] ETSI TS 129 212: "Universal Mobile Telecommunications System (UMTS); LTE; 5G; Policy and Charging Control (PCC); Reference points (3GPP TS 29.212 Release 15)".
- [7] ETSI TS 129 272: "Universal Mobile Telecommunications System (UMTS); LTE; 5G; Evolved Packet System (EPS); Mobility Management Entity (MME) and Serving GPRS Support Node (SGSN) related interfaces based on Diameter protocol (3GPP TS 29.272 Release 15)".
- [8] ETSI TS 129 215: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Policy and Charging Control (PCC) over S9 reference point; Stage 3 (3GPP TS 29.215 Release 15)".
- [9] ETSI TS 129 328: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; 5G; IP Multimedia (IM) Subsystem Sh interface; Signalling flows and message contents (3GPP TS 29.328 Release 15)".
- [10] ETSI TS 129 329: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Sh interface based on the Diameter protocol; Protocol details (3GPP TS 29.329 Release 15)".
- [11] ETSI TS 103 653-1: "Core Network and Interoperability Testing (INT); VoLTE/ViLTE interoperability test description over 4G/early 5G in physical/virtual environments; (3GPP™ Release 15); Part 1: Test Purposes (TP) and Protocol Implementation Conformance Statement (PICS) for VoLTE/ViLTE interoperability".
- [12] ISO/IEC 9646-6: "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 6: Protocol profile test specification".

## 2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long term validity.

The following referenced documents are not necessary for the application of the present document but they assist the user with regard to a particular subject area.

- [i.1] ETSI TS 132 299: "Digital cellular telecommunications system (Phase 2+) (GSM); Universal Mobile Telecommunications System (UMTS); LTE; Telecommunication management; Charging management; Diameter charging applications (3GPP TS 32.299 Release 15)".
- [i.2] ISO/IEC 9646-1: "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 1: General concepts".
- [i.3] ISO/IEC 9646-7: "Information technology -- Open Systems Interconnection -- Conformance testing methodology and framework -- Part 7: Implementation Conformance Statements".
- [i.4] ETSI ETS 300 406: "Methods for testing and Specification (MTS); Protocol and profile conformance testing specifications; Standardization methodology".
- [i.5] ETSI ES 201 873-1: "Methods for Testing and Specification (MTS); The Testing and Test Control Notation version 3; Part 1: TTCN-3 Core Language".

---

## 3 Definition of terms, symbols and abbreviations

### 3.1 Terms

For the purposes of the present document, the terms given in ISO/IEC 9646-7 [i.3], ETSI TS 124 229 [1], ETSI TS 129 165 [2], ETSI TS 129 228 [3], ETSI TS 129 229 [4], ETSI TS 132 299 [i.1], ETSI TS 129 214 [5], ETSI TS 129 212 [6], ETSI TS 129 272 [7], ETSI TS 129 215 [8], ETSI TS 129 328 [9] and ETSI TS 129 329 [10] apply.

### 3.2 Symbols

Void.

### 3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ISO/IEC 9646-1 [i.2], ISO/IEC 9646-6 [12], ISO/IEC 9646-7 [i.3], ETSI TS 124 229 [1], ETSI TS 129 165 [2], ETSI TS 129 228 [3], ETSI TS 129 229 [4], ETSI TS 132 299 [i.1], ETSI TS 129 214 [5], ETSI TS 129 212 [6], ETSI TS 129 272 [7], ETSI TS 129 215 [8], ETSI TS 129 328 [9] and ETSI TS 129 329 [10] apply.

---

## 4 Abstract Test Method (ATM)

### 4.1 Introduction

The following clauses describes the ATM used to test the VoLTE/VoLITE interoperability over 4G/early 5G in physical/virtual environments.

### 4.2 Test architecture

The test architecture foreseen is a complex system of all involved components. The following figures give an overview. Figure 1 shows the network entities involved in the interoperability testing and the mapping to test components. Figure 2 adds a more technical view of the implementation plans for the test system components.





Figure 1: VxLTE interoperability test system configuration



**Figure 2: VxLTE interoperability test component view**

## 4.3 Interconnection of TS and SUT

The interconnection of the Test System (TS) and the System Under Test (SUT) is depicted in figure 2.

The ImsTestCoordinator controls the overall test execution by coordinating the ImsInterfacesMonitor components on the SIP and Diameter interfaces under observation. It synchronizes those test components and receives individual test verdicts from them which are processed for the determination of the final overall test verdict.

ImsTestCoordinator and the ImsInterfacesMonitor components connect through the IoTSystemInterface to the SUT. The ImsEquipmentUser entity is responsible for the connection and management of external equipment.

## 4.4 Implementation of TS

The implementation of the TS in TTCN-3 is depicted in figure 3 which gives the names of all test components and the related TTCN-3 ports, variables and timers. It also shows the connections between the test components via ImsCoordinationPort, VerdictPort and SyncPort and the connections to the IoTSystemInterface via SipPort, DiameterPort, eaPort and acPort.




Figure 3: VxLTE interoperability test component implementation

## 4.5 Test Adapter

For execution of the tests the Test Adapter (TA) will be developed. For the Diameter interfaces there are two possibilities for communicate over the TA that have to be considered:

- ATS provides only Diameter messages; or
- ATS provides Diameter messages and LL primitives.

---

## Annex A (normative): VoLTE/ViLTE interoperability over 4G/early 5G in physical/virtual environments Partial PIXIT pro forma

### A.1 The right to copy

Notwithstanding the provisions of the copyright clause related to the text of the present document, ETSI grants that users of the present document may freely reproduce the Partial PIXIT pro forma in this annex so that it can be used for its intended purposes and may further publish the completed Partial PIXIT.

The PIXIT pro forma is based on ISO/IEC 9646-6 [12]. Any additional information which may be needed can be found in this international standard document.

---

### A.2 Identification summary

**Table A.1**

PIXIT Number:	
Test Laboratory Name:	
Date of Issue:	
Issued to:	

---

### A.3 ATS summary

**Table A.2**

Protocol Specification:	This interoperability test specification covers several protocol specifications for the SIP and DIAMETER protocols. In the below tables, references are given to the protocol specifications in force per interface.
Protocol to be tested:	
ATS Specification:	ETSI TS 103 653-3, annex B
Abstract Test Method:	ETSI TS 103 653-3, clause 4

---

### A.4 Test laboratory

**Table A.3**

Test Laboratory Identification:	
Test Laboratory Manager:	
Means of Testing:	
SAP Address:	

---

### A.5 Client identification

**Table A.4**

Client Identification:	
Client Test manager:	
Test Facilities required:	

## A.6 SUT

**Table A.5**

Name:	
Version:	
SCS Number:	
Machine configuration:	
Operating System Identification:	
IUT Identification:	
PICS Reference for IUT:	
Limitations of the SUT:	
Environmental Conditions:	

## A.7 Protocol layer information

The protocol identification is presented in the clauses below per interface.

The PICS reference for all interfaces is: ETSI TS 103 653-1 [11].

## A.8 PIXIT items

### A.8.1 Introduction

Tables in this clause need to be filled by the IUT Manufacturer to specify how the IUT needs to be configured with IUT specific values or describe IUT specific procedures required for complete testing of the IUT.

The present document describes interoperability testing spanning several interfaces. For a better understanding, namely in cases where not all interfaces are under observation, the PIXIT tables are presented per interface under test.

Each PIXIT item corresponds to a Module Parameter of the ATS.

### A.8.2 PIXIT items for the Gm Interface

The Gm interface connects a UE with a P-CSCF using the SIP and SDP protocols as defined in ETSI TS 124 229 [1].

**Table A.6: Gm interface ports and addresses for network A**

It.	Identifier	Type	Description
1	PX_SIP_GMA_UE_IPADDR	Charstring	Gm IP address of UE
2	PX_SIP_GMA_UE_PORT	Integer	Gm Port number of UE
3	PX_SIP_GMA_PCSCF_IPADDR	Charstring	Gm IP address of P-CSCF
4	PX_SIP_GMA_PCSCF_PORT	Integer	Gm Port number of P-CSCF
5	PX_SIP_GMA_MONITORENABLED	Boolean	Is monitoring of the Gm interface at network A enabled?

**Table A.7: Gm interface ports and addresses for network B**

It.	Identifier	Type	Description
1	PX_SIP_GMB_UE_IPADDR	Charstring	Gm IP address of UE
2	PX_SIP_GMB_UE_PORT	Integer	Gm Port number of UE
3	PX_SIP_GMB_PCSCF_IPADDR	Charstring	Gm IP address of P-CSCF
4	PX_SIP_GMB_PCSCF_PORT	Integer	Gm Port number of P-CSCF
5	PX_SIP_GMB_MONITORENABLED	Boolean	Is monitoring of the Gm interface at network B enabled?

### A.8.3 PIXIT items for the Ic Interface

The Ic interface connects an IBCF with another IBCF using the SIP and SDP protocols as defined in ETSI TS 129 165 [2].

**Table A.8: Ic interface ports and addresses**

It.	Identifier	Type	Description
1	PX_SIP_IC_IBCF_A_IPADDR	Charstring	Ic IP address of IBCF of network A
2	PX_SIP_IC_IBCF_A_PORT	Integer	Ic Port number of IBCF of network A
3	PX_SIP_IC_IBCF_B_IPADDR	Charstring	Ic IP address of IBCF of network B
4	PX_SIP_IC_IBCF_B_PORT	Integer	Ic Port number of IBCF of network B
5	PX_SIP_IC_MONITORENABLED	Boolean	Is monitoring of the Ic interface enabled?

### A.8.4 PIXIT items for the Mw Interface

The Mw interface connects an x-CSCF with another x-CSCF or an IBCF using the SIP and SDP protocols as defined in ETSI TS 124 229 [1].

**Table A.9: Mw interface ports and addresses**

It.	Identifier	Type	Description
1	PX_SIP_MW_P_CSCF_IPADDR	Charstring	Mw IP address of P-CSCF
2	PX_SIP_MW_P_CSCF_PORT	Integer	Mw Port number of P-CSCF
3	PX_SIP_MW_I_CSCF_IPADDR	Charstring	Mw IP address of I-CSCF
4	PX_SIP_MW_I_CSCF_PORT	Integer	Mw Port number of I-CSCF
5	PX_SIP_MW_S_CSCF_IPADDR	Charstring	Mw IP address of S-CSCF
6	PX_SIP_MW_S_CSCF_PORT	Integer	Mw Port number of S-CSCF
7	PX_SIP_MW_IBCF_IPADDR	Charstring	Mw IP address of IBCF
8	PX_SIP_MW_IBCF_PORT	Integer	Mw Port number of IBCF
9	PX_SIP_MW_MONITORENABLED	Boolean	Is monitoring of the Mw interface enabled?

### A.8.5 PIXIT items for the ISC Interface

The ISC interface connects an S-CSCF with an AS using the SIP and SDP protocols as defined in ETSI TS 129 165 [2].

**Table A.10: Ic interface ports and addresses**

It.	Identifier	Type	Description
1	PX_SIP_ISC_S_CSCF_IPADDR	Charstring	Ic IP address of S-CSCF
2	PX_SIP_ISC_S_CSCF_PORT	Integer	Ic Port number of S-CSCF
3	PX_SIP_ISC_AS_IPADDR	Charstring	Ic IP address of AS
4	PX_SIP_ISC_AS_PORT	Integer	Ic Port number of AS
5	PX_SIP_ISC_MONITORENABLED	Boolean	Is monitoring of the ISC interface enabled?

### A.8.6 PIXIT items for the Cx Interface

The Cx interface connects an I- or S-CSCF with an HSS using the Diameter protocol as defined ETSI TS 129 228 [3] and ETSI TS 129 229 [4].

**Table A.11: Cx interface ports and addresses**

It.	Identifier	Type	Description
1	PX_DIAMETER_CX_I_CSCF_IPADDR	Charstring	Cx IP address of I-CSCF
2	PX_DIAMETER_CX_I_CSCF_PORT	Integer	Cx Port number of I-CSCF
3	PX_DIAMETER_CX_S_CSCF_IPADDR	Charstring	Cx IP address of S-CSCF
4	PX_DIAMETER_CX_S_CSCF_PORT	Integer	Cx Port number of S-CSCF
5	PX_DIAMETER_CX_HSS_IPADDR	Charstring	Cx IP address of HSS
6	PX_DIAMETER_CX_HSS_PORT	Integer	Cx Port number of HSS
7	PX_DIAMETER_CX_MONITORENABLED	Boolean	Is monitoring of the Cx interface enabled?

## A.8.7 PIXIT items for the Gx Interface

The Gx interface connects a PCRF with a PGW using the Diameter protocol as defined in ETSI TS 129 212 [6].

**Table A.12: Gx interface ports and addresses**

It.	Identifier	Type	Description
1	PX_DIAMETER_GX_PCRF_IPADDR	Charstring	Gx IP address of PCRF
2	PX_DIAMETER_GX_PCRF_PORT	Integer	Gx Port number of PCRF
3	PX_DIAMETER_GX_PGW_IPADDR	Charstring	Gx IP address of PGW
4	PX_DIAMETER_GX_PGW_PORT	Integer	Gx Port number of PGW
5	PX_DIAMETER_GX_MONITORENABLED	Boolean	Is monitoring of the Gx interface enabled?

## A.8.8 PIXIT items for the Rx Interface

The Rx interface connects a P-CSCF with a PCRF using the Diameter protocol as defined in ETSI TS 129 214 [5].

**Table A.13: Rx interface ports and addresses**

It.	Identifier	Type	Description
1	PX_DIAMETER_RX_P_CSCF_IPADDR	Charstring	Rx IP address of P-CSCF
2	PX_DIAMETER_RX_P_CSCF_PORT	Integer	Rx Port number of P-CSCF
3	PX_DIAMETER_RX_PCRF_IPADDR	Charstring	Rx IP address of PCRF
4	PX_DIAMETER_RX_PCRF_PORT	Integer	Rx Port number of PCRF
5	PX_DIAMETER_RX_MONITORENABLED	Boolean	Is monitoring of the Rx interface enabled?

## A.8.9 PIXIT items for the S6a Interface

The S6a interface connects an MME with an HSS using the Diameter protocol as defined in ETSI TS 129 272 [7].

**Table A.14: S6a interface ports and addresses**

It.	Identifier	Type	Description
1	PX_DIAMETER_S6A_MME_IPADDR	Charstring	S6a IP address of MME
2	PX_DIAMETER_S6A_MME_PORT	Integer	S6a Port number of MME
3	PX_DIAMETER_S6A_HSS_IPADDR	Charstring	S6a IP address of HSS
4	PX_DIAMETER_S6A_HSS_PORT	Integer	S6a Port number of HSS
5	PX_DIAMETER_S6A_MONITORENABLED	Boolean	Is monitoring of the S6a interface enabled?

## A.8.10 PIXIT items for the S9 Interface

The S9 interface connects an H-PCRF with a V-PCRF using the Diameter protocol as defined in ETSI TS 129 215 [8].

**Table A.15: S9 interface ports and addresses**

It.	Identifier	Type	Description
1	PX_DIAMETER_S9_H_PCRF_IPADDR	Charstring	S9 IP address of H-PCRF
2	PX_DIAMETER_S9_H_PCRF_PORT	Integer	S9 Port number of H-PCRF
3	PX_DIAMETER_S9_V_PCRF_IPADDR	Charstring	S9 IP address of V-PCRF
4	PX_DIAMETER_S9_V_PCRF_PORT	Integer	S9 Port number of V-PCRF
5	PX_DIAMETER_S9_MONITORENABLED	Boolean	Is monitoring of the S9 interface enabled?

## A.8.11 PIXIT items for the Sh Interface

The Sh interface connects an AS with an HSS using the Diameter protocol as defined in ETSI TS 129 328 [9] and ETSI TS 129 329 [10].

**Table A.16: Sh interface ports and addresses**

It.	Identifier	Type	Description
1	PX_DIAMETER_SH_AS_IPADDR	Charstring	Sh IP address of AS
2	PX_DIAMETER_SH_AS_PORT	Integer	Sh Port number of AS
3	PX_DIAMETER_SH_HSS_IPADDR	Charstring	Sh IP address of HSS
4	PX_DIAMETER_SH_HSS_PORT	Integer	Sh Port number of HSS
5	PX_DIAMETER_SH_MONITORENABLED	Boolean	Is monitoring of the Sh interface enabled?

## A.8.12 Interface independent PIXIT items

**Table A.17: Interface independent PIXIT items**

It.	Identifier	Type	Description
1	PX_MAX_MSG_WAIT	Float	Maximum time limit used by monitor components for waiting for expected incoming messages
2	PX_EUT_TRIGGER_RESPONSE	Float	Maximum time limit used by trigger component for waiting for EUT response after command has been sent

## A.8.13 LibCommon items

**Table A.18: PIXIT for LibCommon**

It.	Identifier	Type	Description
1	PX_TSYNC_TIME_LIMIT	Float	Default time limit for a sync client to reach a synchronization point
2	PX_TSHUT_DOWN_TIME_LIMIT	Float	Default time limit for a sync client to finish its execution of the shutdown default

---

## Annex B (normative): Abstract Test Suite (ATS)

### B.1 The TTCN-3 Module

This ATS has been produced using the Testing and Test Control Notation (TTCN-3) according to ETSI ES 201 873-1 [i.5].

The TTCN-3 library modules corresponding to the ATS are contained in archive ts\_10365303v010101p0.zip which accompanies the present document.

---

## Annex C (informative): Bibliography

- ETSI TS 103 653-2: "Core Network and Interoperability Testing (INT); VoLTE/VoLTE interoperability test description over 4G/early 5G in physical/virtual environments; (3GPP™ Release 15); Part 2: Test Descriptions for VoLTE/VoLTE interoperability".

---

## History

<b>Document history</b>		
V1.1.1	August 2020	Publication