

ETSI TS 119 615 V1.4.1 (2026-05)



TECHNICAL SPECIFICATION

**Electronic Signatures and Trust Infrastructures (ESI);
Trusted lists;
Procedures for using and interpreting European Union
Member States national trusted lists**

Reference

RTS/ESI-0019615v141

Keywordse-commerce, electronic signature, EU qualified,
security, trust services**ETSI**650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards](#) application.

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver](#) repository.

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2026.
All rights reserved.

Contents

Intellectual Property Rights	5
Foreword.....	5
Modal verbs terminology.....	5
Introduction	5
1 Scope	7
2 References	7
2.1 Normative references	7
2.2 Informative references.....	7
3 Definition of terms, symbols, abbreviations and notations	8
3.1 Terms.....	8
3.2 Symbols.....	8
3.3 Abbreviations	8
3.4 Notations	8
4 Procedures for using and interpreting European Union Member States national trusted lists	9
4.0 General provisions.....	9
4.1 Authenticating the EC compiled list of trusted lists	9
4.1.1 Description.....	9
4.1.2 Inputs	11
4.1.3 Outputs.....	11
4.1.4 Processing	11
4.2 Authenticating an EUMS trusted list.....	15
4.2.1 Description.....	15
4.2.2 Inputs	15
4.2.3 Outputs.....	15
4.2.4 Processing.....	15
4.3 Obtaining listed services matching a certificate	16
4.3.1 Description.....	16
4.3.2 Inputs	16
4.3.3 Outputs.....	17
4.3.4 Processing	17
4.4 EU qualified certificate determination	19
4.4.1 Description.....	19
4.4.2 Inputs	19
4.4.3 Outputs.....	20
4.4.4 Processing.....	20
4.5 QSCD determination	34
4.5.1 Description.....	34
4.5.2 Inputs	34
4.5.3 Outputs.....	34
4.5.4 Processing.....	34
4.6 EU trust service token issuer qualification determination	37
4.6.1 Description.....	37
4.6.2 Inputs	37
4.6.3 Outputs.....	37
4.6.4 Processing.....	38
4.7 EU qualified time stamp determination.....	39
4.7.1 Description.....	39
4.7.2 Inputs	39
4.7.3 Outputs.....	40
4.7.4 Processing.....	40
4.8 EU qualified validation service determination	41
4.8.1 Description.....	41
4.8.2 Inputs	41
4.8.3 Outputs.....	42

4.8.4	Processing	42
4.9	EU qualified preservation service determination	43
4.9.1	Description	43
4.9.2	Inputs	44
4.9.3	Outputs	44
4.9.4	Processing	44
4.10	EU qualified electronic registered delivery service determination	45
4.10.1	Description	45
4.10.2	Inputs and parameters	46
4.10.3	Outputs	46
4.10.4	Processing	46
4.11	EU qualified archiving service determination	47
4.11.1	Description	47
4.11.2	Inputs	48
4.11.3	Outputs	48
4.11.4	Processing	48
4.12	EU qualified electronic attestation of attribute service determination	49
4.12.1	Description	49
4.12.2	Inputs	49
4.12.3	Outputs	49
4.12.4	Processing	49
4.13	EU qualified ledger service determination	50
4.13.1	Description	50
4.13.2	Inputs	50
4.13.3	Outputs	50
4.13.4	Processing	51
Annex A (informative):	Void	52
Annex B (normative):	Output sub-statuses changes	53
Annex C (informative):	Bibliography	54
Annex D (informative):	Change history	55
History		56

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Foreword

This Technical Specification (TS) has been produced by ETSI Technical Committee Electronic Signatures and Trust Infrastructures (ESI).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Introduction

Trusted lists, as specified by ETSI TS 119 612 [1], enable in practice any interested party to determine whether a trust service is or was operating in compliance with relevant requirements, currently or at a given time in the past (e.g. at the time the service was provided, or at the time at which a transaction reliant on that service took place).

ETSI TS 119 612 [1] provides specifications supporting the establishment and management of trusted lists in two contexts, namely the European Union (EU) legislative context as set by Regulation (EU) No 910/2014 [i.1] and the context of countries outside the European Union and the EEA countries, or of international organizations willing to issue trusted lists in accordance with ETSI TS 119 612 [1].

The actual specifications for EU Member States (EUMS) national trusted lists are provided in Commission Implementing Decision (EU) 2015/1505 [i.2] laying down technical specifications and formats relating to trusted lists pursuant to Article 22(5) of Regulation (EU) No 910/2014 [i.1]. Those specifications and formats build upon ETSI TS 119 612 [1].

EUMS trusted lists have a legal constitutive value. It is the single formal source to verify that a claimed qualified trust service is indeed granted a qualified status by the competent EUMS body.

The rules for using and interpreting EUMS national trusted lists are provided in CID (EU) 2015/1505 [i.2]. The present document specifies procedures allowing for implementing those rules when validating EU qualified trust service outputs against such EUMS trusted lists (e.g. validating qualified certificates, EU qualified time stamps, evidences created by qualified electronic registered delivery services, EU electronic signatures or seals on EU qualified validation reports on EU qualified electronic signatures or seals).

1 Scope

The present document specifies procedures for using and interpreting EUMS national trusted lists when validating EU qualified trust service outputs against them (e.g. validating EU qualified certificates, EU qualified time stamps, evidences created by qualified electronic registered delivery services, EU electronic signatures or seals on EU qualified validation reports on EU qualified electronic signatures or seals).

2 References

2.1 Normative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

Referenced documents which are not found to be publicly available in the expected location might be found in the [ETSI docbox](#).

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents are necessary for the application of the present document.

- [1] [ETSI TS 119 612 \(V2.4.1\)](#): "Electronic Signatures and Trust Infrastructures (ESI); Trusted Lists".
- [2] [ISO 3166-1:2020](#): "Codes for the representation of names of countries and their subdivisions - Part 1: Country codes".
- [3] [ETSI EN 319 412-5](#): "Electronic Signatures and Trust Infrastructures (ESI); Certificate Profiles; Part 5: QCStatements".
- [4] [IETF RFC 5280](#): "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile".
- [5] T7 & Teletrust: "[Common PKI Specifications for Interoperable Applications](#)", Specification Part 5: Certificate Path Validation, Version 2.0, 20 January 2009.

2.2 Informative references

References are either specific (identified by date of publication and/or edition number or version number) or non-specific. For specific references, only the cited version applies. For non-specific references, the latest version of the referenced document (including any amendments) applies.

NOTE: While any hyperlinks included in this clause were valid at the time of publication, ETSI cannot guarantee their long-term validity.

The following referenced documents may be useful in implementing an ETSI deliverable or add to the reader's understanding, but are not required for conformance to the present document.

- [i.1] [Regulation \(EU\) No 910/2014](#) of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market and repealing Directive 1999/93/EC.
- [i.2] [Commission Implementing Decision \(EU\) 2015/1505](#) of 8 September 2015 laying down technical specifications and formats relating to trusted lists pursuant to Article 22(5) of Regulation (EU) No 910/2014 of the European Parliament and of the Council on electronic identification and trust services for electronic transactions in the internal market.

- [i.3] [Official Journal of the European Union OJ C 276, 16.08.2019](#): "Information related to data on Member States' trusted lists as notified under Commission Implementing Decision (EU) 2015/1505", pp. 1-7.
- [i.4] ETSI TR 119 001: "Electronic Signatures and Infrastructures (ESI); The framework for standardization of signatures; Definitions and abbreviations".
- [i.5] Void.
- [i.6] IETF RFC 3161: "Internet X.509 Public Key Infrastructure Time-Stamp Protocol (TSP)".
- [i.7] [Directive 1999/93/EC](#) of the European Parliament and of the Council of 13 December 1999 on a Community framework for electronic signatures.
- [i.8] ETSI EN 319 102-1: "Electronic Signatures and Trust Infrastructures (ESI); Procedures for Creation and Validation of AdES Digital Signatures; Part 1: Creation and Validation".

3 Definition of terms, symbols, abbreviations and notations

3.1 Terms

For the purposes of the present document, the terms given in ETSI TR 119 001 [i.4] and the following apply:

pivot LOTL: specific instance of a LOTL that announces changes in the LOTL signing certificates and/or LOTL location

NOTE: For further explanations on the concept of pivot LOTL refer to annex A.

tuple: group of multiple elements or groups of multiple elements

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in ETSI TR 119 001 [i.4] and the following apply:

CID	Commission Implementing Decision
EUMS	European Union Member State
LOTLSO	LOTL Scheme Operator
QTS	Qualified Trust Service

3.4 Notations

The requirements in the present document are identified as follows:

<3 letters identifying the section title or type of requirement>-<the clause number>-<2-digit number (incremental)>

The management of the requirement identifiers for subsequent editions of the present document is as follows:

- When a requirement is inserted at the end of a clause, the 2-digits number above is incremented to the next available digit.
- When a requirement is inserted between two existing requirements, capital letters appended to the previous requirement identifier are used to distinguish new requirements.

- The requirement identifier for deleted requirements is kept and completed with "Void".
- The requirement identifier for modified requirement is kept void and the modified requirement is identified by capital letter(s) appended to the initial requirement number.

4 Procedures for using and interpreting European Union Member States national trusted lists

4.0 General provisions

The present document presents procedures for using and interpreting European Union Member States national trusted lists in the form of algorithms, which provide a conformant behaviour when implemented by a conformant application.

GPR-4.0-01: Alternative implementations may be used provided that they shall produce the same output and main status indication when given the same set of input information.

GPR-4.0-02: The following parameters shall be preconfigured as follows for use in all the procedures specified in the remaining clauses of the present document:

Name	Description - Value
OJEU-Loc	URI value referencing the latest publication of the Official Journal of the European Union (OJEU) related to data on EUMS TL as they are notified under Commission Implementing Decision (EU) 2015/1505 [i.2].
OJEU-LOTL-Loc	URI value representing the location where the current instance of the XML file of the LOTL is available, as specified in the OJEU publication available from OJEU-Loc.
OJEU-LOTL-Certs-Set	The full set of certificates used for ensuring authenticity and integrity of the LOTL as provided in the OJEU publication available from OJEU-Loc.

NOTE 1: At the time of publication of the present document:

- The URI value described in the OJEU-Loc row of the above table was:
https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=uriserv:OJ.C_.2019.276.01.0001.01.ENG [i.3].
- This URI value is expected to be the first URI value not ending by ".xml" in the sequence of URI values present in the 'Scheme information URI' field of the LOTL (see clause 5.3.7 of ETSI TS 119 612 [1]).
- The URI value described in the OJEU-LOTL-Loc row of the above table was:
<https://ec.europa.eu/tools/lotl/eu-lotl.xml>.

NOTE 2: Such initial configurations are likely to be performed outside the software application implementing the procedures specified in the present document and come from configuration files or other appropriate source. Once configured, and as per the content of OJ C 233 276 [i.3] and the explanation material available from that publication, those three variables can be updated in a machine processable way as further explained and specified in clause 4.1.

GPR-4.0-03: In the procedures specified in the present document, whenever the validation of an https connection fails, implementations should refrain from stopping the processing for that reason but should add an appropriate warning to the corresponding procedure sub-status information.

4.1 Authenticating the EC compiled list of trusted lists

4.1.1 Description

EUMS Trusted Lists (TLs) have a legal constitutive value. It is the single formal source to verify that a claimed EU qualified trust service provider and the claimed EU qualified trust service it provides are indeed granted an EU qualified status by the competent EUMS body.

Regulation (EU) No 910/2014 [i.1] mandates EUMS to set up their national TL, at least under an XML machine processable format, compliant to the specifications established by CID (EU) 2015/1505 [i.2] building upon ETSI TS 119 612 [1].

EUMS have the obligation to electronically sign or seal the XML version of their national TL by means of a digital signature compliant with the specifications of CID (EU) 2015/1505 [i.2] relying on clause 5.7.1 of ETSI TS 119 612 [1]. To verify such a digital signature, relying parties need to be able to access the applicable public key.

In order to allow access to the TLs of all Member States in an easy manner, the European Commission (EC) publishes a central list, called the List Of Trusted Lists (LOTL), with links to the locations where the TLs are published as notified by Member States. The public key certificate(s) corresponding to the private key(s) entitled to be used to sign EUMS TLs and hence to be used by relying parties to validate those TL signatures are notified by the EUMSs to the EC and published in the LOTL as well. The LOTL is available in a format suitable for automated processing (XML).

The authenticity and integrity of the machine processable version of the LOTL is ensured through a digital signature supported by a certificate which can be authenticated through a publication in the Official Journal of the European Union.

At the time of publication of the present document, pursuant to a publication in the OJEU C276 [i.3], the LOTL can be accessed from the following location: <https://ec.europa.eu/tools/lotl/eu-lotl.xml>.

OJEU C276 [i.3] additionally identifies and authenticates the LOTL Scheme Operator (LOTLSO) public key certificate(s) corresponding to the private key(s) entitled to be used to sign the LOTL and hence the public keys to be used by relying parties to validate the LOTL signature.

Both the location of the LOTL and the LOTLSO certificates can be updated through a new publication in the OJEU or through the mechanism of pivot LOTL in accordance with OJEU C276 [i.3]. The LOTLSO certificates and the location of the LOTL XML file are contained in the LOTL itself, as part of the first tuple of the 'Pointers to other TSLs' field of the LOTL as specified in clause 5.3.13 of ETSI TS 119 612 [1] and whose 'Scheme territory' corresponds to the "EU" country code. This enables relying parties to detect in a machine processable way a change in the LOTLSO certificates and/or in its location. Any such future change will be reflected in the publication of a new instance of a pivot LOTL which will include a new location URL and/or a modified set of digital certificates for relying parties to use when authenticating the LOTL. The change of the location of the LOTL will always lead to a new publication of the OJEU to authenticate such a new location. A change of the LOTL location is made effective in a pivot LOTL while the previous location is maintained and the current instance of the LOTL is kept available at that location until the next publication in the OJEU and for a further transition period.

Starting at the date of issuance of the pivot LOTL in which new LOTLSO certificates and/or new location is first published, the new URL and/or a modified set of digital certificates can be used by relying parties to locate and authenticate the LOTL in replacement of the formerly issued information. It is however always possible for the European Commission to publish a new publication in the OJEU, for instance as a temporary response to an emergency situation requiring the immediate replacement of all the digital certificates of the LOTL.

Each instance of the LOTL will include, as the first part of the information regarding the underlying scheme ('Scheme information URI' element as specified in clause 5.3.7 of ETSI TS 119 612 [1]), in their chronological order showing the most recent element first, the list of:

- when applicable, one or more URLs where the last archived previous instance(s) of the pivot LOTL containing a new location and/or a modified set of digital certificates of the LOTL is(are) published, back until and followed by;
- the URL of the latest relevant publication in the OJEU resetting the initial location and the initial set of digital certificates for relying parties to use when authenticating the LOTL.

In case of a transition between two publications in the OJEU, the above list can be piled on top of the list of pivot LOTLs, when applicable and the URL of the previous relevant publication in the OJEU resetting the initial location and the initial set of digital certificates for relying parties to use when authenticating the LOTL.

Each pivot LOTL is digitally signed by means of a private key for which the corresponding digital certificate is part of the set of LOTLSO certificates included in the previous pivot LOTL or included in the latest OJEU publication when the pivot LOTL is the first from that OJEU publication.

The current instance of the LOTL includes the exact same set of LOTLSO certificates included in the previous pivot LOTL and is digitally signed by means of a private key corresponding to one of these LOTLSO certificates.

The procedure specified in clause 4.1 allows to obtain the authenticated XML version of the current instance of the LOTL.

NOTE: Further information about the concept of pivot LOTL and on the procedure related to the change of location of the LOTL can be found in OJEU C276 [i.3] and in particular in the referenced webpage <https://ec.europa.eu/tools/lotl/pivot-lotl-explanation.html>.

4.1.2 Inputs

The parameters OJEU-*Loc*, OJEU-*LOTL-Loc* and OJEU-*LOTL-Certs-Set* shall either initially be configured as specified in GPR-4.0-02 or updated through the regular processing specified in clause 4.1.4.

4.1.3 Outputs

Name	Description
Authenticated-LOTL	The authenticated XML version of the current instance of the LOTL.
LOTL-Status	The status indication of the process of authenticating the current instance of the LOTL.
LOTL-Sub-Status	A list of indications supplementing <i>LOTL-Status</i> indication of the process of authenticating the current instance of the LOTL.

OUT-4.1.3-01: All above listed output variables shall be initialized to void.

4.1.4 Processing

NOTE 1: The processing basically checks the chain of trust between the LOTL XML file obtained from OJEU-*LOTL-Loc* input and the OJEU-*LOTL-Certs-Set* input. It checks in particular that:

- the public key certificate corresponding to the private key having signed the LOTL XML file is part of the set of certificates included in the LOTL itself as part of the pointer to itself;
- when no pivot LOTL is present, the public key certificate corresponding to the private key having signed the LOTL XML file is part of the set of certificates included in the OJEU-*LOTL-Certs-Set*.
- when pivot LOTL is/are present:
 - each pivot LOTL is signed by means of a private key for which the corresponding digital certificate:
 - is part of the set of certificates included in the previous pivot LOTL or included in the latest OJEU publication when the pivot LOTL is the first from that OJEU publication; and
 - is part of the set of certificates included in the pivot LOTL itself as part of the pointer to itself;
 - the current instance of the LOTL includes the exact same set of LOTLSO certificates included in the previous pivot LOTL and is signed by means of a private key corresponding to one of these LOTLSO certificates.

The signatures of the LOTL and of each pivot LOTL are valid.

Additional consistency checks are performed:

NOTE 2: As per OJEU C276 [i.3] and in particular the referenced webpage <https://ec.europa.eu/tools/lotl/pivot-lotl-explanation.html>, in case of changing the LOTL location.

- a) The first element value that will change is the 'TSLLocation' value string containing the URI of the machine processable format of the LOTL in the pointer to the LOTL in the LOTL itself. When this is the case, the OJEU-*LOTL-Loc* parameter (see clause 4.0) can be updated with that new location.

- b) Subsequently, when the first encountered element of the LOTL 'Scheme information URI' whose value is not ending by ".xml" is not the value of the configured OJEU-LOC parameter (see clause 4.0), then this parameter can be updated with that new value. This reflects the latest publication of the OJEU related to data on EUMS TL as they are notified under Commission Implementing Decision (EU) 2015/1505 [i.2].
- c) The parameter OJEU-LOTL-Certs-Set (see clause 4.0) can be updated either in an automated way from the set of certificates available in the pointer to the LOTL from the LOTL instance that first includes the new value of the latest publication of the OJEU referred in point b) above, or "manually" directly from that publication.

PRO-4.1.4-01: The processing shall set LOTL to the current instance of the LOTL XML file obtained from OJEU-LOTL-LOC.

PRO-4.1.4-02: The processing shall set LOTL-Signer-Cert to the ds:X509Certificate value of the ds:KeyInfo of the ds:Signature of LOTL.

PRO-4.1.4-03: If the processing parses the 'Scheme information URI' element of LOTL as specified in clause 5.3.7 of ETSI TS 119 612 [1] without finding a URI value matching the OJEU-LOC value, then:

- a) the processing shall set Authenticated-LOTL to void;
- b) the processing shall set LOTL-Status to the value "LOTL_VERIFICATION_FAILED";
- c) the processing shall set LOTL-Sub-Status to the value "OJEU_LOCATION_INPUT_NOT_MATCHING_OJEU_LOCATION_IN_LOTL"; and
- d) **the processing shall stop the process.**

NOTE 3: It is likely that the configuration specified in GPR-4.0-02 is not taking into consideration the latest publication of the OJEU related to data on EUMS TL as they are notified under Commission Implementing Decision (EU) 2015/1505 [i.2].

PRO-4.1.4-04: The processing shall set 'n' to the number of successive URIs having an https scheme, an authority, and a non-empty path ending with the character string ".xml" until the URI value matching the OJEU-LOC value, as those URIs are listed in the 'Scheme information URI' element of LOTL as specified in clause 5.3.7 of ETSI TS 119 612 [1].

PRO-4.1.4-05: If OJEU-LOTL-LOC is not matching the TSLLocation string available in the tuple from the 'Pointers to other TSLs' field of LOTL (see clause 5.3.13 of ETSI TS 119 612 [1]) whose 'Scheme territory' qualifier has the value "EU" and if LOTL does not match the XML file obtained from that TSLLocation string, then:

- a) the processing shall set Authenticated-LOTL to void;
- b) the processing shall set LOTL-Status to the value "LOTL_VERIFICATION_FAILED";
- c) the processing shall set LOTL-Sub-Status to the value "LOTL_FILE_CONFLICT"; and
- d) **the processing shall stop the process.**

PRO-4.1.4-06: If OJEU-LOTL-LOC is matching the TSLLocation string available in the tuple from the 'Pointers to other TSLs' field of LOTL (see clause 5.3.13 of ETSI TS 119 612 [1]) whose 'Scheme territory' qualifier has the value "EU" and if LOTL does not match the XML file obtained from that TSLLocation string, then:

- a) the processing shall set LOTL to the XML file obtained from that TSLLocation string; and
- b) the processing shall go to PRO-4.1.4-02.

NOTE 4: This case corresponds to the publication of a new LOTL instance from the time of the initialization of LOTL.

PRO-4.1.4-07: The processing shall validate ds:Signature of LOTL considering LOTL-Signer-Cert as a directly trusted certificate, i.e. as a trust anchor.

NOTE 5: This corresponds to the basic signature validation process of ETSI EN 319 102-1 [i.8].

PRO-4.1.4-08: If the signature validation performed in PRO-4.1.4-07 failed or was indeterminate, then:

- a) the processing shall set `Authenticated-LOTL` to void;
- b) the processing shall set `LOTL-Status` to the value "LOTL_VERIFICATION_FAILED";
- c) the processing shall set `LOTL-Sub-Status` to the values provided by the validation procedure together with the additional value "LOTL_SIGNATURE_VERIFICATION_FAILED"; and
- d) **the processing shall stop the process.**

PRO-4.1.4-09: The processing shall set the following variables to the following values:

- a) `LOTLSO-Cert` to `LOTL-Signer-Cert`; and
- b) `LOTLSO-Certs-Set` to the full set of certificates available in the tuple from the 'Pointers to other TSLs' field (see clause 5.3.13 of ETSI TS 119 612 [1]) of `LOTL`, whose 'Scheme territory' qualifier has the value "EU".

PRO-4.1.4-10: If `n` is equal to 0, then:

- a) If `LOTLSO-Cert` is not part of `LOTLSO-Certs-Set` then:
 - 1) the processing shall set `Authenticated-LOTL` to void;
 - 2) the processing shall set `LOTL-Status` to the value "LOTL_VERIFICATION_FAILED";
 - 3) the processing shall set `LOTL-Sub-Status` to the value "LOTL_SIGNER_CERT_NOT_AUTHENTICATED_BY_LOTL"; and
 - 4) **the processing shall stop the process.**
- b) The processing shall go to PRO-4.1.4-12.

PRO-4.1.4-11: For all `i` in [1..`n`]:

- a) The processing shall set `Pivot` to the instance of the XML file obtained from the `i`th successive URI having an https scheme, an authority, and a non-empty path ending with the character string ".xml" until the URI value matching the `OJEU-Loc` value in the 'Scheme information URI' (see clause 5.3.7 of ETSI TS 119 612 [1]) field of `LOTL`, considering the first such URI as number 1.
- b) The processing shall set `LOTLSO-Certs-Set` to the full set of certificates as they are available in the tuple from the 'Pointers to other TSLs' field (see clause 5.3.13 of ETSI TS 119 612 [1]) of `Pivot`, whose 'Scheme territory' qualifier has the value "EU".
- c) If `LOTLSO-Cert` is not part of `LOTLSO-Certs-Set` then:
 - 1) the processing shall set `Authenticated-LOTL` to void;
 - 2) the processing shall set `LOTL-Status` to the value "LOTL_VERIFICATION_FAILED";
 - 3) the processing shall set `LOTL-Sub-Status` to the value "PIVOT_i-1_SIGNER_CERT_NOT_AUTHENTICATED_BY_PIVOT_i"; and
 - 4) **the processing shall stop the process.**
- d) The processing shall set `LOTLSO-Cert` to the `ds:X509Certificate` value of the `ds:KeyInfo` of the `ds:Signature` of `Pivot`.
- e) The processing shall validate `ds:Signature` of `Pivot` considering `LOTLSO-Cert` as a directly trusted certificate, i.e. as a trust anchor.

NOTE 6: This corresponds to the basic signature validation process of ETSI EN 319 102-1 [i.8].

- f) If the signature validation performed in the previous point failed or was indeterminate then:
 - 1) the processing shall set `Authenticated-LOTL` to void;

- 2) the processing shall set `LOTL-Status` to the value `"LOTL_VERIFICATION_FAILED"`;
 - 3) the processing shall set `LOTL-Sub-Status` to the values provided by the validation procedure together with the additional value `"PIVOT_i_SIGNATURE_VERIFICATION_FAILED"`; and
 - 4) **the processing shall stop the process.**
- g) If `LOTL-Status` is not part of `LOTL-Certs-Set` then:
- 1) the processing shall set `Authenticated-LOTL` to void;
 - 2) the processing shall set `LOTL-Status` to the value `"LOTL_VERIFICATION_FAILED"`;
 - 3) the processing shall set `LOTL-Sub-Status` to the value `"PIVOT_i_SIGNER_CERT_NOT_AUTHENTICATED_BY_PIVOT_i"`; and
 - 4) **the processing shall stop the process.**

PRO-4.1.4-12: If `LOTL-Status` is not part of `OJEU-LOTL-Certs-Set` then:

- a) the processing shall set `Authenticated-LOTL` to void;
- b) the processing shall set `LOTL-Status` to the value `"LOTL_VERIFICATION_FAILED"`;
- c) the processing shall set `LOTL-Sub-Status` to the value `"PIVOT_n_LOTL-Status_SIGNER_CERT_NOT_AUTHENTICATED_BY_OJEU"`; and
- d) **the processing shall stop the process.**

PRO-4.1.4-13: If the 'Next update' date of `LOTL` (see clause 5.3.15 of ETSI TS 119 612 [1]) has passed then:

- a) the processing shall set `Authenticated-LOTL` to void;
- b) the processing shall set `LOTL-Status` to the value `"LOTL_VERIFICATION_FAILED"`;
- c) the processing shall set `LOTL-Sub-Status` the value `"LOTL_NEXTUPDATE_PASSED"`; and
- d) **the processing shall stop the process.**

PRO-4.1.4-14: The processing shall set `Authenticated-LOTL` to `LOTL`.

PRO-4.1.4-15: The processing shall set `LOTL-Status` to the value `"LOTL_VERIFICATION_PASSED"`.

PRO-4.1.4-16: If `OJEU-LOTL-Loc` is not matching the `TSLLocation` string available in the tuple from the 'Pointers to other TSLs' field of `Authenticated-LOTL` (see clause 5.3.13 of ETSI TS 119 612 [1]) whose 'Scheme territory' qualifier has the value "EU", then the processing shall set `OJEU-LOTL-Loc` to the `TSLLocation` string available in the tuple from the 'Pointers to other TSLs' field of `LOTL` (see clause 5.3.13 of ETSI TS 119 612 [1]) whose 'Scheme territory' qualifier has the value "EU".

PRO-4.1.4-17: If `OJEU-Loc` value is not matching the first URI value having an https scheme, an authority, and a non-empty path not ending with the character string ".xml" in the 'Scheme information URI' (see clause 5.3.7 of ETSI TS 119 612 [1]) field of `Authenticated-LOTL`, then:

- a) the processing shall set `OJEU-Loc` to that first URI value; and
- b) the processing shall set `OJEU-LOTL-Certs-Set`:
 - 1) either to the full set of certificates available in the tuple, whose 'Scheme territory' qualifier has the value "EU", from the 'Pointers to other TSLs' field (see clause 5.3.13 of ETSI TS 119 612 [1]) of the pivot `LOTL` whose location URI is immediately following that first URI value when having an https scheme, an authority, and a non-empty path not ending with the character string ".xml"; or
 - 2) to the full set of certificates used for ensuring authenticity and integrity of the `LOTL` as provided in the `OJEU` publication available from that first URI value.

4.2 Authenticating an EUMS trusted list

4.2.1 Description

The procedure specified in clause 4.2 allows to obtain the authenticated XML version of the national TL of a given EUMS.

4.2.2 Inputs

Name	Description
CC	Country code of the EUMS for which the trusted list is to be authenticated and whose value is in accordance with the ISO 3166-1 [2] Alpha 2 country code, set in capital letters.

4.2.3 Outputs

Name	Description
Authenticated-EUTL	The authenticated XML version of the requested TL of EUMS CC.
EUTL-Status	The status indication of the process of authenticating the requested TL of EUMS CC.
EUTL-Sub-Status	A list of indications supplementing EUTL-Status indication of the process of authenticating the requested TL of EUMS CC.

OUT-4.2.3-01: All above listed output variables shall be initialized to void.

4.2.4 Processing

PRO-4.2.4-01: The processing shall run the process for authenticating the LOTL as described in clause 4.1 of the present document.

PRO-4.2.4-02: If the output `Authenticated-LOTL` is void as a result of the execution of the process referred in PRO-4.2.4-01, then:

- a) the processing shall set `EUTL-Status` to the value "LOTL_VERIFICATION_FAILED";
- b) the processing shall set `EUTL-Sub-Status` to the values provided by set of values from `LOTL-Status` and `LOTL-Sub-Status`; and
- c) **the processing shall stop the process.**

PRO-4.2.4-03: The processing shall set `EUTL-Loc` to the URI provided in the tuple from the 'Pointers to other TSLs' field of `Authenticated-LOTL` (see clause 5.3.13 of ETSI TS 119 612 [1]) for which the 'Scheme territory' qualifier has value CC and for which the 'MIME type' is XML.

PRO-4.2.4-04: The processing shall set `EUTL` to the XML file retrieved from `EUTL-Loc`.

PRO-4.2.4-05: The processing shall set `EUTL-Certs-Set` to the set of certificates provided in the tuple from the 'Pointers to other TSLs' field of `Authenticated-LOTL` (see clause 5.3.13 of ETSI TS 119 612 [1]) for which the 'Scheme territory' qualifier has value CC and for which the 'MIME type' is XML.

PRO-4.2.4-06: The processing shall set `EUTL-Signer-Cert` to the `ds:X509Certificate` value of the `ds:KeyInfo` of the `ds:Signature` of `EUTL`.

PRO-4.2.4-07: If `EUTL-Signer-Cert` is not part of `EUTL-Certs-Set`, then:

- a) the processing shall set `Authenticated-EUTL` to void;
- b) the processing shall set `EUTL-Status` to the value "EUTL_VERIFICATION_FAILED";

- c) the processing shall set `EUTL-Sub-Status` to the value `"EUTLSO_SIGNER_CERT_NOT_AUTHENTICATED_BY_LOTL"`; and
- d) **the processing shall stop the process.**

PRO-4.2.4-08: The processing shall validate `ds:Signature` of EUTL considering `EUTL-Signer-Cert` as a directly trusted certificate, i.e. as a trust anchor.

PRO-4.2.4-09: If the signature validation performed in PRO-4.2.4-08 failed, then:

- a) the processing shall set `Authenticated-EUTL` to void;
- b) the processing shall set `EUTL-Status` to the value `"EUTL_VERIFICATION_FAILED"`;
- c) the processing shall set `EUTL-Sub-Status` to the set of values provided by the validation procedure together with the value `"EUTL_SIGNATURE_VERIFICATION_FAILED"`; and
- d) **the processing shall stop the process.**

PRO-4.2.4-10: If the 'Next update' date of EUTL (see clause 5.3.15 of ETSI TS 119 612 [1]) has passed, then the processing shall add to `EUTL-Sub-Status` the value `"WARNING_EUTL_NEXTUPDATE_PASSED"`.

PRO-4.2.4-11: The processing shall set `Authenticated-EUTL` to EUTL.

PRO-4.2.4-12: The processing shall set `EUTL-Status` to the value `"EUTL_VERIFICATION_PASSED"`.

4.3 Obtaining listed services matching a certificate

4.3.1 Description

The procedure specified in clause 4.3 allows to obtain, from the trusted list of a specific country, matching listed services, associated service information for a certificate for a specific date and time, for a specific service type identifier.

NOTE: The difference between a QTS type and a Service type identifier as specified in clause 5.5.1.1 of ETSI TS 119 612 [1] may reside in the sub-definition of that identifier service type into sub-services defined through 'additionalServiceInformation' extensions (see clause 5.5.9.4 of ETSI TS 119 612 [1]).

4.3.2 Inputs

Name	Description
CERT	X.509 certificate for which the information is to be obtained (e.g. a <code>ds:X509Certificate</code> value of a <code>ds:KeyInfo</code> of the <code>ds:Signature</code>).
TLS-Sti	One of the Service type identifier URI values specified in clause 5.5.1.1 of ETSI TS 119 612 [1].
Date-time	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].
CC	Country code value in accordance with the ISO 3166-1 [2] Alpha 2 country code, set in capital letters.

4.3.3 Outputs

Name	Description
SI-Results	A set of groups of elements, each group made of: <ol style="list-style-type: none"> a) SI-Full defined as an XML section corresponding to a 'Service information' element as specified in clause 5.5 of ETSI TS 119 612 [1]; b) SI-at-Date-time defined as an XML section corresponding either to the Date-time related 'Service (current) information' element as specified in clause 5.5 of ETSI TS 119 612 [1] with the exception of clause 5.5.10 or to the Date-time related 'Service history instance' element as specified in clause 5.6 of ETSI TS 119 612 [1]; c) TSP-Name defined as a 'TSP name' element as defined in clause 5.4.1 of ETSI TS 119 612 [1]; and d) TSP-Trade-Name defined as a 'TSP trade name' element as defined in clause 5.4.2 of ETSI TS 119 612 [1].
SI-Status	The status indication of the process consisting in obtaining for a certificate, for a specific type of 'Service type identifier' URI value specified in clause 5.5.1.1 of ETSI TS 119 612 [1] and for a specific date and time, a matching listed service and its associated service information.
SI-Sub-Status	A list of indications supplementing SI-Status indication of the process.

OUT-4.3.3-01: All above listed output variables shall be initialized to void.

4.3.4 Processing

PRO-4.3.4-01: If CC represents an EUMS and/or is set to "GB" or "UK":

- a) then the processing shall run the process for authenticating the EUMS trusted list from CC as described in clause 4.2 of the present document, passing CC as input to the process;
- b) else:
 - 1) the processing shall set SI-Status to the value "PROCESS_FAILED";
 - 2) the processing shall set SI-Sub-Status to the value "Provided_country_code_not_representing_an_EU_MS"; and
 - 3) **the processing shall stop the process.**

PRO-4.3.4-02: If the output Authenticated-EUTL is void as a result of the execution of the process referred in PRO-4.3.4-01, then:

- a) the processing shall set SI-Status to the value "PROCESS_FAILED";
- b) the processing shall set SI-Sub-Status to the values provided by set of values from EUTL-Status and EUTL-Sub-Status; and
- c) **the processing shall stop the process.**

PRO-4.3.4-03: For each 'Service information' entry (see clause 5.5 of ETSI TS 119 612 [1]) within Authenticated-EUTL, the processing shall check whether:

- i) the 'Service type identifier' (see clause 5.5.1 of ETSI TS 119 612 [1]) matches TLS-Sti; and
- ii) either a certification path (see IETF RFC 5280 [4]) to CERT is found which, when using the 'Service digital identity' public key and associated subject name of the entry as a trust anchor, validates successfully according to section 6.1 of IETF RFC 5280 [4], with input (b) of section 6.1.1 set to Date-time and inputs (c) and (e) to (i) set to the corresponding default values of the data type PathConstraints specified in Common PKI v2.0 part 5 [5], Table 1; or the 'Service digital identity' public key and associated subject name are identical to the public key and subject name in CERT;

NOTE 1: In function of the TLS-Sti value, the length of the certification path can be "0", "1" or longer.

NOTE 2: Name chaining is performed as part of the certificate path validation specified in clause 6 of IETF RFC 5280 [4]. If no valid name chains are found from the subject distinguished name of one of the X.509 certificates present within the above 'Service digital identity' to the issuer distinguished name present within CERT, then no valid certificate path will be built.

NOTE 3: Although multiple X.509 certificates can be present within the above 'Service digital identity', they are necessarily representing the same public key and have identical subject names in a trusted list compliant to ETSI TS 119 612 [1].

and, when both checks succeed, shall add a tuple to *SI-Results* with:

- a) *SI-full* set to the entire such 'Service information' entry (see clause 5.5 of ETSI TS 119 612 [1]); and
- b) *SI-at-Date-time* set to:
 - either the entire such 'Service information' entry excepted, if any, the 'Service history' element (see clause 5.5.10 of ETSI TS 119 612 [1]) when *Date-time* is greater than or equal to 'Current status starting date and time' of that entry (see clause 5.5.5 of ETSI TS 119 612 [1]);
 - or the first 'Service history instance' (see clause 5.6 of ETSI TS 119 612 [1]) of that entry for which the 'Previous status starting date and time' (see clause 5.6.5 of ETSI TS 119 612 [1]) is less than or equal to *Date-time*;
- c) *TSP-Name* set to the 'TSP name' element (see clause 5.4.1 of ETSI TS 119 612 [1]) associated to that 'Service information' entry; and
- d) *TSP-Trade-Name* set to the 'TSP trade name' element (see clause 5.4.2 of ETSI TS 119 612 [1]) associated to that 'Service information' entry.

PRO-4.3.4-03A: For each tuple in *SI-Results*, the processing shall check that the 'Service history instance' elements in the corresponding *SI-full* element are correctly ordered:

- a) when this is not the case, the processing shall stop and report the error;
- b) when 'Service history instance' elements have the exact same 'Previous status starting date and time' value, the processing shall stop and report the error.

PRO-4.3.4-04: The processing shall set *SI-Status* to the value "PROCESS_PASSED".

PRO-4.3.4-05: The processing shall add to *SI-Sub-Status* the indication value "WARNING_T1_DUPLICATION" when two or more of the *SI-Results* tuples include an *SI-at-Date-time* XML section for which:

- a) an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) includes the value <http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures>; and
- b) values included in the respective 'Service current status' and/or 'Service previous status' fields (see respectively clauses 5.5.4 and 5.6.4 of ETSI TS 119 612 [1]) are identical.

PRO-4.3.4-06: The processing shall add to *SI-Sub-Status* the indication value "ERROR_T1_DUPLICATION" when two or more of the *SI-Results* tuples include an *SI-at-Date-time* XML section for which:

- a) an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) includes the value <http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures>; and
- b) values included in the respective 'Service current status' and/or 'Service previous status' fields (see respectively clauses 5.5.4 and 5.6.4 of ETSI TS 119 612 [1]) are not identical.

PRO-4.3.4-07: The processing shall add to *SI-Sub-Status* the indication value "WARNING_T2_DUPLICATION" when two or more of the *SI-Results* tuples include an *SI-at-Date-time* XML section for which:

- a) an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) includes the value <http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSeals>; and

- b) values included in the respective 'Service current status' and/or 'Service previous status' fields (see respectively clauses 5.5.4 and 5.6.4 of ETSI TS 119 612 [1]) are identical.

PRO-4.3.4-08: The processing shall add to *SI-Sub-Status* the indication value "ERROR_T2_DUPLICATION" when two or more of the *SI-Results* tuples include an *SI-at-Date-time* XML section for which:

- a) an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) includes the value <http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSeals>; and
- b) values included in the respective 'Service current status' and/or 'Service previous status' fields (see respectively clauses 5.5.4 and 5.6.4 of ETSI TS 119 612 [1]) are not identical.

PRO-4.3.4-09: The processing shall add to *SI-Sub-Status* the indication value "WARNING_T3_DUPLICATION" when two or more of the *SI-Results* tuples include an *SI-at-Date-time* XML section for which:

- a) an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) includes the value <http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForWebSiteAuthentication>; and
- b) values included in the respective 'Service current status' and/or 'Service previous status' fields (see respectively clauses 5.5.4 and 5.6.4 of ETSI TS 119 612 [1]) are identical.

PRO-4.3.4-10: The processing shall add to *SI-Sub-Status* the indication value "ERROR_T3_DUPLICATION" when two or more of the *SI-Results* tuples include an *SI-at-Date-time* XML section for which:

- a) an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) includes the value <http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForWebSiteAuthentication>; and
- b) values included in the respective 'Service current status' and/or 'Service previous status' fields (see respectively clauses 5.5.4 and 5.6.4 of ETSI TS 119 612 [1]) are not identical.

PRO-4.3.4-11: When two or more of the *SI-Results* tuples include different *TSP-Name* values, then:

- a) the processing shall add to *SI-Sub-Status* the indication value "ERROR_TSP_CONFLICT"; and
- b) the processing shall set *SI-Status* to the value "PROCESS_FAILED".

4.4 EU qualified certificate determination

4.4.1 Description

The procedure specified in clause 4.4 allows determining whether a certificate is confirmed by the applicable EUMS trusted list to have been an EU qualified certificate at a specific date and time and for which type.

4.4.2 Inputs

Name	Description of inputs
CERT	X.509 certificate for which the information is to be obtained (e.g. a <code>ds:X509Certificate</code> value of a <code>ds:KeyInfo</code> of the <code>ds:Signature</code>)
Date-time	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].

4.4.3 Outputs

Name	Description
QC-Results	A set of indications of the EU qualified status of CERT through one or more of the following values: <ol style="list-style-type: none"> "Not_Qualified" to indicate that CERT is not an EU qualified certificate according to the EUMS trusted list from CC at Date-time; "Not_Qualified_For_eSig" to indicate that CERT is not an EU qualified certificate for electronic signatures according to the EUMS trusted list from CC at Date-time; "Not_Qualified_For_eSeal" to indicate that CERT is not an EU qualified certificate for electronic seals according to the EUMS trusted list from CC at Date-time; "Not_QWAC" to indicate that CERT is not an EU qualified certificate for website authentication according to the EUMS trusted list from CC at Date-time; "QC_For_eSig" to indicate that CERT is an EU qualified certificate for electronic signatures according to the EUMS trusted list from CC at Date-time; "QC_For_eSeal" to indicate that CERT is an EU qualified certificate for electronic seals according to the EUMS trusted list from CC at Date-time; "QWAC" to indicate that CERT is an EU qualified certificate for web site authentication according to the EUMS trusted list from CC at Date-time; "INDET_QC_For_eSig" to indicate that the EUMS trusted list from CC cannot be used to confirm that CERT is a qualified certificate for electronic signatures at Date-time; "INDET_QC_For_eSeal" to indicate that the EUMS trusted list from CC cannot be used to confirm that CERT is a qualified certificate for electronic seals at Date-time; "INDET_QWAC" to indicate that the EUMS trusted list from CC cannot be used to confirm that CERT is a qualified certificate for website authentication at Date-time; "INDETERMINATE"; Void.
QC-Status	The status indication of the process.
QC-Sub-Status	A list of indications supplementing QC-Status indication.
CHECK_1_SET-OF_QE	An intermediate result as defined in the process below.
CHECK_2_SET-OF_QE	An intermediate result as defined in the process below.
CHECK_3_SET-OF_QE	An intermediate result as defined in the process below.

OUT-4.4.3-01: All above listed output variables shall be initialized to void.

4.4.4 Processing

PRO-4.4.4-01: The processing shall set CC to the country code value of the countryName attribute of the issuer field of the certificate provided in CERT, in capital letters in accordance with the ISO 3166-1 [2] Alpha 2 country code, with, when applicable:

- the country code value "GB" being converted to "UK";
- the country code value "GR" being converted to "EL".

PRO-4.4.4-02: The processing shall set TLS-Sti to the value "<http://uri.etsi.org/TrstSvc/Svctype/CA/QC>" as specified in clause 5.5.1.1 of ETSI TS 119 612 [1].

PRO-4.4.4-03: The processing shall run the process described in clause 4.3 of the present document, passing the following inputs to the process:

- CERT;
- TLS-Sti;

- c) Date-time;
- d) CC.

PRO-4.4.4-04: If the output `SI-Status` of the process run in PRO-4.4.4-03 has the value "PROCESS_FAILED", then:

- a) the processing shall set `QC-Status` to the value "PROCESS_FAILED";
- b) the processing shall set `QC-Sub-Status` to the values provided by set of values from `SI-Status` and `SI-Sub-Status`; and
- c) **the processing shall stop the process.**

PRO-4.4.4-05: If the output `SI-Results` of the process run in PRO-4.4.4-03 is void, then:

- a) the processing shall set `QC-Status` to the value "PROCESS_PASSED";
- b) the processing shall set `QC-Sub-Status` to the value "No_confirmation_found_in_EUMSTL_CC";
- c) the processing shall set `QC-Results` to the value "Not_Qualified"; and
- d) **the processing shall stop the process.**

PRO-4.4.4-06: When an `organizationName` attribute is present in the `issuerName` field of the certificate provided in CERT, and performing matching verification between two names, naming attributes or distinguished names as specified in clause 7.1 of IETF RFC 5280 [4]:

- a) then if the `organizationName` attribute of the `issuerName` field of the certificate provided in CERT is not matching one of the values of `TSP-Name` or `TSP-Trade-Name` of the output `SI-Results` of the process run in PRO-4.4.4-03, then:
 - 1) the processing shall set `QC-Status` to the value "PROCESS_FAILED";
 - 2) the processing shall set `QC-Results` to the value "INDETERMINATE";
 - 3) the processing shall set `QC-Sub-Status` to the value "ERROR_TSP_NAME_INCONSISTENCY_BETWEEN_CERT_AND_TL"; and
 - 4) **the processing shall stop the process;**
- b) else the processing shall decide the strategy to verify that the legal or natural person having issued CERT is the person identified by one of the values of `TSP-Name` or `TSP-Trade-Name` of the output `SI-Results` of the process run in PRO-4.4.4-03 and in case of failure set `QC-Status` to the value "PROCESS_FAILED", `QC-Results` to the value "INDETERMINATE", `QC-Sub-Status` to the value "ERROR_TSP_NAME_INCONSISTENCY_BETWEEN_CERT_AND_TL" and **shall stop the process.**

EXAMPLE 1: The strategy referred above can include:

- i) verification of the matching of the `commonName` attribute of the `issuerName` field of the certificate provided in CERT with one of the values of `TSP-Name` or `TSP-Trade-Name` of the output `SI-Results` of the process run in PRO-4.4.4-03; or
- ii) verification of the matching of the distinguished name of the `issuerName` field of the certificate provided in CERT with the distinguished name of the `Sdi` of the `SI-full` of the output `SI-Results` of the process run in PRO-4.4.4-03.

PRO-4.4.4-07: When `Date-time` is before 2016-06-30T22:00:00Z, or when the date and time value of the `NotBeforeDate` field of CERT is a value before 2016-06-30T22:00:00Z, the processing shall go to PRO-4.4.4-33.

PRO-4.4.4-08: The processing shall set the working variable `CHECK_1` to void.

NOTE 1: `CHECK_1` is a variable defined as an indication whose possible values are the values present in Table 1.

PRO-4.4.4-09: If the output `SI-Sub-Status` of the process run in PRO-4.4.4-03 includes the value "ERROR_T1_DUPLICATION", then the processing shall set `CHECK_1` to the value "INDET_QC_For_eSig" and shall go to PRO-4.4.4-16.

NOTE 2: The above check could also catch the "WARNING_T1_DUPLICATION" case and treat it the same way i.e. stopping the process and raising the warning. However, considering the trusted lists as legally constitutive information regarding the qualified status of a trust service and hence of one of its output (e.g. certificate, time stamp token, signed evidence), in the case the status information is consistent, the relying party can decide, despite the fact that such a construction of the trusted list is in conflict with CID (EU) 2015/1505 [i.2], to go further and still consider the information in the trusted list, provided no further inconsistency is discovered in the rest of the processing (e.g. conflicting service information qualifications extensions).

PRO-4.4.4-10: If none of the `SI-at-Date-time` element(s) of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) includes an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures>" or if the 'Service current status' or 'Service previous status' field of (any of) the `SI-at-Date-time` element(s) of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) that include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures>" has the value "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/withdrawn>", then the processing shall set `CHECK_1` to the value "Not_Qualified_For_eSig" and shall go to PRO-4.4.4-16.

PRO-4.4.4-10A: If the 'Service current status' or 'Service previous status' field of (any of) the `SI-at-Date-time` element(s) of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) that include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures>" has a value different from either "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/granted>" or "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/withdrawn>", then:

- a) the processing shall add to `QC-Sub-Status` the value "ERROR_Service_Status_Non-compliance_with_TS119612";
- b) the processing shall set `CHECK_1` to the value "INDET_QC_For_eSig"; and
- c) the processing shall go to PRO-4.4.4-16.

PRO-4.4.4-11: The processing shall set `CHECK_1_SET-OF_QE` to the set of all 'QualificationElement' from all 'Qualifications' extensions (see clause 5.5.9.2 of ETSI TS 119 612 [1]) whose 'CriteriaList' element identifies `CERT` from all `SI-at-Date-time` elements of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) that include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures>".

PRO-4.4.4-12: The processing shall proceed as follows:

- a) it shall identify, if any, the set of all applicable qualifiers as per the content of the 'Qualifier' descendant elements (see clause 5.5.9.2.3 of ETSI TS 119 612 [1]) of all 'QualificationElement' elements of `CHECK_1_SET-OF_QE`.

In case one of the following qualifier or combinations is found, it shall set `CHECK_1` to the value "INDET_QC_For_eSig", it shall add to `QC-Sub-Status` the value "WARNING_T1_TL_Inconsistency_in_applying_qualifiers", and it shall go to PRO-4.4.4-16:

- 1) 'QCForESeal' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESeal>");
- 2) 'QCForWSA' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForWSA>");
- 3) 'NotQualified' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/NotQualified>") and 'QCStatement' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCStatement>");
- 4) 'QCForESig' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESig>") and 'QCForESeal' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESeal>");
- 5) 'QCForESig' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESig>") and 'QCForWSA' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForWSA>");

- 6) 'QCForESeal' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESeal>") and 'QCForWSA' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForWSA>"); or
- 7) 'QCForLegalPerson' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForLegalPerson>").

PRO-4.4.4-13: The processing shall get the information about the presence and content of the id-etsi-qcs-QcCompliance and id-etsi-qcs-QcType statements (see ETSI EN 319 412-5 [3], hereafter respectively QcCompliance and QcType) in CERT.

PRO-4.4.4-14: If it results from PRO-4.4.4-13 that CERT includes more than one QcType identifier in its QcType statement when present, then the processing shall add to QC-Sub-Status the value "WARNING_CERT_Inconsistency_in_QcType_qualifiers_Non-compliance_with_EN319412-5".

PRO-4.4.4-15: Using the applicable qualifiers identified in PRO-4.4.4-12.(a):

- a) the processing shall check whether the following qualifiers are present among them: 'QCForESig' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESig>"), 'NotQualified' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/NotQualified>") and 'QCStatement' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCStatement>");
- b) the processing shall use the information obtained in PRO-4.4.4-13 to select the appropriate row of Table 1, and shall use the information obtained in above point PRO-4.4.4-15.(a) to select the appropriate column of Table 1;

NOTE 3: Information in row1/column0 means, and corresponds to the case where, the QcCompliance statement is present in CERT without any QcType statement being present, or the QcCompliance statement is present in CERT together with QcType 1 statement. The meaning of the other rows of column0 can be deduced accordingly.

Information in row0/column1 means, and corresponds to the case where, none of the three qualifiers 'NotQualified', 'QCStatement', 'QCForESig' in the 'Qualifications' extensions (denoted Sie:Q in Table 1) applies to CERT (this also includes the case where no Sie:Q extension is present). Information in row0/column5 means, and corresponds to the case where, both qualifiers 'QCStatement' and 'QCForESig' in the 'Qualifications' extensions (denoted Sie:Q in Table 1) apply to CERT. The meaning of the other columns of row0 can be deduced accordingly.

- c) the processing shall set CHECK_1 to the value found in the selected cell of Table 1;

EXAMPLE 2: If QcCompliance extension is present in CERT together with the QcType 3 and the qualifier 'QCForESig' applies to CERT as per the applicable qualifiers, then the value set to CHECK_1 is "QC_For_eSig" (see row3/column4).

- d) if row8/column3 of Table 1 was selected in step (b) above, then the processing shall add to QC-Sub-Status the value "WARNING_T1_Not_Enough_Info_on_QC_Type".

Table 1: QC-For-eSig determination

		Sie:aSI = ForeSignatures				
		None of Sie:Q NotQualified QCStatement QCForESig	Sie:Q NotQualified (with or without QCForESig)	Sie:Q QCStatement	Sie:Q QCForESig	Sie:Q QCStatement & QCForESig
row0						
row1	QcCompliance or QcCompliance + QcType 1	"QC_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"	"QC_For_eSig"	"QC_For_eSig"
row2	QcCompliance + QcType 2	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"	"QC_For_eSig"
row3	QcCompliance + QcType 3	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"	"QC_For_eSig"
row4	QcCompliance + QcType 1 & QcType 2	"INDET_QC_For_eSig"	"Not_Qualified_For_eSig"	"INDET_QC_For_eSig"	"QC_For_eSig"	"QC_For_eSig"
row5	QcCompliance + QcType 1 & QcType 3	"INDET_QC_For_eSig"	"Not_Qualified_For_eSig"	"INDET_QC_For_eSig"	"QC_For_eSig"	"QC_For_eSig"
row6	QcCompliance + QcType 2 & QcType 3	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"	"QC_For_eSig"
row7	QcCompliance + QcType 1 & QcType 2 & QcType 3	"INDET_QC_For_eSig"	"Not_Qualified_For_eSig"	"INDET_QC_For_eSig"	"QC_For_eSig"	"QC_For_eSig"
row8	no QcCompliance and no QcType	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"INDET_QC_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row9	no QcCompliance + QcType 1	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row10	no QcCompliance + QcType 2	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row11	no QcCompliance + QcType 3	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row12	no QcCompliance + QcType 1 & QcType 2	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"INDET_QC_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row13	no QcCompliance + QcType 1 & QcType 3	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"INDET_QC_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row14	no QcCompliance + QcType 2 & QcType 3	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row15	no QcCompliance + QcType 1 & QcType 2 & QcType 3	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"INDET_QC_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
	column0	column1	column2	column3	column4	column5

PRO-4.4.4-16: The processing shall set the working variable CHECK_2 to void.

NOTE 4: CHECK_2 is a variable defined as an indication whose possible values are the values present in Table 2.

PRO-4.4.4-17: If the output SI-Sub-Status of the process run in PRO-4.4.4-03 includes the value "ERROR_T2_DUPLICATION", then the processing shall set CHECK_2 to the value "INDET_QC_For_eSig" and shall go to PRO-4.4.4-24.

NOTE 5: The above check could also catch the "WARNING_T2_DUPLICATION" case and treat it the same way i.e. stopping the process and raising the warning. However, considering the trusted lists as legally constitutive information regarding the qualified status of a trust service and hence of one of its output (e.g. certificate, time stamp token, signed evidence), in the case the status information is consistent, the relying party can decide, despite the fact that such a construction of the trusted list is in conflict with CID (EU) 2015/1505 [i.2], to go further and still consider the information in the trusted list, provided no further inconsistency is discovered in the rest of the processing (e.g. conflicting service information qualifications extensions).

PRO-4.4.4-18: If none of the `SI-at-Date-time` element(s) of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) includes an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSeals>" or if the 'Service current status' or 'Service previous status' field of (any of) the `SI-at-Date-time` elements of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) that include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSeals>" has the value "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/withdrawn>", then the processing shall set `CHECK_2` to the value "Not_Qualified_For_eSeal" and shall go to PRO-4.4.4-24.

PRO-4.4.4-18A: If the 'Service current status' or 'Service previous status' field of (any of) the `SI-at-Date-time` element(s) of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) that include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSeals>" a value different from either "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/granted>", or "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/withdrawn>", then:

- a) the processing shall add to `QC-Sub-Status` the value "ERROR_Service_Status_Non-compliance_with_TS119612";
- b) the processing shall set `CHECK_1` to the value "INDET_QC_For_eSeal"; and
- c) the processing shall go to PRO-4.4.4-24.

PRO-4.4.4-19: The processing shall set `CHECK_2_SET-OF_QE` to the set of all 'QualificationElement' from all 'Qualifications' extensions (see clause 5.5.9.2 of ETSI TS 119 612 [1]) whose 'CriteriaList' element identifies `CERT` from all `SI-at-Date-time` elements of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) that include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSeals>".

PRO-4.4.4-20: The processing shall proceed as follows:

- a) it shall identify, if any, the set of all applicable qualifiers as per the content of the 'Qualifier' descendant elements (see clause 5.5.9.2.3 of ETSI TS 119 612 [1]) of all 'QualificationElement' elements of `CHECK_2_SET-OF_QE`;
- b) in case one of the following qualifier or combinations is found, it shall set `CHECK_2` to the value "INDET_QC_For_eSeal", it shall add to `QC-Sub-Status` the value "WARNING_T2_TL_Inconsistency_in_applying_qualifiers", and it shall go to PRO-4.4.4-24:
 - 1) 'QCForESig' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESig>");
 - 2) 'QCForWSA' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForWSA>");
 - 3) 'NotQualified' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/NotQualified>") and 'QCStatement' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCStatement>");
 - 4) 'QCForESig' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESig>") and 'QCForESeal' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESeal>");
 - 5) 'QCForESig' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESig>") and 'QCForWSA' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForWSA>"); or
 - 6) 'QCForESeal' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESeal>") and 'QCForWSA' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForWSA>").

PRO-4.4.4-21: The processing shall get the information about the presence and content of the QcCompliance and QcType statements (see ETSI EN 319 412-5 [3]) in CERT.

PRO-4.4.4-22: If it results from PRO-4.4.4-21 that CERT includes more than one QcType identifier in its QcType statement when present, then the processing shall add to QC-Sub-Status the value "WARNING_CERT_Inconsistency_in_QcType_qualifiers_Non-compliance_with_EN319412-5".

PRO-4.4.4-23: Using the applicable qualifiers identified in PRO-4.4.4-20.(a):

- a) the processing shall check whether the following qualifiers are present among them: 'QCForESeal' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESeal>"), 'NotQualified' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/NotQualified>") and 'QCStatement' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCStatement>");
- b) the processing shall use the information obtained in PRO-4.4.4-21 to select the appropriate row of Table 2, and shall use the information obtained in above point PRO-4.4.4-23.(a) to select the appropriate column of Table 2;

NOTE 6: Information in row1/column0 means, and corresponds to the case where, the QcCompliance statement is present in CERT without any QcType statement being present, or the QcCompliance statement is present in CERT together with QcType 1 statement. The meaning of the other rows of column0 can be deduced accordingly.

Information in row0/column1 means, and corresponds to the case where, none of the three qualifiers 'NotQualified', 'QCStatement', 'QCForESeal' in the 'Qualifications' extensions (denoted Sie:Q in Table 2) applies to CERT (this also includes the case where no Sie:Q extension is present). Information in row0/column5 means, and corresponds to the case where, both qualifiers 'QCStatement' and 'QCForESeal' in the 'Qualifications' extensions apply to CERT. The meaning of the other columns of row0 can be deduced accordingly.

- c) the processing shall set CHECK_2 to the value found in the selected cell of Table 2;

EXAMPLE 3: If QcCompliance extension is present in CERT together with the QcType 3 and the qualifier 'QCForESeal' applies to CERT as per the applicable qualifiers, then the value set to CHECK_2 is "QC_For_eSeal" (see row3/column4).

- d) if row8/column3 of Table 2 was selected in step (b) above, then the processing shall add to QC-Sub-Status the value "WARNING_T2_Not_Enough_Info_on_QC_Type".

Table 2: QC-For-eSeal determination

		Sie:aSI = ForeSeals				
		None of Sie:Q NotQualified QCStatement QCForESeal	Sie:Q NotQualified (with or without QCForESeal)	Sie:Q QCStatement	Sie:Q QCForESeal	Sie:Q QCStatement & QCForESeal
row0						
row1	QcCompliance or QcCompliance + QcType 1	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"	"QC_For_eSeal"
row2	QcCompliance + QcType 2	"QC_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"	"QC_For_eSeal"	"QC_For_eSeal"
row3	QcCompliance + QcType 3	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"	"QC_For_eSeal"
row4	QcCompliance + QcType 1 & QcType 2	"INDET_QC_For_eSeal"	"Not_Qualified_For_eSeal"	"INDET_QC_For_eSeal"	"QC_For_eSeal"	"QC_For_eSeal"
row5	QcCompliance + QcType 1 & QcType 3	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"	"QC_For_eSeal"
row6	QcCompliance + QcType 2 & QcType 3	"INDET_QC_For_eSeal"	"Not_Qualified_For_eSeal"	"INDET_QC_For_eSeal"	"QC_For_eSeal"	"QC_For_eSeal"
row7	QcCompliance + QcType 1 & QcType 2 & QcType 3	"INDET_QC_For_eSeal"	"Not_Qualified_For_eSeal"	"INDET_QC_For_eSeal"	"QC_For_eSeal"	"QC_For_eSeal"
row8	no QcCompliance and no QcType	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"INDET_QC_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"
row9	no QcCompliance + QcType 1	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"
row10	no QcCompliance + QcType 2	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"
row11	no QcCompliance + QcType 3	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"
row12	no QcCompliance + QcType 1 & QcType 2	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"INDET_QC_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"
row13	no QcCompliance + QcType 1 & QcType 3	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"
row14	no QcCompliance + QcType 2 & QcType 3	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"INDET_QC_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"
row15	no QcCompliance + QcType 1 & QcType 2 & QcType 3	"Not_Qualified_For_eSeal"	"Not_Qualified_For_eSeal"	"INDET_QC_For_eSeal"	"Not_Qualified_For_eSeal"	"QC_For_eSeal"
	column0	column1	column2	column3	column4	column5

PRO-4.4.4-24: The processing shall set the working variable CHECK_3 to void.

NOTE 7: CHECK_3 is a variable defined as an indication whose possible values are the values present in Table 3.

PRO-4.4.4-25: If the output SI-Sub-Status of the process run in PRO-4.4.4-03 includes the value "ERROR_T3_DUPLICATION", then the processing shall set CHECK_3 to the value "INDET_QWAC" and shall go to PRO-4.4.4-32.

NOTE 8: The above check could also catch the "WARNING_T3_DUPLICATION" case and treat it the same way i.e. stopping the process and raising the warning. However, considering the trusted lists as legally constitutive information regarding the qualified status of a trust service and hence of one of its output (e.g. certificate, time stamp token, signed evidence), in the case the status information is consistent, the relying party can decide, despite the fact that such a construction of the trusted list is in conflict with CID (EU) 2015/1505 [i.2], to go further and still consider the information in the trusted list, provided no further inconsistency is discovered in the rest of the processing (e.g. conflicting service information qualifications extensions).

PRO-4.4.4-26: If none of the `SI-at-Date-time` element(s) of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) includes an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForWebSiteAuthentication>" or if the 'Service current status' or 'Service previous status' field of (any of) the `SI-at-Date-time` elements of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) that include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForWebSiteAuthentication>" has the value "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/withdrawn>", then the processing shall set `CHECK_3` to the value "Not_QWAC" and shall go to PRO-4.4.4-32.

PRO-4.4.4-26A: If the 'Service current status' or 'Service previous status' field of (any of) the `SI-at-Date-time` element(s) of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) that include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForWebSiteAuthentication>" or a value different from either "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/granted>", or "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/withdrawn>", then:

- a) the processing shall add to `QC-Sub-Status` the value "ERROR_Service_Status_Non-compliance_with_TS119612";
- b) the processing shall set `CHECK_1` to the value "INDET_QWAC"; and
- c) the processing shall go to PRO-4.4.4-32.

PRO-4.4.4-27: The processing shall set `CHECK_3_SET-OF_QE` to the set of all 'QualificationElement' from all 'Qualifications' extensions (see clause 5.5.9.2 of ETSI TS 119 612 [1]) whose 'CriteriaList' element identifies `CERT` from all `SI-at-Date-time` elements of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) that include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForWebSiteAuthentication>".

PRO-4.4.4-28: The processing shall proceed as follows:

- a) it shall identify, if any, the set of all applicable qualifiers as per the content of the 'Qualifier' descendant elements (see clause 5.5.9.2.3 of ETSI TS 119 612 [1]) of all 'QualificationElement' elements of `CHECK_3_SET-OF_QE`;
- b) in case one of the following qualifier or combinations is found, it shall set `CHECK_3` to the value "INDET_QWAC", it shall add to `QC-Sub-Status` the value "WARNING_T3_TL_Inconsistency_in_applying_qualifiers", and it shall go to PRO-4.4.4-32:
 - 1) 'QCForESig' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESig>");
 - 2) 'QCForESeal' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESeal>");
 - 3) 'NotQualified' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/NotQualified>") and 'QCStatement' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCStatement>");
 - 4) 'QCForESig' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESig>") and 'QCForESeal' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESeal>");
 - 5) 'QCForESig' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESig>") and 'QCForWSA' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForWSA>"); or
 - 6) 'QCForESeal' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESeal>") and 'QCForWSA' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForWSA>").

PRO-4.4.4-29: The processing shall get the information about the presence and content of the QcCompliance and QcType statements (see ETSI EN 319 412-5 [3]) in CERT.

PRO-4.4.4-30: If it results from PRO-4.4.4-29 that CERT includes more than one QcType identifier in its QcType statement when present, then the processing shall add to QC-Sub-Status the value "WARNING_CERT_Inconsistency_in_QcType_qualifiers_Non-compliance_with_EN319412-5".

PRO-4.4.4-31: Using the applicable qualifiers identified in PRO-4.4.4-28.(a):

- a) the processing shall check whether the following qualifiers are present among them: 'QCForWSA' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForWSA>"), 'NotQualified' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/NotQualified>") and 'QCStatement' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCStatement>");
- b) the processing shall use the information obtained in PRO-4.4.4-29 to select the appropriate row of Table 3, and it shall use the information obtained in above point PRO-4.4.4-31.(a) to select the appropriate column of Table 3;

NOTE 9: Information in row1/column0 means, and corresponds to the case where, the QcCompliance statement is present in CERT without any QcType statement being present, or the QcCompliance statement is present in CERT together with QcType 1 statement. The meaning of the other rows of column0 can be deduced accordingly.

Information in row0/column1 means, and corresponds to the case where, none of the three qualifiers 'NotQualified', 'QCStatement', 'QCForWSA' in the 'Qualifications' extensions (denoted Sie:Q in Table 3) applies to CERT (this also includes the case where no Sie:Q extension is present). Information in row0/column5 means, and corresponds to the case where, both qualifiers 'QCStatement' and 'QCForWSA' in the 'Qualifications' extensions apply to CERT. The meaning of the other columns of row0 can be deduced accordingly.

- c) the processing shall set CHECK_3 to the value found in the selected cell of Table 3;

EXAMPLE 4: If QcCompliance extension is present in CERT together with the QcType 3 and the qualifier 'QCForWSA' applies to CERT as per the applicable qualifiers, then the value set to CHECK_3 is "QWAC" (see row3/column4).

Table 3: QC-For-WebSiteAuthentication determination

		Sie:aSI = ForWebSiteAuthentication				
		None of Sie:Q NotQualified QCStatement QCForWSA	Sie:Q NotQualified (with or without QCFor WSA)	Sie:Q QCStatement	Sie:Q QCFor WSA	Sie:Q QCStatement & QCForWSA
row0						
row1	QcCompliance or QcCompliance + QcType 1	"Not_QWAC"	"Not_QWAC"	"Not_QWAC"	"QWAC"	"QWAC"
row2	QcCompliance + QcType 2	"Not_QWAC"	"Not_QWAC"	"Not_QWAC"	"QWAC"	"QWAC"
row3	QcCompliance + QcType 3	"QWAC"	"Not_QWAC"	"QWAC"	"QWAC"	"QWAC"
row4	QcCompliance + QcType 1 & QcType 2	"Not_QWAC"	"Not_QWAC"	"Not_QWAC"	"QWAC"	"QWAC"
row5	QcCompliance + QcType 1 & QcType 3	"INDET_QWAC"	"Not_QWAC"	"INDET_QWAC"	"QWAC"	"QWAC"
row6	QcCompliance + QcType 2 & QcType 3	"INDET_QWAC"	"Not_QWAC"	"INDET_QWAC"	"QWAC"	"QWAC"
row7	QcCompliance + QcType 1 & QcType 2 & QcType 3	"INDET_QWAC"	"Not_QWAC"	"INDET_QWAC"	"QWAC"	"QWAC"
row8	no QcCompliance and no QcType	"Not_QWAC"	"Not_QWAC"	"INDET_QWAC"	"Not_QWAC"	"QWAC"
row9	no QcCompliance + QcType 1	"Not_QWAC"	"Not_QWAC"	"Not_QWAC"	"Not_QWAC"	"QWAC"
row10	no QcCompliance + QcType 2	"Not_QWAC"	"Not_QWAC"	"Not_QWAC"	"Not_QWAC"	"QWAC"
row11	no QcCompliance + QcType 3	"Not_QWAC"	"Not_QWAC"	"QWAC"	"Not_QWAC"	"QWAC"
row12	no QcCompliance + QcType 1 & QcType 2	"Not_QWAC"	"Not_QWAC"	"Not_QWAC"	"Not_QWAC"	"QWAC"
row13	no QcCompliance + QcType 1 & QcType 3	"Not_QWAC"	"Not_QWAC"	"INDET_QWAC"	"Not_QWAC"	"QWAC"
row14	no QcCompliance + QcType 2 & QcType 3	"Not_QWAC"	"Not_QWAC"	"INDET_QWAC"	"Not_QWAC"	"QWAC"
row15	no QcCompliance + QcType 1 & QcType 2 & QcType 3	"Not_QWAC"	"Not_QWAC"	"INDET_QWAC"	"Not_QWAC"	"QWAC"
	column0	column1	column2	column3	column4	column5

- d) if row8/column3 of Table 3 was selected in step (b) above, then the processing shall add to QC-Sub-Status the value "WARNING_T3_Not_Enough_Info_on_QC_Type".

PRO-4.4.4-32: The processing shall compare two by two the values of CHECK_1, CHECK_2, and CHECK_3 on the basis of Table 4 as follows:

- a) when the comparison results in an "error" indication:
 - 1) the processing shall set QC-Status to the value "PROCESS_FAILED";
 - 2) the processing shall add to QC-Sub-Status appropriate values reflecting the problematic two by two combinations; and
 - 3) **the processing shall stop the process;**
- b) the processing shall set QC-Status to the value "PROCESS_PASSED";

- c) the processing shall set QC-Results to the set of indications provided in CHECK_1, in CHECK_2, and in CHECK_3;
- d) when the comparison results in one or more "warning" indications:
 - 1) the processing shall set QC-Status to the value "PROCESS_PASSED_WITH_WARNING";
 - 2) the processing shall add to QC-Sub-Status appropriate values reflecting the problematic two by two combinations;

Table 4: QC status check

2 by 2 combinations	"QC_For_eSig"	"Not_Qualified_For_eSig"	"INDET_QC_For_eSig"	"QC_For_eSeal"	"Not_Qualified_For_eSeal"	"INDET_QC_For_eSeal"	"QWAC"	"Not_QWAC"	"INDET_QWAC"
"QC_For_eSig"				error	ok	warning	error	ok	warning
"Not_Qualified_For_eSig"				ok	ok	warning	ok	ok	warning
"INDET_QC_For_eSig"				warning	warning	warning	warning	warning	warning
"QC_For_eSeal"	error	ok	warning				error	ok	warning
"Not_Qualified_For_eSeal"	ok	ok	warning				ok	ok	warning
"INDET_QC_For_eSeal"	warning	warning	warning				warning	warning	warning
"QWAC"	error	ok	warning	error	ok	warning			
"Not_QWAC"	ok	ok	warning	ok	ok	warning			
"INDET_QWAC"	warning	warning	warning	warning	warning	warning			

- e) **the processing shall go to PRO-4.4.4-34.**

PRO-4.4.4-33: Proceed as follows:

- a) the processing shall set CHECK_2 to the value "Not_Qualified_For_eSeal";
- b) the processing shall set CHECK_3 to the value "Not_QWAC";
- c) if there are two or more of the SI-Results tuples (from the process run in PRO-4.4.4-03) that include an SI-at-Date-time XML section for which the values included in the 'Service previous status' fields (see clause 5.6.4 of ETSI TS 119 612 [1]) are identical, then the processing shall add to QC-Sub-Status the indication value "WARNING_TL-SERVICE-ENTRY-SDI_DUPLICATION";
- d) if there are two or more of the SI-Results tuples that include an SI-at-Date-time XML section for which the values included in the 'Service previous status' fields (see clause 5.6.4 of ETSI TS 119 612 [1]) are not identical, then:
 - 1) the processing shall add to QC-Sub-Status the indication value "ERROR_TL-SERVICE-ENTRY-SDI_DUPLICATION_STATUS_CONFLICT";
 - 2) the processing shall set QC-Status to the value "PROCESS_FAILED";
 - 3) **the processing shall stop the process;**
- e) the processing shall set CHECK_1 to void;

- f) the processing shall proceed as follow:
- 1) when `Date-time` is before 2016-06-30T22:00:00Z, the processing shall check if the 'Service previous status' field of (any of) the `SI-at-Date-time` element(s) of the `SI-Results` tuples has one of the values "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/supervisionceased>", "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/supervisionrevoked>", "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/accreditationceased>", or "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/accreditationrevoked>";
 - 2) when `Date-time` is after 2016-06-30T22:00:00Z, the processing shall check if none of the `SI-at-Date-time` element(s) of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) includes an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures>" or if the 'Service current status' or 'Service previous status' field of (any of) the `SI-at-Date-time` element(s) of the `SI-Results` tuples (from the process run in PRO-4.4.4-03) that include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) having the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures>" has the value "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/withdrawn>";
 - 3) if the check performed in point 1) or 2) above was successful, then:
 - i) the processing shall set `CHECK_1` to the value "Not_Qualified_For_eSig";
 - ii) the processing shall set `QC-Status` to the value "PROCESS_PASSED";
 - iii) **the processing shall stop the process;**
- g) the processing shall set `CHECK_1_SET-OF_QE` to the set of all 'QualificationElement' from all 'Qualifications' extensions (see clause 5.5.9.2 of ETSI TS 119 612 [1]) whose 'CriteriaList' element identifies CERT from all `SI-at-Date-time` elements of the `SI-Results` tuples (from the process run in PRO-4.4.4-03);
- h) the processing shall proceed as follows:
- 1) it shall identify the set of all applicable qualifiers as per the content of the 'Qualifier' descendant elements (see clause 5.5.9.2.3 of ETSI TS 119 612 [1]) of all 'QualificationElement' elements of `CHECK_1_SET-OF_QE`;
 - 2) in case the qualifier "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForESeal>", the qualifier "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCForWSA>", and/or combination of the qualifiers "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/NotQualified>" and "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCStatement>" is/are found, then:
 - i) the processing shall set `CHECK_1` to the value "INDET_QC_For_eSig";
 - ii) the processing shall add to `QC-Sub-Status` the value "ERROR_T1_TL_Inconsistency_in_applying_qualifiers";
 - iii) the processing shall set `QC-Status` to the value "PROCESS_FAILED";
 - iv) **the processing shall stop the process;**
- i) the processing shall get the information about the presence in CERT of the id-etsi-qcs-QcCompliance statement (see ETSI EN 319 412-5 [3]), the 0.4.0.1456.1.1 (QCP+) ETSI defined certificate policy OID, and/or the 0.4.0.1456.1.2 (QCP) ETSI defined certificate policy OID;
- j) the processing shall use the applicable qualifiers identified in PRO-4.4.4-33.(h).a to select the appropriate column of Table 5, and shall use the information obtained in PRO-4.4.4-33.(i) to select the appropriate row of Table 5;

Table 5: QC-For-eSig determination under Directive 1999/93/EC [i.7]

		Sti = CA/QC		
		None of Sie:Q NotQualified QCStatement	Sie:Q NotQualified	Sie:Q QCStatement
row0				
row1	QcCompliance	"QC_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row2	PolicyId QCP (qcp-public)	"QC_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row3	PolicyId QCP+ (qcp-public-with-sscd)	"QC_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row4	Any combination of QcCompliance, PolicyId QCP, PolicyId QCP+	"QC_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
row5	None	"Not_Qualified_For_eSig"	"Not_Qualified_For_eSig"	"QC_For_eSig"
	column0	column1	column2	column3

NOTE 10: Information in row1/column0 means, and corresponds to the case where, the QcCompliance statement is present in CERT. The meaning of the other rows of column0 can be deduced accordingly. Information in row0/column1 means, and corresponds to the case where, none of the qualifiers 'NotQualified' or 'QCStatement' in the 'Qualifications' extensions (denoted Sie:Q in Table 5) applies to CERT. The meaning of the other columns of row0 can be deduced accordingly.

- k) the processing shall set CHECK_1 to the value found in the selected cell of Table 5;
- l) the processing shall set QC-Status to the value "PROCESS_PASSED";
- m) the processing shall set QC-Results to the set of indications provided in CHECK_1, in CHECK_2, and in CHECK_3.

PRO-4.4.4-34: The processing shall run the process described in clause 4.4 of the present document, until either PRO-4.4.4-32 step is completed or PRO-4.4.4-33 step is completed, passing the following inputs to the process:

- a) CERT;
- b) the date and time value of the NotBeforeDate field of CERT.

PRO-4.4.4-35: If the output QC-Status of the process run in PRO-4.4.4-34 has the value "PROCESS_FAILED", then:

- a) the processing shall set QC-Status to the value "PROCESS_FAILED";
- b) the processing shall add to QC-Sub-Status the values provided by set of values from QC-Status and QC-Sub-Status from the process run in PRO-4.4.4-34; and
- c) **the processing shall stop the process.**

PRO-4.4.4-36: The processing shall compare the values of QC-Results obtained after the first run of process 4.4 (with Date-time from the input) and after the second run of process 4.4 (with the NotBeforeDate):

- a) when the two results do not contain the exact same set of indications then:
 - 1) the processing shall set QC-Status to the value "PROCESS_FAILED";
 - 2) the processing shall add to QC-Sub-Status appropriate values reflecting the problematic comparison(s); and

3) **the processing shall stop the process;**

NOTE 11: When `QC-Results` include either "QC_For_eSig", or "QC_For_eSeal" or "QWAC", then CERT can be considered, at `Date-time`, respectively as an EU qualified certificate for electronic signatures, an EU qualified certificate for electronic seals, or an EU qualified certificate for website authentication.

b) when the `QC-Sub-Status` returned by the process run in PRO-4.4.4-34 contains one or more "warning" indications:

- 1) the processing shall set `QC-Status` to the value "PROCESS_PASSED_WITH_WARNING";
- 2) the processing shall add to `QC-Sub-Status` the values provided by the set of values from `QC-Status` and `QC-Sub-Status` from the process run in PRO-4.4.4-34.

4.5 QSCD determination

4.5.1 Description

The procedure specified in clause 4.5 allows determining whether an EU qualified certificate is confirmed by the applicable EUMS trusted list to have had its private key residing in a QSCD at a specific date and time.

NOTE: As the EUMS trusted list provides such information only for qualified certificates of a certain type, the process will first determine whether or not the certificate is a qualified certificate and for which type.

4.5.2 Inputs

Name	Description of inputs
CERT	X.509 certificate for which the information is to be obtained (e.g. a <code>ds:X509Certificate</code> value of a <code>ds:KeyInfo</code> of the <code>ds:Signature</code>).
Date-time	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].

4.5.3 Outputs

Name	Description
QSCD-Results	An indication on whether CERT had its private key residing in a QSCD in accordance with the trusted lists, through one of the following values: <ol style="list-style-type: none"> a) "QSCD_YES" to indicate that CERT had its private key residing in a QSCD at <code>Date-time</code> according to the EUMS trusted lists; b) "QSCD_NO" to indicate that CERT did not have its private key residing in a QSCD at <code>Date-time</code> according to the EUMS trusted lists; c) "QSCD_INDETERMINATE" to indicate that the EUMS trusted lists cannot be used to confirm whether CERT had its private key residing in a QSCD at <code>Date-time</code>; d) Void.
QSCD-Status	The status indication of the process.
QSCD-Sub-Status	A list of indications supplementing <code>QSCD-Status</code> indication.

OUT-4.5.3-01: All above listed output variables shall be initialized to void.

4.5.4 Processing

PRO-4.5.4-01: The processing shall run the process described in clause 4.4 of the present document, passing the following inputs to the process:

- a) CERT;
- b) Date-time.

PRO-4.5.4-02: If the output `QC-Status` of the process run in PRO-4.5.4-01 has the value "PROCESS_FAILED", then:

- a) the processing shall set `QSCD-Status` to the value "PROCESS_FAILED";
- b) the processing shall set `QSCD-Sub-Status` to the values provided by set of values from `QC-Status` and `QC-Sub-Status`; and
- c) **the processing shall stop the process.**

PRO-4.5.4-03: When `Date-time` is strictly before 2016-06-30T22:00:00Z:

- a) If `QC_Results` includes the value "QC_For_eSig", then considering `CHECK_1_SET-OF_QE` as part of the outputs of the process run in PRO-4.5.4-01:
 - 1) the processing shall identify the set of all applicable qualifiers as per the content of the 'Qualifier' descendant elements (see clause 5.5.9.2.3 of ETSI TS 119 612 [1]) of all 'QualificationElement' elements of `CHECK_1_SET-OF_QE`, and shall check whether the following qualifiers are present among them: 'QCWithSSCD' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCWithSSCD>"), 'QCNoSSCD' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCNoSSCD>"), and 'QCSSCDStatusAsInCert' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCSSCDStatusAsInCert>");
 - 2) in case one of the following combinations is found, the processing shall set `QSCD-Results` to the value "QSCD_INDETERMINATE", shall set `QSCD-Status` to the value "PROCESS_PASSED_WITH_WARNING", shall add to `QSCD-Sub-Status` the value "WARNING_Inconsistency_in_applying_qualifiers_for_SSCD_status", and **shall stop the process**:
 - i) 'QCWithSSCD' and 'QCNoSSCD';
 - ii) 'QCSSCDStatusAsInCert' and 'QCWithSSCD';
 - iii) 'QCSSCDStatusAsInCert' and 'QCNoSSCD';
 - 3) the processing shall identify the presence of the 0.4.0.1456.1.1 (QCP+) ETSI defined certificate policy OID in the CertificatePolicies extension and the presence of the QcSSCD statement in the QCStatements extension (see ETSI EN 319 412-5 [3]) in CERT;
 - 4) the processing shall use the information obtained in above point PRO-4.5.4-03.(a).a. to select the appropriate column of Table 6, and shall use the information obtained in above point PRO-4.5.4-03.(a).c. to select the appropriate row of Table 6, and shall set `QSCD-Results` to the value found in the selected cell;

Table 6: QSCD status check (Directive regime)

Sie:Q		"QCWithSSCD"	"QCSSCDStatusAsInCert" or no indication	"QCNoSSCD"
CERT	QcSSCD present and/or PolicyId QCP+ (qcp-public-with-sscd) present	QSCD_YES	QSCD_YES	QSCD_NO
	QcSSCD not present and PolicyId QCP+ (qcp-public-with-sscd) not present	QSCD_YES	QSCD_NO	QSCD_NO

- 5) the processing shall set `QSCD-Status` to the value "PROCESS_PASSED"; and
 - 6) **the processing shall stop the process;**
- b) the processing shall set `QSCD-Results` to the value "QSCD_INDETERMINATE";

- c) the processing shall set QSCD-Status to the value "PROCESS_PASSED"; and
- d) **the processing shall stop the process.**

PRO-4.5.4-04: If QC_Results includes the value "QC_For_eSig" or "QC_For_eSeal", then considering respectively CHECK_1_SET-OF_QE or CHECK_2_SET-OF_QE as part of the outputs of the process run in PRO-4.5.4-01:

- a) the processing shall identify the set of all applicable qualifiers as per the content of the 'Qualifier' descendant elements (see clause 5.5.9.2.3 of ETSI TS 119 612 [1]) of all 'QualificationElement' elements of the considered output variable, and shall check whether the following qualifiers are present among them: 'QCWithQSCD' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCWithQSCD>"), 'QCNoQSCD' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCNoQSCD>"), 'QCQSCDStatusAsInCert' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCQSCDStatusAsInCert>"), and 'QCQSCDManagedOnBehalf' ("<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/QCQSCDManagedOnBehalf>");
- b) in case one of the applicable qualifiers is not known by the processing, then:
 - 1) if the 'Qualifications' extension from which this qualifier was retrieved is marked "critical", the processing shall set QSCD-Status to the value "PROCESS_FAILED", shall add to QSCD-Sub-Status the value "ERROR_Unknown_critical_qualifiers_for_QSCD_status", and **shall stop the process**;
 - 2) else the processing shall add to QSCD-Sub-Status the value "WARNING_Unknown_qualifiers_for_QSCD_status";

NOTE: The set of qualifiers that are known by the processing is implementation dependent. In the context of EU qualified certificates, the set of qualifiers that can be used when the type of the service to which it applies is "CA/QC" is specified in clause 5.5.9.2.3 of ETSI TS 119 612 [1].

- c) in case one of the following qualifier or combinations is found, the processing shall set QSCD-Results to the value "QSCD_INDETERMINATE", shall set QSCD-Status to the value "PROCESS_PASSED_WITH_WARNING", shall add to QSCD-Sub-Status the value "WARNING_Inconsistency_in_applying_qualifiers_for_QSCD_status", and **shall stop the process**:
 - 1) 'QCWithSSCD' and absence of 'QCWithQSCD';
 - 2) 'QCNoSSCD' and absence of 'QCNoQSCD';
 - 3) 'QCWithQSCD' and 'QCNoQSCD';
 - 4) 'QCQSCDManagedOnBehalf' and 'QCNoQSCD';
 - 5) 'QCQSCDStatusAsInCert' and any one of the other qualifiers listed in PRO-4.5.4-04.(a);
- d) the processing shall identify the presence of the QcSSCD statement in the QCStatements extension (see ETSI EN 319 412-5 [3]) in CERT;
- e) the processing shall use the information obtained in above point PRO-4.5.4-04.(a) to select the appropriate column of Table 7, shall use the information obtained in above point PRO-4.5.4-04.(c) to select the appropriate row of Table 7, and shall set QSCD-Results to the value found in the selected cell.

Table 7: QSCD status check (Regulation regime)

Sie:Q		"QCWithQSCD" or "QCQSCDManagedOnBehalf"	"QCQSCDStatusAsInCert" or no indication	"QCNoQSCD"
CERT	QcSSCD present	QSCD_YES	QSCD_YES	QSCD_NO
	QcSSCD not present	QSCD_YES	QSCD_NO	QSCD_NO

- f) the processing shall set `QSCD-Status` to the value "PROCESS_PASSED"; and
- g) **the processing shall stop the process.**

PRO-4.5.4-05: If `QC_Results` does not include the value "QC_For_eSig" nor the value "QC_For_eSeal" then:

- a) the processing shall set `QSCD-Results` to the value "QSCD_INDETERMINATE";
- b) the processing shall set `QSCD-Status` to the value "PROCESS_PASSED"; and
- c) **the processing shall stop the process.**

4.6 EU trust service token issuer qualification determination

4.6.1 Description

The procedure specified in the present clause allows determining whether the signer identified in the certificate supporting the validation of the digital signature of a trust service output is confirmed by the applicable EUMS trusted list to have been, at a specific date and time, an EU qualified trust service provider for the provision of a qualified trust service corresponding to the 'service type identifier' URI provided as input.

NOTE: The present process is only applicable when the qualified trust service provider providing a qualified service is making use of PKI technology (e.g. for digitally signing evidences, attestations, reports) and the related PKI certificate is published in the applicable EUMS trusted list.

4.6.2 Inputs

Name	Description of inputs
<code>CERT</code>	X.509 certificate for which the information is to be obtained (e.g. a <code>ds:X509Certificate</code> value of a <code>ds:KeyInfo</code> of the <code>ds:Signature</code> from the corresponding trust service output).
<code>Date-time</code>	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].
<code>TLS-Sti</code>	A 'Service type identifier' URI value, taking one of the values specified in clause 5.5.1.1 of ETSI TS 119 612 [1].

4.6.3 Outputs

Name	Description
<code>QTSTo-Results</code>	An indication of the EU qualified status of the QTSP/QTS identified through the subject attribute of <code>CERT</code> , which is one of the following values: <ul style="list-style-type: none"> a) "Not_Qualified" to indicate that the signer identified in the <code>CERT</code> is confirmed by the applicable EUMS trusted list from <code>CC</code> to not have been, at <code>Date-time</code>, an EU qualified trust service provider for the provision of the qualified trust service corresponding to the URI provided as input in <code>TLS-Sti</code>; b) "Qualified" to indicate that the signer identified in the <code>CERT</code> is confirmed by the applicable EUMS trusted list from <code>CC</code> to have been, at <code>Date-time</code>, an EU qualified trust service provider for the provision of the qualified trust service corresponding to the URI provided as input in <code>TLS-Sti</code>; c) "Indeterminate" to indicate that the EUMS trusted list from <code>CC</code> cannot be used to confirm that the signer identified in the <code>CERT</code> has been, at <code>Date-time</code>, an EU qualified trust service provider for the provision of the qualified trust service corresponding to the URI provided as input in <code>TLS-Sti</code>.
<code>QTSTo-Status</code>	The status indication of the process.
<code>QTSTo-Sub-Status</code>	A list of indications supplementing the <code>QTSTo-Status</code> indication.
<code>CC</code>	The country code of the EUMS trusted list being used to obtain the above listed three other outputs.
<code>TSP-Name</code>	A 'TSP name' element as defined in clause 5.4.1 of ETSI TS 119 612 [1].

OUT-4.6.3-01: All above listed output variables shall be initialized to void.

4.6.4 Processing

PRO-4.6.4-01: If `Date-time` is before "2016-06-30T22:00:00Z", then:

- a) the processing shall set `QTSTo-Status` to the value "PROCESS_PASSED";
- b) the processing shall set `QTSTo-Results` to the set of values "Not_Qualified"; and
- c) **the processing shall stop the process.**

PRO-4.6.4-02: The processing shall set `CC` to the country code value of the `countryName` attribute of the `subject` field of the certificate provided in `CERT`, in capital letters in accordance with the ISO 3166-1 [2] Alpha 2 country code with, when applicable:

- a) the country code value "GB" being converted to "UK";
- b) the country code value "GR" being converted to "EL".

PRO-4.6.4-03: The processing shall run the process described in clause 4.3 of the present document, passing the following inputs to the process:

- a) `CERT`;
- b) `TLS-Sti`;
- c) `Date-time`;
- d) `CC`.

PRO-4.6.4-04: If the output `SI-Status` of the process run in PRO-4.6.4-03 has the value "PROCESS_FAILED", then:

- a) the processing shall set `QTSTo-Status` to the value "PROCESS_FAILED";
- b) the processing shall set `QTSTo-Results` to the value "Indeterminate";
- c) the processing shall set `QTSTo-Sub-Status` to the set of values from `SI-Status` and `SI-Sub-Status`; and
- d) **the processing shall stop the process.**

PRO-4.6.4-05: If the output `SI-Results` of the process run in PRO-4.6.4-03 is void, then:

- a) the processing shall set `QTSTo-Status` to the value "PROCESS_PASSED";
- b) the processing shall set `QTSTo-Results` to the set of values "Not_Qualified"; and
- c) **the processing shall stop the process.**

PRO-4.6.4-06: If the output `SI-Results` of the process run in PRO-4.6.4-03 includes more than one tuple for which the `SI-at-Date-time` respective parts include different values for their 'Service current status' or 'Service previous status' field, then:

- a) the processing shall set `QTSTo-Status` to the value "PROCESS_FAILED";
- b) the processing shall set `QTSTo-Results` to the value "Indeterminate";
- c) the processing shall set `QTSTo-Sub-Status` to the value "ERROR_INCONSISTENCY_IN_TL_ON_TSTO-CERT_STATUS"; and
- d) **the processing shall stop the process.**

PRO-4.6.4-07: If the output `SI-Results` of the process run in PRO-4.6.4-03 includes more than one tuple for which the `SI-at-Date-time` respective parts include different public key values for their 'Service digital identifier' field (see clause 5.5.3 of ETSI TS 119 612 [1]), then the processing shall add to `QTSTo-Sub-Status` the value "WARNING_DUPLICATION_OF_SERVICE_INFORMATION_IN_TL_REGARDING_TSTO-CERT".

PRO-4.6.4-08: If the `organizationName` attribute of the `subjectName` field of the certificate provided in `CERT` is not matching one of the values of `TSP-Name` or `TSP-Trade-Name` of the output `SI-Results` of the process run in PRO-4.6.4-03, then:

- a) the processing shall set `QTSTo-Status` to the value "PROCESS_FAILED";
- b) the processing shall set `QTSTo-Results` to the value "Indeterminate";
- c) the processing shall set `QTSTo-Sub-Status` to the value "ERROR_TSP_NAME_INCONSISTENCY_BETWEEN_TSTO-CERT_AND_TL"; and
- d) **the processing shall stop the process.**

PRO-4.6.4-09: If the 'Service current status' or 'Service previous status' field(s) of the `SI-at-Date-time` part(s) of the output `SI-Results` of the process run in PRO-4.6.4-03 has the value "<http://uri.etsi.org/TrstSvc/TrustedList/Svcstatus/granted>":

- a) then:
 - 1) the processing shall set `QTSTo-Status` to the value "PROCESS_PASSED";
 - 2) the processing shall set `QTSTo-Results` to the value "Qualified";
 - 3) the processing shall set `TSP-Name` the value `TSP-Name` of the output `SI-Results`; and
 - 4) **the processing shall stop the process.**
- b) else:
 - 1) the processing shall set `QTSTo-Status` to the value "PROCESS_PASSED";
 - 2) the processing shall set `QTSTo-Results` to the value "Not_Qualified";
 - 3) the processing shall set `TSP-Name` to the value `TSP-Name` of the output `SI-Results`; and
 - 4) **the processing shall stop the process.**

4.7 EU qualified time stamp determination

4.7.1 Description

The procedure specified in clause 4.7 allows determining whether a time stamp token is confirmed by the applicable EUMS trusted list to have been an EU qualified time stamp at its generation time, provided that the timestamp is valid.

4.7.2 Inputs

Name	Description of inputs
TST	The time stamp token for which the information is to be obtained.
Date-time	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].

4.7.3 Outputs

Name	Description
QTST-Results	An indication of the EU qualified status of TST through one of the following values: a) "Not_Qualified" to indicate that TST is not an EU qualified time stamp according to the EUMS trusted list from CC at Date-time; b) "Qualified" to indicate that TST is an EU qualified time stamp according to the EUMS trusted list from CC at Date-time; c) "Indeterminate" to indicate that the EUMS trusted list from CC cannot be used to confirm that TST is an EU qualified time stamp at Date-time.
QTST-Status	The status indication of the process.
QTST-Sub-Status	A list of indications supplementing QTST-Status indication.
CC	The country code of the EUMS trusted list being used to obtain the above listed three other outputs.

OUT-4.7.3-01: All above listed output variables shall be initialized to void.

4.7.4 Processing

PRO-4.7.4-01: The processing shall set TLS-Sti to the value "<http://uri.etsi.org/TrstSvc/Svctype/TSA/QTST>" as specified in clause 5.5.1.1 of ETSI TS 119 612 [1].

PRO-4.7.4-02: The processing shall run the process described in clause 4.6 of the present document, passing the following inputs to the process:

- a) CERT;
- b) TLS-Sti;
- c) Date-time.

PRO-4.7.4-03: The processing shall:

- a) set QTST-Status to the same value from QTSTo-Status;
- b) set QTST-Results to the same value, or same set of values, as the value, or set of values, from QTSTo-Results; and
- c) set QTST-Sub-Status to the set of values from QTSTo-Sub-Status.

PRO-4.7.4-04: The processing shall run the process described in clause 4.6 of the present document, passing the following inputs to the process:

- a) CERT;
- b) TLS-Sti;
- c) the date and time value as specified in TST and expressed as specified in clause 5.1.3 of ETSI TS 119 612 [1].

EXAMPLE: This date and time indication can be genTime from TSTInfo as specified in IETF RFC 3161 [i.6].

PRO-4.7.4-05: If the output QTSTo-Status of the process run in PRO-4.7.4-04 has the value "PROCESS_FAILED", then:

- a) the processing shall set QTST-Status to the value "PROCESS_FAILED";
- b) the processing shall add to QTST-Sub-Status the values provided by set of values from QTSTo-Status and QTSTo-Sub-Status from the process run in PRO-4.7.4-04; and
- c) **the processing shall stop the process.**

PRO-4.7.4-06: The processing shall compare the values of `QTST-Results` obtained as a result of PRO-4.7.4-03 and the values of `QTSTo-Results` obtained as a result of PRO-4.7.4-04:

- a) when the two results do not contain the exact same indication then:
 - 1) the processing shall set `QTST-Status` to the value "PROCESS_FAILED";
 - 2) the processing shall add to `QTST-Sub-Status` appropriate values reflecting the problematic comparison(s); and
 - 3) **the processing shall stop the process.**

4.8 EU qualified validation service determination

4.8.1 Description

The procedure specified in clause 4.8 allows determining whether the signer identified in the certificate supporting the validation of the digital signature of a trust service output is confirmed by the applicable EUMS trusted list to have been, at a specific date and time, an EU qualified trust service provider for the provision of a qualified validation service for qualified electronic signatures and/or for the provision of a qualified validation service for qualified electronic seals.

NOTE: The verification whether the trust service output is indeed a signature validation report attesting the result of the validation process of an EU qualified electronic signature or of an EU qualified electronic seal is out of scope of the present procedure.

4.8.2 Inputs

Name	Description of inputs
CERT	X.509 certificate for which the information is to be obtained (e.g. a <code>ds:X509Certificate</code> value of a <code>ds:KeyInfo</code> of the <code>ds:Signature</code> from the corresponding trust service output).
Date-time	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].

4.8.3 Outputs

Name	Description
QVSO-Results	A set of indications of the EU qualified status of the QTSP/QTS identified through the <code>subject</code> attribute of <code>CERT</code> , which contains one or more of the following values: <ol style="list-style-type: none"> "Not_Qualified_For_eSig" to indicate that the signer identified in the <code>CERT</code> is confirmed by the applicable EUMS trusted list from <code>CC</code> to not have been, at <code>Date-time</code>, an EU qualified trust service provider for the provision of a qualified validation service for qualified electronic signatures; "Not_Qualified_For_eSeal" to indicate that the signer identified in the <code>CERT</code> is confirmed by the applicable EUMS trusted list from <code>CC</code> to not have been, at <code>Date-time</code>, an EU qualified trust service provider for the provision of a qualified validation service for qualified electronic seals; "Qualified_For_eSig" to indicate that the signer identified in the <code>CERT</code> is confirmed by the applicable EUMS trusted list from <code>CC</code> to have been, at <code>Date-time</code>, an EU qualified trust service provider for the provision of a qualified validation service for qualified electronic signatures; "Qualified_For_eSeal" to indicate that the signer identified in the <code>CERT</code> is confirmed by the applicable EUMS trusted list from <code>CC</code> to have been, at <code>Date-time</code>, an EU qualified trust service provider for the provision of a qualified validation service for qualified electronic seals; "Indeterminate" to indicate that the EUMS trusted list from <code>CC</code> cannot be used to confirm that the signer identified in the <code>CERT</code> has been, at <code>Date-time</code>, an EU qualified trust service provider for the provision of a qualified validation service for qualified electronic signatures or for the provision of a qualified validation service for qualified electronic seals.
QVSO-Status	The status indication of the process.
QVSO-Sub-Status	A list of indications supplementing <code>QVSO-Status</code> indication.
CC	The country code of the EUMS trusted list being used to obtain the above listed three other outputs.

OUT-4.8.3-01: All above listed output variables shall be initialized to void.

4.8.4 Processing

PRO-4.8.4-01: The processing shall set `TLS-Sti` to the value "<http://uri.etsi.org/TrstSvc/Svctype/QESValidation/Q>" as specified in clause 5.5.1.1 of ETSI TS 119 612 [1].

PRO-4.8.4-02: The processing shall run the process described in clause 4.6 of the present document, passing the following inputs to the process:

- CERT;
- TLS-Sti;
- Date-time.

PRO-4.8.4-03: If the output `QTSTo-Status` of the process run in PRO-4.8.4-02 has the value "PROCESS_FAILED", then:

- the processing shall set `QVSO-Status` to the value "PROCESS_FAILED";
- the processing shall set `QVSO-Results` to the same value, or same set of values, as the value, or set of values, from `QTSTo-Results`;
- the processing shall set `QVSO-Sub-Status` to the same value, or same set of values, as the value, or set of values, from `QTSTo-Sub-Status`; and
- the processing shall stop the process.**

PRO-4.8.4-04: If the output `QTSTo-Status` of the process run in PRO-4.8.4-02 has the value "PROCESS_PASSED" and the output `QTSTo-Results` has the value "Not_Qualified", then:

- a) the processing shall set `QVSO-Status` to the value "PROCESS_PASSED";
- b) the processing shall set `QVSO-Results` to the same value, or same set of values, as the value, or set of values, from `QTSTo-Sub-Status`;
- c) the processing shall set `QVSO-Results` to the set of values "Not_Qualified_For_eSig" and "Not_Qualified_For_eSeal"; and
- d) **the processing shall stop the process.**

PRO-4.8.4-05: If the output `QTSTo-Status` of the process run in PRO-4.8.4-02 has the value "PROCESS_PASSED" and the output `QTSTo-Results` has the value "Qualified":

- a) then:
 - 1) the processing shall set `QVSO-Status` to the value "PROCESS_PASSED";
 - 2) if one of these `SI-at-Date-time` respective parts include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) including the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures>":
 - i) then the processing shall add to `QVSO-Results` the value "Qualified_For_eSig";
 - ii) else the processing shall add to `QVSO-Results` the value "Not_Qualified_For_eSig";
 - 3) if one of these `SI-at-Date-time` respective parts include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) including the value "<http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSeals>":
 - i) then the processing shall add to `QVSO-Results` the value "Qualified_For_eSeal";
 - ii) else the processing shall add to `QVSO-Results` the value "Not_Qualified_For_eSeal"; and
 - 4) **the processing shall stop the process;**
- b) else:
 - 1) the processing shall set `QVSO-Status` to the value "PROCESS_PASSED";
 - 2) the processing shall set `QVSO-Results` to the set of values "Not_Qualified_For_eSig" and "Not_Qualified_For_eSeal"; and
 - 3) **the processing shall stop the process.**

4.9 EU qualified preservation service determination

4.9.1 Description

The procedure specified in clause 4.9 allows determining whether the signer identified in the certificate supporting the validation of the digital signature of a trust service output is confirmed by the applicable EUMS trusted list to have been, at a specific date and time, an EU qualified trust service provider for the provision of a qualified preservation service for qualified electronic signatures and/or for the provision of a qualified preservation service for qualified electronic seals.

NOTE: The present process is only applicable when the qualified trust service provider providing a qualified preservation service for qualified electronic signatures and/or for qualified electronic seals is making use of PKI technology (e.g. for digitally signing evidences, attestations, reports) and the related PKI certificate is published in the applicable EUMS trusted list.

4.9.2 Inputs

Name	Description of inputs
CERT	X.509 certificate for which the information is to be obtained (e.g. a <code>ds:X509Certificate</code> value of a <code>ds:KeyInfo</code> of the <code>ds:Signature</code> from the corresponding trust service output)
Date-time	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].

4.9.3 Outputs

Name	Description
QPSO-Results	A set of indications of the EU qualified status of the QTSP/QTS identified through the subject attribute of CERT, which contains one or more of the following values: <ol style="list-style-type: none"> "Not_Qualified_For_eSig" to indicate that the signer identified in the CERT is confirmed by the applicable EUMS trusted list from CC to not have been, at Date-time, an EU qualified trust service provider for the provision of a qualified preservation service for qualified electronic signatures; "Not_Qualified_For_eSeal" to indicate that the signer identified in the CERT is confirmed by the applicable EUMS trusted list from CC to not have been, at Date-time, an EU qualified trust service provider for the provision of a qualified preservation service for qualified electronic seals; "Qualified_For_eSig" to indicate that the signer identified in the CERT is confirmed by the applicable EUMS trusted list from CC to have been, at Date-time, an EU qualified trust service provider for the provision of a qualified preservation service for qualified electronic signatures; "Qualified_For_eSeal" to indicate that the signer identified in the CERT is confirmed by the applicable EUMS trusted list from CC to have been, at Date-time, an EU qualified trust service provider for the provision of a qualified preservation service for qualified electronic seals; "Indeterminate" to indicate that the EUMS trusted list from CC cannot be used to confirm that the signer identified in the CERT has been, at Date-time, an EU qualified trust service provider for the provision of a qualified preservation service for qualified electronic signatures or for the provision of a qualified preservation service for qualified electronic seals.
QPSO-Status	The status indication of the process.
QPSO-Sub-Status	A list of indications supplementing QPSO-Status indication.
CC	The country code of the EUMS trusted list being used to obtain the above listed three other outputs.

OUT-4.9.3-01: All above listed output variables shall be initialized to void.

4.9.4 Processing

PRO-4.9.4-01: The processing shall set `TLS-Sti` to the value "<http://uri.etsi.org/TrstSvc/Svctype/PSES/Q>" as specified in clause 5.5.1.1 of ETSI TS 119 612 [1].

PRO-4.9.4-02: The processing shall run the process described in clause 4.6 of the present document, passing the following inputs to the process:

- CERT;
- `TLS-Sti`;
- `Date-time`.

PRO-4.9.4-03: If the output `QTSTo-Status` of the process run in PRO-4.9.4-02 has the value "PROCESS_FAILED", then:

- the processing shall set `QPSO-Status` to the value "PROCESS_FAILED";

- b) the processing shall set QPSO-Results to the same value, or same set of values, as the value, or set of values, from QTSTo-Results;
- c) the processing shall set QPSO-Sub-Status to the set of values from SI-QTSTo-Sub-Status; and
- d) **the processing shall stop the process.**

PRO-4.9.4-04: If the output QTSTo-Status of the process run in PRO-4.9.4-02 has the value "PROCESS_PASSED" and the output QTSTo-Results has the value "Not_Qualified", then:

- a) the processing shall set QPSO-Status to the value "PROCESS_PASSED";
- b) the processing shall set QPSO-Results to the set of values "Not_Qualified_For_eSig" and "Not_Qualified_For_eSeal"; and
- c) **the processing shall stop the process.**

PRO-4.9.4-05: If the output QTSTo-Status of the process run in PRO-4.9.4-02 has the value "PROCESS_PASSED" and the output QTSTo-Results has the value "Qualified":

- a) then:
 - 1) the processing shall set QPSO-Status to the value "PROCESS_PASSED";
 - 2) if one of these SI-at-Date-time respective parts include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) including the value ["http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures"](http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSignatures):
 - i) then the processing shall add to QPSO-Results the value "Qualified_For_eSig";
 - ii) else the processing shall add to QPSO-Results the value "Not_Qualified_For_eSig";
 - 3) if one of these SI-at-Date-time respective parts include an 'additionalServiceInformation' extension (see clause 5.5.9.4 of ETSI TS 119 612 [1]) including the value ["http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSeals"](http://uri.etsi.org/TrstSvc/TrustedList/SvcInfoExt/ForeSeals):
 - i) then the processing shall add to QPSO-Results the value "Qualified_For_eSeal";
 - ii) else the processing shall add to QPSO-Results the value "Not_Qualified_For_eSeal"; and
 - 4) **the processing shall stop the process;**
- b) else:
 - 1) the processing shall set QPSO-Status to the value "PROCESS_PASSED";
 - 2) the processing shall set QPSO-Results to the set of values "Not_Qualified_For_eSig" and "Not_Qualified_For_eSeal"; and
 - 3) **the processing shall stop the process.**

4.10 EU qualified electronic registered delivery service determination

4.10.1 Description

The procedure specified in clause 4.10 allows determining whether the signer identified in the certificate supporting the validation of the digital signature of a trust service output is confirmed by the applicable EUMS trusted list to have been, at a specific date and time, an EU qualified trust service provider for the provision of a qualified electronic registered delivery service.

NOTE: The verification whether the trust service output is indeed a qualified electronic registered delivery service evidence or statement is out of scope of the present procedure.

4.10.2 Inputs and parameters

Name	Description of inputs
CERT	X.509 certificate for which the information is to be obtained (e.g. a <code>ds:X509Certificate</code> value of a <code>ds:KeyInfo</code> of the <code>ds:Signature</code> from the corresponding trust service output).
Date-time	A date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].

4.10.3 Outputs

Name	Description
QERDSO-Results	An indication of the EU qualified status of the QTSP/QTS identified through the <code>subject</code> attribute of CERT, which is one of the following values: <ul style="list-style-type: none"> a) "Not_Qualified" to indicate that the signer identified in the CERT is confirmed by the applicable EUMS trusted list from CC to not have been, at Date-time, an EU qualified trust service provider for the provision of a qualified electronic registered delivery service; b) "Qualified" to indicate that the signer identified in the CERT is confirmed by the applicable EUMS trusted list from CC to have been, at Date-time, an EU qualified trust service provider for the provision of a qualified electronic registered delivery service; c) "Indeterminate" to indicate that the EUMS trusted list from CC cannot be used to confirm that the signer identified in the CERT has been, at Date-time, an EU qualified trust service provider for the provision of a qualified electronic registered delivery service.
QERDSO-Status	The status indication of the process.
QERDSO-Sub-Status	A list of indications supplementing QERDSO-Status indication.
CC	The country code of the EUMS trusted list being used to obtain the above listed three other outputs.

OUT-4.10.3-01: All above listed output variables shall be initialized to void.

4.10.4 Processing

PRO-4.10.4-01: The processing shall set `TLS-Sti-1` to the value "<http://uri.etsi.org/TrstSvc/Svctype/EDS/Q>" as specified in clause 5.5.1.1 of ETSI TS 119 612 [1].

PRO-4.10.4-02: The processing shall set `TLS-Sti-2` to the value "<http://uri.etsi.org/TrstSvc/Svctype/EDS/REM/Q>" as specified in clause 5.5.1.1 of ETSI TS 119 612 [1].

PRO-4.10.4-03: The processing shall run the process described in clause 4.6 of the present document, passing the following inputs to the process:

- a) CERT;
- b) `TLS-Sti-1`;
- c) `Date-time`.

PRO-4.10.4-04: The processing shall run the process described in clause 4.6 of the present document, passing the following inputs to the process:

- a) CERT;
- b) `TLS-Sti-2`;
- c) `Date-time`.

PRO-4.10.4-05: If one of the outputs `QTSTo-Status` of the processes run in PRO-4.10.4-03 and in PRO-4.10.4-04 has the value "PROCESS_FAILED", then:

- a) the processing shall set `QERDSO-Status` to the value "PROCESS_FAILED";

- b) the processing shall set `QERDSO-Results` to the set of values from `QTSTo-Results` of both processes;
- c) the processing shall set `QERDSO-Sub-Status` to the set of values from `QTSTo-Sub-Status` of both processes; and
- d) **the processing shall stop the process.**

PRO-4.10.4-06: If both outputs `QTSTo-Status` of the processes run in PRO-4.10.4-03 and in PRO-4.10.4-04 have the value "PROCESS_PASSED" and both corresponding outputs `QTSTo-Results` have the value "Not_Qualified", then:

- a) the processing shall set `QERDSO-Status` to the value "PROCESS_PASSED";
- b) the processing shall set `QERDSO-Results` to the value "Not_Qualified"; and
- c) **the processing shall stop the process.**

PRO-4.10.4-07: When the outputs `TSP-Name` from the processes run in PRO-4.10.4-03 and in PRO-4.10.4-04 have different values, then:

- a) the processing shall add to `QERDSO-Sub-Status` the indication value "ERROR_TSP_CONFLICT";
- b) the processing shall set `QERDSO-Results` to the value "Indeterminate";
- c) the processing shall set `QERDSO-Status` to the value "PROCESS_FAILED"; and
- d) **the processing shall stop the process.**

PRO-4.10.4-08: If the output `QTSTo-Status` of both of the process run in PRO-4.10.4-03 and in PRO-4.10.4-04 has the value "PROCESS_PASSED" and the output `QTSTo-Results` of any of those two processes has the value "Qualified":

- a) then:
 - 1) the processing shall set `QERDSO-Status` to the value "PROCESS_PASSED";
 - 2) the processing shall set `QERDSO-Results` to the value "Qualified"; and
 - 3) **the processing shall stop the process;**
- b) else:
 - 1) the processing shall set `QERDSO-Status` to the value "PROCESS_PASSED";
 - 2) the processing shall set `QERDSO-Results` to the value "Not_Qualified"; and
 - 3) **the processing shall stop the process.**

4.11 EU qualified archiving service determination

4.11.1 Description

The procedure specified in clause 4.11 allows determining whether the signer identified in the certificate supporting the validation of the digital signature of a trust service output (e.g. the signature of the report of an electronic archiving service) is confirmed by the applicable EUMS trusted list to have been, at a specific date and time, an EU qualified trust service provider for the provision of a qualified archiving service.

NOTE: The present process is only applicable when the qualified trust service provider providing a qualified archiving service for qualified electronic signatures and/or for qualified electronic seals is making use of PKI technology (e.g. for digitally signing evidences, attestations, reports) and the related PKI certificate is published in the applicable EUMS trusted list.

4.11.2 Inputs

Name	Description of inputs
CERT	X.509 certificate for which the information is to be obtained (e.g. a <code>ds:X509Certificate</code> value of a <code>ds:KeyInfo</code> of the <code>ds:Signature</code> from the corresponding trust service output)
Date-time	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].

4.11.3 Outputs

Name	Description
QARCH-Results	An indication of the EU qualified status of the QTSP/QTS identified through the <code>subject</code> attribute of CERT, which is one of the following values: <ol style="list-style-type: none"> "Not_Qualified" to indicate that the signer identified in the CERT is confirmed by the applicable EUMS trusted list from CC to not have been, at Date-time, an EU qualified trust service provider for the provision of a qualified electronic archiving service; "Qualified" to indicate that the signer identified in the CERT is confirmed by the applicable EUMS trusted list from CC to have been, at Date-time, an EU qualified trust service provider for the provision of a qualified electronic archiving service; "Indeterminate" to indicate that the EUMS trusted list from CC cannot be used to confirm that the signer identified in the CERT has been, at Date-time, an EU qualified trust service provider for the provision of a qualified electronic archiving service.
QARCH-Status	The status indication of the process.
QARCH-Sub-Status	A list of indications supplementing the QARCH-Status indication.
CC	The country code of the EUMS trusted list being used to obtain the above listed three other outputs.

OUT-4.11.3-01: All above listed output variables shall be initialized to void.

4.11.4 Processing

PRO-4.11.4-01: The processing shall set `TLS-Sti` to the value "<http://uri.etsi.org/TrstSvc/Svctype/ElectronicArchiving/Q>" as specified in clause 5.5.1.1 of ETSI TS 119 612 [1].

PRO-4.11.4-02: The processing shall run the process described in clause 4.6 of the present document, passing the following inputs to the process:

- CERT;
- TLS-Sti;
- Date-time.

PRO-4.11.4-03: The processing shall:

- set `QARCH-Status` to the same value from `QTSTo-Status`;
- set `QARCH-Results` to the same value, or same set of values, as the value, or set of values, from `QTSTo-Results`;
- set `QARCH-Sub-Status` to the set of values from `QTSTo-Sub-Status`; and
- stop the process.**

4.12 EU qualified electronic attestation of attribute service determination

4.12.1 Description

The procedure specified in clause 4.12 allows determining whether an electronic attestation of attribute is confirmed by the applicable EUMS trusted list to have been an EU qualified electronic attestation of attribute at its generation time, provided that the electronic attestation of attribute is valid.

4.12.2 Inputs

Name	Description of inputs
EAA	The electronic attestation of attribute for which the information is to be obtained.
Date-time	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].

4.12.3 Outputs

Name	Description
QEAA-Results	An indication of the EU qualified status of TST through one of the following values: a) "Not_Qualified" to indicate that EAA is not an EU qualified electronic attestation of attribute according to the EUMS trusted list from CC at Date-time; b) "Qualified" to indicate that EAA is an EU qualified electronic attestation of attribute according to the EUMS trusted list from CC at Date-time; c) "Indeterminate" to indicate that the EUMS trusted list from CC cannot be used to confirm that EAA is an EU qualified electronic attestation of attribute at Date-time.
QEAA-Status	The status indication of the process.
QEAA-Sub-Status	A list of indications supplementing QEAA-Status indication.
CC	The country code of the EUMS trusted list being used to obtain the above listed three other outputs.

OUT-4.12.3-01: All above listed output variables shall be initialized to void.

4.12.4 Processing

PRO-4.12.4-01: The processing shall set TLS-Sti to the value "http://uri.etsi.org/TrstSvc/Svctype/EAA/Q" as specified in clause 5.5.1.1 of ETSI TS 119 612 [1].

PRO-4.12.4-02: The processing shall set CERT to the X.509 certificate supporting the validation of the digital signature on EAA.

PRO-4.12.4-03: The processing shall check whether the URN 'urn:etsi:esi:eea:eu:qualified' is present within the content of EAA and if this URN is not present, then:

- a) the processing shall set QEAA-Status to the value "PROCESS_FAILED";
- b) the processing shall set QEAA-Results to the value "Indeterminate";
- c) the processing shall set QEAA-Sub-Status to the value "ERROR_NO_ETSI_QEAA_TYPE_INDICATION_FOUND"; and
- d) **the processing shall stop the process.**

PRO-4.12.4-04: If the URN 'urn:etsi:esi:eea:eu:qualified' was found in the content of EAA as a result of PRO-4.12.4-03, then the processing shall run the process described in clause 4.6 of the present document, passing the following inputs to the process:

- a) CERT;

- b) TLS-Sti;
- c) Date-time.

PRO-4.12.4-05: The processing shall:

- a) set QEAA-Status to the same value from QTSTo-Status;
- b) set QEAA-Results to the same value, or same set of values, as the value, or set of values, from QTSTo-Results;
- c) set QEAA-Sub-Status to the set of values from QTSTo-Sub-Status; and
- d) **stop the process.**

4.13 EU qualified ledger service determination

4.13.1 Description

The procedure specified in clause 4.13 allows determining whether the signer identified in the certificate supporting the validation of the digital signature of a record on a ledger is confirmed by the applicable EUMS trusted list to have been, at a specific date and time, an EU qualified trust service provider for the provision of a qualified service for the recording of electronic data in qualified electronic ledgers.

NOTE: The present process is only applicable when the qualified trust service provider providing a qualified service for the recording of electronic data in qualified electronic ledgers is making use of PKI technology (e.g. for digitally signing ledger records) and the related PKI certificate is published in the applicable EUMS trusted list.

4.13.2 Inputs

Name	Description of inputs
CERT	X.509 certificate for which the information is to be obtained (e.g. a ds:X509Certificate value of a ds:KeyInfo of the ds:Signature from the corresponding trust service output)
Date-time	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].

4.13.3 Outputs

Name	Description
QLEDG-Results	An indication of the EU qualified status of the QTSP/QTS identified through the subject attribute of CERT, which is one of the following values: <ul style="list-style-type: none"> a) "Not_Qualified" to indicate that the signer identified in the CERT is confirmed by the applicable EUMS trusted list from CC to not have been, at Date-time, an EU qualified trust service provider for the provision of a qualified service for the recording of electronic data in qualified electronic ledgers; b) "Qualified" to indicate that the signer identified in the CERT is confirmed by the applicable EUMS trusted list from CC to have been, at Date-time, an EU qualified trust service provider for the provision of a qualified service for the recording of electronic data in qualified electronic ledgers; c) "Indeterminate" to indicate that the EUMS trusted list from CC cannot be used to confirm that the signer identified in the CERT has been, at Date-time, an EU qualified trust service provider for the provision of a service for the recording of electronic data in qualified electronic ledgers.
QLEDG-Status	The status indication of the process.
QLEDG-Sub-Status	A list of indications supplementing the QLEDG-Status indication.
CC	The country code of the EUMS trusted list being used to obtain the above listed three other outputs.

OUT-4.13.3-01: All above listed output variables shall be initialized to void.

4.13.4 Processing

PRO-4.13.4-01: The processing shall set `TLS-Sti` to the value "http://uri.etsi.org/TrstSvc/Svctype/Ledgers/Q" as specified in clause 5.5.1.1 of ETSI TS 119 612 [1].

PRO-4.13.4-02: The processing shall run the process described in clause 4.6 of the present document, passing the following inputs to the process:

- a) `CERT`;
- b) `TLS-Sti`;
- c) `Date-time`.

PRO-4.13.4-03: The processing shall:

- a) set `QLEG-Status` to the same value from `QTSTo-Status`;
- b) set `QLEDG-Results` to the same value, or same set of values, as the value, or set of values, from `QTSTo-Results`;
- c) set `QLEDG-Sub-Status` to the set of values from `QTSTo-Sub-Status`; and
- d) **stop the process.**

New status	Previous statuses
TST	The time stamp token for which the information is to be obtained.
Date-time	Date and time indication as specified in clause 5.1.3 of ETSI TS 119 612 [1].

Annex A (informative):
Void

Annex B (normative): Output sub-statuses changes

In version 1.2.1 of the present document, the possible set of values for the output statuses QTST-Sub-Status, QVSO-Sub-Status, QPSO-Sub-Status and QERDSO-Sub-Status were different for the processes specified in clause 4.7 to clause 4.10 of the present document.

Table B.1 provides a mapping of the previous sub-status values to the new values.

Table B.1

Outputs	Previous statuses	New statuses
QTST-Sub-Status	ERROR_INCONSISTENCY_IN_TL_ON_TST_STATUS	ERROR_INCONSISTENCY_IN_TL_ON_TSTO-CERT_STATUS
QVSO-Sub-Status	ERROR_INCONSISTENCY_IN_TL_ON_VSO-CERT_STATUS	
QPSO-Sub-Status	ERROR_INCONSISTENCY_IN_TL_ON_PSO-CERT_STATUS	
QERDSO-Sub-Status	ERROR_INCONSISTENCY_IN_TL_ON_ERDS_CERT_STATUS	
QTST-Sub-Status	WARNING_DUPLICATION_OF_SERVICE_INFORMATION_IN_TL_REGARDING_TST	WARNING_DUPLICATION_OF_SERVICE_INFORMATION_IN_TL_REGARDING_TSTO-CERT
QVSO-Sub-Status	WARNING_DUPLICATION_OF_SERVICE_INFORMATION_IN_TL_REGARDING_VSO-CERT	
QPSO-Sub-Status	WARNING_DUPLICATION_OF_SERVICE_INFORMATION_IN_TL_REGARDING_PSO-CERT	
QERDSO-Sub-Status	WARNING_DUPLICATION_OF_SERVICE_INFORMATION_IN_TL_REGARDING_ERDS_CERT	
QTST-Sub-Status QVSO-Sub-Status QPSO-Sub-Status QERDSO-Sub-Status	ERROR_TSP_NAME_INCONSISTENCY_BETWEEN_CERT_AND_TL	ERROR_TSP_NAME_INCONSISTENCY_BETWEEN_TSTO-CERT_AND_TL

Annex C (informative): Bibliography

CEF eSignature - eIDAS Technical Subgroup and web conference on eSignature: "[Reaching relying parties after a change of LOTL Administrative Anchors](#)".

Annex D (informative): Change history

Date	Version	Information about changes
May 2021	V1.1.1	Publication
May 2023	V1.2.1	CR#1 Fix of trust anchor usage when obtaining listed services matching a certificate CR#2 Fix of qualification determination of pre-eIDAS certificates at post-eIDAS times CR#3 Fix of pre-eIDAS status at post-eIDAS times CR#4 Fix of conflicting information between 'additionalServiceInformation' and 'Qualification' extensions CR#5 Fix of unexpected qualifiers for S/QSCDs CR#6 Fix of timestamp qualification determination CR#7 Fix wording on RFC 5280 processing CR#8 Fix normative requirement in note
June 2025	V1.3.1	CR#01_019615: New TSTo issuer qualification determination process CR#02_019615 Refactoring of previous processes for qualified trust token determination CR#03_019615 New processes for the determination of the qualified status of the new qualified trust services
March 2026	V1.3.2	Fix of QEAA URN.
April 2026	V1.3.3	Editorial changes.

History

Version	Date	Status
V1.1.1	May 2021	Publication
V1.2.1	June 2023	Publication
V1.3.1	January 2026	Publication
V1.4.1	May 2026	Publication