

ETSI TS 122 034 V3.1.0 (2000-01)

Technical Specification

**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
High Speed Circuit Switched Data (HSCSD) - Stage 1
(3G TS 22.034 version 3.1.0 Release 1999)**



Reference

DTS/TSGS-0122034U

Keywords

GSM, UMTS

ETSI

Postal address

F-06921 Sophia Antipolis Cedex - FRANCE

Office address

650 Route des Lucioles - Sophia Antipolis
Valbonne - FRANCE
Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16
Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Internet

secretariat@etsi.fr
Individual copies of this ETSI deliverable
can be downloaded from
<http://www.etsi.org>
If you find errors in the present document, send your
comment to: editor@etsi.fr

Important notice

This ETSI deliverable may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.
All rights reserved.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://www.etsi.org/ipr>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables. The mapping of document identities is as follows:

For 3GPP documents:

3G TS | TR nn.nnn "<title>" (with or without the prefix 3G)

is equivalent to

ETSI TS | TR 1nn nnn "[Digital cellular telecommunications system (Phase 2+) (GSM);] Universal Mobile Telecommunications System; <title>

For GSM document identities of type "GSM xx.yy", e.g. GSM 01.04, the corresponding ETSI document identity may be found in the Cross Reference List on www.etsi.org/key

Contents

Foreword	5
1 Scope.....	6
2 References.....	6
3 Abbreviations and definitions	6
3.1 Abbreviations.....	6
3.2 Definitions	7
4 Description.....	7
4.1 General.....	7
4.2 Applicability	7
4.3 General Bearer Services.....	7
4.4 Parameters to be indicated and negotiated	7
4.4.1 Call set-up	7
4.4.1.1 T services.....	8
4.4.1.2 NT services.....	8
4.4.2 Network initiated modification	8
4.4.2.1 T services.....	8
4.4.2.2 NT services.....	8
4.4.3 User initiated modification.....	9
4.4.3.1 T services.....	9
4.4.3.2 NT services.....	9
4.5 Air Interface Resource Allocation	9
4.5.1 Minimum Air Interface Resource Allocation and Allocation Increment	9
4.5.2 Flexible Air Interface Resource Allocation.....	9
4.6 Symmetric and asymmetric connections.....	9
4.6.1 Symmetric connections	9
4.6.2 Asymmetric connections	9
4.6.2.1 Asymmetric air interface connection.....	9
4.6.2.2 Channel coding asymmetry	10
4.6.3 Network choice of connection symmetry.....	10
4.7 Mobile Station/Mobile Equipment requirements.....	10
4.8 Mobility Management.....	10
4.9 Roaming.....	10
4.10 Quality of Service	11
4.10.1 Bit error rate	11
4.10.1.1 TCH/F Bit Error Rate	11
4.10.1.2 Overall HSCSD Bit Error Rate.....	11
4.10.2 Radio resource management	11
4.10.3 Call set-up delay.....	11
4.10.4 End-to-end delay	11
4.10.5 Throughput.....	11
4.10.6 Network planning and interference levels.....	11
4.11 Mapping of FNUR to TCH/F for T services.....	11
4.12 Mapping of AIUR to TCH/F for NT services.....	11
4.13 HSCSD MMI aspects.....	12
4.14 HSCSD Subscription aspects.....	12
4.15 HSCSD charging aspects	12
4.16 O and M aspects.....	12
4.17 HSCSD security aspects	12
5 Exceptional procedures or unsuccessful outcome	13
6 Interworking requirements.....	13
6.1 Service interworking.....	13
6.1.1 Interworking with supplementary services.....	13
6.1.2 Interworking with other services.....	13

6.2 Network interworking 13

Annex A: Change history 14

History..... 15

Foreword

This Technical Specification has been produced by the 3GPP.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of this TS, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version 3.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 Indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the specification;

1 Scope

This Technical Specification (TS) specifies the Stage 1 description of High Speed Circuit Switched Data (HSCSD). HSCSD is a feature that allows users subscribing to the General Bearer Services to access user rates that can be achieved with one or more TCH/F. HSCSD also defines a flexible use of air interface resources which makes efficient and flexible use of higher user rates feasible.

Note: The present document covers description for GSM only. The document needs to be updated to make it applicable to 3GPP.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies.
- For this Release 1999 document, references to GSM documents are for Release 1999 versions (version 8.x.y).

- [1] GSM 01.04: "Digital cellular telecommunications system (Phase 2+); Abbreviations and acronyms".
- [2] TS 22.002: "Bearer Services (BS) supported by a Public Land Mobile Network (PLMN)".
- [3] TS 22.004: "General on supplementary services".
- [4] GSM 02.06: "Digital cellular telecommunications system (Phase 2+); Types of Mobile Stations (MS)".
- [5] GSM 05.02: "Digital cellular telecommunications system (Phase 2+); Multiplexing and multiple access on the radio path".
- [6] TR 21.905: "Vocabulary for 3GPP Specifications"

3 Abbreviations and definitions

3.1 Abbreviations

For the purposes of this TS, the following abbreviations apply:

HSCSD	High Speed Circuit Switched Data
MO	Mobile Originated
MT	Mobile Terminated
T	Transparent
NT	Non Transparent
AIUR	Air Interface User Rate
FNUR	Fixed Network User Rate
EDGE	Enhanced Data rates for GSM Evolution

Additional GSM related abbreviations can be found in GSM 01.04 [1].

3.2 Definitions

For the purposes of this TS, the following definitions apply:

Fixed Network User Rate: The user rate between IWF and the fixed network.

Air Interface User Rate: The user rate between Mobile Termination and IWF. For T services it is the maximum possible AIUR not including padding. For NT services it is the maximum possible AIUR.

maximum possible AIUR: The highest possible AIUR that the multiple TCH/F can provide, e.g. 2 TCH/F using TCH/F9.6 provides a maximum possible AIUR of 19,2 kbit/s.

padding: Fill bits needed to adapt the maximum possible AIUR supported by a given number of TCH/F with a given channel coding to a FNUR that is lower than the maximum possible AIUR.

4 Description

4.1 General

HSCSD is a feature that allows users subscribing to the General Bearer Services to access user rates that can be achieved with one or more TCH/F. HSCSD also defines mechanisms for the use of air interface resources which makes efficient and flexible use of higher user rates feasible.

4.2 Applicability

HSCSD shall provide flexible ways of supporting GSM Phase 2, T and NT data services and new data services at the higher rates possible with one or more TCH/F. Data compression shall be applicable to NT HSCSD. Supplementary Services that are applicable to the General Bearer Services can be used with the HSCSD feature (Reference TS 22.004, [3]).

4.3 General Bearer Services

The General Bearer Services are defined in TS 22.002 [2].

The General Bearer Services consist of two Bearer Services, and they are as follows:

- asynchronous;
- synchronous.

4.4 Parameters to be indicated and negotiated

4.4.1 Call set-up

The parameters to be indicated, and negotiated, if applicable, during the call set-up shall include:

- FNUR;
- Channel coding(s) acceptable (for the call);
- Maximum number of TCH/F (that the mobile user can accept);
- Wanted AIUR (desired rate that the mobile user wants the network to allocate). The wanted AIUR is applicable to NT services only;
- Indication if the user initiated modification is required, and if so, the network resource needs.

- Channel coding asymmetry indication

The channel coding(s) acceptable shall be indicated by the mobile at call set-up and is not negotiable. It indicates the channel coding(s) that may be chosen by the network for the call.

The maximum number of TCH/F shall be indicated at call set-up. It enables the mobile user to limit the number of TCH/F used and thus to control an essential parameter for charging. It sets the upper limit of number of TCH/F that the network may allocate to the mobile.

The wanted AIUR (applicable to NT services only) indicates the AIUR that the mobile user wants and which the network shall try to reach but which it is not allowed to exceed. The exception where the network is allowed to exceed the wanted AIUR is when the network can achieve the AIUR with a lower number of TCH/F, e.g. wanted AIUR indicated by the mobile is 14,4 kbit/s, channel codings acceptable are both TCH/F9.6 and TCH/F4.8 and maximum number of TCH/F are 3, then the network shall choose 2 x 9,6 over 3 x 4,8 if a channel coding of TCH/F9.6 is available on two TCH/F.

If the user wishes to make use of the user initiated modification procedure, this shall be indicated at the call set-up.

It shall be possible to reserve a FNUR that is considerably higher than the AIUR.

Channel coding asymmetry indication is only applicable to NT calls where the user has indicated acceptance for channel coding(s) based on enhanced modulation. In this case the user may indicate preference for channel coding symmetry, downlink biased channel coding asymmetry, or uplink biased channel coding asymmetry. The channel coding asymmetry indication is only applicable in direction MS to network.

4.4.1.1 T services

The ME or the network may propose to modify the FNUR. The calling entity may accept or release the call. Autobauding is not allowed.

The AIUR is always equal to the FNUR.

Fax Group 3 can make use of HSCSD.

The channel coding selected must be one of the channel coding(s) indicated in the channel coding(s) acceptable parameter, the number of TCH/F selected shall not exceed the maximum number of TCH/F parameter, and the combination of the two shall result in an AIUR that is equal to the FNUR.

4.4.1.2 NT services

The ME or the network may propose to modify the FNUR. The calling entity may accept or release the call. Autobauding is allowed.

The wanted AIUR is indicated by the mobile at call set-up.

4.4.2 Network initiated modification

4.4.2.1 T services

For transparent calls the radio resource parameters must remain within limits that allow the transparent call to maintain its characteristics of fixed end to end throughput and delay. This means that the channel coding and the number of TCH/F used may change during the call as long as a channel coding indicated in the channel coding(s) acceptable parameter is used, the maximum number of TCH/F is not exceeded and the AIUR is kept constant.

4.4.2.2 NT services

For NT calls the network may modify the number of TCH/F and the channel coding used and thus also the AIUR during the call as long as the maximum number of TCH/F, and the channel coding(s) acceptable are all respected. The network shall try to reach the wanted AIUR indicated, as long as the resource situation allows it.

4.4.3 User initiated modification

The in-call modification feature shall be supported in case of alternate services.

4.4.3.1 T services

The user initiated modification is not applicable to T services.

4.4.3.2 NT services

The user may indicate a change of the parameters maximum number of TCH/F, wanted AIUR, and channel coding asymmetry. No other parameters may be modified.

The user initiated modification is only applicable to the data phase of alternate services.

4.5 Air Interface Resource Allocation

4.5.1 Minimum Air Interface Resource Allocation and Allocation Increment

Air interface resources shall be allocated to HSCSD calls at TCH/F increments. The minimum air interface resource allocation for HSCSD calls shall be one TCH/F.

4.5.2 Flexible Air Interface Resource Allocation

Flexible air interface resource allocation enables:

The network to allocate dynamically resources related to the air interface usage according to the network operator's strategy, within the limits negotiated at the call set-up or during a user initiated modification.

4.6 Symmetric and asymmetric connections

4.6.1 Symmetric connections

For symmetric connections, air interface resources are allocated symmetrically.

4.6.2 Asymmetric connections

There are two types of asymmetry, asymmetric air interface connection and channel coding asymmetry. Asymmetric air interface connection implies that more time slots are used in the downlink than in the uplink. Channel coding asymmetry implies that one channel coding is used in the uplink and another channel coding is used in the downlink.

4.6.2.1 Asymmetric air interface connection

The provision of the asymmetric air interface connections allows simple ME (of Type 1, Reference GSM 05.02, [5]) to receive at higher AIUR than otherwise would be possible with a symmetric connection.

Asymmetric air interface connections that are a subset of the symmetric HSCSD, and support different user rates at uplink and downlink, shall be provided.

Asymmetric air interface connections are only applicable to the downlink-biased asymmetry, i.e., where the ME is receiving at a higher rate than it is transmitting.

Asymmetric air interface connections shall only be applicable to NT HSCSD.

4.6.2.2 Channel coding asymmetry

Channel coding asymmetry may be set up by the network in three cases:

- If the MS only supports enhanced modulation in the downlink.
- If the MS supports enhanced modulation in both links, but the user indicates preference for uplink or downlink biased channel coding asymmetry.
- If the MS supports enhanced modulation in both links, and the user indicates preference for channel coding symmetry, but the link conditions justifies different channel codings in up- and downlink.

In the case when preference of uplink or downlink biased channel coding asymmetry is indicated by the user, and a asymmetric channel coding connection is set up based on this indication, the network shall always assign a TCH/F14.4 channel on the unbiased link.

Channel coding asymmetry shall only be applicable to NT services applying the channel codings TCH/F14.4, TCH/F28.8 and TCH/F43.2.

In case a symmetric channel coding connection is set up, the link adaptation mechanism may change a symmetric channel coding connection to an asymmetric channel coding connection.

4.6.3 Network choice of connection symmetry

When the network has a choice of allocating either a symmetric or an asymmetric air interface connection it shall proceed as follows:

- In the case where the wanted AIUR is smaller than or equal to the AIUR supported symmetrically by the ME, or asymmetric air interface connection is not supported by the network, then a symmetric air interface connection is established.
- In the case where the wanted AIUR exceeds the AIUR supported symmetrically by the ME, the network shall assign the maximum AIUR supported by the ME in the down-link, upper-bounded by the maximum number of TCH/F indicated by the mobile user, and the number of TCH/F supported by the network, maintaining the minimum of one TCH/F.

4.7 Mobile Station/Mobile Equipment requirements

The general MS capabilities is applicable to HSCSD (Reference GSM 02.60 [4]).

A ME that supports HSCSD shall support one or more of the channel types TCH/F at or above 4,8 kbit/s.

Given that the ME supports a certain channel coding, the network shall be able to assume that the ME can support this channel coding in any multislot configuration allowed by its multislot class (Reference GSM 05.02, [5]).

4.8 Mobility Management

HSCSD shall be provided for within the existing supported Mobility Management.

4.9 Roaming

Roaming shall be possible.

4.10 Quality of Service

4.10.1 Bit error rate

4.10.1.1 TCH/F Bit Error Rate

The bit error rate performance of each TCH/F of a multiple TCH/F HSCSD call shall be the same as that of a single TCH/F data call for the same channel coding.

4.10.1.2 Overall HSCSD Bit Error Rate

Any increase in the bit error rate caused by the splitting and combining of multiple TCH/F shall be kept to a minimum.

4.10.2 Radio resource management

HSCSD shall be provided for within the existing Radio Resource management control functions, including the relevant handover types. The handover shall be simultaneous for all air interface timeslots making up an HSCSD call.

HSCSD shall be provided with full mobility.

4.10.3 Call set-up delay

Any increase in call set-up delay of the HSCSD calls compared to Phase 2 data services shall be kept to a minimum.

4.10.4 End-to-end delay

Any increase in end-to-end delay of the HSCSD calls compared to Phase 2 data services shall be kept to a minimum.

4.10.5 Throughput

The throughput for HSCSD T calls shall remain constant for the duration of the call except for the interruption of transmission at handover.

4.10.6 Network planning and interference levels

The impact of HSCSD on network planning and interference levels shall be kept to a minimum.

4.11 Mapping of FNUR to TCH/F for T services

For some FNUR padding is required to adapt the maximum possible AIUR to the FNUR.

4.12 Mapping of AIUR to TCH/F for NT services

The following table indicates the mapping of AIUR to the number of TCH/F for NT services.

Table 1/GSM 02.34: Mapping of AIUR to TCH/F for NT services

AIUR	TCH/F4.8	TCH/F9.6	TCH/F14.4	TCH/F28.8	TCH/F43.2
4,8 kbit/s	1	N/A	N/A	N/A	N/A
9,6 kbit/s	2	1	N/A	N/A	N/A
14,4 kbit/s	3	N/A	1	N/A	N/A
19,2 kbit/s	4	2	N/A	N/A	N/A
28,8 kbit/s	N/A	3	2	1	N/A
38,4 kbit/s	N/A	4	N/A	N/A	N/A
43.2 kbit/s	N/A	N/A	3	N/A	1
57.6 kbit/s	N/A	N/A	4	2	N/A

N/A Not applicable.

For Fixed Network User Rates (FRUR) see GSM 02.02.

NOTE: TCH/F28.8 and TCH/F43.2 require EDGE capability.

4.13 HSCSD MMI aspects

It shall be possible to configure the parameters negotiated and indicated at HSCSD call set-up and during user initiated modification.

4.14 HSCSD Subscription aspects

HSCSD is not subscribed to. Users wanting to use HSCSD must subscribe to the General Bearer Services.

4.15 HSCSD charging aspects

To allow accurate charging of HSCSD calls, a record of start and stop timestamps versus the number of TCH/F, for each change in TCH/F allocation, shall be provided.

NOTE: For MO HSCSD calls, the A party is liable for the use of all the TCH/F in her PLMN.

For MT HSCSD calls, the B party may have to pay for one or more of the TCH/F in her PLMN.

In case the originating or terminating subscriber is a fixed network subscriber, there should be no additional charge (in respect of the changing allocation of TCH/F) for the originating or terminating fixed network subscriber.

4.16 O and M aspects

For HSCSD call, there are several new and modified parameters compared to GSM Phase 2 data calls.

For HSCSD, the air interface resource allocation may change several times during the call (network initiated and user initiated changes). It shall be possible to limit the frequency of changes per call, separately for network initiated and user initiated changes.

HSCSD calls can occupy multiple TCH/F. It shall dynamically be possible to limit the maximum number of TCH/F allowed for HSCSD calls per cell.

4.17 HSCSD security aspects

Authentication and ciphering are applicable to HSCSD calls with no or minimal reduction in the security of the air interface.

5 Exceptional procedures or unsuccessful outcome

When a HSCSD call is offered to an entity (either ME or network) unable to support the offered HSCSD call, it shall be possible, within the limitations of the service, to revert the call:

- to an HSCSD call the entity can support; or
- to a GSM Phase 2 data service.

6 Interworking requirements

6.1 Service interworking

6.1.1 Interworking with supplementary services

Supplementary Services that are applicable to the General Bearer Services can be used with the HSCSD feature (Reference TS 22.004, [3]).

6.1.2 Interworking with other services

The simultaneous use of HSCSD and SMS MO/PP, and HSCSD and SMS MT/PP services shall be possible.

6.2 Network interworking

Interworking should be possible to all networks which are covered by GSM Phase 2 bearer services:

- PSTN;
- ISDN;
- PSPDN.

Annex A: Change history

Change history						
TSG SA#	Spec	Version	CR	<Phase>	New Version	Subject/Comment
Jun 1999	GSM 02.34	8.1.0				Transferred to 3GPP SA1
SA#04	22.034				3.0.0	
SA#05	22.034	3.0.0	001 002	R99	3.1.0	Editorial update of references for GSM/3GPP use Channel coding asymmetry for ECSD

History

Document history		
V3.1.0	January 2000	Publication