

ETSI TS 122 038 V17.0.0 (2022-04)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
(U)SIM Application Toolkit (USAT);
Service description;
Stage 1
(3GPP TS 22.038 version 17.0.0 Release 17)**



Reference

RTS/TSGS-0122038vh00

Keywords

UMTS, GSM, CARD, SIM, STAGE 1

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope	6
2 References	6
2.1 Normative references	7
3 Definitions and abbreviations.....	7
3.1 Definitions	7
3.2 Abbreviations	8
4 Description	8
5 High level USAT requirements.....	9
6 SAT/USAT/ME interface requirements.....	10
6.1 (U)SAT APIs.....	10
6.2 USAT proactive capability	10
6.3 ME Capability for support of bearer independent protocol.....	11
6.4 ME equipped with positioning features.....	12
7 USAT User Interface requirements	12
7.1 Data presentation requirements (e.g. Display)	12
7.2 Data acquisition requirements (e.g. Keypad)	12
7.3 Access requirements (e.g. Menu)	12
7.4 Menu capability.....	12
7.4.1 Set up capability	12
7.4.2 Selection capability.....	12
7.5 Soft-key capability	13
7.6 User control of the SAT/USAT execution environment	13
7.7 MMS presentation requirements	13
8 Network interface requirements	13
8.1 USAT/Network interaction	13
8.2 Communication control capability	13
8.3 Service Interworking requirements	14
9 USAT data exchange capabilities requirements.....	14
9.1 Data exchange capabilities supported.....	14
10 Charging requirements	14
11 Security requirements.....	15
11.1 Secure Environment requirements.....	15
12 Emergency calls	15
13 Roaming	15
14 Interaction with supplementary services	16
14.1 General	16
14.2 Line Identification	16
14.2.1 Calling Line Identification Presentation (CLIP).....	16
14.2.2 Calling Line Identification Restriction (CLIR).....	16
14.2.3 Connected Line Identification Presentation (COLP).....	16
14.2.4 Connected Line Identification Restriction (COLR).....	16
14.3 Call Forwarding.....	16
14.3.1 Call Forwarding Unconditional (CFU).....	16

14.3.2	Call Forwarding Busy (CFB).....	16
14.3.3	Call Forwarding on No Reply (CFNRy).....	16
14.3.4	Call Forwarding on Not Reachable (CFNRc).....	16
14.4	Call Completion	16
14.4.1	Call Hold (CH)	16
14.4.2	Call Waiting (CW).....	16
14.5	Multi Party (MPTY).....	17
14.6	Closed User Group (CUG)	17
14.7	Advice of Charge (AoC)	17
14.8	Call Barring	17
14.8.1	Barring of all outgoing calls	17
14.8.2	Barring of outgoing international calls	17
14.8.2.1	Mobile originated calls.....	17
14.8.2.2	Forwarded Calls	17
14.8.3	Barring of outgoing international calls except those directed to the HPLMN country	17
14.8.4	Barring of all incoming calls.....	17
14.8.5	Barring of incoming calls when roaming.....	17
14.9	Explicit Call Transfer (ECT).....	17
14.10	Completion of Call to Busy Subscriber (CCBS)	17
14.11	Multiple Subscriber Profile (MSP).....	18
15	Interaction with network features.....	18
15.1	Interactions with Operator Determined Barring (ODB).....	18
15.1.1	Barring of all outgoing calls	18
15.1.2	Barring of all outgoing international calls	18
15.1.3	Barring of all outgoing international calls except those directed to the home PLMN country	18
15.1.4	Barring of outgoing calls when roaming outside the home PLMN country	18
15.1.5	Barring of outgoing premium rate calls	18
15.1.6	Barring of incoming calls	18
15.1.7	Barring of incoming calls when roaming outside the home PLMN country	18
15.1.8	Operator Specific Barring	18
15.1.9	Barring of Supplementary Services Management.....	18
15.2	Interactions with Optimal Routing (OR)	19
15.3	Interactions with MExE.....	19
15.4	Interactions with CAMEL	19
16	Compatibility of USAT ME's and applications	19
16.1	USAT Classification.....	19
16.2	ME/USIM operation.....	19
16.3	ME/UICC capability information exchange.....	20
16.4	ME and compatibility.....	20
16.5	Void.....	20
17	Void.....	20
Annex A (informative): Change history		21
History		23

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

This 3GPP Technical Specification defines the stage one description of the USIM application Toolkit (USAT). Stage one is an overall service description, primarily from the subscriber's and serving environment's points of view, and does not deal with the details of the human interface itself.

This TS includes information applicable to network operators, serving environments and terminal, switch and database manufacturers.

This TS contains the core requirements for a USIM application Toolkit (USAT) which are sufficient to provide a complete service.

It is highly desirable however, that technical solutions for a USIM application Toolkit (USAT) are sufficiently flexible to allow for possible enhancements. Additional functionalities not documented in this TS may implement requirements which are considered outside the scope of this TS. This additional functionality may be on a network-wide basis, nation-wide basis or particular to a group of users. Such additional functionality shall not compromise conformance to the core requirements of the service.




Figure 1: Scope of this TS

As indicated in Figure 1, the scope of this TS encompasses the USAT functionality in the UE (comprising USIM and ME) and the interaction with the PLMN environment. The USAT Server is not necessarily a separate entity as shown in the figure; nodes providing USAT services may also exist within the PLMN. The functionalities of the USAT servers (such as charging aspects, security level classification etc.) are not covered by this specification.

The requirements are considered to be applicable to both GSM and UMTS systems.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.

- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

2.1 Normative references

- [1] 3GPP TS 31.101: "UICC-Terminal Interface; Physical and Logical Characteristics".
- [2] Void.
- [3] Void.
- [4] 3GPP TS 51.011: "Specification of the Subscriber Identity Module, Mobile Equipment (SIM - ME) interface" Release 4.
- [5] Void.
- [6] Void.
- [7] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [8] Void.
- [9] Void.
- [10] Void.
- [11] Void.
- [12] Void.
- [13] Void.
- [14] 3GPP TS 31.111: "USIM Application Toolkit (USAT)".
- [15] 3GPP TS 31.102: "Characteristics of the USIM Application".
- [16] 3GPP TS 22.140: "Multimedia Messaging Service (MMS); Stage 1".
- [17] 3GPP TS 51.014: "Specification of the SIM Application Toolkit for the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface" Release 4.
- [18] ETSI TS 102 240: "UICC Application Programming Interface and Loader Requirements; Service description" Release 6.
- [19] 3GPP TS 22.071: "Location Services (LCS); Service description; Stage 1"..

3 Definitions and abbreviations

3.1 Definitions

For the purposes of this TS the following definitions apply:

applet: a small program that is intended not to be run on its own, but rather to be embedded inside another application.

application: USAT information in the form of software, applications, associated resources (e.g. libraries) and/or data.

bearer independent protocol: Mechanism at the interface between the USIM and the ME which provide access to the data bearers supported by the ME.

buffer: A dedicated memory used to temporarily store data to be sent and/or retrieved.

content: data and/or information associated with, or independent of, a particular application which may be presented to or collected from a user.

data channel: allow the USIM and the network to exchange data using a selected data exchange capability.

link: radio resource.

USAT service: a service enhanced (or made possible) by USAT technology.

USAT execution environment: the USAT execution environment provides the mechanisms to operate single or multiple USAT-applications.

USAT serving environment: an entity which delivers USAT services to the subscriber. This is normally the PLMN operator, but could be an entity with USAT responsibility (which may have been delegated by the PLMN operator).

USAT subscriber: the owner of a PLMN subscription who has entered into an agreement with a USAT serving environment for USAT services. Access to USAT services through other types of networks is out of scope of this specification.

USAT server: a node supporting USAT services in the USAT service environment.

user: the user of a USAT UE, who may or may not be the subscriber.

(U)SIM: SIM and/or USIM.

3.2 Abbreviations

For the purposes of this TS the following abbreviations apply:

API	Application Programming Interface
CAMEL	Customized Applications for Mobile network Enhanced Logic
CS	Circuit Switched
CSE	CAMEL Service Environment
IN	Intelligent Network
ME	Mobile Equipment
MExE	Mobile Execution Environment
MMI	Man Machine Interface
NO	Network Operator
PLMN	Public Land Mobile Network
SAT	SIM Application Toolkit
SCI	Subscriber Controlled Input
SIM	Subscriber Identity Module
UE	User Equipment
USAT	USIM Application Toolkit
USIM	Universal Subscriber Identity Module

Further abbreviations are given in TS 21.905 [7].

4 Description

USAT provides a standardised execution environment for applications stored on the UICC and the ability to utilize certain functions of the supporting mobile equipment. USAT provides mechanisms which allow applications, existing in the UICC, to interact and operate with any ME which supports the specified mechanism(s) thus ensuring interoperability between a UICC and an ME, independent of the respective manufacturers and operators. A transport mechanism is provided enabling applications to be down-loaded and/or updated.

A significant aspect of USAT is the highly secure environment provided by the UICC. This is further enhanced by the fact that the subscriber and the issuer of the UICC and also the USAT applications have a "trusted relationship" (e.g. the subscriber trusts the issuer of the UICC to charge correctly for the resources used). This allows certain features, such as call control, to be implemented with a degree of freedom which would not be acceptable in a "non-trusted relationship".

The introduction of the USAT execution environment into UEs (i.e. ME+USIM) is a significant step forward in their evolution. The ability of UEs to support USAT represents an extension of the UE's and PLMN capabilities. In order to allow current and future technologies to exploit and benefit from this, a standardized means of exchanging the MEs' and USIMs capability profiles is supported.

This Technical Specification defines an enhancement of the USIM/ME interface.

5 High level USAT requirements

The requirements described in the present document apply independently of the UICC/ME interfaces described in TS 31.101 [1]. However, this may imply different technical implementations of these requirements depending on the used interface (e.g. ISO or HSP), in order to optimize the USAT implementation.

The high level requirements of USAT are as follows:-

- provide the user with additional user interface functionalities to control and invoke services (e.g. menus, icons, etc.) ;
- to provide means for the user to personalize applications by means of parameters, if such parameters are made available by the application;
- provide support of a wide variety of applications;
- provide the means for USAT to interact with the user via the input and output devices of the ME;
- the means to transfer applications automatically or on demand to the USIM from a USAT server, and upgrade existing applications via the PLMN;
- the means to transfer content automatically or on demand to or from the USIM from or to a USAT server;
- the means to transfer content directly from one USAT application to a second UE with a USAT application via the PLMN;
- the need for an inherent security architecture such that it shall be possible for both the USAT and USAT server sides of a connection to be authenticated (possibly implicitly by the use of digital signature or ciphering). The USAT server shall maintain security of subscribers' personal data and PLMN data;
- it shall be possible to charge subscribers for the use of PLMN or third party USAT services;
- the means for USAT applications on the USIM to communicate with other PLMN nodes;
- the means for the ME and USIM to exchange USAT capability information;
- provision of USAT API(s) to facilitate the development and downloading of USAT applications;
- It may be possible for the user to activate and deactivate the USIM/SIM application execution environment; in this case the ME shall initiate a new USIM session.- the means for the network operator to provide and manage the USAT execution environment resources and also to provide and manage (i.e. identify version, activate, deactivate, delete, modify, download etc.) the applications;
- the means for the USAT application to fully control the display of all actions and network-responses related to the operation of the application. Optionally under user control the ME may display the individual actions/responses;
- the means for the USAT application to control the PLMN services/supplementary services and IP multimedia services via the standardized MMI. Only the originator (i.e. either user or USAT application) of the action shall directly receive the results/responses of that action (e.g. network response to an SCI). Optionally under user control the ME may display the individual actions/responses.
- provide the user with additional user interface functionality to control and invoke IP multimedia services

Some of the above requirements are subsequently elaborated.

6 SAT/USAT/ME interface requirements

6.1 (U)SAT APIs

The (U)SIM-API is defined in ETSI TS 102 240 [18]. This API is valid for (U)SAT and is referred to in this TS as (U)SAT API.

The (U)SAT API for the UICC shall allow application programmers easy access to the functions and data described in 3GPP TS 51.011 [4], TS 31.101 [1], TS 31.102 [15], TS 51.014 [17], TS 31.111 [14], such that (U)SIM based services can be developed and loaded onto UICCs (independent of the UICC manufacturer), quickly and, if necessary, remotely, after the card has been issued. The (U)SAT API shall support pro-active functions as described in 3GPP TS 51.014 [17] and TS 31.111 [14], and transport functions as described in 3GPP TS 51.011 [4] and TS 31.102 [15].

6.2 USAT proactive capability

The USAT proactive capability is a mechanism whereby the UICC can request specific actions to be taken by the ME by issuing "proactive commands" thus establishing and maintaining an interactive dialogue with the user and/or communicating with the network or an external device.

An ME may have a variety of configurations, for example, it may consist of a modem connected to an external display. The USAT proactive capability requirements are applicable to the ME as a whole without regard to any particular configuration.

The ME shall inform the UICC of the success or otherwise of each command issued to it by the UICC, and also indicate the command details and if applicable add more specific information.

The proactive command set allows the USAT to instruct the ME to:

- 1 display text supplied by the USAT on the ME's display, with an indication of priority (normal or high), and a defined action (user activity or timeout) to terminate the text display.
- 2 display a text string and obtain the response in the form of a single user keystroke or a string of keys entered by the user and pass the response to the UICC. If the response is designated as private by the UICC the ME shall not display the users response on the screen.
- 3 set up a voice call to an address with a specific priority as indicated by the UICC with all parameters indicated by the UICC.
- 4 set up a data call to an address with specific bearer capability and priority, all parameters are indicated by the UICC.
- 5 set up and manage a data channel (using CSD, Packet service bearer (e.g.: GPRS, UTRAN packet service, HSDPA, ...), SMS, USSD or I-WLAN) between the UICC and an address using information provided by the UICC. It shall be possible for the USAT application to provide the ME with the network connectivity parameters to be used (e.g. PDP context parameters) to establish IP connectivity between a USAT application and a remote entity.
- 6 send data through a previously set up data channel. The UICC informs the ME if the data is to be sent immediately.
- 7 retrieve data from the ME that has previously been received via a data channel set up using (5) above. The UICC informs the ME as to how much data it expects to retrieve.
- 8 send a short message to the network. The short message text is supplied by the UICC to the ME in either packed or unpacked SMS 7-bit alphabet, or UCS2 alphabet.
- 9 send a SS control, SS MMI string or USSD string, indicating which alphabet is used where applicable.
- 10 play a tone in the appropriate audio device.
- 11 negotiate, within reasonable tolerances, a periodic "polling" of the USIM Toolkit.

- 12 refresh the image (if applicable) of the USIM data contained in the ME memory, either entirely, or partially, or instruct the ME to re-initialize completely.
 - 13 set up an event list in the ME such that the UICC is informed by the ME when an indicated event has occurred.
 - 14 set up an additional menu in the ME, by issuing the ME with a menu list, and allow indication back to the UICC of the user selected menu item.
 - 15 provide requested information from the ME to the UICC, for example the MCC, MNC and IMEI.
 - 16 communicate bi-directionally with an auxiliary device, e.g. a second card reader.
 - 17 set up, refresh and interrogate several timers, and inform the UICC when these expire, within reasonable tolerances.
 - 18 display additional MMI information such as display information or tones with commands that employ network resources, with an indication to the ME as to the required level of ME generated MMI as a result of the interaction with the network.
 - 19 allow the ME to display help information with the commands, by providing the associated text, related to the user action (e.g. menu selection).
 - 20 Provide indication from the ME to the USAT when a key on the MMI has been pressed in a "menu" (response to prompt) or and event (independent action) methods, with key identification. This indication shall be done in a secure manner.
 - 21 send a MM to the network, using a data channel as (5) above. The MM content is supplied by the ME or the UICC.
 - 22 start an ME-based application that the USAT application knows about. For example USAT applications have the ability to launch a micro-browser if provided by the ME as already described in this document (see Interactions with MExE), or may ask the ME to initiate a data synchronisation process.
- Note: addressing of ME applications and other relevant parameters if needed, shall be properly defined by the corresponding USAT specifications.
- 23 Provide location information from the ME to the UICC (e.g. GPS, A-GPS, Galileo, etc) if the ME is equipped with a positioning feature.
 - 24 Provide a list of the CSG identities available application for selection together with the corresponding HNB Names from the ME to the UICC applications, if available to the ME.
 - 25 Inform the UICC applications when selecting and leaving a CSG cell and to provide the corresponding CSG identity and HNB Name, if HNB Name is available.

Unless otherwise stated the following shall apply:

- The format of text to be displayed is designated by the UICC and is either SMS default alphabet (packed or unpacked) or UCS2 alphabet.
- The format of the response from the ME is designated by the UICC and is either keypad digit (0-9, *, #, +), SMS default alphabet characters or UCS2 alphabet characters.

6.3 ME Capability for support of bearer independent protocol

The ME supporting bearer independent protocol shall provide to the USIM a common interface for any type of data bearer. This interface is in addition to dedicated commands (e.g. SMS, SS and USSD) for USAT application to exchange data with entities outside the UICC.

The communication is initiated by the UICC. The ME negotiates with the UICC and the addressed entity to establish the optimum channel considering the UICC request, the network and ME capabilities.

The ME is responsible for maintaining and restoring the link should there be a link error.

6.4 ME equipped with positioning features

It shall be possible for the UICC to request the current location information from the ME for USAT applications if the ME is equipped with a positioning feature capable of operating in autonomous, MS Assisted or MS Based modes (e.g. GPS, A-GPS, Galileo, etc).

It shall be possible for the UICC to detect the presence of a positioning feature in the Terminal Profile if the ME is equipped with a positioning feature.

The ME shall inform the UICC if the location feature is disabled when the UICC requests the ME to send the location information.

The ME shall inform the UICC if the location information retrieval is not possible (e.g. due to lack of GPS coverage) when the UICC requests the ME to send the location information.

The UICC request for location information shall be treated in accordance with the principles defined in TS 22.071 [19].

7 USAT User Interface requirements

7.1 Data presentation requirements (e.g. Display)

In order to be able to create and operate applications with a homogeneous display(s) USAT shall fully control the display of all actions and all network-responses concerned with the operation of the application. USAT shall, upon completion/closure of the application, return full control to the ME.

The display of information shall be either in the form of text (i.e. alphanumeric characters) or in graphical form or both.

Optionally under user control the ME may display the individual actions/network responses.

7.2 Data acquisition requirements (e.g. Keypad)

In order to be able to create and operate applications with a homogeneous user interface USAT shall fully control the function associated with the user input for example via the keypad of the ME. Exceptions to this are keys which are "dedicated ME keys" such as the ON/OFF key. USAT shall, upon completion/closure of the application, return full control to the ME.

7.3 Access requirements (e.g. Menu)

A simple, powerful method for the user to access and interact with certain USAT applications shall be provided.

It shall be possible for the USAT-Application to set up a user interface (e.g. menu, icons) via the capabilities provided by the ME to allow the user to interact with a USAT application using, for example, the display and keypad.

7.4 Menu capability

7.4.1 Set up capability

The menu set up capability is a mechanism whereby the menu items (menu entries/structure etc.) required by the USAT is indicated to the ME by means of a proactive command. The menu set up capability is not directly available to the user. As an option this may include "help information" items.

7.4.2 Selection capability

The menu selection capability is a mechanism whereby the menu item selected by the user is indicated to the USAT by the ME via the UICC-ME interface. As an option this may include "help information" items.

7.5 Soft-key capability

The soft-key allocation capability is a mechanism whereby the UICC indicates to the ME the text to be displayed and the USAT function which is to be assigned to a ME soft-key.

7.6 User control of the SAT/USAT execution environment

The user may be able to control the USAT execution environment via the ME in accordance with the following cases:

- i) the USAT execution environment is enabled/disabled
- ii) the USAT execution environment is not allowed to make automatic calls
- iii) the USAT execution environment is allowed to make automatic calls but only with user confirmation
- iv) the USAT execution environment is allowed to make automatic calls without user confirmation.

In addition it shall be possible for the user to independently enable/disable the AT command feature.

Note that for ease of reading the term "automatic call" is used but this shall be taken to mean any network interaction initiated by USAT including SMS, USSD etc. but excluding user initiated interactions modified by USAT.

The user shall be notified by the ME if service access is prevented as the result of partially disabling the USAT execution environment. It shall be possible to enable the USAT execution environment if service access has been prevented.

7.7 MMS presentation requirements

The USAT shall be able to request the ME to present to the user a Multimedia Message (i.e. via the MMS user agent in the ME) stored in the UICC (see TS 22.140 [16]).

8 Network interface requirements

8.1 USAT/Network interaction

USAT/Network interaction is required such that the USAT and the network can bi-directionally exchange data through the ME, employing any of the transport mechanisms defined in the section "USAT data exchange capabilities requirements".

8.2 Communication control capability

The communication control capability is a mechanism whereby the use of communication resources is either initiated by the USAT application or modified by the USAT application subsequent to a user action. If supported by the ME, the ME shall, at the time of the user initiated communication request, inform the UICC of the current cell location identity. The UICC shall indicate to the ME if the presentation of information (display, tones etc.) shall be restricted to the explicit presentation of USAT supplied information or if it is required to present standard PLMN information (e.g. network responses) in addition to the USAT supplied information.

It shall be possible for the UICC:

- to initiate and terminate a (UICC initiated) communication request with or without explicit confirmation by the user
- to allow, bar or modify a communication request initiated by the user
- to replace a user initiated communication request by another communication request (e.g. replace call request by an SS action etc.).

It shall be possible for the SAT/USAT serving environment to enable/disable the communication control capability. As an option, dependant on the subscribers subscription and the application, the user may enable/disable the communication control capability via a SAT/USAT serving environment and/or under the control of the Network Operator. The user shall be notified by the ME in case network service is lost as the result of disabling the communication control capability.

The communication control capability applies to all mobile originated requests independent of the applicable data exchange capability. Explicitly it applies to voice calls, IMS based communications and to all services listed in the section "USAT data exchange capabilities requirements" (e.g. SMS, supplementary service, circuit switched connection, packet switched connection, etc.).

8.3 Service Interworking requirements

The USAT application shall be able to use all PLMN services and supplementary services (SS) including those functions available to the user via the standardized MMI (e.g. 2 SEND for Call Hold). Only the originator (i.e. either user or USAT application) of the action shall directly receive the results/responses of that action (e.g. network response to an SCI). Optionally under user control the ME may display the individual actions/responses.

9 USAT data exchange capabilities requirements

9.1 Data exchange capabilities supported

USAT shall support the transmission (mobile originated) and the reception (mobile terminated) of data by means of one of the following data exchange capabilities, either using dedicated commands or managed by the ME (using the Bearer Independent Protocol) ;

Data exchange capability
SMS
CSD
Packet service bearer
SS (MO only)
USSD (MO only)
Cell Broadcast (MT only)
SMS via GPRS
I-WLAN
Local Bearer (Bluetooth, IrDA, RS232, USB)

10 Charging requirements

It shall be possible to charge the subscriber for the use of USAT applications.

It shall be possible to charge for the following activities:-

- subscription:
 - the subscriber's registration to use USAT services
- application transfer (download):
 - the transfer of applications and/or information to a subscriber's USAT UE
- application upgrading (download):
 - the upgrading of previously transferred applications to a subscriber's USAT UE

- application use:
the use of applications by a subscriber's USAT UE
- content:
the provision of content within a USAT application
- roaming:
the use of USAT applications by a subscriber when roaming
- transport:
the use of a transport/bearer service (e.g. SMS)

11 Security requirements

The integrity of the USIM and existing security mechanisms shall not be compromised with the introduction of USAT services.

The security of the PLMN, the USIM and the USAT applications shall not be able to be compromised by an external execution environment.

Applications running within an external execution environment are considered "non-trusted" until a secure authentication and identification procedure has been successfully performed. MExE is considered to be an external execution environment. MExE is not covered by this specification.

Applications designed using the features in this specification may require additional methods to provide additional data confidentiality, data integrity, and data sender validation, or any subset thereof.

11.1 Secure Environment requirements

A major aspect of the UICC is the security provided by the chip technology combined with the encryption and challenge/response procedures. The enhancement of the UICC by USAT shall not reduce nor endanger the current security. In addition, the USAT environment shall maintain (or improve) the same high levels of security. Adequate (future) measures shall be taken to ensure the fulfilment of this requirement also with future advances in technologies/services (either network-centric and/or UE-centric).

12 Emergency calls

The SAT/USAT shall be able to instruct the ME to set up an emergency call to the default emergency call centre. All other call set up requests shall proceed as a normal call set up, and the dialled digits offered by the SAT/USAT shall not be altered.

13 Roaming

Provided a roaming agreement for the necessary transport/bearer service(s) (e.g. SMS, GPRS) is currently valid, the USAT execution environment shall be supported when roaming.

14 Interaction with supplementary services

14.1 General

This subclause defines the interaction between PLMN supplementary services and the USAT feature. PLMN supplementary services shall not have any knowledge of USAT based services.

14.2 Line Identification

14.2.1 Calling Line Identification Presentation (CLIP)

No interaction.

14.2.2 Calling Line Identification Restriction (CLIR)

No interaction.

14.2.3 Connected Line Identification Presentation (COLP)

14.2.4 Connected Line Identification Restriction (COLR)

No interaction.

14.3 Call Forwarding

14.3.1 Call Forwarding Unconditional (CFU)

USAT shall be able to modify the forwarded to number entered by the user and displayed, upon interrogation, to the user.

14.3.2 Call Forwarding Busy (CFB)

USAT shall be able to modify the forwarded to number entered by the user and displayed, upon interrogation, to the user.

14.3.3 Call Forwarding on No Reply (CFNRy)

USAT shall be able to modify the forwarded to number entered by the user and displayed, upon interrogation, to the user.

14.3.4 Call Forwarding on Not Reachable (CFNRc)

USAT shall be able to modify the forwarded to number entered by the user and displayed, upon interrogation, to the user.

14.4 Call Completion

14.4.1 Call Hold (CH)

No interaction.

14.4.2 Call Waiting (CW)

No interaction.

14.5 Multi Party (MPTY)

USAT shall be able to modify the called number entered by the user.

14.6 Closed User Group (CUG)

No interaction.

14.7 Advice of Charge (AoC)

No interaction.

14.8 Call Barring

14.8.1 Barring of all outgoing calls

No interaction.

14.8.2 Barring of outgoing international calls

14.8.2.1 Mobile originated calls

No interaction.

14.8.2.2 Forwarded Calls

No interaction.

14.8.3 Barring of outgoing international calls except those directed to the HPLMN country

No interaction.

14.8.4 Barring of all incoming calls

No interaction.

14.8.5 Barring of incoming calls when roaming

No interaction.

14.9 Explicit Call Transfer (ECT)

USAT shall be able to modify the transfer number entered by the user.

14.10 Completion of Call to Busy Subscriber (CCBS)

USAT shall be able to modify the number displayed to the user.

14.11 Multiple Subscriber Profile (MSP)

No interaction.

15 Interaction with network features

All services available in the network shall continue to be offered and remain applicable in addition to USAT. This includes the basic services, supplementary services and network features.

15.1 Interactions with Operator Determined Barring (ODB)

15.1.1 Barring of all outgoing calls

No interaction.

15.1.2 Barring of all outgoing international calls

No interaction.

15.1.3 Barring of all outgoing international calls except those directed to the home PLMN country

No interaction.

15.1.4 Barring of outgoing calls when roaming outside the home PLMN country

No interaction.

15.1.5 Barring of outgoing premium rate calls

No interaction.

15.1.6 Barring of incoming calls

No interaction.

15.1.7 Barring of incoming calls when roaming outside the home PLMN country

No interaction.

15.1.8 Operator Specific Barring

No interaction.

15.1.9 Barring of Supplementary Services Management

No interaction.

15.2 Interactions with Optimal Routing (OR)

No interaction.

15.3 Interactions with MExE

The SAT/USAT applications have the the ability to launch a micro-browser (on a given URL and a given bearer) if provided by the ME.

15.4 Interactions with CAMEL

No interaction.

16 Compatibility of USAT ME's and applications

16.1 USAT Classification

Given the wide ranging hardware capabilities of UICCs and MEs, together with the development of USAT applications and applets, a USAT classification shall be supported to determine their respective capability and compatibility. The USAT classification shall apply both to UICCs, MEs and applications and applets.

The objective is to:-

- classify the requirements of a USAT UICC/applications and
- identify the commands and features supported by the ME

The development and maintenance of the USAT specification is done in accordance to the ETSI/3GPP release procedures. . I.e. annual releases of the specifications are done providing support for new commands and enhancements of existing commands. The annual Release may both contain commands that are mandatory for that Release and commands that are optional.

The classification of the optional commands and features in a given Release may be done with the concept of "Letter Classes". A Letter Class identifies a subset of functionality of the Release, which will provide the user, USAT serving environment and application writer with a consistent set of commands and features.

The concept of a USAT Letter Classes is introduced to help identify the ME, and the UICC /USAT application compatibility within a given Release. The USAT Letter Class is distinct and unrelated to the existing PLMN UE Classmark. The USAT Letter Classes are not used during capability negotiations, but are intended to assist in designing applications by provision of a means for an application designer to identify which combinations of USAT features are supported by the MEs. Capability negotiations between the UICC and the ME are performed at the feature level, independent of the USAT Letter Class.

In addition to classifying the ME as conforming to a specific Release and if applicable one or several Letter Classes within the release, an ME manufacturers declaration shall be provided. This shall indicate in detail the commands and features supported by the ME. Any conformance testing shall be performed in accordance to this declaration.

The support of a given Letter Class doesn't require the support of another Letter Class.

USAT applications will be developed to execute on USAT UE's in one or more classifications. In order for USAT applications to be properly supported by a USAT UE, the application shall be designated by the same classification of USAT UE's on which they are intended to be executed.

16.2 ME/USIM operation

In the case of an ME not supporting SAT/USAT or not supporting a certain SAT/USAT feature the following shall apply:

- the USIM shall control (i.e. allow or prevent) the access to the network.
This allows the USIM to prevent the use of a subscription (which may rely on the support of USAT features for correct operation) in an uncontrolled manner.
- if access to a PLMN is not prevented the ME shall support the non-USAT PLMN features without restriction.

16.3 ME/UICC capability information exchange

If supported, the UICC and the ME shall exchange USAT capabilities when the card session is initiated.

This exchange of information is important since the UICC then knows what the ME is capable of, and the UICC can thus adapt the service made available to the user accordingly. If the UICC does not receive any ME capability information it shall assume that the ME does not support USAT.

A UICC that supports USAT shall not attempt to invoke USAT functions in the ME if the ME has not indicated USAT support.

An ME that supports USAT shall not attempt to invoke USAT functions in the UICC if the UICC has not indicated that USAT is supported and is active.

16.4 ME and compatibility

For compatibility testing the ME manufacturers shall provide a declaration of the Release and if applicable the Letter Class(es) supported by the ME including the detail of all commands and features supported by the ME. It can be envisaged that ME implementations will exist that are compliant to a given release and which support commands and features from later releases.

16.5 Void

17 Void

Annex A (informative): Change history

Document history		
Date	Version	Comment
June 98	0.0.0	Initial draft based on MExE stage 1.
June 98	0.1.0	Output of SMG1/SMG9 joint ad hoc
August 98	0.2.0	Updated by editor reflecting discussion at joint ad hoc in June.
August 98	0.3.0	Output of SMG1/SMG9 joint ad hoc meeting
November 98	0.4.0	Output of SMG1/SMG9 joint ad hoc meeting
January 99	0.5.0	Output of SMG1/SMG9 joint ad hoc meeting
January 99	0.5.1	Improved output of SMG1/SMG9 joint ad hoc meeting, submitted to SMG1 for information, with recommendation to raise to Version 1.0.0.
March 99	1.0.0	Raised to Version 1.0.0 by SMG1 Plenary
May 99	1.0.1	Draft changes, interim output of SMG1/SMG9 ad hoc meeting.
May 99	1.1.0	Output of SMG1/SMG9 joint ad hoc meeting
May 99	1.1.1	Minor editorial changes only. Output of SMG1/SMG9 joint ad hoc meeting
June 99	1.1.2	Spelling and editorial corrections, changes agreed to by email after the 5 th ad hoc
September 99	1.3.0	New version after S1 meeting
September 99	1.3.1	Final version for approval at TSG-SA Korea
October 99	2.0.0	Editorial clean-up for version 2.0.0

Change history											
TSG SA#	SA Doc.	SA1 Doc	Spec	CR	Rev	Rel	Cat	Subject/Comment	Old	New	WI
SA#05	SP99-434							Version 3.0.0 Approved		3.0.0	
SMG#30	SP99-434							Version 3.0.0 Approved		3.0.0	
SP-07	SP-000058	S1-000120	22.038	001		R99	D	USIM/SIM Application Toolkit, Service Description, Stage 1	3.0.0	3.1.0	
SP-07	SP-000152		22.038	002	1	R99	B	Addition requirements for bearer independent data transfer feature	3.0.0	3.1.0	
SP-08	SP-000196	S1-000432	22.038	003		R99	F	Deletion of note to non-existent TS	3.1.0	3.2.0	
SP-09	SP-000381	S1-000637	22.038	005		R4	D	Change of MExE name	3.2.0	4.0.0	
SP-09	SP-000382	S1-000629	22.038	004		R5	B	Release 2000 features	3.2.0	5.0.0	
SP-10	SP-000541	S1-000862	22.038	007		Rel-5	B	LS on USAT local link mechanism and impact on TS 22.038	5.0.0	5.1.0	USAT1- LocLnk
SP-12	SP-010261	S1-010419	22.038	008		Rel-5	B	Indication of Key identification	5.1.0	5.2.0	USAT1
SP-20	SP-030238	S1-030466	22.038	011		Rel-5	A	Clean up of USAT requirements	5.2.0	5.3.0	TEI
SP-20	SP-030355		22.038	013	2	Rel-6	B	MMS support on the card	5.2.0	6.0.0	MMS-R6
SP-21	SP-030461	S1-030887	22.038	014		Rel-6	B	MMS support by the USIM Application Toolkit	6.0.0	6.1.0	MMS-R6

SP-22	SP-030772	-	22.038	016	1	Rel-6	F	Change of the term "bearer" to "data exchange capability" and removal of implementation dependent statements in TS 22.038	6.1.0	6.2.0	TEI
SP-22	SP-030688	S1-031336	22.038	018	-	Rel-6	A	Enable Cell Broadcast Bearer for USAT application while connected to UTRAN networks	6.1.0	6.2.0	TEI5
SP-22	SP-030685	S1-031322	22.038	022	-	Rel-6	A	CR to align TS 22.038 with the T3 specifications TS 11.14 and TS 31.111	6.1.0	6.2.0	EMC1-CS
SP-22	SP-030696	S1-031220	22.038	015	-	Rel-7	B	Interaction between ME and USAT applications	6.1.0	7.0.0	USAT1
SP-25	SP-040679	-	22.038	023	1	Rel-7	A	Enhance the USAT MMS presentation	7.0.0	7.1.0	UEMMS
SP-26	SP-040734	S1-040985	22.038	025	-	Rel-7	B	Extention of the USAT bearers	7.1.0	7.2.0	WLAN
SP-27	SP-050057	S1-050247	22.038	027	-	Rel-7	A	References corrections	7.2.0	7.3.0	TEI-7
SP-28	SP-050220	S1-050479	22.038	028	-	Rel-7	F	Correction of WLAN into I-WLAN	7.3.0	7.4.0	WLAN
SP-29	SP-050606	-	22.038	0030	1	Rel-7	A	Addition of UTRAN packet service as a data bearer for the UICC	7.4.0	7.5.0	TEI-7
SP-39	SP-080043	S1-080277	22.038	0032	3	Rel-8	C	Extension of Toolkit communication control to IMS	7.5.0	8.0.0	TEI8
SP-39	SP-080043	S1-080311	22.038	0033	4	Rel-8	B	Availability of Location information in the UICC	7.5.0	8.0.0	TEI8
SP-39	SP-080043	S1-080305	22.038	0035	4	Rel-8	B	Toolkit over HSP	7.5.0	8.0.0	TEI8
-	-	-	-	-	-	-	-	Some revision marks appearing in v.8.0.0 have been accepted	8.0.0	8.0.1	
SP-43	SP-090215	S1-090288 rev	22.038	0036	5	Rel-9	B	Discovery of surrounding home (e)NodeB by UICC	8.0.1	9.0.0	EHNB
SP-50	SP-100805	S1-103325	22.038	0037	1	Rel-10	F	Correction of USAT requirements	9.0.0	10.0.0	TEI10
2011-03								Update to Rel-10 version (MCC)	10.0.0	10.0.1	
2012-09	-	-	-	-	-	-	-	Update to Rel-11 version (MCC)	10.0.1	11.0.0	
2014-10	-	-	-	-	-	-	-	Update to Rel-12 version (MCC)	11.0.0	12.0.0	
2015-12								Update to Rel-13 version (MCC)	12.0.0	13.0.0	
2017-03	-	-	-	-	-	-	-	Updated to Rel-14 by MCC	13.0.0	14.0.0	
2018-06	-	-	-	-	-	-	-	Updated to Rel-15 by MCC	14.0.0	15.0.0	
SA#88e	-	-	-	-	-	-	-	Updated to Rel-16 by MCC	15.0.0	16.0.0	
2022-03	-	-	-	-	-	-	-	Updated to Rel-17 by MCC	16.0.0	17.0.0	

History

Document history		
V17.0.0	April 2022	Publication