

ETSI TS 122 140 V4.3.0 (2002-12)

Technical Specification

**Universal Mobile Telecommunications System (UMTS);
Multimedia Messaging Service;
Stage 1
(3GPP TS 22.140 version 4.3.0 Release 4)**



Reference

RTS/TSGS-0122140v430

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.org

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the TIPHON logo are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

All published ETSI deliverables shall include information which directs the reader to the above source of information.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.2 Abbreviations	6
4 High level Requirements	6
5 General Requirements	7
5.1 Multimedia message management	7
5.2 Multimedia message delivery and submission	9
5.3 Notification and Acknowledgement	10
5.4 Addressing.....	10
6 User Profile	11
7 Security.....	11
8 Charging	11
9 External Interface	11
10 Interworking	12
11 Roaming	12
Annex A (informative): Change history	13
History	14

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

SMS has been very successful in the GSM second generation system, as all mobiles have supported the application level and it is possible to send to any GSM handset without the need to check for individual support. This easy to use service for non realtime text transmission between GSM users shall be succeeded to in third generation mobile systems by a non real-time Multimedia Message Service, MMS. The MMS will allow users to send and receive messages exploiting the whole array of media types available today e.g. text, images, audio, video while also making it possible to support new content types as they become popular.

3GPP shall not standardise new services themselves, but instead uses the standardised set of service capabilities features on which the new services will be built.

Multimedia technology a rapidly developing allowing new capabilities, such as multimedia messages, games, presentations and services that are now considered to be a part of every day life. Multimedia consists of one or more media elements (such as text, voice, image and video), and it is the combination of these media elements in a ordered synchronised manner that creates a multimedia presentation.

A non-realtime multimedia message as observed by the user is a combination of one or more different media elements in a multimedia presentation, that can be transferred between users without the requirement for the need to be transferred in realtime. The non-real-time multimedia messaging service shall be capable of supporting current and future multimedia messaging services, and exploit the advances being made in the world multimedia community, with additional mobile requirements.

1 Scope

This Technical Specification defines the stage one description of the non real-time Multimedia Messaging Service, MMS. Stage one is the set of requirements which shall be supported for the provision of non real-time multimedia messaging service, seen primarily from the subscriber's and service providers' points of view.

This TS includes information applicable to network operators, service providers, terminal and network manufacturers.

This TS contains the core requirements for the Multimedia Messaging Service, which are sufficient to provide a complete service.

Additional functionalities not documented in this TS may implement requirements which are considered outside the scope of this TS. Such additional functionality may be on a network-wide basis, nation-wide basis or particular to a group of users. Such additional functionality shall not compromise conformance to the core requirements of the service.

This TS defines the requirements for MMS to be understood as a framework to enable non real-time transmissions for different types of media including such functionality as:

- multiple media elements per single message
- individual handling of message elements
- different delivery methods for each message element
- negotiate different terminal and network MM capabilities
- notification and acknowledgement of MM related events (e.g. delivery, deletion, ...)
- handling of undeliverable MM
- personalised MMS configuration
- flexible charging

The above list is not exhaustive.

Thus the MMS enables a unified application which integrates the composition, storage, access, and delivery of different kinds of media, e.g. text, voice, image or video in combination with additional mobile requirements.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3G TS 22.101 (V3.6.0 onwards): "Service Principles".

[2] 3G TS 22.121 (V3.0.0 onwards): "The Virtual home Environment".

[3] 3G TS 21.133 (V3.0.0 onwards): "3G Security; Security Threats and Requirements".

[4] 3G TS 22.975 (V3.0.0 onwards): "Advanced Addressing".

3 Definitions and abbreviations

3.1 Definitions

Recipient : the recipient is the entity to which a MM has been sent.

Sender: the sender is the entity that sent a MM.

User: the user is the MM sender or the MM recipient.

message element: a message element is a part of a MM consisting of only one media type.

multimedia message: a multimedia message is a message composed of one or more message elements.

multimedia message service: A multimedia message service allows transfer of multimedia messages between users without the requirement for the multimedia messages to be transferred in real-time.

media types: a media type refers to one form of presenting information to a user, e.g. voice or fax.**media formats:** within one media type different media formats are applicable for the media presentation, e.g. a picture can be GIF or JPEG format.

network: for the purposes of supporting multimedia messaging, the term network shall be considered to include the mobile operator's network and any functionality which may exist outside the mobile operator's network (i.e.fixed, internet and multimedia technologies etc.), and the support provided by that functionality for multimedia messaging.

service capabilities features: see Reference [2].

3.2 Abbreviations

For the purposes of this document the following abbreviations apply:

MM	Multimedia Message
MMS	Multimedia Message Service
SMS	Short Message Service

4 High level Requirements

The following list gives the high level requirements of the MMS. These are requirements which are independent of the user's perception of the service:

- **Forward compatible multimedia messaging**

Multimedia messaging mechanisms shall provide the capability to support current and evolving multimedia messaging by re-using existing standards as far as possible and proposing extensions (as necessary) to existing standards (i.e. the multimedia messaging service shall support the evolution of multimedia messaging technologies).

- **Consistent messaging**

Regardless of the message type / format, MMS shall be capable of supporting integration of all types of messaging (e.g. fax, SMS, Multimedia, voicemail, e-mail etc.) in a consistent manner.

- **Universal messaging access**

Within the capabilities of networks and terminals, the user shall be able to experience consistent access to the MMS regardless of the access point.

For example the user should be capable of accessing her multimedia messages through a number of different access points, which should include 3GPP systems, fixed networks, the Internet, etc.

- **Interoperability**

The MMS shall support a minimum set of functionality and message formats to ensure interoperability. (e.g. deletion of MM, identified standardised message notification, message media types and message content formats).

The MMS shall provide a minimum set of supported formats to ensure full interoperability between different terminals and networks from the very beginning of service provisioning (e.g. JPEG for pictures, MP3 for audio, MPEG for motion pictures, etc.).

The MMS shall support version management by indicating a version number in the MM for interoperability purpose.

- **The MMS shall comply with the Virtual Home Environment specified in 22.121[2]**

The non-real-time multimedia messaging service shall be supported using the standardised set of service capabilities features.

5 General Requirements

Network operators have many differing requirements, and MMS shall be supported in the network in a manner which allows network operators to consider different configurations depending on their network and commercial requirements. Thus, an identified set of functionalities and formats shall be standardised to ensure interoperability across networks and terminals to support MMS.

However, some network operators may wish to design and configure networks in different ways, and the subsequent requirements are identified to allow flexibility in how the MMS functionality is supported. For example in some networks the network operators may wish to implement the MMS functionality within the core network, whereas other may wish to place the MMS functionality on the periphery of the core network (e.g. a centralised network model instead of a distributed architecture). Further, some network operators may wish to support a limited set of MMS functionality, while others may require extensive and elaborate MMS support according to their business models (e.g. basic MMS instead of advanced MMS). Interoperability shall always be maintained within this flexible architecture.

The following sub-clauses use the term "*The MMS shall be able to support a request for ...*" and similar phrases to allow network operators to consider these different network models and business requirements, to permit flexible architectures and ensure MMS interoperability.

The following sub-clauses use the term "*This requirement shall be supported at the application layer in the terminal (and/or the network), and will not be further elaborated.*" and similar phrases to identify those service requirements that shall be supported by MMS but do not require standardisation.

The criterion for identifying these types of requirements is as follows:

If the requirement corresponds to an interaction and/or command between the terminal and the network applications from the same Service Provider (e.g. between the recipient's terminal resident messaging application and the recipient's network resident application. The same applies for the sender), then this requirement shall be supported by MMS but does not require standardisation.

The following general requirements shall be supported via the use of service capability features.

5.1 Multimedia message management

- **Terminal-sensitive MM management**

The MMS shall be able to support the capability for the terminal and network to take account of the capability of the user's terminal (e.g. deliver a MM / notification in a manner compatible with the terminals capability).

- **Terminal status-sensitive MM Management**

The MMS shall be able to support the capability of the network to take account of the availability, changes of the state of availability of the terminal (e.g. store messages if the recipient is not available).

- **MMS Control by the operator**

The MMS shall be able to support a request from the operator to enable/disable MM delivery and submission.

- **MMS Control by the user**

The MMS shall be able to support a request from the user to enable/disable MM delivery and submission.

This requirement shall be supported at the application layer in the terminal, and will not be further elaborated.

- **Storage of MMS parameters**

The (U)SIM shall be able to store the following types of MMS related data:

- i) a number of sets of issuer configuration information to allow access to MMS services.

At least one of these sets of configuration information should be stored on the (U)SIM by the issuer of the (U)SIM.

The first issuer configuration information set is denoted as the default configuration set.

This configuration information shall only be configurable by the issuer of the (U)SIM.

- ii) a number of sets of user configuration information to allow access to MMS services.

If more than one set of configuration information is present, it shall be possible for the user to select which set is used. If the user has not selected any of the configuration information sets, then the default set in the active (U)SIM is used.

- iii) MMS notifications

- iv) MMS user preferences

A terminal using a (U)SIM, should by default use the MMS parameters and the related preferred bearer stored in (U)SIM, to access to the MMS services.

- **Personalise multimedia messaging**

The MMS shall be able to support a request by the user to manage the Service Preferences of his User Service Profile related to this MMS [2](e.g. customise his MM environment within the capabilities of the terminal, network and MM application. This could be unconditional or conditional e.g. depending on roaming conditions or operator restrictions).

- **MM creation**

The MMS shall be able to support the request to create a MM by the user or an application.

This requirement shall be supported at the application layer in the terminal, and will not be further elaborated.

- **MM Time Stamping**

The MMS shall be able to support the request to include a reliable time value in an MM, a notification and an acknowledgement as appropriate.

- **Multiple Media**

Multimedia messages may be composed of either a single medium (e.g. voice) or multi-media (e.g. Voice and video). The MMS shall be able to support a request for media synchronisation / sequencing.

- **Media Type Conversion**

The MMS shall be able to support a request to convert between media types (e.g. Fax to image).

This requirement shall be supported at the application layer in the network, and will not be further elaborated.

- **Media Format Conversion**

The MMS shall be able to support a request by the user or the application to convert between MM media formats (e.g. JPEG to GIF).

This requirement shall be supported at the application layer in the terminal and/or in the network, and will not be further elaborated.

- **Message forwarding**

The MMS shall be able to support a request to forward multimedia messages or multimedia message elements without having to first download the MM to the terminal.

- **Storage of Multi-Media Messages**

The MMS shall be able to support a request for multimedia messages or message elements to be stored until delivered to the recipient's terminal, until they expire, or until they are deleted by the user (unless configured differently). The MMS shall be able to support a request to store and manage all MMs in a network based repository rather than on the mobile terminal.

This requirement shall be supported at the application layer in the network, and will not be further elaborated.

NOTE: There is no requirement for the MMS to be responsible for the processing/presentation of the MM message, after it has been delivered to the terminal.

- **Prioritisation of Messages**

The MMS shall be able to support a request for MM prioritisation subject to the capabilities of the network (e.g. the sender of the MM may request to prioritise the importance of the multimedia messages).

- **Message qualification**

The MMS shall be able to support a request for MM qualification (e.g. subject) for the purpose of advanced user experience and awareness.

- **Screening of Messages**

The MMS shall be able to support a request for MM screening subject to the capabilities of the network (e.g. automatically delete "junk mail", anonymous messages without delivery to the recipient's terminal).

This requirement shall be supported at the application layer in the terminal and/or in the network, and will not be further elaborated.

- **Validity Period**

The MMS shall be able to support a request by the originator of a message to define validity periods (earliest and latest desired time) for message delivery (e.g. if a message can not be delivered within a certain time it will be automatically deleted). The MMS service provider shall be able to set the MAXIMUM allowable validity period for any message.

5.2 Multimedia message delivery and submission

- **Submission mechanism**

The MMS shall support multimedia messages or messages elements to be submitted to the recipient's terminal.

- **Push Mechanism**

The MMS shall be able to support a request for multimedia messages or messages elements to be automatically delivered to the recipient's terminal.

- **Pull Mechanism**

The MMS shall be able to support a request for multimedia messages or messages elements to be delivered to the recipient's terminal on request by the recipient.

Editor's Note: push and pull delivery mechanisms could be identical; the criteria which decide on the type of mechanism (push / pull) are either described in the User Services Profile or out of the scope of this specification.

- **Concurrency**

The MMS shall be able to support MM delivery to and from the user's terminal not be restricted during other active services (subject to the capabilities of the terminal and the network).

- **Streaming**

The MMS shall be able to support streaming for MM delivery from the MMS system to the terminal.

Support for streaming for MM upload from the terminal to the MMS system will be considered for future releases.

- **Preferred Bearer**

It shall be possible to define a list of precedence for bearers in the configuration information sets for delivery and submission of MM (e.g. GPRS, CSD). By default, the terminal should support automatic bearer selection (i.e. without user intervention) based on the order of precedence defined in the configuration information sets on the (U)SIM.

The user shall be able to enable or disable automatic bearer selection. When disabled, manual bearer selection shall be available from the list of bearers.

5.3 Notification and Acknowledgement

The MMS shall be able to support a request to send generic notification and acknowledgement capability to inform the user in an appropriate manner of MMS events. Examples may include:

- notify the recipient about received messages (including a description of the message, e.g. content, size, type).
- notify the recipient about actions taken by the MMS, (e.g. due to profile settings like automatic MM forwarding, deletion, etc.).
- acknowledge the sender about successful or failed MM or storage of a MM.
- acknowledge the sender about successful or failed MM submission.
- acknowledge the sender about successful or failed MM delivery to the recipient terminal (subject to the recipient permitting such an acknowledgement).
- acknowledge the sender about the MM being read/handled at the recipient terminal (subject to the recipient permitting such an acknowledgement).
- acknowledge the sender about successful or failed MM deletion.
- acknowledge the sender, upon request, about the status of a submitted MM (i.e. delivered / not delivered).

5.4 Addressing

The MMS shall support different addressing formats to identify the sender and recipient as specified in 22.975 [4] where applicable. It shall be possible to submit one message to multiple recipients.

The MMS shall be able to support the request to hide the sender's address from the recipient.

6 User Profile

The MMS shall be able to support the ability to create, update, store, transfer, interrogate, manage and retrieve a user's multimedia messaging profiles.

The multimedia messaging profiles shall allow a user to configure and personalise his multimedia messaging environment with the multimedia messaging profiles (e.g. which media types and notifications that shall be delivered to the recipient, such as voice only or text only).

The multimedia messaging profiles shall form part of the user's virtual home environment.

7 Security

The user shall be able to use and access MM in a secure manner. It shall be possible for the contents of MMs to be read only by the intended recipient(s). A recipient shall be informed of the reliability of the identity of the sender in case the sender has authorised his identity to be transmitted.

The integrity of MMs during transit shall be assured to extent of the network capabilities.

The MMS shall be intrinsically resistant to attempts of malicious or fraudulent use.

The "Security Threats and Requirements" specified in 21.133 [3] shall not be compromised.

8 Charging

The MMS shall be able to support various charging mechanisms. The following charging characteristics may be considered:

- message types, length, storage time in the network, etc,
- delivering time, upload / download method,
- MM-sender / -recipient,
- number of messages sent,
- number of messages received,
- roaming conditions,
- location conditions,
- Indication of charging,

The MMS indicates to the recipient prior to the recipient downloading a multi media message whether the sender has paid or the recipient is expected to pay for the message.

- Prepaid subscriptions.

9 External Interface

External interfaces for controlling and delivering MM between the terminal and an external device e.g. portable computer should be supported.

10 Interworking

The standard shall permit interworking with other or existing messaging technologies, messaging services, intelligent network services and supplementary services, either located within or outside a mobile network.

11 Roaming

Roaming between network operators shall be supported.

Annex A (informative): Change history

Change history											
TSG SA#	SA Doc.	SA1 Doc	Spec	CR	Rev	Rel	Cat	Subject/Comment	Old	New	Work Item
SP_06	PP-99529		22.140	-		R99	-	Approved at SA#08 as version 3.0.0	2.0.0	3.0.0	
SP_08	SP-000214	S1-000347	22.140	001		R00	B	Introduction of streaming for MMS	3.0.0	4.0.0	
-	-	-	22.140	-		R00	-	Corrected implementation of CR001 by MCC, re-introducing the R00 text deleted by implementation of CR002 to R99 version (see SP-000208). Some editorial clean-up.	4.0.0	4.0.1	
SP-11	SP-010062	S1-010265	22.140	004		Rel-4	C	Alignment of Stage 1 MMS to Stage 2 MMS	4.0.1	4.1.0	MMS
SP-11	SP-010062	S1-010016	22.140	005		Rel-4	C	Support for Streaming in MMS	4.0.1	4.1.0	MMS
SP-11	SP-010062	S1-010014	22.140	006		Rel-4	F	MM Forwarding	4.0.1	4.1.0	MMS
SP-11	SP-010062	S1-010015	22.140	007		Rel-4	B	New features in MMS R'4	4.0.1	4.1.0	MMS
SP-15	SP-020045	S1-020457	22.140	011	-	Rel-4	F	Editorial CR to correct terms and references	4.1.0	4.2.0	CORRECT
SP-18	SP-020843	S1-022386	22.140	018	2	Rel-4	F	Storage of configuration information on the (U)SIM - for Rel 4	4.2.0	4.3.0	MMS

History

Document history		
V4.1.0	March 2001	Publication
V4.2.0	March 2002	Publication
V4.3.0	December 2002	Publication