

# ETSI TS 123 003 V13.5.0 (2016-04)



**Digital cellular telecommunications system (Phase 2+) (GSM);  
Universal Mobile Telecommunications System (UMTS);  
Numbering, addressing and identification  
(3GPP TS 23.003 version 13.5.0 Release 13)**



---

Reference

RTS/TSGC-0423003vd50

---

Keywords

GSM,UMTS

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:  
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at  
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:  
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2016.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.  
**3GPP™** and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.  
**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

## Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	9
1 Scope .....	10
1.1 References .....	10
1.1.1 Normative references.....	10
1.1.2 Informative references .....	14
1.2 Abbreviations .....	14
1.3 General comments to references .....	15
1.4 Conventions on bit ordering .....	15
2 Identification of mobile subscribers .....	15
2.1 General .....	15
2.2 Composition of IMSI.....	15
2.3 Allocation principles .....	16
2.4 Structure of TMSI .....	16
2.5 Structure of LMSI .....	17
2.6 Structure of TLLI .....	17
2.7 Structure of P-TMSI Signature.....	18
2.8 Globally Unique Temporary UE Identity (GUTI).....	18
2.8.1 Introduction.....	18
2.8.2 Mapping between Temporary and Area Identities for the EUTRAN and the UTRAN/GERAN based systems.....	19
2.8.2.0 Introduction.....	19
2.8.2.1 Mapping from GUTI to RAI, P-TMSI and P-TMSI signature.....	19
2.8.2.1.1 Introduction .....	19
2.8.2.1.2 Mapping in the UE .....	19
2.8.2.1.3 Mapping in the old MME .....	20
2.8.2.2 Mapping from RAI and P-TMSI to GUTI .....	20
2.8.2.2.1 Introduction .....	20
2.8.2.2.2 Mapping in the UE .....	20
2.8.2.2.3 Mapping in the new MME.....	21
2.9 Structure of the S-Temporary Mobile Subscriber Identity (S-TMSI) .....	21
3 Numbering plan for mobile stations .....	21
3.1 General .....	21
3.2 Numbering plan requirements .....	22
3.3 Structure of MS international PSTN/ISDN number (MSISDN) .....	22
3.4 Mobile Station Roaming Number (MSRN) for PSTN/ISDN routing.....	23
3.5 Structure of Mobile Station International Data Number .....	23
3.6 Handover Number .....	23
3.7 Structure of an IP v4 address.....	23
3.8 Structure of an IP v6 address.....	24
4 Identification of location areas and base stations .....	24
4.1 Composition of the Location Area Identification (LAI).....	24
4.2 Composition of the Routing Area Identification (RAI).....	24
4.3 Base station identification .....	25
4.3.1 Cell Identity (CI) and Cell Global Identification (CGI).....	25
4.3.2 Base Station Identify Code (BSIC).....	25
4.4 Regional Subscription Zone Identity (RSZI).....	26
4.5 Location Number.....	26
4.6 Composition of the Service Area Identification (SAI) .....	27
4.7 Closed Subscriber Group.....	27
4.8 HNB Name .....	27

4.9	CSG Type .....	27
4.10	HNB Unique Identity .....	27
5	Identification of MSCs, GSNs, location registers and CSSs .....	27
5.1	Identification for routing purposes .....	27
5.2	Identification of HLR for HLR restoration application .....	28
5.3	Identification of the HSS for SMS .....	28
6	International Mobile Station Equipment Identity and Software Version Number .....	28
6.1	General .....	28
6.2	Composition of IMEI and IMEISV .....	29
6.2.1	Composition of IMEI .....	29
6.2.2	Composition of IMEISV .....	29
6.3	Allocation principles .....	30
7	Identification of Voice Group Call and Voice Broadcast Call Entities .....	30
7.1	Group Identities .....	30
7.2	Group Call Area Identification .....	30
7.3	Voice Group Call and Voice Broadcast Call References .....	31
8	SCCP subsystem numbers .....	31
8.1	Globally standardized subsystem numbers used for GSM/UMTS .....	31
8.2	National network subsystem numbers used for GSM/UMTS .....	31
9	Definition of Access Point Name .....	32
9.0	General .....	32
9.1	Structure of APN .....	32
9.1.1	Format of APN Network Identifier .....	33
9.1.2	Format of APN Operator Identifier .....	33
9.2	Definition of the Wild Card APN .....	34
9.2.1	Coding of the Wild Card APN .....	34
9.3	Definition of Emergency APN .....	34
10	Identification of the Cordless Telephony System entities .....	34
10.1	General description of CTS-MS and CTS-FP Identities .....	34
10.2	CTS Mobile Subscriber Identities .....	34
10.2.1	General .....	34
10.2.2	Composition of the CTSM SI .....	35
10.2.3	Allocation principles .....	35
10.2.4	CTSM SI hexadecimal representation .....	35
10.3	Fixed Part Beacon Identity .....	35
10.3.1	General .....	35
10.3.2	Composition of the FPBI .....	36
10.3.2.1	FPBI general structure .....	36
10.3.2.2	FPBI class A .....	36
10.3.2.3	FPBI class B .....	36
10.3.3	Allocation principles .....	37
10.4	International Fixed Part Equipment Identity .....	37
10.4.1	General .....	37
10.4.2	Composition of the IFPEI .....	37
10.4.3	Allocation principles .....	38
10.5	International Fixed Part Subscription Identity .....	38
10.5.1	General .....	38
10.5.2	Composition of the IFPSI .....	38
10.5.3	Allocation principles .....	38
11	Identification of Localised Service Area .....	39
12	Identification of PLMN, RNC, Service Area, CN domain and Shared Network Area .....	39
12.1	PLMN Identifier .....	39
12.2	CN Domain Identifier .....	39
12.3	CN Identifier .....	40
12.4	RNC Identifier .....	40
12.5	Service Area Identifier .....	40
12.6	Shared Network Area Identifier .....	40

13	.....	Numbering, addressing and identification within the IP multimedia core network subsystem	41
13.1		Introduction .....	41
13.2		Home network domain name.....	41
13.3		Private User Identity.....	41
13.4		Public User Identity.....	42
13.4A		Wildcarded Public User Identity .....	42
13.4B		Temporary Public User Identity .....	43
13.5		Public Service Identity (PSI).....	43
13.5A		Private Service Identity .....	44
13.6		Anonymous User Identity .....	44
13.7		Unavailable User Identity.....	44
13.8		Instance-ID.....	44
13.9		XCAP Root URI.....	44
13.9.1		XCAP Root URI on Ut interface .....	44
13.9.1.1		General.....	44
13.9.1.2		Format of XCAP Root URI.....	45
13.10		Default Conference Factory URI for MMTel.....	45
14		Numbering, addressing and identification for 3GPP System to WLAN Interworking .....	46
14.1		Introduction .....	46
14.2		Home network realm .....	46
14.3		Root NAI.....	46
14.4		Decorated NAI .....	47
14.4A		Fast Re-authentication NAI .....	47
14.5		Temporary identities.....	48
14.6		Alternative NAI.....	48
14.7		W-APN.....	48
14.7.1		Format of W-APN Network Identifier.....	49
14.7.2		Format of W-APN Operator Identifier.....	49
14.7.3		Alternative Format of W-APN Operator Identifier.....	50
14.8		Emergency Realm and Emergency NAI for Emergency Cases.....	50
15		Identification of Multimedia Broadcast/Multicast Service .....	51
15.1		Introduction .....	51
15.2		Structure of TMGI.....	51
15.3		Structure of MBMS SAI.....	52
15.4		Home Network Realm.....	52
15.5		Addressing and identification for Bootstrapping MBMS Service Announcement.....	52
16		Numbering, addressing and identification within the GAA subsystem .....	53
16.1		Introduction .....	53
16.2		BSF address.....	53
17		Numbering, addressing and identification within the Generic Access Network.....	54
17.1		Introduction .....	54
17.2		Network Access Identifiers .....	54
17.2.1		Home network realm .....	54
17.2.2		Full Authentication NAI .....	55
17.2.3		Fast Re-authentication NAI .....	55
17.3		Node Identifiers.....	55
17.3.1		Home network domain name.....	55
17.3.2		Provisioning GANC-SEGW identifier.....	56
17.3.3		Provisioning GANC identifier .....	56
18		Addressing and Identification for IMS Service Continuity and Single-Radio Voice Call Continuity.....	57
18.1		Introduction .....	57
18.2		CS Domain Routeing Number (CSRN).....	57
18.3		IP Multimedia Routeing Number (IMRN).....	57
18.4		Session Transfer Number (STN).....	57
18.5		Session Transfer Identifier (STI).....	58
18.6		Session Transfer Number for Single Radio Voice Call Continuity (STN-SR).....	58
18.7		Correlation MSISDN.....	58

18.8	Transfer Identifier for CS to PS Single Radio Voice Call Continuity (STI-rSR).....	58
18.9	Additional MSISDN.....	58
19	Numbering, addressing and identification for the Evolved Packet Core (EPC).....	58
19.1	Introduction .....	58
19.2	Home Network Realm/Domain .....	59
19.3	3GPP access to non-3GPP access interworking .....	59
19.3.1	Introduction.....	59
19.3.2	Root NAI .....	59
19.3.3	Decorated NAI.....	60
19.3.4	Fast Re-authentication NAI .....	61
19.3.5	Pseudonym Identities.....	62
19.3.6	Emergency NAI for Limited Service State .....	62
19.3.7	Alternative NAI .....	63
19.4	Identifiers for Domain Name System procedures .....	63
19.4.1	Introduction.....	63
19.4.2	Fully Qualified Domain Names (FQDNs) .....	64
19.4.2.1	General .....	64
19.4.2.2	Access Point Name FQDN (APN-FQDN) .....	64
19.4.2.2.1	Structure .....	64
19.4.2.2.2	Void .....	64
19.4.2.2.3	Void .....	64
19.4.2.2.4	Void .....	64
19.4.2.3	Tracking Area Identity (TAI) .....	64
19.4.2.4	Mobility Management Entity (MME) .....	65
19.4.2.5	Routing Area Identity (RAI) - EPC.....	66
19.4.2.6	Serving GPRS Support Node (SGSN) within SGSN pool.....	66
19.4.2.7	Target RNC-ID for U-TRAN .....	66
19.4.2.8	DNS subdomain for operator usage in EPC .....	67
19.4.2.9	ePDG FQDN and Visited Country FQDN for non-emergency bearer services .....	67
19.4.2.9.1	General .....	67
19.4.2.9.2	Operator Identifier based ePDG FQDN .....	67
19.4.2.9.3	Tracking/Location Area Identity based ePDG FQDN.....	68
19.4.2.9.4	Visited Country FQDN.....	68
19.4.2.9A	ePDG FQDN for emergency bearer services .....	69
19.4.2.9A.1	General .....	69
19.4.2.9A.2	ePDG FQDN for dynamic selection of an ePDG supporting emergency bearer services .....	69
19.4.2.10	Global eNodeB-ID for eNodeB.....	69
19.4.2.11	Local Home Network identifier .....	69
19.4.3	Service and Protocol service names for 3GPP.....	70
19.5	Access Network Identity .....	71
19.6	E-UTRAN Cell Identity (ECI) and E-UTRAN Cell Global Identification (ECGI).....	71
19.7	Identifiers for communications with packet data networks and applications .....	71
19.7.1	Introduction.....	71
19.7.2	External Identifier .....	71
19.8	TWAN Operator Name .....	72
19.9	IMSI-Group Identifier .....	72
19.10	Presence Reporting Area Identifier (PRA ID).....	73
20	Addressing and Identification for IMS Centralized Services.....	73
20.1	Introduction .....	73
20.2	UE based solution.....	73
20.3	Network based solution .....	73
20.3.1	General.....	73
20.3.2	Home network domain name .....	74
20.3.3	Private User Identity .....	74
20.3.4	Public User Identity .....	74
20.3.5	Conference Factory URI.....	75
21	Addressing and Identification for Dual Stack Mobile IPv6 (DSMIPv6) .....	75
21.1	Introduction .....	75
21.2	Home Agent – Access Point Name (HA-APN).....	75
21.2.1	General .....	75

21.2.2	Format of HA-APN Network Identifier.....	75
21.2.3	Format of HA-APN Operator Identifier.....	76
22	Addressing and identification for ANDSF.....	76
22.1	Introduction.....	76
22.2	ANDSF Server Name (ANDSF-SN).....	76
22.2.1	General.....	76
22.2.2	Format of ANDSF-SN.....	76
23	Numbering, addressing and identification for the OAM System.....	77
23.1	Introduction.....	77
23.2	OAM System Realm/Domain.....	77
23.3	Identifiers for Domain Name System procedures.....	78
23.3.1	Introduction.....	78
23.3.2	Fully Qualified Domain Names (FQDNs).....	78
23.3.2.1	General.....	78
23.3.2.2	Relay Node Vendor-Specific OAM System.....	78
23.3.2.3	Multi-vendor eNodeB Plug-and Play Vendor-Specific OAM System.....	78
23.3.2.3.1	General.....	78
23.3.2.3.2	Certification Authority server.....	79
23.3.2.3.3	Security Gateway.....	79
23.3.2.3.4	Element Manager.....	79
24	Numbering, addressing and identification for Proximity-based Services (ProSe).....	80
24.1	Introduction.....	80
24.2	ProSe Application ID.....	80
24.2.1	General.....	80
24.2.2	Format of ProSe Application ID Name in ProSe Application ID.....	80
24.2.3	Format of PLMN ID in ProSe Application ID.....	81
24.2.4	Usage of wild cards in place of PLMN ID in ProSe Application ID.....	81
24.2.5	Informative examples of ProSe Application ID.....	81
24.3	ProSe Application Code.....	82
24.3.1	General.....	82
24.3.2	Format of PLMN ID in ProSe Application Code.....	82
24.3.3	Format of temporary identity in ProSe Application Code.....	83
24.3A	ProSe Application Code Prefix.....	83
24.3B	ProSe Application Code Suffix.....	83
24.4	EPC ProSe User ID.....	83
24.4.1	General.....	83
24.4.2	Format of EPC ProSe User ID.....	83
24.5	Home PLMN ProSe Function Address.....	83
24.6	ProSe Restricted Code.....	84
24.7	ProSe Restricted Code Prefix.....	84
24.8	ProSe Restricted Code Suffix.....	84
24.9	ProSe Query Code.....	84
24.10	ProSe Response Code.....	84
24.11	ProSe Discovery UE ID.....	85
24.11.1	General.....	85
24.11.2	Format of ProSe Discovery UE ID.....	85
24.12	ProSe UE ID.....	85
24.13	ProSe Relay UE ID.....	85
24.14	User Info ID.....	85
24.15	Relay Service Code.....	85
24.16	Discovery Group ID.....	86
25	Identification of Online Charging System.....	86
25.1	Introduction.....	86
25.2	Home network domain name.....	86
<b>Annex A (informative): Colour Codes.....</b>		<b>87</b>
A.1	Utilization of the BSIC.....	87
A.2	Guidance for planning.....	87



A.3	Example of PLMN Colour Codes (NCCs) for the European region.....	88
<b>Annex B (normative):</b>	<b>IMEI Check Digit computation.....</b>	<b>89</b>
B.1	Representation of IMEI.....	89
B.2	Computation of CD for an IMEI.....	89
B.3	Example of computation .....	89
<b>Annex C (normative):</b>	<b>Naming convention .....</b>	<b>91</b>
C.1	Routing Area Identities .....	91
C.2	GPRS Support Nodes .....	92
C.3	Target ID .....	92
<b>Annex D (informative):</b>	<b>Applicability and use of the ".3gppnetwork.org" domain name.....</b>	<b>93</b>
<b>Annex E (normative):</b>	<b>Procedure for sub-domain allocation.....</b>	<b>94</b>
<b>Annex F (informative):</b>	<b>Change history .....</b>	<b>96</b>
History .....		101

---

# Foreword

This Technical Specification (TS) has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The present document defines the principal purpose and use of International Mobile station Equipment Identities (IMEI) within the digital cellular telecommunications system and the 3GPP system.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The present document defines the principal purpose and use of International Mobile station Equipment Identities (IMEI) within the digital cellular telecommunications system and the 3GPP system.

The present document defines:

- a) an identification plan for mobile subscribers in the GSM system;
- b) principles of assigning telephone and ISDN numbers to MSs in the country of registration of the MS;
- c) principles of assigning Mobile Station (MS) roaming numbers to visiting MSs;
- d) an identification plan for location areas, routing areas, and base stations in the GSM system;
- e) an identification plan for MSCs, SGSNs, GGSNs, and location registers in the GSM system;
- f) principles of assigning international mobile equipment identities;
- g) principles of assigning zones for regional subscription;
- h) an identification plan for groups of subscribers to the Voice Group Call Service (VGCS) and to the Voice Broadcast Service (VBS); and identification plan for voice group calls and voice broadcast calls; an identification plan for group call areas;
- i) principles for assigning Packet Data Protocol (PDP) addresses to mobile stations;
- j) an identification plan for point-to-multipoint data transmission groups;
- k) an identification plan for CN domain, RNC and service area in the UTRAN system.
- l) an identification plan for mobile subscribers in the WLAN system.
- m) addressing and identification for IMS Service Continuity
- n) an identification plan together with principles of assignment and mapping of identities for the Evolved Packet System; and
- o) addressing and identification for Proximity-based (ProSe) Services.
- p) an identification for Online Charging System (OCS).

The present document specifies functions, procedures and information which apply to GERAN Iu mode. However, functionality related to GERAN Iu mode is neither maintained nor enhanced.

## 1.1 References

### 1.1.1 Normative references

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

[1] 3GPP TS 21.905: "Vocabulary for 3GPP Specifications".

- [2] 3GPP TS 23.008: "Organization of subscriber data".
- [3] 3GPP TS 23.060: "General Packet Radio Service (GPRS); Service description; Stage 2"
- [4] 3GPP TS 23.070: "Routeing of calls to/from Public Data Networks (PDN)".
- [5] 3GPP TS 24.008: "Mobile Radio Interface Layer 3 specification; Core Network Protocols; Stage 3".
- [6] 3GPP TS 29.060: "GPRS Tunnelling protocol (GTP) across the Gn and Gp interface".
- [7] 3GPP TS 43.020: "Digital cellular telecommunications system (Phase 2+); Security related network functions".
- [8] void
- [9] 3GPP TS 51.011: " Specification of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface".
- [10] ITU-T Recommendation E.164: "The international public telecommunication numbering plan".
- [11] ITU-T Recommendation E.212: "The international identification plan for mobile terminals and mobile users".
- [12] ITU-T Recommendation E.213: "Telephone and ISDN numbering plan for land Mobile Stations in public land mobile networks (PLMN)".
- [13] ITU-T Recommendation X.121: "International numbering plan for public data networks".
- [14] IETF RFC 791: "Internet Protocol".
- [15] IETF RFC 2373: "IP Version 6 Addressing Architecture".
- [16] 3GPP TS 25.401: "UTRAN Overall Description".
- [17] 3GPP TS 25.413: "UTRAN Iu Interface RANAP Signalling".
- [18] IETF RFC 2181: "Clarifications to the DNS Specification".
- [19] IETF RFC 1035: "Domain Names - Implementation and Specification".
- [20] IETF RFC 1123: "Requirements for Internet Hosts -- Application and Support".
- [21] IETF RFC 2462: "IPv6 Stateless Address Autoconfiguration".
- [22] IETF RFC 3041: "Privacy Extensions for Stateless Address Autoconfiguration in IPv6".
- [23] 3GPP TS 23.236: "Intra Domain Connection of RAN Nodes to Multiple CN Nodes".
- [24] 3GPP TS 23.228: "IP Multimedia (IM) Subsystem – Stage 2"
- [25] Void
- [26] IETF RFC 3261: "SIP: Session Initiation Protocol"
- [27] 3GPP TS 31.102: "Characteristics of the USIM Application."
- [28] Void
- [29] 3GPP TS 44.118: "Radio Resource Control (RRC) Protocol, Iu Mode".
- [30] 3GPP TS 23.073: "Support of Localised Service Area (SoLSA); Stage 2"
- [31] 3GPP TS 29.002: "Mobile Application Part (MAP) specification"
- [32] 3GPP TS 22.016: "International Mobile Equipment Identities (IMEI)"
- [33] Void

- [34] Void
- [35] 3GPP TS 45.056: "CTS-FP Radio Sub-system"
- [36] 3GPP TS 42.009: "Security aspects" [currently not being raised to rel-5 – Pete H. looking into it]
- [37] 3GPP TS 25.423: "UTRAN Iur interface RNSAP signalling"
- [38] 3GPP TS 25.419: "UTRAN Iu-BC interface: Service Area Broadcast Protocol (SABP)"
- [39] 3GPP TS 25.410: "UTRAN Iu Interface: General Aspects and Principles"
- [40] ISO/IEC 7812: "Identification cards - Numbering system and registration procedure for issuer identifiers"
- [41] Void
- [42] 3GPP TS 33.102 "3G security; Security architecture"
- [43] 3GPP TS 43.130: "Iur-g interface; Stage 2"
- [45] IETF RFC 3966: "The tel URI for Telephone Numbers"
- [46] 3GPP TS 44.068: "Group Call Control (GCC) protocol".
- [47] 3GPP TS 44.069: "Broadcast Call Control (BCC) Protocol".
- [48] 3GPP TS 24.234: "3GPP System to WLAN Interworking; UE to Network protocols; Stage 3".
- [49] Void
- [50] IETF RFC 4187: "EAP AKA Authentication".
- [51] IETF RFC 4186: "EAP SIM Authentication".
- [52] 3GPP TS 23.246: "Multimedia Broadcast/Multicast Service (MBMS); Architecture and functional description"
- [53] IETF RFC 4282: "The Network Access Identifier".
- [54] IETF RFC 2279: "UTF-8, a transformation format of ISO 10646".
- [55] 3GPP TS 33.234: "Wireless Local Area Network (WLAN) interworking security".
- [56] Void
- [58] 3GPP TS 33.221 "Generic Authentication Architecture (GAA); Support for Subscriber Certificates".
- [60] IEEE 1003.1-2004, Part 1: Base Definitions
- [61] 3GPP TS 43.318: "Generic Access to the A/Gb interface; Stage 2"
- [62] 3GPP TS 44.318: "Generic Access (GA) to the A/Gb interface; Mobile GA interface layer 3 specification"
- [63] 3GPP TS 29.163: "Interworking between the IP Multimedia (IM) Core Network (CN) subsystem and Circuit Switched (CS) networks"
- [64] IETF RFC 2606: "Reserved Top Level DNS Names"
- [65] Void
- [66] 3GPP TS 51.011 Release 4: "Specification of the Subscriber Identity Module - Mobile Equipment (SIM - ME) interface"
- [67] 3GPP2 X.S0013-004: "IP Multimedia Call Control Protocol based on SIP and SDP; Stage 3"

- [68] 3GPP TS 23.402: "Architecture Enhancements for non-3GPP accesses"
- [69] 3GPP TS 33.402: "3GPP System Architecture Evolution: Security Aspects of non-3GPP accesses"
- [70] 3GPP TS 23.292: "IP Multimedia Subsystem (IMS) Centralized Services; Stage 2"
- [71] 3GPP TS 23.237: "IP Multimedia Subsystem (IMS) Service Continuity"
- [72] 3GPP TS 23.401: "General Packet Radio Service (GPRS) enhancements for Evolved Universal Terrestrial Radio Access Network (E-UTRAN) access"
- [73] 3GPP TS 29.303: "Domain Name System Procedures; Stage 3"
- [74] IETF RFC 3958: "Domain-Based Application Service Location Using SRV RRs and the Dynamic Delegation Discovery Service (DDDS)"
- [75] Void
- [76] 3GPP TS 23.237: "Mobility between 3GPP-Wireless Local Area Network (WLAN) interworking and 3GPP systems"
- [77] 3GPP TS 24.302: "Access to the 3GPP Evolved Packet Core (EPC) via non-3GPP access networks; Stage 3"
- [78] 3GPP TS 23.273: "Evolved Packet System; 3GPP EPS AAA Interfaces"
- [79] IETF RFC 7254: "A Uniform Resource Name Namespace for the Global System for Mobile Communications Association (GSMA) and the International Mobile station Equipment Identity (IMEI)".
- [80] IETF RFC 4122: "A Universally Unique Identifier (UUID) URN Namespace".
- [81] 3GPP TS 24.229: "IP multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".
- [82] IETF RFC5448: "Improved Extensible Authentication Protocol Method for 3rd Generation Authentication and Key Agreement (EAP-AKA) "
- [83] 3GPP TS 22.011: "Service accessibility".
- [84] 3GPP TS 36.413: "Evolved Universal Terrestrial Radio Access Network (E-UTRAN) ; S1 Application Protocol (S1AP)".
- [85] Guidelines for use of a 48-bit Extended Unique Identifier (EUI-48™), <http://standards.ieee.org/regauth/oui/tutorials/EUI48.html>
- [86] GUIDELINES FOR 64-BIT GLOBAL IDENTIFIER (EUI-64) REGISTRATION AUTHORITY, <http://standards.ieee.org/regauth/oui/tutorials/EUI64.html>
- [87] The Broadband Forum TR-069: "CPE WAN Management Protocol v1.1", Issue 1 Amendment 2, December 2007
- [88] 3GPP TS 29.274: "Evolved General Packet Radio Service (GPRS) Tunnelling Protocol for Control plane (GTPv2-C); Stage 3".
- [89] 3GPP TS 33.401: "3GPP System Architecture Evolution: Security Architecture".
- [90] 3GPP TS 24.301: "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3".
- [91] 3GPP TS 36.300: " Evolved Universal Terrestrial Radio Access (E-UTRA) and Evolved Universal Terrestrial Radio Access Network (E-UTRAN); Overall description; Stage 2".
- [92] 3GPP TS 23.216: "Single Radio Voice Call Continuity (SRVCC)".
- [93] 3GPP TS 31.103: "IP Multimedia Services Identity Module (ISIM) application".

- [94] IETF RFC 4825: "The Extensible Markup Language (XML) Configuration Access Protocol (XCAP)".
- [95] 3GPP TS 29.229: "Cx and Dx interfaces based on the Diameter protocol; Protocol details".
- [96] 3GPP TS 29.329: "Sh Interface based on the Diameter protocol; Protocol details".
- [97] 3GPP TS 29.165: "Inter-IMS Network to Network Interface (NNI); Stage 3".
- [98] 3GPP TS 23.682: "Architecture Enhancements to facilitate communications with Packet Data Networks and Applications".
- [99] 3GPP TS 44.018: "Mobile radio interface layer 3 specification; Radio Resource Control (RRC) protocol".
- [100] 3GPP TS 44.060: "General Packet Radio Service (GPRS); Mobile Station (MS) – Base Station System (BSS) interface; Radio Link Control / Medium Access Control (RLC/MAC) protocol".
- [101] 3GPP TS 23.251: "Network Sharing; Architecture and functional description".
- [102] 3GPP TS 32.508: "Procedure flows for multi-vendor plug-and-play eNB connection to the network".
- [103] 3GPP TS 23.303: "Proximity-based services (ProSe)".
- [104] IETF RFC 7255: "Using the International Mobile station Equipment Identity (IMEI) Uniform Resource Name (URN) as an Instance ID".
- [105] 3GPP TS 26.346: "Multimedia Broadcast/Multicast Service (MBMS); Protocols and codecs".
- [106] 3GPP TS 29.212: "Policy and Charging Control (PCC); Reference points".
- [107] 3GPP TS 23.203: "Policy and charging control architecture".
- [108] 3GPP TS 29.272: "Evolved Packet System (EPS); Mobility Management Entity (MME) and Serving GPRS Support Node (SGSN) related interfaces based on Diameter protocol".

### 1.1.2 Informative references

- [44] "COMPLEMENT TO ITU-T RECOMMENDATION E.212 (11/98)", Annex to ITU Operational Bulletin No. 741 – 1.VI.200; This is published on the ITU-T website, whose home page is at <http://www.itu.int/ITU-T/>
- [57] GSMA PRD IR.34 "Inter-PLMN Backbone Guidelines"
- [59] Void
- [109] GSMA TS.06 "IMEI Allocation and Approval Process"  
<http://www.gsma.com/newsroom/gsmadocuments/>

## 1.2 Abbreviations

For the purposes of the present document, the abbreviations defined in 3GPP TS 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

EPS	Evolved Packet System
GUTI	Globally Unique Temporary UE Identity
ICS	IMS Centralized Services
MTC	Machine Type Communication
OCS	Online Charging System
UUID	Universally Unique Identifier

## 1.3 General comments to references

The identification plan for mobile subscribers defined below is that defined in ITU-T Recommendation E.212.

The ISDN numbering plan for MSs and the allocation of mobile station roaming numbers is that defined in ITU-T Recommendation E.213. Only one of the principles for allocating ISDN numbers is proposed for PLMNs. Only the method for allocating MS roaming numbers contained in the main text of ITU-T Recommendation E.213 is recommended for use in PLMNs. If there is any difference between the present document and the ITU-T Recommendations, the former shall prevail.

For terminology, see also ITU-T Recommendations E.164 and X.121.

## 1.4 Conventions on bit ordering

The following conventions hold for the coding of the different identities appearing in the present document and in other GSM Technical Specifications if not indicated otherwise:

- the different parts of an identity are shown in the figures in order of significance;
- the most significant part of an identity is on the left part of the figure and the least significant on the right.

When an identity appears in other Technical Specifications, the following conventions hold if not indicated otherwise:

- digits are numbered by order of significance, with digit 1 being the most significant;
- bits are numbered by order of significance, with the lowest bit number corresponding to the least significant bit.

---

# 2 Identification of mobile subscribers

## 2.1 General

A unique International Mobile Subscriber Identity (IMSI) shall be allocated to each mobile subscriber in the GSM/UMTS/EPS system.

**NOTE:** This IMSI is the concept referred to by ITU-T as "International Mobile Station Identity".

In order to support the subscriber identity confidentiality service the VLRs, SGSNs and MME may allocate Temporary Mobile Subscriber Identities (TMSI) to visiting mobile subscribers. The VLR,SGSN and MME must be capable of correlating an allocated TMSI with the IMSI of the MS to which it is allocated.

An MS may be allocated three TMSIs, one for services provided through the MSC, one for services provided through the SGSN (P-TMSI for short) and one for the services provided via the MME (M-TMSI part GUTI for short).

For addressing on resources used for GPRS, a Temporary Logical Link Identity (TLLI) is used. The TLLI to use is built by the MS either on the basis of the P-TMSI (local or foreign TLLI), or directly (random TLLI).


In order to speed up the search for subscriber data in the VLR a supplementary Local Mobile Station Identity (LMSI) is defined.

The LMSI may be allocated by the VLR at location updating and is sent to the HLR together with the IMSI. The HLR makes no use of it but includes it together with the IMSI in all messages sent to the VLR concerning that MS.

## 2.2 Composition of IMSI

IMSI is composed as shown in figure 1.





**Figure 1: Structure of IMSI**

IMSI is composed of three parts:

- 1) Mobile Country Code (MCC) consisting of three digits. The MCC identifies uniquely the country of domicile of the mobile subscriber;
- 2) Mobile Network Code (MNC) consisting of two or three digits for GSM/UMTS applications. The MNC identifies the home PLMN of the mobile subscriber. The length of the MNC (two or three digits) depends on the value of the MCC. A mixture of two and three digit MNC codes within a single MCC area is not recommended and is outside the scope of this specification.
- 3) Mobile Subscriber Identification Number (MSIN) identifying the mobile subscriber within a PLMN.

The National Mobile Subscriber Identity (NMSI) consists of the Mobile Network Code and the Mobile Subscriber Identification Number.

## 2.3 Allocation principles

IMSI shall consist of decimal digits (0 through 9) only.

The number of digits in IMSI shall not exceed 15.

The allocation of Mobile Country Codes (MCCs) is administered by the ITU-T. The current allocation is given in the COMPLEMENT TO ITU-T RECOMMENDATION E.212 [44].

The allocation of National Mobile Subscriber Identity (NMSI) is the responsibility of each administration.

If more than one PLMN exists in a country, the same Mobile Network Code should not be assigned to more than one PLMN.

The allocation of IMSIs should be such that not more than the digits MCC + MNC of the IMSI have to be analysed in a foreign PLMN for information transfer.

## 2.4 Structure of TMSI

Since the TMSI has only local significance (i.e. within a VLR and the area controlled by a VLR, or within an SGSN and the area controlled by an SGSN, or within an MME and the area controlled by an MME), the structure and coding of it can be chosen by agreement between operator and manufacturer in order to meet local needs.

The TMSI consists of 4 octets. It can be coded using a full hexadecimal representation.

In order to avoid double allocation of TMSIs after a restart of an allocating node, some part of the TMSI may be related to the time when it was allocated or contain a bit field which is changed when the allocating node has recovered from the restart.

In areas where both MSC-based services and SGSN-based services are provided, some discrimination is needed between the allocation of TMSIs for MSC-based services and the allocation of TMSIs for SGSN-based services. The discrimination shall be done on the 2 most significant bits, with values 00, 01, and 10 being used by the VLR, and 11 being used by the SGSN.

If intra domain connection of RAN nodes to multiple CN nodes as described in 3GPP TS 23.236 [23] is applied in the MSC/VLR or SGSN, then the NRI shall be part of the TMSI. The NRI has a configurable length of 0 to 10 bits. A configurable length of 0 bits indicates that the NRI is not used and this feature is not applied in the MSC/VLR or SGSN. The NRI shall be coded in bits 23 to 14. An NRI shorter than 10 bits shall be encoded with the most significant bit of the NRI field in bit 23.

The TMSI shall be allocated only in ciphered form. See also 3GPP TS 43.020 [7] and 3GPP TS 33.102 [42].

The network shall not allocate a TMSI with all 32 bits equal to 1 (this is because the TMSI must be stored in the SIM, and the SIM uses 4 octets with all bits equal to 1 to indicate that no valid TMSI is available).

To allow for eventual modifications of the management of the TMSI code space management, MSs shall not check if an allocated TMSI belongs to the range allocated to the allocating node. MSs shall use an allocated TMSI according to the specifications, whatever its value.

## 2.5 Structure of LMSI

The LMSI consists of 4 octets and may be allocated by the VLR. The VLR shall not allocate the value zero. The value zero is reserved to indicate that an LMSI parameter sent from the HLR to the VLR shall not be interpreted.

## 2.6 Structure of TLLI

A TLLI is built by the MS or by the SGSN either on the basis of the P-TMSI (local or foreign TLLI), or directly (random or auxiliary TLLI), according to the following rules.

The TLLI consists of 32 bits, numbered from 0 to 31 by order of significance, with bit 0 being the LSB.

A local TLLI is built by an MS which has a valid P-TMSI as follows:

- bits 31 down to 30 are set to 1; and
- bits 29 down to 0 are set equal to bits 29 to 0 of the P-TMSI.

A foreign TLLI is built by an MS which has a valid P-TMSI as follows:

- bit 31 is set to 1 and bit 30 is set to 0; and
- bits 29 down to 0 are set equal to bits 29 to 0 of the P-TMSI.

A random TLLI is built by an MS as follows:

- bit 31 is set to 0;
- bits 30 down to 27 are set to 1; and
- bits 0 to 26 are chosen randomly.

An auxiliary TLLI is built by the SGSN as follows:

- bit 31 is set to 0;
- bits 30 down to 28 are set to 1;
- bit 27 is set to 0; and
- bits 0 to 26 can be assigned independently.

Other types of TLLI may be introduced in the future.

Part of the TLLI codespace is re-used in GERAN to allow for the inclusion of the GERAN Radio Network Temporary Identifier in RLC/MAC messages. The G-RNTI is defined in 3GPP TS 44.118 [29].

The structure of the TLLI is summarised in table 1.

Table 1: TLLI structure

31	30	29	28	27	26 to 0	Type of TLLI
1	1	T	T	T	T	Local TLLI
1	0	T	T	T	T	Foreign TLLI
0	1	1	1	1	R	Random TLLI
0	1	1	1	0	A	Auxiliary TLLI
0	1	1	0	X	X	Reserved
0	1	0	X	X	X	Reserved
0	0	0	0	G	G	Part of the assigned G-RNTI
0	0	0	1	R	R	Random G-RNTI

'T', 'R', 'A' and 'X' indicate bits which can take any value for the type of TLLI. More precisely, 'T' indicates bits derived from a P-TMSI, 'R' indicates bits chosen randomly, 'A' indicates bits chosen by the SGSN, 'G' indicates bits derived from the assigned G-RNTI and 'X' indicates bits in reserved ranges.

## 2.7 Structure of P-TMSI Signature

The P-TMSI Signature consists of 3 octets and may be allocated by the SGSN.

The network shall not allocate a P-TMSI Signature with all 24 bits equal to 1 (this is because the P-TMSI Signature must be stored in the SIM, and the SIM uses 3 octets with all bits equal to 1 to indicate that no valid P-TMSI signature is available).

## 2.8 Globally Unique Temporary UE Identity (GUTI)

### 2.8.1 Introduction

The purpose of the GUTI is to provide an unambiguous identification of the UE that does not reveal the UE or the user's permanent identity in the Evolved Packet System (EPS). It also allows the identification of the MME and network. It can be used by the network and the UE to establish the UE's identity during signalling between them in the EPS. See 3GPP TS 23.401 [72].

The GUTI has two main components:

- one that uniquely identifies the MME which allocated the GUTI; and
- one that uniquely identifies the UE within the MME that allocated the GUTI.

Within the MME, the mobile shall be identified by the M-TMSI.

The Globally Unique MME Identifier (GUMMEI) shall be constructed from the MCC, MNC and MME Identifier (MMEI).

The MMEI shall be constructed from an MME Group ID (MMEGI) and an MME Code (MMEC).

The GUTI shall be constructed from the GUMMEI and the M-TMSI.

For paging purposes, the mobile is paged with the S-TMSI. The S-TMSI shall be constructed from the MMEC and the M-TMSI.

The operator shall need to ensure that the MMEC is unique within the MME pool area and, if overlapping pool areas are in use, unique within the area of overlapping MME pools.

**NOTE:** In some network sharing cases it is required that the MMEC and NRI values are coordinated between the sharing operators, as described in 3GPP TS 23.251 [101]. In order to achieve CS/PS coordination in shared GERAN/UTRAN networks, the MMEC included in the GUTI can be set to identify the CS operator serving the UE.

The GUTI shall be used to support subscriber identity confidentiality, and, in the shortened S-TMSI form, to enable more efficient radio signalling procedures (e.g. paging and Service Request).

The format and size of the GUTI is therefore the following:

<GUTI> = <GUMMEI><M-TMSI>,

where <GUMMEI> = <MCC><MNC><MME Identifier>

and <MME Identifier> = <MME Group ID><MME Code>

MCC and MNC shall have the same field size as in earlier 3GPP systems.

M-TMSI shall be of 32 bits length.

MME Group ID shall be of 16 bits length.

MME Code shall be of 8 bits length.

## 2.8.2 Mapping between Temporary and Area Identities for the EUTRAN and the UTRAN/GERAN based systems

### 2.8.2.0 Introduction

This section provides information on the mapping of the temporary and location area identities, e.g. for the construction of the Routing Area Update Request message in GERAN/UTRAN or Tracking Area Update Request message in E-UTRAN.

In GERAN and UTRAN:

<RAI> = <MCC><MNC><LAC><RAC>

<P-TMSI/TLLI> includes the mapped NRI

P-TMSI shall be of 32 bits length where the two topmost bits are reserved and always set to '11'. Hence, for a UE which may handover to GERAN/UTRAN (based on subscription and UE capabilities), the corresponding bits in the M-TMSI are set to '11' (see subclause 2.8.2.1.3).

3GPP TS 23.236 [23] specifies that the NRI field is of variable length and shall be mapped into the P-TMSI starting at bit 23 and down to bit 14. The most significant bit of the NRI is located at bit 23 of the P-TMSI regardless of the configured length of the NRI. To support mobility between GERAN/UTRAN and E-UTRAN, the NRI length is limited to a maximum of 8 bits to be compatible for the mapping to MME Code within GUTI (see subclause 2.8.2.2).

The P-TMSI and NRI are defined elsewhere in this specification.

In the case of a combined MME-SGSN node, the NRI of the SGSN part and the MME code of the MME part, refer to the same combined node. RAN configuration allows NAS messages on GERAN/UTRAN and E-UTRAN to be routed to the same combined node. The same or different values of NRI and MME code may be used for a combined node.

### 2.8.2.1 Mapping from GUTI to RAI, P-TMSI and P-TMSI signature

#### 2.8.2.1.1 Introduction

This subclause addresses the case when a UE moves from an MME to an SGSN. The SGSN may be either an S4 SGSN or a Gn/Gp SGSN.

#### 2.8.2.1.2 Mapping in the UE

When a UE moves from an E-UTRAN to a GERAN/UTRAN, the UE needs to map the GUTI to an RAI, a P-TMSI and a P-TMSI Signature, for them to be sent to the SGSN. For GERAN, the TLLI is derived from the P-TMSI by the UE and is a foreign TLLI (see subclause 2.6).

The mapping of the GUTI shall be done to the combination of RAI of GERAN / UTRAN and the P-TMSI:

E-UTRAN <MCC> maps to GERAN/UTRAN <MCC>

E-UTRAN <MNC> maps to GERAN/UTRAN <MNC>

E-UTRAN <MME Group ID> maps to GERAN/UTRAN <LAC>

E-UTRAN <MME Code> maps to GERAN/UTRAN <RAC> and is also copied into the 8 Most Significant Bits of the NRI field within the P-TMSI;

E-UTRAN <M-TMSI> maps as follows:

- 6 bits of the E-UTRAN <M-TMSI> starting at bit 29 and down to bit 24 are mapped into bit 29 and down to bit 24 of the GERAN/UTRAN <P-TMSI>;
- 16 bits of the E-UTRAN <M-TMSI> starting at bit 15 and down to bit 0 are mapped into bit 15 and down to bit 0 of the GERAN/UTRAN <P-TMSI>;
- and the remaining 8 bits of the E-UTRAN <M-TMSI> are mapped into the 8 Most Significant Bits of the <P-TMSI signature> field.

The UE shall fill the remaining 2 octets of the <P-TMSI signature> according to subclauses 9.1.1, 9.4.1, 10.2.1, or 10.5.1 of 3GPP TS.33.401 [89], as appropriate, for RAU/Attach procedures.

For UTRAN, the 10-bit long NRI bits are masked out from the P-TMSI and are also supplied by the UE to the RAN node as IDNNS (Intra Domain NAS Node Selector) (see 3GPP TS 23.236 [23]). However, the RAN configured NRI length should not exceed 8 bits.

### 2.8.2.1.3 Mapping in the old MME

A new SGSN attempts to retrieve information regarding the UE, e.g. the IMSI, from the old MME. In order to find the UE context, the MME needs to map the RAI, P-TMSI (or TLLI) and the P-TMSI Signature (sent by the SGSN) to create the GUTI and compare it with the stored GUTI.

The MME shall perform a reverse mapping to the mapping procedure specified in subclause 2.8.2.1.2 "Mapping in the UE" (see 3GPP TS 29.060 [6] and 3GPP TS 29.274 [88] for specifics of the messaging). For the reverse mapping, the E-UTRAN <MME Code> within the GUTI shall be set either to bits 23 to 16 of the GERAN/UTRAN <P-TMSI> (i.e., the NRI field) or to the GERAN/UTRAN <RAC>. For GERAN TLLI, the old MME replaces the two topmost bits of TLLI, received from new SGSN via GTPv1, with '11' before mapping the TLLI to the GUTI used for looking up the "UE Context".

## 2.8.2.2 Mapping from RAI and P-TMSI to GUTI

### 2.8.2.2.1 Introduction

This subclause addresses the case when a UE moves from an SGSN to an MME (i.e. during a TAU or an Attach to MME). The SGSN may be either an S4 SGSN or a Gn/Gp SGSN.

### 2.8.2.2.2 Mapping in the UE

When the UE moves from the GERAN/UTRAN to the E-UTRAN, the UE needs to map the RAI and P-TMSI to a GUTI to be sent to the MME. The P-TMSI signature is sent intact to the MME.

The mapping of P-TMSI (TLLI) and RAI in GERAN/UTRAN to GUTI in E-UTRAN shall be performed as follows:

GERAN/UTRAN <MCC> maps to E-UTRAN <MCC>

GERAN/UTRAN <MNC> maps to E-UTRAN <MNC>

GERAN/UTRAN <LAC> maps to E-UTRAN <MME Group ID>

GERAN/UTRAN <RAC> maps into bit 23 and down to bit 16 of the M-TMSI

The 8 most significant bits of GERAN/UTRAN <NRI> map to the MME code.

GERAN/UTRAN <P-TMSI> maps as follows:

- 6 bits of the GERAN/UTRAN <P-TMSI> starting at bit 29 and down to bit 24 are mapped into bit 29 and down to bit 24 of the E-UTRAN <M-TMSI>;
- 16 bits of the GERAN/UTRAN <P-TMSI> starting at bit 15 and down to bit 0 are mapped into bit 15 and down to bit 0 of the E-UTRAN <M-TMSI>.

The values of <LAC> and <MME group id> shall be disjoint, so that they can be differentiated.

The most significant bit of the <LAC> shall be set to zero; and the most significant bit of <MME group id> shall be set to one. Based on this definition, the most significant bit of the <MME group id> can be used to distinguish the node type, i.e. whether it is an MME or SGSN. The UE copies the received old SGSN's <LAC> into the <MME Group ID> when sending a message to an MME, regardless of the value of the most significant bit of the <LAC>.

In networks where this definition is not applied (e.g. in networks already configured with LAC with the most significant bit set to 1 before LTE deployment), the information in the TAU/RAU request indicating whether the provided GUTI/P-TMSI is "native" (i.e. no system change) or "mapped" (i.e. system change) can be used to distinguish the node type for UEs implemented according to this release of the specification (see 3GPP TS 24.301 [90] and 3GPP TS 24.008 [5]). Specific network implementations still satisfying 3GPP standard interfaces can be used for pre-Rel-10 UEs to distinguish the node type.

NOTE 1: As an example, at NAS level, the MME/SGSN can retrieve the old SGSN/MME by using additional GUTI/additional RAI/P-TMSI with double DNS query to solve the first time the UE moves between E-UTRAN and GERAN/UTRAN. As another example, the MME/SGSN can retrieve the old SGSN/MME by using double DNS query.

#### 2.8.2.2.3 Mapping in the new MME

In order to retrieve the UE's information, e.g. the IMSI, from the old SGSN, the new MME extracts only the RAI and P-TMSI from the GUTI via the reverse mapping procedure to that specified in subclause 2.8.2.2.2. This is done in order to be able to include the mapped RAI and P-TMSI, along with the P-TMSI Signature received by the MME from the UE, in the corresponding message sent to the old SGSN (see 3GPP TS 29.060 [6] and 3GPP TS 29.274 [88] for specifics of the messaging). The old SGSN compares the received RAI, P-TMSI and P-TMSI Signature with the stored values for identifying the UE.

## 2.9 Structure of the S-Temporary Mobile Subscriber Identity (S-TMSI)

The S-TMSI is the shortened form of the GUTI to enable more efficient radio signalling procedures (e.g. paging and Service Request). For paging purposes, the mobile is paged with the S-TMSI. The S-TMSI shall be constructed from the MMEC and the M-TMSI:

$$\langle \text{S-TMSI} \rangle = \langle \text{MMEC} \rangle \langle \text{M-TMSI} \rangle$$

See subclause 2.8 for these definitions and the mapping.

---

# 3 Numbering plan for mobile stations

## 3.1 General

The structure of the following numbers is defined below:

- the number used by a subscriber of a fixed (or mobile) network to call a mobile station of a PLMN;
- the network addresses used for packet data communication between a mobile station and a fixed (or mobile) station;
- mobile station roaming numbers.

One or more numbers of the ISDN numbering plan shall be assigned to a mobile station to be used for all calls to that station, i.e. the assignment of at least one MSISDN to a mobile station is mandatory. As an exception, GPRS and EPS allow for operation whereby a MSISDN is not allocated as part of the subscription data (see 3GPP TS 23.060 [3] subclause 5.3.17 and 3GPP TS 23.401 [72]).

NOTE: For card operated stations the ISDN number should be assigned to the holder of the card (personal number).

## 3.2 Numbering plan requirements

In principle, it should be possible for any subscriber of the ISDN or PSTN to call any MS in a PLMN. This implies that ISDN numbers for MSs should comply with the ISDN numbering plan in the home country of the MS.

The ISDN numbers of MSs should be composed in such a way that standard ISDN/PSTN charging can be used for calls to MSs.

It should be possible for each administration to develop its own independent numbering/addressing plan for MSs.

The numbering/addressing plan should not limit the possibility for MSs to roam among PLMNs.


It should be possible to change the IMSI without changing the ISDN number allocated to an MS and vice versa.

In principle, it should be possible for any subscriber of the CSPDN/PSPDN to call any MS in a PLMN. This implies that it may be necessary for an MS to have a X.121 number.

In principle, it should be possible for any fixed or mobile terminal to communicate with a mobile terminal using an IP v4 address or IP v6 address.

## 3.3 Structure of MS international PSTN/ISDN number (MSISDN)

MS international ISDN numbers are allocated from the ITU-T Recommendation E.164 numbering plan; see also ITU-T Recommendation E.213. The structure of the MS international ISDN number will then be as shown in figure 2.



**Figure 2: Number Structure of MSISDN**

The number consists of:

- Country Code (CC) of the country in which the MS is registered, followed by:
- National (significant) mobile number, which consists of:
  - National Destination Code (NDC) and
  - Subscriber Number (SN).

For GSM/UMTS applications, a National Destination Code is allocated to each PLMN. In some countries more than one NDC may be required for each PLMN.

The composition of the MS international ISDN number should be such that it can be used as a global title address in the Signalling Connection Control Part (SCCP) for routing messages to the home location register of the MS. The country code (CC) and the national destination code (NDC) will provide such routing information. If further routing information is required, it should be contained in the first few digits of the subscriber number (SN).

A sub-address may be appended to an ISDN number for use in call setup and in supplementary service operations where an ISDN number is required (see ITU-T Recommendations E.164, clause 11.2 and X.213 annex A). The sub-address is transferred to the terminal equipment denoted by the ISDN number.

The maximum length of a sub-address is 20 octets, including one octet to identify the coding scheme for the sub-address (see ITU-T Recommendation X.213, annex A). All coding schemes described in ITU-T Recommendation X.213, annex A are supported in GSM and UMTS.

As an exception to the rules above, the MSISDN shall take the dummy MSISDN value composed of 15 digits set to 0 (encoded as an E.164 international number) when the MSISDN is not available in messages in which the presence of the MSISDN parameter is required for backward compatibility reason. See the relevant stage 3 specifications.

### 3.4 Mobile Station Roaming Number (MSRN) for PSTN/ISDN routing

The Mobile Station Roaming Number (MSRN) is used to route calls directed to an MS. On request from the Gateway MSC via the HLR it is temporarily allocated to an MS by the VLR with which the MS is registered; it addresses the Visited MSC collocated with the assigning VLR. More than one MSRN may be assigned simultaneously to an MS.

The MSRN is passed by the HLR to the Gateway MSC to route calls to the MS.

The Mobile Station Roaming Number for PSTN/ISDN routing shall have the same structure as international ISDN numbers in the area in which the roaming number is allocated, i.e.:

- the country code of the country in which the visitor location register is located;
- the national destination code of the visited PLMN or numbering area;
- a subscriber number with the appropriate structure for that numbering area.

The MSRN shall not be used for subscriber dialling. It should be noted that the MSRN can be identical to the MSISDN (clause 3.3) in certain circumstances. In order to discriminate between subscriber generated access to these numbers and re-routing performed by the network, re-routing or redirection indicators or other signalling means should be used, if available.

### 3.5 Structure of Mobile Station International Data Number

The structure of MS international data numbers should comply with the data numbering plan of ITU-T Recommendation X.121 as applied in the home country of the mobile subscriber. Implications for numbering interworking functions which may need to be provided by the PLMN (if the use of X.121 numbers is required) are indicated in 3GPP TS 23.070 [4].

### 3.6 Handover Number

The handover number is used for establishment of a circuit between MSCs to be used for a call being handed over. The structure of the handover number is the same as the structure of the MSRN. The handover number may be reused in the same way as the MSRN.

### 3.7 Structure of an IP v4 address

One or more IP address domains may be allocated to each PLMN. The IP v4 address structure is defined in RFC 791 [14].

An IP v4 address may be allocated to an MS either permanently or temporarily during a connection with the network.



## 3.8 Structure of an IP v6 address

One or more IP address domains could be allocated to each PLMN. The IP v6 address structure is defined in RFC 2373 [15].

An IP v6 address may be allocated to an MS either permanently or temporarily during a connection with the network

If the dynamic IPv6 stateless address autoconfiguration procedure is used, then each PDP context, or group of PDP contexts sharing the same IP address, is assigned a unique prefix as defined in 3GPP TS 23.060 [3].


As described in RFC 2462 [21] and RFC 3041 [22], the MS can change its interface identifier without the GPRS network being aware of the change.

---

## 4 Identification of location areas and base stations

### 4.1 Composition of the Location Area Identification (LAI)

The Location Area Identification shall be composed as shown in figure 3:



**Figure 3: Structure of Location Area Identification**

The LAI is composed of the following elements:

- Mobile Country Code (MCC) identifies the country in which the GSM PLMN is located. The value of the MCC is the same as the three digit MCC contained in international mobile subscriber identity (IMSI);
- Mobile Network Code (MNC) is a code identifying the GSM PLMN in that country. The MNC takes the same value as the two or three digit MNC contained in IMSI;
- Location Area Code (LAC) is a fixed length code (of 2 octets) identifying a location area within a PLMN. This part of the location area identification can be coded using a full hexadecimal representation except for the following reserved hexadecimal values:

0000, and


FFFE.

These reserved values are used in some special cases when no valid LAI exists in the MS (see 3GPP TS 24.008 [5], 3GPP TS 31.102 [27] and 3GPP TS 51.011 [9]).

A specific GSM PLMN code (MCC + MNC) may be broadcast for mobile stations which are not compatible with SoLSA and which do not understand the exclusive access indicator (see 3GPP TS 23.073 [30]). The reserved value of the escape PLMN code is MCC = 901 and MNC = 08.

### 4.2 Composition of the Routing Area Identification (RAI)

The Routing Area Identification shall be composed as shown in figure 4:



**Figure 4: Structure of Routing Area Identification**

The RAI is composed of the following elements:


- A valid Location Area Identity (LAI) as defined in clause 4.1. Invalid LAI values are used in some special cases when no valid RAI exists in the mobile station (see 3GPP TS 24.008 [5], 3GPP TS 31.102 [27] and 3GPP TS 51.011 [9]).
- Routing Area Code (RAC) which is a fixed length code (of 1 octet) identifying a routing area within a location area.

## 4.3 Base station identification

### 4.3.1 Cell Identity (CI) and Cell Global Identification (CGI)

The BSS and cell within the BSS are identified within a location area or routing area by adding a Cell Identity (CI) to the location area or routing area identification, as shown in figure 5. The CI is of fixed length with 2 octets and it can be coded using a full hexadecimal representation.


The Cell Global Identification is the concatenation of the Location Area Identification and the Cell Identity. Cell Identity shall be unique within a location area.



**Figure 5: Structure of Cell Global Identification**

### 4.3.2 Base Station Identify Code (BSIC)

The base station identity code is a local colour code that allows an MS to distinguish between different neighbouring base stations. BSIC is a 6 bit code which is structured as shown in Figure 6.



**Figure 6: Structure of BSIC**


In the definition of the NCC, care should be taken to ensure that the same NCC is not used in adjacent PLMNs which may use the same BCCH carrier frequencies in neighbouring areas. Therefore, to prevent potential deadlocks, a definition of the NCC appears in annex A. This annex will be reviewed in a co-ordinated manner when a PLMN is created.

In addition to the above, the GERAN networks should be configured so that:

- in a cell shared between different PLMNs as per GERAN network sharing (see 3GPP TS 44.018 [99] and 3GPP TS 44.060 [100]), the NCC used in this cell is different from the NCC used in the neighbouring non-shared cells of these PLMNs; and that
- these PLMNs use different NCCs in non-shared cells neighbouring this shared cell.

## 4.4 Regional Subscription Zone Identity (RSZI)

A PLMN-specific regional subscription defines unambiguously for the entire PLMN the regions in which roaming is allowed. It consists of one or more regional subscription zones. The regional subscription zone is identified by a Regional Subscription Zone Identity (RSZI). A regional subscription zone identity is composed as shown in figure 7.



**Figure 7: Structure of Regional Subscription Zone Identity (RSZI)**

The elements of the regional subscription zone identity are:

- 1) the Country Code (CC) which identifies the country in which the PLMN is located;
- 2) the National Destination Code (NDC) which identifies the PLMN in that country;
- 3) the Zone Code (ZC) which identifies a regional subscription zone as a pattern of allowed and not allowed location areas uniquely within that PLMN.

CC and NDC are those of an ITU-T E.164 VLR or SGSN number (see clause 5.1) of the PLMN; they are coded with a trailing filler, if required. ZC has fixed length of two octets and is coded in full hexadecimal representation.


RSZIs, including the zone codes, are assigned by the VPLMN operator. The zone code is evaluated in the VLR or SGSN by information stored in the VLR or SGSN as a result of administrative action. If a zone code is received by a VLR or SGSN during updating by the HLR and this zone code is related to that VLR or SGSN, the VLR or SGSN shall be able to decide for all its MSC or SGSN areas and all its location areas whether they are allowed or not allowed.

For details of assignment of RSZI and of ZC as subscriber data see 3GPP TS 23.008 [2].

For selection of RSZI at location updating by comparison with the leading digits of the VLR or SGSN number and for transfer of ZC from the HLR to VLR and SGSN see 3GPP TS 29.002 [31].

## 4.5 Location Number

A location number is a number which defines a specific location within a PLMN. The location number is formatted according to ITU-T Recommendation E.164, as shown in figure 8. The Country Code (CC) and National Destination Code (NDC) fields of the location number are those which define the PLMN of which the location is part.



**Figure 8: Location Number Structure**

The structure of the locally significant part (LSP) of the location number is a matter for agreement between the PLMN operator and the national numbering authority in the PLMN's country. It is desirable that the location number can be interpreted without the need for detailed knowledge of the internal structure of the PLMN; the LSP should therefore include the national destination code in the national numbering plan for the fixed network which defines the geographic area in which the location lies.

The set of location numbers for a PLMN shall be chosen so that a location number can be distinguished from the MSISDN of a subscriber of the PLMN. This will allow the PLMN to trap attempts by users to dial a location number.

## 4.6 Composition of the Service Area Identification (SAI)

Void (see subclause 12.5).

## 4.7 Closed Subscriber Group

A Closed Subscriber Group consists of a single cell or a collection of cells within an E-UTRAN and UTRAN that are open to only a certain group of subscribers.

Within a PLMN, a Closed Subscriber Group is identified by a Closed Subscriber Group Identity (CSG-ID). The CSG-ID shall be fix length 27 bit value.

## 4.8 HNB Name

HNB Name shall be a broadcast string in free text format that provides a human readable name for the Home NodeB or Home eNodeB CSG identity.

HNB Name shall be coded in UTF-8 format with variable number of bytes per character. The maximum length of HNB Name shall be 48 bytes.

See 3GPP TS 22.011 [83] for details.

## 4.9 CSG Type

CSG Type shall provide the type of a CSG identity in a human readable form. It shall reside in the UE only. See 3GPP TS 22.011 [83] for details.

When the CSG Type has a text component, the CSG Type shall be coded in UTF-8 format with variable number of bytes per character . The maximum text length shall not exceed 12 characters in any language.

## 4.10 HNB Unique Identity

HNB Unique Identity uniquely identifies a Home NodeB or Home eNodeB.

The HNB unique identity shall be defined as either a 48-bit or 64-bit extended unique identifier (EUI-48 or EUI-64) as defined in [45] (EUI-48) and [46] (EUI-64).

For use in HNB certificates, the HNB Unique Identity shall be transformed into a FQDN in the form:

- <EUI-48/64>.<REALM>

<EUI48/64> is the first label which shall be the EUI-48 or EUI-64, represented as a string of 12 or 16 hexadecimal digits including any leading zeros. <REALM> denotes the realm which may consist of 3 labels , e.g. hnb.femtocellvendor.com.

---

# 5 Identification of MSCs, GSNs, location registers and CSSs


## 5.1 Identification for routeing purposes

MSCs, GSNs, location registers and CSSs are identified by international PSTN/ISDN numbers and/or Signalling Point Codes ("entity number", i.e., "HLR number", "VLR number", "MSC number", "SGSN number", "GGSN number" and "CSS number") in each PLMN.

MMEs that support "SMS in MME" are identified by international PSTN/ISDN numbers for SM Routing via an IWF (i.e. "MME number for MT SMS").

Additionally SGSNs and GGSNs are identified by GSN Addresses. These are the SGSN Address and the GGSN Address.

A GSN Address shall be composed as shown in figure 9.



**Figure 9: Structure of GSN Address**

The GSN Address is composed of the following elements:

- 1) The Address Type, which is a fixed length code (of 2 bits) identifying the type of address that is used in the Address field.
- 2) The Address Length, which is a fixed length code (of 6 bits) identifying the length of the Address field.
- 3) The Address, which is a variable length field which contains either an IPv4 address or an IPv6 address.

Address Type 0 and Address Length 4 are used when Address is an IPv4 address.

Address Type 1 and Address Length 16 are used when Address is an IPv6 address.

The IP v4 address structure is defined in RFC 791 [14].

The IP v6 address structure is defined in RFC 2373 [15].

## 5.2 Identification of HLR for HLR restoration application

HLR may also be identified by one or several "HLR id(s)", consisting of the leading digits of the IMSI (MCC + MNC + leading digits of MSIN).

## 5.3 Identification of the HSS for SMS

The HSS may also be identified by a HSS-ID.

The HSS-ID shall consist of decimal digits (0 through 9) only and be composed of the MCC consisting of three digits, the MNC consisting of two or three digits and an index consisting of one to several digits. The number of digits in the HSS-ID shall not exceed 15. This composition is compatible with the IMSI one. The HSS-ID shall not be identical to the complete IMSI of a UE.

NOTE: The composition of the HSS-ID is compatible with the composition of the IMSI in clause 2.2 for routing purposes.

---

# 6 International Mobile Station Equipment Identity and Software Version Number

## 6.1 General


The structure and allocation principles of the International Mobile station Equipment Identity and Software Version number (IMEISV) and the International Mobile station Equipment Identity (IMEI) are defined below.

The Mobile Station Equipment is uniquely defined by the IMEI or the IMEISV.

## 6.2 Composition of IMEI and IMEISV

### 6.2.1 Composition of IMEI

The International Mobile station Equipment Identity (IMEI) is composed as shown in figure 10.



**Figure 10: Structure of IMEI**

The IMEI is composed of the following elements (each element shall consist of decimal digits only):

- Type Allocation Code (TAC). Its length is 8 digits;
- Serial Number (SNR) is an individual serial number uniquely identifying each equipment within the TAC. Its length is 6 digits;
- Check Digit (CD) / Spare Digit (SD): If this is the Check Digit see paragraph below; if this digit is Spare Digit it shall be set to zero, when transmitted by the MS.


The IMEI (14 digits) is complemented by a Check Digit (CD). The Check Digit is not part of the digits transmitted when the IMEI is checked, as described below. The Check Digit is intended to avoid manual transmission errors, e.g. when customers register stolen MEs at the operator's customer care desk. The Check Digit is defined according to the Luhn formula, as defined in annex B.

NOTE: The Check Digit is not applied to the Software Version Number.

The security requirements of the IMEI are defined in 3GPP TS 22.016 [32].

### 6.2.2 Composition of IMEISV

The International Mobile station Equipment Identity and Software Version Number (IMEISV) is composed as shown in figure 11.



**Figure 11: Structure of IMEISV**

The IMEISV is composed of the following elements (each element shall consist of decimal digits only):

- Type Allocation Code (TAC). Its length is 8 digits;

- Serial Number (SNR) is an individual serial number uniquely identifying each equipment within each TAC. Its length is 6 digits;
- Software Version Number (SVN) identifies the software version number of the mobile equipment. Its length is 2 digits.

Regarding updates of the IMEISV: The security requirements of 3GPP TS 22.016 [32] apply only to the TAC and SNR, but not to the SVN part of the IMEISV.

## 6.3 Allocation principles

The Type Allocation Code (TAC) is issued by the GSM Association in its capacity as the Global Decimal Administrator. Further information can be found in the GSMA TS.06 [109] .

Manufacturers shall allocate individual serial numbers (SNR) in a sequential order.

For a given ME, the combination of TAC and SNR used in the IMEI shall duplicate the combination of TAC and SNR used in the IMEISV.

The Software Version Number is allocated by the manufacturer. SVN value 99 is reserved for future use.

---

# 7 Identification of Voice Group Call and Voice Broadcast Call Entities

## 7.1 Group Identities

Logical groups of subscribers to the Voice Group Call Service or to the Voice Broadcast Service are identified by a Group Identity (Group ID). Group IDs for VGCS are unique within a PLMN. Likewise, Group IDs for VBS are unique within a PLMN. However, no uniqueness is required between the sets of Group IDs. These sets may be intersecting or even identical, at the option of the network operator.

The Group ID is a number with a maximum value depending on the composition of the voice group call reference or voice broadcast call reference defined in section 7.3.

For definition of Group ID on the radio interface, A interface and Abis interface, see 3GPP TS 44.068 [46] and 3GPP TS 44.069 [47].

For definition of Group ID coding on MAP protocol interfaces, see 3GPP TS 29.002 [31].

VGCS or VBS shall also be provided for roaming. If this applies, certain Group IDs shall be defined as supra-PLMN Group IDs which have to be co-ordinated between the network operators and which shall be known in the networks and in the SIM.

The format of the Group ID is identical for VBS and VGCS.

## 7.2 Group Call Area Identification

Grouping of cells into specific group call areas occurs in support of both the Voice Group Call Service and the Voice Broadcast Service. These service areas are known by a "Group Call Area Identity" (Group Call Area Id). No restrictions are placed on what cells may be grouped into a given group call area.

The Group Call Area ID is a number uniquely assigned to a group call area in one network and with a maximum value depending on the composition of the voice group call reference or voice broadcast reference defined under 7.3.

The formats of the Group Call Area ID for VGCS and the Group Call Area ID for VBS are identical.

## 7.3 Voice Group Call and Voice Broadcast Call References


Specific instances of voice group calls (VGCS) and voice broadcast calls (VBS) within a given group call area are known by a "Voice Group Call Reference" or by a "Voice Broadcast Call Reference" respectively.

Each voice group call or voice broadcast call in one network is uniquely identified by its Voice Group Call Reference or Voice Broadcast Call Reference. The Voice Group Call Reference or Voice Broadcast Call Reference is composed of the Group ID and the Group Call Area ID. The composition of the group call area ID and the group ID can be specific for each network operator.

For definition of Group Call Reference (with leading zeros inserted as necessary) on the radio interface, A interface and Abis interface, see 3GPP TS 24.008 [5], 3GPP TS 44.068 [46] and 3GPP TS 44.069 [47].

For definition of Group Call Reference (also known as ASCII Call Reference, Voice Group Call Reference or Voice Broadcast Call Reference) coding on MAP protocol interfaces, see 3GPP TS 29.002 [31].

The format is given in figure 12.



**Figure 12: Voice Group Call Reference / Voice Broadcast Call Reference**

## 8 SCCP subsystem numbers

Subsystem numbers are used to identify applications within network entities which use SCCP signalling. In GSM and UMTS, subsystem numbers may be used between PLMNs, in which case they are taken from the globally standardized range (1 - 31) or the part of the national network range (129 - 150) reserved for GSM/UMTS use between PLMNs. For use within a PLMN, they are taken from the part of the national network range (32 - 128 & 151 - 254) not reserved for GSM/UMTS use between PLMNs.

### 8.1 Globally standardized subsystem numbers used for GSM/UMTS

The following globally standardised subsystem numbers have been allocated for use by GSM/UMTS:

0000 0110HLR (MAP);

0000 0111VLR (MAP);

0000 1000MSC (MAP);

0000 1001EIR (MAP);

0000 1010is allocated for evolution (possible Authentication Centre).

### 8.2 National network subsystem numbers used for GSM/UMTS

The following national network subsystem numbers have been allocated for use within GSM/UMTS networks:

1111 1000CSS (MAP);



1111 1001PCAP;  
1111 1010BSC (BSSAP-LE);  
1111 1011MSC (BSSAP-LE);  
1111 1100SMLC (BSSAP-LE);  
1111 1101BSS O&M (A interface);  
1111 1110BSSAP (A interface).

The following national network subsystem numbers have been allocated for use within and between GSM/UMTS networks:

1000 1110RANAP;  
1000 1111RNSAP;  
1001 0001GMLC (MAP);  
1001 0010CAP;  
1001 0011gsmSCF (MAP) or IM-SSF (MAP) or Presence Network Agent;  
1001 0100SIWF (MAP);  
1001 0101SGSN (MAP);  
1001 0110GGSN (MAP).

---

## 9 Definition of Access Point Name

In the GPRS backbone, an Access Point Name (APN) is a reference to a GGSN. To support inter-PLMN roaming, the internal GPRS DNS functionality is used to translate the APN into the IP address of the GGSN.

### 9.0 General

Access Point Name as used in the Domain Name System (DNS) Procedures defined in 3GPP TS 29.303 [73] is specified in subclause 19.4.2.2.

### 9.1 Structure of APN

The APN is composed of two parts as follows:

- The APN Network Identifier; this defines to which external network the GGSN/PGW is connected and optionally a requested service by the MS. This part of the APN is mandatory.
- The APN Operator Identifier; this defines in which PLMN GPRS/EPS backbone the GGSN/PGW is located. This part of the APN is optional.

NOTE 1: The APN Operator Identifier is mandatory on certain interfaces, see the relevant stage 3 specifications.

The APN Operator Identifier is placed after the APN Network Identifier. An APN consisting of both the Network Identifier and Operator Identifier corresponds to a DNS name of a GGSN/PGW; the APN has, after encoding as defined in the paragraph below, a maximum length of 100 octets.

The encoding of the APN shall follow the Name Syntax defined in RFC 2181 [18], RFC 1035 [19] and RFC 1123 [20]. The APN consists of one or more labels. Each label is coded as a one octet length field followed by that number of octets coded as 8 bit ASCII characters. Following RFC 1035 [19] the labels shall consist only of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-). Following RFC 1123 [20], the label shall begin and end with

either an alphabetic character or a digit. The case of alphabetic characters is not significant. The APN is not terminated by a length byte of zero.

NOTE 2: A length byte of zero is added by the SGSN/MME at the end of the APN before interrogating a DNS server.

For the purpose of presentation, an APN is usually displayed as a string in which the labels are separated by dots (e.g. "Label1.Label2.Label3").

### 9.1.1 Format of APN Network Identifier

The APN Network Identifier shall contain at least one label and shall have, after encoding as defined in subclause 9.1 above, a maximum length of 63 octets. An APN Network Identifier shall not start with any of the strings "rac", "lac", "sgsn" or "rnc", and it shall not end in ".gprs", i.e. the last label of the APN Network Identifier shall not be "gprs". Further, it shall not take the value "\*".

In order to guarantee uniqueness of APN Network Identifiers within or between GPRS/EPS PLMN, an APN Network Identifier containing more than one label shall correspond to an Internet domain name. This name should only be allocated by the PLMN if that PLMN belongs to an organisation which has officially reserved this name in the Internet domain. Other types of APN Network Identifiers are not guaranteed to be unique within or between GPRS/EPS PLMNs.

An APN Network Identifier may be used to access a service associated with a GGSN/PGW. This may be achieved by defining:

- an APN which corresponds to a FQDN of a GGSN/PGW, and which is locally interpreted by the GGSN/PGW as a request for a specific service, or
- an APN Network Identifier consisting of 3 or more labels and starting with a Reserved Service Label, or an APN Network Identifier consisting of a Reserved Service Label alone, which indicates a GGSN/PGW by the nature of the requested service. Reserved Service Labels and the corresponding services they stand for shall be agreed between operators who have GPRS/EPS roaming agreements.

### 9.1.2 Format of APN Operator Identifier

The APN Operator Identifier is composed of three labels. The last label (or domain) shall be "gprs". The first and second labels together shall uniquely identify the GPRS/EPS PLMN.

For each operator, there is a default APN Operator Identifier (i.e. domain name). This default APN Operator Identifier is derived from the IMSI as follows:

```
"mnc<MNC>.mcc<MCC>.gprs"
```

where:

"mnc" and "mcc" serve as invariable identifiers for the following digits.

<MNC> and <MCC> are derived from the components of the IMSI defined in subclause 2.2.

This default APN Operator Identifier is used for home routed inter-PLMN roaming situations when attempting to translate an APN consisting only of a Network Identifier into the IP address of the GGSN/PGW in the HPLMN. The PLMN may provide DNS translations for other, more human-readable, APN Operator Identifiers in addition to the default Operator Identifier described above.

Alternatively, in the roaming case if the GGSN/PGW from the VPLMN is to be selected, the APN Operator Identifier for the UE is constructed from the serving network PLMN ID. In this case, the APN-OI replacement field, if received, shall be ignored.

In order to guarantee inter-PLMN DNS translation, the <MNC> and <MCC> coding used in the "mnc<MNC>.mcc<MCC>.gprs" format of the APN OI shall be:

- <MNC> = 3 digits
- <MCC> = 3 digits

- If there are only 2 significant digits in the MNC, one "0" digit is inserted at the left side to fill the 3 digits coding of MNC in the APN OI.

As an example, the APN OI for MCC 345 and MNC 12 will be coded in the DNS as "mnc012.mcc345.gprs".

The APN-OI replacement is only used for selecting the GGSN/PGW from the HPLMN. The format of the domain name used in the APN-OI replacement field (as defined in 3GPP TS 23.060 [3] and 3GPP TS 23.401 [72]) is the same as the default APN-OI as defined above except that it may be preceded by one or more labels each separated by a dot.

EXAMPLE 1: province1.mnc012.mcc345.gprs

EXAMPLE 2: ggsn-cluster-A.provinceB.mnc012.mcc345.gprs

The APN constructed using the APN-OI replacement field is only used for DNS translation. The APN when being sent to other network entities over GTP interfaces shall follow the rules as specified in 3GPP TS 23.060 [3] and 3GPP TS 23.401 [72].

## 9.2 Definition of the Wild Card APN

The APN field in the HLR may contain a wild card APN if the HPLMN operator allows the subscriber to access any network of a given PDP Type. If an SGSN has received such a wild card APN, it may either choose the APN Network Identifier received from the Mobile Station or a default APN Network Identifier for addressing the GGSN when activating a PDP context.

### 9.2.1 Coding of the Wild Card APN

The wild card APN is coded as an APN with "\*" as its single label, (i.e. a length octet with value one, followed by the ASCII code for the asterisk).

## 9.3 Definition of Emergency APN

The Emergency APN (Em-APN) is an APN used to derive a PDN GW selected for IMS Emergency call support. The exact encoding of the Em-APN is the responsibility of each PLMN operator as it is only valid within a given PLMN.

---

# 10 Identification of the Cordless Telephony System entities

## 10.1 General description of CTS-MS and CTS-FP Identities


Every CTS-FP broadcasts a local identity - the Fixed Part Beacon Identity (FPBI) - which contains an Access Rights Identity. Every CTS-MS has both an Access Rights Key and a CTS Mobile Subscriber Identity (CTSMSI). These operate as a pair. A CTS-MS is allowed to access any CTS-FP which broadcasts an FPBI which can be identified by any of the CTS-MS Access Rights Keys of that CTS-MS. The CTS-MS Access Rights Key contains the FPBI and the FPBI Length Indicator (FLI) indicating the relevant part of the FPBI used to control access.

## 10.2 CTS Mobile Subscriber Identities

### 10.2.1 General

Each CTS-MS has one or more temporary identities which are used for paging and to request access. The structure and allocation principles of the CTS Mobile Subscriber Identities (CTSMSI) are defined below.

## 10.2.2 Composition of the CTSMSI



**Figure 13: Structure of CTSMSI**

The CTSMSI is composed of the following elements:

- CTSMSI Type. Its length is 2 bits;
- Significant Part. Its length is 20 bits.

The following CTSMSI Type values have been allocated for use by CTS:

- 00 Default Individual CTSMSI;
- 01 Reserved;
- 10 Assigned Individual CTSMSI;
- 11 Assigned Connectionless Group CTSMSI.

## 10.2.3 Allocation principles

The default Individual CTSMSI contains the least significant portion of the IMSI. This is the default CTS-MS identity.

Assigned CTSMSIs are allocated by the CTS-FP during enrolment, registration and other access procedures. Significant Part of the assigned CTSMSI shall be allocated in the range 00001-FFFFE. CTS-FP shall not allocate Significant Part equal to 00000 or to FFFFF and shall not allocate Assigned CTSMSI using Reserved Type value. Such assignments shall be ignored by the CTS-MS.

Assigned CTSMSIs are allocated in ciphered mode.

**NOTE:** The assigned individual CTSMSI should be updated whenever it is sent in clear text on the CTS radio interface during RR connection establishment.

The value FFFFF from the set of Assigned Connectionless Group CTSMSI shall be considered in all CTS-MS as the value of the Connectionless Broadcast Identifier.

## 10.2.4 CTSMSI hexadecimal representation

The 22 bits of CTSMSI are padded with 2 leading zeroes to give a 6 digit hexadecimal value.

**EXAMPLE:** binary CTSMSI value: 11 1001 0010 0000 1011 1100  
hexadecimal CTSMSI value: 39 20 BC.

## 10.3 Fixed Part Beacon Identity

### 10.3.1 General


Each CTS-FP has one Fixed Part Beacon Identity known by the enrolled CTS-MSs. The FPBI is periodically broadcast on the BCH logical channel so that the CTS-MSs are able to recognise the identity of the CTS-FP. The FPBI contains an Access Rights Identity.

Enrolled CTS-MSs shall store the FPBI to which their assigned CTSMSIs are related.

Below the structure and allocation principles of the Fixed Part Beacon Identity (FPBI) are defined.

## 10.3.2 Composition of the FPBI

### 10.3.2.1 FPBI general structure



**Figure 14: General structure of FPBI**

The FPBI is composed of the following elements:

- FPBI Type. Its length is 2 bits;
- FPBI Significant Part. Its length is 17 bits.

NOTE: The three LSBs bits of the FPBI form the 3-bit training sequence code (TSC). See 3GPP TS 45.056 [35].


The following FPBI Type values have been allocated for use by CTS:

- 00 FPBI class A: residential and single-cell systems;
- 01 FPBI class B: multi-cell PABXs.

All other values are reserved and CTS-MSs shall treat these values as FPBI class A.

### 10.3.2.2 FPBI class A

This class is intended to be used for small residential and private (PBX) single cell CTS-FP.



**Figure 15: Structure of FPBI class A**


The FPBI class A is composed of the following elements:

- FPBI Class A Type. Its length is 2 bits and its value is 00;
- Fixed Part Number (FPN). Its length is 17 bits. The FPN contains the least significant bits of the Serial Number part of the IFPEI.

The FPBI Length Indicator shall be set to 19 for a class A FPBI.

### 10.3.2.3 FPBI class B

This class is reserved for more complex private installation such as multi-cell PABXs.



**Figure 16: Structure of FPBI class B**

The FPBI class B is composed of the following elements:

- FPBI Class B Type. Its length is 2 bits and its value is 01;
- CTS Network Number (CNN). Its length is defined by the manufacturer or the system installer;
- Fixed Part Number (FPN). Its length is defined by the manufacturer or the system installer;
- Radio Part Number (RPN) assigned by the CTS manufacturer or system installer. Its length is defined by the manufacturer or the system installer.

NOTE: RPN is used to separate a maximum of  $2^{\text{RPN length}}$  different cells from each other. This defines a cluster of cells supporting intercell handover. RPN length is submitted to a CTS-MS as a result of a successful attachment.

The FPBI Length Indicator shall be set to (2 + CNN Length) for a class B FPBI.

### 10.3.3 Allocation principles

The FPBI shall be allocated during the CTS-FP initialisation procedure. Any change to the value of the FPBI of a given CTS-FP shall be considered as a CTS-FP re-initialisation; i.e. each enrolled CTS-MS needs to be enrolled again.


FPBI are not required to be unique (i.e. several CTS-FP can have the same FPBI in different areas). Care should be taken to limit CTS-MS registration attempts to a fixed part with the same FPBI as another fixed part.

## 10.4 International Fixed Part Equipment Identity

### 10.4.1 General

The structure and allocation principles of the International Fixed Part Equipment Identity (IFPEI) are defined below.

### 10.4.2 Composition of the IFPEI



**Figure 17: Structure of IFPEI**

The IFPEI is composed of the following elements (each element shall consist of decimal digits only):

- Type Approval Code (TAC). Its length is 6 decimal digits;
- Final Assembly Code (FAC). Its length is 2 decimal digits;
- Serial Number (SNR). Its length is 6 decimal digits;

- Software Version Number (SVN) identifies the software version number of the fixed part equipment. Its length is 2 digits.

Regarding updates of the IFPEI: the TAC, FAC and SNR shall be physically protected against unauthorised change (see 3GPP TS 42.009 [36]); i.e. only the SVN part of the IFPEI can be modified.

### 10.4.3 Allocation principles

The Type Approval Code (TAC) is issued by a central body.

The place of final assembly (FAC) is encoded by the manufacturer.

Manufacturers shall allocate unique serial numbers (SNR) in a sequential order.


The Software Version Number (SVN) is allocated by the manufacturer after authorisation by the type approval authority. SVN value 99 is reserved for future use.

## 10.5 International Fixed Part Subscription Identity

### 10.5.1 General

The structure and allocation principles of the International Fixed Part Subscription Identity (IFPSI) are defined below.

### 10.5.2 Composition of the IFPSI



**Figure 18: Structure of IFPSI**

The IFPSI is composed of the following elements (each element shall consist of decimal digits only):

- Mobile Country Code (MCC) consisting of three digits. The MCC identifies the country of the CTS-FP subscriber (e.g. 208 for France);
- CTS Operator Number (CON). Its length is three digits;
- Fixed Part Identification Number (FPIN) identifying the CTS-FP subscriber.

The National Fixed Part Subscriber Identity (NFPSI) consists of the CTS Operator Number and the Fixed Part Identification Number.

### 10.5.3 Allocation principles

IFPSI shall consist of decimal characters (0 to 9) only.

The allocation of Mobile Country Codes (MCCs) is administered by the ITU-T.

The allocation of CTS Operator Number (CON) and the structure of National Fixed Part Subscriber Identity (NFPSI) are the responsibility of each National Regulation Authority.

CTS Operators shall allocate unique Fixed Part Identification Numbers.

## 11 Identification of Localised Service Area

Cells may be grouped into specific localised service areas. Each localised service area is identified by a localised service area identity (LSA ID). No restrictions are placed on what cells may be grouped into a given localised service area.

The LSA ID can either be a PLMN significant number or a universal identity. This shall be known both in the networks and in the SIM.

The LSA ID consists of 24 bits, numbered from 0 to 23, with bit 0 being the LSB. Bit 0 indicates whether the LSA is a PLMN significant number or a universal LSA. If the bit is set to 0 the LSA is a PLMN significant number; if it is set to 1 it is a universal LSA.

The LSA ID shall be composed as shown in figure 19:




Figure 19: Structure of LSA ID

## 12 Identification of PLMN, RNC, Service Area, CN domain and Shared Network Area

The following clauses describe identifiers which are used by both the CN and the UTRAN across the Iu interface. For identifiers which are solely used within the UTRAN, see 3GPP TS 25.401 [16].

NOTE: in the following subclauses, the double vertical bar notation || indicates the concatenation operator.

### 12.1 PLMN Identifier

A Public Land Mobile Network is uniquely identified by its PLMN identifier. PLMN-Id consists of Mobile Country Code (MCC) and Mobile Network Code (MNC).

- **PLMN-Id = MCC || MNC**

The MCC and MNC are predefined within a UTRAN, and set in the RNC via O&M.

### 12.2 CN Domain Identifier

A CN Domain Edge Node is identified within the UTRAN by its CN Domain Identifier. The CN Domain identifier is used over UTRAN interfaces to identify a particular CN Domain Edge Node for relocation purposes. The CN Domain identifier for Circuit Switching (CS) consists of the PLMN-Id and the LAC, whereas for Packet Switching (PS) it consists of the PLMN-Id, the LAC, and the RAC of the first accessed cell in the target RNS.

The two following CN Domain Identifiers are defined:

- **CN CS Domain-Id = PLMN-Id || LAC**
- **CN PS Domain-Id = PLMN-Id || LAC || RAC**

The LAC and RAC are defined by the operator, and set in the RNC via O&M.



For the syntax description and the use of this identifier in RANAP signalling, see 3GPP TS 25.413 [17].

## 12.3 CN Identifier

A CN node is uniquely identified within a PLMN by its CN Identifier (CN-Id). The CN-Id together with the PLMN identifier globally identifies the CN node. The CN-Id together with the PLMN-Id is used as the CN node identifier in RANAP signalling over the Iu interface.

**Global CN-Id = PLMN-Id || CN-Id**

The CN-Id is defined by the operator, and set in the nodes via O&M.

For the syntax description and the use of this identifier in RANAP signalling, see 3GPP TS 25.413 [17].

## 12.4 RNC Identifier

An RNC node is uniquely identified by its RNC Identifier (RNC-Id). The RNC-Id of an RNC is used in the UTRAN, in a GERAN which is operating in GERAN Iu mode and between them. A BSC which is part of a GERAN operating in Iu mode is uniquely identified by its RNC Identifier (RNC-Id). The RNC-Id of a BSC is used in a GERAN which is operating in GERAN Iu mode, in the UTRAN and between them. RNC-Id together with the PLMN identifier globally identifies the RNC. The RNC-Id on its own or the RNC-Id together with the PLMN-Id is used as the RNC identifier in the UTRAN Iub, Iur and Iu interfaces. The SRNC-Id is the RNC-Id of the SRNC. The C-RNC-Id is the RNC-Id of the controlling RNC. The D-RNC-Id is the RNC Id of the drift RNC.

- **Global RNC-Id = PLMN-Id || RNC-Id**

The RNC-Id is defined by the operator, and set in the RNC via O&M

For the syntax description and the use of this identifier in RANAP signalling, see 3GPP TS 25.413 [17].

For the usage of this identifier on Iur-g, see 3GPP TS 43.130 [43].

## 12.5 Service Area Identifier

The Service Area Identifier (SAI) is used to identify an area consisting of one or more cells belonging to the same Location Area. Such an area is called a Service Area and can be used for indicating the location of a UE to the CN.

The Service Area Code (SAC) together with the PLMN-Id and the LAC constitute the Service Area Identifier.

- **SAI = PLMN-Id || LAC || SAC**

The SAC is defined by the operator, and set in the RNC via O&M.

For the syntax description and the use of this identifier in RANAP signalling, see 3GPP TS 25.413 [17]. 3GPP TS 25.423 [37] and 3GPP TS 25.419 [38] define the use of this identifier in RNSAP and SABP signalling.

A cell may belong to one or two Service Areas. If it belongs to two Service Areas, one is applicable in the Broadcast (BC) domain and the other is applicable in both the CS and PS domains.

The Broadcast (BC) domain requires that its Service Areas each consist of only one cell. This does not limit the use of Service Areas for other domains. Refer to 3GPP TS 25.410 [39] for a definition of the BC domain.

## 12.6 Shared Network Area Identifier

The Shared Network Area Identifier (SNA-Id) is used to identify an area consisting of one or more Location Areas. Such an area is called a Shared Network Area and can be used to grant access rights to parts of a Shared Network to a UE in connected mode (see 3GPP TS 25.401 [39]).

The Shared Network Area Identifier consists of the PLMN-Id followed by the Shared Network Area Code (SNAC).

- **SNA-Id = PLMN-Id || SNAC**

The SNAC is defined by the operator.

For the syntax description and the use of this identifier in RANAP signalling, see 3GPP TS 25.413 [17].

---

## 13 Numbering, addressing and identification within the IP multimedia core network subsystem

### 13.1 Introduction

This clause describes the format of the parameters needed to access the IP multimedia core network subsystem. For further information on the use of the parameters see 3GPP TS 23.228 [24] and 3GPP TS 29.163 [63]. For more information on the ".3gppnetwork.org" domain name and its applicability, see Annex D of the present document. For more information on the ".invalid" top level domain see IETF RFC 2606 [64].

### 13.2 Home network domain name

The home network domain name shall be in the form of an Internet domain name, e.g. operator.com, as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The home network domain name consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

For 3GPP systems, if there is no ISIM application, the UE shall derive the home network domain name from the IMSI as described in the following steps:

1. Take the first 5 or 6 digits, depending on whether a 2 or 3 digit MNC is used (see 3GPP TS 31.102 [27]) and separate them into MCC and MNC; if the MNC is 2 digits then a zero shall be added at the beginning.
2. Use the MCC and MNC derived in step 1 to create the "mnc<MNC>.mcc<MCC>.3gppnetwork.org" domain name.
3. Add the label "ims." to the beginning of the domain.

An example of a home network domain name is:

IMSI in use: 234150999999999;

where:

- MCC = 234;
- MNC = 15; and
- MSIN = 0999999999,

which gives the home network domain name: ims.mnc015.mcc234.3gppnetwork.org.

For 3GPP2 systems, if there is no IMC present, the UE shall derive the home network domain name as described in Annex C of 3GPP2 X.S0013-004 [67].

### 13.3 Private User Identity

The private user identity shall take the form of an NAI, and shall have the form username@realm as specified in clause 2.1 of IETF RFC 4282 [53].

NOTE: It is possible for a representation of the IMSI to be contained within the NAI for the private identity.

For 3GPP systems, if there is no ISIM application, the private user identity is not known. If the private user identity is not known, the private user identity shall be derived from the IMSI.

The following steps show how to build the private user identity out of the IMSI:

1. Use the whole string of digits as the username part of the private user identity; and
2. convert the leading digits of the IMSI, i.e. MNC and MCC, into a domain name, as described in subclause 13.2.

The result will be a private user identity of the form "<IMSI>@ims.mnc<MNC>.mcc<MCC>.3gppnetwork.org". For example: If the IMSI is 234150999999999 (MCC = 234, MNC = 15), the private user identity then takes the form "234150999999999@ims.mnc015.mcc234.3gppnetwork.org".

For 3GPP2 systems, if there is no IMC present, the UE shall derive the private user identity as described in Annex C of 3GPP2 X.S0013-004 [67].

## 13.4 Public User Identity

A Public User Identity is any identity used by a user within the IMS subsystem for requesting communication to another user.

The Public User Identity shall take the form of either a SIP URI (see IETF RFC 3261 [26]) or a Tel URI (see IETF RFC 3966 [45]).

The 3GPP specifications describing the interfaces over which Public User Identities are transferred specify the allowed Public User Identity formats, in particular 3GPP TS 24.229 [81] for SIP signalling interfaces, 3GPP TS 29.229 [95] for Cx and Dx interfaces, 3GPP TS 29.329 [96] for Sh interface, 3GPP TS 29.165 [97] for II-NNI interface.

In the case the user identity is a telephone number, it shall be represented either by a Tel URI or by a SIP URI that includes a 'user=phone' URI parameter and a "userinfo" part that shall follow the same format as the Tel URI.

According to 3GPP TS 24.229 [81], the UE can use either:

- a global number as defined in IETF RFC 3966 [45] and following E.164 format, as defined by ITU-T Recommendation E.164 [10] or
- a local number, that shall include a 'phone-context' parameter that identifies the scope of its validity, as per IETF RFC 3966 [45].

According to 3GPP TS 29.165 [97] a global number as defined in IETF RFC 3966 [45] shall be used in a tel-URI or in the user portion of a SIP URI with the user=phone parameter when conveyed via a non-roaming II-NNI except when agreement exists between the operators to also allow other kinds of numbers.

According to 3GPP TS 29.229 [95] and 3GPP TS 29.329 [96] the canonical forms of SIP URI and Tel URI shall be used over the corresponding Diameter interfaces.

The canonical form of a SIP URI for a Public User Identity shall take the form "sip:username@domain" as specified in IETF RFC 3261 [26], section 10.3. SIP URI comparisons shall be performed as defined in IETF RFC 3261 [26], section 19.1.4.

The canonical form of a Tel URI for a Public User Identity shall take the form 'tel:+<CC><NDC><SN>' (max number of digits is 15), that represents an E.164 number and shall contain a global number without parameters and visual separators (see IETF RFC 3966[45], section 3). Tel URI comparisons shall be performed as defined in IETF RFC 3966[45], section 4.

Public User Identities are stored in the HSS either as a distinct Public User Identity or as a Wildcarded Public User Identity. A distinct Public User Identity contains the Public User Identity that is used in routing and it is explicitly provisioned in the HSS.

### 13.4A Wildcarded Public User Identity

Public User Identities may be stored in the HSS as Wildcarded Public User Identities. A Wildcarded Public User Identity represents a collection of Public User Identities that share the same service profile and are included in the same implicit registration set. Wildcarded Public User Identities enable optimisation of the operation and maintenance of the nodes for the case in which a large amount of users are registered together and handled in the same way by the network. The format of a Wildcarded Public User Identity is the same as for the Wildcarded PSI described in subclause 13.5.

## 13.4B Temporary Public User Identity

For 3GPP systems, if there is no ISIM application to host the Public User Identity, a Temporary Public User Identity shall be derived, based on the IMSI. The Temporary Public User Identity shall be of the form as described in sub-clause 13.4 and shall consist of the string "sip:" appended with a username and domain portion equal to the IMSI derived Private User Identity, as described in sub-clause 13.2. An example using the same example IMSI from sub-clause 13.2 can be found below:

EXAMPLE: "sip:23415099999999@ims.mnc015.mcc234.3gppnetwork.org".

For 3GPP2 systems, if there is no IMC present, the UE shall derive the public user identity as described in Annex C of 3GPP2 X.S0013-004 [67].

## 13.5 Public Service Identity (PSI)

The public service identity shall take the form of either a SIP URI (see IETF RFC 3261 [26]) or a Tel URI (see IETF RFC 3966 [45]). A public service identity identifies a service, or a specific resource created for a service on an application server. The domain part is pre-defined by the IMS operators and the IMS system provides the flexibility to dynamically create the user part of the PSIs.

The PSIs are stored in the HSS either as a distinct PSI or as a wildcarded PSI. A distinct PSI contains the PSI that is used in routing, whilst a wildcarded PSI represents a collection of PSIs. Wildcarded PSIs enable optimisation of the operation and maintenance of the nodes. A wildcarded PSI consists of a delimited regular expression located either in the userinfo portion of the SIP URI or in the telephone-subscriber portion of the Tel URI. The regular expression in the wildcarded PSI shall take the form of Extended Regular Expressions (ERE) as defined in chapter 9 in IEEE 1003.1-2004 Part 1 [60]. The delimiter shall be the exclamation mark character ("!"). If more than two exclamation mark characters are present in the userinfo portion or telephone-subscriber portion of a wildcarded PSI then the outside pair of exclamation mark characters is regarded as the pair of delimiters (i.e. no exclamation mark characters are allowed to be present in the fixed parts of the userinfo portion or telephone-subscriber portion).

When stored in the HSS, the wildcarded PSI shall include the delimiter character to indicate the extent of the part of the PSI that is wildcarded. It is used to separate the regular expression from the fixed part of the wildcarded PSI.

Example: The following PSI could be stored in the HSS - "sip:chatlist!\*!@example.com".

When used on an interface, the exclamation mark characters within a PSI shall not be interpreted as delimiter..

Example: The following PSIs communicated in interface messages to the HSS will match to the wildcarded PSI of "sip:chatlist!\*!@example.com" stored in the HSS:

sip:chatlist1@example.com

sip:chatlist2@example.com

sip:chatlist42@example.com

sip:chatlistAbC@example.com

sip:chatlist!1@example.com

Note that sip:chatlist1@example.com and sip:chatlist!1@example.com are regarded different specific PSIs, both matching the wildcarded PSI sip:chatlist!\*!@example.com.

When used by an application server to identify a specific resource (e.g. a chat session) over Inter Operator Network to Network Interface (II-NNI), the PSI should be a SIP URI without including a port number.

NOTE: Based on local configuration policy, a PSI can be routed over Inter Operator Network to Network Interface (II-NNI). Details of this routing are operator specific and out of scope of this specification.

## 13.5A Private Service Identity

The Private Service Identity is applicable to a PSI user and is similar to a Private User Identity in the form of a Network Access Identifier (NAI), which is defined in IETF RFC 4282 [53]. The Private Service Identity is operator defined and although not operationally used for registration, authorisation and authentication in the same way as Private User Identity, it enables Public Service Identities to be associated to a Private Service Identity which is required for compatibility with the Cx procedures.

## 13.6 Anonymous User Identity

The Anonymous User Identity shall take the form of a SIP URI (see IETF RFC 3261 [26]). A SIP URI for an Anonymous User Identity shall take the form "sip:user@domain". The user part shall be the string "anonymous" and the domain part shall be the string "anonymous.invalid". The full SIP URI for Anonymous User Identity is thus:

"sip:anonymous@anonymous.invalid"

For more information on the Anonymous User Identity and when it is used, see 3GPP TS 29.163 [63].

## 13.7 Unavailable User Identity

The Unavailable User Identity shall take the form of a SIP URI (see IETF RFC 3261 [26]). A SIP URI for an Unavailable User Identity shall take the form "sip:user@domain". The user part shall be the string "unavailable" and the domain part shall be the string "unknown.invalid". The full SIP URI for Unavailable User Identity is thus:

"sip:unavailable@unknown.invalid"

For more information on the Unavailable User Identity and when it is used, see 3GPP TS 29.163 [63].

## 13.8 Instance-ID

An instance-id is a SIP Contact header parameter that uniquely identifies the SIP UA performing a registration.

When an IMEI is available, the instance-id shall take the form of a IMEI URN (see RFC 7254 [79]). The format of the instance-id shall take the form "urn:gsma:imei:<imeival>" where by the imeival shall contain the IMEI encoded as defined in RFC 7254 [79]. The optional <sw-version-param> and <imei-version-param> parameters shall not be included in the instance-id. RFC 7255 [104] specifies additional considerations for using the IMEI as an instance-id. An example of such an instance-id is as follows:

EXAMPLE: urn:gsma:imei:90420156-025763-0

If no IMEI is available, the instance-id shall take the form of a string representation of a UUID as a URN as defined in IETF RFC 4122 [80]. An example of such an instance-id is as follows:

EXAMPLE: urn:uuid:f81d4fae-7dec-11d0-a765-00a0c91e6bf6

For more information on the instance-id and when it is used, see 3GPP TS 24.229 [81].

## 13.9 XCAP Root URI

### 13.9.1 XCAP Root URI on Ut interface

#### 13.9.1.1 General

XCAP Root URI is an HTTP URI that represents the XCAP Root. Although a valid URI, the XCAP Root URI does not correspond to an actual resource.

### 13.9.1.2 Format of XCAP Root URI

The XCAP Root URI, as defined in IETF RFC 4825 [94], is an HTTP URI that should have the following format:

"http://xcap.<domain>"

in which "<domain>" identifies the domain hosting the XCAP server.

NOTE 1: The XCAP Root URI does not contain a port portion or an abs path portion of a standard HTTP URI.

If a preconfigured or provisioned XCAP Root URI is available then the UE shall use it. When a preconfigured or provisioned XCAP Root URI does not exist then the UE shall create the XCAP Root URI as follows:

- The first label shall be "xcap".
- The next label(s) shall identify the home network as follows:
  1. When the UE has an ISIM, the domain name from the IMPI shall be used (see 3GPP TS 31.103 [93]) as follows:
    - a. if the last two labels of the domain name from the IMPI are "3gppnetwork.org":
      - i. the next labels shall be all labels of the domain name from the IMPI apart from the last two labels; and
      - ii. the last three labels shall be "pub.3gppnetwork.org";
    - b. if the last two labels of the domain name from the IMPI are other than the "3gppnetwork.org":
      - i. the next labels shall be all labels of the domain name from the IMPI;
  2. When the UE has a USIM and does not have ISIM, the home network shall be "ims.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org" where <MNC> and <MCC> shall be derived from the components of the IMSI defined in subclause 2.2. If there are only two significant digits in the MNC, one "0" digit shall be inserted at the left side to fill the 3 digits coding of MNC in the FQDN of XCAP Root URI.

As an example for the case when the UE has ISIM, where the IMPI is "user@operator.com", the overall XCAP Root URI used by the UE would be:

"http://xcap.operator.com".

As an example for the case when the UE has ISIM, where the IMPI is "234150999999999@ims.mnc015.mcc234.3gppnetwork.org", the overall XCAP Root URI used by the UE would be:

"xcap.ims.mnc015.mcc234.pub.3gppnetwork.org".

As an example for the case when the UE has USIM and does not have ISIM, where the MCC is 345 and the MNC is 12, the overall XCAP Root URI created and used by the UE would be:

"xcap.ims.mnc012.mcc345.pub.3gppnetwork.org"

## 13.10 Default Conference Factory URI for MMTel

The Default Conference Factory URI for MMTel shall take the form of a SIP URI (see IETF RFC 3261 [26]) with a host portion set to the home network domain name as described in subclause 13.2 prefixed with "conf-factory.". The user portion shall be set to "mmtel".

Examples of the Default Conference Factory URI for MMTel can be found below:

EXAMPLE 1: "sip:mmtel@conf-factory.operator.com"

when the UE has a home network domain name of operator.com.

EXAMPLE 2: "sip:mmtel@conf-factory.ims.mnc015.mcc234.3gppnetwork.org"

for 3GPP systems, when the UE with no ISIM application has a home network domain name of `ims.mnc015.mcc234.3gppnetwork.org` derived from the same example IMSI as described in sub-clause 13.2.

---

## 14 Numbering, addressing and identification for 3GPP System to WLAN Interworking

### 14.1 Introduction

This clause describes the format of the parameters needed to access the 3GPP system supporting the WLAN interworking. For further information on the use of the parameters see 3GPP TS 24.234 [48]. For more information on the ".3gppnetwork.org" domain name and its applicability, see Annex D of the present document.

**NOTE:** The WLAN Network Selection and WLAN/3GPP Radio Interworking features supersede the I-WLAN feature from Rel-12 onwards, therefore all I-WLAN related requirements specified in the present Clause are no longer maintained.

### 14.2 Home network realm

The home network realm shall be in the form of an Internet domain name, e.g. `operator.com`, as specified in RFC 1035 [19].

When attempting to authenticate within WLAN access, the WLAN UE shall derive the home network domain name from the IMSI as described in the following steps:

1. take the first 5 or 6 digits, depending on whether a 2 or 3 digit MNC is used (see 3GPP TS 31.102 [27], 3GPP TS 51.011 [66]) and separate them into MCC and MNC; if the MNC is 2 digits then a zero shall be added at the beginning;
2. use the MCC and MNC derived in step 1 to create the "`mnc<MNC>.mcc<MCC>.3gppnetwork.org`" domain name;
3. add the label "`wlan.`" to the beginning of the domain name.

An example of a WLAN NAI realm is:

IMSI in use: 234150999999999;

Where:

MCC = 234;

MNC = 15;

MSIN = 0999999999

Which gives the home network domain name: `wlan.mnc015.mcc234.3gppnetwork.org`.

**NOTE:** If it is not possible for the WLAN UE to identify whether a 2 or 3 digit MNC is used (e.g. SIM is inserted and the length of MNC in the IMSI is not available in the "Administrative data" data file), it is implementation dependent how the WLAN UE determines the length of the MNC (2 or 3 digits).

### 14.3 Root NAI

The Root NAI shall take the form of a NAI, and shall have the form `username@realm` as specified in clause 2.1 of IETF RFC 4282 [53].

The username part format of the Root NAI shall comply with IETF RFC 4187 [50] when EAP AKA authentication is used and with IETF RFC 4186 [51], when EAP SIM authentication is used.

When the username part includes the IMSI, the Root NAI shall be built according to the following steps:

1. Generate an identity conforming to NAI format from IMSI as defined in EAP SIM [51] and EAP AKA [50] as appropriate;
2. Convert the leading digits of the IMSI, i.e. MNC and MCC, into a domain name, as described in subclause 14.2.

The result will be a root NAI of the form:

"0<IMSI>@wlan.mnc<MNC>.mcc<MCC>.3gppnetwork.org", for EAP AKA authentication and  
 "1<IMSI>@wlan.mnc<MNC>.mcc<MCC>.3gppnetwork.org", for EAP SIM authentication

For example, for EAP AKA authentication: If the IMSI is 234150999999999 (MCC = 234, MNC = 15), the root NAI then takes the form 023415099999999@wlan.mnc015.mcc234.3gppnetwork.org.

## 14.4 Decorated NAI

The Decorated NAI shall take the form of a NAI and shall have the form 'homerealm!username@otherrealm' as specified in clause 2.7 of the IETF RFC 4282 [53].

The realm part of Decorated NAI consists of 'otherrealm', see the IETF draft 2486-bisRFC 4282 [53]. 'Homerealm' is the realm as specified in clause 14.2, using the HPLMN ID ('homeMCC' + 'homeMNC'). 'Otherrealm' is the realm built using the PLMN ID (visitedMCC + visited MNC) of the PLMN selected as a result of WLAN PLMN selection (see 3GPP TS 24.234 [48]).

The username part format of the Root NAI shall comply with IETF RFC 4187 [50] when EAP AKA authentication is used and with IETF RFC 4186 [51], when EAP SIM authentication is used.

When the username part of Decorated NAI includes the IMSI, it shall be built following the same steps specified for Root NAI in clause 14.3.

The result will be a decorated NAI of the form:

"wlan.mnc<homeMNC>.mcc<homeMCC>.3gppnetwork.org  
 !0<IMSI>@wlan.mnc<visitedMNC>.mcc<visitedMCC>.3gppnetwork.org", for EAP AKA authentication and "  
 wlan.mnc<homeMNC>.mcc<homeMCC>.3gppnetwork.org  
 !1<IMSI>@wlan.mnc<visitedMNC>.mcc<visitedMCC>.3gppnetwork.org ", for EAP SIM authentication

For example, for EAP AKA authentication: If the IMSI is 234150999999999 (MCC = 234, MNC = 15) and the PLMN ID of the Selected PLMN is MCC = 610, MNC = 71 then the Decorated NAI takes the form  
 wlan.mnc015.mcc234.3gppnetwork.org!023415099999999@wlan.mnc071.mcc610.3gppnetwork.org.

NOTE: the 'otherrealm' specified in the present document is resolved by the WLAN AN. If the WLAN AN does not have access to the GRX, then the WLAN AN should resolve the realm by other means e.g. static look-up table, private local DNS server acting as an authoritative name server for that sub-domain.

### 14.4A Fast Re-authentication NAI

The Fast Re-authentication NAI in both EAP-SIM and EAP-AKA shall take the form of a NAI as specified in clause 2.1 of IETF RFC 4282 [53]. If the 3GPP AAA server does not return a complete NAI, the Fast Re-authentication NAI shall consist of the username part of the fast re-authentication identity as returned from the 3GPP AAA server and the same realm as used in the permanent user identity. If the 3GPP AAA server returns a complete NAI as the re-authentication identity, then this NAI shall be used. The username part of the fast re-authentication identity shall be decorated as described in 14.4 if the Selected PLMN is different from the HPLMN.

NOTE: The permanent user identity is either the root or decorated NAI as defined in clauses 14.3 and 14.4.

EXAMPLE 1: If the fast re-authentication identity returned by the 3GPP AAA Server is 458405627015 and the IMSI is 234150999999999 (MCC = 234, MNC = 15), the Fast Re-authentication NAI for the case when NAI decoration is not used takes the form: 458405627015@wlan.mnc015.mcc234.3gppnetwork.org

EXAMPLE 2: If the fast re-authentication identity returned by the 3GPP AAA Server is "458405627015@aaa1.wlan.mnc015.mcc234.3gppnetwork.org" and the IMSI is 234150999999999 (MCC = 234,



MNC = 15), the Fast Re-authentication NAI for the case when NAI decoration is not used takes the form:  
458405627015@aaa1.wlan.mnc015.mcc234.3gppnetwork.org

EXAMPLE 3: If the fast re-authentication identity returned by the 3GPP AAA Server is 458405627015 and the IMSI is 234150999999999 (MCC = 234, MNC = 15), and the PLMN ID of the Selected PLMN is MCC = 610, MNC = 71, the Fast Re-authentication NAI takes the form: wlan.mnc015.mcc234.3gppnetwork.org  
!458405627015@wlan.mnc071.mcc610.3gppnetwork.org

## 14.5 Temporary identities

The Temporary identities (Pseudonyms and re-authentication identities) shall take the form of a NAI username as specified in clause 2.1 of the IETF RFC 4282 [53].

Temporary identity shall be generated as specified in subclause 6.4.1 of 3GPP TS 33.234 [55]. This part of the temporary identity shall follow the UTF-8 transformation format specified in IETF RFC 2279 [54] except for the following reserved hexadecimal octet value:

FF.

When the temporary identity username is coded with FF, this reserved value is used to indicate the special case when no valid temporary identity exists in the WLAN UE (see 3GPP TS 24.234 [48]). The network shall not allocate a temporary identity with the whole username coded with the reserved hexadecimal value FF.

For EAP-AKA authentication, the username portion of the pseudonym identity shall be prepended with the single digit "2" and the username portion of the fast re-authentication identity shall be prepended with the single digit "4" as specified in sub-clause 4.1.1.7 of IETF RFC 4187 [50].

For EAP-SIM authentication, the username portion of the pseudonym identity shall be prepended with the single digit "3" and the username portion of the fast re-authentication identity shall be prepended with the single digit "5" as specified in sub-clause 4.2.1.7 of IETF RFC 4186 [51].

## 14.6 Alternative NAI

The Alternative NAI shall take the form of a NAI, i.e. 'any\_username@REALM' as specified of IETF RFC 4282 [53]. The Alternative NAI shall not be routable from any AAA server.

The Alternative NAI shall contain a username part which is not derived from the IMSI. The username part shall not be a null string.

The REALM part of the NAI shall be 'unreachable.3gppnetwork.org'.

The result shall be an NAI in the form of:

"<any\_non\_null\_string>@unreachable.3gppnetwork.org"

## 14.7 W-APN

The W-APN is composed of two parts as follows:

- The W-APN Network Identifier; this defines to which external network the PDG is connected.
- The W-APN Operator Identifier; this defines in which PLMN the PDG serving the W-APN is located.

The W-APN Operator Identifier is placed after the W-APN Network Identifier. The W-APN consisting of both the Network Identifier and Operator Identifier corresponds to a FQDN of a PDG; the W-APN has, after encoding as defined in the paragraph below, a maximum length of 100 octets.

The encoding of the W-APN shall follow the Name Syntax defined in IETF RFC 2181 [18], IETF RFC 1035 [19] and IETF RFC 1123 [20]. The W-APN consists of one or more labels. Each label is coded as a one octet length field followed by that number of octets coded as 8 bit ASCII characters. Following IETF RFC 1035 [19] the labels shall consist only of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-). Following IETF RFC 1123 [20],

the label shall begin and end with either an alphabetic character or a digit. The case of alphabetic characters is not significant. The W-APN is not terminated by a length byte of zero.

For the purpose of presentation, a W-APN is usually displayed as a string in which the labels are separated by dots (e.g. "Label1.Label2.Label3").

The W-APN for the support of IMS Emergency calls shall take the form of a common, reserved Network Identifier described in subclause 14.7.1 together with the usual W-APN Operator Identifier as described in subclause 14.7.2.

### 14.7.1 Format of W-APN Network Identifier

The W-APN Network Identifier follows the format defined for APNs in subclause 9.1.1. In addition to what has been defined in subclause 9.1.1 the W-APN Network Identifier shall not contain "w-apn." and not end in ".3gppnetwork.org".

A W-APN Network Identifier may be used to access a service associated with a PDG. This may be achieved by defining:

- a W-APN which corresponds to a FQDN of a PDG, and which is locally interpreted by the PDG as a request for a specific service, or
- a W-APN Network Identifier consisting of 3 or more labels and starting with a Reserved Service Label, or a W-APN Network Identifier consisting of a Reserved Service Label alone, which indicates a PDG by the nature of the requested service. Reserved Service Labels and the corresponding services they stand for shall be agreed between operators who have WLAN roaming agreements.

The W-APN Network Identifier for the support of IMS Emergency calls shall take the form of a common, reserved Network Identifier of the form "sos".

As an example, the W-APN for MCC 345 and MNC 12 is coded in the DNS as:

"sos.w-apn.mnc012.mcc345.pub.3gppnetwork.org".

where "sos" is the W-APN Network Identifier and "mnc012.mcc345.pub.3gppnetwork.org" is the W-APN Operator Identifier.

### 14.7.2 Format of W-APN Operator Identifier

The W-APN Operator Identifier is composed of six labels. The last three labels shall be "pub.3gppnetwork.org". The second and third labels together shall uniquely identify the PLMN. The first label distinguishes the domain name as a W-APN.

For each operator, there is a default W-APN Operator Identifier (i.e. domain name). This default W-APN Operator Identifier is derived from the IMSI as follows:

"w-apn.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org"

where:

"mnc" and "mcc" serve as invariable identifiers for the following digits.

<MNC> and <MCC> are derived from the components of the IMSI defined in subclause 2.2.

Alternatively, the default W-APN Operator Identifier is derived using the MNC and MCC of the VPLMN. See 3GPP TS 24.234 [48] for more information.

The default W-APN Operator Identifier is used in both non-roaming and roaming situations when attempting to translate a W-APN consisting only of a Network Identifier into the IP address of the PDG in the HPLMN.

In order to guarantee inter-PLMN DNS translation, the <MNC> and <MCC> coding used in the "w-apn.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org" format of the W-APN OI shall be:

- <MNC> = 3 digits

- <MCC> = 3 digits

If there are only 2 significant digits in the MNC, one "0" digit shall be inserted at the left side to fill the 3 digits coding of MNC in the W-APN OI.

As an example, the W-APN OI for MCC 345 and MNC 12 is coded in the DNS as:

"w-apn.mnc012.mcc345.pub.3gppnetwork.org".

### 14.7.3 Alternative Format of W-APN Operator Identifier

For situations when the PDG serving the W-APN is located in such network that is not part of the GRX (i.e. the Interoperator IP backbone), the default Operator Identifier described in sub-clause 14.7.2 is not available for use. This restriction originates from the '.3gppnetwork.org' domain, which is only available in GRX DNS for actual use. Thus an alternative format of W-APN Operator Identifier is required for this case.

The Alternative W-APN Operator Identifiers shall be constructed as follows:

"w-apn.<valid operator"s REALM>"

where:

<valid operator"s REALM> corresponds to REALM names owned by the operator hosting the PDG serving the desired W-APN.

REALM names are required to be unique, and are piggybacked on the administration of the Public Internet DNS namespace. REALM names may also belong to the operator of the VPLMN.

As an example, the W-APN OI for the Operator REALM "notareal.com" is coded in the Public Internet DNS as:

"w-apn.notareal.com".

## 14.8 Emergency Realm and Emergency NAI for Emergency Cases

The emergency realm shall be of the form of a home network realm as described in clause 14.2 prefixed with the label "sos." at the beginning of the domain name.

An example of a WLAN emergency NAI realm is:

IMSI in use: 234150999999999;

Where:

MCC = 234;

MNC = 15;

MSIN = 0999999999

Which gives the home network domain name: sos.wlan.mnc015.mcc234.3gppnetwork.org.

The NAI for emergency cases shall be of the form as specified in subclauses 14.3 and 14.4, with the addition of the emergency realm as described above for PLMNs where the emergency realm is supported.

When UE is using I-WLAN as the access network for IMS emergency calls and IMSI is not available, the Emergency NAI shall be an NAI compliant with IETF RFC 4282 [53] consisting of username and realm, either constructed with IMEI or MAC address, as specified in 3GPP TS 33.234 [55]. The exact format shall be:

imei<IMEI>@sos.wlan.mnc<visitedMNC>.mcc<visitedMCC>.3gppnetwork.org

or if IMEI is not available,

mac<MAC>@sos.wlan.mnc<visitedMNC>.mcc<visitedMCC>.3gppnetwork.org

The realm part of the above NAI consists of the realm built using the PLMN ID (visitedMCC + visitedMNC) of the PLMN selected as a result of the network selection procedure, as specified in section 5.2.5.4 of the 3GPP TS 24.234 [48].

The MNC and MCC shall be with 3 digits coded. If there are only 2 significant digits in the MNC, one "0" digit shall be inserted at the left side to fill the 3 digits coding of MNC in the realm of the NAI.

For example, if the IMEI is 219551288888888, and the selected PLMN is with MCC 345 and MNC 12, the Emergency NAI then takes the form of [imei21955128888888@sos.wlan.mnc012.mcc345.3gppnetwork.org](mailto:imei21955128888888@sos.wlan.mnc012.mcc345.3gppnetwork.org).

For example, if the MAC address is 44-45-53-54-00-AB, and the selected PLMN is with MCC 345 and MNC 12, the Emergency NAI then takes the form of [mac4445535400AB@sos.wlan.mnc012.mcc345.3gppnetwork.org](mailto:mac4445535400AB@sos.wlan.mnc012.mcc345.3gppnetwork.org), where the MAC address is represented in hexadecimal format without separators.

## 15 Identification of Multimedia Broadcast/Multicast Service


### 15.1 Introduction

This clause describes the format of the parameters needed to access the Multimedia Broadcast/Multicast service. For further information on the use of the parameters see 3GPP TS 23.246 [52].

### 15.2 Structure of TMGI

Temporary Mobile Group Identity (TMGI) is used within MBMS to uniquely identify Multicast and Broadcast bearer services.

TMGI is composed as shown in figure 15.2.1.



**Figure 15.2.1: Structure of TMGI**

The TMGI is composed of three parts:

- 1) MBMS Service ID consisting of three octets. MBMS Service ID consists of a 6-digit fixed-length hexadecimal number between 000000 and FFFFFFFF. MBMS Service ID uniquely identifies an MBMS bearer service within a PLMN.
- 2) Mobile Country Code (MCC) consisting of three digits. The MCC identifies uniquely the country of domicile of the BM-SC;
- 3) Mobile Network Code (MNC) consisting of two or three digits (depending on the assignment to the PLMN by its national numbering authority). The MNC identifies the PLMN which the BM-SC belongs to. For more information on the use of the TMGI, see 3GPP TS 23.246 [52].

## 15.3 Structure of MBMS SAI

The MBMS Service Area (MBMS SA) is defined in 3GPP TS 23.246 [52]. It comprises of one or more MBMS Service Area Identities (MBMS SAIs), in any case each MBMS SA shall not include more than 256 MBMS SAIs. An MBMS SAI shall identify a group of cells within a PLMN, that is independent of the associated Location/ Routing/Service Area and the physical location of the cell(s). A cell shall be able to belong to one or more MBMS SAs, and therefore is addressable by one or more MBMS SAIs.

The MBMS SAI shall be a decimal number between 0 and 65,535 (inclusive). The value 0 has a special meaning; it shall denote the whole PLMN as the MBMS Service Area and it shall indicate to a receiving RNC/BSS/MCE that all cells reachable by that RNC/BSS/MCE shall be part of the MBMS Service Area.

With the exception of the specific MBMS Service Area Identity with value 0, the MBMS Service Area Identity shall be unique within a PLMN and shall be defined in such a way that all the corresponding cells are MBMS capable.

## 15.4 Home Network Realm

The home network realm shall be in the form of an Internet domain name, e.g. operator.com, as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The home network realm consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

During the MBMS service activation in roaming scenario, the BM-SC in the visited network shall derive the home network domain name from the IMSI as described in the following steps:

1. Take the first 5 or 6 digits, depending on whether a 2 or 3 digit MNC is used (see 3GPP TS 31.102 [27], 3GPP TS 51.011 [66]) and separate them into MCC and MNC; if the MNC is 2 digits then a zero shall be added at the beginning;
2. Use the MCC and MNC derived in step 1 to create the "mnc<MNC>.mcc<MCC>.3gppnetwork.org" realm name;
3. Add the label "mbms." to the beginning of the realm name.

An example of a home realm used in the MBMS roaming case is:

IMSI in use: 234150999999999;

Where:

MCC = 234;

MNC = 15;

MSIN = 0999999999

Which gives the home network realm: mbms.mnc015.mcc234.3gppnetwork.org.

## 15.5 Addressing and identification for Bootstrapping MBMS Service Announcement

The UE needs a Service Announcement Fully Qualified Domain Name (FQDN) to bootstrap MBMS Service Announcement as specified in 3GPP TS 26.346 [105].

The Service Announcement FQDN is composed of six labels. The last three labels shall be "pub.3gppnetwork.org". The second and third labels together shall uniquely identify the PLMN. The first label shall be "mbmsbs".

The Service Announcement FQDN is derived from the IMSI or Visited PLMN Identity as follows:

"mbmsbs.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org"

where:

"mnc" and "mcc" serve as invariable identifiers for the following digits.

- When using the Service Announcement FQDN in a visited network, the <MNC> and <MCC> shall be derived from the visited PLMN Identity as defined in subclause 12.1.
- When using the Service Announcement FQDN in the home network, the <MNC> and <MCC> shall be derived from the components of the IMSI as defined in subclause 2.2.

In order to guarantee inter-PLMN DNS translation, the <MNC> and <MCC> coding used in the "mbmsbs.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org" format of the Service Announcement FQDN shall be:

- <MNC> = 3 digits
- <MCC> = 3 digits

If there are only 2 significant digits in the MNC, one "0" digit shall be inserted at the left side to fill the 3 digits coding of MNC in the Service Announcement FQDN.

As an example, the Service Announcement FQDN for MCC 345 and MNC 12 is coded in the DNS as:

"mbmsbs.mnc012.mcc345.pub.3gppnetwork.org".

---

## 16 Numbering, addressing and identification within the GAA subsystem

### 16.1 Introduction

This clause describes the format of the parameters needed to access the GAA system. For further information on the use of the parameters see 3GPP TS 33.221 [58]. For more information on the ".3gppnetwork.org" domain name and its applicability, see Annex D of the present document.

### 16.2 BSF address

The Bootstrapping Server Function (BSF) address is in the form of a Fully Qualified Domain Name as defined in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The BSF address consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

For 3GPP systems, the UE shall discover the BSF address from the identity information related to the UICC application that is used during the bootstrapping procedure i.e. IMSI for USIM, or IMPI for ISIM, in the following way:

- In the case where the USIM is used in bootstrapping, the BSF address shall be derived as follows:
  1. take the first 5 or 6 digits, depending on whether a 2 or 3 digit MNC is used (see 3GPP TS 31.102 [27]) and separate them into MCC and MNC; if the MNC is 2 digits then a zero shall be added at the beginning;
  2. use the MCC and MNC derived in step 1 to create the "mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org" domain name;
  3. add the label "bsf." to the beginning of the domain.

Example 1: If IMSI in use is "234150999999999", where MCC=234, MNC=15, and MSIN=0999999999, the BSF address would be "bsf.mnc015.mcc234.pub.3gppnetwork.org".

- In the case where ISIM is used in bootstrapping, the BSF address shall be derived as follows:

1. extract the domain name from the IMPI;
2. if the last two labels of the domain name extracted from the IMPI are "3gppnetwork.org":
  - a. the first label is "bsf";
  - b. the next labels are all labels of the domain name extracted from the IMPI apart from the last two labels; and
  - c. the last three labels are "pub.3gppnetwork.org";

Example 2: If the IMPI in use is "23415099999999@ims.mnc015.mcc234.3gppnetwork.org", the BSF address would be "bsf.ims.mnc015.mcc234.pub.3gppnetwork.org".

3. if the last two labels of the domain name extracted from the IMPI are other than the "3gppnetwork.org":
  - a. add the label "bsf." to the beginning of the domain.

Example 3: If the IMPI in use is "user@operator.com", the BSF address would be "bsf.operator.com".

---

## 17 Numbering, addressing and identification within the Generic Access Network

### 17.1 Introduction

This clause describes the format of the parameters needed to access the Generic Access Network (GAN). For further information on the use of the parameters and GAN in general, see 3GPP TS 43.318 [61] and 3GPP TS 44.318 [62]. For more information on the ".3gppnetwork.org" domain name and its applicability, see Annex D of the present document.

### 17.2 Network Access Identifiers

#### 17.2.1 Home network realm

The home network realm shall be in the form of an Internet domain name, e.g. operator.com, as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The home network realm consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

The UE shall derive the home network realm from the IMSI as described in the following steps:

1. take the first 5 or 6 digits, depending on whether a 2 or 3 digit MNC is used (see 3GPP TS 31.102 [27], 3GPP TS 51.011 [66]) and separate them into MCC and MNC; if the MNC is 2 digits then a zero shall be added at the beginning;
2. use the MCC and MNC derived in step 1 to create the "mnc<MNC>.mcc<MCC>.3gppnetwork.org" network realm;
3. add the label "gan." to the beginning of the network realm.

An example of a home network realm is:

IMSI in use: 234150999999999;

Where:

MCC = 234;

MNC = 15;

MSIN = 0999999999,

Which gives the home network realm: gan.mnc015.mcc234.3gppnetwork.org.

NOTE: If it is not possible for the UE to identify whether a 2 or 3 digit MNC is used (e.g. SIM is inserted and the length of MNC in the IMSI is not available in the "Administrative data" data file), it is implementation dependent how the UE determines the length of the MNC (2 or 3 digits).

## 17.2.2 Full Authentication NAI

The Full Authentication NAI in both EAP-SIM and EAP-AKA shall take the form of an NAI as specified in clause 2.1 of IETF RFC 4282 [53]. The format of the Full Authentication NAI shall comply with IETF RFC 4187 [50] when EAP-AKA authentication is used and with IETF RFC 4186 [51], when EAP-SIM authentication is used. The realm used shall be a home network realm as defined in sub-clause 17.2.1.

The result will therefore be an identity of the form:

"0<IMSI>@gan.mnc<MNC>.mcc<MCC>.3gppnetwork.org", for EAP-AKA authentication and  
"1<IMSI>@gan.mnc<MNC>.mcc<MCC>.3gppnetwork.org", for EAP-SIM authentication

EXAMPLE 1: For EAP AKA authentication: If the IMSI is 234150999999999 (MCC = 234, MNC = 15), the Full Authentication NAI takes the form 023415099999999@gan.mnc015.mcc234.3gppnetwork.org.

EXAMPLE 2: For EAP SIM authentication: If the IMSI is 234150999999999 (MCC = 234, MNC = 15), the Full Authentication NAI takes the form 123415099999999@gan.mnc015.mcc234.3gppnetwork.org.

## 17.2.3 Fast Re-authentication NAI

The Fast Re-authentication NAI in both EAP-SIM and EAP-AKA shall take the form of an NAI as specified in clause 2.1 of IETF RFC 4282 [53]. The UE shall use the re-authentication identity received during the previous EAP-SIM or EAP-AKA authentication procedure. If such an NAI contains a realm part then the UE should not modify it, otherwise it shall use a home network realm as defined in sub clause 17.2.1.

The result will therefore be an identity of the form:

"<re-authentication\_ID\_username>@<re-authentication\_ID\_realm> for both EAP-SIM and EAP-AKA authentication when a realm is present in the re-authentication identity received during the previous EAP-SIM or EAP-AKA authentication procedure and

"<re-authentication\_ID\_username>@gan.mnc<MNC>.mcc<MCC>.3gppnetwork.org", for both EAP-SIM and EAP-AKA authentication when a realm is *not* present in the re-authentication identity received during the previous EAP-SIM or EAP-AKA authentication procedure.

EXAMPLE 1: If the re-authentication identity is "12345" and the IMSI is 234150999999999 (MCC = 234, MNC = 15), the Fast Re-authentication NAI takes the form 12345@gan.mnc015.mcc234.3gppnetwork.org

EXAMPLE 2: If the re-authentication identity is "12345@aaa1.gan.mnc015.mcc234.3gppnetwork.org", the Fast Re-authentication NAI takes the form 12345@aaa1.gan.mnc015.mcc234.3gppnetwork.org

## 17.3 Node Identifiers

### 17.3.1 Home network domain name

The home network domain name shall be in the form of an Internet domain name, e.g. operator.com, as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The home network domain name consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

The UE shall derive the home network domain name from the IMSI as described in the following steps:



1. take the first 5 or 6 digits, depending on whether a 2 or 3 digit MNC is used (see 3GPP TS 31.102 [27], 3GPP TS 51.011 [66]) and separate them into MCC and MNC; if the MNC is 2 digits then a zero shall be added at the beginning;
2. use the MCC and MNC derived in step 1 to create the "mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org" domain name;
3. add the label "gan." to the beginning of the domain name.

An example of a home network domain name is:

IMSI in use: 234150999999999;

Where:

MCC = 234;

MNC = 15;

MSIN = 0999999999,

Which gives the home network domain name: gan.mnc015.mcc234.pub.3gppnetwork.org.

NOTE: If it is not possible for the UE to identify whether a 2 or 3 digit MNC is used (e.g. SIM is inserted and the length of MNC in the IMSI is not available in the "Administrative data" data file), it is implementation dependent how the UE determines the length of the MNC (2 or 3 digits).

### 17.3.2 Provisioning GANC-SEGW identifier

The Provisioning GANC-SEGW identifier shall take the form of a fully qualified domain name (FQDN) as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The Provisioning GANC-SEGW identifier consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

If the (U)SIM is not provisioned with the FQDN or IP address of the Provisioning GANC-SEGW, the UE derives an FQDN from the IMSI to identify the Provisioning GANC-SEGW. The UE shall derive such an FQDN as follows:

1. create a domain name as specified in 17.3.1;
2. add the label "psegw." to the beginning of the domain name.

An example of an FQDN for a Provisioning GANC-SEGW is:

IMSI in use: 234150999999999;

Where:

MCC = 234;

MNC = 15;

MSIN = 0999999999,

Which gives the FQDN: psegw.gan.mnc015.mcc234.pub.3gppnetwork.org.

NOTE: If it is not possible for the UE to identify whether a 2 or 3 digit MNC is used (e.g. SIM is inserted and the length of MNC in the IMSI is not available in the "Administrative data" data file), it is implementation dependent how the UE determines the length of the MNC (2 or 3 digits).

### 17.3.3 Provisioning GANC identifier

The Provisioning GANC identifier shall take the form of a fully qualified domain name (FQDN) as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The Provisioning GANC identifier consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF

RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

If the (U)SIM is not provisioned with the FQDN or IP address of the Provisioning GANC, the UE derives an FQDN from the IMSI to identify the Provisioning GANC. The UE shall derive such an FQDN as follows:

1. create a domain name as specified in 17.3.1;
2. add the label "pganc." to the beginning of the domain name.

An example of an FQDN for a Provisioning GANC is:

IMSI in use: 234150999999999;

Where:

MCC = 234;

MNC = 15;

MSIN = 0999999999,

Which gives the FQDN: pganc.gan.mnc015.mcc234.pub.3gppnetwork.org.

NOTE: If it is not possible for the UE to identify whether a 2 or 3 digit MNC is used (e.g. SIM is inserted and the length of MNC in the IMSI is not available in the "Administrative data" data file), it is implementation dependent how the UE determines the length of the MNC (2 or 3 digits).

---

## 18 Addressing and Identification for IMS Service Continuity and Single-Radio Voice Call Continuity

### 18.1 Introduction

This clause describes the format of the parameters needed for the support of IMS Service Continuity. For further information on the use of the parameters see 3GPP TS 23.237 [71] and also 3GPP TS 23.292 [70].

### 18.2 CS Domain Routeing Number (CSRN)

A CS Domain Routeing Number (CSRN) is a number that is used to route a call from the IM CN subsystem to the user in the CS domain. The structure is as defined in sub-clause 3.4.

### 18.3 IP Multimedia Routeing Number (IMRN)

An IP Multimedia Routeing Number (IMRN) is a routable number that points to the IM CN subsystem. In a roaming scenario, the IMRN has the same structure as an international ISDN number (see sub-clause 3.4). The Tel URI format of the IMRN (see IETF RFC 3966 [45]) is treated as a PSI (see sub-clause 13.5) within the IM CN subsystem.

### 18.4 Session Transfer Number (STN)

A Session Transfer Number (STN) is a public telecommunication number, as defined by ITU-T Recommendation E.164 [10] and is used by the UE to request Session Transfer of the media path from PS to CS access.

## 18.5 Session Transfer Identifier (STI)

A Session Transfer Identifier (STI) is a SIP URI or SIP dialogue ID (see IETF RFC 3261 [26] for more information) and is used by the UE to request Session Transfer of a media path.

## 18.6 Session Transfer Number for Single Radio Voice Call Continuity (STN-SR)

The Session Transfer Number for Single Radio Voice Call Continuity (STN-SR) is a public telecommunication number, as defined by ITU-T Recommendation E.164 [10] and is used by the MSC Server to request session transfer of the media path from the PS domain to CS domain.

## 18.7 Correlation MSISDN

A Correlation MSISDN (C-MSISDN) is an MSISDN (see sub-clause 3.3) that is used for correlation of sessions at access transfer and to route a call from the IM CN subsystem to the same user in the CS domain. The C-MSISDN is equal to the MSISDN or the basic MSISDN if multinumbrering option is used (see 3GPP TS 23.008 [2], section 2.1.3) of the CS access. Any MSISDN of a user that can be used for TS11 (telephony) in the CS domain which is not shared by more than one IMS Private Identity in an IMS CN subsystem, can serve as the user's C-MSISDN.

The C-MSISDN is bound to the IMS Private User Identity and is uniquely assigned per IMSI and IMS Private User Identity.

If A-MSISDN is available it shall be used as the C-MSISDN. For the definition of A-MSISDN refer to section 18.9.

## 18.8 Transfer Identifier for CS to PS Single Radio Voice Call Continuity (STI-rSR)

A Session Transfer Identifier for CS to PS Single Radio Voice Call Continuity (STI-rSR) is a SIP URI (see IETF RFC 3261 [26] for more information) and is used by the UE to request access transfer of a media path.

## 18.9 Additional MSISDN

An Additional MSISDN (A-MSISDN) is an MSISDN (see sub-clause 3.3) that is assigned to a user with PS subscription in addition to the already assigned MSISDN(s).

The structure of an A-MSISDN should follow the structure of an MS international ISDN number as defined in section 3.3.

The A-MSISDN shall be able to be used for TS11 (telephony) in the CS domain and shall be uniquely assigned per IMSI.

---

# 19 Numbering, addressing and identification for the Evolved Packet Core (EPC)

## 19.1 Introduction

This clause describes the format of the parameters needed to access the Enhanced Packet Core (EPC). For further information on the use of the parameters see 3GPP TS 23.401 [72] and 3GPP TS 23.402 [68]. For more information on the ".3gppnetwork.org" domain name and its applicability, see Annex D of the present document

## 19.2 Home Network Realm/Domain

The home Network Realm/Domain shall be in the form of an Internet domain name, e.g. operator.com, as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The home Network Realm/Domain consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

The Home Network Realm/Domain shall be in the form of "epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org", where "<MNC>" and "<MCC>" fields correspond to the MNC and MCC of the operator's PLMN. Both the "<MNC>" and "<MCC>" fields are 3 digits long. If the MNC of the PLMN is 2 digits, then a zero shall be added at the beginning.

For example, the Home Network Realm/Domain of an IMSI shall be derived as described in the following steps:

1. take the first 5 or 6 digits, depending on whether a 2 or 3 digit MNC is used (see 3GPP TS 31.102 [27]) and separate them into MCC and MNC; if the MNC is 2 digits then a zero shall be added at the beginning;
2. use the MCC and MNC derived in step 1 to create the "mnc<MNC>.mcc<MCC>.3gppnetwork.org" domain name;
3. add the label "epc" to the beginning of the domain name.

An example of a Home Network Realm/Domain is:

IMSI in use: 234150999999999;

Where:

MCC = 234;

MNC = 15;

MSIN = 0999999999;

Which gives the Home Network Realm/Domain name: epc.mnc015.mcc234.3gppnetwork.org.

NOTE: If it is not possible for a UE to identify whether a 2 or 3 digit MNC is used (e.g. USIM is inserted and the length of MNC in the IMSI is not available in the "Administrative data" data file), it is implementation dependent how the UE determines the length of the MNC (2 or 3 digits).

## 19.3 3GPP access to non-3GPP access interworking

### 19.3.1 Introduction

This subclause describes the format of the UE identification needed to access the 3GPP EPC from both 3GPP and non-3GPP accesses.

The NAI is generated respectively by the S-GW at the S5/S8 reference point and by the UE for the S2a, S2b and S2c reference points.

The NAI shall be generated based on the IMSI or, when UE is performing emergency attach and IMSI is not available or not authenticated, on the IMEI (see subclause 19.3.6).

For further information on the use of the parameters see the subclauses below and 3GPP TS 33.402 [69] and 3GPP TS 29.273 [78].

### 19.3.2 Root NAI

The Root NAI shall take the form of an NAI, and shall have the form username@realm as specified in clause 2.1 of IETF RFC 4282 [53].

When the username part is the IMSI, the realm part of Root NAI shall be built according to the following steps:

1. Convert the leading digits of the IMSI, i.e. MNC and MCC, into a domain name, as described in subclause 19.2.
2. Prefix domain name with the label of "nai".

The resulting realm part of the Root NAI will be in the form:

"@nai.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org"

When including the IMSI, the Root NAI is prepended with a specific leading digit when used for EAP authentication (see 3GPP TS 29.273 [78]) in order to differentiate between EAP authentication method. The leading digit is:

- "0" when used in EAP-AKA, as specified in IETF RFC 4187 [50]
- "6" when used in EAP-AKA', as specified in IETF RFC 5448 [82].

The resulting Root NAI will be in the form:

"0<IMSI>@nai.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org" when used for EAP AKA authentication

"6<IMSI>@nai.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org" when used for EAP AKA' authentication

For example, if the IMSI is 234150999999999 (MCC = 234, MNC = 15), the Root NAI takes the form 023415099999999@nai.epc.mnc015.mcc234.3gppnetwork.org for EAP AKA authentication and the Root NAI takes the form [623415099999999@nai.epc.mnc015.mcc234.3gppnetwork.org](mailto:623415099999999@nai.epc.mnc015.mcc234.3gppnetwork.org) for EAP AKA' authentication.

The NAI sent in the Mobile Node Identifier field in PMIPv6 shall not include the digit prepended in front of the IMSI based username that is described above.

### 19.3.3 Decorated NAI

The Decorated NAI shall take the form of a NAI and shall have the form 'homerealm!username@otherrealm' or 'Visitedrealm!homerealm!username@otherrealm' as specified in clause 2.7 of the IETF RFC 4282 [53].

The realm part of Decorated NAI consists of 'otherrealm', see the IETF RFC 4282 [53]. 'Homerealm' is the realm as specified in subclause 19.2, using the HPLMN ID ('homeMCC' + 'homeMNC'). 'Visitedrealm' is the realm built using the VPLMN ID ('VisitedMCC' + 'VisitedMNC'), 'Otherrealm' is:

- the realm built using the PLMN ID (visitedMCC + visited MNC) if the service provider selected as a result of the service provider selection (see 3GPP TS 24.302 [77]) has a PLMN ID; or
- a domain name of a service provider if the selected service provider does not have a PLMN ID (3GPP TS 24.302 [77]).

When the username part of Decorated NAI includes the IMSI and the service provider has a PLMN ID, the Decorated NAI shall be built following the same steps as specified for Root NAI in subclause 19.3.2.

The result will be a decorated NAI of the form:

- nai.epc.mnc<homeMNC>.mcc<homeMCC>.3gppnetwork.org  
!0<IMSI>@nai.epc.mnc<visitedMNC>.mcc<visitedMCC>.3gppnetwork.org for EAP AKA authentication.
- or
- nai.epc.mnc<homeMNC>.mcc<homeMCC>.3gppnetwork.org  
!6<IMSI>@nai.epc.mnc<visitedMNC>.mcc<visitedMCC>.3gppnetwork.org for EAP AKA' authentication.

For example, if the service provider has a PLMN ID and the IMSI is 234150999999999 (MCC = 234, MNC = 15) and the PLMN ID of the Selected PLMN is MCC = 610, MNC = 71, then the Decorated NAI takes the form either as:

- nai.epc.mnc015.mcc234.3gppnetwork.org!023415099999999@nai.epc.mnc071.mcc610.3gppnetwork.org for EAP AKA authentication
- or

- nai.epc.mnc015.mcc234.3gppnetwork.org!6234150999999999@nai.epc.mnc071.mcc610.3gppnetwork.org for EAP AKA' authentication.

For example, if the domain name of a service provider is 'realm.org' and IMSI-based permanent username is used, then the Decorated NAI takes the form either as:

- nai.epc.mnc<homeMNC>.mcc<homeMCC>.3gppnetwork.org !0<IMSI>@realm.org for EAP AKA authentication
- or
- nai.epc.mnc<homeMNC>.mcc<homeMCC>.3gppnetwork.org !6<IMSI>@realm.org for EAP AKA' authentication.

If the UE has selected a WLAN that directly interworks with a service provider in the Equivalent Visited Service Providers (EVSP) list provided by the RPLMN, see 3GPP TS 23.402 [77], subclause 4.8.2b, then the decorated NAI is constructed to include the realm of this service provider and the realm of RPLMN. If the domain name of a service provider is 'realm.org' and IMSI-based permanent username is used, then the Decorated NAI with double decoration takes the form either as:

- nai.epc.mnc<rplmnMNC>.mcc<rplmnMCC>.3gppnetwork.org !nai.epc.mnc<homeMNC>.mcc<homeMCC>.3gppnetwork.org!0<IMSI>@realm.org for EAP AKA authentication
- or
- nai.epc.mnc<rplmnMNC>.mcc<rplmnMCC>.3gppnetwork.org !nai.epc.mnc<homeMNC>.mcc<homeMCC>.3gppnetwork.org!6<IMSI>@realm.org for EAP AKA' authentication.

When the username part of Decorated NAI includes a Fast Re-authentication NAI, the Decorated NAI shall be built following the same steps as specified for the Fast Re-authentication NAI in subclause 19.3.4.

When the username part of Decorated NAI includes a Pseudonym, the Decorated NAI shall be built following the same steps as specified for the Pseudonym identity in subclause 19.3.5.

### 19.3.4 Fast Re-authentication NAI

The Fast Re-authentication NAI shall take the form of a NAI as specified in clause 2.1 of IETF RFC 4282 [53]. If the 3GPP AAA server does not return a complete NAI, the Fast Re-authentication NAI shall consist of the username part of the fast re-authentication identity as returned from the 3GPP AAA server and the same realm as used in the permanent user identity. If the 3GPP AAA server returns a complete NAI as the re-authentication identity, then this NAI shall be used. The username part of the fast re-authentication identity shall be decorated as described in 19.3.3 if the Selected PLMN is different from the HPLMN.

For EAP-AKA authentication, the username portion of the fast re-authentication identity shall be prepended with the single digit "4" as specified in sub-clause 4.1.1.7 of IETF RFC 4187 [50].

For EAP AKA', see IETF RFC 5448 [82], the Fast Re-authentication NAI shall comply with IETF RFC 4187 [50] except that the username part of the NAI shall be prepended with single digit "8".

**NOTE:** The permanent user identity is either the Root NAI or Decorated NAI as defined in clauses 19.3.2 and 19.3.3, respectively.

**EXAMPLE 1:** If the fast re-authentication identity returned by the 3GPP AAA Server is 358405627015, the IMSI is 234150999999999 (MCC = 234, MNC = 15) and EAP-AKA is used, the Fast Re-authentication NAI for the case when NAI decoration is not used takes the form:  
4358405627015@nai.epc.mnc015.mcc234.3gppnetwork.org

**EXAMPLE 2:** If the fast re-authentication identity returned by the 3GPP AAA Server is "358405627015@aaa1.nai.epc.mnc015.mcc234.3gppnetwork.org", the IMSI is 234150999999999 (MCC = 234, MNC = 15) and EAP-AKA' is used, the Fast Re-authentication NAI for the case when NAI decoration is not used takes the form:  
8358405627015@aaa1.nai.epc.mnc015.mcc234.3gppnetwork.org

**EXAMPLE 3:** If the fast re-authentication identity returned by the 3GPP AAA Server is 358405627015, the IMSI is 234150999999999 (MCC = 234, MNC = 15), the PLMN ID of the Selected PLMN is MCC = 610, MNC = 71 and EAP-AKA is used, the Fast Re-authentication NAI takes the form:  
nai.epc.mnc015.mcc234.3gppnetwork.org  
!4358405627015@nai.epc.mnc071.mcc610.3gppnetwork.org.

### 19.3.5 Pseudonym Identities

The pseudonym shall take the form of an NAI, as specified in sub-clause 2.1 of IETF RFC 4282 [53].

The pseudonym shall be generated as specified in sub-clause 6.4.1 of 3GPP TS 33.234 [55]. This part of the pseudonym shall follow the UTF-8 transformation format specified in IETF RFC 2279 [54] except for the following reserved hexadecimal octet value:

FF

When the pseudonym username is coded with FF, this reserved value is used to indicate the special case when no valid temporary identity exists in the UE (see 3GPP TS 24.234 [48] for more information). The network shall not allocate a temporary identity with the whole username coded with the reserved hexadecimal value FF.

The username portion of the pseudonym identity shall be prepended with the single digit "2" as specified in sub-clause 4.1.1.7 of IETF RFC 4187 [50] for EAP-AKA. For EAP AKA', see IETF RFC 5448 [82], the pseudonym NAI shall comply with IETF RFC 4187 [50] except that the username part of the NAI shall be prepended with single digit "7".

**NOTE:** The permanent user identity is either the Root NAI or Decorated NAI as defined in sub-clauses 19.3.2 and 19.3.3, respectively.

**EXAMPLE 1:** For EAP AKA, if the pseudonym returned by the 3GPP AAA Server is 258405627015 and the IMSI is 234150999999999 (MCC = 234, MNC = 15), the pseudonym NAI for the case when NAI decoration is not used takes the form: 258405627015@nai.epc.mnc015.mcc234.3gppnetwork.org

**EXAMPLE 2:** For EAP AKA', if the pseudonym returned by the 3GPP AAA Server is 758405627015 and the IMSI is 234150999999999 (MCC = 234, MNC = 15), the pseudonym NAI for the case when NAI decoration is not used takes the form: 758405627015@nai.epc.mnc015.mcc234.3gppnetwork.org

**EXAMPLE 3:** For EAP AKA, if the pseudonym returned by the 3GPP AAA Server is 258405627015 and the IMSI is 234150999999999 (MCC = 234, MNC = 15), and the PLMN ID of the Selected PLMN is MCC = 610, MNC = 71, the pseudonym NAI takes the form:  
nai.epc.mnc015.mcc234.3gppnetwork.org!  
258405627015@nai.epc.mnc071.mcc610.3gppnetwork.org

**EXAMPLE 4:** For EAP AKA', if the pseudonym returned by the 3GPP AAA Server is 758405627015 and the IMSI is 234150999999999 (MCC = 234, MNC = 15), and the PLMN ID of the Selected PLMN is MCC = 610, MNC = 71, the pseudonym NAI takes the form:  
nai.epc.mnc015.mcc234.3gppnetwork.org!  
758405627015@nai.epc.mnc071.mcc610.3gppnetwork.org

### 19.3.6 Emergency NAI for Limited Service State

This subclause describes the format of the UE identification needed to access the 3GPP EPC from both 3GPP and non-3GPP accesses, when UE is performing emergency attach and IMSI is not available or not authenticated. For more information, see sections 4.6.1 and 5.2 of 3GPP TS 23.402 [68].

The Emergency NAI for Limited Service State shall take the form of an NAI, and shall have the form username@realm as specified in clause 2.1 of IETF RFC 4282 [53]. The exact format shall be:

imei<IMEI>@sos.invalid

NOTE: The top level domain ".invalid" is a reserved top level domain, as specified in IETF RFC 2606 [64], and is used here due to the fact that this NAI never needs to be resolved for routing (as specified in 3GPP TS 23.402 [68]).

or

mac<MAC>@sos.invalid

For example, if the IMEI is 219551288888888, the Emergency NAI for Limited Service State then takes the form of imei219551288888888@sos.invalid.

For example, if the MAC address is 44-45-53-54-00-AB, the Emergency NAI for Limited Service State then takes the form of [mac4445535400AB@sos.invalid](mailto:mac4445535400AB@sos.invalid), where the MAC address is represented in hexadecimal format without separators.

### 19.3.7 Alternative NAI

The Alternative NAI shall take the form of a NAI, i.e. 'any\_username@REALM' as specified of IETF RFC 4282 [53]. The Alternative NAI shall not be routable from any AAA server.

The Alternative NAI shall contain a username part which is not derived from the IMSI. The username part shall not be a null string.

The REALM part of the NAI shall be 'unreachable.3gppnetwork.org'.

The result shall be an NAI in the form of:

```
"<any_non_null_string>@unreachable.3gppnetwork.org"
```

## 19.4 Identifiers for Domain Name System procedures

### 19.4.1 Introduction

This clause describes Domain Name System (DNS) related identifiers used by the procedures specified in 3GPP TS 29.303 [73].

The DNS identifiers for APNs for legacy systems (as defined in clause 9), RAIs (as defined in clause C.1), GSNs (as defined in clause C.2) and RNCs (as defined in clause C.3) in the present document use the top level domain ".gprs" and have a similar purpose and function as those described below. These clauses are still valid and DNS records based on these and the below types of identifiers are expected to coexist in an operator's network for the purpose of backwards compatibility and interworking with legacy networks.

The APN as defined in clause 9 is used also in EPC to identify the access network to be used for a specific PDN connection or PDP Context. In addition, the APN Network Identifier (APN-NI) part of the APN as defined in subclause 9.1.1 of the present document may be used to access a service associated with a PDN-GW or GGSN. This is achieved by defining an APN which in addition to being usable to select a PDN-GW or GGSN is locally interpreted by the PDN-GW or GGSN as a request for a specific service.

For DNS procedures defined in 3GPP TS 29.303 [73], an APN-FQDN derived from a given APN is used instead of the APN itself as defined in subclause 19.4.2.2. For all other purposes, including communication between EPC nodes and to the UE, the APN format defined in clause 9 is used. In order to support backwards compatibility with existing GPRS/PS roaming using the Gn/Gp interfaces, the APN as specified in clause 9 of the present document may also be used for the DNS procedures as defined in 3GPP TS 23.060 [3].



## 19.4.2 Fully Qualified Domain Names (FQDNs)

### 19.4.2.1 General

The encoding of any identifier used as part of a Fully Qualified Domain Name (FQDN) shall follow the Name Syntax defined in IETF RFC 2181 [18], IETF RFC 1035 [19] and IETF RFC 1123 [20]. An FQDN consists of one or more labels. Each label is coded as a one octet length field followed by that number of octets coded as 8 bit ASCII characters. Following IETF RFC 1035 [19] the labels shall consist only of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-). Following IETF RFC 1123 [20], the label shall begin and end with either an alphabetic character or a digit. The case of alphabetic characters is not significant. Identifiers are not terminated by a length byte of zero.

**NOTE:** A length byte of zero is added by the querying entity at the end of the FQDN before interrogating a DNS server.

For the purpose of presentation, identifiers are usually displayed as a string in which the labels are separated by dots (e.g. "Label1.Label2.Label3").

### 19.4.2.2 Access Point Name FQDN (APN-FQDN)

#### 19.4.2.2.1 Structure

The Access Point Name FQDN (APN-FQDN) is derived from an APN as follows. The APN consists of an APN Network Identifier (APN-NI) and an APN Operator Identifier (APN-OI), which are as defined in subclause 9.1.1 and 9.1.2 of the present document.

If an APN is constructed using the default APN-OI, the APN-FQDN shall be obtained from the APN by inserting the labels "apn.epc." between the APN-NI and the default APN - OI, and by replacing the label ".gprs" at the end of the default APN-OI with the labels ".3gppnetwork.org".

**EXAMPLE1:** For an APN of internet.mnc015.mcc234.gprs, the derived APN-FQDN is internet.apn.epc.mnc015.mcc234.3gppnetwork.org

If an APN is constructed using the APN-OI Replacement field (as defined in 3GPP TS 23.060 [3] and 3GPP TS 23.401 [72]), the APN-FQDN shall be obtained from the APN by inserting the labels "apn.epc." between the label "mnc<MNC>" and its preceding label, and by replacing the label ".gprs" at the end of the APN-OI Replacement field with the labels ".3gppnetwork.org".

**EXAMPLE 2:** If an APN-OI Replacement field is province1.mnc015.mcc234.gprs and an APN-NI is internet, the derived APN-FQDN is internet.province1.apn.epc.mnc015.mcc234.3gppnetwork.org


19.4.2.2.2 Void

19.4.2.2.3 Void

19.4.2.2.4 Void

### 19.4.2.3 Tracking Area Identity (TAI)

The Tracking Area Identity (TAI) consists of a Mobile Country Code (MCC), Mobile Network Code (MNC), and Tracking Area Code (TAC). It is composed as shown in figure 19.4.2.3.1.



**Figure 19.4.2.3.1: Structure of the Tracking Area Identity (TAI)**

The TAI is composed of the following elements:

- Mobile Country Code (MCC) identifies the country in which the PLMN is located. The value of the MCC is the same as the three digit MCC contained in the IMSI;
- Mobile Network Code (MNC) is a code identifying the PLMN in that country. The value of the MNC is the same as the two or three digit MNC contained in the IMSI;
- Tracking Area Code (TAC) is a fixed length code (of 2 octets) identifying a Tracking Area within a PLMN. This part of the tracking area identification shall be coded using a full hexadecimal representation. The following are reserved hexadecimal values of the TAC:
  - 0000, and
  - FFFE.

NOTE: The above reserved values are used in some special cases when no valid TAI exists in the MS (see 3GPP TS 24.301 [90] for more information).

A subdomain name can be derived from the TAI. This shall be done by adding the label "tac" to the beginning of the Home Network Realm/Domain (see subclause 19.2) and encoding the TAC as a sub-domain. This is called the TAI FQDN..

The TAI FQDN shall be constructed as follows:

```
tac-lb<TAC-low-byte>.tac-hb<TAC-high-byte>.tac.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

The TAC is a 16-bit integer. The <TAC-high-byte> is the hexadecimal string of the most significant byte in the TAC and the <TAC-low-byte > is the hexadecimal string of the least significant byte. If there are less than 2 significant digits in <TAC-high-byte> or <TAC-low-byte >, "0" digit(s) shall be inserted at the left side to fill the 2 digit coding.

#### 19.4.2.4 Mobility Management Entity (MME)

A Mobility Management Entity (MME) within an operator's network is identified using a MME Group ID (MMEGI), and an MME Code (MMEC).

A subdomain name shall be derived from the MNC and MCC by adding the label "mme" to the beginning of the Home Network Realm/Domain (see subclause 19.2).

The MME node FQDN shall be constructed as:

```
mmecc<MMEC>.mmegei<MMEGI>.mme.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

Where <MMEC> and <MMEGI> are the hexadecimal strings of the MMEC and MMEGI.

An MME pool FQDN shall be constructed as:

```
mmegei<MMEGI>.mme.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

If there are less than 2 significant digits in <MMEC>, "0" digit(s) shall be inserted at the left side to fill the 2 digit coding. If there are less than 4 significant digits in <MMEGI>, "0" digit(s) shall be inserted at the left side to fill the 4 digit coding.

### 19.4.2.5 Routing Area Identity (RAI) - EPC

The Routing Area Identity (RAI) consists of a RAC, LAC, MNC and MCC.

A subdomain name for use by core network nodes based on RAI shall be derived from the MNC and MCC by adding the label "rac" to the beginning of the Home Network Realm/Domain (see subclause 19.2).

The RAI FQDN shall be constructed as:

```
rac<RAC>.lac<LAC>.rac.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

<RAC> and <LAC> shall be Hex coded digits representing the LAC and RAC codes respectively.

If there are less than 4 significant digits in <RAC> or <LAC>, one or more "0" digit(s) is/are inserted at the left side to fill the 4 digit coding.

Note: Above subdomain is for release 8 core network nodes to allow DNS records other than A/AAAA records. The subdomain name in Annex C.2 are still used for existing A/AAAA records for pre-Release 8 nodes and are also still used for backward compatibility.

### 19.4.2.6 Serving GPRS Support Node (SGSN) within SGSN pool

A specific SGSN within an operator's network is identified using the RAI FQDN (subclause 19.4.2.5) and the Network Resource Identifier (NRI) (see 3GPP TS 23.236 [23]). Such an identifier can be used by a target MME or SGSN node to connect to the source SGSN node.

The SGSN FQDN shall be constructed as:

```
nri-sgsn<NRI>.rac<RAC>.lac<LAC>.rac.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

<NRI> shall be Hex coded digits representing the NRI code of the SGSN.

If there are less than 4 significant digits in <NRI>, one or more "0" digit(s) is/are inserted at the left side to fill the 4 digit coding. Coding for other fields is the same as in Section 19.4.2.5.

When a target MME constructs the FQDN of the source SGSN in the case of SGSN pooling, it should derive the NRI from the 8-bit MME Code received in the GUTI from the UE. However, if the length of the NRI, e.g., X, which is configured in the MME is less than 8 bits, then the MME should use only the most significant X bits of the MME Code as the NRI within the SGSN FQDN.

Note: Above subdomain is for release 8 core network nodes to allow DNS records other than A/AAAA records. The subdomain name in Annex C.2 are still used for existing A/AAAA records for pre-Release 8 nodes and are also still used for backward compatibility. .

### 19.4.2.7 Target RNC-ID for U-TRAN

In the special case of a UTRAN target RNC a possible SGSN that can control that RNC can be identified by RNC-ID. This identifier can be used for SRNS relocation with a U-TRAN target RNC.

A subdomain name for use by core network nodes based on RNC-ID shall be derived from the MNC and MCC by adding the label "rnc" to the beginning of the Home Network Realm/Domain (see subclause 19.2).

The RNC FQDN shall be constructed as:

```
rnc<RNC>.rnc.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

<RNC> shall be Hex coded digits representing the RNC-ID code of the RNC.

If there are less than 4 significant digits in <RNC>, one or more "0" digit(s) is/are inserted at the left side to fill the 4 digit coding.

NOTE: Above subdomain is for release 8 core network nodes to allow DNS records other than A/AAAA records. The subdomain name in Annex C.3 are still used for existing A/AAAA records for pre-Release 8 nodes and are still used for backward compatibility. However, RNC-ID in Annex C.3 was originally intended for the case where only one SGSN controlled an RNC-ID and gave the SGSN IP address. The usage for the above RNC FQDN is potentially broader and can target an SGSN pool.

### 19.4.2.8 DNS subdomain for operator usage in EPC

The EPC nodes DNS subdomain (DNS zone) shall be derived from the MNC and MCC by adding the label "node" to the beginning of the Home Network Realm/Domain (see subclause 19.2) and shall be constructed as:

```
node.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

This DNS subdomain is formally placed into the operator's control. 3GPP shall never take this DNS subdomain back or any zone cut/subdomain within it for any purpose. As a result the operator can safely provision any DNS records it chooses under this subdomain without concern about future 3GPP standards encroaching on the DNS names within this zone.

### 19.4.2.9 ePDG FQDN and Visited Country FQDN for non-emergency bearer services

#### 19.4.2.9.1 General

The ePDG Fully Qualified Domain Name (ePDG FQDN), for non-emergency bearers services, shall be constructed using one of the following formats, as specified in subclause 4.5.4 of 3GPP TS 23.402 [68]:

- Operator Identifier based ePDG FQDN;
- Tracking/Location Area Identity based ePDG FQDN;
- the ePDG FQDN configured in the UE by the HPLMN.

NOTE: The ePDG FQDN configured in the UE can have a different format than those specified in the following subclauses.

The Visited Country FQDN is used by a roaming UE to determine whether the visited country mandates the selection of an ePDG in this country (see subclause 4.5.4.5 of 3GPP TS 23.402 [68]). The Visited Country FQDN shall be constructed as specified in subclause 19.4.2.9.4.

#### 19.4.2.9.2 Operator Identifier based ePDG FQDN

The ePDG Fully Qualified Domain Name (ePDG FQDN) contains an Operator Identifier that shall uniquely identify the PLMN where the ePDG is located. The ePDG FQDN is composed of seven labels. The last three labels shall be "pub.3gppnetwork.org". The third and fourth labels together shall uniquely identify the PLMN. The first two labels shall be "epdg.epc". The result of the ePDG FQDN will be:

```
"epdg.epc.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org"
```

In the roaming case, the UE can utilise the services of the VPLMN or the HPLMN (see 3GPP TS 23.402 [68] and 3GPP TS 24.302 [77]). In this case, the Operator Identifier based ePDG FQDN shall be constructed as described above, but using the MNC and MCC of the VPLMN or the HPLMN.

In order to guarantee inter-PLMN DNS translation, the <MNC> and <MCC> coding used in the "epdg.epc.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org" format of the Operator Identifier based ePDG FQDN shall be:

- <MNC> = 3 digits
- <MCC> = 3 digits

If there are only 2 significant digits in the MNC, one "0" digit shall be inserted at the left side to fill the 3 digits coding of MNC in the ePDG FQDN.

As an example, the Operator Identifier based ePDG FQDN for MCC 345 and MNC 12 is coded in the DNS as:

```
"epdg.epc.mnc012.mcc345.pub.3gppnetwork.org".
```

NOTE: The replacement string returned by the DNS of the visited country, when the visited country mandates the selection of an ePDG in this country, takes the form of an Operator Identifier based ePDG FQDN. The DNS response contains one Operator Identifier based ePDG FQDN per VPLMN in this country. See 3GPP TS 24.302 [77].

#### 19.4.2.9.3 Tracking/Location Area Identity based ePDG FQDN

The Tracking/Location Area Identity based ePDG FQDN is used to support location based ePDG selection within a PLMN.

The Tracking Area Identity based ePDG FQDN and the Location Area Identity based ePDG FQDN shall be constructed respectively as:

```
"tac-lb<TAC-low-byte>.tac-hb<TAC-high-byte>.tac.epdg.epc.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org"
```

and

```
"lac<LAC>.epdg.epc.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org"
```

where

- the <MNC> and <MCC> shall identify the PLMN where the ePDG is located and shall be encoded as
  - <MNC> = 3 digits
  - <MCC> = 3 digits

If there are only 2 significant digits in the MNC, one "0" digit shall be inserted at the left side to fill the 3 digits coding of MNC in the ePDG FQDN.

- the <TAC>, together with the <MCC> and <MNC> shall identify the Tracking Area Identity the UE is located in.

The TAC is a 16-bit integer. The <TAC-high-byte> is the hexadecimal string of the most significant byte in the TAC and the <TAC-low-byte > is the hexadecimal string of the least significant byte. If there are less than 2 significant digits in <TAC-high-byte> or <TAC-low-byte >, "0" digit(s) shall be inserted at the left side to fill the 2 digit coding;

- the <LAC>, together with the <MCC> and <MNC> shall identify the Location Area Identity the UE is located in.

The <LAC> shall be hexadecimal coded digits representing the LAC; if there are less than 4 significant digits in <LAC>, one or more "0" digit(s) is/are inserted at the left side to fill the 4 digit coding;

As examples,

- the Tracking Area Identity based ePDG FQDN for the TAC H'0B21, MCC 345 and MNC 12 is coded in the DNS as:

```
" tac-lb21.tac-hb0b.tac.epdg.epc.mnc012.mcc345.pub.3gppnetwork.org"
```

- the Location Area Identity based ePDG FQDN for the LAC H'0B21, MCC 345 and MNC 12 is coded in the DNS as:

```
" lac0b21.epdg.epc.mnc012.mcc345.pub.3gppnetwork.org"
```

#### 19.4.2.9.4 Visited Country FQDN

The Visited Country FQDN, used by a roaming UE to determine whether the visited country mandates the selection of an ePDG in this country, shall be constructed as described below.

The Visited Country FQDN shall contain a MCC that uniquely identifies the country in which the UE is located.

The Visited Country FQDN is composed of seven labels. The last three labels shall be "pub.3gppnetwork.org". The fourth label shall be "visited-country". The third label shall uniquely identify the MCC of the visited country. The first and second labels shall be "epdg.epc". The resulting Visited Country FQDN will be:

```
"epdg.epc.mcc<MCC>.visited-country.pub.3gppnetwork.org"
```

The <MCC> coding used in this FQDN shall be:

- <MCC> = 3 digits

As an example, the Visited Country FQDN for MCC 345 is coded in the DNS as:

```
"epdg.epc.mcc345.visited-country.pub.3gppnetwork.org".
```

## 19.4.2.9A ePDG FQDN for emergency bearer services

### 19.4.2.9A.1 General

The ePDG FQDN used for the selection of an ePDG supporting emergency bearer services shall be constructed using one of the following formats, as specified in subclause 4.5.4a of 3GPP TS 23.402 [68] and 3GPP TS 24.302 [77]:

- an ePDG FQDN dynamically generated by the UE as specified in subclause 19.4.2.9A.2;
- an ePDG FQDN configured in the UE by the HPLMN, which may have a different format than the one specified in the following subclause.

### 19.4.2.9A.2 ePDG FQDN for dynamic selection of an ePDG supporting emergency bearer services

The ePDG FQDN used for the dynamic selection of an ePDG supporting emergency bearer services shall be constructed as:

```
"sos.epdg.epc.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org"
```

where the fourth and fifth labels together shall identify the PLMN where the ePDG is located.

The <MNC> and <MCC> shall be coded as specified for the Operator Identifier based ePDG FQDN in subclause 19.4.2.9.

As an example, the ePDG FQDN for MCC 345 and MNC 12 is coded in the DNS as:

```
"sos.epdg.epc.mnc012.mcc345.pub.3gppnetwork.org".
```

### 19.4.2.10 Global eNodeB-ID for eNodeB

The Global eNodeB-ID is used to identify eNodeBs globally which is composed of the concatenation of MCC, MNC and the eNodeBID. The MCC and MNC are the same as included in the E-UTRAN Cell Global Identifier (ECGI) (see subclause 19.6).

A subdomain name shall be derived from the MNC and MCC by adding the label "enb" to the beginning of the Home Network Realm/Domain (see subclause 19.2).

The Global eNodeB-ID FQDN shall be constructed as:

```
enb<eNodeB-ID>.enb.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

The <eNodeB-ID> shall be coded using a full hexadecimal representation. If there are less than 4 significant digits in <eNodeB-ID>, "0" digit(s) shall be inserted at the left side to fill the 4 digit coding.

### 19.4.2.11 Local Home Network identifier

The Local Home Network identifier uniquely identifies a local home network. For the definition of a local home network see 3GPP TS 23.060 [3] and 3GPP TS 23.401 [72].

A subdomain name shall be derived from the MNC and MCC from the visited network by adding the label "lhn" to the beginning of the Home Network Realm/Domain (see subclause 19.2).

The Local Home Network-ID FQDN shall be constructed as:

lhn<LHN name>.lhn.epc.mnc<MNC>.mcc<MCC>.3gppnetwork.org

The <LHN-name> length and content is an operator choice. The labels shall follow the rules specified in sub-clause 19.4.2.1.

### 19.4.3 Service and Protocol service names for 3GPP

A list of standardized "service-parms" names is required to identify a "service" as defined in section 6.5 of IETF RFC 3958 [74].

The following table defines the names to be used in the procedures specified in 3GPP TS 29.303 [73]:

**Table 19.4.3.1: List of 'app-service' and 'app-protocol' names**

Description	IETF RFC 3958 section 6.5 'app-service' name	IETF RFC 3958 section 6.5 'app-protocol' name
PGW and interface types supported by the PGW	x-3gpp-pgw	x-s5-gtp , x-s5-pmip, x-s8-gtp , x-s8-pmip, x-s2a-pmip, x-s2a-mipv4, x-s2a-gtp, x-s2b-pmip, x-s2b-gtp, x-s2c-dsmip, x-gn, x-gp See NOTE.
SGW and interface types supported by the SGW	x-3gpp-sgw	x-s5-gtp , x-s5-pmip, x-s8-gtp , x-s8-pmip, x-s11, x-s12, x-s4, x-s1-u, x-s2a-pmip, x-s2b-pmip See NOTE.
GGSN	x-3gpp-ggsn	x-gn, x-gp See NOTE.
SGSN	x-3gpp-sgsn	x-gn, x-gp, x-s4,x-s3, x-s16, x-sv, x-nqprime See NOTE.
MME and interface types supported by the MME	x-3gpp-mme	x-s10, x-s11, x-s3, x-s6a, x-s1-mme, x-gn, x-gp, x-sv, x-nq See NOTE.
MSC Server	x-3gpp-msc	x-sv
NOTE: When using Dedicated Core Networks, the character string "+ue-<ue usage type>" shall be appended to the 'app-protocol' name, for the interfaces applicable to Dedicated Core Networks, where <ue-usage-type> contains one or more UE usage type values. See 3GPP TS 29.303 [73] and 3GPP TS 29.272 [108]. Example: x-s5-gtp+ue-<ue usage type> If multiple UE usage type values are embedded in the "+ue-<ue usage type>", they shall be separated by the symbol ".", e.g. "+ue-1.3.4.20" as specified in IETF RFC 3958 [74].		

NOTE 1: The formats follow the experimental format as specified in IETF RFC 3958 [74]. For example, to find the S8 PMIP interfaces on a PGW the Service Parameter of "3gpp-pgw:x-s8-pmip" would be used as input in the procedures defined in IETF RFC 3958 [74].

NOTE 2: Currently 'app-service' names identify 3GPP node type and 'app-protocol' identify 3GPP interfaces, which differs from more common usage of S-NAPTR where app-protocol is used for transport protocol. Type of nodes (i.e PGW, SGW, SGSN, MME, MSC Server etc) and interfaces (i.e. S11, S5, S8, Sv, etc.) follow the standard names from 3GPP TS 23.401 [72], 3GPP TS 29.060 [6] and 3GPP TS 23.216 [92] with prefix "x-" added.

NOTE 3: x-gn denotes an intra-PLMN interface using GTPv1-C, x-gp denotes a inter-PLMN interface using GTPv1-C.

NOTE 4: The app-service of x-3gpp-pgw with app-protocols x-gn or x-gp identifies the co-located GGSN function on a PGW. The app-service of x-3gpp-ggsn with app-protocols x-gn or x-gp identifies a GGSN function that is not co-located with a PGW.

NOTE 5: The app-service of x-3gpp-msc with app-protocol x-sv identifies the MSC Sv interface service.


## 19.5 Access Network Identity

A trusted non-3GPP access network used by the UE to access EPS can be identified using the Access Network Identity. The Access Network Identity is used as an input parameter in the EPS security procedures as specified in 3GPP TS 33.402 [69]. The format and signalling of the parameter between the network and the UE is specified in 3GPP TS 24.302 [77] and the format and signalling of this parameter between access network and core network is specified in 3GPP TS 29.273 [78].

The encoding of the Access Network Identity shall be specified within 3GPP, but the Access Network Identity definition for each non-3GPP access network is under the responsibility of the corresponding standardisation organisation respectively.

## 19.6 E-UTRAN Cell Identity (ECI) and E-UTRAN Cell Global Identification (ECGI)

The E-UTRAN Cell Global Identification (ECGI) shall be composed of the concatenation of the PLMN Identifier (PLMN-Id) and the E-UTRAN Cell Identity (ECI) as shown in figure 19.6.1 and shall be globally unique:



**Figure 19.6.1: Structure of E-UTRAN Cell Global Identification**

The ECI shall be of fixed length of 28 bits and shall be coded using full hexadecimal representation. The exact coding of the ECI is the responsibility of each PLMN operator.

For more details on ECI and ECGI, see 3GPP TS 36.413 [84].

## 19.7 Identifiers for communications with packet data networks and applications

### 19.7.1 Introduction

This subclause describes external identifiers used to facilitate communications with packet data networks and applications (e.g. Machine Type Communication (MTC) applications on the external network/MTC servers) as specified in 3GPP TS 23.682 [98].

### 19.7.2 External Identifier

An External Identifier identifies a subscription associated to an IMSI. A subscription associated to an IMSI may have one or several External Identifier(s) that are stored in the HSS.

The External Identifier is used at:

- the Tsp reference point;



- the T4 reference point;
- the S6m reference point;
- the Gi/SGi reference point;

The External Identifier shall have the form `username@realm` as specified in clause 2.1 of IETF RFC 4282 [53].

The username part format of the External Identifier shall contain a Local Identifier as specified in 3GPP TS 23.682 [98]. The realm part format of the External Identifier shall contain a Domain Identifier as specified in 3GPP TS 23.682 [98]. As specified in subclause 4 of IETF RFC 4282 [53], the Domain Identifier shall be a duly registered Internet domain name. The combination of Local Identifier and Domain Identifier makes the External Identifier globally unique.

The result of the External Identifier form is:

"<Local Identifier>@<Domain Identifier>"

An example of an External Identifier is:

Local Identifier in use: "123456789";

Domain Identifier = "domain.com";

Which gives the External Identifier as:

123456789@domain.com

## 19.8 TWAN Operator Name

The TWAN Operator Name identifies the TWAN operator when the TWAN is not operated by a mobile operator.


The TWAN Operator Name shall be encoded as a realm in the form of an Internet domain name, e.g. `operator.com`, as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The TWAN Operator Name consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

NOTE: The TWAN Operator Name is encoded as a dotted string.

## 19.9 IMSI-Group Identifier

IMSI-Group Identifier is a network internal globally unique ID which identifies a set of IMSIs (e.g. MTC devices) from a given network that are grouped together for one or more specific group related services. It is used e.g. for group specific NAS level congestion control (see 3GPP TS 23.401 [72]).

An IMSI-Group Identifier shall be composed as shown in figure 19.9-1.



**Figure 19.9-1: Structure of IMSI-Group Identifier**

IMSI-Group Identifier is composed of four parts:

- 1) Group Service Identifier, identifies up to 32 services (4 Octets) for which the IMSI-Group Identifier is valid.

- 2) Mobile Country Code (MCC) consisting of three digits. The MCC identifies uniquely the country of domicile of the mobile subscriber;
- 3) Mobile Network Code (MNC) consisting of two or three digits. The MNC identifies the home PLMN of the mobile subscriber. The length of the MNC (two or three digits) depends on the value of the MCC. A mixture of two and three digit MNC codes within a single MCC area is not recommended and is outside the scope of this specification.
- 4) the Local Group Id is assigned by the network operator and may have a length of up to 10 octets.

Two different IMSI-Group Identifier values with MCC/MNC values that point to the same PLMN shall have two different Local Group Ids.

## 19.10 Presence Reporting Area Identifier (PRA ID)

The Presence Reporting Area Identifier (PRA ID) is used to identify a Presence Reporting Area (PRA).

PRAs can be used for reporting changes of UE presence in a PRA, e.g. for policy control or charging decisions. See 3GPP TS 23.401 [72], 3GPP TS 23.060 [3] and 3GPP TS 23.203 [107].

A PRA is composed of a short list of TAs/RAs, or eNBs and/or cells/SAs in a PLMN. A PRA can be:

- either a "UE-dedicated PRA", defined in the subscriber profile;
- or a "Core Network predefined PRA", pre-configured in MME/S4-SGSN.

PRA IDs used to identify "Core Network predefined PRAs" shall not be used for identifying "UE-dedicated PRAs".

The same PRA ID may be used for different UEs to identify different "UE-dedicated PRAs", i.e. PRA IDs may overlap between different UEs, while identifying different "UE-dedicated PRAs".

The PRA ID shall be encoded as an integer on 3 octets. The most significant bit of the PRA ID shall be set to 0 for UE-dedicated PRA and shall be to 1 for Core Network predefined PRA.

---

# 20 Addressing and Identification for IMS Centralized Services

## 20.1 Introduction

This clause describes the format of the parameters needed specifically for IMS Centralized Services (ICS). For further information on the use of ICS parameters, see 3GPP TS 23.292 [70].

## 20.2 UE based solution

In this solution, the UE is provisioned with an ICS specific client that simply reuses IMS registration as defined in 3GPP TS 23.228 [24]. Therefore, ICS capable UE shall reuse the identities defined in clause 13.

## 20.3 Network based solution

### 20.3.1 General

In this solution the MSC Server enhanced for ICS performs a special IMS registration on behalf of the UE. Thus, the MSC Server enhanced for ICS shall use a Private User Identity and Temporary Public User Identity that are different to those defined in clause 13 (see 3GPP TS 23.292 [70], sub-clause 4.6.2 for more information). Furthermore, the MSC Server enhanced for ICS derives a Conference Factory URI that is known to the home IMS. These are defined in the following sub-clauses.

## 20.3.2 Home network domain name

The home network domain name shall be in the form of an Internet domain name, e.g. operator.com, as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The home network domain name consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

The MSC Server enhanced for ICS shall derive the home network domain name from the subscriber's IMSI as described in the following steps:

1. Take the first 5 or 6 digits, depending on whether a 2 or 3 digit MNC is used (see 3GPP TS 31.102 [27]) and separate them into MCC and MNC; if the MNC is 2 digits then a zero shall be added at the beginning.
2. Use the MCC and MNC derived in step 1 to create the "mnc<MNC>.mcc<MCC>.3gppnetwork.org" domain name.
3. Add the label "ics." to the beginning of the domain.

An example of a home network domain name is:

IMSI in use: 234150999999999;

where:

- MCC = 234;
- MNC = 15; and
- MSIN = 0999999999,

which gives the home network domain name: ics.mnc015.mcc234.3gppnetwork.org

## 20.3.3 Private User Identity

The Private User Identity shall take the form of an NAI, and shall have the form "username@realm" as specified in clause 2.1 of IETF RFC 4282 [53].

The MSC Server enhanced for ICS shall derive the Private User Identity from the subscriber's IMSI as follows:

1. Use the whole string of digits as the username part of the private user identity; and
2. convert the leading digits of the IMSI, i.e. MNC and MCC, into a domain name, as described in sub-clause 20.3.2.

The result will be a Private User Identity of the form "<IMSI>@ics.mnc<MNC>.mcc<MCC>.3gppnetwork.org". For example if the IMSI is 234150999999999 (MCC = 234, MNC = 15), the private user identity then takes the form 234150999999999@ics.mnc015.mcc234.3gppnetwork.org

## 20.3.4 Public User Identity

The Public User Identity shall take the form of a SIP URI (see IETF RFC 3261 [26]), and shall have the form "sip:username@domain".

The MSC Server enhanced for ICS shall derive the Public User Identity from the subscriber's IMSI. The Public User Identity shall consist of the string "sip:" appended with a username and domain portion equal to the IMSI derived Private User Identity described in sub-clause 20.3.3. An example using the same example IMSI from sub-clause 20.3.3 can be found below:

EXAMPLE: "sip:234150999999999@ics.mnc015.mcc234.3gppnetwork.org".

## 20.3.5 Conference Factory URI

The Conference Factory URI shall take the form of a SIP URI (see IETF RFC 3261 [26]) with a host portion set to the home network domain name as described in subclause 20.3.2 prefixed with "conf-factory.". An example using the same example IMSI from sub-clause 20.3.2 can be found below:

EXAMPLE: "sip:conf-factory.ics.mnc015.mcc234.3gppnetwork.org".

The user portion of the SIP URI is optional and implementation specific.

---

# 21 Addressing and Identification for Dual Stack Mobile IPv6 (DSMIPv6)

## 21.1 Introduction

This clause describes the format of the parameters needed by the UE to use Dual Stack Mobile IPv6 (DSMIPv6 as specified in 3GPP TS 23.327 [76] and 3GPP TS 23.402 [68].

## 21.2 Home Agent – Access Point Name (HA-APN)

### 21.2.1 General

The HA-APN is composed of two parts as follows:

- The HA-APN Network Identifier; this defines to which external network the HA is connected.
- The HA-APN Operator Identifier; this defines in which PLMN the HA serving the HA-APN is located.

The HA-APN Operator Identifier is placed after the HA-APN Network Identifier. The HA-APN consisting of both the Network Identifier and Operator Identifier corresponds to a FQDN of a HA; the HA-APN has, after encoding as defined in the paragraph below, a maximum length of 100 octets.

The encoding of the HA-APN shall follow the Name Syntax defined in IETF RFC 2181 [18], IETF RFC 1035 [19] and IETF RFC 1123 [20]. The HA-APN consists of one or more labels. Each label is coded as a one octet length field followed by that number of octets coded as 8 bit ASCII characters. Following IETF RFC 1035 [19] the labels shall consist only of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-). Following IETF RFC 1123 [20], the label shall begin and end with either an alphabetic character or a digit. The case of alphabetic characters is not significant. The HA-APN is not terminated by a length byte of zero.

For the purpose of presentation, a HA-APN is usually displayed as a string in which the labels are separated by dots (e.g. "Label1.Label2.Label3").

### 21.2.2 Format of HA-APN Network Identifier

The HA-APN Network Identifier follows the format defined for APNs in subclause 9.1.1. In addition to what has been defined in subclause 9.1.1 the HA-APN Network Identifier shall not contain "ha-apn." or "w-apn." and not end in ".3gppnetwork.org".

A HA-APN Network Identifier may be used to access a service associated with a HA. This may be achieved by defining:

- a HA-APN which corresponds to a FQDN of a HA, and which is locally interpreted by the HA as a request for a specific service, or
- a HA-APN Network Identifier consisting of 3 or more labels and starting with a Reserved Service Label, or a HA-APN Network Identifier consisting of a Reserved Service Label alone, which indicates a HA by the nature of the requested service. Reserved Service Labels and the corresponding services they stand for shall be agreed between operators who have roaming agreements.

As an example, the HA-APN for MCC 345 and MNC 12 is coded in the DNS as:

```
"internet.ha-apn.mnc012.mcc345.pub.3gppnetwork.org".
```

where "internet" is the HA-APN Network Identifier and "mnc012.mcc345.pub.3gppnetwork.org" is the HA-APN Operator Identifier.

### 21.2.3 Format of HA-APN Operator Identifier

The HA-APN Operator Identifier is composed of six labels. The last three labels shall be "pub.3gppnetwork.org". The second and third labels together shall uniquely identify the PLMN. The first label distinguishes the domain name as a HA-APN.

For each operator, there is a default HA-APN Operator Identifier (i.e. domain name). This default HA-APN Operator Identifier is derived from the IMSI as follows:

```
"ha-apn.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org"
```

where:

"mnc" and "mcc" serve as invariable identifiers for the following digits.

<MNC> and <MCC> are derived from the components of the IMSI defined in subclause 2.2.

Alternatively, the default HA-APN Operator Identifier is derived using the MNC and MCC of the VPLMN.

In order to guarantee inter-PLMN DNS translation, the <MNC> and <MCC> coding used in the "ha-apn.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org" format of the HA-APN OI shall be:

- <MNC> = 3 digits
- <MCC> = 3 digits

If there are only 2 significant digits in the MNC, one "0" digit shall be inserted at the left side to fill the 3 digits coding of MNC in the HA-APN OI.

As an example, the HA-APN OI for MCC 345 and MNC 12 is coded in the DNS as:

```
"ha-apn.mnc012.mcc345.pub.3gppnetwork.org".
```

---

## 22 Addressing and identification for ANDSF

### 22.1 Introduction

This clause describes the format of the parameters needed by the UE to use Access Network Discovery and Selection Function (ANDSF) as specified in 3GPP TS 23.402 [68].

### 22.2 ANDSF Server Name (ANDSF-SN)

#### 22.2.1 General

ANDSF Server Name (ANDSF-SN) is used by UE to discover ANDSF Server in the network.

#### 22.2.2 Format of ANDSF-SN

The ANDSF-SN is composed of six labels. The last three labels shall be "pub.3gppnetwork.org". The second and third labels together shall uniquely identify the PLMN. The first label shall be "andsf".

The ANDSF-SN is derived from the IMSI or Visited PLMN Identity as follows:

"andsf.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org"

where:

"mnc" and "mcc" serve as invariable identifiers for the following digits.

- When contacting Visited ANDSF (V-ANDSF), the <MNC> and <MCC> shall be derived from the Visited PLMN Identity as defined in subclause 12.1.
- When contacting Home ANDSF (H-ANDSF), the <MNC> and <MCC> shall be derived from the components of the IMSI defined in subclause 2.2.

In order to guarantee inter-PLMN DNS translation, the <MNC> and <MCC> coding used in the "andsf.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org" format of the ANDSF-SN shall be:

- <MNC> = 3 digits
- <MCC> = 3 digits

If there are only 2 significant digits in the MNC, one "0" digit shall be inserted at the left side to fill the 3 digits coding of MNC in the ANDSF-SN.

As an example, the ANDSF-SN OI for MCC 345 and MNC 12 is coded in the DNS as:

"andsf.mnc012.mcc345.pub.3gppnetwork.org".

---

## 23 Numbering, addressing and identification for the OAM System

### 23.1 Introduction

This clause describes some information needed to access the OAM system as specified in TS 36.300 [91]. For more information on the ".3gppnetwork.org" domain name and its applicability, see Annex D of the present document.

### 23.2 OAM System Realm/Domain

The OAM System Realm/Domain shall be in the form of an Internet domain name, e.g. operator.com, as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The OAM System Realm/Domain consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

The OAM System Realm/Domain shall be in the form of "oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org", where "<MNC>" and "<MCC>" fields correspond to the MNC and MCC of the operator's PLMN. Both the "<MNC>" and "<MCC>" fields are 3 digits long. If the MNC of the PLMN is 2 digits, then a zero shall be added at the beginning.

For example, the OAM System Realm/Domain of an IMSI shall be derived as described in the following steps:

1. take the first 5 or 6 digits, depending on whether a 2 or 3 digit MNC is used (see 3GPP TS 31.102 [27]) and separate them into MCC and MNC; if the MNC is 2 digits then a zero shall be added at the beginning;
2. use the MCC and MNC derived in step 1 to create the "mnc<MNC>.mcc<MCC>.3gppnetwork.org" domain name;
3. add the label "oam" to the beginning of the domain name.

An example of an OAM System Realm/Domain is:

IMSI in use: 234150999999999;

Where:

MCC = 234;

MNC = 15;

MSIN = 0999999999;

Which gives the OAM System Realm/Domain name: oam.mnc015.mcc234.3gppnetwork.org.

NOTE: If it is not possible for a Relay Node to identify whether a 2 or 3 digit MNC is used (e.g. USIM is inserted and the length of MNC in the IMSI is not available in the "Administrative data" data file), it is implementation dependent how the Relay Node determines the length of the MNC (2 or 3 digits).

## 23.3 Identifiers for Domain Name System procedures

### 23.3.1 Introduction

This clause describes Domain Name System (DNS) related identifiers used by the procedures specified in 3GPP TS 29.303 [73].

### 23.3.2 Fully Qualified Domain Names (FQDNs)

#### 23.3.2.1 General

See subclause 19.4.2.1.

#### 23.3.2.2 Relay Node Vendor-Specific OAM System

As part of the startup procedure, relay nodes (see 3GPP TS 36.300 [91], sub-clause 4.7) needs to discover its Operations and Maintenance (OAM) system. A relay node vendor-specific OAM system within an operator's network is identified using the relay node type allocation code from IMEI or IMEISV (IMEI-TAC), MNC and MCC from IMSI and in some cases also tracking area code information associated to the eNB serving the relay node.

A subdomain name for use by EUTRAN OAM system nodes shall be derived from the MNC and MCC by adding the label "eutran" to the beginning of the OAM System Realm/Domain (see sub-clause 23.2).

The vendor-specific relay node OAM system FQDN shall be constructed as following:

- tac-lb<TAC-low-byte>.tac-hb<TAC-high-byte>.imei-tac<IMEI-TAC>.eutran-rn.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org

The IMEI-TAC is 8 decimal digits (see sub-clause 6.2).

NOTE: IMEI-TAC is used for the type allocation code from IMEI or IMEISV instead of TAC in this sub-clause in order to separate it from the tracking area code (TAC).

The TAC is a 16 bit integer. <TAC-high-byte> is the hexadecimal string of the most significant byte in the TAC and <TAC-low-byte > is the hexadecimal string of the least significant byte. If there are less than 2 significant digits in <TAC-high-byte> or <TAC-low-byte >, "0" digit(s) shall be inserted at the left side to fill the 2 digit coding.

#### 23.3.2.3 Multi-vendor eNodeB Plug-and Play Vendor-Specific OAM System

##### 23.3.2.3.1 General

This clause describes the Fully Qualified Domain Names (FQDNs) used in Multi Vendor Plug and Connect (MvPnC) procedures (see 3GPP TS 32.508 [102]).

The FQDNs used in MvPnC shall be in the form of an Internet domain name and follow the general encoding rules specified in section 19.4.2.1.

The format of FQDNs used in MvPnC shall follow the "<vendor ID>.<system>.<OAM realm>" pattern.

NOTE: "<vendor ID>.<system>.oam" represents the <service\_id> shown in the first row of table E.1.

The <vendor ID> label is optional and is only used in the operator deployments where multiple instances of a particular network entity type are not provided by the same vendor. If present, the <vendor ID> label shall be in the form "vendor<ViD>", where <ViD> field corresponds to the ID of the vendor.

The format of the ViD is vendor specific.

The details of the <system> label are specified in the clauses below.

#### 23.3.2.3.2 Certification Authority server

The Certification Authority server (CA/RA) FQDN shall be derived as follows. The "cara" <system> label is added in front of the operator's OAM realm domain name:

```
cara.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

If particular operator deployment scenarios where there are multiple CA/RA servers (one per vendor), the <vendor ID> label is added in front of the "cara" label:

```
vendor<ViD>.cara.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

An example of a CA/RA FQDN is:

```
MCC = 123;
```

```
MNC = 45;
```

```
ViD = abcd;
```

which gives the CA/RA FQDN: "cara.oam.mnc045.mcc123.3gppnetwork.org" and "vendorabcd.cara.mnc045.mcc123.3gppnetwork.org".

#### 23.3.2.3.3 Security Gateway

The Security Gateway (SeGW) FQDN shall be derived as follows. The "segw" <system> label is added in front of the operator's OAM realm domain name:

```
segw.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

If particular operator deployment scenarios where there are multiple Security Gateways (one per vendor), the <vendor ID> label is added in front of the "segw" label:

```
vendor<ViD>.segw.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

An example of a SeGW FQDN is:

```
MCC = 123;
```

```
MNC = 45;
```

```
ViD = abcd;
```

which gives the SeGW FQDN: "segw.oam.mnc045.mcc123.3gppnetwork.org" and "vendorabcd.segw.mnc045.mcc123.3gppnetwork.org".

#### 23.3.2.3.4 Element Manager

The Element Manager (EM) FQDN shall be derived as follows. The "em" <system> label is added in front of the operator's OAM realm domain name:



```
em.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

If particular operator deployment scenarios where there are multiple Element Managers (one per vendor), the <vendor ID> label is added in front of the "em" label:

```
vendor<ViD>.em.oam.mnc<MNC>.mcc<MCC>.3gppnetwork.org
```

An example of a EM FQDN is:

```
MCC = 123;
```

```
MNC = 45;
```

```
ViD = abcd;
```

which gives the EM FQDN: "em.oam.mnc045.mcc123.3gppnetwork.org" and "vendorabcd.em.mnc045.mcc123.3gppnetwork.org".

## 24 Numbering, addressing and identification for Proximity-based Services (ProSe)

### 24.1 Introduction

This clause describes the format of the parameters used for ProSe. For further information on the use of the parameters see 3GPP TS 23.303 [103].

### 24.2 ProSe Application ID

#### 24.2.1 General

The ProSe Application ID is composed of two parts as follows:

- The ProSe Application ID Name, which is described in its entirety by a data structure characterized by different levels e.g, broad-level business category (Level 0) / business sub-category (Level 1) / business name (Level 2) / shop ID (Level 3).
- The PLMN ID, which corresponds to the PLMN that assigned the ProSe Application ID Name.

The PLMN ID is placed before the ProSe Application ID Name as shown in Figure 24.2.1. The PLMN ID and the ProSe Application ID Name shall be separated by a dot.




Figure 24.2.1-1: Structure of ProSe Application ID

#### 24.2.2 Format of ProSe Application ID Name in ProSe Application ID

The ProSe Application ID Name is composed of a string of labels. These labels represent hierarchical levels and shall be separated by dots (e.g. "Label1.Label2.Label3"). The ProSe Application ID Name shall contain at least one label. The first label on the left shall be "ProSeApp".

NOTE: The hierarchical structure and the content of the ProSe Application ID Name are outside the scope of 3GPP.

Any label in the ProSe Application ID Name except the first label on the left ("ProSeApp") can be wild carded. A wild card label is represented as "\*",

EXAMPLE: A ProSe Application ID Name used to discover nearby Italian restaurants could be "ProSeApp.Food.Restaurants.Italian".

### 24.2.3 Format of PLMN ID in ProSe Application ID

The PLMN ID shall uniquely identify the PLMN of the ProSe Function that has assigned the ProSe Application ID. The PLMN ID is composed of two labels which shall be separated by a dot as follows:

"mcc<MCC>.mnc<MNC>"

where:

"mcc" and "mnc" serve as invariable identifiers for the following digits.

<MCC> contains the MCC (Mobile Country Code) of the ProSe Function that has assigned the ProSe Application ID.

<MNC> contains the MNC (Mobile Network Code) of the ProSe Function that has assigned the ProSe Application ID.

In order to guarantee inter-PLMN operability, the <MCC> and the <MNC> shall be represented by 3 digits. If there are only 2 significant digits in the MNC, one "0" digit is inserted at the left side of the MNC to form the <MNC> in the "mnc<MNC>" label.

EXAMPLE: The PLMN ID for MCC 345 and MNC 12 will be "mcc345.mnc012".

### 24.2.4 Usage of wild cards in place of PLMN ID in ProSe Application ID

If the scope of the ProSe Application ID is country-specific, the PLMN ID part in the ProSe Application ID shall be replaced by "mcc<MCC>.mnc\*" with <MCC> set to the MCC of the corresponding country.

NOTE: Handling of the case when a country has been allocated more than one MCC value is outside the scope of 3GPP.

If the scope of the ProSe Application ID is global, the PLMN ID part in the ProSe Application ID shall be replaced by "mcc\*.mnc\*".

EXAMPLE: For a ProSe Application ID specific to a country with MCC 345, the PLMN ID part will be replaced by "mcc345.mnc\*".

### 24.2.5 Informative examples of ProSe Application ID

Examples of ProSe Application IDs following the format defined in the previous subclauses are provided for information below.

EXAMPLE 1: "mcc345.mnc012.ProSeApp.Food.Restaurants.Italian"

EXAMPLE 2: "mcc300.mnc165.ProSeApp.Shops.Sports.Surfing"

EXAMPLE 3: "mcc300.mnc165.ProSeApp.\*.Sports.Surfing"

EXAMPLE 4: "mcc208.mnc\*.ProSeApp.Shops.Food.Wine"

EXAMPLE 5: "mcc\*.mnc\*.ProSeApp.Food.Restaurants.Coffee"

## 24.3 ProSe Application Code

### 24.3.1 General


The ProSe Application Code as described in 3GPP TS 23.303 [103] is composed of the following two parts:

- The PLMN ID of the ProSe Function that assigned the ProSe Application Code, i.e. Mobile Country Code (MCC) and Mobile Network Code (MNC).
- A temporary identity that corresponds to the ProSe Application ID Name. The temporary identity is allocated by the ProSe Function and it may contain a metadata index. The internal structure of the temporary identity is not specified in 3GPP.

The ProSe Application Code shall have a fixed length of 184 bits.

### 24.3.2 Format of PLMN ID in ProSe Application Code

The PLMN ID in the ProSe Application Code is composed as shown in Figure 24.3.2-1:



**Figure 24.3.2-1: Structure of PLMN ID in ProSe Application Code**

The PLMN-ID is composed of four parts:

- Scope indicates whether the MNC, or both the MCC and the MNC, or neither are wild carded in the ProSe Application ID associated with the ProSe Application Code, with the following mapping:
  - 00 global scope.
  - 01 reserved.
  - 10 country-specific scope.
  - 11 PLMN-specific scope.
- Spare bit that shall be set to 0 and shall be ignored if set to 1.
- E bit indicates whether the MCC and the MNC of the ProSe Function that has assigned the ProSe Application Code are included in the PLMN ID in ProSe Application Code, with the following mapping:
  - 0 Neither MCC nor MNC is included.
  - 1 MCC and MNC included.
- When present, the MCC and the MNC shall each have a fixed length of 10 bits and shall be coded as the binary representation of their decimal value.

In this release, the MCC and the MNC of the ProSe Function that has assigned the ProSe Application Code shall always be included in the PLMN ID in ProSe Application Code. The E bit shall always be set to 1.

### 24.3.3 Format of temporary identity in ProSe Application Code

The temporary identity in the ProSe Application Code is a bit string whose value is allocated by the ProSe Function. The length of the temporary identity in the ProSe Application Code is equal to:

- 180 bits when the E bit of the PLMN ID in the ProSe Application Code is set to 0.
- 160 bits when the E bit of the PLMN ID in the ProSe Application Code is set to 1.

The temporary identity in the ProSe Application Code shall contain a metadata index to reflect the current metadata version if dynamic metadata is used when allocating the ProSe Application Code. The content, position and length of metadata index is operator specific.

In this release, the MCC and the MNC of the ProSe Function that has assigned the ProSe Application Code are always included in the PLMN ID in ProSe Application Code. The length of the temporary identity in the ProSe Application Code shall always be equal to 160 bits.

### 24.3A ProSe Application Code Prefix

The ProSe Application Code Prefix as described in 3GPP TS 23.303 [103] is to be used with a ProSe Application Code Suffix. The ProSe Application Code Prefix has the same composition and format as the ProSe Application Code, with the following exceptions:

- The temporary identity part of the ProSe Application Code Prefix is of variable length. The length of the temporary identity part shall be incremented in multiple of 8, with a minimum size of 8 bits and a maximum size of 152 bits.
- The sum of the length of the ProSe Application Code Prefix and the length of the ProSe Application Code Suffix shall be 184 bits.

### 24.3B ProSe Application Code Suffix

The ProSe Application Code Suffix as described in 3GPP TS 23.303 [103] is an identifier to be appended to a ProSe Application Code Prefix. The ProSe Application Code Suffix is of variable length. The length of the ProSe Application Code Suffix shall be incremented in multiple of 8, with a minimum size of 8 bits and a maximum size of 152 bits. The sum of the length of the ProSe Application Code Prefix and the length of the ProSe Application Code Suffix shall be 184 bits.

## 24.4 EPC ProSe User ID

### 24.4.1 General

The EPC ProSe User ID as described in 3GPP TS 23.303 [103] identifies the UE registered for EPC-level ProSe Discovery in the context of the ProSe Function.

### 24.4.2 Format of EPC ProSe User ID

The EPC ProSe User ID is a bit string whose value is allocated by the ProSe Function. The length of the EPC ProSe User ID is equal to 32 bits.

## 24.5 Home PLMN ProSe Function Address

The Home PLMN ProSe Function address is in the form of a Fully Qualified Domain Name as defined in IETF RFC 1035 [19] and IETF RFC 1123 [20]. This address consists of six labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

For 3GPP systems, if not pre-configured on the UE or provisioned by the network, the UE shall derive the Home PLMN ProSe Function address from the IMSI as described in the following steps:

1. Take the first 5 or 6 digits, depending on whether a 2 or 3-digit MNC is used (see 3GPP TS 31.102 [27]) and separate them into MCC and MNC; if the MNC is 2-digit MNC then a zero shall be added at the beginning.
2. Use the MCC and MNC derived in step 1 to create the "mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org" domain name.
3. Add the label "prose-function." to the beginning of the domain.

An example of a Home PLMN ProSe Function address is:

IMSI in use: 234150999999999;

where:

- MCC = 234;
- MNC = 15; and
- MSIN = 0999999999,

which gives the following Home PLMN ProSe Function address:

"prose-function.mnc015.mcc234.pub.3gppnetwork.org".

## 24.6 ProSe Restricted Code

The ProSe Restricted Code as described in 3GPP TS 23.303 [103] is a single 64-bit identifier that corresponds to one or more Restricted ProSe Application User ID(s) (as defined in 3GPP TS 23.303 [103]). The exact content of the identifier is not specified in 3GPP.

## 24.7 ProSe Restricted Code Prefix

The ProSe Restricted Code Prefix as described in 3GPP TS 23.303 [103] is a ProSe Restricted Code which to be used with a ProSe Restricted Code Suffix. It shall have the same size and format as the ProSe Restricted Code.

## 24.8 ProSe Restricted Code Suffix

The ProSe Restricted Code Suffix as described in 3GPP TS 23.303 [103] is an identifier to be appended to a ProSe Restricted Code Prefix. Depending on the application configuration, the bit length of a ProSe Restricted Code Suffix varies from 8 to 120, incremented by multiples of 8.

## 24.9 ProSe Query Code

The ProSe Query Code as described in 3GPP TS 23.303 [103] is a ProSe Restricted Code allocated by the ProSe Function to the Discoverer UE for restricted ProSe direct discovery model B. The format of the ProSe Query Code is the same as that of the ProSe Restricted Code defined in subclause 24.6.

## 24.10 ProSe Response Code

The ProSe Response Code as described in 3GPP TS 23.303 [103] is a ProSe Restricted Code allocated by the ProSe Function to the Discoveree UE for restricted ProSe direct discovery model B. The format of the ProSe Response Code is the same as that of the ProSe Restricted Code defined in subclause 24.6.

## 24.11 ProSe Discovery UE ID

### 24.11.1 General

The ProSe Discovery UE ID as described in 3GPP TS 23.303 [103] identifies the UE participating in restricted ProSe direct discovery in the context of the ProSe Function.

It is composed of two parts as follows:

- The PLMN ID of the ProSe Function that assigned the ProSe Discovery UE ID, i.e. Mobile Country Code (MCC) and Mobile Network Code (MNC).
- A temporary identifier allocated by the ProSe Function. The content of the temporary identifier is not specified in 3GPP.

### 24.11.2 Format of ProSe Discovery UE ID

The ProSe Discovery UE ID is a bit string whose value is allocated by the ProSe Function. The length of the ProSe Discovery UE ID is equal to 64 bits and the format is described as shown in Figure 24.11.2-1.




Figure 24.11.2-1: Structure of ProSe Discovery UE ID

## 24.12 ProSe UE ID

The ProSe UE ID as described in 3GPP TS 23.303 [103] identifies the link layer address used for ProSe direct communication by a ProSe-enabled Public Safety UE.

The format of ProSe UE ID is a bit string whose length is equal to 24 bits.

## 24.13 ProSe Relay UE ID

The ProSe Relay UE ID as described in 3GPP TS 23.303 [103] identifies the link layer address used for ProSe direct communication by a ProSe UE-to-network relay UE.

The format of ProSe Relay UE ID is a bit string whose length is equal to 24 bits.

## 24.14 User Info ID

The User Info ID as described in 3GPP TS 23.303 [103] is used to identify the user information to be discovered for public safety use case. The value of User Info ID is allocated either by the operator or 3rd-party public safety provider application server.

The format of the User Info ID is a 48-bit bit-string.

## 24.15 Relay Service Code

The Relay Service Code as described in 3GPP TS 23.303 [103] identifies a connectivity service the ProSe UE-to-network relay provides.

The format of the Relay Service Code is a 24-bit bit-string.

## 24.16 Discovery Group ID

The Discovery Group ID as described in 3GPP TS 23.303 [103] identifies a group of Public Safety users that are affiliated for Group Member Discovery.

The format of the Discovery Group ID is a 24-bit bit-string.

---

# 25 Identification of Online Charging System

## 25.1 Introduction

This clause describes the format of the home network domain name of the Online Charging System (OCS), needed to access the Online Charging System. For further information on the use of this home network domain name, see 3GPP TS 29.212 [106]. For more information on the ".3gppnetwork.org" domain name and its applicability, see Annex D of the present document.

## 25.2 Home network domain name

The home network domain name of the OCS shall be in the form of an Internet domain name, e.g. operator.com, as specified in IETF RFC 1035 [19] and IETF RFC 1123 [20]. The home network domain of the OCS consists of one or more labels. Each label shall consist of the alphabetic characters (A-Z and a-z), digits (0-9) and the hyphen (-) in accordance with IETF RFC 1035 [19]. Each label shall begin and end with either an alphabetic character or a digit in accordance with IETF RFC 1123 [20]. The case of alphabetic characters is not significant.

If the home network domain of the OCS is not known (e.g. through an available static address or through its reception from another node), it shall be:

- in the form of "ocs.mnc<MNC>.mcc<MCC>.3gppnetwork.org", where "<MNC>" and "<MCC>" fields correspond to the MNC and MCC of the operator's PLMN to which the OCS belongs. Both the "<MNC>" and "<MCC>" fields are 3 digits long. If the MNC of the PLMN is 2 digits, then a zero shall be added at the beginning; and
- derived from the subscriber's IMSI, as described in the following steps:
  1. take the first 5 or 6 digits, depending on whether a 2 or 3 digit MNC is used (see 3GPP TS 31.102 [27]) and separate them into MCC and MNC; if the MNC is 2 digits then a zero shall be added at the beginning;
  2. use the MCC and MNC derived in step 1 to create the "mnc<MNC>.mcc<MCC>.3gppnetwork.org" domain name;
  3. add the label "ocs" to the beginning of the domain name.

An example of a home network domain name is:

IMSI in use: 234150999999999;

Where:

MCC = 234;

MNC = 15;

MSIN = 0999999999;

Which gives the home network domain name: ocs.mnc015.mcc234.3gppnetwork.org.

NOTE: It is implementation dependent to determine that the length of the MNC is 2 or 3 digits.

---

## Annex A (informative): Colour Codes

### A.1 Utilization of the BSIC

A BSIC is allocated to each cell. A BSIC can take one of 64 values. In each cell the BSIC is broadcast in each burst sent on the SCH, and is then known by all MSs which synchronise with this cell. The BSIC is used by the MS for several purposes, all aiming at avoiding ambiguity or interference which can arise when an MS in a given position can receive signals from two cells *using the same BCCH frequency*.

Some of the uses of the BSIC relate to cases where the MS is attached to one of the cells. Other uses relate to cases where the MS is attached to a third cell, usually somewhere between the two cells in question.

The first category of uses includes:

- The three least significant bits of the BSIC indicate which of the 8 training sequences is used in the bursts sent on the downlink common channels of the cell. Different training sequences allow for a better transmission if there is interference. The group of the three least significant bits of the BSIC is called the BCC (Base station Colour Code).
- The BSIC is used to modify the bursts sent by the MSs on the access bursts. This aims to avoid one cell correctly decoding access bursts sent to another cell.

The second category of uses includes:

- When in connected mode, the MSs measure and report the level they receive on a number of frequencies, corresponding to the BCCH frequencies of neighbouring cells in the same network as the used cell. Along with the measurement result, the MS sends to the network the BSIC which it has received on that frequency. This enables the network to discriminate between several cells which happen to use the same BCCH frequency. Poor discrimination might result in faulty handovers.
- The content of the measurement report messages is limited to information for 6 neighbour cells. It is therefore useful to limit the reported cells to those to which handovers are accepted. For this purpose, each cell provides a list of the values of the three most significant bits of the BSICs which are allocated to the cells which are useful to consider for handovers (usually excluding cells in other PLMNs). This information enables the MS to discard information for cells with non-conformant BSICs and not to report them. The group of the three most significant bits of the BSIC is called the NCC (Network Colour Code).

It should be noted that when in idle mode, the MS identifies a cell (for cell selection purposes) according to the cell identity broadcast on the BCCH and *not* by the BSIC.

---

### A.2 Guidance for planning

From these uses, the following planning rule can be derived:

*If there exist places where MSs can receive signals from two cells, whether in the same PLMN or in different PLMNs, which use the same BCCH frequency, it is highly preferable that these two cells have different BSICs.*

Where the coverage areas of two PLMNs overlap, the rule above is respected if:

- 1) The PLMNs use different sets of BCCH frequencies (In particular, this is the case if no frequency is common to the two PLMNs. This usually holds for PLMNs in the same country), or
- 2) The PLMNs use different sets of NCCs, or
- 3) BSIC and BCCH frequency planning is co-ordinated.

Recognizing that method 3) is more cumbersome than method 2), and that method 1) is too constraining, it is suggested that overlapping PLMNs which use a common part of the spectrum agree on different NCCs to be used in any



overlapping areas. As an example, a preliminary NCC allocation for countries in the European region can be found in clause A.3 of this annex.

This example can be used as a basis for bilateral agreements. However, the use of the NCCs allocated in clause A.3 is not compulsory. PLMN operators can agree on different BSIC allocation rules in border areas. The use of BSICs is not constrained in non-overlapping areas, or if ambiguities are resolved by using different sets of BCCH frequencies.

If the PLMNs share one or more cells with other PLMNs, the planning rule above should be applied also when the BCCH frequency is different. The rule should be respected by using different sets of NCCs. In addition to that, the PLMN sharing one or more cells with other PLMNs should use different NCCs for shared and non-shared neighbouring cells.

---

## A.3 Example of PLMN Colour Codes (NCCs) for the European region

Austria	:	0
Belgium	:	1
Cyprus	:	3
Denmark	:	1
Finland	:	0
France	:	0
Germany	:	3
Greece	:	0
Iceland	:	0
Ireland	:	3
Italy	:	2
Liechtenstein	:	2
Luxembourg	:	2
Malta	:	1
Monaco	:	3 (possibly 0(=France))
Netherlands	:	0
Norway	:	3
Portugal	:	3
San Marino	:	0 (possibly 2(= Italy))
Spain	:	1
Sweden	:	2
Switzerland	:	1
Turkey	:	2
UK	:	2
Vatican	:	1 (possibly 2(=Italy))
Yugoslavia	:	3

This allows a second operator for each country by allocating the colour codes  $n$  (in the table) and  $n + 4$ . More than 2 colour codes per country may be used provided that in border areas only the values  $n$  and/or  $n+4$  are used.

## Annex B (normative): IMEI Check Digit computation

### B.1 Representation of IMEI

The International Mobile station Equipment Identity and Software Version number (IMEISV), as defined in clause 6, is a 16 digit decimal number composed of three distinct elements:

- an 8 digit Type Allocation Code (TAC);
- a 6 digit Serial Number (SNR); and
- a 2 digit Software Version Number (SVN).

The IMEISV is formed by concatenating these three elements as illustrated below:

TAC	SNR	SVN
-----	-----	-----

**Figure A.1: Composition of the IMEISV**

The IMEI is complemented by a check digit as defined in clause 3. The Luhn Check Digit (CD) is computed on the 14 most significant digits of the IMEISV, that is on the value obtained by ignoring the SVN digits.

The method for computing the Luhn check is defined in Annex B of the International Standard "Identification cards - Numbering system and registration procedure for issuer identifiers" (ISO/IEC 7812 [3]).

In order to specify precisely how the CD is computed for the IMEI, it is necessary to label the individual digits of the IMEISV, excluding the SVN. This is done as follows:

The (14 most significant) digits of the IMEISV are labelled D14, D13 ... D1, where:

- TAC = D14, D13 ... D7 (with D7 the least significant digit of TAC);
- SNR = D6, D5 ... D1 (with D1 the least significant digit of SNR).

### B.2 Computation of CD for an IMEI

Computation of CD from the IMEI proceeds as follows:

- Step 1: Double the values of the odd labelled digits D1, D3, D5 ... D13 of the IMEI.
- Step 2: Add together the individual digits of all the seven numbers obtained in Step 1, and then add this sum to the sum of all the even labelled digits D2, D4, D6 ... D14 of the IMEI.
- Step 3: If the number obtained in Step 2 ends in 0, then set CD to be 0. If the number obtained in Step 2 does not end in 0, then set CD to be that number subtracted from the next higher number which does end in 0.

### B.3 Example of computation

**IMEI (14 most significant digits):**

TAC							SNR						
D14	D13	D12	D11	D10	D9	D8	D7	D6	D5	D4	D3	D2	D1
2	6	0	5	3	1	7	9	3	1	1	3	8	3

**Step 1:**

2	6	0	5	3	1	7	9	3	1	1	3	8	3
x2		x2		x2		x2		x2		x2		x2	
12		10		2		18		2		6		6	

**Step 2:**

$$2 + 1 + 2 + 0 + 1 + 0 + 3 + 2 + 7 + 1 + 8 + 3 + 2 + 1 + 6 + 8 + 6 = 53$$

**Step 3:**

$$CD = 60 - 53 = 7$$

---

## Annex C (normative): Naming convention

This normative annex defines a naming convention which will make it possible for DNS servers to translate logical names for GSNs and RAs to physical IP addresses. The use of logical names is optional, but if the option is used, it shall comply with the naming convention described in this annex. The fully qualified domain names used throughout this annex shall follow the general encoding rules specified in section 19.4.2.1.

---

### C.1 Routing Area Identities

This subclause describes a possible way to support inter-PLMN roaming.

When an MS roams between two SGSNs within the same PLMN, the new SGSN finds the address of the old SGSN from the identity of the old RA. Thus, each SGSN can determine the address of every other SGSN in the PLMN.

When an MS roams from an SGSN in one PLMN to an SGSN in another PLMN, the new SGSN may be unable to determine the address of the old SGSN. Instead, the SGSN transforms the old RA information to a logical name of the form:

`racAAAA.lacBBBB.mncYYY.mccZZZ.gprs`

A and B shall be Hex coded digits; Y and Z shall be encoded as single digits (in the range 0-9).

If there are less than 4 significant digits in AAAA or BBBB, one or more "0" digit(s) is/are inserted at the left side to fill the 4 digit coding. If there are only 2 significant digits in YYY, a "0" digit is inserted at the left side to fill the 3 digit coding.

As an example, the logical name for RAC 123A, LAC 234B, MCC 167 and MNC 92 will be coded in the DNS server as:

`rac123A.lac234B.mnc092.mcc167.gprs.`

The SGSN may then acquire the IP address of the old SGSN from a DNS server, using the logical address. Introducing the DNS concept in GPRS enables operators to use logical names instead of IP addresses when referring to nodes (e.g. GSNs), thus providing flexibility and transparency in addressing. Each PLMN should include at least one DNS server (which may optionally be connected via the DNS service provided by the GSM Association). Note that these DNS servers are GPRS internal entities, unknown outside the GPRS system.

The above implies that at least MCC || MNC || LAC || RAC (= RAI) is sent as the RA parameter over the radio interface when an MS roams to another RA.

If for any reason the new SGSN fails to obtain the address of the old SGSN, the new SGSN takes the same actions as when the corresponding event occurs within one PLMN.

Another way to support seamless inter-PLMN roaming is to store the SGSN IP addresses in the HLR and request them when necessary.

If Intra Domain Connection of RAN Nodes to Multiple CN Nodes (see 3GPP TS 23.236 [23]) is applied then the Network Resource Identifier (NRI) identifies uniquely a given SGSN node out of all the SGSNs serving the same pool area.

If the new SGSN is not able to extract the NRI from the old P-TMSI, it shall retrieve the address of the default SGSN (see 3GPP TS 23.236 [23]) serving the old RA, using the logical name described earlier in this section. The default SGSN in the old RA relays the GTP signalling to the old SGSN identified by the NRI in the old P-TMSI unless the default SGSN itself is the old SGSN.

If the new SGSN is able to extract the NRI from the old P-TMSI, then it shall attempt to derive the address of the old SGSN from the NRI and the old RAI. NRI-to-SGSN assignments may be either configured (by O&M) in the new SGSN, or retrieved from a DNS server. If a DNS server is used, it shall be queried using the following logical name, derived from the old RAI and NRI information:

nriCCCC.racDDDD.lacEEEE.mncYYY.mccZZZ.gprs

C, D and E shall be Hex coded digits, Y and Z shall be encoded as single digits (in the range 0-9). If there are less than 4 significant digits in CCCC, DDDD or EEEE, one or more "0" digit(s) is/are inserted at the left side to fill the 4 digit coding. If there are only 2 significant digits in YYY, a "0" digit is inserted at the left side to fill the 3 digits coding.

As an example, the logical name for NRI 3A, RAC 123A, LAC 234B, MCC 167 and MNC 92 will be coded in the DNS server as:

*nri003A.rac123A.lac234B.mnc092.mcc167.gprs.*

If for any reason the new SGSN fails to obtain the address of the old SGSN using this method, then as a fallback method it shall retrieve the address of the default SGSN serving the old RA.

---

## C.2 GPRS Support Nodes

This subclause defines a naming convention for GSNs.

It shall be possible to refer to a GSN by a logical name which shall then be translated into a physical IP address. This clause proposes a GSN naming convention which would make it possible for an internal GPRS DNS server to make the translation.

An example of how a logical name of an SGSN could appear is:

*sgsnXXXX.mncYYY.mccZZZ.gprs*

X, shall be Hex coded digits, Y and Z shall be encoded as single digits (in the range 0-9).

If there are less than 4 significant digits in XXXX one or more "0" digit(s) is/are inserted at the left side to fill the 4 digits coding. If there are only 2 significant digits in YYY, a "0" digit is inserted at the left side to fill the 3 digit coding.

As an example, the logical name for SGSN 1B34, MCC 167 and MNC 92 will be coded in the DNS server as:

*sgsn1B34.mnc092.mcc167.gprs*

---

## C.3 Target ID

This subclause describes a possible way to support SRNS relocation.

In UMTS, when SRNS relocation is executed, a target ID which consists of MCC, MNC and RNC ID is used as routing information to route to the target RNC via the new SGSN. An old SGSN shall resolve a new SGSN IP address by a target ID to send the Forward Relocation Request message to the new SGSN.

It shall be possible to refer to a target ID by a logical name which shall be translated into an SGSN IP address to take into account inter-PLMN handover. The old SGSN transforms the target ID information into a logical name of the form:

*rncXXXX.mncYYY.mccZZZ.gprs*

X shall be Hex coded digits; Y and Z shall be encoded as single digits (in the range 0-9). If there are less than 4 significant digits in XXXX, one or more "0" digit(s) is/are inserted at the left side to fill the 4 digits coding. If there are only 2 significant digits in YYY, a "0" digit is inserted at the left side to fill the 3 digit coding. Then, for example, a DNS server is used to translate the logical name to an SGSN IP address.

As an example, the logical name for RNC 1B34, MCC 167 and MNC 92 will be coded in the DNS server as:

*rnc1B34.mnc092.mcc167.gprs*

---

## Annex D (informative): Applicability and use of the ".3gppnetwork.org" domain name

There currently exists a private IP network between operators to provide connectivity for user transparent services that utilise protocols that rely on IP. This includes (but is not necessarily limited to) such services as GPRS/PS roaming, WLAN roaming, GPRS/PS inter-PLMN handover and inter-MMSC MM delivery. This inter-PLMN IP backbone network consists of indirect connections using brokers (known as GRXs – GPRS Roaming Exchanges) and direct inter-PLMN connections (e.g. private wire); it is however *not* connected to the Internet. More details can be found in GSMA PRD IR.34 [57].

Within this inter-PLMN IP backbone network, the domain name ".gprs" was originally conceived as the only domain name to be used to enable DNS servers to translate logical names for network nodes to IP addresses (and vice versa). However, after feedback from the Internet Engineering Task Force (IETF) it was identified that use of this domain name has the following drawbacks:

1. Leakage of DNS requests for the ".gprs" top level domain into the public Internet is inevitable at sometime or other, especially as the number of services (and therefore number of nodes) using the inter-PLMN IP backbone increases. In the worst case scenario of faulty clients, the performance of the Internet's root DNS servers would be seriously degraded by having to process requests for a top level domain that does not exist.
2. It would be very difficult for network operators to detect if/when DNS requests for the ".gprs" domain were leaked to the public Internet (and therefore the security policies of the inter-PLMN IP backbone network were breached), because the Internet's root DNS servers would simply return an error message to the sender of the request only.

To address the above, the IETF recommended using a domain name that is *routable* in the public domain but which requests to it are not actually *serviced* in the public domain. The domain name ".3gppnetwork.org" was chosen as the new top level domain name to be used (as far as possible) within the inter-PLMN IP backbone network.

Originally, only the DNS servers connected to the inter-PLMN IP backbone network were populated with the correct information needed to service requests for *all* sub-domains of this domain. However, it was later identified that some new services needed their allocated sub-domain(s) to be resolvable by the UE and not just inter-PLMN IP network nodes. To address this, additional, higher-level sub-domains were created:

- "pub.3gppnetwork.org", which is to be used for domain names that need to be resolvable by UEs (and possibly network nodes too) that are connected to a local area network that is connected to the Internet; and
- "ipxuni.3gppnetwork.org", which is to be used for domain names for UNI interfaces that need to be resolvable by UEs that are connected to a local area network that is not connected to the Internet (e.g. local area networks connected to the inter-PLMN IP network of the IPX).

Therefore, DNS requests for the above domain names can be resolved, while requests for all other sub-domains of ".3gppnetwork.org" can simply be configured to return the usual DNS error for unknown hosts (thereby avoiding potential extra, redundant load on the Internet's root DNS servers).

The GSM Association is in charge of allocating new sub-domains of the ".3gppnetwork.org" domain name. The procedure for requesting new sub-domains can be found in Annex E.

## Annex E (normative): Procedure for sub-domain allocation

When a 3GPP member company identifies the need for a new sub-domain name of ".3gppnetwork.org", that 3GPP member company shall propose a CR to this specification at the earliest available meeting of the responsible working group for this TS. The CR shall propose a new sub-domain name. The new sub-domain proposed shall be formatted in one of the formats as described in the following table.

Sub-domain Format	Intended Usage
<service_id>.mnc<MNC>.mcc<MCC>.3gppnetwork.org (see notes 1 and 2)	Domain name that is to be resolvable by network nodes only. This format inherently adds protection to the identified node, in that attempted DNS resolutions instigated directly from end user equipment will fail indefinitely.
<service_id>.mnc<MNC>.mcc<MCC>.pub.3gppnetwork.org (see notes 1 and 2)	Domain name that is to be resolvable by UEs and/or network nodes. This format inherently adds global resolution capability, but at the expense of confidentiality of network topology.
<service_id>.mnc<MNC>.mcc<MCC>.ipxuni.3gppnetwork.org (see notes 1 and 2)	Domain name for UNI interface that is to be resolvable by UEs that are connected to an inter-PLMN IP network that has no connectivity to the Internet. This format inherently adds resolution capability for UEs in closed IP networks e.g. IPX.
<service_id>.mcc<MCC>.visited-country.pub.3gppnetwork.org (see notes 1 and 2)	Domain name in the visited country that is to be resolvable by UEs and/or network nodes, which is not specific to an individual operator.

**Table E.1: Sub-domain formats for the "3gppnetwork.org" domain and their respective intended usage**

NOTE 1: "<service\_ID>" is a chosen label, conformant to DNS naming conventions (usually IETF RFC 1035 [19] and IETF RFC 1123 [20]) that clearly and succinctly describe the service and/or operation that is intended to use this sub-domain.

NOTE 2: "<MNC>" and "<MCC>" are the MNC (padded to the left with a zero, if only a 2-digit MNC) and MCC of a PLMN.

NOTE 3: The definition of the new sub-domain "<service\_id>.mcc<MCC>.visited-country.pub.3gppnetwork.org" is pending approval from GSMA.

Care should be taken when choosing which format a domain name should use. Once a format has been chosen, the responsible working group shall then check the CR and either endorse it or reject it. If the CR is endorsed, then the responsible working group shall send an LS to the GSMA IREG with TSG-CT in copy. The LS shall describe the following key points:

- the context
- the service
- intended use
- involved actors
- proposed new sub-domain name

GSMA IREG will then verify the consistence of the proposal and its usage within the domain's structure and interworking rules (e.g. access to the GRX/IPX Root DNS servers). GSMA IREG will then endorse or reject the proposal and inform the responsible working group (in 3GPP) and also TSG CT. It is possible that GSMA IREG will also specify, changes to the newly proposed sub-domain name (e.g. due to requested sub-domain name already allocated).

NOTE 3: There is no need to request GSMA IREG for new labels to the left of an already GSMA IREG approved '<service\_ID>'. It is the responsibility of the responsible working group to ensure uniqueness of such new labels.

It should be noted that services already defined to use the ".gprs" domain name will continue to do so and shall not use the new domain name of ".3gppnetwork.org"; this is to avoid destabilising services that are already live.



## Annex F (informative): Change history

Change history						
TSG CN#	Spec	Version	CR	<Phase>	New Version	Subject/Comment
Apr 1999	GSM 03.03	7.0.0				Transferred to 3GPP CN1
CN#03	23.003				3.0.0	Approved at CN#03
CN#04	23.003	3.0.0	001	R99	3.1.0	Definition of escape PLMN code
CN#04	23.003	3.0.0	002r1	R99	3.1.0	SSN reallocation for CAP, gsmSCF, SIWF, GGSN, SGSN,
CN#04	23.003	3.0.0	003	R99	3.1.0	Correction of VGC/VBC reference
CN#04	23.003	3.0.0	004	R99	3.1.0	Harmonisation of the MNC-length; correction of CR A019r1
CN#04	23.003	3.0.0	005	R99	3.1.0	Correction to the MNC length
CN#05	23.003	3.1.3	007r1	R99	3.2.0	ASCII coding of <MNC> and <MCC> in APN OI
CN#05	23.003	3.1.3	008	R99	3.2.0	New SSN allocation for RANAP and RNSAP
CN#06	23.003	3.2.1	011	R99	3.3.0	Support of VLR and HLR Data Restoration procedures with LCS
CN#07	23.003	3.3.0	014	R99	3.4.0	Necessity of the function of the calculation of an SGSN IP address from the target ID
CN#07	23.003	3.3.0	016	R99	3.4.0	Definition of Service Area Identification
CN#07	23.003	3.3.0	017r2	R99	3.4.0	Modification of clause 6.2 to enhance IMEI security
CN#07	23.003	3.3.0	018	R99	3.4.0	Coding of a deleted P-TMSI signature
CN#07	23.003	3.4.0	013r2	R99	3.4.1	Introduction of Reserved Service Labels in the APN
CN#08	23.003	3.4.1	019	R99	3.5.0	Missing UTRAN identifiers
CN#08	23.003	3.4.1	021r1	R99	3.5.0	Editorial Modification of clause 6.2.2.
CN#08	23.003	3.4.1	022	R99	3.5.0	IMEI Formats and Encoding
CN#09	23.003	3.5.0	023	R99	3.6.0	Alignment of 23.003 with text from 25.401
CN#10	23.003	3.6.0	024	R99	3.7.0	Moving informative Annex A from 3G TS 29.060 and making it normative.
CN#11	23.003	3.7.0	025	R99	3.8.0	Clarification to Definition of Service Area Identifier
CN#11	23.003	3.7.0	026	R99	3.8.0	Forbidden APN network identifier labels
CN#11	23.003	3.8.0		Rel-4	4.0.0	Updated from R99 to Rel-4 after CN#11
CN#12	23.003	4.0.0	028r1	Rel-4	4.1.0	Remove reference to TS23.022
CN#12	23.003	4.1.0	029r1	Rel-5	5.0.0	New Subsystem Number for the Position Calculation Application Part on the Iupc interface
CN#13	23.003	5.0.0	032	Rel-5	5.1.0	Clarification on APN labels that begin with a digit
CN#13	23.003	5.0.0		Rel-5	5.1.0	Editorial clean up
CN#14	23.003	5.1.0	033	Rel-5	5.2.0	Rules for TMSI partitioning
CN#14	23.003	5.1.0	035	Rel-5	5.2.0	Introduction of Global CN-ID definition
CN#16	23.003	5.2.0	037r1	Rel-5	5.3.0	IuFlex support for determining old SGSN during handover/relocation
CN#16	23.003	5.2.0	038	Rel-5	5.3.0	Allocation of unique prefixes to IPv6 terminals
CN#16	23.003	5.2.0	041r2	Rel-5	5.3.0	Use of a temporary public user identity
CN#16	23.003	5.2.0	044	Rel-5	5.3.0	Restructuring the IMEI to combine the TAC and FAC
CN#16	23.003	5.2.0	045	Rel-5	5.3.0	Use of the TLLI codespace in GERAN Iu mode
CN#17	23.003	5.3.0	048r3	Rel-5	5.4.0	Clarification on the definition of DNS
CN#17	23.003	5.3.0	050r1	Rel-5	5.4.0	Support for Shared Network in connected mode: definition of SNA
CN#17	23.003	5.3.0	053r1	Rel-5	5.4.0	Restructuring the IMEI to combine the TAC and FAC in Annex B
CN#17	23.003	5.3.0	054	Rel-5	5.4.0	SCCP sub-system Number for IM-SSF
CN#18	23.003	5.4.0	055r1	Rel-5	5.5.0	Iur-g Introduction
CN#18	23.003	5.4.0	056r2	Rel-5	5.5.0	Editorial clean-up
CN#18	23.003	5.4.0	057	Rel-5	5.5.0	Correction of the private user identity's form
CN#18	23.003	5.4.0	058	Rel-5	5.5.0	Addition of a reference to the ITU-T RECOMMENDATION E.212 for Mobile Country Codes
CN#18	23.003	5.4.0	059	Rel-5	5.5.0	Correction to the form of public user identity

Change history						
TSG CN#	Spec	Version	CR	<Phase>	New Version	Subject/Comment
CN#18	23.003	5.4.0	062	Rel-5	5.5.0	Fix miss-interworking for LMSI handling (LMSI definition)
CN#18	23.003	5.5.0		Rel-5	5.5.1	Corrupted figures 13 – 18 fixed
CN#20	23.003	5.5.1	065	Rel-5	5.6.0	Correction to Annex C.3 – Target ID
CN#21	23.003	5.6.0	072	Rel-5	5.7.0	Correction to definition of Group-ID, Group call area ID and Group Call Reference
CN#21	23.003	5.7.0	073r2	Rel-6	6.0.0	PSI definition
CN#22	23.003	6.0.0	078	Rel-6	6.1.0	On the length of the APN NI
CN#23	23.003	6.1.0	081	Rel-6	6.2.0	Changes and corrections to DNS names
CN#23	23.003	6.1.0	083r2	Rel-6	6.2.0	Changes to enable the GSMA root DNS architecture using ".3gppnetwork.org" TLD
CN#23	23.003	6.1.0	085r1	Rel-6	6.2.0	WLAN access parameters moved from TS 24.234 to TS 23.003
CN#23	23.003	6.1.0	087	Rel-6	6.2.0	Assignment of SSN for Presence Network Agent
CN#24	23.003	6.2.0	086r4	Rel-6	6.3.0	Clarification of the uses of SIP URIs for Public User ID
CN#24	23.003	6.2.0	088r1	Rel-6	6.3.0	Addition of TMGI
CN#25	23.003	6.3.0	089	Rel-6	6.4.0	Background of and procedures for the ".3gppnetwork.org" domain name
CN#25	23.003	6.3.0	090r2	Rel-6	6.4.0	Decorated NAI format
CN#25	23.003	6.3.0	091r1	Rel-6	6.4.0	Introduction of temporary identities
CN#26	23.003	6.4.0	092r2	Rel-6	6.5.0	'otherrealm' format of Decorated NAI
CN#26	23.003	6.4.0	095r1	Rel-6	6.5.0	Clarification of NRI position within (P)-TMSI
CN#26	23.003	6.4.0	096r1	Rel-6	6.5.0	BSF address
CN#27	23.003	6.5.0	097	Rel-6	6.6.0	Clarification of the TMGI
CN#27	23.003	6.5.0	093r3	Rel-6	6.6.0	Definition of Alternative NAI
CT#28	23.003	6.6.0	0099r4	Rel-6	6.7.0	W-APN Definition
CT#28	23.003	6.6.0	0100r5	Rel-6	6.7.0	Correction to wildcards in PSI
		6.7.0		Rel-6	6.7.1	2005-07: Correct line break before clause 14 header
CT#29	23.003	6.7.1	0102r2	Rel-6	6.8.0	Corrections to "3gppnetwork.org" addressing
CT#29	23.003	6.7.1	0103	Rel-6	6.8.0	Addition of addressing for the Generic Access Network
CT#29	23.003	6.7.1	0104r1	Rel-6	6.8.0	PSI routing
CT#31	23.003	6.8.0	0106r1	Rel-6	6.9.0	IETF references update
CT#32	23.003	6.9.0	0107r1	Rel-6	6.10.0	Fast re-authentication identity clarification
CT#32	23.003	6.9.0	0109r1 0111r1	Rel-6	6.10.0	Case insensitive naming convention Correction to the W-APN definition
CT#32	23.003	6.10.0	0112r1	Rel-7	7.0.0	Definition of Anonymous URI in IMS
CT#33	23.003	7.0.0	0117r1 0115r3	Rel-7	7.1.0	Re-authentication identity definition correction Definition of MBMS SAI
CT#34	23.003	7.1.0	0118 0119r2 0120  0121 0122r2	Rel-7	7.2.0	Voice Call Continuity Identification and Addressing Unavailable User Identity Emergency Realm for I-WLAN network advertisement Definition of emergency W-APN Format of emergency public identity
CT#35	23.003	7.2.0	0128r2 0126r2 0129r2	Rel-7	7.3.0	Definition of Private Service identity Definition of emergency APN for IMS em-calls Clarification to TMGI definition
CT#36	23.003	7.3.0	0131r2	Rel-7	7.4.0	Correction of derivation of identifiers, by the UE, using the IMSI
CT#37	23.003	7.4.0	0134r1 0135r2 0136	Rel-7	7.5.0	Home realm construction for MBMS roaming PSI clarification Remove emergency APN
CT#38	23.003	7.5.0	0138	Rel-7	7.6.0	Correction to text describing W-APN format
CT#39	23.003	7.6.0	0141r1	Rel-7	7.7.0	Structure of TMGI
CT#39	23.003	7.7.0	0140	Rel-8	8.0.0	Wildcarded Public User Identities format
CT#40	23.003	8.0.0	0142r2 0144	Rel-8	8.1.0	IMS public and private identity derivation in 3GPP2 Minor corrections to the IMS section

Change history						
TSG CN#	Spec	Version	CR	<Phase>	New Version	Subject/Comment
			0146r2			NAI for 3GPP access to Non-3GPP Access Interworking
			0143r2			Addition of IMS Centralized Services related identities
CT#41	23.003	8.1.0	0150	Rel-8	8.2.0	Emergency Public User Identity Removal
			0152r3			Introduction of IMC in support of common IMS
			0153r1			Introduction of STN-SR
			0154r1			Addition and correction of DNS related identifiers for EPC
			0155r1			Definition of Globally Unique Temporary UE Identity
			0156			Reference correction
			0158r1			Addition of Conference Factory URI for IMS Centralized Services
			0159r1			Naming for HA discovery HA-APN
			0160r2			Definition and format of access network identifier
CT#42	23.003	8.2.0	0161		8.3.0	SGSN related FQDNs
			0162			New "nodes" subdomain for EPC
			0165			Clarify the mapping between M-TMSI and P-TMSI
			0166			Revising the GUTI Definition
			0163r4			Closed Subscriber Group
			0167r1			Adding the S-TMSI Definition
			0168r1			Definition of instance Id
			0169			STN-SR in SGSN
CT#43	23.003	8.3.0	0170	Rel-8	8.4.0	Correction to NAI format
			0172			Missing service identifiers for DNS procedures
			0174			Correction of the GUTI format
			0176r1			Correction of the GUTI P-TMSI mapping
			0177			Corrections to Service Continuity addressing
			0178r1			Support of EAP-AKA"
			0179r2			Naming for ANDSF discovery
			0180r1			ePDG naming
			0181r2			Clarification about canonical form of IMS Public User Identity when format is TEL URL
			0182			Temporary Identity Tag Values for Fast Re-authentication Ids
			0187r2			DNS-APN-OI
CT#44	23.003	8.4.0	0189r1	Rel-8	8.5.0	HNB Name Definition
			0190r1			Clarification on TAI FQDN
			0191			Service Parameters for S2c
			0193r2			Reference update for draft-montemurro-gsma-imei-urn
CT#45	23.003	8.5.0	0194r1	Rel-8	8.6.0	Public User Identity definition in TS 23.003
			0197r1			Inclusion of CSG Type
CT#45	23.003	8.6.0	0199r1	Rel-9	9.0.0	IMEI Based NAI definitions for emergency services
CT#46	23.003	9.0.0	0200r1	Rel-9	9.1.0	IMEI based NAI
			0205r4			IMEI Based NAI
			0210r1			Reintroducing Emergency APN definition for IMS based Emergency Call
			0212r1			Clarification for the format of ANDSF-SN in roaming scenario
			0215			Tracking Area Code
			0217			E-UTRAN Cell Global Identification definition
CT#47	23.003	9.1.0	0213r4	Rel-9	9.2.0	Defining H(e)NB identity
			0219r2			Exclude prepended digit from the NAI in PMIPv6
			0221r2			APN-FQDN construction
			0223			Corrections to APN structure
			0225r1			Correction on Home Network Realm/Domain
			0227			Corrections to IMS Public Identity
CT#48	23.003	9.2.0	0229r1	Rel-9	9.3.0	Removal of the redundancy reference to 23.401
			0232r1			IMEI and IMEISV

Change history						
TSG CN#	Spec	Version	CR	<Phase>	New Version	Subject/Comment
CT#49	23.003	9.3.0	0235r1	Rel-9	9.4.0	Remove ambiguities and improved definition of HNB Unique Identity
			0237r2			Essential corrections to GUTI mapping
			0242r1			PSI use for services hosted in an AS
			0246r3			Essential corrections to GUTI mapping
			0247r2			Use of NRI
			0256			Format of the Unavailable User Identity
			0257			Clarification of UE behaviour with regards to LAC format
CT#50	23.003	9.4.0	0252r2	Rel-9	9.5.0	Correction of C-MSISDN definition
			0265			Updating IMEI URN draft reference
			0268r1			Determination of type of source node during TAU/RAU
CT#50	23.003	9.5.0	0258r3	Rel-10	10.0.0	eNodeB-ID FQDN for DNS procedures
			0269r1			Determination of type of source node during TAU/RAU
			0259			Service Parameter on PGW selection for GTP based S2b
CT#51	23.003	10.0.0	0274r3	Rel-10	10.1.0	Relay Node OAM system identification
			0279r3			Correction of C-MSISDN definition
			0277r1			Determination of type of source node during TAU/RAU
			0285			Correction to a reference of an outdated IETF draft to an RFC
			0280r2			Correction to the reserved values for Tracking Area Code (TAC)
			0286			DNS Service Support For Sv
			0289			Clarification of decoding of NRI
CT#52	23.003	10.1.0	0290	Rel-10	10.2.0	Closed Subscriber Group clarification
			0293r2			UE moving from E-UTRAN to GERAN
			0294r2			XCAP Addressing
			0296r1			APN Network Identifier
			0299			Updating IMEI URN draft reference
CT#53	23.003	10.2.0	0307	Rel-10	10.3.0	Updating IMEI URN draft reference
			0282r4			Format of Public User Identities and SIP/TEL URI
			0303r3			Emergency NAI for UICC-less Terminal
CT#54	23.003	10.3.0	0316r1	Rel-10	10.4.0	Definition of Distinct Public User Identity
			0309r1			Emergency NAI for UICC-less Terminal
CT#54	23.003	10.4.0	0308r2	Rel-11	11.0.0	APN Operator Identifier for local breakout
			0312r2			Definition of STI-rSR
CT#55	23.003	11.0.0	0334	Rel-11	11.1.0	BSF address correction
			0322r2			Correction to domain name for XCAP Root URI
			0325			Updating IMEI URN draft reference
			0317r2			Clarification of GUTI mapping
			0318			Service Parameter on PGW selection for GTP based S2a
CT#56	23.003	11.1.0	0320r6	Rel-11	11.2.0	MTC External Identifier
			0337r1			New Service Parameters for CS to PS SRVCC
			0319r5			Definition of A-MSISDN
			0335r2			MME Number for SMS in MME
			0311r7			SSN Reallocation for CSS and its Number Definition
CT#57	23.003	11.2.0	0338r1	Rel-11	11.3.0	External Identifier definition
			0339r1			PS only subscription w/o MSISDN
			0340r1			NCC allocation in a shared network
			0342r1			MSB in the GUTI and P-TMSI mapping
			0345r2			Clarification to MME FQDN
CT#58	23.003	11.3.0	0347	Rel-11	11.4.0	Clarification on the use of APN Operator Identifier
			0348r1			PS only subscription without MSISDN
			0352r1			Updating IMEI URN draft reference
CT#59	23.003	11.4.0	0346r5	Rel-11	11.5.0	MME FQDN Clarification

Change history						
TSG CN#	Spec	Version	CR	<Phase>	New Version	Subject/Comment
CT#61	23.003	11.5.0	0358	Rel-11	11.6.0	Updating IMEI URN draft reference
			0361r1			MBMS SAI Definition Correction for LTE Access
			0363r2			NRI and MMEC coordination
CT#61	23.003	11.6.0	0362r2	Rel-12	12.0.0	SIPTO permission for Local Network LHN ID definition
			0364			GERAN lu Mode
CT#62	23.003	12.0.0	0370 0365r3	Rel-12	12.1.0	Updating IMEI URN draft reference Multi-Vendor eNB Plug and Play
CT#63	23.003	12.1.0	0379	Rel-12	12.2.0	Updating IMEI URN draft reference
			0371r2			Update of working procedures with GSMA IREG
			0372r1			TWAN Operator Name
CT#64	23.003	12.2.0	0381r4	Rel-12	12.3.0	Addition of ProSe Application ID format
			0382r5			Addition of ProSe Application Code format
			0383r1			Correct definition of Decorated NAI for Evolved Packet Core (EPC)
			0384r1			Definition of Alternative NAI for Evolved Packet Core (EPC)
			0386r6			Conference Factory URI for IMS
07-2014	23.003	12.3.0		Rel-12	12.3.1	Subclause 19.3.7 title corrected
CT#65	23.003	12.3.1	0391	Rel-12	12.4.0	Updating IMEI URN draft reference to RFC 7254
			0392r2			Identification of the HSS
			0393r2			Update of ProSe Application Code format
			0394			IMSI based Decorated NAI
10-2014	23.003	12.4.0		Rel-12	12.4.1	Clause number 10.2.2 added.
CT#66	23.003	12.4.1	0398r1	Rel-12	12.5.0	Clarification of NAI handling
			0399r2			Maintenance of I-WLAN requirements
			0402			Addressing and Identifications for Bootstrapping MBMS Service Announcement
			0401r1			Definiton for EPC Prose User ID
			0403r1			Prose Application ID Name description
CT#66	23.003	12.5.0	0396r3	Rel-13	13.0.0	Defining app protocol name for Nq and Nq'
CT#67	23.003	13.0.0	0409r2	Rel-13	13.1.0	Extension of decorated NAI
			0414			Definition of Vendor ID
			0413r2			Clarification in the definition of the ProSe Application Code
CT#68	23.003	13.1.0	0412r6	Rel-13	13.2.0	Clarification of Root NAI and Decorated NAI
			0416r1			Correction of examples for the Fast-Reauth NAI
			0417r1			Domain name starting by a digit
CT#69	23.003	13.2.0	0420	Rel-13	13.3.0	Removal of Editor"s Note about ProSe Application Code Length
			0418r3			Definition of IMSI-Group Identifier
			0421r1			FQDN format for ProSe Function
CT#70	23.003	13.3.0	0423r2	Rel-13	13.4.0	FQDN for ePDG selection for emergency bearer services
			0424r1			FQDN for ePDG selection (for non-emergency bearer services)
			0431r4			Introduce home network domain name for OCS
			0426r2			ProSe Application code and Metadata index
			0427r1			ProSe identifiers for restricted ProSe direct discovery
			0433r1			ProSe identifiers used in direct discovery for public safety
			0429r1			Presence Reporting Area Identifier
			0432r2			Enhancement of service parameters to support Decor
CT#71	23.003	13.4.0	0434r1	Rel-13	13.5.0	Addition of ProSe Application Code Prefix and ProSe Application Code Suffix formats
			0437r1			ePDG selection with DNS-based Discovery of Regulatory Requirements
			0438r1			Clarification of TAC Allocation

---

# History

<b>Document history</b>		
V13.4.0	March 2016	Publication
V13.5.0	April 2016	Publication