

ETSI TS 124 216 V18.0.0 (2024-05)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Communication Continuity Management Object (MO)
(3GPP TS 24.216 version 18.0.0 Release 18)**



Reference

RTS/TSGC-0124216vi00

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	5
4 Communication Continuity Management Object.....	6
5 Management Object parameters	7
5.1 General	7
5.2 Node: /<X>	7
5.3 /<X>/Name	8
5.4 /<X>/VDI/.....	8
5.5 /<X>/VDN/.....	8
5.6 /<X>/Preferred_domain/	8
5.7 /<X>/Immediate_DT/	9
5.8 /<X>/DT_CS-to-IM_CN_direction /	9
5.9 /<X>/DT_IM_CN-to-CS_direction /	9
5.10 /<X>/DT_in_held_waiting_calls/	10
5.11 /<X>/STI/.....	10
5.12 /<X>/STN/	10
5.13 /<X>/OperatorPolicy	10
5.14 /<X>/OperatorPolicy/<X>.....	11
5.15 /<X>/OperatorPolicy/<X>/MediaPref	11
5.16 /<X>/OperatorPolicy/<X>/MediaPref/MediaPrefId	11
5.17 /<X>/OperatorPolicy/<X>/MediaPref/MediaorGroups.....	11
5.18 /<X>/OperatorPolicy/<X>/MediaPref/MediaorGroups/<X>/	11
5.19 /<X>/OperatorPolicy/<X>/MediaPref/MediaorGroups/<X>/Media	12
5.20 /<X>/OperatorPolicy/<X>/MediaPref/RestrictedAccessNetworkType.....	12
5.21 /<X>/OperatorPolicy/<X>/MediaPref/RestrictedAccessNetworkType/<X>	12
5.22 /<X>/OperatorPolicy/<X>/MediaPref/RestrictedAccessNetworkType /<X>/AccessNetworkType.....	13
5.23 /<X>/OperatorPolicy/<X>/MediaPref/PreferredAccessNetworks.....	13
5.24 /<X>/OperatorPolicy/<X>/MediaPref/ PreferredAccessNetworks/<X>	13
5.25 /<X>/OperatorPolicy/<X>/MediaPref/ PreferredAccessNetworks/<X>/AccessNetworkType.....	13
5.26 /<X>/OperatorPolicy/<X>/MediaPref/SC_media_transfer	14
5.27 /<X>/OperatorPolicy/<X>/MediaPref/ SC_non_transferable_media /.....	14
5.28 /<X>/InterUETTransferSCCASURI/	14
5.29 /<X>/Ext/	15
5.30 /<X>/PStoPSSTIURI/	15
Annex A (informative): Management Object DDF	16
Annex B (informative): Change history	26
History	27

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

This document defines the Communication Continuity Management Object. The management object is compatible with OMA Device Management protocol specifications, version 1.2 and upwards, and is defined using the OMA DM Device Description Framework as described in the Enabler Release Definition OMA-ERELED_DM-V1_2 [4].

The Communication Continuity Management Object consists of relevant parameters that can be managed for Communication Continuity capabilities.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the Communication Continuity Management Object document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.003: "Numbering, addressing and identification".
- [3] 3GPP TS 24.206: "Voice call continuity between Circuit Switched (CS) and IP Multimedia Subsystem (IMS); Stage 3".
- [4] OMA-ERELED-DM-V1_2-20060602-C: "Enabler Release Definition for OMA Device Management, Candidate Version 1.2".
- [5] 3GPP TS 24.237: "IP Multimedia Subsystem (IMS) Service Continuity ; Stage 3".
- [6] 3GPP TS 24.229: "IP multimedia call control protocol based on Session Initiation Protocol (SIP) and Session Description Protocol (SDP); Stage 3".
- [7] IETF RFC 4566 (July 2006): " SDP: Session Description Protocol".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] apply.

For the purposes of the present document, the following terms and definitions given in 3GPP TS 23.003 [2] apply:

VCC Domain Transfer Number (VDN)
VCC Domain Transfer URI (VDI)

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CN	Core Network
DDF	Device Description Framework
DM	Device Management

DT	Domain Transfer
IMS	IP Multimedia core network Subsystem
IP	Internet Protocol
MO	Management Object
OMA	Open Mobile Alliance
SC	Service Continuity
SIP	Session Initiation Protocol
ST	Session Transfer
STI	SC Transfer URI
STN	SC Transfer Number
UE	User Equipment
VCC	Voice Call Continuity
VDI	VCC Domain Transfer URI
VDN	VCC Domain Transfer Number

4 Communication Continuity Management Object

The Communication Continuity Management Object is used to manage settings of the UE for communication continuation capabilities. The Management Object covers parameters for communication continuation related capabilities. The Management Object enables the management of the settings on behalf of the end user.

The Communication Continuity MO covers settings of the UE for the following capabilities:

- Voice Call Continuity (VCC) as specified in 3GPP TS 24.206 [3];
- Service Continuity (SC) as specified in 3GPP TS 24.237 [5];
- inter UE transfer as specified in 3GPP TS 24.237 [5].

NOTE: The Communication Continuity MO can be expanded to cover settings of further communication continuity capabilities.

The Management Object Identifier is: urn:oma:mo:ext-3gpp-communication-continuity:1.0.

Protocol compatibility: This MO is compatible with OMA DM 1.2.

The following nodes and leaf objects are possible under the Communication Continuity node:




Figure 1: The Communication Continuity Object

5 Management Object parameters

5.1 General

This clause describes the parameters for the Communication Continuity Management Object.

5.2 Node: /<X>

This interior node acts as a placeholder for one or more accounts for a fixed node.

- Occurrence: OneOrMore
- Format: node
- Access Types: Get
- Values: N/A

The interior node is mandatory if the UE supports one or more Communication Continuity capabilities. Support for a UE is defined by the related roles as defined by the related communication continuity service, as listed in clause 4 of this specification.

NOTE: One node is normally used.

5.3 /<X>/Name

The Name leaf is a name for the Communication Continuity settings.

- Occurrence: ZeroOrOne
- Format: chr
- Access Types: Get
- Values: <User displayable name>

5.4 /<X>/VDI/

The VDI leaf is the VCC Transfer URI that the user includes in SIP INVITE requests to initiate domain transfer.

- Occurrence: One
- Format: chr
- Access Types: Get, Replace
- Values: < A VCC VDI >

The format of the VCC VDI is defined by 3GPP TS 23.003 [2].

EXAMPLE: sip:domain.xfer@dtf1.home1.net

5.5 /<X>/VDN/

The VDN leaf is the VCC Transfer Number that the user includes in a circuit switched call setup to initiate domain transfer.

- Occurrence: One
- Format: chr
- Access Types: Get, Replace
- Values: < A VCC VDN >

The format of the VCC VDN is defined by 3GPP TS 23.003 [2].

EXAMPLE: +12125555555

5.6 /<X>/Preferred_domain/

The Preferred domain leaf represents the operator's preferred domain for UE originated calls/sessions.

- Occurrence: One
- Format: chr
- Access Types: Get, Replace
- Values: 0, 1, 2, 3
 - 0 – Indicates the preference for CS domain.
 - 1 – Indicates the preference for IM CN subsystem.

- 2 – Indicates the preference for CS domain only.
- 3 – Indicates the preference for IM CN subsystem only.

5.7 /<X>/Immediate_DT/

The Immediate Domain Transfer leaf indicates whether to initiate a VCC domain transfer immediately to the operator's preferred domain when that domain becomes available. This operator policy only affects ongoing sessions.

- Occurrence: One
 - Format: bool
 - Access Types: Get, Replace
 - Values: 0, 1
- 0 – Indicates the preference to not initiate domain transfer immediately to the preferred domain when that domain becomes available.
- 1 – Indicates the preference to initiate domain transfer immediately to the preferred domain when that domain becomes available.

NOTE 1: If the Immediate Domain Transfer operator policy indicates that the domain transfer is not immediately required then it is up to the VCC UE to decide when to perform the domain transfer if the preferred domain is available.

5.8 /<X>/ DT_CS-to-IM_CN_direction /

The Domain Transfer CS-to-IM CN direction leaf indicates if a VCC domain transfer from CS domain to IMS is restricted.

- Occurrence: One
 - Format: bool
 - Access Types: Get, Replace
 - Values: 0, 1
- 0 – Indicates that the network operator prefers the domain transfer in the CS to IM CN subsystem direction can occur.
- 1 – Indicates that the network operator prefers the domain transfer in the CS to IM CN subsystem direction cannot occur.

5.9 /<X>/ DT_IM_CN-to-CS_direction /

The Domain Transfer IM CN-to-CS direction leaf indicates if a VCC domain transfer from IM CN subsystem to CS domain is restricted.

- Occurrence: One
 - Format: bool
 - Access Types: Get, Replace
 - Values: 0, 1
- 0 – Indicates that the network operator prefers the domain transfer in the IM CN subsystem to CS direction can occur.

- 1 – Indicates that the network operator prefers the domain transfer in the IM CN subsystem to CS direction cannot occur.

5.10 /<X>/DT_in_held_waiting_calls/

The Domain Transfer in held_waiting calls leaf indicates whether a VCC domain transfer is restricted when the VCC UE is engaged in an active and a held/waiting call/session on the transferring-out domain (the restriction doesn't apply in the case the VCC UE is losing coverage in the transferring-out domain). If the operator policy requires restriction in the Domain Transfer in held_waiting calls then the VCC UE should not consider other operator policy for the domain transfer.

- Occurrence: One

- Format: bool

- Access Types: Get, Replace

- Values: 0, 1

0 – Indicates that the network operator prefers the domain transfer can occur when the VCC UE is engaged in an active and a held/waiting call/session on the transferring-out domain.

1 – Indicates that the network operator prefers the domain transfer cannot occur when the VCC UE is engaged in an active and a held/waiting call/session on the transferring-out domain.

5.11 /<X>/STI/

The STI leaf is the SC Transfer URI that the user includes in SIP INVITE requests to initiate session transfer.

- Occurrence: One

- Format: chr

- Access Types: Get, Replace

- Values: < A SC STI >

The format of the SC STI is defined by 3GPP TS 23.003 [2].

EXAMPLE: sip:domain.xfer@dtf1.home1.net

5.12 /<X>/STN/

The STN leaf is the SC Transfer Number that the user includes in a circuit switched call setup to initiate session transfer.

- Occurrence: One

- Format: chr

- Access Types: Get, Replace

- Values: < A SC STN >

The format of the SC STN is defined by 3GPP TS 23.003 [2].

EXAMPLE: +12125555555

5.13 /<X>/OperatorPolicy

This interior node indicates the presence of an operator policy list used to allow the session transfer of the media of non-emergency sessions on the specified access networks.

- Occurrence: ZeroOrOne
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.14 /<X>/OperatorPolicy/<X>

This run-time node acts as a placeholder for one or more OperatorPolicy to allow the session transfer of the media on the specified access networks.

- Occurrence: OneOrMore
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.15 /<X>/OperatorPolicy/<X>/MediaPref

This interior node indicates one or more operator media preferences; each preference contains the operator preferences associated to each media or a group of media.

- Occurrence: One
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.16 /<X>/OperatorPolicy/<X>/MediaPref/MediaPrefId

The MediaPrefId leaf is a name for the operator media preference.

- Occurrence: One
- Format: chr
- Access Types: Get, Replace
- Values: < preference number X >

5.17 /<X>/OperatorPolicy/<X>/MediaPref/MediaorGroups

This interior node indicates one or more media or group of media access networks that are subject to the operator preferences.

- Occurrence: OneOrMore
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.18 /<X>/OperatorPolicy/<X>/MediaPref/MediaorGroups/<X>/

This run-time node acts as a placeholder for one or more media to which the operator preferences are applicable.

- Occurrence: OneOrMore
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.19

`/<X>/OperatorPolicy/<X>/MediaPref/MediaorGroups/<X>/Media`

This leaf indicates the media, for which the operator policy are applicable by the UE with SC capabilities for session transfer

- Occurrence: One
- Format: chr
- Access Types: Get, Replace
- Values: one or more of the value coded according to the IETF RFC 4566 [7].

5.20

`/<X>/OperatorPolicy/<X>/MediaPref/RestrictedAccessNetworkType`

The RestrictedAccessNetworkType node indicates one or more restricted access technologies according to the operator preferences related to the session origination and the session transfer of the media on the specified access networks.

- Occurrence: ZeroOrOne
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.21

`/<X>/OperatorPolicy/<X>/MediaPref/RestrictedAccessNetworkType/<X>`

This run-time node acts as a placeholder for one or more access networks, according to the operator preferences to avoid the session origination and the session transfer of the media on the specified access networks.

- Occurrence: OneOrMore
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.22

`<X>/OperatorPolicy/<X>/MediaPref/RestrictedAccessNetworkType /<X>/AccessNetworkType`

The `AccessNetworkType` leaf indicates an access technology that should be avoided if the current rule is active, according to the operator preferences to avoid the session origination and the session transfer of the media on the specified access networks type.

- Occurrence: One
- Format: chr
- Access Types: Get, Replace
- Values: one of the following values:
 - coded according to the access-type field defined for the P-Access-Network-Info header in 3GPP TS 24.229 [6] ; or
 - "CS".

5.23

`<X>/OperatorPolicy/<X>/MediaPref/PreferredAccessNetworks`

The `PreferredAccessNetworks` node indicates one or more preferred access network technologies according to the operator preferences related to the session origination and the session transfer of the media on the specified access networks.

- Occurrence: ZeroOrOne
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.24 `<X>/OperatorPolicy/<X>/MediaPref/PreferredAccessNetworks/<X>`

This run-time node acts as a placeholder for one or more access networks, according to the operator policy are preferred for the session origination and the session transfer of the media on the specified access networks.

- Occurrence: OneOrMore
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.25 `<X>/OperatorPolicy/<X>/MediaPref/PreferredAccessNetworks/<X>/AccessNetworkType`

The `AccessNetworkType` leaf indicates an access technology that should be considered preferred if the current rule is active, for the session origination and the session transfer of the media on the specified access networks type.

- Occurrence: One

- Format: chr
- Access Types: Get, Replace
- Values: one of the following values:
 - coded according to the access-type field defined for the P-Access-Network-Info header in 3GPP TS 24.229 [6] ; or
 - "CS".

5.26 /<X>/OperatorPolicy/<X>/MediaPref/SC_media_transfer

This leaf provides to the UE the indication whether the media shall/should/may transferred to target access network according to the operator preferences to allow the session transfer of the media on the specified access networks.

- Occurrence: One
- Format: chr
- Access Types: Get, Replace
- Values: <shall,should,may>

shall– Indicates that the UE shall start session transfer according to the home operator's list of preferred access networks as soon as possible;

should – Indicates that the UE start session transfer according to the home operator's list of preferred access networks, if session transfer is possible and desirable after having taken into account the Local Operating Environment Information;

may - Indicates that the UE is free.to decide whether or not to start session transfer in accordance with user preferences (when configured), if session transfer is possible and desirable after having taken into account the Local Operating Environment Information.

5.27 /<X>/OperatorPolicy/<X>/MediaPref/SC_non_transferable_media /

This leaf provides to the UE the indication on the behaviour expected in case of media which cannot be transferred to other Access Networks, according to the operator preferences to allow the session transfer of the media on the specified access networks.

- Occurrence:One
- Format: chr
- Access Types: Get, Replace
- Values: <keep, drop>

keep– Indicates that the UE will prevent the execution of the media transfer for those media.

drop- Indicates that the UE will perform the media transfer dropping the non transferable media.

5.28 /<X>/InterUETransferSCCASURI/

This leaf contains the inter UE transfer SCC AS URI used in 3GPP TS 24.237 [5].

- Occurrence: One
- Format: chr
- Access Types: Get, Replace

- Value: <A SIP URI>

5.29 /<X>/Ext/

The Ext is an interior node for where the vendor specific information about the Communication Continuity MO is being placed (vendor meaning application vendor, device vendor etc.). Usually the vendor extension is identified by vendor specific name under the ext node. The tree structure under the vendor identified is not defined and can therefore include one or more un-standardized sub-trees.

- Occurrence: ZeroOrOne
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.30 /<X>/PStoPSSTIURI/

This leaf contains the PS to PS STI URI used in 3GPP TS 24.237 [5].

- Occurrence: One
- Format: chr
- Access Types: Get, Replace
- Value: <A SIP URI>

Annex A (informative): Management Object DDF

This DDF is the standardized minimal set. A vendor can define it's own DDF for the complete device. This DDF can include more features than this minimal standardized version.

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE MgmtTree PUBLIC "-//OMA//DTD-DM-DDF 1.2//EN"
"http://www.openmobilealliance.org/tech/DTD/dm_ddf-v1_2.dtd">
<MgmtTree>
  <VerDTD>1.2</VerDTD>
  <Man--The device manufacturer--</Man>
  <Mod--The device model--</Mod>

  <Node>
    <NodeName>Communication_Continuity</NodeName>
    <DFProperties>
      <AccessType>
        <Get/>
      </AccessType>
      <Description>Communication Continuity settings</Description>
      <DFFormat>
        <node/>
      </DFFormat>
      <Occurrence>
        <OneOrMore/>
      </Occurrence>
      <DFTitle>The Communication Continuity Management Object.</DFTitle>
      <DFType>
        <DDFName/>
      </DFType>
    </DFProperties>

    <Node>
      <NodeName>Name</NodeName>
      <DFProperties>
        <AccessType>
          <Get/>
        </AccessType>
        <DFFormat>
          <chr/>
        </DFFormat>
        <Occurrence>
          <ZeroOrOne/>
        </Occurrence>
        <DFTitle>User displayable name for the node.</DFTitle>
        <DFType>
          <MIME>text/plain</MIME>
        </DFType>
      </DFProperties>
    </Node>

    <Node>
      <NodeName>VDI</NodeName>
      <DFProperties>
        <AccessType>
          <Get/>
          <Replace/>
        </AccessType>
        <DFFormat>
          <chr/>
        </DFFormat>
      </DFProperties>
    </Node>
  </MgmtTree>
```

```

    </DFFormat>
    <Occurrence>
      <One/>
    </Occurrence>
    <DFTitle>The VCC Transfer URI.</DFTitle>
    <DFType>
      <DDFName/>
    </DFType>
  </DFProperties>
</Node>

<Node>
  <NodeName>VDN</NodeName>
  <DFProperties>
    <AccessType>
      <Get/>
      <Replace/>
    </AccessType>
    <DFFormat>
      <chr/>
    </DFFormat>
    <Occurrence>
      <One/>
    </Occurrence>
    <DFTitle>The VCC Transfer Number.</DFTitle>
    <DFType>
      <DDFName/>
    </DFType>
  </DFProperties>
</Node>

<Node>
  <NodeName>Preferred_domain</NodeName>
  <DFProperties>
    <AccessType>
      <Get/>
      <Replace/>
    </AccessType>
    <DFFormat>
      <chr/>
    </DFFormat>
    <Occurrence>
      <One/>
    </Occurrence>
    <DFTitle> Preferred_domain </DFTitle>
    <DFType>
      <MIME>text/plain</MIME>
    </DFType>
  </DFProperties>
</Node>

<Node>
  <NodeName>Immediate_DT</NodeName>
  <DFProperties>
    <AccessType>
      <Get/>
      <Replace/>
    </AccessType>
    <DFFormat>
      <bool/>
    </DFFormat>
    <Occurrence>

```

```
<One/>
</Occurrence>
<DFTitle>Immediate_DT</DFTitle>
<DFType>
  <MIME>text/plain</MIME>
</DFType>
</DFProperties>
</Node>

<Node>
  <NodeName>DT_CS-to-IM_CN_direction</NodeName>
  <DFProperties>
    <AccessType>
      <Get/>
      <Replace/>
    </AccessType>
    <DFFormat>
      <bool/>
    </DFFormat>
    <Occurrence>
      <One/>
    </Occurrence>
    <DFTitle> DT_CS-to-IM_CN_direction </DFTitle>
    <DFType>
      <MIME>text/plain</MIME>
    </DFType>
    </DFProperties>
  </Node>

<Node>
  <NodeName>DT_IM_CN-to-CS_direction</NodeName>
  <DFProperties>
    <AccessType>
      <Get/>
      <Replace/>
    </AccessType>
    <DFFormat>
      <bool/>
    </DFFormat>
    <Occurrence>
      <One/>
    </Occurrence>
    <DFTitle> DT_IM_CN-to-CS_direction </DFTitle>
    <DFType>
      <MIME>text/plain</MIME>
    </DFType>
    </DFProperties>
  </Node>

<Node>
  <NodeName>DT_in_held_waiting_calls</NodeName>
  <DFProperties>
    <AccessType>
      <Get/>
      <Replace/>
    </AccessType>
    <DFFormat>
      <bool/>
    </DFFormat>
    <Occurrence>
      <One/>
    </Occurrence>
```

```
<DFTitle> DT_in_held_waiting_calls </DFTitle>
<DFType>
  <MIME>text/plain</MIME>
</DFType>
</DFProperties>
</Node>
```

```
<Node>
  <NodeName>STI</NodeName>
  <DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>
    <chr/>
  </DFFormat>
  <Occurrence>
    <One/>
  </Occurrence>
  <DFTitle>The SC Transfer URI.</DFTitle>
  <DFType>
    <DDFName/>
  </DFType>
  </DFProperties>
</Node>
```

```
<Node>
  <NodeName>STN</NodeName>
  <DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>
    <chr/>
  </DFFormat>
  <Occurrence>
    <One/>
  </Occurrence>
  <DFTitle>The SC Transfer Number.</DFTitle>
  <DFType>
    <DDFName/>
  </DFType>
  </DFProperties>
</Node>
```

```
<Node>
  <NodeName>OperatorPolicy</NodeName>
  <DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>
    <node/>
  </DFFormat>
  <Occurrence>
    <One/>
  </Occurrence>
```

```

<Scope>
  <Permanent/>
</Scope>
<DFTitle>A collection of Operator Policy</DFTitle>
<DFType>
  <DDFName/>
</DFType>
</DFProperties>

<Node>
  <NodeName/>
  <DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>
    <node/>
  </DFFormat>
  <Occurrence>
    <OneOrMore/>
  </Occurrence>
  <Scope>
    <Dynamic/>
  </Scope>
  <DFTitle>The "name" node for the MediaPref object.</DFTitle>
  <DFType>
    <DDFName/>
  </DFType>
  </DFProperties>

<Node>
  <NodeName>MediaPref</NodeName>
  <DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>
    <node/>
  </DFFormat>
  <Occurrence>
    <One/>
  </Occurrence>
  <Scope>
    <Permanent/>
  </Scope>
  <DFTitle>A collection of MediaPreferences</DFTitle>
  <DFType>
    <DDFName/>
  </DFType>
  </DFProperties>

<Node>
  <NodeName>MediaPrefId</NodeName>
  <DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>
    <chr/>

```

```

</DFFormat>
<Occurrence>
  <One/>
</Occurrence>
<DFTitle>Media Preference Id</DFTitle>
<DFType>
  <MIME>text/plain</MIME>
</DFType>
</DFProperties>
</Node>

<Node>
  <NodeName>MediaorGroups</NodeName>
  <DFProperties>
    <AccessType>
      <Get/>
      <Replace/>
    </AccessType>
    <DFFormat>
      <node/>
    </DFFormat>
    <Occurrence>
      <One/>
    </Occurrence>
    <Scope>
      <Permanent/>
    </Scope>
    <DFTitle>A collection of Media or group of media</DFTitle>
    <DFType>
      <DDFName/>
    </DFType>
  </DFProperties>

  <Node>
    <NodeName/>
    <DFProperties>
      <AccessType>
        <Get/>
        <Replace/>
      </AccessType>
      <DFFormat>
        <node/>
      </DFFormat>
      <Occurrence>
        <OneOrMore/>
      </Occurrence>
      <Scope>
        <Dynamic/>
      </Scope>
      <DFTitle> Media</DFTitle>
      <DFType>
        <DDFName/>
      </DFType>
    </DFProperties>

    <Node>
      <NodeName>Media</NodeName>
      <DFProperties>
        <AccessType>
          <Get/>
          <Replace/>
        </AccessType>

```

```

    <DFFormat>
      <chr/>
    </DFFormat>
  <Occurrence>
    <One/>
  </Occurrence>
</Scope>
  <Permanent/>
</Scope>
  <DFTitle>A collection of Media</DFTitle>
  <DFType>
    <MIME>text/plain</MIME>
  </DFType>
</DFProperties>
</Node>
</Node>
</Node>

<Node>
  <NodeName>RestrictedAccessNetworkType</NodeName>
  <DFProperties>
    <AccessType>
      <Get/>
      <Replace/>
    </AccessType>
    <DFFormat>
      <node/>
    </DFFormat>
    <Occurrence>
      <One/>
    </Occurrence>
  <Scope>
    <Permanent/>
  </Scope>
  <DFTitle>A collection of Access Network Types</DFTitle>
  <DFType>
    <DDFName/>
  </DFType>
</DFProperties>

<Node>
  <NodeName/>
  <DFProperties>
    <AccessType>
      <Get/>
      <Replace/>
    </AccessType>
    <DFFormat>
      <node/>
    </DFFormat>
    <Occurrence>
      <OneOrMore/>
    </Occurrence>
  <Scope>
    <Dynamic/>
  </Scope>
  <DFTitle> Access NetworkType</DFTitle>
  <DFType>
    <DDFName/>
  </DFType>
</DFProperties>

```

```

    <Node>
      <NodeName>AccessNetworkType</NodeName>
      <DFProperties>
        <AccessType>
          <Get/>
          <Replace/>
        </AccessType>
        <DFFormat>
          <node/>
        </DFFormat>
        <Occurrence>
          <ZeroOrOne/>
        </Occurrence>
        <Scope>
          <Permanent/>
        </Scope>
        <DFTitle>A collection of access network type</DFTitle>
        <DFType>
          <DDFName/>
        </DFType>
      </DFProperties>
    </Node>
  </Node>
  <Node>
    <NodeName>PreferredAccessNetworks</NodeName>
    <DFProperties>
      <AccessType>
        <Get/>
        <Replace/>
      </AccessType>
      <DFFormat>
        <node/>
      </DFFormat>
      <Occurrence>
        <One/>
      </Occurrence>
      <Scope>
        <Permanent/>
      </Scope>
      <DFTitle>A collection of Access Network Types</DFTitle>
      <DFType>
        <DDFName/>
      </DFType>
    </DFProperties>

    <Node>
      <NodeName/>
      <DFProperties>
        <AccessType>
          <Get/>
          <Replace/>
        </AccessType>
        <DFFormat>
          <node/>
        </DFFormat>
        <Occurrence>
          <OneOrMore/>
        </Occurrence>
        <Scope>
          <Dynamic/>
        </Scope>
      </DFProperties>
    </Node>
  </Node>

```



```

    </Scope>
    <DFTitle> Access Network Type</DFTitle>
    <DFType>
    <DDFName/>
    </DFType>
  </DFProperties>

  <Node>
    <NodeName>AccessNetworkType</NodeName>
    <DFProperties>
    <AccessType>
      <Get/>
      <Replace/>
    </AccessType>
    <DFFormat>
      <node/>
    </DFFormat>
    <Occurrence>
      <ZeroOrOne/>
    </Occurrence>
    <Scope>
      <Permanent/>
    </Scope>
    <DFTitle>A collection of access network type</DFTitle>
    <DFType>
      <DDFName/>
    </DFType>
    </DFProperties>
  </Node>
</Node>
</Node>

```

```

<Node>
  <NodeName>SC_media_transfer</NodeName>
  <DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>
    <chr/>
  </DFFormat>
  <Occurrence>
    <One/>
  </Occurrence>
  <DFTitle>SC_media_transfer </DFTitle>
  <DFType>
    <MIME>text/plain</MIME>
  </DFType>
  </DFProperties>
</Node>

```

```

<Node>
  <NodeName>SC_non_transferable_media</NodeName>
  <DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>

```

```

    <bool/>
  </DFFormat>
  <Occurrence>
    <One/>
  </Occurrence>
  <DFTitle> SC_non_transferable_media </DFTitle>
  <DFType>
    <MIME>text/plain</MIME>
  </DFType>
  </DFProperties>
</Node>
</Node>
</Node>
</Node>

```

```

<Node>
  <NodeName>InterUETransferSCCASURI</NodeName>
  <DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>
    <chr/>
  </DFFormat>
  <Occurrence>
    <One/>
  </Occurrence>
  <DFTitle>the inter UE transfer SCC AS URI</DFTitle>
  <DFType>
    <DDFName/>
  </DFType>
  </DFProperties>
</Node>

```

```

<Node>
  <NodeName>Ext</NodeName>
  <!-- The Extension node starts here. -->
  <DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>
    <node/>
  </DFFormat>
  <Occurrence>
    <ZeroOrOne/>
  </Occurrence>
  <DFTitle>A collection of all Extension objects.</DFTitle>
  <DFType>
    <DDFName/>
  </DFType>
  </DFProperties>
</Node>

```

```

</Node>

```

```

<Node>
  <NodeName>PStoPSSTIURI</NodeName>

```

```

<DFProperties>
  <AccessType>
    <Get/>
    <Replace/>
  </AccessType>
  <DFFormat>
    <chr/>
  </DFFormat>
  <Occurrence>
    <One/>
  </Occurrence>
  <DFTitle>the PS to PS STI URI</DFTitle>
  <DFType>
    <DDFName/>
  </DFType>
</DFProperties>
</Node>

```

```

</MgmtTree>

```

Annex B (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New	WG doc
2007-01					Version 0.0.0: Preliminary proposal		0.0.0	
2007-01					Version 0.0.1: Version after CT1#45	0.0.0	0.0.1	
2007-02					Version 2.0.0: Editor introduced TS number, sent to TSG CT 35 for information and approval	0.0.1	1.0.0	
2007-03					Version 1.0.0 approved by CT#35 in CP-070128 and version 7.0.0 created by MCC	1.0.0	7.0.0	
2007-06	CT#36	CP-070377	0001	1	Corrections to parameters in 24.216	7.0.0	7.1.0	C1-070942
2007-06	CT#36	CP-070377	0002	1	Introduction of operator policies	7.0.0	7.1.0	C1-071341
2007-09	CT-37	CP-070593	0003		Editorial modification of the CC object	7.1.0	7.2.0	C1-071541
2008-12	CT-42	CP-080874	0008		CC MO URN	7.2.0	7.3.0	C1-085083
2008-12	CT-42				Introduction of STI, STN in SC MO and IMS SC Operator Policy coding	7.3.0	8.0.0	
2008-12	CT-42	CP-080968	0009		Editorial cleanup by MCC	7.3.0	8.0.0	
2009-03	CT-43	CP-090119	0011	1	MO syntax correction	8.0.0	8.1.0	C1-091022
2009-03	CT-43	CP-090147	0012	1	IMS SC Operator Policy coding	8.0.0	8.1.0	C1-090917
2009-03	CT-43	CP-090119	0014		MO DDF XML bug fix	8.0.0	8.1.0	C1-090291
2009-09	CT-45	CP-090669	0016	2	Alignment with stage 2	8.1.0	8.2.0	C1-093020
2009-12	CT-46				Upgrade to Rel-9	8.2.0	9.0.0	
2010-03	CT-47	CP-100142	0019		Inter UE Transfer SCC AS URI	9.0.0	9.1.0	C1-100706
2010-06	CT-48	CP-100344	0021	1	Update scope of TS to correctly cover functionality specified.	9.1.0	9.2.0	C1-101898
2010-09	CT-49				Correcting DDF and Description of Communication Continuity MO	9.2.0	9.3.0	
2010-09	CT-49	CP-100493	0023	1				C1-102698
2010-09	CT-49	CP-100519	0029	2	Insertion of missing requirement to prohibit PS-CS continuity	9.3.0	10.0.0	C1-103505
2012-09	CT-57				Upgrade to Rel-11	10.0.0	11.0.0	
2012-12	CT-58	CP-120793	0030	1	PS to PS STI URI configuration	11.0.0	11.1.0	C1-124870
2014-09	CT-65				Upgrade to Rel-12	11.1.0	12.0.0	
2015-12	CT-70				Upgrade to Rel-13	12.0.0	13.0.0	

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2016-09	CT-73	CP-160518	0031		F	Emergency calls not impacted by the policy in /<X>/OperatorPolicy	14.0.0
2018-06	CT-80					Upgrade to Rel-15	15.0.0
2020-07	SA-88e	-	-	-	-	Update to Rel-16 version (MCC)	16.0.0
2022-03	SA-95e	-	-	-	-	Update to Rel-17 version (MCC)	17.0.0
2024-04	-	-	-	-	-	Update to Rel-18 version (MCC)	18.0.0

History

Document history		
V18.0.0	May 2024	Publication