

ETSI TS 124 368 V14.1.0 (2017-04)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Non-Access Stratum (NAS)
configuration Management Object (MO)
(3GPP TS 24.368 version 14.1.0 Release 14)**



Reference

RTS/TSGC-0124368ve10

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, PLUGTESTS™, UMTS™ and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are NOT allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|---|-----------|
| Intellectual Property Rights | 2 |
| Foreword..... | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 4 |
| 1 Scope | 5 |
| 2 References | 5 |
| 3 Definitions, symbols and abbreviations | 5 |
| 3.1 Definitions | 5 |
| 3.2 Abbreviations | 6 |
| 4 NAS configuration MO | 6 |
| 5 NAS configuration MO parameters | 7 |
| 5.1 General | 7 |
| 5.2 Node: <X> | 7 |
| 5.3 <X>/NAS_SignallingPriority | 8 |
| 5.4 <X>/AttachWithIMSI..... | 8 |
| 5.5 <X>/MinimumPeriodicSearchTimer | 8 |
| 5.6 <X>/NMO_I_Behaviour..... | 8 |
| 5.7 <X>/Timer_T3245_Behaviour | 9 |
| 5.8 <X>/ExtendedAccessBarring | 9 |
| 5.9 <X>/Override_NAS_SignallingLowPriority | 9 |
| 5.10 <X>/Override_ExtendedAccessBarring | 10 |
| 5.10a <X>/FastFirstHigherPriorityPLMNSearch | 10 |
| 5.10b <X>/EUTRADisablingAllowedForEMMCause15 | 10 |
| 5.10c <X>/SM_RetryWaitTime | 11 |
| 5.10d <X>/SM_RetryAtRATChange | 11 |
| 5.10e <X>/Default_DCN_ID | 11 |
| 5.10f /<X>/3GPP_PS_data_off..... | 12 |
| 5.10g /<X>/3GPP_PS_data_off/Exempted_service_list..... | 12 |
| 5.10h /<X>/3GPP_PS_data_off/Exempted_service_list/<X> | 12 |
| 5.10i /<X>/3GPP_PS_data_off/Exempted_service_list/<X>/Device_management_over_PS | 12 |
| 5.10j /<X>/3GPP_PS_data_off/Exempted_service_list/<X>/Bearer_independent_protocol..... | 13 |
| 5.11 <X>/Ext | 13 |
| 5.12 <X>/ExceptionDataReportingAllowed..... | 13 |
| Annex A (informative): NAS configuration MO DDF | 14 |
| Annex B (informative): Change history | 19 |
| History | 20 |

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document defines a Management Object (MO) that can be used to configure the UE with parameters related to Non-Access Stratum (NAS) functionality.

The MO is compatible with the OMA Device Management (DM) protocol specifications, version 1.2 and upwards, and is defined using the OMA DM Device Description Framework (DDF) as described in the Enabler Release Definition OMA-ERELD-DM-V1_2 [2].

The MO consists of relevant parameters for NAS related configuration of a UE.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] OMA-ERELD-DM-V1_2: "Enabler Release Definition for OMA Device Management".
- [3] 3GPP TS 23.122: "Non-Access-Stratum (NAS) functions related to Mobile Station (MS) in idle mode".
- [4] 3GPP TS 24.008: "Mobile radio interface Layer 3 specification; Core network protocols; Stage 3".
- [5] 3GPP TS 24.301: "Non-Access-Stratum (NAS) protocol for Evolved Packet System (EPS); Stage 3".
- [5A] 3GPP TS 23.401: "GPRS enhancements for E-UTRAN access".
- [6] 3GPP TS 31.102: "Characteristics of the USIM Application".
- [7] 3GPP TS 31.111: "Universal Subscriber Identity Module (USIM) Application Toolkit (USAT)".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] apply.

Reserved: The value "reserved" is assigned to a code point to indicate that it is reserved for future use. The present document specifies no processing rules for handling of "reserved" value by the receiving entity.

For the purposes of the present document, the following terms and definitions given in 3GPP TS 23.122 [6] apply:

HPLMN
EHPLMN

For the purposes of the present document, the following terms and definitions given in 3GPP TS 24.301 [5] apply:

In NB-S1 mode

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

| | |
|-----|------------------------------|
| ACL | Access Control List |
| DDF | Device Description Framework |
| DM | Device Management |
| MO | Management Object |
| NAS | Non-Access Stratum |
| OMA | Open Mobile Alliance |

4 NAS configuration MO

The NAS configuration MO is used to manage configuration parameters related to NAS functionality for a UE supporting provisioning of such information. The presence and format of the non-access stratum configuration file on the USIM is specified in 3GPP TS 31.102 [6].

The MO identifier is: urn:oma:mo:ext-3gpp-nas-config:1.0.

The OMA DM Access Control List (ACL) property mechanism (see OMA-ERELD-DM-V1_2 [2]) may be used to grant or deny access rights to OMA DM servers in order to modify nodes and leaf objects of the NAS configuration MO.

The following nodes and leaf objects are possible in the NAS configuration MO as described in figure 4-1:




Figure 4-1: The NAS configuration Management Object

5 NAS configuration MO parameters

5.1 General

This clause describes the parameters for the NAS configuration MO.

5.2 Node: <X>

This interior node acts as a placeholder for zero or one accounts for a fixed node.

- Occurrence: ZeroOrOne
- Format: node
- Access Types: Get
- Values: N/A

5.3 <X>/NAS_SignallingPriority

The NAS_SignallingPriority leaf indicates a NAS signalling priority which is used to determine the setting of the low priority indicator to be included in NAS messages as specified in 3GPP TS 24.008 [4] and 3GPP TS 24.301 [5].

- Occurrence: ZeroOrOne
- Format: int
- Access Types: Get, Replace
- Values: <NAS signalling priority>

Possible values for the NAS signalling priority are specified in table 5.3.1.

Table 5.3.1: Values of NAS_SignallingPriority leaf

| Value | Description |
|-------|-----------------------------|
| 0 | Reserved |
| 1 | NAS signalling low priority |
| 2-255 | Reserved |

5.4 <X>/AttachWithIMSI

The AttachWithIMSI leaf indicates whether attach with IMSI is performed when moving to a non-equivalent PLMN as specified in 3GPP TS 24.008 [4] and 3GPP TS 24.301 [5].

- Occurrence: ZeroOrOne
- Format: bool
- Access Types: Get, Replace
- Values: 0, 1
 - 0 Indicates that normal behaviour is applied.
 - 1 Indicates that attach with IMSI is performed when moving to a non-equivalent PLMN.

The default value 0 applies if this leaf is not provisioned.

5.5 <X>/MinimumPeriodicSearchTimer

The MinimumPeriodicSearchTimer leaf gives a minimum value in minutes for the timer T controlling the periodic search for higher prioritized PLMNs as specified in 3GPP TS 23.122 [3].

- Occurrence: ZeroOrOne
- Format: int
- Access Types: Get, Replace
- Values: 0-255

The default value 0 applies if this leaf is not provisioned.

5.6 <X>/NMO_I_Behaviour

The NMO_I_Behaviour leaf indicates whether the "NMO I, Network Mode of Operation I" indication as specified in 3GPP TS 24.008 [4] is applied by the UE.

- Occurrence: ZeroOrOne

- Format: bool
- Access Types: Get, Replace
- Values: 0, 1
 - 0 Indicates that the "NMO I, Network Mode of Operation I" indication is not used.
 - 1 Indicates that the "NMO I, Network Mode of Operation I" indication is used, if available.

The default value 0 applies if this leaf is not provisioned.

5.7 <X>/Timer_T3245_Behaviour

The Timer_T3245_Behaviour leaf indicates whether the timer T3245 and the related functionality as specified in 3GPP TS 24.008 [4] and 3GPP TS 24.301 [5] is used by the UE.

- Occurrence: ZeroOrOne
- Format: bool
- Access Types: Get, Replace
- Values: 0, 1
 - 0 Indicates that the timer T3245 is not used.
 - 1 Indicates that the timer T3245 is used.

The default value 0 applies if this leaf is not provisioned.

5.8 <X>/ExtendedAccessBarring

The ExtendedAccessBarring leaf indicates whether the extended access barring is applicable for the UE as specified in 3GPP TS 24.008 [4] and 3GPP TS 24.301 [5].

- Occurrence: ZeroOrOne
- Format: bool
- Access Types: Get, Replace
- Values: 0, 1
 - 0 Indicates that the extended access barring is not applied for the UE.
 - 1 Indicates that the extended access barring is applied for the UE.

The default value 0 applies if this leaf is not provisioned.

5.9 <X>/Override_NAS_SignallingLowPriority

The Override_NAS_SignallingLowPriority leaf indicates whether the UE can override the NAS_SignallingPriority leaf node configured to NAS signalling low priority.

The setting of the low priority indicator included in NAS messages when the Override_NAS_SignallingPriority leaf exists is specified in 3GPP TS 24.008 [4] and 3GPP TS 24.301 [5].

- Occurrence: ZeroOrOne
- Format: bool
- Access Types: Get, Replace

- Values: 0, 1
- 0 Indicates that the UE cannot override the NAS signalling low priority indicator
- 1 Indicates that the UE can override the NAS signalling low priority indicator

The default value 0 applies if this leaf is not provisioned.

If provisioned, this leaf is set to the same value as that provisioned for the Override_ExtendedAccessBarring leaf, e.g., if the UE is configured to override the NAS signalling low access priority indicator, then UE is also configured to override extended access class barring (see 3GPP TS 23.401 [5A]).

5.10 <X>/Override_ExtendedAccessBarring

The Override_ExtendedAccessBarring leaf indicates whether the UE can override ExtendedAccessBarring leaf node configured to extended access barring.

The handling of extended access barring for the UE when the Override_ExtendedAccessBarring leaf exists is specified in 3GPP TS 24.008 [4] and 3GPP TS 24.301 [5].

- Occurrence: ZeroOrOne
- Format: bool
- Access Types: Get, Replace
- Values: 0, 1
- 0 Indicates that the UE cannot override extended access barring
- 1 Indicates that the UE can override extended access barring

The default value 0 applies if this leaf is not provisioned.

If provisioned, this leaf is set to the same value as that provisioned for the Override_NAS_SignallingLowPriority leaf, e.g., if the UE is configured to override the NAS signalling low access priority indicator, then UE is also configured to override extended access class barring (see 3GPP TS 23.401 [5A]).

5.10a <X>/FastFirstHigherPriorityPLMNSearch

The FastFirstHigherPriorityPLMNSearch leaf indicates whether the UE performs the first search for a higher priority PLMN after at least 2 minutes and at most T minutes upon entering a VPLMN as specified in 3GPP TS 23.122 [3].

- Occurrence: ZeroOrOne
- Format: bool
- Access Types: Get, Replace
- Values: 0, 1
- 0 Indicates that the Fast First Higher Priority PLMN Search is disabled, see 3GPP TS 23.122 [3]
- 1 Indicates that the Fast First Higher Priority PLMN Search is enabled, see 3GPP TS 23.122 [3]

The default value 0 applies if this leaf is not provisioned.

5.10b <X>/EUTRADisablingAllowedForEMMCause15

The EUTRADisablingAllowedForEMMCause15 leaf indicates whether the UE is allowed to disable the E-UTRA capability when it receives the Extended EMM cause IE with value "E-UTRAN not allowed" as described in 3GPP TS 24.301 [5].

- Occurrence: ZeroOrOne
- Format: bool
- Access Types: Get, Replace
- Values: 0, 1

0 Indicates that "E-UTRA Disabling for EMM cause #15" is disabled, see 3GPP TS 24.301 [5]

1 Indicates that "E-UTRA Disabling for EMM cause #15" is enabled, see 3GPP TS 24.301 [5]

The default value 0 applies if this leaf is not provisioned.

5.10c <X>/SM_RetryWaitTime

The SM_RetryWaitTime leaf indicates a configured UE retry wait time value applicable when in HPLMN or EHPLMN (see 3GPP TS 23.122 [3]) for controlling the UE session management retry behaviour when prior session management request was rejected by the network with cause value #8, #27, #32, #33 as specified in 3GPP TS 24.008 [4] and 3GPP TS 24.301 [5].

- Occurrence: ZeroOrOne
- Format: int
- Access Types: Get, Replace
- Values: 0-255

The default value of 12 minutes applies if this leaf is not provisioned.

SM_RetryWaitTime shall be coded in the same format as the value part of GPRS Timer 3 IE as specified in Table 10.5.163a/3GPP TS 24.008 [4] converted into a decimal value.

5.10d <X>/SM_RetryAtRATChange

The SM_RetryAtRATChange leaf indicates the UE's retry behaviour when in HPLMN or EHPLMN (see 3GPP TS 23.122 [3]) after inter-system change between S1 mode and A/Gb or Iu mode as specified in 3GPP TS 24.008 [4] and 3GPP TS 24.301 [5].

- Occurrence: ZeroOrOne
- Format: bool
- Access Types: Get, Replace
- Values: 0, 1

0 Indicates that the UE is allowed to retry the corresponding ESM procedure in S1 mode if an SM procedure was rejected in A/Gb or Iu mode, and to retry the corresponding SM procedure in A/Gb or Iu mode if an ESM procedure was rejected in S1 mode, see 3GPP TS 24.008 [4] and 3GPP TS 24.301 [5]

1 Indicates that the UE is not allowed to retry an SM procedure or the corresponding ESM procedure in any of the modes: A/Gb, Iu and S1 mode, see 3GPP TS 24.008 [4] and 3GPP TS 24.301 [5]

The default value 0 applies if this leaf is not provisioned.

5.10e <X>/Default_DCN_ID

The Default_DCN_ID leaf indicates the default DCN-ID.

- Occurrence: ZeroOrOne

- Format: int
- Access Types: Get, Replace
- Values: 0-65535

Default_DCN_ID shall be coded as DCN-ID as specified in 3GPP TS 23.003 [5], converted into a decimal value.

5.10f /<X>/3GPP_PS_data_off

The interior node contains configuration parameters for 3GPP PS data off.

- Occurrence: ZeroOrOne
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.10g /<X>/3GPP_PS_data_off/Exempted_service_list

The interior node contains one or more services which are exempted of 3GPP PS data off.

- Occurrence: One
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.10h /<X>/3GPP_PS_data_off/Exempted_service_list/<X>

This interior node acts as a placeholder for one or more nodes.

- Occurrence: ZeroOrMore
- Format: node
- Access Types: Get, Replace
- Values: N/A

5.10i

/<X>/3GPP_PS_data_off/Exempted_service_list/<X>/Device_management_over_PS

This interior node acts as a placeholder for.

- Occurrence: One
- Format: bool
- Access Types: Get, Replace
- Values: 0, 1

0 - Indicates that the device management over PS is not a 3GPP PS data off exempt service.

1 - Indicates that the device management over PS is a 3GPP PS data off exempt service.

The default value 0 applies if this leaf is not provisioned.

5.10j

/<X>/3GPP_PS_data_off/Exempted_service_list/<X>/Bearer_independent_protocol

This interior node acts as a placeholder for.

- Occurrence: One
- Format: bool
- Access Types: Get, Replace
- Values: 0, 1
 - 0 - Indicates that the bearer independent protocol is not a 3GPP PS data off exempt service (see 3GPP TS 31.111 [7]).
 - 1 - Indicates that the bearer independent protocol is a 3GPP PS data off exempt service (see 3GPP TS 31.111 [7]).

The default value 0 applies if this leaf is not provisioned.

Editor's note [WI PS_DATA_OFF-CT CR#0024]: It is for further study whether an APN list and associated packet filter(s) need to be included in the MO.

5.11 <X>/Ext

The Ext is an interior node for where the vendor specific information about the NAS configuration MO is being placed (vendor meaning application vendor, device vendor etc.). Usually the vendor extension is identified by vendor specific name under the ext node. The tree structure under the vendor identifier is not defined and can therefore include one or more un-standardized sub-trees.

- Occurrence: ZeroOrOne
- Format: node
- Access Types: Get
- Values: N/A

5.12 <X>/ExceptionDataReportingAllowed

For the UE in NB-S1 mode, the ExceptionDataReportingAllowed leaf indicates whether the UE is allowed to use the RRC establishment cause mo-ExceptionData, as specified in 3GPP TS 24.301 [5].

- Occurrence: ZeroOrOne
- Format: bool
- Access Types: Get, Replace
- Values: 0, 1
 - 0 - Indicates that the UE is not allowed to use the RRC establishment cause mo-ExceptionData.
 - 1 - Indicates that the UE is allowed to use the RRC establishment cause mo-ExceptionData.

If this leaf is not provisioned, the value of 0 is used.

Annex A (informative): NAS configuration MO DDF

This DDF is the standardized minimal set. A vendor can define its own DDF for the complete device. This DDF can include more features than this minimal standardized version.

Editor's note [WI PS_DATA_OFF-CT CR#0024]: The DDF needs to be updated with the nodes added by CR0024.

```
<?xml version="1.0" encoding="UTF-8"?>
<!DOCTYPE MgmtTree PUBLIC "-//OMA//DTD-DM-DDF 1.2//EN"
"http://www.openmobilealliance.org/tech/DTD/dm_ddf-v1_2.dtd">

<MgmtTree>
  <VerDTD>1.2</VerDTD>
  <Man>--The device manufacturer--</Man>
  <Mod>--The device model--</Mod>

  <Node>
    <NodeName/>
    <DFProperties>
      <AccessType>
        <Get/>
      </AccessType>
      <Description>NAS configuration</Description>
      <DFFormat>
        <node/>
      </DFFormat>
      <Occurrence>
        <ZeroOrOne/>
      </Occurrence>
      <DFTitle>The NAS configuration Management Object.</DFTitle>
      <DFType>
        <DDFName>urn:oma:mo:ext-3gpp-nas-config:1.0</DDFName>
      </DFType>
    </DFProperties>

    <Node>
      <NodeName>NAS_SignallingPriority</NodeName>
      <DFProperties>
        <AccessType>
          <Get/>
          <Replace/>
        </AccessType>
        <DFFormat>
          <int/>
        </DFFormat>
        <Occurrence>
          <ZeroOrOne/>
        </Occurrence>
        <DFTitle>NAS Signalling Priority.</DFTitle>
        <DFType>
          < MIME>text/plain</ MIME>
        </DFType>
      </DFProperties>
    </Node>

    <Node>
      <NodeName>AttachWithIMSI</NodeName>
      <DFProperties>
        <AccessType>
          <Get/>
          <Replace/>
        </AccessType>
        <DFFormat>
          <bool/>
        </DFFormat>
        <Occurrence>
          <ZeroOrOne/>
        </Occurrence>
        <DFTitle>Attach with IMSI.</DFTitle>
        <DFType>
          < MIME>text/plain</ MIME>
        </DFType>
      </DFProperties>
    </Node>
  </Node>
</MgmtTree>
```

```

        </DFProperties>
    </Node>

    <Node>
        <NodeName>MinimumPeriodicSearchTimer</NodeName>
        <DFProperties>
            <AccessType>
                <Get/>
                <Replace/>
            </AccessType>
            <DFFormat>
                <int/>
            </DFFormat>
            <Occurrence>
                <ZeroOrOne/>
            </Occurrence>
            <DFTitle>Minimum periodic search timer.</DFTitle>
            <DFType>
                < MIME>text/plain</ MIME>
            </DFType>
        </DFProperties>
    </Node>

    <Node>
        <NodeName>NMO_I_Behaviour</NodeName>
        <DFProperties>
            <AccessType>
                <Get/>
                <Replace/>
            </AccessType>
            <DFFormat>
                <bool/>
            </DFFormat>
            <Occurrence>
                <ZeroOrOne/>
            </Occurrence>
            <DFTitle>NMO I behaviour.</DFTitle>
            <DFType>
                < MIME>text/plain</ MIME>
            </DFType>
        </DFProperties>
    </Node>

    <Node>
        <NodeName>Timer_T3245_Behaviour</NodeName>
        <DFProperties>
            <AccessType>
                <Get/>
                <Replace/>
            </AccessType>
            <DFFormat>
                <bool/>
            </DFFormat>
            <Occurrence>
                <ZeroOrOne/>
            </Occurrence>
            <DFTitle>Timer T3245 Behaviour.</DFTitle>
            <DFType>
                < MIME>text/plain</ MIME>
            </DFType>
        </DFProperties>
    </Node>

    <Node>
        <NodeName>ExtendedAccessBarring</NodeName>
        <DFProperties>
            <AccessType>
                <Get/>
                <Replace/>
            </AccessType>
            <DFFormat>
                <bool/>
            </DFFormat>
            <Occurrence>
                <ZeroOrOne/>
            </Occurrence>
            <DFTitle>Extended Access Barring.</DFTitle>
            <DFType>

```

```

        < MIME>text/plain</ MIME>
    </ DFType>
</ DFProperties>
</ Node>

< Node>
    < NodeName>Override_NAS_SignallingLowPriority</ NodeName>
    < DFProperties>
        < AccessType>
            < Get/>
            < Replace/>
        </ AccessType>
        < DFFormat>
            < bool/>
        </ DFFormat>
        < Occurrence>
            < ZeroOrOne/>
        </ Occurrence>
        < DFTitle>Override NAS Signalling Low Priority.</ DFTitle>
        < DFType>
            < MIME>text/plain</ MIME>
        </ DFType>
    </ DFProperties>
</ Node>

< Node>
    < NodeName>Override_ExtendedAccessBarring</ NodeName>
    < DFProperties>
        < AccessType>
            < Get/>
            < Replace/>
        </ AccessType>
        < DFFormat>
            < bool/>
        </ DFFormat>
        < Occurrence>
            < ZeroOrOne/>
        </ Occurrence>
        < DFTitle>Override ExtendedAccessBarring.</ DFTitle>
        < DFType>
            < MIME>text/plain</ MIME>
        </ DFType>
    </ DFProperties>
</ Node>

< Node>
    < NodeName>FastFirstHigherPriorityPLMNSearch</ NodeName>
    < DFProperties>
        < AccessType>
            < Get/>
            < Replace/>
        </ AccessType>
        < DFFormat>
            < bool/>
        </ DFFormat>
        < Occurrence>
            < ZeroOrOne/>
        </ Occurrence>
        < DFTitle> FastFirstHigherPriorityPLMNSearch.</ DFTitle>
        < DFType>
            < MIME>text/plain</ MIME>
        </ DFType>
    </ DFProperties>
</ Node>

< Node>
    < NodeName>EUTRADisablingAllowedForEMMCause15</ NodeName>
    < DFProperties>
        < AccessType>
            < Get/>
            < Replace/>
        </ AccessType>
        < DFFormat>
            < bool/>
        </ DFFormat>
        < Occurrence>
            < ZeroOrOne/>
        </ Occurrence>
    </ DFProperties>
</ Node>
```

```

        </Occurrence>
        <DFTitle> EUTRADisablingAllowedForEMMCause15.</DFTitle>
        <DFType>
          < MIME>text/plain</ MIME>
        </DFType>
      </DFProperties>
    </Node>

  <Node>
    <NodeName>SM_RetryWaitTime</NodeName>
    <DFProperties>
      <AccessType>
        <Get/>
        <Replace/>
      </AccessType>
      <DFFormat>
        <int/>
      </DFFormat>
      <Occurrence>
        <ZeroOrOne/>
      </Occurrence>
      <DFTitle> SM_RetryWaitTime</DFTitle>
      <DFType>
        < MIME>text/plain</ MIME>
      </DFType>
    </DFProperties>
  </Node>

  <Node>
    <NodeName>SM_RetryAtRATChange</NodeName>
    <DFProperties>
      <AccessType>
        <Get/>
        <Replace/>
      </AccessType>
      <DFFormat>
        <bool/>
      </DFFormat>
      <Occurrence>
        <ZeroOrOne/>
      </Occurrence>
      <DFTitle> SM_RetryAtRATChange</DFTitle>
      <DFType>
        < MIME>text/plain</ MIME>
      </DFType>
    </DFProperties>
  </Node>

  <Node>
    <NodeName>ExceptionDataReportingAllowed</NodeName>
    <DFProperties>
      <AccessType>
        <Get/>
        <Replace/>
      </AccessType>
      <DFFormat>
        <bool/>
      </DFFormat>
      <Occurrence>
        <ZeroOrOne/>
      </Occurrence>
      <DFTitle> ExceptionDataReportingAllowed.</DFTitle>
      <DFType>
        < MIME>text/plain</ MIME>
      </DFType>
    </DFProperties>
  </Node>

  <Node>
    <NodeName> Default_DCN_ID</NodeName>
    <DFProperties>
      <AccessType>
        <Get/>
        <Replace/>
      </AccessType>
      <DFFormat>
        <int/>
      </DFFormat>

```

```
<Occurrence>
  <ZeroOrOne/>
</Occurrence>
<DFTitle>Default_DCN_ID </DFTitle>
<DFType>
  < MIME>text/plain</ MIME>
</DFType>
</DFProperties>
</Node>

<Node>
  <NodeName>Ext</NodeName>
  <DFProperties>
    <AccessType>
      <Get/>
    </AccessType>
    <DFFormat>
      <node/>
    </DFFormat>
    <Occurrence>
      <ZeroOrOne/>
    </Occurrence>
    <DFTitle>A collection of all extension objects.</DFTitle>
    <DFType>
      <DDFName/>
    </DFType>
  </DFProperties>
</Node>
</Node>
</MgmtTree>
```

Annex B (informative): Change history

| Change history | | | | | | | |
|----------------|--------|-----------|------|-----|--|--------|--------|
| Date | TSG # | TSG Doc. | CR | Rev | Subject/Comment | Old | New |
| 2010-10 | CT1#67 | | | | Includes the following contribution agreed by CT1: C1-104202 | | 0.1.0 |
| 2010-11 | CT1#68 | | | | Includes the following contribution agreed by CT1: C1-105247 | 0.1.0 | 0.2.0 |
| 2010-12 | CT#50 | CP-100719 | | | V1.0.0 created by MCC for presentation for information at CT-50 | 0.2.0 | 1.0.0 |
| 2010-12 | CT#50 | CP-100888 | | | V1.0.1 TS-number added at CT#50 | 1.0.0 | 1.0.1 |
| 2011-01 | CT1#69 | | | | Includes the following contributions agreed by CT1: C1-110073, C1-110308, C1-110484 | 1.0.1 | 1.1.0 |
| 2011-02 | CT1#70 | | | | Includes the following contributions agreed by CT1: C1-110790; C1-111456 | 1.1.0 | 1.2.0 |
| 2011-03 | CT-51 | CP-110153 | | | Version 2.0.0 created by MCC for presentation to CT-51 for approval | 1.2.0 | 2.0.0 |
| 2011-03 | CT-51 | | | | Version 10.0.0 created by MCC after approval at CT-51 | 2.0.0 | 10.0.0 |
| 2011-06 | CT-52 | CP-110462 | 0001 | 1 | Reference to NAS configuration in USIM | 10.0.0 | 10.1.0 |
| 2011-09 | CT-53 | CP-110695 | 0002 | 1 | Definition of reserved code point | 10.1.0 | 11.0.0 |
| 2012-06 | CT-56 | CP-120315 | 0004 | 2 | Override Low Priority Configuration | 11.0.0 | 11.1.0 |
| 2012-06 | CT-56 | | | | Re-ordering of subclauses of clause 5 | 11.1.0 | 11.1.1 |
| 2012-09 | CT-57 | CP-120589 | 0006 | | Correction on overriding configurations | 11.1.1 | 11.2.0 |
| 2013-12 | CT-62 | CP-130762 | 0007 | 3 | Fast higher priority PLMN search upon entering VPLMN | 11.2.0 | 12.0.0 |
| 2014-06 | CT-64 | CP-140331 | 0009 | | Addition of configuration parameter for EMM cause #15 extension | 12.0.0 | 12.1.0 |
| 2014-09 | CT-65 | CP-140643 | 0012 | 1 | "Override_NAS_SignallingLowPriority" and "Override_ExtendedAccessBarring" linkage | 12.1.0 | 12.2.0 |
| 2015-03 | CT-67 | CP-150069 | 0014 | 2 | Addition of UE retry configuration parameter to NAS MO | 12.2.0 | 12.3.0 |
| 2015-06 | CT-68 | CP-150323 | 0017 | 1 | Correcting DDF to be valid XML document | 12.3.0 | 13.0.0 |
| 2015-06 | CT-68 | CP-150329 | 0018 | | Clarification to the applicability of the UE retry wait time value or behaviour | 12.3.0 | 13.0.0 |
| 2015-09 | CT-69 | CP-150511 | 0020 | | NAS MO figure | 13.0.0 | 13.1.0 |
| 2015-12 | CT-70 | CP-150710 | 0021 | 1 | Setting of override EAB and override NSLP leaves | 13.1.0 | 13.2.0 |
| 2016-06 | CT-72 | CP-160309 | 0022 | 6 | UE configuration for exceptional data reporting | 13.2.0 | 13.3.0 |

| Change history | | | | | | | |
|----------------|---------|-----------|------|-----|-----|---|-------------|
| Date | Meeting | TDoc | CR | Rev | Cat | Subject/Comment | New version |
| 2016-12 | CT#74 | CP-160738 | 0023 | 2 | B | Addition of default standardized DCN-ID | 14.0.0 |
| 2017-03 | CT#75 | CP-170130 | 0024 | 4 | B | 3GPP PS data off configuration for non-SIP services | 14.1.0 |
| 2017-03 | CT#75 | CP-170122 | 0026 | 3 | F | Resolve DCN-ID length | 14.1.0 |

History

| Document history | | |
|-------------------------|------------|-------------|
| V14.1.0 | April 2017 | Publication |
| | | |
| | | |
| | | |
| | | |