

# ETSI TS 125 452 V9.0.0 (2010-01)

---

*Technical Specification*

## **Universal Mobile Telecommunications System (UMTS); UTRAN Iu-PS interface: signalling transport (3GPP TS 25.452 version 9.0.0 Release 9)**



---

**Reference**

RTS/TSGR-0325452v900

---

**Keywords**

UMTS

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

[http://portal.etsi.org/chaicor/ETSI\\_support.asp](http://portal.etsi.org/chaicor/ETSI_support.asp)

---

**Copyright Notification**

No part may be reproduced except as authorized by written permission.  
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2010.  
All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

**3GPP™** is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**LTE™** is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

**GSM®** and the GSM logo are Trade Marks registered and owned by the GSM Association.

---

## Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

---

## Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Foreword.....	4
1 Scope .....	5
2 References .....	5
3 Definitions and abbreviations.....	5
3.1 Definitions .....	5
3.2 Abbreviations .....	5
4 PCAP Signalling Bearer .....	6
4.1 Introduction .....	6
4.2 Signalling Bearer.....	6
4.3 Services Provided by the Signalling Bearer .....	6
<b>Annex A (informative): Change history .....</b>	<b>7</b>
History .....	8

---

## Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The present document specifies the signalling transport related to PCAP signalling to be used across the Iupc interface. The Iupc interface is a logical interface for the interconnection of Stand-Alone SMLC (SAS) and Radio Network Controller (RNC) components of the Universal Terrestrial Radio Access Network (UTRAN) for the UMTS system. The radio network control signalling between these nodes is based upon the Position Calculation Application Part (PCAP).

---

## 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 25.422: "UTRAN Iur Interface Signalling Transport".
- [2] ITU-T Recommendation Q.711 (1996): "Functional description of the signalling connection control part".
- [3] ITU-T Recommendation Q.712 (1996): "Definition and function of Signalling connection control part messages".
- [4] ITU-T Recommendation Q.713 (1996): "Signalling connection control part formats and codes".
- [5] ITU-T Recommendation Q.714 (1996): "Signalling connection control part procedures".
- [6] ITU-T Recommendation Q.715 (1996): "Signalling connection control part user guide".
- [7] ITU-T Recommendation Q.716 (1993): "Signalling Connection Control Part (SCCP) performance".
- [8] 3GPP TS 25.305: "Stage 2 functional specification of UE positioning in UTRAN"

---

## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the following definition applies:

**Stand-Alone SMLC (SAS):** As defined in [8].

### 3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AAL5	ATM Adaptation Layer type 5
A-GPS	Assisted GPS
ATM	Asynchronous Transfer Mode
CRNC	Controlling Radio Network Controller
GPS	Global Positioning System

GT	Global Title
IP	Internet Protocol
M3UA	SS7 MTP3 User Adaptation Layer
MTP	Message Transfer Part
PCAP	Position Calculation Application Part
RNC	Radio Network Controller
SAP	Service Access Point
SAS	Stand-Alone SMLC
SCCP	Signalling Connection Control Part
SCTP	Stream Control Transmission Protocol
SMLC	Serving Mobile Location Centre
SPC	Signalling Point Code
SRNC	Serving Radio Network Controller
SS7	Signalling System N° 7
SSCF-NNI	Service Specific Co-ordination Function – Network Node Interface
SSCOP	Service Specific Connection Oriented Protocol
SSN	Sub-System Number
UE	User Equipment
UMTS	Universal Mobile Telecommunication System
UTRAN	UMTS Terrestrial Radio Access Network

---

## 4 PCAP Signalling Bearer

### 4.1 Introduction

This clause specifies the Signalling Bearer protocol stack that supports the PCAP signalling protocol.

The following requirements on the Signalling Bearer can be stated:

- provide reliable transfer of control plane signalling messages in both connectionless mode and connection-oriented mode;
- provide separate independent connections for distinguishing individual transactions;
- provide networking and routing functions;
- provide redundancy in the signalling network;
- provide load sharing.

### 4.2 Signalling Bearer

The Iupc signalling bearer shall comply with the requirements of clause 5.2 in [1].

### 4.3 Services Provided by the Signalling Bearer

When considering the requirements that the upper layers, i.e. PCAP, have on the Signalling Bearer, there are a number of services it has to provide and a number of functions to perform. These numbers of services that the signalling bearer shall provide, to the upper layers, are stated in references [2] to [7].

---

## Annex A (informative): Change history

Date / TSG	TSG Doc.	CR	Rev	Subject/Comment	New
12/2008	-	-	-	Creation of Rel-8 version based on v7.1.0	8.0.0
12/2009	-	-	-	Creation of Rel-9 version based on v8.0.0	9.0.0



---

# History

<b>Document history</b>		
V9.0.0	January 2010	Publication