

ETSI TS 125 452 V16.0.0 (2020-08)



TECHNICAL SPECIFICATION

**Universal Mobile Telecommunications System (UMTS);
UTRAN Iu-CS interface: signalling transport
(3GPP TS 25.452 version 16.0.0 Release 16)**



ReferenceRTS/TSGR-0325452vg00

KeywordsUMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	4
<i>1</i> Scope	5
<i>2</i> References	5
<i>3</i> Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	5
<i>4</i> PCAP Signalling Bearer.....	6
4.1 Introduction	6
4.2 Signalling Bearer.....	6
4.3 Services Provided by the Signalling Bearer	6
Annex A (informative): Change history	7
History	8

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document specifies the signalling transport related to PCAP signalling to be used across the Iupc interface. The Iupc interface is a logical interface for the interconnection of Stand-Alone SMLC (SAS) and Radio Network Controller (RNC) components of the Universal Terrestrial Radio Access Network (UTRAN) for the UMTS system. The radio network control signalling between these nodes is based upon the Position Calculation Application Part (PCAP).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 25.422: "UTRAN Iur Interface Signalling Transport".
 - [2] ITU-T Recommendation Q.711 (1996-07): "Functional description of the signalling connection control part".
 - [3] ITU-T Recommendation Q.712 (1996-07): "Definition and function of Signalling connection control part messages".
 - [4] ITU-T Recommendation Q.713 (1996-07): "Signalling connection control part formats and codes".
 - [5] ITU-T Recommendation Q.714 (1996-07): "Signalling connection control part procedures".
 - [6] ITU-T Recommendation Q.715 (1996-07): "Signalling connection control part user guide".
 - [7] ITU-T Recommendation Q.716 (1993-03): "Signalling Connection Control Part (SCCP) performance".
 - [8] 3GPP TS 25.305: "Stage 2 functional specification of UE positioning in UTRAN"
-

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following definition applies:

Stand-Alone SMLC (SAS): As defined in TS 25.305 [8].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

PCAP	Position Calculation Application Part
SAP	Service Access Point
SAS	Stand-Alone SMLC
SCCP	Signalling Connection Control Part
SMLC	Serving Mobile Location Centre
UE	User Equipment

UMTS Universal Mobile Telecommunication System
UTRAN UMTS Terrestrial Radio Access Network

4 PCAP Signalling Bearer

4.1 Introduction

This clause specifies the Signalling Bearer protocol stack that supports the PCAP signalling protocol.

The following requirements on the Signalling Bearer can be stated:

- provide reliable transfer of control plane signalling messages in both connectionless mode and connection-oriented mode;
- provide separate independent connections for distinguishing individual transactions;
- provide networking and routing functions;
- provide redundancy in the signalling network;
- provide load sharing.

4.2 Signalling Bearer

The Iupc signalling bearer shall comply with the requirements of clause 5.2 in TS 25.422 [1].

4.3 Services Provided by the Signalling Bearer

When considering the requirements that the upper layers, i.e. PCAP, have on the Signalling Bearer, there are a number of services it has to provide and a number of functions to perform. These numbers of services that the signalling bearer shall provide, to the upper layers, are stated in references ITU-T Rec. Q.711 [2], ITU-T Rec. Q.712 [3], ITU-T Rec. Q.713 [4], ITU-T Rec. Q.714 [5], ITU-T Rec. Q.715 [6], and ITU-T Rec. Q.716 [7].

Annex A (informative): Change history

Date / TSG	TSG Doc.	CR	Rev	Subject/Comment	New
12/2008	-	-	-	Creation of Rel-8 version based on v7.1.0	8.0.0
12/2009	-	-	-	Creation of Rel-9 version based on v8.0.0	9.0.0
SP-49	SP-100629			Clarification on the use of References (TS 21.801 CR#0030)	9.0.1
03/2011				Creation of Rel-10 version based on v9.0.1	10.0.0
52	RP-110685	0003	1	References cleanup (25.452)	10.1.0
09/2012				Update to Rel-11 version (MCC)	11.0.0
09/2014				Update to Rel-12 version (MCC)	12.0.0
12/2015				Update to Rel-13 version (MCC)	13.0.0

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2017-03	SA#75					Promotion to Release 14 without technical change	14.0.0
2018-07	SA#80	-	-	-	-	Promotion to Release 15 without technical change	15.0.0
2020-07	SA#88-e	-	-	-	-	Update to Rel-16 version (MCC)	16.0.0

History

Document history		
V16.0.0	August 2020	Publication