
ETSITS 126 111 V3.2.0 (2000-06)

Technical Specification

Universal Mobile Telecommunications System (UMTS); Codec for Circuit Switched Multimedia Telephony Service; Modifications to H.324 (3G TS 26.111 version 3.2.0 Release 1999)



Reference
RTS/TSGS-0426111UR1

Keywords

UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from: http://www.etsi.org

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at http://www.etsi.org/tb/status/

If you find errors in the present document, send your comment to: editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2000.

All rights reserved.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://www.etsi.org/ipr).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by the ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under www.etsi.org/key.

Contents

Forev	word	4
Intro	duction	4
1	Scope	5
2	References	5
3 3.1 3.2	Definitions and abbreviations	6
4	General	6
5	Document structure	6
6 6.1 6.2 6.3 6.4 6.5 6.6 6.6.1 6.7	Functional requirements Required elements Information streams Modem Multiplex Control channel Video channels Requirements for MPEG-4 usage Audio channels Data channels	6 7 7 7 7 7 7 8
7	Terminal procedures	8
8	Optional enhancements	8
9	Interoperation with other terminals	8
10	Multipoint considerations	8
11	Maintenance	8
Anne	ex A (informative): Change Request History	9

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

In the present document is described additions, deletions, and changes made to ITU-T H.324 with annex C for the purpose of using that recommendation as a basis for the technical specification for circuit switched multimedia service in 3GPP networks. The present document does not address call setup procedures, which are described in 3G TS 26.112.

1 Scope

[10]

In ITU-T recommendation H.324 with annex C describes a generic multimedia codec for use in error-prone, wireless networks. The scope of the present document are the changes, deletions, and additions to those texts necessary to fully specify a multimedia codec for use in 3GPP networks. Note that this implicitly excludes the network interface and call setup procedures. Also excluded are any general introductions to the system components.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.

1	
• For a non-sp	ecific reference, the latest version applies.
[1]	ITU-T Recommendation H.223: "Multiplexing protocol for low bitrate multimedia communication".
[2]	ITU-T Recommendation H.223 - Annex A: "Multiplexing protocol for low bitrate multimedia communication over low error-prone channels".
[3]	ITU-T Recommendation H.223 - Annex B: "Multiplexing protocol for low bitrate multimedia communication over moderate error-prone channels".
[4]	ITU-T Recommendation H.223 - Annex C: "Multiplexing protocol for low bitrate multimedia communication over highly error-prone channels".
[5]	ITU-T Recommendation H.223 - Annex D: "Optional multiplexing protocol for low bitrate multimedia communication over highly error-prone channels".
[6]	ITU-T Recommendation H.245: "Control protocol for multimedia communication".
[7]	ITU-T Recommendation G.723.1: "Dual rate speech coder for multimedia communication transmitting at 5,3 and 6,3 kbit/s".
[8]	ITU-T Recommendation H.263: "Video coding for low bitrate communication".
[9]	ITU-T Recommendation H.261: "Video CODEC for audiovisual services at p X 64 kbit/s".

[11] 3GPP Technical Specification 3G TS 26.111: "Modifications to H.324".

[11] SGIT Technical Specification SG 18 20.111. Wouldedness to 11.321.

[12] 3GPP Technical Specification 3G TS 26.112: "Call Set Up Requirements".

[13] 3GPP Technical Reference 3G TS 26.911: "Terminal Implementor's Guide".

[14] ITU-T Recommendation X.691: "Information Technology - ASN.1 Encoding Rules - Specification of Packed Encoding Rules (PER)".

ITU-T Recommendation H.324: "Terminal for low bitrate multimedia communication".

[15] International Standard ISO/IEC 14494-2: "Information technology - Generic coding of audiovisual object - Part 2: Visual, 1999".

[16] 3GPP Technical Specification 3G TS 26.071: "Mandatory Speech Codec; General Description".

[17] 3GPP Technical Specification 3G TS 26.090: "Mandatory Speech Codec; Speech Transcoding Functions".

[18] 3GPP Technical Specification 3G TS 26.073: "Mandatory Speech Codec; ANSI C-Code".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply:

H.324: ITU-T H.324 with annex C.

3G-324M terminal: Based on ITU-T H.324 recommendation modified by 3GPP for purposes of 3GPP circuit switched network based video telephony.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

RVLC Reverse Variable Length Code

DP Data Partitioning

RM Resynchronization Marker MCU Multipoint Control Unit

4 General

The present document contains any deviations to ITU-T H.324 required for the specification of 3G-324M Terminals.

5 Document structure

The structure of H.324 is followed in the present document. Where there are no differences in a specific section, that section is skipped. Where differences are minor, only the differences are described. Where major differences exist, the section is rewritten in the present document. It is important to note that for wireless terminals, Annex C of H.324 supersedes respective portions of the main body of H.324. For the present document, these modifications are treated as if they are part of the main body of H.324. Therefore, a reader must keep in mind both the main body and Annex C of H.324 when reading the present document.

6 Functional requirements

6.1 Required elements

3G-324M implementations are not required to have each functional element except a wireless interface, H.223 with Annex A and B multiplex, and H.245 version 3 or later versions for system control protocol.

3G-324M terminals offering audio communication shall support the AMR audio codec. Support for G.723.1 is not mandatory, but recommended.

3G-324M terminals offering video communication shall support the H.263 video codec. Support for MPEG-4 simple profile and H.261 is optional.

3G-324M terminals shall support H.223 with annex A and annex B.

3G-324M terminals shall support at least 32 kbit/s minimum bit rate at the mux to wireless network interface.

6.2 Information streams

V.25ter discussion does not apply.

6.3 Modem

Does not apply.

6.4 Multiplex

3G-324M terminals shall support H.223 with annex A and annex B. All other aspects shall follow H.324 with annex C. H.223 Annex C and D are optional.

6.5 Control channel

No differences with H.324.

Should it not be possible to signal an element of the 3G-324M terminal using a published version of H.245, a procedure will be defined here.

6.6 Video channels

Support for H.261 is optional. Support for MPEG-4 is optional. MPEG-4 provides error concealment as part of the simple profile through Data Partitioning (DP), Reversible Variable Length Coding (RVLC), Resynchronization Marker (RM) and header extension code. MPEG-4 is baseline compatible with H.263.

When opening a logical channel for MPEG-4 Visual, configuration information (Visual Object Sequence Header, Visual Object Header, and Video Object Layer Header) shall be sent in the decoderConfigurationInformation parameter. The same information shall also be sent in the MPEG-4 video bitstream. If the operational mode of MPEG-4 encoder needs to be changed, the existing MPEG-4 video logical channel shall be closed and H.245 procedures for opening a new MPEG-4 video logical channel shall be started. The new operational mode shall be indicated in the parameters of the new logical channel.

6.6.1 Requirements for MPEG-4 usage

The following requirements (a)-(e) apply to the usage of specific parameters within MPEG-4.

- a) Each 3G-324M MPEG-4 decoder shall be able to decode all frame-rates up to 15 frames per second, but need not support higher rates when MPEG-4 Simple Profile Level 1 is used.
- b) Each 3G-324M MPEG-4 encoder shall use a fixed f-code value of 1 when MPEG-4 Simple Profile Level 1 is used.
- c) Each 3G-324M MPEG-4 encoder shall use a fixed intra_dc_vlc_threshold of 0 when MPEG-4 Simple Profile Level 1 is used.
- d) Each 3G-324M MPEG-4 decoder shall be able to decode all horizontal luminance pixel resolutions up to 176 pels/line when MPEG-4 Simple Profile Level 1 is used. The decoder shall not be required to support higher horizontal resolutions even if the resulting number of MBs was within the 99 MB limit stipulated in MPEG-4 Simple Profile Level 1.
- e) Each 3G-324M MPEG-4 decoder shall be able to decode all vertical luminance pixel resolutions up to 144 pels/VOP when MPEG-4 Simple Profile Level 1 is used. The decoder shall not be required to support higher vertical resolutions even if the resulting number of MBs was within the 99 MB limit stipulated in MPEG-4 Simple Profile Level 1.

6.7 Audio channels

AMR is the mandatory speech codec. Support for G.723.1 is not mandatory, but recommended. If both the receiving and transmitting terminals support AMR and G.723.1, then AMR shall be used. This applies to connections without an Multipoint Control Unit (MCU).

6.8 Data channels

No differences with H.324.

7 Terminal procedures

See 3G TS 26.112.

8 Optional enhancements

No differences with H.324.

9 Interoperation with other terminals

For further study.

10 Multipoint considerations

For further study.

11 Maintenance

No differences with H.324.

Annex A (informative): Change Request History

TSG_M EETING	TSG_DOC	SPEC	VERS_CURR ENT	VERS_N EW	CR	REV	SUBJECT
SP-05	SP-99359	26.111	3.0.1	3.0.2	001		Changes to editorial notes.
SP-06	SP-99434	26.111	3.0.2	3.1.0	002	2	Specification of coding parameters for MPEG-4 video codec
SP-06	SP-99514	26.111	3.0.2	3.1.0	003		Transmission of MPEG-4 configuration information in 3G-324M
SP-08	SP-00263	26.111	3.1.0	3.2.0	004		Changes to editorial notes

Change history					
3.0.0	June 22, 1999	Approved at TSG SA#4 meeting			
3.0.1	August 22, 1999	Copyright removed			
3.0.2	October 1999	CR approved at TSG-SA#5 meeting			
3.1.0	December 1999	CR approved at TSG-SA#6 meeting			
3.2.0	June 2000	CR approved at TSG-SA#8 meeting			

History

Document history						
V3.1.0	January 2000	Publication				
V3.2.0	June 2000	Publication				