

ETSI TS 126 141 V17.0.0 (2022-05)



**Digital cellular telecommunications system (Phase 2+) (GSM);  
Universal Mobile Telecommunications System (UMTS);  
LTE;  
5G;  
IP Multimedia System (IMS) Messaging and Presence;  
Media formats and codecs  
(3GPP TS 26.141 version 17.0.0 Release 17)**



---

**Reference**

RTS/TSGS-0426141vh00

---

**Keywords**

5G,GSM,LTE,UMTS

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our  
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction .....	4
1 Scope .....	5
2 References .....	5
3 Definitions, symbols and abbreviations .....	8
3.1 Definitions .....	8
3.2 Abbreviations .....	8
4 Formats for Static Media.....	9
4.1 Text .....	9
4.2 Still Image .....	9
4.3 Bitmap Graphics.....	9
5 Formats for Continuous Media.....	9
5.1 Speech .....	9
5.2 Audio.....	10
5.3 Video .....	10
5.4 File Format for video and associated speech/audio media types.....	10
5.5 Synthetic audio .....	11
5.6 Vector graphics .....	11
6 Media synchronisation and presentation format.....	11
<b>Annex A (informative): CSI Handling.....</b>	<b>12</b>
A.1 Introduction .....	12
A.2 Sharing personal content during CS voice call.....	12
A.3 Sharing personal content during CS multimedia call .....	12
<b>Annex B (informative): Change history .....</b>	<b>13</b>
History .....	14

---

# Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# Introduction

The 3GPP Technical Specifications TS 22.340 [55] and TS 22.141 [56] define the requirements for the 3GPP IP Multimedia Subsystem (IMS) based messaging and presence services. This Technical Specification takes the requirements into account when defining the minimal baseline and optional media codecs and message container format to be used by IMS Messaging and associated Presence service, when supported.

IMS Messaging services incorporate one or more of the following messaging types Immediate messaging, Deferred delivery messaging, and Session based messaging. With Immediate messaging the sender expects immediate message delivery in what is perceived as real time compared with Deferred messaging where the sender expects the network to deliver the message as soon as the recipient becomes available. With Session based messaging a communications association is established between two or more users before communication can take place. In the simplest form Session based messaging may be a direct communication between two users. This specification defines the media types and container formats for both the Immediate message type and the Session based message type.

The specification provides the ability to have an interoperable baseline set of media types for messaging and presence services, that will simultaneously maximise the technology re-use of the already existing 3GPP services with media types, defined in TS 26.140 [13] and TS 26.234 [14]. Simultaneously, the specification will provide the ability to indicate the IMS system about the complete set of UE media and storage capabilities relevant for the IMS messaging and presence service.

For IMS terminals capable of Combined CS and IMS (CSI) operation [59][60], the specification provides an Annex with guidelines on how to combine IMS media with CS calls.

---

# 1 Scope

The present document specifies the basic media formats and codecs to be used in the IMS Messaging and Presence services, including CSI. It defines the mandatory 'baseline' set of media types for the services. Additionally, it also targets to allow possible message content type enhancements, either 3GPP-standardized or other generally used media types, in a flexible way.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 1) [-] 1) 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 2) [-] 2) The Unicode Consortium: "The Unicode Standard", Version 2.0, Addison-Wesley Developers Press, 1996.URL: <http://www.unicode.org/>.
- [3] 3) [-] 3) ANSI X3.4, 1986: "Information Systems; Coded Character Set 7 Bit; American National Standard Code for Information Interchange".
- [4] 4) [-] 4) ISO/IEC 8859-1:1998: "Information technology; 8-bit single-byte coded graphic character sets; Part 1: Latin alphabet No. 1".
- [5] 5) [-] 5) IETF; RFC 2279: "UTF-8, A Transformation format of ISO 10646", URL: <http://www.ietf.org/rfc/rfc2279.txt>.
- [6] 6) [-] 6) 3GPP TS 24.011: "Point-to-Point (PP) Short Message Service (SMS) support on mobile radio interface".
- [7] 7) [-] 7) 3GPP TS 26.090: "AMR speech Codec Transcoding functions".
- [8] 8) [-] 8) ITU-T Recommendation T.81: "Information technology; Digital compression and coding of continuous-tone still images: Requirements and guidelines".
- [9] 9) [-] 9) "JPEG File Interchange Format", Version 1.02, September 1, 1992.
- [10] 10)[-] 10)(void)
- [11] 11)[-] 11)(void)
- [12] 12)[-] 12)ISO/IEC 14496-2 (2004): "Information technology - Coding of audio-visual objects - Part 2: Visual".
- [13] 13)[-] 13)3GPP TS 26.140: "Multimedia Messaging Service (MMS); Media formats and codecs"
- [14] 14)[-] 14)3GPP TS 26.234: "End-to-end transparent streaming Service; Protocols and codecs".
- [15] 15)[-] 15)CompuServe Incorporated: "GIF Graphics Interchange Format: A Standard defining a mechanism for the storage and transmission of raster-based graphics information", Columbus, OH, USA, 1987.
- [16] 16)[-] 16)Compuserve Incorporated, Columbus, Ohio (1990): "Graphics Interchange Format (Version 89a)".

- [17] 17)[-] 17)IETF RFC 2083: "PNG (Portable Networks Graphics) Specification version 1.0 ", T. Boutell, et. al., March 1997.
- [18] 18)[-] 18)(void)
- [19] 19)[-] 19)ISO/IEC 14496-3:2001, "Information technology -- Coding of audio-visual objects -- Part 3: Audio".
- [20] 20)[-] 20)W3C Last Call Working Draft: "Scalable Vector Graphics (SVG) 1.2", <http://www.w3.org/TR/2004/WD-SVG12-20041027/>, October 2004.
- [21] 21)[-] 21)W3C Last Call Working Draft: "Mobile SVG Profile: SVG Tiny, Version 1.2", <http://www.w3.org/TR/2004/WD-SVGMobile12-20040813/>, August 2004.
- [22] 22)[-] 22)3GPP 22.140: "Service Aspects; Stage 1; Multimedia Messaging Service".
- [23] 23)[-] 23)3GPP 23.140: "Multimedia Messaging Service (MMS); Functional Description; Stage 2".
- [24] 24)[-] 24)W3C Recommendation: "Synchronized Multimedia Integration Language (SMIL 2.0)", <http://www.w3.org/TR/2001/REC-smil20-20010807/>, August 2001.
- [25] 25)[-] 25)IETF RFC 2046: "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types".
- [26] 26)[-] 26)3GPP TS 26.071: "Mandatory Speech Codec speech processing functions; AMR Speech Codec; General description".
- [27] 27)[-] 27)3GPP TS 26.171: "AMR speech codec; General description".
- [28] 28)[-] 28)Scalable Polyphony MIDI Specification Version 1.0, RP-34, MIDI Manufacturers Association, Los Angeles, CA, February 2002.
- [29] 29)[-] 29)Scalable Polyphony MIDI Device 5-to-24 Note Profile for 3GPP, RP-35, MIDI Manufacturers Association, Los Angeles, CA, February 2002.
- [30] 30)[-] 30)WAP Forum Specification: "XHTML Mobile Profile", <http://www1.wapforum.org/tech/terms.asp?doc=WAP-277-XHTMLMP-20011029-a.pdf>, October 2001.
- [31] 31)[-] 31)"Standard MIDI Files 1.0", RP-001, in "The Complete MIDI 1.0 Detailed Specification, Document Version 96.1 " The MIDI Manufacturers Association, Los Angeles, CA, USA, February 1996.
- [32] 32)[-] 32)IETF RFC 3267: " RTP payload format and file storage format for the Adaptive Multi-Rate (AMR) Adaptive Multi-Rate Wideband (AMR-WB) audio codecs ", March 2002.
- [33] 33)[-] 33)3GPP TS 26.244: "Transparent end-to-end packet switched streaming service (PSS); 3GPP file format (3GP)".
- [34] 34)[-] 34)3GPP TS 26.246: "Transparent end-to-end packet switched streaming service (PSS); 3GPP SMIL Language Profile".
- [35] 35)[-] 35)3GPP TS 26.245: "Transparent end-to-end packet switched streaming service (PSS); Timed text format".
- [36] 36)[-] 36)IETF RFC 1952 "GZIP file format specification version 4.3", Deutsch P, May 1996.
- [37] 37)[-] 37)(void)
- [38] 38)[-] 38)Mobile DLS, MMA specification v1.0. RP-41 Los Angeles, CA, USA. 2004.
- [39] 39)[-] 39)Mobile XMF Content Format Specification, MMA specification v1.0., RP-42, Los Angeles, CA, USA. 2004.
- [40] 40)[-] 40)3GPP TS 26.090: "Mandatory Speech Codec speech processing functions; Adaptive Multi-Rate (AMR) speech codec; Transcoding functions".

- [41] 41)[-] 41)3GPP TS 26.073: "ANSI-C code for the Adaptive Multi Rate (AMR) speech codec".
- [42] 42)[-] 42)3GPP TS 26.104: "ANSI-C code for the floating-point Adaptive Multi Rate (AMR) speech codec".
- [43] 43)[-] 43)3GPP TS 26.190: "Speech Codec speech processing functions; AMR Wideband speech codec; Transcoding functions".
- [44] 44)[-] 44)3GPP TS 26.173: "ANSI-C code for the Adaptive Multi Rate - Wideband (AMR-WB) speech codec".
- [45] 45)[-] 45)3GPP TS 26.204: "ANSI-C code for the Floating-point Adaptive Multi-Rate Wideband (AMR-WB) speech codec".
- [46] 46)[-] 46)3GPP TS 26.290: "Extended AMR Wideband codec; Transcoding functions".
- [47] 47)[-] 47)3GPP TS 26.304: "ANSI-C code for the Floating-point; Extended AMR Wideband codec".
- [48] 48)[-] 48)3GPP TS 26.273: "ANSI-C code for the Fixed-point; Extended AMR Wideband codec".
- [49] 49)[-] 49)3GPP TS 26.401: "General audio codec audio processing functions; Enhanced aacPlus general audio codec; General description".
- [50] 50)[-] 50)3GPP TS 26.410: "General audio codec audio processing functions; Enhanced aacPlus general audio codec; Floating-point ANSI-C code".
- [51] 51)[-] 51)3GPP TS 26.411: "General audio codec audio processing functions; Enhanced aacPlus general audio codec; Fixed-point ANSI-C code".
- [52] 52)[-] 52)void
- [53] 53)[-] 53)ISO/IEC 14496-10/FDAM1: "AVC Fidelity Range Extensions".
- [54] 54)[-] 54)3GPP TS 23.228; 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; IP Multimedia Subsystem (IMS); Stage 2.
- [55] 55)[-] 55)3GPP TS 22.340: "Stage 1, IMS Messaging Service".
- [56] 56)[-] 56)3GPP TS 22.141: "Stage 1, Presence Service".
- [57] 57)[-] 57)Standard ECMA-327: "ECMAScript 3<sup>rd</sup> Edition Compact Profile", June 2001.
- [58] 58)[-] 58)"Exchangeable image file format for digital still cameras: EXIF 2.2", Specification by the Japan Electronics and Information Technology Industries Association (JEITA), April 2002, URL: <http://www.exif.org/>.
- [59] 59)[-] 59)3GPP TS 22.279: "Combining CS and IMS services; Stage 1".
- [60] 60)[-] 60)3GPP TS 23.279: "Combining CS and IMS services; Stage 2".
- [61] 61)[-] 61)3GPP TS 26.235: "Packet switched conversational multimedia applications; Default codecs".
- [62] 62)[-] 62)3GPP TR [26.936](#): "Performance characterization of 3GPP audio codecs".
- [63] 63)[-] 63)3GPP TS [26.114](#): "IP Multimedia Subsystem (IMS); Multimedia Telephony; Media handling and interaction".



## 3 Definitions, symbols and abbreviations

### 3.1 Definitions

**Deferred delivery messaging:** A type of IMS Messaging service by which the sender expects the network to deliver the message as soon as the recipient becomes available.

**Immediate messaging:** A type of IMS Messaging service by which the sender expects immediate message delivery in (near) real time fashion.

**IMS Messaging services:** A group of services, supported by capabilities of the 3GPP IP Multimedia Subsystem 3GPP TS 22.228 [54], that allows an IMS user to send and receive messages to other users. IMS messaging services comprise of one or more types: Immediate messaging, Session based messaging and Deferred delivery messaging.

**Session based messaging:** A type of IMS Messaging service by which the sender expects immediate message delivery in (near) real time fashion. In addition the sender(s) and the receiver(s) have to join to a messaging session e.g. chat room, before message exchange can take place.

**continuous media:** media with an inherent notion of time, in the present document speech, audio, synthetic audio and video.

**static media:** media that itself does not contain an element of time, in the present document all media not defined as continuous media.

**scene description:** description of the spatial layout and temporal behaviour of a presentation, it can also contain hyperlinks.

### 3.2 Abbreviations

3GP	3GPP file format
AAC	Advanced Audio Coding
AMR	Adaptive Multi-rate Codec
CC/PP	Composite Capability/Preference Profiles
CSI	Combination of CS and IMS services
DLS	Downloadable Sounds
Enhanced aacPlus	MPEG-4 High Efficiency AAC plus MPEG-4 Parametric Stereo
EXIF	Exchangeable image file format
GIF	Graphics Interchange Format
IP	Internet Protocol
IMS	IP Multimedia Subsystem
ITU-T	International Telecommunications Union - Telecommunications
JFIF	JPEG File Interchange Format
JPEG	Joint Picture Expert Group
MIDI	Musical Instrument Digital Interface
MIME	Multipurpose Internet Mail Extensions
MM	Multimedia Message
MMS	Multimedia Messaging Service
MPEG	Motion Picture Expert Group
MP4	MPEG-4 file format
MTSI	Multimedia Telephony Service for IMS
PSS	Packet-switched Streaming Service
SBR	Spectral Band Replication
SP-MIDI	Scalable Polyphony MIDI
SVG	Scalable Vector Graphics
UTF-8	Unicode Transformation Format (the 8-bit form)
XMF	Extensible Music Format

---

## 4 Formats for Static Media

Multiple media elements shall be combined into a composite single IMS message using MIME multipart content type format as defined in RFC 2046 [25]. The media type of a single IMS message element shall be identified by its appropriate MIME type whereas the media format shall be indicated by its appropriate MIME subtype.

In order to guarantee a minimum support and compatibility between IMS Messaging and Presence Service capable terminals and OMA IMPS 1.1 capable terminals, IMS Messaging User Agent and IMS Presence User Agent supporting specific media types shall comply with the following selection of media formats:

### 4.1 Text

Plain text. Any character encoding (charset) that contains a subset of the logical characters in Unicode [2] shall be used (e.g. US-ASCII [3], ISO-8859-1 [4], UTF-8 [5], Shift\_JIS, etc.).

Unrecognized subtypes of "text" shall be treated as subtype "plain" as long as the MIME implementation knows how to handle the charset. Any other unrecognized subtype and unrecognized charset shall be treated as "application/octet - stream".

### 4.2 Still Image

For IMS terminals supporting still images, ISO/IEC JPEG [8] together with JFIF [9] shall be supported. The support for ISO/IEC JPEG only apply to the following two modes:

- mandatory: baseline DCT, non-differential, Huffman coding, as defined in table B.1, symbol 'SOF0' in [8];
- optional: progressive DCT, non-differential, Huffman coding, as defined in table B.1, symbol 'SOF2' [8].

For JPEG baseline DCT, EXIF compressed image file format should also be supported, as defined in [58]. In that case there is no requirement for the MMS Messaging and Presence client to interpret or present the EXIF parameters recorded in the file.

### 4.3 Bitmap Graphics

For IMS terminals, supporting bitmap graphics, the following bitmap graphics formats should be supported:

- GIF87a [15];
- GIF89a [16];
- PNG [17].

---

## 5 Formats for Continuous Media

In order to guarantee a minimum support and compatibility between IMS Messaging and Presence Service capable terminals and MMS capable terminals that offer support of continuous media formats (section 5) and media synchronisation and scene description (see section 6), IMS Messaging User Agent and IMS Presence User Agent supporting specific media types should in addition to formats listed in section 4 of this document comply with the following selection of media formats:

### 5.1 Speech

For IMS terminals supporting speech, the AMR codec shall be supported for narrow-band speech [26][40][41][42].

The AMR wideband speech codec [27] [43][44][45] shall be supported when wideband speech working at 16 kHz sampling frequency is supported.

When using speech media type alone, AMR or AMR-WB data stored according to the file format specified in [32] should be supported. The mandatory format is defined in clause 5.4.

Multi-channel sessions shall not be used.

## 5.2 Audio

For IMS terminals supporting audio, one or both of the following two audio codecs should be supported:

- Enhanced aacPlus [49][50][51]
- Extended AMR-WB [46][47][45]

There is no requirement that a terminal supporting decoding by one of the codecs shall also support encoding by that codec.

Specifically, based on the audio codec selection test results Extended AMR-WB is strong for the scenarios marked with blue, Enhanced aacPlus is strong for the scenarios marked with orange, and both are strong for the scenarios marked with green colour in the table below:

Content type	Music	Speech over Music	Speech between Music	Speech
Bit rate				
14 kbps mono				
18 kbps stereo				
24 kbps stereo				
24 kbps mono				
32 kbps stereo				
48 kbps stereo				

More recent information on the performance of the codecs based on more recent versions of the codecs can be found in TR 26.936 [62].

Enhanced aacPlus decoder is also able to decode MPEG-4 AAC LC content.

Extended AMR-WB decoder is also able to decode AMR-WB content.

In addition, MPEG-4 AAC Low Complexity and MPEG-4 AAC Long Term Prediction object types [19] may be supported. The maximum sampling rate to be supported by the decoder is 48 kHz. The channel configurations to be supported are mono (1/0) and stereo (2/0).

## 5.3 Video

For IMS terminals supporting video, media codecs are specified in TS 26.114 [63], clause 5.2.2. The video codecs are the same as for MTSI clients in terminals.

## 5.4 File Format for video and associated speech/audio media types

To ensure interoperability for the transport of video and associated speech/audio in an IMS Messaging and Presence client, the 3GPP file format with Basic profile shall be supported.

The usage of the 3GPP file format shall follow the technical specifications and the implementation guidelines specified in TS 26.244 [33].

## 5.5 Synthetic audio

For IMS terminals supporting synthetic audio, the Scalable Polyphony MIDI (SP-MIDI) content format defined in Scalable Polyphony MIDI Specification [28] and the device requirements defined in Scalable Polyphony MIDI Device 5-to-24 Note Profile for 3GPP [29] should be supported.

SP-MIDI content is delivered in the structure specified in Standard MIDI Files 1.0 [31], either in format 0 or format 1.

In addition the Mobile DLS instrument format defined in [38] and the Mobile XMF content format defined in [39] should be supported.

A MSS client supporting Mobile DLS shall meet the minimum device requirements defined in [38] in section 1.3 and the requirements for the common part of the synthesizer voice as defined in [38] in sections 1.2.1.2. If Mobile DLS is supported, wavetables encoded with the G.711 A-law codec (wFormatTag value 0x0006, as defined in [38]) shall also be supported. The optional group of processing blocks as defined in [38] may be supported. Mobile DLS resources are delivered either in the file format defined in [38], or within Mobile XMF as defined in [39]. For Mobile DLS files delivered outside of Mobile XMF, the loading application should unload Mobile DLS instruments so that the sound bank required by the SP-MIDI profile [29] is not persistently altered by temporary loadings of Mobile DLS files.

Content that pairs Mobile DLS and SP-MIDI resources is delivered in the structure specified in Mobile XMF [39]. As defined in [39], a Mobile XMF file shall contain one SP-MIDI SMF file and no more than one Mobile DLS file. MMS clients supporting Mobile XMF must not support any other resource types in the Mobile XMF file. Media handling behaviours for the SP-MIDI SMF and Mobile DLS resources contained within Mobile XMF are defined in [39].

## 5.6 Vector graphics

For IMS terminals supporting 2D vector graphics, the Scalable Vector Graphics (SVG) Tiny 1.2 format [20][21] and ECMAScript [54] shall be supported.

NOTE 1: The compression format for SVG content is GZIP [35], in accordance with the SVG specification [20].

NOTE 2: Only media formats supported by IMS Messaging and Presence, as specified in clauses 4 and 5 of this specification, shall be used. MMS Messaging and Presence clients do not support the Ogg Vorbis format.

NOTE 3: Content creators of SVG Tiny 1.2 for IMS Messaging and Presence clients are strongly recommended to follow the content creation guidelines provided for PSS clients in Annex L of [14].

NOTE 4: If SVG Tiny 1.2 will not be published within a reasonable timeframe, the decision to adopt SVG Tiny 1.2 in favour of SVG Tiny 1.1 may be reconsidered.

---

# 6 Media synchronisation and presentation format

The 3GPP IMS Messaging and Presence uses a subset of SMIL 2.0 [24] for media synchronisation and scene description. IMS clients and servers with support for media synchronization and scene descriptions shall support the 3GPP SMIL Language Profile defined in [34].

- This profile is a subset of the SMIL 2.0 Language Profile but a superset of the SMIL 2.0 Basic Language Profile. Document [34] also includes an informative annex A that provides guidelines for SMIL content authors.

Additionally, XHTML Mobile Profile [30] for scene description should be supported. IMS clients and servers with support for scene descriptions based on XHTML shall support XHTML Mobile Profile [30], defined by the WAP Forum.

- XHTML Mobile Profile is a subset of XHTML 1.1 but a superset of XHTML Basic.

---

# Annex A (informative): CSI Handling

## A.1 Introduction

The Combination of CS and IMS services (CSI) is an operation mode combining circuit switch calls and IMS services, where the UE presents the CS and IMS services within one context to the user [59][60]. However, the capability to simultaneously render certain media types of a CS call and IMS session may be limited by a UE and capability exchange alone may not be enough to resolve such conflicts. For instance:

- During a CS speech call, a UE may not be able to render additional speech accompanying a video clip in an IMS session. This limitation is not clear if the UE has indicated that it is capable of receiving video clips.
- During a CS multimedia call, a UE may not be able to both display video from the CS call and images from the IMS session. Although the UE is not capable to fully render images and video simultaneously, it may be possible to view images in front of video.

The above conflicts are resolved by applying default rules specified in [59]. This Annex describes the UE behaviour for a number of scenarios drawn from the rules in [59]. This list may be extended in future versions of this specification.

Note that the IMS media types and formats applicable to CSI are specified in:

- clauses 6 and 9 of reference [61] for streamed media;
- clauses 4 and 5 of the present document for media delivered in messages.

---

## A.2 Sharing personal content during CS voice call

In a person-2-person communication, participants can combine a CS voice call with an IMS session and share content such as still images and video. In particular participants may share media content that is (or has been) created by the participants in the session.

TS 22.279 [59] defines that if media, or parts thereof, accepted by a user cannot be rendered by the UE simultaneously with the CS call, conflicts shall be resolved such that the user is presented with CS speech with preference over IMS speech/audio.

---

## A.3 Sharing personal content during CS multimedia call

In a person-2-person communication, participants can combine a CS multimedia call (3G-324M) with an IMS session and share content such as still images. In particular participants may share media content that is (or has been) created by the participants in the session.

TS 22.279 [59] defines that if media, or parts thereof, accepted by a user cannot be rendered by the UE simultaneously with the CS call, conflicts shall be resolved such that the user is presented with:

- CS speech with preference over IMS speech/audio;
- IMS video and images with preference over CS video.

## Annex B (informative): Change history

Change history								
TSG SA#	SA Doc.	Spec	CR	Rev	Cat	Subject/Comment	Old	New
26	SP-040835	26.141				Version 1.0.0 approved at TSG SA#26	1.0.0	6.0.0
27	SP-050098	26.141	001	1	F	Editorial correction on missing IMS Presence UA	6.0.0	6.1.0
30	SP-050789	26.141	0003	2	F	Adding missing reference numbers	6.1.0	6.2.0
30	SP-050790	26.141	0002	5	B	CSI interoperability of media types and formats	6.2.0	7.0.0
31	SP-060009	26.141	0005	1	A	Addition of a reference to TR 26.936	7.0.0	7.1.0
42		26.141				Version for Release 8	7.1.0	8.0.0
46		26.141				Version for Release 9	8.0.0	9.0.0
51		26.141				Version for Release 10	9.0.0	10.0.0
57		26.141				Version for Release 11	10.0.0	11.0.0
62	SP-130578	26.141	0006		D	Clarification of H.264 profile support requirement	11.0.0	12.0.0
63	SP-140015	26.141	0007	1	C	Video Coding Enhancements in IMS Messaging and Presence	12.0.0	12.1.0
70		26.141				Version for Release 13	12.1.0	13.0.0

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2017-03	75					Version for Release 14	14.0.0
2018-06	80					Version for Release 15	15.0.0
2020-07	-	-	-	-	-	Update to Rel-16 version (MCC)	16.0.0
2022-04	-	-	-	-	-	Update to Rel-17 version (MCC)	17.0.0

---

# History

<b>Document history</b>		
V17.0.0	May 2022	Publication