

ETSI TS 126 453 V15.0.0 (2018-07)



**Universal Mobile Telecommunications System (UMTS);  
LTE;  
Codec for Enhanced Voice Services (EVS);  
Speech codec frame structure  
(3GPP TS 26.453 version 15.0.0 Release 15)**



---

Reference

RTS/TSGS-0426453vf00

---

Keywords

LTE,UMTS

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° 7803/88

---

**Important notice**

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

**3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

**oneM2M** logo is protected for the benefit of its Members.

**GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

---

# Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

---

# Contents

Intellectual Property Rights .....	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	4
1 Scope .....	5
2 References .....	5
3 Abbreviations .....	5
4 EVS Codec generic frame format in CS Networks .....	6
4.1 General .....	6
4.2 EVS payload sizes in CS Networks.....	6
4.3 EVS generic frame header.....	7
4.4 EVS frame quality classification .....	7
4.5 EVS codec mode request in CS Networks .....	7
<b>Annex A (informative): Change history .....</b>	<b>8</b>
History .....	9

---

# Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The **Enhanced Voice Services (EVS)** Codec is specified in the series of Technical Specifications 3GPP TS 26.441 [3] to TS 26.451 [13] and it is characterized in TR 26.952 [14].

The present document describes the "generic frame format" for the EVS Codec for the application in 3G Circuit-Switched Networks. This format is based on the RTP framing, as specified in TS 26.445 [7]. This generic frame format will be used as a common reference point, when interfacing speech frames between different elements of the 3G system. Appropriate mappings to and from this generic frame format will be used within and between each system element.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TR 41.001: "GSM Specification set".
- [3] 3GPP TS 26.441: "Codec for Enhanced Voice Services (EVS); General overview".
- [4] 3GPP TS 26.442: "Codec for Enhanced Voice Services (EVS); ANSI C code (fixed-point)".
- [5] 3GPP TS 26.443: "Codec for Enhanced Voice Services (EVS); ANSI C code (floating-point)".
- [6] 3GPP TS 26.444: "Codec for Enhanced Voice Services (EVS); Test Sequences".
- [7] 3GPP TS 26.445: "Codec for Enhanced Voice Services (EVS); Detailed algorithmic description".
- [8] 3GPP TS 26.446: "Codec for Enhanced Voice Services (EVS); Adaptive Multi-Rate - Wideband (AMR-WB) backward compatible functions".
- [9] 3GPP TS 26.447: "Codec for Enhanced Voice Services (EVS); Error concealment of lost packets".
- [10] 3GPP TS 26.448: "Codec for Enhanced Voice Services (EVS); Jitter buffer management".
- [11] 3GPP TS 26.449: "Codec for Enhanced Voice Services (EVS); Comfort Noise Generation (CNG) aspects".
- [12] 3GPP TS 26.450: "Codec for Enhanced Voice Services (EVS); Discontinuous Transmission (DTX)".
- [13] 3GPP TS 26.451: "Codec for Enhanced Voice Services (EVS); Voice Activity Detection (VAD)".
- [14] 3GPP TR 26.952: "Codec for Enhanced Voice Services (EVS); Performance Characterization".

---

# 3 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

AMR-WB	Adaptive Multi-Rate - WideBand
--------	--------------------------------

CMR	Codec Mode Request (for AMR and AMR-WB and EVS)
CS	Circuit Switched
EVS	Enhanced Voice Services
EVS-CMR	CMR for EVS
EVS-SID	SID for EVS
FQC	Frame quality Classification
EVS AMR-WB IO	EVS AMR-WB Inter Operable (mode of operation)
MSB	Most Significant Bit
RTP	Real Time Protocol
SID	Silence Insertion Descriptor (for AMR and AMR-WB)
ToC	Table of Contents
WB-CMR	CMR for AMR-WB
WB-SID	SID for AMR-WB (and for EVS AMR-WB IO)

## 4 EVS Codec generic frame format in CS Networks

### 4.1 General

This clause describes the "generic frame format" of the EVS Codec in 3G CS networks for the Speech and SID frames of the primary modes of operation and the Speech and SID frames of the EVS AMR-WB IO mode of operation.

This generic frame format is illustrated in Figure 4.1-1 and it is based on the RTP format specified in TS 26.445 [7], Annex A, Figure A.3 (c), "Payload structure of Header-Full format with CMR + ToC single frame" and in TS 26.445 [7], Annex A, Figure A.6, "Payload structure for EVS AMR-WB IO SID (56 bit) payload" with the following modifications:

- The leading "1" bit,  $d(0)$ , in the CMR octet (MSB) is omitted in CS networks; bits  $d(1) \dots d(7)$  are copied bit by bit in the same order. EVS-CMR has therefore 7 bits.
- The ToC octet is omitted (Table of Contents in RTP).
- The Speech data or SID of the EVS primary and the EVS AMR-WB IO modes are copied bit by bit. Each rate has its own, unique number of bits ( $n+1$ ).
- The 40 bits of the AMR-WB SID,  $d(0) \dots d(39)$ , are copied bit by bit into the generic frame format.

Note that the order of Speech data or SID bits is the same as in in TS 26.445 [7].




Figure 4.1-1: EVS Generic Frame Format in CS Networks

### 4.2 EVS payload sizes in CS Networks

Table 4.2-1 lists all EVS Primary rates for the application in CS Networks, including No\_Data. These payload sizes are always integer multiples of 8 bits (excluding the 7-bit EVS-CMR).

**Table 4.2-1: Payload sizes for EVS Primary Rates in CS Networks**

Rate	Payload Size (bits)	Net bit rate for active speech (kbps)
No_Data	0	-
EVS Primary SID	48	-
EVS Primary 2.8	56	2,8
EVS Primary 7.2	144	7,2
EVS Primary 8.0	160	8,0
EVS Primary 9.6	192	9,6
EVS Primary 13.2	264	13,2
EVS Primary 16.4	328	16,4
EVS Primary 24.4	488	24,4

Table 4.2-2 lists all EVS AMR-WB IO rates for the application in CS Networks. In contrast to the payload sizes used in RTP, these payloads do not include any CMR overhead. These payload sizes are not always integer multiples of 8 bits (excluding the 7-bit EVS-CMR).

**Table 4.2-2: Payload sizes for EVS AMR-WB IO modes in CS Networks**

Rate	Payload Size (bits)	Net bit rate for active speech (kbps)
EVS-AMR-WB IO SID	40	-
EVS AMR-WB IO 6.6	132	6,6
EVS AMR-WB IO 8.85	177	8,85
EVS AMR-WB IO 12.65	253	12,65

### 4.3 EVS generic frame header

The EVS Codec generic frame format in CS networks has no header. The payload size defines the used Codec rate. Parameters inside this EVS payload differentiate the EVS audio bandwidth and the EVS mode of operation. For details, see TS 26.445 [7].

### 4.4 EVS frame quality classification

The EVS Codec generic frame format has no own Frame Quality Indicator. If transported on Iu and Nb the "Frame Quality Classification" (FQC) of the Iu and Nb framing protocol is used.

### 4.5 EVS codec mode request in CS Networks

The EVS Codec Mode Request (EVS-CMR) is specified in TS 26.445 [7], Annex A, Table A.3: Structure of CMR. The EVS-CMR has a size of 7 bits. The Header bit (MSB), specified in TS 26.445 [7], is omitted in CS networks.



## Annex A (informative): Change history

Change history							
Date	TSG SA #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2016-03	70	SP-160071			Presented to TSG SA#71 Plenary (for approval)	-	1.0.0
2016-03					Approved at TSG SA#71	1.0.0	13.0.0

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2017-03	75					Version for Release 14	14.0.0
2018-06	80					Version for Release 15	15.0.0

---

# History

<b>Document history</b>		
V15.0.0	July 2018	Publication