

ETSI TS 128 517 V15.0.0 (2018-06)



**LTE;
Telecommunication management;
Fault Management (FM) for mobile networks
that include virtualized network functions;
Stage 2
(3GPP TS 28.517 version 15.0.0 Release 15)**



Reference

RTS/TSGS-0528517vf00

Keywords

LTE

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2018.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and
of the 3GPP Organizational Partners.

oneM2M logo is protected for the benefit of its Members.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	5
4 General descriptions	5
5 Information model definition	6
5.1 Itf-N.....	6
5.2 Os-Ma-nfvo	6
5.3 Ve-Vnfm-em	6
5.4 Ve-Vnfm-vnf.....	6
5.5 Mapping rule for alarm information elements.....	6
5.5.1 For construction of notifyNewAlarm.....	6
5.5.2 For construction of notifyClearedAlarm.....	7
5.5.3 For construction of notifyChangedAlarm	8
5.5.4 For construction of notifyAckStateChangedAlarm	8
6 Interface definition	8
6.1 Itf-N.....	8
6.2 Ve-Vnfm-em	9
Annex A (informative): Change history	10
History	11

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management, as identified below:

TS 28.515 "Fault Management (FM) for mobile networks that include virtualized network functions; Requirements".

TS 28.516 "Fault Management (FM) for mobile networks that include virtualized network functions; Procedures".

TS 28.517 "Fault Management (FM) for mobile networks that include virtualized network functions; stage 2".

TS 28.518 "Fault Management (FM) for mobile networks that include virtualized network functions; Stage 3".

1 Scope

The present document is Fault Management stage 2 specification for mobile networks that include virtualized network functions which can be part of EPC or IMS.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
 - [2] 3GPP TS 32.111-2: "Telecommunication management; Fault Management; Part 2: Alarm Integration Reference Point (IRP); Information Service (IS)".
 - [3] 3GPP TS 32.302: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP); Information Service (IS)".
 - [4] 3GPP TS 28.515: "Telecommunication management; Fault Management (FM) for mobile networks that include virtualized network functions; Requirements".
 - [5] ETSI GS NFV-IFA 008 (V2.1.1): "Network Functions Virtualisation (NFV); Management and Orchestration; Ve-Vnfm reference point – Interface and Information Model Specification".
 - [6] 3GPP TS 28.500: "Telecommunication management; Management concept, architecture and requirements for mobile networks that include virtualized network functions".
-

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and in 3GPP TS 28.500 [6] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1] or in 3GPP TS 28.500 [6].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and in 3GPP TS 28.500 [6] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1] or in 3GPP TS 28.500 [6].

4 General descriptions

For VNF Fault Management stage 2 solution over Itf-N, the Alarm IRP IS is applicable. The overall architectural feature of Alarm IRP is specified in TS 32.111-2 [2]. The Alarm IRP IS defines the semantics of alarms and the interactions visible across the reference point in a protocol neutral way. It defines the semantics of the operations and notifications visible in the Alarm IRP. It does not define the syntax or encoding of the operations, notifications and their parameters. For the purpose of notification, Notification IRP [3] is needed.

5 Information model definition

5.1 Itf-N

For Itf-N VNF alarm management, the IOCs defined by AlarmIRP which is specified in clause 5 of 3GPP TS 32.111-2 [2] shall be used.

5.2 Os-Ma-nfvo

None.

5.3 Ve-Vnfm-em

For Ve-Vnfm-em alarm management, the information elements and notifications which are specified in subclause 9.3 of IFA 008 [5] for VNF alarm management shall be used.

5.4 Ve-Vnfm-vnf

None.

5.5 Mapping rule for alarm information elements

5.5.1 For construction of notifyNewAlarm

The following table shows the rule on how to construct the various attributes of notifyNewAlarm (see clause 6.8.1 of TS 32.111-2 [2]).

The first column shows the notifyNewAlarm notification attributes.

The second column shows the "Attributes of the Alarm information element" (see clause 9.3.4.2 of [5]) used by AlarmNotification (see clause 9.3.2 of [5]) produced by VNFM.

Table 5.5.1: Mapping rule for notifyNewAlarm

NotifyNewAlarm attributes of TS 32.111-2 [2]	Attributes of Alarm information elements in AlarmNotification of [5]	Notes
objectClass		This and the next 3GPP defined attribute are used for the DN of an MOI (whose attribute vnflInstanceList contains one vnflInstance).
objectInstance		See above
notificationId		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
eventTime	eventTime	
systemDN		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
notificationType		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
probableCause	probableCause	
perceivedSeverity	perceivedSeverity	
rootCauseIndicator	isRootCause	
alarmType	faultType	
specificProblem	faultDetails	
correlatedNotifications	correlatedAlarmId	
backedUpStatus		Not used
backUpObject		Not used
trendIndication		Not used
thresholdInfo		Not used
stateChangeDefinition		Not used
monitoredAttributes		Not used
proposedRepairActions		Not used
additionalText		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
additionalInformation	managedObjectId, vnfcid	This is a list of two elements (encoded as strings) separated by a semicolon. The first element is a string "vnfl:abc" where 'abc' is managedObjectId (of second column). The second element is a string "vnfcid:xyz" where xyz is the vnfcid (of second column).
alarmId	alarmId	

5.5.2 For construction of notifyClearedAlarm

The following table shows the rule on how to construct the various attributes of notifyClearedAlarm (see clause 6.8.3 of TS 32.111-2 [2]).

The first column shows the notifyClearedAlarm notification attributes.

The second column shows the "Attributes of the AlarmClearedNotification (see clause 9.3.3.3 of [5]) produced by VNFM.

Table 5.5.2: Mapping rule for notifyClearedAlarm

NotifyClearedAlarm attributes of TS 32.111-2 [2]	Attributes of Alarm information elements in AlarmNotification of [5]	Notes
objectClass		See Notes of Table 5.5.1
objectInstance		See Notes of Table 5.5.1
notificationId		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
eventTime	alarmClearedTime	
systemDN		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
notificationType		See entry in Table 6.8.3.2 of TS 32.111-2 [2]
probableCause		Use the probableCause of the related notifyNewAlarm
perceivedSeverity		Use the value 'cleared'.
alarmType		Use the alarmType of the related notifyNewAlarm.
correlated Notifications		See entry in Table 6.8.3.2 of TS 32.111-2 [2]
clearUserId		Not used.
clearSystemId		Not used
alarmId	alarmId	

5.5.3 For construction of notifyChangedAlarm

The following table shows the rule on how to construct the various attributes of notifyChangedAlarm (see clause 6.8.1 of TS 32.111-2 [2]).

The first column shows the notifyChangedAlarm notification attributes.

The second column shows the “Attributes of the Alarm information element” (see clause 9.3.4.2 of [5]) used by AlarmNotification (see clause 9.3.2 of [5]) produced by VNFM.

Table 5.5.3: Mapping rule for notifyChangedAlarm

NotifyChangedAlarm attributes of TS 32.111-2 [2]	Attributes of Alarm information elements in AlarmNotification of [5]	Notes
objectClass		See Notes of Table 5.5.1
objectInstance		See Notes of Table 5.5.1
notificationId		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
eventTime	alarmChangedTime	
systemDN		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
notificationType		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
probableCause	probableCause	
perceivedSeverity	perceivedSeverity	
alarmType	faultType	
alarmId	alarmId	

5.5.4 For construction of notifyAckStateChangedAlarm

The following table shows the rule on how to construct the various attributes of notifyAckStateChangedAlarm (see clause 6.8.2 of TS 32.111-2 [2]).

The first column shows the notifyAckStateChangedAlarm notification attributes.

The second column shows the “Attributes of the Alarm information element” (see clause 9.3.4.2 of [5]) used by AlarmNotification (see clause 9.3.2 of [5]) produced by VNFM.

Table 5.5.4: Mapping rule for notifyAckStateChangedAlarm

NotifyAckStateChangedAlarm attributes of [3]	Attributes of Alarm information elements in AlarmNotification of [2]	Notes
objectClass		See Notes of Table 5.5.1
objectInstance		See Notes of Table 5.5.1
notificationId		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
eventTime	eventTime	
systemDN		See above
notificationType		See entry in Table 6.8.1.2 of TS 32.111-2 [2]
probableCause	probableCause	
perceivedSeverity	perceivedSeverity	
alarmType	faultType	
alarmId	alarmId	
ackState	ackState	
ackUserId		
ackSystemId		

6 Interface definition

6.1 Itf-N

For Itf-N VNF alarm management, the operations and notifications defined by AlarmIRP which is specified in 3GPP TS 32.111-2 [2] shall be used.

6.2 Ve-Vnfm-em

For REQ-NFV_FM_Ve-Vnfm-em-FUN-1 specified in 3GPP TS 28.515 [4], the Notify operation specified in clause 7.5.3 of ETSI GS NFV-IFA 008 [5] shall be used.

For REQ-NFV_FM_Ve-Vnfm-em-FUN-2 specified in 3GPP TS 28.515 [4], the Notify operation specified in clause 7.5.3 of ETSI GS NFV-IFA 008 [5] shall be used.

For REQ-NFV_FM_Ve-Vnfm-em-FUN-3 specified in 3GPP TS 28.515 [4], the Heal VNF operation specified in clause 7.2.10 of ETSI GS NFV-IFA 008 [5] shall be used.

For REQ-NFV_FM_Ve-Vnfm-em-FUN-4 specified in 3GPP TS 28.515 [4], the Subscribe operation specified in clause 7.5.2 of ETSI GS NFV-IFA 008 [5] shall be used.

Annex A (informative): Change history

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2017-06	SA#76	SP-170505	0001	-	D	Update text in ltf-N interface clause to align with other clauses	14.1.0
2018-06	SA#80	SP-180417	0002	1	B	Scope extension to cover RAN	15.0.0

History

Document history		
V15.0.0	June 2018	Publication