

ETSI TS 128 540 V19.2.0 (2025-10)



**5G;
Management and orchestration;
5G Network Resource Model (NRM);
Stage 1
(3GPP TS 28.540 version 19.2.0 Release 19)**



Reference

RTS/TSGS-0528540vj20

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver repository](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|--|-----------|
| Intellectual Property Rights | 2 |
| Legal Notice | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 5 |
| Introduction | 5 |
| 1 Scope | 6 |
| 2 References | 6 |
| 3 Definitions and abbreviations..... | 7 |
| 3.1 Definitions | 7 |
| 3.2 Abbreviations | 7 |
| 4 Concepts and background | 8 |
| 4.1 NR and NG-RAN deployment scenarios..... | 8 |
| 4.2 MR-DC..... | 8 |
| 4.3 5GC architecture | 8 |
| 4.4 Data storage architecture | 8 |
| 4.5 AMF load balancing insides AMF Region/AMF Set | 9 |
| 4.6 5GC NFs supporting edge computing | 9 |
| 4.7 General information for network slice instance and network slice subnet instance | 9 |
| 4.8 Remote Interference Management | 9 |
| 4.9 Void..... | 9 |
| 4.10 Management of NTN..... | 9 |
| 4.10.1 Management of transparent mode feature..... | 9 |
| 4.10.2 Management of Backhaul feature | 9 |
| 4.10.3 Management of regenerative mode feature..... | 9 |
| 4.11 Management of RedCap feature | 10 |
| 4.12 Management of WAB-gNB..... | 10 |
| 4.13 Management of Ambient IoT | 11 |
| 4.14 Management of IAB-node..... | 11 |
| 5 Requirements..... | 11 |
| 5.1 Requirements for management of NG-RAN | 11 |
| 5.2 Requirements for management of MR-DC..... | 12 |
| 5.3 Requirements for management of 5GC NFs | 12 |
| 5.4 Requirements for management of AMF Set..... | 13 |
| 5.5 Requirements for management of edge computing | 13 |
| 5.6 Requirements for management of network slice and network slice subnet..... | 13 |
| 5.7 Requirements Remote Interference Management | 13 |
| 5.8 Void..... | 13 |
| 5.9 Requirements for management of NTN | 13 |
| 5.9.1 Management of transparent mode feature..... | 13 |
| 5.9.1.1 Management of transparent mode feature for NG-RAN..... | 13 |
| 5.9.1.2 Management of transparent mode feature for 5GC | 13 |
| 5.9.2 Management of Backhaul feature | 14 |
| 5.9.3 Management of UE-Satellite-UE communication feature | 14 |
| 5.9.4 Management of regenerative mode feature..... | 14 |
| 5.10 Requirements for management of RedCap feature..... | 14 |
| 5.11 Requirements for management of WAB-gNB | 14 |
| 5.12 Requirements for management of Ambient IoT | 14 |
| 5.12.1 Management of Ambient IoT for NG-RAN | 14 |
| 5.12.2 Management of Ambient IoT for 5GC | 15 |
| 5.13 Requirements for management of IAB-node..... | 15 |
| Annex A (informative): Change history | 16 |

| | |
|---------------|----|
| History | 17 |
|---------------|----|

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project Technical Specification Group Services and System Aspects Management and orchestration of networks, as identified below:

- TS 28.540: Management and orchestration of 5G networks; Network Resource Model (NRM); Stage 1.**
- TS 28.541: Management and orchestration of 5G networks; Network Resource Model (NRM); Stage 2 and stage 3.

1 Scope

The present document specifies the requirements for the Network Resource Model (NRM) definition of NR, NG-RAN, 5G Core Network (5GC) and network slice, to support the management for:

- variety of 5G radio access network functions and features, covering management for NR connectivity options defined in 3GPP TS 37.340 [5] and NG-RAN architectural options defined in 3GPP TS 38.401 [4].
- variety of 5GC network functions and features defined in 3GPP TS 23.501 [2].
- network slice and network slice subnet.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.501: "System Architecture for the 5G System".
- [3] 3GPP TS 38.300: "NR; Overall description; Stage-2".
- [4] 3GPP TS 38.401: "NG-RAN; Architecture description".
- [5] 3GPP TS 37.340: "NR; Multi-connectivity; Overall description; Stage 2".
- [6] 3GPP TS 28.531: "Management and orchestration of 5G networks; Provisioning".
- [7] 3GPP TS 23.502: "Procedures for the 5G System; Stage 2".
- [8] GSMA NG.116 – "Generic Network Slice Template" v1.0 (2019-05-23).
- [9] 3GPP TS 28.533: "Management and orchestration; Architecture framework".
- [10] 3GPP TS 38.331: "NR; Radio Resource Control (RRC); Protocol specification".
- [11] 3GPP TS 23.369: "Ambient power-enabled Internet of Things; Stage 2".
- [12] 3GPP TS 23.304: "Proximity based Services (ProSe) in the 5G System (5GS)".
- [13] 3GPP TS 28.314: "Management and orchestration; Plug and Connect; Concepts and requirements".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

5G Core Network: Defined in 3GPP TS 23.501 [2].

AMF Region: Defined in 3GPP TS 23.501 [2].

AMF Set: Defined in 3GPP TS 23.501 [2].

en-gNB: Defined in 3GPP TS 37.340 [5].

gNB: Defined in 3GPP TS 38.300 [3].

gNB Central Unit (gNB-CU): Defined in 3GPP TS 38.401 [4].

gNB-CU-Control Plane (gNB-CU-CP): Defined in 3GPP TS 38.401 [4].

gNB-CU-User Plane (gNB-CU-UP): Defined in 3GPP TS 38.401 [4].

gNB Distributed Unit (gNB-DU): Defined in 3GPP TS 38.401 [4].

ng-eNB: Defined in 3GPP TS 38.300 [3].

NG-RAN: Defined in 3GPP TS 23.501 [2].

RedCap UE: defined in 3GPP TS 38.331 [10].

eRedCap UE: defined in 3GPP TS 38.331 [10].

AIoT: defined in 3GPP TS 23.369 [11]

AIOTF: defined in 3GPP TS 23.369 [11]

ADM: defined in 3GPP TS 23.369 [11]

IAB-node: as defined in TS 38.401 [4]

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

| | |
|--------|---|
| 5GC | 5G Core network |
| 5GS | 5G System |
| ADM | AIoT Data Management |
| AIOTF | Ambient IoT Function |
| AMF | Access and Mobility Management Function |
| EN-DC | E-UTRA-NR Dual Connectivity |
| EPS | Evolved Packet System |
| IAB | Integrated Access and Backhaul |
| MR-DC | Multi-Radio Dual Connectivity |
| NG-RAN | NG Radio Access Network |
| NR | New Radio |
| PCF | Policy Control Function |
| UDM | Unified Data Management |
| UDR | Unified Data Repository |

4 Concepts and background

4.1 NR and NG-RAN deployment scenarios

According to NG-RAN architecture defined in 3GPP TS 38.300 [3], An NG-RAN node is either a gNB or an ng-eNB connected to 5GC.

A gNB may consist of a gNB-CU and one or more gNB-DU(s), and a gNB-CU may consist of a gNB-CU-CP and one or more gNB-CU-UP. From functional split point of view, there have following gNB deployment scenarios which are specified in 3GPP TS 38.401 [4]:

- 1) gNB which does not consist split function.
- 2) gNB which consists of gNB-CU and gNB-DU(s).
- 3) gNB which consists of gNB-CU-CP, gNB-CU-UP(s) and gNB-DU(s).

Abovementioned deployment scenarios apply to en-gNB also.

Part of gNB (e.g. gNB-CU) can be deployed as virtualized network function.

4.2 MR-DC

Besides single connectivity operation, E-UTRAN, NR and NG-RAN support Multi-RAT Dual Connectivity (MR-DC) operation defined in 3GPP TS 37.340 [5], which can be further divided into following two categories based on connected core network types.

- 1) MR-DC with the EPC via EN-DC, the NR node in EN-DC is called en-gNB.
- 2) MR-DC with the 5GC via either NG-RAN E-UTRA-NR Dual Connectivity (NGEN-DC) or NR-E-UTRA Dual Connectivity (NE-DC) or NR-NR Dual Connectivity (NR-DC).

There are different user plane connectivity options of the master node and secondary node involved in MR-DC (see detail in 3GPP TS 37.340 [5]).

4.3 5GC architecture

The 5G architecture is defined as service-based and the interaction between network functions is represented in the following two ways:

- Service-based representation
- Reference point representation

The network functions composed 5GC is specified in 3GPP TS 23.501 [2], network functions within the 5GC control plane shall only use service-based interfaces for their interactions.

4.4 Data storage architecture

5G system architecture allows UDM, PCF and NEF to store their data in the Unified Data Repository (UDR), and allows any NF to store and retrieve its unstructured data (e.g. UE context) into/from a UDSF.

4.5 AMF load balancing insides AMF Region/AMF Set

When deploying AMF Region or AMF Set, AMF load balancing insides AMF Region/AMF Set is achieved by setting a weight factor for each AMF according to its relative capacity compared to other AMFs, see detail in clause 5.19.3 of 3GPP TS 23.501 [2].

4.6 5GC NFs supporting edge computing

Edge computing enables operator and 3rd party services to be hosted close to the UE's access point of attachment, so as to achieve an efficient service delivery through the reduced end-to-end latency and load on the transport network, see details in clause 5.13 of 3GPP TS 23.501 [2].

4.7 General information for network slice instance and network slice subnet instance

The general information used to describe network slice instance and network slice subnet instance are specified in TS 28.531 [6].

4.8 Remote Interference Management

A remote interference scenario may involve a number of victim and aggressor cells, where the gNBs execute Remote Interference Management (RIM) coordination on behalf of their respective cells. Aggressor and victim gNBs or cells can be grouped into semi-static sets, where each cell is assigned a set ID, and is configured with a RIM Reference Signal (RIM-RS) and the radio resources associated with the set ID. As defined in TS 38.300 [3].

4.9 Void

4.10 Management of NTN

4.10.1 Management of transparent mode feature

Satellite Transparent Mode is a communication mode where a satellite functions as a simple relay or "bent-pipe" that merely forwards signals between the user equipment (UE) and the terrestrial network, without any signal processing or modification by the satellite. The 3GPP management system should provide the satellite ephemeris parameters to the gNB providing non-terrestrial access as outlined in TS 38.300 [3] to support management of NTN function. Satellite assistance information (e.g. ephemeris information) can be used for the handling of coverage holes or discontinuous satellite coverage in a power efficient way.

For a UE using a Non-Terrestrial Network that provides discontinuous coverage, 3GPP management system needs to support UE location verification, NTN access restriction and NTN mobility management.

4.10.2 Management of Backhaul feature

The AMF report the satellite backhaul category and indicates the satellite backhaul category change to SMF as outlined in TS 23.501 [2]. And the AMF can determine the Satellite backhaul category based on the information within Global RAN Node IDs associated with satellite backhaul. The 3GPP management system should provide a capability to allow the MnS consumer to configure satellite backhaul information for NTN node.

4.10.3 Management of regenerative mode feature

Fig. 4.10.3-1 illustrates an NTN system with regenerative mode, where the gNB is located onboard the satellite. In this case, the ground segment Core Network (CN) will serve the same beams all the time, while the space segment gNB on different satellites (satellite 1, 2 and 3) will serve the beam in different time periods as the satellites are approaching and leaving the coverage of the beam over time.




Figure 4.10.3-1: Non-geosynchronous satellites in NTN with regenerative gNB processed satellite payload

As defined in TS 38.300 [3], with Non-Geosynchronous orbit (NGSO) satellites, the gNB can provide either quasi-Earth-fixed cell coverage or Earth-moving cell coverage.

One consequence of non-geosynchronous satellites is that the associations between the entities on ground segment and entities in space segment are changing frequently, typically with a period of one to several minutes.

Another issue is the topology between space segment Managed Element (MnS producer) and the ground based Management System (MnS consumer): With long distances in between, disturbances (e.g. bad weather conditions), and partial reachability issues (when satellites fly over oceans with no gateway coverage), the latency, availability and reliability of the interface between them (feeder link + Inter-satellite link) are impacted.

Summary:

For the deployment scenario of RAN nodes on-board satellites, this would result in the following scenario: a LEO or MEO satellite with an onboard RAN node leaves the coverage area of a CN and then returns to the coverage area of that CN after cycling around the earth one or several times seen from the operator's perspective, it is necessary to investigate how to efficiently manage 1) The cell configuration of satellite gNBs when quasi-Earth-fixed cell coverage is applied, as the moving satellite gNB is serving different coverage areas over time. 2) The connections between RAN nodes and CN to avoid errors in CN due to stale connections, e.g. AMF sending paging requests or AMF configuration updates to an unavailable RAN node. For example, 3GPP management system configures AMF and/or gNB to add necessary information to support their awareness of when connectivity between a RAN node and a CN NF is available or unavailable.

4.11 Management of RedCap feature

RedCap is a lightweight network access solution aiming at scenarios with relatively low cost, low energy consumption, and low data rate requirement, mainly applying to scenarios such as industrial sensors, video surveillance, wearable scenarios, smart grid, etc.

NOTE: The term RedCap UE used in the present document refers to both RedCap UE and eRedCap UE defined in TS 38.331 [10].

In some scenarios, operator may want to prohibit RedCap UEs to access specific NR cells for a specified time to improve the network performance for non-RedCap UEs. After the specified time, operator will allow RedCap UEs to access specific NR cells again. So, the 3GPP management system should have the capability to allow operators to configure the NR cell to allow or prohibit RedCap UEs to access.

An initial BWP can be configured for RedCap UEs' initial access instead of initial BWP that may exceed the (e)RedCap UE maximum bandwidth. So, the 3GPP management system should have the capability to configure initial BWP separately for RedCap UEs.

4.12 Management of WAB-gNB

WAB provides an NR access link to UEs in proximity and connects to the 5GC serving the UE through an IP connectivity provided by a Backhaul PDU session(s). A WAB-node consists of a WAB-gNB and a WAB-UE. The

WAB-gNB is based on the gNB functionality specified in TS 38.300 [3] and serves UEs by means of a terrestrial NR Uu radio link. The 3GPP management system should provide the configuration parameters to the WAB-gNB to support management of WAB-gNB. The 3GPP management system should provision configuration parameters based on the current location of the WAB-node. In that case, the continuity of OAM connectivity needs to be ensured as the WAB-node moves.

The OAM provides configuration parameters for WAB-gNB including the configuraton for activating/deactivating the WAB-gNB operation, and to assist the WAB-gNB providing information used by WAB-UE for the BH PDU Session(s) management via URSP processing.

Note that the name of WAB-gNB and MWAB-gNB are used exchangeably.

4.13 Management of Ambient IoT

As defined in TS 23.369[11], Ambient IoT is a service that can be provided by the 5G system to support Ambient power-enabled IoT devices that are powered by energy harvesting, being either battery-less or with limited energy storage capability (e.g. using a capacitor) and the energy is provided through the harvesting of radio waves, light, motion, heat, or any other suitable power source. The 5GS System architecture for AIoT includes core network functions, AIoT Readers and AIoT Devices, where AIoT Reader can be supported by NG-RAN. However, to enable AIoT services such as inventory service and command service, as defined in the TS 23.369[11], it is required to correctly identify the appropriate AIOTF and RAN node instance with A-IoT capability to ensure accurate identification of AIoT devices for correctly triggering various AIoT related operations. This requires an effective mapping between the expected external target area (provided by the Application Function) and the internal target area served by the 5G Core (5GC) and RAN nodes and readers.

The AIoT service operations can work flawlessly with the help of configurations provided by Operations, Administration, and Management (OAM). The NEF can obtain internal area mapping corresponding to the external target area from OAM and use it for further processes like identifying of correct AIOTF with the help of NRF. This ensures that the NEF can accurately identify and interact with the correct internal network segments, leading to targeted service delivery. Management of Ambient IoT includes the configuration for core network functions and NG-RAN with A-IoT capability to support Ambient IoT.

4.14 Management of IAB-node

IAB architecture is specified in 3GPP TS 38.401 [4]. The management of IAB-node includes the IAB-node connectivity to management system as specified in TS 28.314 [13] and IAB-node configuration as specified in TS 28.531 [6].

5 Requirements

5.1 Requirements for management of NG-RAN

The following specific requirements apply to NG-RAN:

REQ-NGRAN_NRM-CON-001: The NRM definitions shall support management of NG-RAN, containing gNB or/and ng-eNB.

REQ-NGRAN_NRM-CON-002: The NRM definitions shall support management of either gNB without split function or gNB with split functions defined in 3GPP TS 38.401 [4].

REQ-NGRAN_NRM-CON-003: The NRM definitions shall support management of virtualized network functions that are part of gNB, e.g. virtualized gNB-CU.

REQ-NGRAN_NRM-CON-004: The NRM definitions shall support management of intra-NG-RAN handover between any combinations of gNB and ng-eNB.

REQ-NGRAN_NRM-CON-005: The NRM definitions shall support management of inter-system handover between 5GS and EPS.

REQ-NGRAN_NRM-CON-006: The NRM definitions shall support management of network slicing feature in NG-RAN.

REQ-NGRAN_NRM-CON-007: The NRM definitions shall have a read-only representation of NR beam properties in NG-RAN.

REQ-NGRAN_NRM-CON-008: The NRM definitions shall support configuration of sector carrier coverage properties in NG-RAN.

REQ-NGRAN_NRM-CON-009: The NRM definitions shall support management of radio access network sharing feature in NG-RAN.

REQ-NGRAN_NRM-CON-010: The NRM definitions shall support management of self optimization network feature in NG-RAN.

5.2 Requirements for management of MR-DC

The following specific requirements apply to MR-DC management, including management of NR in EN-DC and other MR-DC operations.

REQ-MRDC_NRM-CON-001: The NRM definitions shall support management of NR node in EN-DC operation (en-gNB).

REQ-MRDC_NRM-CON-002: The NRM definitions shall support management of en-gNB with different user plane connectivity options defined in 3GPP TS 37.340 [5].

REQ-MRDC_NRM-CON-003: The NRM definitions shall support management of NG-RAN nodes in NGEN-DC operation.

REQ-MRDC_NRM-CON-004: The NRM definitions shall support management of different user plane connectivity options in NGEN-DC operation defined in 3GPP TS 37.340 [5].

REQ-MRDC_NRM-CON-005: The NRM definitions shall support management of NG-RAN nodes in NE-DC operation.

REQ-MRDC_NRM-CON-006: The NRM definitions shall support management of different user plane connectivity options in NE-DC operation defined in 3GPP TS 37.340 [5].

REQ-MRDC_NRM-CON-007: The NRM definitions shall support management of NG-RAN nodes in NR-DC operation.

REQ-MRDC_NRM-CON-008: The NRM definitions shall support management of different user plane connectivity options in NR-DC operation defined in 3GPP TS 37.340 [5].

5.3 Requirements for management of 5GC NFs

The following specific requirements apply to management of 5GC NFs:

REQ-5GC_NRM-CON-001: The NRM definitions shall support management of 5GC containing variety of network functions defined in 3GPP TS 23.501 [2].

REQ-5GC_NRM-CON-002: The NRM definitions should support management of all the relationships between network functions and corresponding data storage functions where the network functions store/retrieve their data.

REQ-5GC_NRM-CON-003: The NRM definitions shall support management of interworking between 5GC and EPC.

REQ-5GC_NRM-CON-004: The NRM definitions shall support management of network slicing feature in 5GC.

REQ-5GC_NRM-CON-005: The NRM definitions shall support management of 5GC network function services independently to align with requirements of 3GPP TS 23.501 [2].

REQ-5GC_NRM-CON-006: The NRM definitions shall support NF service instance registration, deregistration, update, etc., with NRF during NF service instance lifecycle to align with requirements of 3GPP TS 23.501 [2] and 3GPP TS 23.502 [7].

REQ-5GC_NRM-CON-007: The NRM definitions shall support configuration of NF profile for NF Service registration and discovery to align with requirements of 3GPP TS 23.501 [2] and 3GPP TS 23.502 [7].

REQ-5GC_NRM-CON-008: The NRM definitions should support 5G ProSe Direct Discovery and Communication to align with requirements of 3GPP TS 23.304 [12].

5.4 Requirements for management of AMF Set

REQ-AMFSET_NRM-CON-001: The NRM definitions shall support management of AMF Region and AMF Set, including AMF load balancing management.

5.5 Requirements for management of edge computing

REQ-ECM_NRM-CON-001 The NRM definitions shall support management of 5GC NFs supporting edge computing.

5.6 Requirements for management of network slice and network slice subnet

The following requirements apply to network slice and network slice subnet:

REQ-NS_NRM-CON-001: The NRM definitions shall support management of network slice.

REQ-NS_NRM-CON-002: The NRM definitions shall support management of network slice subnet.

REQ-NS_NRM-CON-003: The NRM definitions shall support the attributes of the Generic network Slice Template (GST) defined by GSMA [8].

NOTE: The NEST attributes values represent the SLS requirements for a network slice. These attribute values are used as input for network slice SLA management related activities.

5.7 Requirements Remote Interference Management

REQ-RIM_NRM-CON-001: The NRM definitions should support Remote Interference Management.

5.8 Void

5.9 Requirements for management of NTN

5.9.1 Management of transparent mode feature

5.9.1.1 Management of transparent mode feature for NG-RAN

REQ-NTN_TRANS_NNRNM-001: The 3GPP management system should support management of NTN NG-RAN node.

REQ-NTN_TRANS_NNRNM-002: The 3GPP management system should support NTN mobility management.

5.9.1.2 Management of transparent mode feature for 5GC

REQ-NTN_TRANS_5GCNRM-001: The 3GPP management system should support NTN UE location verification.

REQ-NTN_TRANS_5GCNRM-002: The 3GPP management system should support NTN access restriction.

REQ-NTN_TRANS_5GCNRM-003: The 3GPP management system should support NTN mobility management.

5.9.2 Management of Backhaul feature

REQ-NTN_BACKHAUL-001: The 3GPP management system should support a capability to allow the MnS consumer to configure satellite backhaul information for NTN node.

5.9.3 Management of UE-Satellite-UE communication feature

REQ-NTN_USU_5GCNRM-001: The 3GPP management system should support NTN UE-Satellite-UE communication feature.

5.9.4 Management of regenerative mode feature

REQ-NTN_REGEN-001: The 3GPP management system shall have the capability to allow the MnS consumer to configure NTN neighbour cells considering the satellite movement.

REQ-NTN_REGEN-002: The 3GPP Management System should have the capability to allow the configuration of the connections between RAN nodes on-board satellite and 5GC considering that the availability of the management interface to the RAN nodes may be intermittent.

REQ-NTN_REGEN-003: The 3GPP Management System should have the capability to allow the configuration of the (quasi-Earth-fixed) cell configurations of RAN nodes where, due to satellite movement, the configuration requires continuous update while considering that the availability of the management interface to the RAN nodes may be intermittent.

REQ-NTN_REGEN-004: The 3GPP Management System shall have the capability to allow the MnS consumer to configure TACs for NTN cell, while considering the satellite movement.

5.10 Requirements for management of RedCap feature

REQ-RedCap_NRRM-1: The 3GPP management system should support a capability to allow MnS consumer to configure Multi-Initial BWPs to support RedCap and Non-RedCap UEs co-existence scenario.

REQ-RedCap_NRRM-2: The 3GPP management system should support a capability to allow MnS consumer to configure the NR cell to allow or prohibit RedCap UEs to access.

REQ-RedCap_NRRM-3: The 3GPP management system should support a capability to allow MnS consumer to configure initial BWP separately for RedCap UEs.

5.11 Requirements for management of WAB-gNB

REQ-VMR-CON-001: The 3GPP management system may support IP address configuraton for WAB-gNB management.

REQ-VMR-CON-002: The 3GPP management system should support TAC/RANAC (re)configuraton for WAB-gNB management.

REQ-VMR-CON-003: The 3GPP management system should support activating/deactivating the WAB-gNB operation.

5.12 Requirements for management of Ambient IoT

5.12.1 Management of Ambient IoT for NG-RAN

REQ-AIOT_NRRM-1: The 3GPP management system should support the capability to configure NG-RAN to support AIoT.

REQ-AIOT_NRNRM-2: The 3GPP management system should support the capability to configure gNB reader served A-IoT areas for management of Ambient IoT.

REQ-AIOT_NRNRM-3: The 3GPP management system should support the capability to configure reader location for management of Ambient IoT.

5.12.2 Management of Ambient IoT for 5GC

REQ-AIOT_5GCNRM-1: The 3GPP management system should support the capability to configure 5GC Network Functions to support A-IoT.

REQ-AIOT_5GCNRM-2: The 3GPP management system should support the capability to configure A-IoT areas, reader location and index for A-IoT capable gNB/reader selection.

REQ-AIOT_5GCNRM-3: The 3GPP management system should support the capability to configure NEF with mapping information between external target area and internal target area for correct identification of AIOTF.

5.13 Requirements for management of IAB-node

REQ_IAB_NRM_1: The NR NRM definitions should support location information of IAB-node.

REQ_IAB_NRM_2: The NR NRM definitions should support IP configuration for IAB-node OAM connectivity.

Annex A (informative): Change history

| Change history | | | | | | | |
|----------------|---------|-----------|------|-----|-----|--|-------------|
| Date | Meeting | TDoc | CR | Rev | Cat | Subject/Comment | New version |
| 2018-12 | SA#82 | SP-181046 | 0001 | 2 | C | Support read-only representation of NR beam properties in NG-RAN NRM definitions | 15.1.0 |
| 2019-06 | SA#84 | SP-190373 | 0002 | 1 | B | Update NRM requirement to support SBA management | 16.0.0 |
| 2019-12 | SA#86 | SP-191166 | 0003 | 2 | B | Add OAM support for RIM parameters | 16.1.0 |
| 2019-12 | SA#86 | SP-191170 | 0004 | 1 | C | Add GSMA GST mapping related requirements | 16.1.0 |
| 2019-12 | SA#86 | SP-191166 | 0007 | 1 | B | Add requirement on NR sector carrier coverage configuration | 16.1.0 |
| 2020-03 | SA#87E | SP-200169 | 0009 | - | F | Correction of requirement number | 16.2.0 |
| 2020-09 | SA#89e | SP-200748 | 0011 | - | B | Add requirements for NR NRM to support RAN sharing scenario | 17.0.0 |
| 2021-06 | SA#92e | SP-210410 | 0014 | 1 | B | Update the requirements for management of network slice and network slice subnet | 17.1.0 |
| 2021-12 | SA#94e | SP-211468 | 0016 | - | B | Add NRM requirements for authentication and authorization | 17.2.0 |
| 2022-12 | SA#98e | SP-221167 | 0019 | - | F | EditorialCorrections | 17.3.0 |
| 2024-04 | - | - | - | - | - | Update to Rel-18 version (MCC) | 18.0.0 |
| 2024-12 | SA#106 | SP-241657 | 0022 | 1 | F | Rel-18 CR TS 28.540 add missing requirements for NTN management | 18.1.0 |
| 2025-03 | SA#107 | SP-250175 | 0027 | 1 | F | Rel-18 CR TS 28.540 Remove requirements of MSAC | 18.2.0 |
| 2025-03 | SA#107 | SP-250168 | 0025 | 1 | B | Rel-19 CR TS 28.540 Requirements for NTN neighbour cell management | 19.0.0 |
| 2025-03 | SA#107 | SP-250164 | 0026 | 1 | B | Rel-19 CR TS 28.540 corrections for MR-DC related description | 19.0.0 |
| 2025-03 | SA#107 | SP-250164 | 0028 | | B | Rel-19 CR TS 28.540 add usecase and requirements for WAB-gNB management | 19.0.0 |
| 2025-03 | SA#107 | SP-250162 | 0030 | 1 | B | Rel-19 CR TS28.540 Add new requirements for NTN management | 19.0.0 |
| 2025-03 | SA#107 | SP-250162 | 0031 | | C | Rel-19 CR TS 28.540 Add requirements for management of RedCap feature | 19.0.0 |
| 2025-06 | SA#108 | SP-250520 | 0033 | 1 | F | Rel-19 CR TS 28.540 Enhance the requirement description | 19.1.0 |
| 2025-06 | SA#108 | SP-250520 | 0035 | 1 | B | Rel-19 CR TS 28.540 Add requirements for management of Ambient IoT | 19.1.0 |
| 2025-06 | SA#108 | SP-250546 | 0037 | 1 | B | Rel-19 CR 28540 Add NTN regenerative concepts and requirements | 19.1.0 |
| 2025-06 | SA#108 | SP-250546 | 0040 | 1 | B | Rel-19 CR TS 28.540 Add new requirements to support broadcast multiple TACs for NTN | 19.1.0 |
| 2025-06 | SA#108 | SP-250520 | 0041 | 1 | C | Rel-19 CR TS 28.540 Enhance description of WAB-gNB management | 19.1.0 |
| 2025-09 | SA#109 | SP-251098 | 0045 | 1 | B | Rel-19 CR TS 28.540 Update requirements for reader location and AIoT service area configurations | 19.2.0 |
| 2025-09 | SA#109 | SP-251078 | 0047 | 1 | C | Rel-19 CR TS 28.540 add missing feature concepts and requirements | 19.2.0 |
| 2025-09 | SA#109 | SP-251097 | 0048 | 1 | B | Management of IAB-node | 19.2.0 |

History

| Document history | | |
|------------------|--------------|-------------|
| V19.2.0 | October 2025 | Publication |
| | | |
| | | |
| | | |
| | | |