

ETSI TS 128 623 V15.6.0 (2023-01)



**Universal Mobile Telecommunications System (UMTS);
LTE;
5G;
Telecommunication management;
Generic Network Resource Model (NRM)
Integration Reference Point (IRP);
Solution Set (SS) definitions
(3GPP TS 28.623 version 15.6.0 Release 15)**



Reference

RTS/TSGS-0528623vf60

Keywords

5G,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
3 Definitions and abbreviations.....	7
3.1 Definitions	7
3.2 Abbreviations	7
4 Solution Set (SS) definitions	7
Annex A (normative): CORBA Solution Set	8
A.0 General	8
A.1 Architectural features	8
A.1.1 Syntax for Distinguished Names	8
A.1.2 Rules for NRM extensions	8
A.1.2.0 Introduction.....	8
A.1.2.1 Allowed extensions.....	8
A.1.2.2 Extensions not allowed	8
A.2 Mapping	10
A.2.1 General mapping	10
A.2.2 Information Object Class (IOC) mapping	10
A.2.2.1 IOC SubNetwork	10
A.2.2.2 IOC ManagedElement	10
A.2.2.3 IOC MeContext	10
A.2.2.4 IOC ManagementNode	11
A.2.2.5 IOC VsDataContainer.....	11
A.2.2.6 IOC ManagedFunction	11
A.2.2.7 IOC IRPAgent	11
A.2.2.8 IOC Top.....	11
A.2.2.9 IOC Link.....	12
A.2.2.10 IOC EP_RP	12
A.3 Solution Set definitions	13
A.3.1 IDL definition structure	13
A.3.2 IDL specification "GenericNetworkResourcesIRPSystem.idl"	13
A.3.3 IDL specification "GenericNetworkResourcesNRMDefs.idl"	16
Annex B (normative): XML Definitions	19
B.0 General	19
B.1 Architectural features	19
B.1.0 Introduction	19
B.1.1 Syntax for Distinguished Names	19
B.2 Mapping	19
B.2.1 General mapping	19
B.2.2 Information Object Class (IOC) mapping	19
B.3 Solution Set (SS) definitions	20
B.3.1 XML definition structure.....	20

B.3.2	Graphical Representation	20
B.3.3	XML schema "genericNrm.xsd"	21
Annex C (normative): JSON definitions		27
C.1	General	27
C.2	Architectural features	27
C.2.1	Introduction	27
C.2.2	Syntax for Distinguished Names	27
C.3	Mapping	27
C.4	Solution Set (SS) definitions	27
C.4.1	JSON definition structure	27
C.4.2	Graphical representation	27
C.4.3	JSON schema "genericNrm.json"	27
Annex D (normative): YANG definitions.....		35
D.1	General	35
D.2	Modules	35
D.2.0	list of YANG modules for the Generic NRM.....	35
D.2.1	module _3gpp-common-ep-rp.yang	35
D.2.2	module _3gpp-common-managed-element.yang	36
D.2.3	module _3gpp-common-managed-function.yang.....	38
D.2.4	module _3gpp-common-measurements.yang	40
D.2.5	module _3gpp-common-subnetwork.yang	45
D.2.6	module _3gpp-common-top.yang.....	47
D.2.7	module _3gpp-common-yang-extensions.yang.....	47
D.2.8	module _3gpp-common-yang-types.yang	49
D.3	Graphical representation.....	54
Annex E (informative): Change history		56
History		57

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

28.621 Generic Network Resource Model (NRM) Integration Reference Point (IRP); Requirements.

28.622 Generic Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS).

28.623 Generic Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions.

1 Scope

The TS 28.62x-series (Generic Network Resources IRP) define an Integration Reference Point (IRP) through which an "IRPAgent" (typically an Element Manager or Network Element) can communicate Network Management related information to one or several "IRPManagers" (typically Network Managers).

This TS-family specifies a generic Network Resource Model, NRM (also referred to as a Management Information Model - MIM) with definitions of Information Object Classes (IOCs) and Managed Object Classes (MOCs).

The present document specifies the Solution Set definition for the Generic NRM IRP.

The Solution Set definition is related to 3GPP TS 28.622 V15.4.X [4].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [4] 3GPP TS 28.622: "Generic Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)".
- [5] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [6] Void
- [7] 3GPP TS 32.616: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); Solution Set (SS) definitions".
- [8] W3C REC-xml11-20060816: "Extensible Markup Language (XML) 1.1 (Second Edition)".
- [9] Void.
- [10] W3C XML Schema Definition Language (XSD) 1.1 Part 1: Structures.
- [11] W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes.
- [12] W3C REC-xml-names-20060816: "Namespaces in XML 1.1 (Second Edition)".
- [13] 3GPP TS 32.158: "Management and orchestration; Design rules for REpresentational State Transfer (REST) Solution Sets (SS)".
- [14] 3GPP TS 32.160: "Management and orchestration; Management Service Template".
- [15] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [15], TS 32.101 [1], TS 32.102 [2], TS 32.600 [3], TS 28.622 [4] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [15] and 3GPP TS 32.101 [1], TS 32.102 [2] and TS 32.600 [3] and TS 28.622 [4].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [15], TS 32.600 [3] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [15] and TS 32.600 [3].

JSON	JavaScript Object Notation
SS	Solution Set

4 Solution Set (SS) definitions

This specification defines the following 3GPP Generic NRM IRP Solution Set Definitions:

- 3GPP Generic NRM IRP CORBA SS (Annex A).
- 3GPP Generic NRM IRP XML Definitions (Annex B).
- 3GPP Generic NRM IRP JSON Definitions (Annex C).

Annex A (normative): CORBA Solution Set

A.0 General

This annex contains the CORBA Solution Set for the IRP whose semantics is specified in Generic NRM IRP: Information Service (3GPP TS 28.622 [4]).

A.1 Architectural features

The overall architectural feature of Generic Network Resources IRP is specified in 3GPP TS 28.622 [4]. This clause specifies features that are specific to the CORBA SS.

A.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

A.1.2 Rules for NRM extensions

A.1.2.0 Introduction

This clause discusses how the models and IDL definitions provided in the present document can be extended for a particular implementation and still remain compliant with 3GPP SA5's specifications.

A.1.2.1 Allowed extensions

Vendor-specific MOCs may be supported. The vendor-specific MOCs may support new types of attributes. The 3GPP SA5-specified notifications may be issued referring to the vendor-specific MOCs and vendor-specific attributes. New MOCs shall be distinguishable from 3GPP SA5 MOCs by name. 3GPP SA5-specified and vendor-specific attributes may be used in vendor-specific MOCs. Vendor-specific attribute names shall be distinguishable from existing attribute names.

NRM MOCs may be subclassed. Subclassed MOCs shall maintain the specified behaviour of the 3GPP SA5's superior classes. They may add vendor-specific behaviour with vendor-specific attributes. When subclassing, naming attributes cannot be changed. The subclassed MOC shall support all attributes of its superior class. Vendor-specific attributes cannot be added to 3GPP SA5 NRM MOCs without subclassing.

When subclassing, the 3GPP SA5-specified containment rules and their specified cardinality shall still be followed. As an example, ManagementNode (or its subclasses) shall be contained under SubNetwork (or its subclasses).

Managed Object Instances may be instantiated as CORBA objects. This requires that the MOCs be represented in IDL. 3GPP SA5's NRM MOCs are not currently specified in IDL, but may be specified in IDL for instantiation or subclassing purposes. However, management information models should not require that IRPManagers access the instantiated managed objects other than through supported methods in the present document.

Extension rules related to notifications (Notification categories, Event Types, Extended Event Types etc.) are for further study.

A.1.2.2 Extensions not allowed

The IDL specifications in the present document cannot be edited or altered. Any additional IDL specifications shall be specified in separate IDL files.

IDL interfaces (note: not MOCs) specified in the present document may not be subclassed or extended. New interfaces may be defined with vendor-specific methods.

A.2 Mapping

A.2.1 General mapping

Attributes modelling associations as defined in the NRM (here also called "reference attributes") are in this SS mapped to attributes. The names of the reference attributes in the NRM are mapped to the corresponding attribute names in the MOC. When the cardinality for an association is 0..1 or 1..1 the datatype for the reference attribute is defined as an MOReference. The value of an MO reference contains the distinguished name of the associated MO. When the cardinality for an association allows more than one referred MO, the reference attribute will be of type MOReferenceSet, which contains a sequence of MO references.

A.2.2 Information Object Class (IOC) mapping

This Solution Set supports reference attributes for relations other than containment relations between objects. Reference attributes are therefore introduced in each MOC where needed.

A.2.2.1 IOC SubNetwork

Mapping from NRM IOC SubNetwork attributes to SS equivalent MOC SubNetwork attributes

IS Attributes	SS Attributes	SS Type
id	id	string
dnPrefix	dnPrefix	string
userLabel	userLabel	string
userDefinedNetworkType	userDefinedNetworkType	string
setOfMcc	setOfMcc	GenericNetworkResourcesIRPSystem::AttributeTypes::StringSet

A.2.2.2 IOC ManagedElement

Mapping from NRM IOC ManagedElement attributes and association roles to SS equivalent MOC ManagedElement attributes

IS Attributes	SS Attributes	SS Type
id	id	string
dnPrefix	dnPrefix	string
userLabel	userLabel	string
locationName	locationName	string
vendorName	vendorName	string
userDefinedState	userDefinedState	string
managedElementType	managedElementType	GenericNetworkResourcesIRPSystem::AttributeTypes::StringSet
managedBy	managedBy	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet
swVersion	swVersion	string

A.2.2.3 IOC MeContext

Mapping from NRM IOC MeContext attributes to SS equivalent MOC MeContext attributes

IS Attributes	SS Attributes	SS Type
id	id	string
dnPrefix	dnPrefix	string

A.2.2.4 IOC ManagementNode

Mapping from NRM IOC ManagementNode attributes and association roles to SS equivalent MOC ManagementNode attributes

IS Attributes	SS Attributes	SS Type
id	id	string
userLabel	userLabel	string
locationName	locationName	string
vendorName	vendorName	string
userDefinedState	userDefinedState	string
managedElements	managedElements	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet
swVersion	swVersion	string

A.2.2.5 IOC VsDataContainer

Mapping from NRM IOC VsDataContainer attributes and association roles to SS equivalent MOC VsDataContainer attributes

IS Attributes	SS Attributes	SS Type
id	id	string
vsDataType	vsDataType	string
vsData	vsData	any
vsDataFormatVersion	vsDataFormatVersion	string

A.2.2.6 IOC ManagedFunction

Mapping from NRM IOC ManagedFunction attributes and association roles to SS equivalent MOC ManagedFunction attributes

IS Attributes	SS Attributes	SS Type
id	id	string
peeParametersList	peeParametersList	GenericNetworkResourcesIRPSystem::AttributeTypes::PEEParametersListType
userLabel	userLabel	string
vnfParametersList	vnfParametersList	GenericNetworkResourcesIRPSystem::AttributeTypes::VNFParametersListType

A.2.2.7 IOC IRPAgent

Mapping from NRM IOC IRPAgent attributes to SS equivalent MOC IRPAgent attributes

IS Attributes	SS Attributes	SS Type
id	id	string
systemDN	systemDN	string

A.2.2.8 IOC Top

Mapping from NRM IOC Top attributes to SS equivalent attributes in all MOCs

IS Attributes	SS Attributes	SS Type
objectClass	CLASS	string
objectInstance	No direct mapping	

A.2.2.9 IOC Link

Mapping from NRM IOC Link attributes to SS equivalent MOC IRPAgent attributes

IS Attributes	SS Attributes	SS Type
id	id	string
userLabel (see note 2)	userLabel	string
aEnd	aEnd	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference
zEnd	zEnd	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference
linkType	linkType	LinkTypeType
protocolName	protocolName	string
protocolVersion	protocolVersion	string

NOTE 1: Void.

NOTE 2: Void.

A.2.2.10 IOC EP_RP

Mapping from NRM IOC EP_RP attributes to SS equivalent MOC EP_RP attributes

IS Attributes	SS Attributes	SS Type
id	id	string
userLabel	userLabel	string
farEndEntity	farEndEntity	GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference

A.3 Solution Set definitions

A.3.1 IDL definition structure

Clause A.3.2 defines the types which are used by the Generic NRM IRP.

Clause A.3.3 defines the MO classes for the Generic NRM IRP.

A.3.2 IDL specification "GenericNetworkResourcesIRPSystem.idl"

```
//File: GenericNetworkResourcesIRPSystem.idl
#ifndef _GENERIC_NETWORK_RESOURCES_IRP_SYSTEM_IDL_
#define _GENERIC_NETWORK_RESOURCES_IRP_SYSTEM_IDL_

// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"

module GenericNetworkResourcesIRPSystem
{
    /**
     * The format of Distinguished Name (DN) is specified in "Name Convention
     * for Managed Objects (3GPP TS 32.300 [5])".
     */
    typedef string DN;

    /**
     * This module adds datatype definitions for types
     * used in the NRM which are not basic datatypes defined
     * already in CORBA.
     */
    module AttributeTypes
    {
        /**
         * An MO reference refers to an MO instance.
         * "otherMO" contains the distinguished name of the referred MO.
         * A conceptual "null" reference (meaning no MO is referenced)
         * is represented as an empty string ("").
         */
        struct MOReference
        {
            DN otherMO;
        };

        /**
         * MOReferenceSet represents a set of MO references.
         * This type is used to hold 0..n MO references.
         * A referred MO is not allowed to be repeated (therefore
         * it is denoted as a "Set")
         */
        typedef sequence<MOReference> MOReferenceSet;

        /**
         * A set of strings.
         */
        typedef sequence<string> StringSet;

        /**
         * A set of long.
         */
        typedef sequence<long> LongSet;

        /**
         * The LinkListSet represents the Link_X_Y objects (or subclasses of
         * Link_X_Y objects) that have a relationship with this object instance.
         * Each Link_X_Y object models interface(s) between objects of class X and
         * Y. The object containing this attribute must either be a class of type X,
         * Y, XFunction, YFunction or a subclass of one of those classes. The
         * LinkListSet may be empty, or there may be no instances for a particular
         * Link_X_Y class name.
         */
        typedef MOReferenceSet LinkListSet;
    }
}
```

```

/**
 * VNFPParameters includes several attributes of a VNF instance.
 * The detailed definition of the attributes, see clause 4.4.1 of [4].
 */
struct VNFPParameters
{
    string vnfInstanceId;
    string vnfdId;
    string flavourId;
    boolean autoScalable;
};

/**
 * VNFPParametersListType represents a list of VNFPParameters.
 * The detailed definition of vnfpParametersListType, see clause 4.4.1 of [4].
 */
typedef sequence<VNFPParameters> VNFPParametersListType;
struct PEEPParameters
{
    string siteIdentification;
    float siteLatitude;
    float siteLongitude;
    string siteDescription;
    string equipmentType;
    string environmentType;
    string powerInterface;
};

/**
 * PEEPParametersListType represents a list of PEEPParameters.
 * The detailed definition of PEEPParametersListType, see clause 4.4.1 of [4].
 */
typedef sequence<PEEPParameters> PEEPParametersListType;

};

/**
 * This module adds datatype definitions for PM Control
 */
module PMControlTypes
{
    Struct Measurements
    {
        measurementTypes StringSet,
        gPs LongSet
    };
    typedef sequence <Measurements> Measurements;

    enum PMAdministrativeStateType
    {
        LOCKED,
        SHUTTINGDOWN,
        UNLOCKED
    };

    enum PMOperationalStateType
    {
        ENABLED,
        DISABLED
    };

    typedef MOReferenceSet ManagedObjectDNsType;

    typedef MOReferenceSet ManagedObjectDNsBasicType;

    typedef integer DefaultFileBasedGPType;
    typedef integer DefaultFileReportPeriodType;
    typedef string DefaultFileLocationType;
    typedef integer DefaultStreamBasedGPType;
    typedef string DefaultStreamTargetType;

    typedef integer FileBasedGPType;
    typedef integer FileReportingPeriodType;
    typedef string FileLocationType;
    typedef integer StreamBasedGPType;
    typedef string StreamTargetType;

```

```
};
```

```
};
```

```
#endif // _GENERIC_NETWORK_RESOURCES_IRP_SYSTEM_IDL_
```


A.3.3 IDL specification "GenericNetworkResourcesNRMDefs.idl"

```

//File: GenericNetworkResourcesNRMDefs.idl
#ifndef _GENERIC_NETWORK_RESOURCES_NRM_DEFS_IDL_
#define _GENERIC_NETWORK_RESOURCES_NRM_DEFS_IDL_
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"
/**
 * This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
 */
module GenericNetworkResourcesNRMDefs
{
    /**
     * Definitions for MO class Top
     */
    interface Top
    {
        // Attribute Names
        //
        const string CLASS = "Top";
    };
    /**
     * Definitions for MO class SubNetwork
     */
    interface SubNetwork : Top
    {
        const string CLASS = "SubNetwork";
        // Attribute Names
        //
        const string id = "id";
        const string dnPrefix = "dnPrefix";
        const string userLabel = "userLabel";
        const string userDefinedNetworkType = "userDefinedNetworkType";
        const string setOfMcc = "setOfMcc";
        const string measurements = "measurements";
    };
    /**
     * Definitions for MO class ManagedElement
     */
    interface ManagedElement : Top
    {
        const string CLASS = "ManagedElement";
        // Attribute Names
        //
        const string id = "id";
        const string dnPrefix = "dnPrefix";
        const string managedElementType = "managedElementType";
        const string userLabel = "userLabel";
        const string vendorName = "vendorName";
        const string userDefinedState = "userDefinedState";
        const string locationName = "locationName";
        const string managedBy = "managedBy";
        const string swVersion = "swVersion";
        const string measurements = "measurements";
    };
    /**
     * Definitions for MO class MeContext
     */
    interface MeContext : Top
    {
        const string CLASS = "MeContext";
        // Attribute Names
        //
        const string id = "id";
        const string dnPrefix = "dnPrefix";
    };
    /**
     * Definitions for MO class ManagementNode
     */
    interface ManagementNode : Top
    {
        const string CLASS = "ManagementNode";

        // Attribute Names

```

```

    //
    const string id = "id";
    const string userLabel = "userLabel";
    const string vendorName = "vendorName";
    const string userDefinedState = "userDefinedState";
    const string locationName = "locationName";
    const string managedElements = "managedElements";
    const string swVersion = "swVersion";
};

/**
 * Definitions for abstract MO class ManagedFunction
 *
 */
interface ManagedFunction : Top
{
    const string CLASS = "ManagedFunction";
    // Attribute Names
    //
    const string id = "id";
    const string peeParametersList = "peeParametersList";
    const string userLabel = "userLabel";
    const string vnfParametersList = "vnfParametersList";
    const string measurements = "measurements";
};

/**
 * Definitions for MO class IRPAgent
 *
 */
interface IRPAgent : Top
{
    const string CLASS = "IRPAgent";
    // Attribute Names
    //
    const string id = "id";
    const string systemDN = "systemDN";
};

/**
 * Definitions for abstract MO class Link
 * This inherits from ManagedFunction
 * The attributes aEnd and zEnd are populated with the DNs
 * of the entities associated via the link class.
 * The aEnd takes the DN of the 1st entity in alphabetical order,
 * the zEnd takes the 2nd entity in alphabetical order of the class
 * names.
 */
interface Link : ManagedFunction
{
    const string CLASS = "Link";
    // Attribute Names
    //
    const string aEnd = "aEnd";
    const string zEnd = "zEnd";
    const string linkType = "linkType";
    const string protocolName = "protocolName";
    const string protocolVersion = "protocolVersion";
};

/**
 * Definitions for MO class VsDataContainer
 *
 */
interface VsDataContainer : Top
{
    const string CLASS = "VsDataContainer";
    // Attribute Names
    //
    const string id = "id";
    const string vsDataType = "vsDataType";
    const string vsData = "vsData";
    const string vsDataFormatVersion = "vsDataFormatVersion";
};

/**
 * Definitions for abstract MO class EP_RP
 *
 */
interface EP_RP : Top
{
    const string CLASS = "EP_RP";
    // Attribute Names
    //

```

```
    const string farEndEntity = "farEndEntity";
    const string id = "id";
    const string userLabel = "userLabel";
    const string measurements = "measurements";
};

/**
 * Definitions for MO class MeasurementControl
 */
interface MeasurementControl: GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "MeasurementControl";
    // Attribute Names
    //
    const string id= "id";
    const string pMAdministrativeState = "pMAdministrativeState";
    const string pMOperationalState = "pMOperationalState";
    const string defaultFileBasedGP = "defaultFileBasedGP";
    const string defaultFileReportingPeriod = "defaultFileReportingPeriod";
    const string defaultFileLocation = "defaultFileLocation";
    const string defaultStreamBasedGP = "defaultStreamBasedGP";
    const string defaultStreamTarget = "defaultStreamTarget";
};

/**
 * Definitions for MO class MeasurementReader
 */
interface MeasurementReader: GenericNetworkResourcesNRMDefs::Top
{
    const string CLASS = "MeasurementReader";
    // Attribute Names
    //
    const string id= "id";
    const string measurementTypes = "measurementTypes";
    const string fileBasedGP = "fileBasedGP";
    const string fileReportingPeriod = "fileReportingPeriod";
    const string fileLocation = "fileLocation";
    const string streamBasedGP = "streamBasedGP";
    const string streamTarget = "streamTarget";
    const string managedObjectDNsBasic = "managedObjectDNsBasic";
    const string managedObjectDNs = "managedObjectDNs";
};

/**
 * This module adds datatypes definitions for the Link Class
 * These attributes are not the basic datatypes already defined
 */
module LinkAttributeTypes
{
    enum LinkType
    {
        SIGNALLING,
        BEARER,
        OAM_AND_P,
        OTHER
    };
    typedef sequence <LinkType> LinkTypeType;
};

};

#endif // _GENERIC_NETWORK_RESOURCES_NRM_DEFS_IDL_
```

Annex B (normative): XML Definitions

B.0 General

This annex contains the XML Definitions for the Generic NRM IRP as it applies to Itf-N, in accordance with Generic NRM IRP IS definitions TS 28.622 [4].

The XML file formats are based on XML [8], XML W3C REC-xml11-20060816 [8], W3C XML Schema Definition Language (XSD) 1.1 Part 1: Structures [10] W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes [11] and W3C REC-xml-names-20060816 [12] standards.

B.1 Architectural features

B.1.0 Introduction

The overall architectural feature of Generic Network Resources IRP is specified in 3GPP TS 28.622 [4].

This clause specifies features that are specific to the Schema definitions.

B.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

B.2 Mapping

B.2.1 General mapping

An IOC maps to an XML element of the same name as the IOC's name in the IS. An IOC attribute maps to a sub-element of the corresponding IOC's XML element, and the name of this sub-element is the same as the attribute's name in the IS.

B.2.2 Information Object Class (IOC) mapping

The mapping is not present in the current version of this specification.

B.3 Solution Set (SS) definitions

B.3.1 XML definition structure

The overall description of the file format of configuration data XML files is provided by 3GPP TS 28.616 [7].

Annex B.3.3 of the present document defines the NRM-specific XML schema `genericNrm.xsd` for the Generic Network Resources IRP NRM defined in 3GPP TS 28.622 [4].

XML schema `genericNrm.xsd` explicitly declares NRM-specific XML element types for the related NRM.

The definition of those NRM-specific XML element types complies with the generic mapping rules defined in 3GPP TS 28.616 [7], with the following exception: as defined in 3GPP TS 28.616 [7], the `vsData` XML element type has an empty XML content.

Additionally, XML schema `genericNrm.xsd` also provides the following global XML declarations and definitions:

- XML complex type `NrmClass`: derivation base type (see [8], [10] and [11]) for all NRM class associated XML element types (see 3GPP TS 28.616 [7]);
- XML element type `vsData`: derivation base type (see [8], [10] and [11]) for all vendor-specific XML element types (see 3GPP TS 28.616 [7]);
- XML element type `SubNetworkOptionallyContainedNrmClass`: substitution group head (see [8], [10] and [11]) for all XML element types associated to further NRM classes optionally contained under `SubNetwork` NRM class;
- XML element type `ManagedElementOptionallyContainedNrmClass`: substitution group head (see [8], [10] and [11]) for all XML element types associated to further NRM classes optionally contained under `ManagedElement` NRM class.

B.3.2 Graphical Representation

The graphical representation is not present in the current version of this specification.

B.3.3 XML schema "genericNrm.xsd"

```

<?xml version="1.1" encoding="UTF-8"?>

<!--
 3GPP TS 28.623 Generic Network Resources IRP
 Bulk CM Configuration data file NRM-specific XML schema
 genericNrm.xsd
-->

<schema
 targetNamespace="http://www.3gpp.org/ftp/specs/archive/28_series/28.623#genericNrm"
 elementFormDefault="qualified"
 attributeFormDefault="unqualified"
 xmlns="http://www.w3.org/2001/XMLSchema"
 xmlns:xn="http://www.3gpp.org/ftp/specs/archive/28_series/28.623#genericNrm"
 xmlns:sp="http://www.3gpp.org/ftp/specs/archive/28_series/28.629#sonPolicyNrm"
 >
<import namespace="http://www.3gpp.org/ftp/specs/archive/28_series/28.629#sonPolicyNrm"/>
<!-- Base XML type for all NRM class associated XML elements -->

<complexType name="NrmClass">
  <attribute name="id" type="string" use="required"/>
  <attribute name="modifier" use="optional">
    <simpleType>
      <restriction base="string">
        <enumeration value="create"/>
        <enumeration value="delete"/>
        <enumeration value="update"/>
      </restriction>
    </simpleType>
  </attribute>
</complexType>

<!-- Generic Network Resources IRP NRM attribute related XML types -->

<simpleType name="dn">
  <restriction base="string">
    <maxLength value="400"/>
  </restriction>
</simpleType>

<complexType name="dnList">
  <sequence minOccurs="0" maxOccurs="unbounded">
    <element name="dn" type="xn:dn"/>
  </sequence>
</complexType>

<simpleType name="linkType">
  <list>
    <simpleType>
      <restriction base="string">
        <enumeration value="Signalling"/>
        <enumeration value="Bearer"/>
        <enumeration value="OAM_AND_P"/>
        <enumeration value="Other"/>
      </restriction>
    </simpleType>
  </list>
</simpleType>

<complexType name="linkListType">
  <sequence minOccurs="0" maxOccurs="unbounded">
    <element name="dn" type="xn:dn"/>
  </sequence>
</complexType>

<complexType name="managedElementTypeListType">
  <sequence minOccurs="0" maxOccurs="unbounded">
    <element name="managedElementType" type="string"/>
  </sequence>
</complexType>

<complexType name="vnfParametersListType">
  <sequence minOccurs="1" maxOccurs="unbounded">
    <element name="vnfInstanceId" type="string"/>
    <element name="vnfdId" type="string" minOccurs="0"/>
  </sequence>
</complexType>

```

```
<element name="flavourId" type="string" minOccurs="0"/>
<element name="autoScalable" type="boolean"/>
</sequence>
</complexType>

<simpleType name="latitude">
  <restriction base="decimal">
    <fractionDigits value="4"/>
    <minInclusive value="-90.0000"/>
    <maxInclusive value="90.0000"/>
  </restriction>
</simpleType>

<simpleType name="longitude">
  <restriction base="decimal">
    <fractionDigits value="4"/>
    <minInclusive value="-180.0000"/>
    <maxInclusive value="180.0000"/>
  </restriction>
</simpleType>

<complexType name="peeParametersListType">
  <sequence minOccurs="1" maxOccurs="unbounded">
    <element name="siteIdentification" type="string"/>
    <element name="siteLatitude" type="xn:latitude" minOccurs="0"/>
    <element name="siteLongitude" type="xn:longitude" minOccurs="0"/>
    <element name="siteDescription" type="string"/>
    <element name="equipmentType" type="string"/>
    <element name="environmentType" type="string"/>
    <element name="powerInterface" type="string"/>
  </sequence>
</complexType>

<simpleType name="pMAdministrativeStateType">
  <restriction base="string">
    <enumeration value="LOCKED"/>
    <enumeration value="SHUTTINGDOWN"/>
    <enumeration value="UNLOCKED"/>
  </restriction>
</simpleType>

<simpleType name="pMOperationalStateType">
  <restriction base="string">
    <enumeration value="ENABLED"/>
    <enumeration value="DISABLED"/>
  </restriction>
</simpleType>

<complexType name="MeasurementTypeList">
  <sequence minOccurs="1" maxOccurs="unbounded">
    <element name="measurementType" type="string"/>
  </sequence>
</complexType>

<complexType name="GPList">
  <sequence minOccurs="1" maxOccurs="unbounded">
    <element name="gP" type="integer"/>
  </sequence>
</complexType>

<complexType name="Measurements">
  <sequence>
    <element name="measurementTypes" type="xn:MeasurementTypeList"/>
    <element name="GPs" type="xn:GPList"/>
  </sequence>
</complexType>

<complexType name="MeasurementsList">
  <sequence>
    <element name="measurements" type="xn:Measurements" minOccurs="1" maxOccurs="unbounded"/>
  </sequence>
</complexType>

<!-- Generic Network Resources IRP NRM class associated XML elements -->
```

```

<element name="SubNetwork">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="dnPrefix" minOccurs="0"/>
                <element name="userLabel" type="string"/>
                <element name="userDefinedNetworkType"/>
                <element name="setOfMcc" minOccurs="0"/>
                <element name="priority" type="integer" minOccurs="0"/>
                <element name="measurementsList" type="xn:MeasurementsList" minOccurs="0"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:SubNetwork"/>
            <element ref="xn:ManagedElement"/>
            <element ref="xn:MeContext"/>
            <element ref="xn:ManagementNode"/>
            <element ref="xn:IRPAgent"/>
            <element ref="xn:SubNetworkOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:MeasurementControl"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="ManagedElement">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="dnPrefix"/>
                <element name="managedElementTypeList" type="xn: managedElementTypeListType"
minOccurs="0"/>
                <element name="userLabel" type="string"/>
                <element name="vendorName"/>
                <element name="userDefinedState"/>
                <element name="locationName"/>
                <element name="swVersion"/>
                <element name="managedBy" type="xn:dnList" minOccurs="0"/>
                <element name="priority" type="integer" minOccurs="0"/>
                <element name="measurementsList" type="xn:MeasurementsList" minOccurs="0"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:IRPAgent"/>
            <element ref="xn:ManagedElementOptionallyContainedNrmClass"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:MeasurementControl"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="ManagedFunction">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>

```



```

    <all>
      <element name="userLabel" type="string"/>
      <element name="vnfParametersList" type="xn:vnfParametersListType"/>
      <element name="peeParametersList" type="xn:peeParametersListType"/>
      <element name="priority" type="integer" minOccurs="0"/>
      <element name="measurementsList" type="xn:MeasurementsList" minOccurs="0"/>
    </all>
  </complexType>
</element>
<choice minOccurs="0" maxOccurs="unbounded">
  <element ref="xn:VsDataContainer"/>
  <element ref="xn:EP_RP"/>
</choice>
<choice minOccurs="0" maxOccurs="unbounded">
  <element ref="xn:MeasurementControl"/>
</choice>
</sequence>
</extension>
</complexContent>
</complexType>
</element>
<element name="MeContext">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="dnPrefix" minOccurs="0"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:ManagedElement"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<element name="ManagementNode">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="userLabel" type="string"/>
                <element name="vendorName"/>
                <element name="locationName"/>
                <element name="managedElements" type="xn:dnList" minOccurs="0"/>
                <element name="swVersion"/>
                <element name="userDefinedState"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:IRPAgent"/>
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
<element name="MeasurementControl">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">

```

```

    <complexType>
      <all>
        <element name="pMAAdministrativeState" type="xn:pMAAdministrativeStateType"/>
        <element name="pMOperationalState" type="xn:pMOperationalStateType"/>
        <element name="defaultFileBasedGP" type="integer"/>
        <element name="defaultFileReportingPeriod" type="integer"/>
        <element name="defaultFileLocation" type="string"/>
        <element name="defaultStreamBasedGP" type="integer"/>
        <element name="defaultStreamTarget" type="string"/>
      </all>
    </complexType>
  </element>
  <choice minOccurs="0" maxOccurs="unbounded">
    <element ref="xn:MeasurementReader"/>
  </choice>
</sequence>
</extension>
</complexContent>
</complexType>
</element>

<element name="MeasurementReader">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="measurementTypes"/>
                <element name="fileBasedGP" type="integer" minOccurs="0"/>
                <element name="fileReportingPeriod" type="integer" minOccurs="0"/>
                <element name="fileLocation" type="string" minOccurs="0"/>
                <element name="streamBasedGP" type="integer" minOccurs="0"/>
                <element name="streamTarget" type="string" minOccurs="0"/>
                <element name="managedObjectDNsBasic" type="xn:dnList" minOccurs="0"/>
                <element name="managedObjectDNs" type="xn:dnList" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="IRPAgent">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element ref="xn:systemDN" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<element name="EP_RP">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="farEndEntity" type="xn:dn" minOccurs="0"/>
                <element name="userLabel" type="string" minOccurs="0"/>
                <element name="measurementsList" type="xn:MeasurementsList" minOccurs="0"/>
                <element name="measurements" type="xn:MeasurementTypesAndGPsList" minOccurs="0"/>
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

```

```

        </element>
      </sequence>
    </extension>
  </complexContent>
</complexType>
</element>

<element name="VsDataContainer">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="vsDataType"/>
                <element name="vsDataFormatVersion"/>
                <element ref="xn:vsData"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

<!--
  IRPAgent IOC attributes
-->

<element name="systemDN" type="xn:dn"/>

<!--
  VsDataContainer NRM class vsData attribute associated empty XML element
-->

<complexType name="vsData"/>
<element name="vsData" type="xn:vsData"/>

<!--
  Abstract head XML element for all XML elements associated to further
  NRM classes optionally contained under SubNetwork NRM class
-->

<element
  name="SubNetworkOptionallyContainedNrmClass"
  type="xn:NrmClass"
  abstract="true"
/>

<!--
  Abstract head XML element for all XML elements associated to further
  NRM classes optionally contained under ManagedElement NRM class
-->

<element
  name="ManagedElementOptionallyContainedNrmClass"
  type="xn:NrmClass"
  abstract="true"
/>
</schema>

```

Annex C (normative): JSON definitions

C.1 General

This annex contains the JSON Definitions for the Generic NRM, in accordance with Generic NRM IRP IS definitions [4].

C.2 Architectural features

C.2.1 Introduction

The overall architectural feature of Generic NRM is specified in 3GPP TS 28.622 [4].

This clause specifies features that are specific to the Schema definitions.

C.2.2 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

C.3 Mapping

Refer to TS 32.160 [x].

C.4 Solution Set (SS) definitions

C.4.1 JSON definition structure

JSON is used as resource representations format carried in the HTTP request and HTTP response message bodies. The properties (key-value pairs) on an object are defined using the properties keyword.

The definition of the JSON resource object complies with the generic rules defined in 3GPP TS 32.158 [13].

C.4.2 Graphical representation

None.

C.4.3 JSON schema "genericNrm.json"

```
{
  "openapi": "3.0.1",
  "info": {
    "title": "3GPP generic NRM",
    "version": "15.3.0",
    "description": "OAS 3.0.1 specification compatible schema for 3GPP generic NRM"
  },
  "paths": {},
  "components": {
    "schemas": {
```

```

"Dn": {
  "type": "string",
  "maxLength": 400
},
"DnList": {
  "type": "array",
  "items": {
    "$ref": "#/components/schemas/Dn"
  }
},
"Mcc": {
  "type": "string",
  "pattern": "^[0-9]{3}$"
},
"AdministrativeState": {
  "type": "string",
  "enum": [
    "LOCKED",
    "SHUTTING_DOWN",
    "UNLOCKED"
  ]
},
"OperationalState": {
  "type": "string",
  "enum": [
    "ENABLED",
    "DISABLED"
  ]
},
"SetOfMcc": {
  "type": "array",
  "items": {
    "$ref": "#/components/schemas/Mcc"
  }
},
"ManagedElementType": {
  "type": "string"
},
"ManagedElementTypeList": {
  "type": "array",
  "items": {
    "$ref": "#/components/schemas/ManagedElementType"
  }
},
"VnfParameter": {
  "type": "object",
  "properties": {
    "vnfInstanceId": {
      "type": "string"
    },
    "vnfdId": {
      "type": "string"
    },
    "flavourId": {
      "type": "string"
    },
    "autoScalable": {
      "type": "boolean"
    }
  }
},
"VnfParametersList": {
  "type": "array",
  "items": {
    "$ref": "#/components/schemas/VnfParameter"
  }
},
"SiteLatitude": {
  "type": "number",
  "format": "float",
  "minimum": -90,
  "maximum": 90
},
"SiteLongitude": {
  "type": "number",
  "format": "float",
  "minimum": -180,
  "maximum": 180
}

```

```

    },
    "PeeParameter": {
      "type": "object",
      "properties": {
        "siteIdentification": {
          "type": "string"
        },
        "siteDescription": {
          "type": "string"
        },
        "siteLatitude": {
          "$ref": "#/components/schemas/SiteLatitude"
        },
        "siteLongitude": {
          "$ref": "#/components/schemas/SiteLongitude"
        },
        "equipmentType": {
          "type": "string"
        },
        "environmentType": {
          "type": "string"
        },
        "powerInterface": {
          "type": "string"
        }
      }
    },
    "PeeParametersList": {
      "type": "array",
      "items": {
        "$ref": "#/components/schemas/PeeParameter"
      }
    },
    "Ipv4Addr": {
      "type": "string",
      "pattern": "^(([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\\.){3}([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])$",
      "example": "198.51.100.1"
    },
    "Ipv4AddrRm": {
      "type": "string",
      "pattern": "^(([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])\\.){3}([0-9]|[1-9][0-9]|1[0-9][0-9]|2[0-4][0-9]|25[0-5])$",
      "example": "198.51.100.1",
      "nullable": true
    },
    "Ipv6Addr": {
      "type": "string",
      "allOf": [
        {
          "pattern": "^((:|0?|([1-9a-f][0-9a-f]{0,3})))(0?|([1-9a-f][0-9a-f]{0,3}))::{0,6}(:|0?|([1-9a-f][0-9a-f]{0,3}))$"
        },
        {
          "pattern": "^(((^[^:]+){7}([^[^:]+))|(((^[^:]+)*[^[^:]+)?::((^[^:]+)*[^[^:]+)?))$"
        }
      ],
      "example": "2001:db8:85a3::8a2e:370:7334"
    },
    "Ipv6AddrRm": {
      "type": "string",
      "allOf": [
        {
          "pattern": "^((:|0?|([1-9a-f][0-9a-f]{0,3})))(0?|([1-9a-f][0-9a-f]{0,3}))::{0,6}(:|0?|([1-9a-f][0-9a-f]{0,3}))$"
        },
        {
          "pattern": "^(((^[^:]+){7}([^[^:]+))|(((^[^:]+)*[^[^:]+)?::((^[^:]+)*[^[^:]+)?))$"
        }
      ],
      "example": "2001:db8:85a3::8a2e:370:7334",
      "nullable": true
    },
    "Ipv6Prefix": {
      "type": "string",
      "allOf": [
        {

```

```

        "pattern": "^(:(|0?|([1-9a-f][0-9a-f]{0,3})):)(0?|([1-9a-f][0-9a-f]{0,3})):(|0?|([1-9a-f][0-9a-f]{0,3}))(\\/((([0-9])|([0-9]{2})|(1[0-1][0-9])|(12[0-8])))$"
      },
      {
        "pattern": "^((([^:]+):){7}([^:]+)|((([^:]+)*[^:]+)?::((([^:]+)*[^:]+)?))(\\/.+)$"
      }
    ],
    "example": "2001:db8:abcd:12::0/64"
  },
  "TransportProtocol": {
    "anyOf": [
      {
        "type": "string",
        "enum": [
          "TCP"
        ]
      },
      {
        "type": "string"
      }
    ]
  },
  "Measurements": {
    "type": "object",
    "properties": {
      "measurementTypes": {
        "type": "array",
        "items": {
          "type": "string"
        }
      },
      "gPs": {
        "type": "array",
        "items": {
          "type": "integer"
        }
      }
    }
  },
  "Top-Attributes": {
    "type": "object",
    "properties": {
      "id": {
        "type": "string"
      }
    }
  },
  "SubNetwork-Attributes": {
    "type": "object",
    "properties": {
      "dnPrefix": {
        "type": "string"
      },
      "userLabel": {
        "type": "string"
      },
      "userDefinedNetworkType": {
        "type": "string"
      },
      "setOfMcc": {
        "$ref": "#/components/schemas/SetOfMcc"
      },
      "priorityLabel": {
        "type": "integer"
      },
      "measurementsList": {
        "type": "array",
        "items": {
          "$ref": "#/components/schemas/Measurements"
        }
      }
    }
  },
  "ManagedElement-Attributes": {
    "type": "object",
    "properties": {
      "dnPrefix": {
        "type": "string"
      }
    }
  }
}

```

```

    },
    "managedElementTypeList": {
      "$ref": "#/components/schemas/ManagedElementTypeList"
    },
    "userLabel": {
      "type": "string"
    },
    "locationName": {
      "type": "string"
    },
    "managedBy": {
      "$ref": "#/components/schemas/DnList"
    },
    "vendorName": {
      "type": "string"
    },
    "userDefinedState": {
      "type": "string"
    },
    "swVersion": {
      "type": "string"
    },
    "priorityLabel": {
      "type": "integer"
    },
    "measurementsList": {
      "type": "array",
      "items": {
        "$ref": "#/components/schemas/Measurements"
      }
    }
  }
},
"ManagedFunction-Attributes": {
  "type": "object",
  "properties": {
    "userLabel": {
      "type": "string"
    },
    "vnfParametersList": {
      "$ref": "#/components/schemas/VnfParametersList"
    },
    "peeParametersList": {
      "$ref": "#/components/schemas/PeeParametersList"
    },
    "priorityLabel": {
      "type": "integer"
    },
    "measurementsList": {
      "type": "array",
      "items": {
        "$ref": "#/components/schemas/Measurements"
      }
    }
  }
},
"EP_RP-Attributes": {
  "type": "object",
  "properties": {
    "userLabel": {
      "type": "string"
    },
    "farEndEntity": {
      "type": "string"
    },
    "measurementsList": {
      "type": "array",
      "items": {
        "$ref": "#/components/schemas/Measurements"
      }
    }
  }
},
"SubNetwork-ContainingObjects": {
  "type": "object",
  "properties": {
    "ManagementNode": {
      "$ref": "#/components/schemas/ManagementNode-Multiple"
    }
  }
}

```



```

    },
    "MeContext": {
      "$ref": "#/components/schemas/MeContext-Multiple"
    },
    "MeasurementControl": {
      "$ref": "#/components/schemas/MeasurementControl-Multiple"
    },
    "VsDataContainer": {
      "$ref": "#/components/schemas/VsDataContainer-Multiple"
    }
  }
},
"ManagedElement-ContainingObjects": {
  "type": "object",
  "properties": {
    "MeasurementControl": {
      "$ref": "#/components/schemas/MeasurementControl-Multiple"
    },
    "VsDataContainer": {
      "$ref": "#/components/schemas/VsDataContainer-Multiple"
    }
  }
},
"ManagedFunction-ContainingObjects": {
  "type": "object",
  "properties": {
    "MeasurementControl": {
      "$ref": "#/components/schemas/MeasurementControl-Multiple"
    },
    "VsDataContainer": {
      "$ref": "#/components/schemas/VsDataContainer-Multiple"
    }
  }
},
"ManagementNode-Single": {
  "type": "object",
  "required": [
    "id"
  ],
  "properties": {
    "id": {
      "type": "string"
    },
    "attributes": {
      "type": "object",
      "properties": {
        "userLabel": {
          "type": "string"
        }
      },
      "managedElements": {
        "$ref": "#/components/schemas/DnList"
      },
      "vendorName": {
        "type": "string"
      },
      "userDefinedState": {
        "type": "string"
      },
      "locationName": {
        "type": "string"
      },
      "swVersion": {
        "type": "string"
      }
    }
  }
},
"ManagementNode-Multiple": {
  "type": "array",
  "items": {
    "$ref": "#/components/schemas/ManagementNode-Single"
  }
},
"MeContext-Single": {
  "type": "object",
  "required": [
    "id"
  ]
}

```

```

    ],
    "properties": {
      "id": {
        "type": "string"
      },
      "attributes": {
        "type": "object",
        "properties": {
          "dnPrefix": {
            "type": "string"
          }
        }
      }
    }
  },
  "MeContext-Multiple": {
    "type": "array",
    "items": {
      "$ref": "#/components/schemas/MeContext-Single"
    }
  },
  "VsDataContainer-Single": {
    "type": "object",
    "required": [
      "id"
    ],
    "properties": {
      "id": {
        "type": "string"
      },
      "attributes": {
        "type": "object",
        "properties": {
          "vsDataType": {
            "type": "string"
          },
          "vsDataFormatVersion": {
            "type": "string"
          },
          "vsData": {
            "type": "object",
            "properties": {}
          }
        }
      }
    }
  },
  "VsDataContainer-Multiple": {
    "type": "array",
    "items": {
      "$ref": "#/components/schemas/VsDataContainer-Single"
    }
  },
  "MeasurementControl-Single": {
    "type": "object",
    "properties": {
      "id": {
        "type": "string"
      },
      "attributes": {
        "type": "object",
        "properties": {
          "pMAdministrativeState": {
            "$ref": "#/components/schemas/AdministrativeState"
          },
          "pMOperationalState": {
            "$ref": "#/components/schemas/OperationalState"
          },
          "defaultFileBasedGp": {
            "type": "integer"
          },
          "defaultFileReportPeriod": {
            "type": "integer"
          },
          "defaultStreamBasedGp": {
            "type": "integer"
          },
          "defaultFileLocation": {

```

```
        "type": "string"
      },
      "defaultStreamTarget": {
        "type": "string"
      }
    }
  },
  "MeasurementReader": {
    "$ref": "#/components/schemas/MeasurementReader-Multiple"
  }
},
"MeasurementControl-Multiple": {
  "type": "array",
  "items": {
    "$ref": "#/components/schemas/MeasurementControl-Single"
  }
},
"MeasurementReader-Single": {
  "type": "object",
  "properties": {
    "id": {
      "type": "string"
    },
    "attributes": {
      "type": "object",
      "properties": {
        "measurementTypes": {
          "type": "string"
        },
        "fileBasedGp": {
          "type": "integer"
        },
        "fileReportingPeriod": {
          "type": "integer"
        },
        "streamBasedGp": {
          "type": "integer"
        },
        "fileLocation": {
          "type": "string"
        },
        "streamTarget": {
          "type": "string"
        },
        "managementObjectDNsBasic": {
          "$ref": "#/components/schemas/DnList"
        },
        "managementObjectDNs": {
          "$ref": "#/components/schemas/DnList"
        }
      }
    }
  }
},
"MeasurementReader-Multiple": {
  "type": "array",
  "items": {
    "$ref": "#/components/schemas/MeasurementReader-Single"
  }
}
}
```

Annex D (normative): YANG definitions

D.1 General

This annex contains the YANG definitions for the Generic NRM.

D.2 Modules

D.2.0 list of YANG modules for the Generic NRM

Below is the list of YANG modules for the Generic NRM.

```
_3gpp-common-ep-rp.yang
_3gpp-common-managed-element.yang
_3gpp-common-managed-function.yang
_3gpp-common-measurements.yang
_3gpp-common-subnetwork.yang
_3gpp-common-top.yang
_3gpp-common-yang-extensions.yang
_3gpp-common-yang-types.yang
```

D.2.1 module _3gpp-common-ep-rp.yang

```
<CODE BEGINS>
module _3gpp-common-ep-rp {
  yang-version 1.1;
  namespace "urn:3gpp:sa5:_3gpp-common-ep-rp";
  prefix "eprp3gpp";

  import _3gpp-common-yang-types { prefix types3gpp ; }
  import ietf-inet-types { prefix inet; }
  import _3gpp-common-measurements { prefix meas3gpp; }

  organization "3GPP SA5";
  description "Common/basic class/grouping to be inherited/reused.
  This IOC represents an end point of a link used across a reference
  point between two network entities.";
  reference
    "3GPP TS 28.622
    Generic Network Resource Model (NRM)
    Integration Reference Point (IRP);
    Information Service (IS)

    3GPP TS 28.620
    Umbrella Information Model (UIM)";

  revision 2019-06-17 {
    description "Initial revision";
    reference "Based on
    3GPP TS 28.620
    3GPP TS 28.622 ";
  }

  grouping EP_RPGrp {
    description "Abstract class, represents an end point of a link used
    across a reference point between two network entities.

    For naming the subclasses of EP_RP, the following rules shall apply:
    - The name of the subclassed IOC shall have the form "EP_<rp>",
    where <rp> is a string that represents the name of the reference point.
    Thus, two valid examples of EP_RP subclassed IOC names would be:
    EP_S1 and EP_X2.";
```

```

    leaf userLabel {
        type string;
        description "A user-friendly (and user assignable) name of this object.";
    }

    leaf farEndEntity {
        config false;
        type types3gpp:DistinguishedName;
    }
}

grouping EP_Common {
    uses EP_RPGrp;
    uses meas3gpp:Measurements;
    list localAddress {
        description "Local IP address and VLAN ID.";
        key "ipAddress vlanId";
        min-elements 1;
        max-elements 1;
        uses types3gpp:AddressWithVlan;
    }

    leaf remoteAddress {
        description "Remote IP address.";
        mandatory true;
        type inet:ip-address;
    }
}
}
}
}
<CODE ENDS>

```

D.2.2 module _3gpp-common-managed-element.yang

```

<CODE BEGINS>
module _3gpp-common-managed-element {
    yang-version 1.1;
    namespace urn:3gpp:sa5:_3gpp-common-managed-element;
    prefix "me3gpp";

    import _3gpp-common-yang-types { prefix types3gpp ; }
    import _3gpp-common-top { prefix top3gpp; }
    import _3gpp-common-measurements { prefix meas3gpp; }

    organization "3GPP SA5";
    description "Defines ManagedElement which will be augmented
        by other IOCs";
    reference "3GPP TS 28.622
        Generic Network Resource Model (NRM)
        Integration Reference Point (IRP);
        Information Service (IS)

        3GPP TS 28.620
        Umbrella Information Model (UIM)";

    revision 2019-06-17 {
        description "Initial revision";
        reference "Based on
            3GPP TS 28.620
            3GPP TS 28.622 ";
    }

    feature MeasurementsUnderManagedElement {
        description "The MeasurementSubtree shall be contained under ManageElement";
    }

    grouping ManagedElement_Grp {
        description "Abstract class representing telecommunications resources.
            An ME communicates with a manager (directly or indirectly) for the
            purpose of being monitored and/or controlled. MEs may perform element
            management functionality.
            An ME (and its contained Function_(s)) may or may not be geographically
            distributed. An ME (and its contained Function_(s)) is often referred
            to as a Network Element";
    }
}

```

```

leaf dnPrefix {
  description "Provides naming context that allows the Managed
    Elements to be partitioned into logical domains.
    A Distinguished Name(DN) is defined by 3GPP TS 32.300,
    which splits the DN into a DN Prefix and Local DN";
  type types3gpp:DistinguishedName;
}

leaf userLabel {
  description "A user-friendly (and user assignable) name of this object.";
  type string;
}

leaf locationName {
  description "The physical location (e.g. an address) of an entity
    represented by a (derivative of) ManagedElement_. It may contain no
    information to support the case where the derivative of
    ManagedElement_ needs to represent a distributed multi-location NE.";
  config false;
  type string;
}

leaf-list managedBy {
  description "Relates to the role played by ManagementSystem_ in the
    between ManagedSystem_ and ManagedElement_. This attribute contains
    a list of the DN(s) of the related subclasses of
    ManagementSystem_ instance(s).";

  config false;
  type types3gpp:DistinguishedName;
}

leaf-list managedElementTypeList {
  description "The type of functionality provided by the ManagedElement.
    It may represent one ME functionality or a combination of
    more than one functionality.
    1) The allowed values of this attribute are the names of the IOC(s)
    that are (a) derived/subclassed from ManagedFunction and (b) directly
    name-contained by ManagedElement IOC (on the first level below
    ManagedElement), but with the string "Function" excluded.
    2) If a ManagedElement contains multiple instances of a ManagedFunction
    this attribute will not contain repeated values.
    3) The capitalisation (usage of upper/lower case) of characters in this
    attribute is insignificant. Thus, the NodeB should be case insensitive
    when reading these values.
    4) Two examples of allowed values are:
    • NodeB;
    • HLR, VLR.";

  config false;
  min-elements 1;
  type string;
}

grouping ManagedElementGrp {
  description "Represents telecommunications equipment or
    TMN entities within the telecommunications network providing support
    and/or service to the subscriber.";

  uses ManagedElement_Grp;
  uses meas3gpp:Measurements {
    if-feature MeasurementsUnderManagedElement ;
  }

  leaf vendorName {
    config false;
    type string;
  }

  leaf userDefinedState {
    type string;
    description "An operator defined state for operator specific usage";
  }

  leaf swVersion {
    config false;
    type string;
  }
}

```

```

    }

    leaf priorityLabel {
        type uint32;
        mandatory true;
    }
}

list ManagedElement {
    description "Represents telecommunications equipment or
        TMN entities within the telecommunications network providing support
        and/or service to the subscriber.
        An ME communicates with a manager (directly or indirectly) over one or
        more management interfaces for the purpose of being monitored and/or
        controlled. MEs may or may not additionally perform element management
        functionality.
        An ME contains equipment that may or may not be geographically
        distributed. An ME is often referred to as a Network Element.
        A telecommunication equipment has software and hardware components.
        The IOC described above represents the case when the software component
        is designed to run on dedicated hardware component. In the case when the
        software is designed to run on ETSI NFV defined NFVI [15], the IOC
        description would exclude the NFVI component supporting the above
        mentioned subject software. A ManagedElement may be contained in either
        a SubNetwork or in a MeContext instance. A single ManagedElement may also
        exist stand-alone with no parent at all.
        The ManagedElement IOC may be used to represent combined ME functionalit
        y (as indicated by the managedElementType attribute and the contained
        instances of different functional IOCs).";

    key id; // TODO: should this have a min-element/max-elements?
    uses top3gpp:Top_Grp;
    container attributes {
        uses ManagedElementGrp;
    }

    uses meas3gpp:MeasurementSubtree {
        if-feature MeasurementsUnderManagedElement ;
    }
}
}

<CODE ENDS>

```

D.2.3 module _3gpp-common-managed-function.yang

```

<CODE BEGINS>
module _3gpp-common-managed-function {
    yang-version 1.1;
    namespace urn:3gpp:sa5:_3gpp-common-managed-function;
    prefix mf3gpp;

    organization "3GPP SA5";
    description "The module defines a base class/grouping for major 3GPP functions.";
    reference
        "3GPP TS 28.622
        Generic Network Resource Model (NRM)
        Integration Reference Point (IRP);
        Information Service (IS)

        3GPP TS 28.620
        Umbrella Information Model (UIM)";

    revision 2019-06-18 {
        description "Initial revision";
        reference "Based on
            3GPP TS 28.620
            3GPP TS 28.622 ";
    }

    grouping Function_Grp {
        description "A base grouping for 3GPP functions.";

        leaf userLabel {
            type string;
            description "A user-friendly (and user assignable) name of this object.";
        }
    }
}

```

```

}

grouping ManagedFunctionGrp {
  description "Abstract root class to be inherited/reused by classes
    representing 3GPP functions.";

  uses Function_Grp;

  container vnfParametersList {
    description "Contains the parameter set of the VNF
      instance(s) corresponding to an NE.";
    presence "The presence of this container indicates that the ManagedFunction
      represented is realized by one or more VNF instance(s). Otherwise it
      shall be absent.";

    leaf vnfInstanceId {
      type string ;
      mandatory true;
      description "VNF instance identifier";
      reference "ETSI GS NFV-IFA 008 v2.1.1:
        Network Functions Virtualisation (NFV); Management and Orchestration;
        Ve-Vnfm reference point - Interface and Information Model Specification
        section 9.4.2

        ETSI GS NFV-IFA 015 v2.1.2: Network Functions Virtualisation (NFV);
        Management and Orchestration; Report on NFV Information Model
        section B2.4.2.1.2.3";
    }

    leaf vnfdId {
      type string ;
      description "Identifier of the VNFD on which the VNF instance is based.
        The absence of the leaf or a string length of zero for vnfInstanceId
        means the VNF instance(s) does not exist (e.g. has not been
        instantiated yet, has already been terminated).";
      reference "ETSI GS NFV-IFA 008 v2.1.1:
        Network Functions Virtualisation (NFV); Management and Orchestration;
        Ve-Vnfm reference point - Interface and Information Model Specification
        section 9.4.2";
    }

    leaf flavourId {
      type string ;
      description "Identifier of the VNF Deployment Flavour applied to this
        VNF instance.";
      reference "ETSI GS NFV-IFA 008 v2.1.1:
        Network Functions Virtualisation (NFV); Management and Orchestration;
        Ve-Vnfm reference point - Interface and Information Model Specification
        section 9.4.3";
    }

    leaf autoScalable {
      type boolean ;
      mandatory true;
      description "Indicator of whether the auto-scaling of this
        VNF instance is enabled or disabled.";
    }
  }

  container peeParametersList {
    description "Contains the parameter set for the control
      and monitoring of power, energy and environmental parameters of
      ManagedFunction instance(s).";
    presence "Present supported if the control and monitoring of PEE
      parameters is supported by the ManagedFunction or sub-class instance.";

    leaf siteIdentification {
      type string;
      mandatory true;
      description "The identification of the site where the
        ManagedFunction resides.";
    }

    leaf siteLatitude {
      type decimal64 {
        fraction-digits 4;
        range "-90.0000..+90.0000";
      }
    }
  }
}

```



```

        description "The latitude of the site where the ManagedFunction
        instance resides, based on World Geodetic System (1984 version)
        global reference frame (WGS 84). Positive values correspond to
        the northern hemisphere. This attribute is optional in case of
        BTSFunction and RNCFunction instance(s).";
    }

    leaf siteLongitude {
        type decimal64 {
            fraction-digits 4;
            range "-180.0000..+180.0000";
        }
        description "The longitude of the site where the ManagedFunction
        instance resides, based on World Geodetic System (1984 version)
        global reference frame (WGS 84). Positive values correspond to
        degrees east of 0 degrees longitude. This attribute is optional in
        case of BTSFunction and RNCFunction instance(s).";
    }

    leaf siteDescription {
        type string;
        mandatory true;
        description "An operator defined description of the site where
        the ManagedFunction instance resides.";
    }

    leaf equipmentType {
        type string;
        mandatory true;
        description "The type of equipment where the managedFunction
        instance resides.";
        reference "clause 4.4.1 of ETSI ES 202 336-12";
    }

    leaf environmentType {
        type string;
        mandatory true;
        description "The type of environment where the managedFunction
        instance resides.";
        reference "clause 4.4.1 of ETSI ES 202 336-12";
    }

    leaf powerInterface {
        type string;
        mandatory true;
        description "The type of power.";
        reference "clause 4.4.1 of ETSI ES 202 336-12";
    }
}

leaf priorityLabel {
    mandatory true;
    type uint32;
}
}
}
<CODE ENDS>

```

D.2.4 module _3gpp-common-measurements.yang

```

<CODE BEGINS>
module _3gpp-common-measurements {
    yang-version 1.1;
    namespace "urn:3gpp:sa5:_3gpp-common-measurements";
    prefix "meas3gpp";

    import _3gpp-common-top { prefix top3gpp; }
    import _3gpp-common-yang-types { prefix types3gpp; }

    organization "3GPP SA5";

    description "Defines Measurement related groupings
    Any list/class intending to use this should include 2 uses statements
    controlled by a feature:

    A)
+++   feature MeasurementsUnderMyClass {

```

```
+++     description 'Indicates whether measurements are supported for this class.';
+++     }
```

B) include the attribute supportedMeasurementsGPs indicating the supported measurementTypes and GPs. Note that for classes inheriting from ManagedFunction, EP_RP or SubNetwork this attribute is already inherited, so there is no need to include it once more. E.g.

```
+++     grouping MyClassGrp {
+++         uses meas3gpp:Measurements;
+++     }
```

C) include the classes MeasurementControl & MeasurementReader to control the measurements. E.g.

```
+++     list MyClass {
+++         container attributes {
+++             uses MyClassGrp;
+++         }
+++         uses meas3gpp:MeasurementSubtree {
+++             if-feature MeasurementsUnderMyClass ;
+++         }
+++     }
```

Measurements can be contained under ManagedElement, SubNetwork, or any list representing a class inheriting from EP_RP, Subnetwork or ManagedFunction."

```
reference "3GPP TS 28.622
Generic Network Resource Model (NRM)
Integration Reference Point (IRP);
Information Service (IS)";
```

```
revision 2019-11-21 { reference "S5-197733, S5-197734"; }
```

```
revision 2019-06-17 { reference "Initial version"; }
```

```
feature StreamingSupported {
description "The delivery of measurement data using streaming is supported.";
}
```

```
grouping Measurements {
description "Identifies the supported Measurement types and their
supported GPs.";
```

```
list measurementsList {
key idx;
config false;
description "List of supported Measurement types and their
supported GPs for the parent function/class";
```

```
leaf idx { type uint32 ; }
```

```
leaf-list measurementTypes {
type string;
min-elements 1;
description "The Measurement types can be those specified
in TS 28.552, TS 32.404 and can be those specified by
other SDOs or can be vendor-specific.";
```

```
leaf-list gPs {
type uint32 ;
min-elements 1;
units second;
description "Identifies supported GPs.
GP (granularity period) is the time between the initiation
of two successive gatherings of measurement data.";
```

```
    }
}
```

```
grouping MeasurementControlGrp {
description "represents the capabilities to produce and deliver Measurements
identified by a MeasurementReader.
There are two delivery methods (i.e. file-based and stream-based) via
which the consumer(s) can receive the Measurements.";
```

```

leaf pMAdministrativeState {
  default LOCKED;
  type types3gpp:AdministrativeState ;
  description "It describes the permission to use or prohibition against
    using the capability of MeasurementControl, imposed through the consumer
    of OAM services produced by MeasurementControl,

    The measurement report production would begin when pMadministrativeState
    is UNLOCKED and pMOperationalState is ENABLED.";
}

leaf pMOperationalState {
  config false;
  mandatory true;
  type types3gpp:OperationalState ;
  description "Indicates whether the MeasurementControl is working.";
}

leaf defaultFileLocation {
  type string ;
  description "It is the path to the location where produced
    measurement reports (containing PM data) are stored. File based
    measurement delivery will not start if this leaf does not have a
    valid value.

    It is the path to a location on either the producer's file system or a
    URI to a network file location that is not part of the producer's file
    system. In case it points to a location on the producer's file system,
    it is a relative path based on a vendor-specified root directory for
    measurement files.

    The size of this fileLocation is decided by consumer and producer.
    The producer is expected to remove old files to make room for
    new files, when necessary.

    This value is ignored in case the fileLocation leaf in the
    MeasurementReader is defined.";
}

leaf defaultFileBasedGP {
  when '../defaultFileLocation' ;
  mandatory true;
  type uint32 ;
  units second;
  description "GP (granularity period) defines the frequency of producing
    measurement data. Measurement data would be produced immediately at the
    end of each fileBasedGP.

    This value is ignored in case the fileBasedGP leaf in the
    MeasurementReader is defined.";
}

leaf defaultFileReportingPeriod {
  when '../defaultFileLocation' ;
  must '*. *60 >= ../defaultFileBasedGP' {
    error-message "defaultFileBasedGP must not be greater than defaultFileReportingPeriod";
  }
  mandatory true;
  type uint32 ;
  units minute;
  description "The frequency of producing the measurement report files.
    A measurement report file contains multiple measurement data.

    This value is ignored in case the fileReportingPeriod leaf in the
    MeasurementReader is defined.";
}

leaf defaultStreamTarget {
  if-feature StreamingSupported ;
  type string ;
  description "Identifies the target of the notifications carrying the
    content of the measurement report.

    This value is ignored in case the streamTarget leaf in the
    MeasurementReader is defined.";
}

leaf defaultStreamBasedGP {

```

```

    if-feature StreamingSupported ;
    when '../defaultStreamTarget' ;
    mandatory true;
    type uint32 ;
    units second;
    description "It defines the frequency of producing and sending the
        Measurement to the streamTargets.

        This value is ignored in case the streamBasedGP leaf in the
        MeasurementReader is defined.";
}
}

grouping MeasurementReaderGrp {
    description "Identifies the entity whose Measurements are required by
        consumer, the types of Measurements required and the delivery method for
        the measurements.";

    leaf-list measurementTypes {
        type string ;
        description "The Measurement type to be reported. It must be one of the
            measurmentTypes supported by the containing function/class.
            The Measurement type can be those specified in TS 28.552,
            TS 32.404 and can be those specified by other SDOs or can be
            vendor-specific.";
    }

    leaf-list managedObjectDNsBasic {
        type types3gpp:DistinguishedName ;
        description "Identifies the managed functions whose Measurements are
            required to be produced.

            It identifies specific managed entities (say X, Y, Z). It would mean
            Measurements type specified in MeasurementReader.measurementTypes,
            are required to be produced if X, Y, Z are capable of supporting
            the Measurement types.

            If managedObjectDNs of the same MeasurementReader instance has valid
            information, the information of this leaf-list is ignored.";
    }

    leaf-list managedObjectDNs {
        type types3gpp:DistinguishedName ;
        description "Identifies the managed entities whose Measurements are
            required to be produced.

            In case the base is SubNetwork, it identifies all, including the base,
            managed entities that are subordinates, in the sense of name-containment,
            of the base.

            In case the base is NetworkSliceSubnet, it identifies all, including
            the base, managed entities that has aggregation association relation
            with the base.

            We called the identified entities a collection. It would mean
            Measurement types specified in attribute
            MeasurementReader.measurementTypes, are required to be produced if the
            member (of the collection) is capable of supporting the Measurement
            types.";
    }

    leaf fileLocation {
        type string ;
        description "It is the path to the location where produced
            measurement reports (containing PM data) are stored. File based
            measurement delivery will not start if this leaf does not have a
            valid value.

            It is the path to a location on either the producer's file system or a
            URI to a network file location that is not part of the producer's file
            system. In case it points to a location on the producer's file system,
            it is a relative path based on a vendor-specified root directory for
            measurement files.

            The size of this fileLocation is decided by consumer and producer.
            The producer is expected to remove old files to make room for
            new files, when necessary.";
    }
}

```

```

    If defined this value overrides the value of defaultFileLocation in the
    parent MeasurementControl.";
}

leaf fileBasedGP {
    when '../fileLocation' ;
    mandatory true;
    type uint32 ;
    units second;
    description "GP (granularity period) defines the frequency of producing
    measurement data.";
}

leaf fileReportingPeriod {
    when '../fileLocation' ;
    must '. *60 >= ../fileBasedGP' {
        error-message "fileBasedGP must not be greater than fileReportingPeriod";
    }
    mandatory true;
    type uint32 ;
    units minute;
    description "The frequency of producing the measurement report files.";
}

leaf streamTarget {
    when 'not(../fileLocation)' ;
    type string ;
    description "Identifies the target of the notification carrying the
    content of the measurement report.
    There are two delivery methods (i.e. file-based and stream-based) via
    which the consumer(s) can receive the Measurements. This attribute
    is used for the stream-based delivery method.";
}

leaf streamBasedGP {
    when '../streamTarget' ;
    mandatory true;
    type uint32 ;
    units second;
    description "Defines the frequency of producing and sending the
    Measurement to the consumer.";
}
}

grouping MeasurementSubtree {
    description "Contains classes that define measurements.
    Should be used in all classes (or classes inheriting from)
    - SubNnetwork
    - ManagedElement
    - ManagedFunction
    - NetworkSliceSubnet
    - EP_RP

    If some YAM wants to augment these classes/list/groupings they must
    augment all user classes!

    If a class uses this grouping in its list it shall also use the
    grouping Measurements to add supportedMeasurementsGPs as
    an attribute to its grouping";
}

list MeasurementControl {
    description "Represents the properties of the file-based and stream-based
    measurement delivery methods.

    The file-based delivery method has properties for the file location,
    the file reporting period and the file-based GP.
    The stream-based delivery method has properties for the stream target
    and the stream-based GP.
    These properties are labelled as default (e.g. defaultFileBasedGP) in
    that they will be ignored in case the same properties captured in
    MeasurementReader are used.

    Instance of this list shall not be created nor deleted by client. It
    shall be created and deleted by the system.

    Depending on particular deployment context and agreement between
    operator and vendor, all attributes could be config=false.";
}

```



```

feature ExternalsUnderSubNetwork {
  description "Classes representing external entities like EUTranFrequency,
  ExternalGNBCUCPFunction, ExternalENBFunction
  are contained under a Subnetwork list/class.";
}

feature MeasurementsUnderSubNetwork {
  description "The MeasurementSubtree shall be contained under SubNetwork";
}

grouping Domain_Grp {
  description "A domain is a partition of instances of managed entities
  such that :
  - the group represents a topological structure which describes the
  potential for connectivity
  - Subject to common administration
  - With common characteristics";

  leaf dnPrefix {
    type types3gpp:DistinguishedName;
    reference "Annex C of 32.300 ";
  }

  leaf userLabel {
    type string;
    description "A user-friendly (and user assignable) name of this object.";
  }

  leaf userDefinedNetworkType {
    type string;
    description "Textual information indicating network type, e.g. 'UTRAN'.";
  }
}

grouping SubNetworkGrp {
  uses Domain_Grp;
  uses meas3gpp:Measurements;

  leaf-list setOfMcc {
    description "Set of Mobile Country Code (MCC).
    The MCC uniquely identifies the country of domicile
    of the mobile subscriber. MCC is part of the IMSI (3GPP TS 23.003)

    This list contains all the MCC values in subordinate object
    instances to this SubNetwork instance.

    See clause 2.3 of 3GPP TS 23.003 for MCC allocation principles.

    It shall be supported if there is more than one value in setOfMcc
    of the SubNetwork. Otherwise the support is optional.";
    type types3gpp:Mcc;
  }

  leaf priorityLabel {
    mandatory true;
    type uint32;
  }
}

list SubNetwork {
  key id;
  description "Represents a set of managed entities";

  uses top3gpp:Top_Grp;
  container attributes {
    uses SubNetworkGrp;
    leaf-list parents {
      description "Reference to all containg SubNetwork instances
      in strict order from the root subnetwork down to the immediate
      parent subnetwork.
      If subnetworks form a containment hierarchy this is
      modeled using references between the child SubNetwork and the parent
      SubNetworks.
      This reference MUST NOT be present for the top level SubNetwork and
      MUST be present for other SubNetworks.";
      type leafref {
        path "../..../SubNetwork/id";
      }
    }
  }
}

```

```

    }
  }

  leaf-list containedChildren{
    description "Reference to all directly contained SubNetwork instances.
      If subnetworks form a containment hierarchy this is
      modeled using references between the child SubNetwork and the parent
      SubNetwork.";
    type leafref {
      path "../../../../SubNetwork/id";
    }
  }
}

uses meas3gpp:MeasurementSubtree {
  if-feature MeasurementsUnderSubNetwork ;
}

yangmnt:mount-point children-of-SubNetwork {
  description "Mountpoint for ManagedElement";
  reference "RFC8528 YANG Schema Mount";
}

// augment external parts here
}
}
<CODE ENDS>

```

D.2.6 module _3gpp-common-top.yang

```

<CODE BEGINS>
module _3gpp-common-top {
  yang-version 1.1;

  namespace urn:3gpp:sa5:_3gpp-common-top;
  prefix top3gpp;

  organization "3gpp SA5";
  description "The model defines a YANG mapping of the top level
    information classes used for management of 5G networks and
    network slicing.";
  reference
    "3GPP TS 28.622
    Generic Network Resource Model (NRM)
    Integration Reference Point (IRP);
    Information Service (IS)

    3GPP TS 28.620
    Umbrella Information Model (UIM)";

  revision 2019-06-17 {
    description "Initial revision";
    reference "Based on
      3GPP TS 28.620
      3GPP TS 28.622 ";
  }

  grouping Top_Grp {
    description "Abstract class supplying a naming attribute";
    reference "3GPP TS 28.620";

    leaf id {
      type string;
      description "Key leaf (namingAttribute) for a class/list.
        Should be used as a key leaf for lists representing
        stage 2 classes.";
      reference "3GPP TS 32.300 Name convention for managed objects";
    }
  }
}
<CODE ENDS>

```

D.2.7 module _3gpp-common-yang-extensions.yang

```

<CODE BEGINS>
module _3gpp-common-yang-extensions {

```



```
yang-version 1.1;
namespace urn:3gpp:sa5:_3gpp-common-yang-extensions ;
prefix yext3gpp ;
```

```
organization "3GPP SA5";
description "The module defines YANG extensions needed
  3GPP YANG modeling.
```

```
Copyright (c) 2019 3GPP. All rights reserved.";
```

Extensions MUST be defined with the following structure in the description statement:

- What is this statement.
- Newline,
- This statement can be a substatement of the xxx statements with cardinality x.y.
- This statement can have the following substatements with cardinality x.y.
- Newline
- Is changing this statement an editorial, BC(backwards compatible) or NBC(non-BC) change?
- Newline.
- The argument its meaning and type. Preferably use YANG types and constraints to define the argument's type.

Any extension statement can be added with a deviation/deviate add statement. In this case the restriction about the parent statement of the extension SHALL be evaluated based on the target of the deviation statement.

Support for this module does not mean that a YANG server implements support for each of these extensions.

Implementers of each specific module using an extensions MUST check if the server implements support for the used extension.

Note: modules use many extensions which individual implementations MAY or MAY NOT support.

If support for an extension is missing the extension statement needs individual handling or it SHOULD be removed from the module using the extension e.g. with a deviation.

```
";
```

```
revision "2019-06-23" {
  description "Initial version";
}
```

```
extension inVariant {
  description
    "Indicates that the value for the data node can only be set when its
    parent data node is being created. To change the value after that, the
    parent data node must be deleted and recreated with the data node
    having the new value.
```

```
It is unnecessary to use and MUST NOT be used for key leafs.
```

```
The statement MUST only be a substatement of a leaf, leaf-list, list
statements that is config=true.
```

```
Zero or one inVariant statement is allowed per parent statement.
NO substatements are allowed.
```

```
Adding this statement is an NBC change, removing it is BC.";
```

```
}
```

```
extension initial-value {
  description "Specifies a value that the system will set for a leaf
  leaf-list if a value is not specified for it when its parent list
  or container is created. The value has no effect in any other
  modification e.g. changing or removing the value.
```

```
The description statement of the parent statement SHOULD contain
the label 'Initial-value: ' followed by the text from the argument.
```

```
The statement MUST only be a substatement of a leaf or leaf-list.
The statement MUST NOT be present if the leaf or the leaf-list
has a default statement or the type used for the data node
has a default value.
```

```
The statement MUST NOT be used for config=false data or in an
action, rpc or notification.
```

```
Zero or one initial-value statements are allowed for a leaf parent
```

statement. Zero or more initial-value statements are allowed for a leaf-list parent statement. If the leaf-list is ordered-by user, the initial values are stored in the order they appear in the YANG definition. NO substatements are allowed.

Always consider using a YANG-default statement instead.

Modification of the initial-value is a non-backwards-compatible change.

The argument specifies a single initial value for a leaf or leaf-list. The value MUST be part of the valuespace of the leaf/leaf-list. It follows the same rules as the argument of the default statement.";

```

    argument "initial-value";
  }
}
<CODE ENDS>

```

D.2.8 module _3gpp-common-yang-types.yang

```

<CODE BEGINS>
module _3gpp-common-yang-types {
  yang-version 1.1;
  namespace "urn:3gpp:sa5:_3gpp-common-yang-types";
  prefix "types3gpp";

  import ietf-inet-types { prefix inet; }

  organization "3GPP SA5";
  description "The model defines a YANG mapping of the top level
    information classes used for management of 5G networks and
    network slicing.";
  reference "3GPP TS 28.541";

  revision 2019-06-23 {
    description "Initial version.";
    reference "Based on
      3GPP TS 28.541 ";
  }

  typedef Mcc {
    description "The mobile country code consists of three decimal digits,
      The first digit of the mobile country code identifies the geographic
      region (the digits 1 and 8 are not used).";
    type string {
      pattern '[02-79][0-9][0-9]';
    }
    reference "3GPP TS 23.003 subclause 2.2 and 12.1";
  }

  typedef Mnc {
    description "The mobile network code consists of two or three
      decimal digits (for example: MNC of 001 is not the same as MNC of 01)";
    type string {
      pattern '[0-9][0-9][0-9]|[0-9][0-9]';
    }
    reference "3GPP TS 23.003 subclause 2.2 and 12.1";
  }

  grouping PLMNid {
    leaf mcc {
      mandatory true;
      type Mcc;
    }
    leaf mnc {
      mandatory true;
      type Mnc;
    }
  }
  reference "TS 23.658";
}

typedef Nci {
  description "NR Cell Identity. The NCI shall be of fixed length of 36 bits
    and shall be coded using full hexadecimal representation.
    The exact coding of the NCI is the responsibility of each PLMN operator";
  reference "TS 23.003";
  type union {

```

```

    type string {
        length 36;
        pattern '[01]+';
    }
    type string {
        length 9;
        pattern '[a-fA-F0-9]*';
    }
}

typedef OperationalState {
    reference "3GPP TS 28.625 and ITU-T X.731";
    type enumeration {
        enum DISABLED {
            value 0;
            description "The resource is totally inoperable.";
        }

        enum ENABLED {
            value 1;
            description "The resource is partially or fully operable.";
        }
    }
}

typedef AdministrativeState {
    reference "3GPP TS 28.625 and ITU-T X.731";
    type enumeration {
        enum LOCKED {
            value 0;
            description "The resource is administratively prohibited from performing
                services for its users.";
        }

        enum UNLOCKED {
            value 1;
            description "The resource is administratively permitted to perform
                services for its users. This is independent of its inherent
                operability.";
        }

        enum SHUTTINGDOWN {
            value 2;
            description "Use of the resource is administratively permitted to
                existing instances of use only. While the system remains in
                the shutting down state the manager or the managed element
                may at any time cause the resource to transition to the
                locked state.";
        }
    }
}

typedef AvailabilityStatus {
    type enumeration {
        enum IN_TEST;
        enum FAILED;
        enum POWER_OFF;
        enum OFF_LINE;
        enum OFF_DUTY;
        enum DEPENDENCY;
        enum DEGRADED;
        enum NOT_INSTALLED;
        enum LOG_FULL;
    }
}

typedef CellState {
    type enumeration {
        enum IDLE;
        enum INACTIVE;
        enum ACTIVE;
    }
}

typedef SNssai {
    type union {

```

```

        type uint8;
        type uint32;
    }
    description "Single Network Slice Selection Assistance Information.";
    reference "TS 23.501 clause 5.15.2";
}

typedef Sst {
    type uint8;
}

typedef Nrpci {
    type uint32;
    description "Physical Cell Identity (PCI) of the NR cell.";
    reference "TS 36.211 subclause 6.11";
}

typedef Tac {
    type int32 {
        range 0..16777215 ;
    }
    description "Tracking Area Code";
    reference "TS 23.003 clause 19.4.2.3";
}

typedef AmfRegionId {
    type union {
        type uint8 ;
        type string {
            length 8;
            pattern '[01]*';
        }
    }
    reference "clause 2.10.1 of 3GPP TS 23.003";
}

typedef AmfSetId {
    type union {
        type uint16 {
            range '0..1023';
        }
        type string {
            length 8;
            pattern '[01]*';
        }
    }
    reference "clause 2.10.1 of 3GPP TS 23.003";
}

typedef AmfPointer {
    type union {
        type uint8 {
            range '0..63';
        }
        type string {
            length 6;
            pattern '[01]*';
        }
    }
    reference "clause 2.10.1 of 3GPP TS 23.003";
}

grouping AmfIdentifier {
    leaf amfRegionId {
        type AmfRegionId;
    }
    leaf amfSetId {
        type AmfSetId;
    }
    leaf amfPointer {
        type AmfPointer;
    }
}
description "The AMFI is constructed from an AMF Region ID,
an AMF Set ID and an AMF Pointer.
The AMF Region ID identifies the region,
the AMF Set ID uniquely identifies the AMF Set within the AMF Region, and
the AMF Pointer uniquely identifies the AMF within the AMF Set. ";
}

```

```
// type definitions especially for core NFs

typedef NfType {
  type enumeration {
    enum NRF;
    enum UDM;
    enum AMF;
    enum SMF;
    enum AUSF;
    enum NEF;
    enum PCF;
    enum SMSF;
    enum NSSF;
    enum UDR;
    enum LMF;
    enum GMLC;
    enum 5G_EIR;
    enum SEPP;
    enum UPF;
    enum N3IWF;
    enum AF;
    enum UDSF;
    enum BSF;
    enum CHF;
  }
}

typedef NotificationType {
  type enumeration {
    enum N1_MESSAGES;
    enum N2_INFORMATION;
    enum LOCATION_NOTIFICATION;
  }
}

typedef Load {
  description "Latest known load information of the NF, percentage ";
  type uint8 {
    range 0..100;
  }
}

typedef N1MessageClass {
  type enumeration {
    enum 5GMM;
    enum SM;
    enum LPP;
    enum SMS;
  }
}

typedef N2InformationClass {
  type enumeration {
    enum SM;
    enum NRPPA;
    enum PWS;
    enum PWS_BCAL;
    enum PWS_RF;
  }
}

grouping DefaultNotificationSubscription {

  leaf notificationType {
    type NotificationType;
  }

  leaf callbackUri {
    type inet:uri;
  }

  leaf n1MessageClass {
    type N1MessageClass;
  }

  leaf n2InformationClass {
    type N2InformationClass;
  }
}
```

```

    }
  }

  grouping Ipv4AddressRange {
    leaf start {
      type inet:ipv4-address;
    }
    leaf end {
      type inet:ipv4-address;
    }
  }

  grouping Ipv6PrefixRange {
    leaf start {
      type inet:ipv6-prefix;
    }
    leaf end {
      type inet:ipv6-prefix;
    }
  }

  typedef NsiId {
    type string;
  }

  typedef UeMobilityLevel {
    type enumeration {
      enum STATIONARY;
      enum NOMADIC;
      enum RESTRICTED_MOBILITY;
      enum FULLY_MOBILITY;
    }
  }

  typedef ResourceSharingLevel {
    type enumeration {
      enum SHARED;
      enum NOT_SHARED;
    }
  }

  typedef TxDirection {
    type enumeration {
      enum DL;
      enum UL;
      enum DL_AND_UL;
    }
  }

  grouping AddressWithVlan {
    leaf ipAddress {
      type inet:ip-address;
    }
    leaf vlanId {
      type uint16;
    }
  }

  typedef DistinguishedName { // TODO is this equivalent to TS 32.300 ?
    type string {
      pattern '([a-zA-Z][a-zA-Z0-9-]*=(\\( [#|\\|>|<|;|"|\+|,|[a-fA-F0-9]{2})|[^\\><;"+, # ])'
        + '(((\\( [#|\\|>|<|;|"|\+|,|[a-fA-F0-9]{2})|[^\\><;"+, ])*'
        + '(\\( [#|\\|>|<|;|"|\+|,|[a-fA-F0-9]{2})|[^\\><;"+, ]))?)'
        + '[,\\+])*[a-zA-Z][a-zA-Z0-9-]*=(\\( [#|\\|>|<|;|"|\+|,|[a-fA-F0-9]{2})|[^\\><;"+, # ])'
        + '(((\\( [#|\\|>|<|;|"|\+|,|[a-fA-F0-9]{2})|'
        + '|[^\\><;"+, ])*\\( [#|\\|>|<|;|"|\+|,|[a-fA-F0-9]{2})|[^\\><;"+, ]))?)';
    }
    description "Represents the international standard for the representation
      of Distinguished Name (RFC 4512).
      The format of the DistinguishedName REGEX is:
      {AttributeType = AttributeValue}

      AttributeType consists of alphanumeric and hyphen (OIDs not allowed).
      All other characters are restricted.
      The Attribute value cannot contain control characters or the
      following characters : \\ > < ; \" + , (Comma) and White space
      The Attribute value can contain the following characters if they
      are escaped : \\ > < ; \" + , (Comma) and White space

```

```

The Attribute value can contain control characters if its an escaped
double digit hex number.
Examples could be
  UID=nobody@example.com,DC=example,DC=com
  CN=John Smith,OU=Sales,O=ACME Limited,L=Moab,ST=Utah,C=US";
reference "RFC 4512 Lightweight Directory Access Protocol (LDAP):
  Directory Information Models";
} // recheck regexp it doesn't handle posix [:cntrl:]

typedef QOffsetRange {
  type int8 {
    range "-24 | -22 | -20 | -18 | -16 | -14 | -12 | -10 | -8 | -6 | " +
      " -5 | -4 | -3 | -2 | -1 | 0 | 1 | 2 | 3 | 4 | 5 | 6 | 8 | 10 | " +
      " 12 | 14 | 16 | 18 | 20 | 22 | 24";
  }
  units dB;
}
}
<CODE ENDS>

```

D.3 Graphical representation

This is the YANG module tree diagram whose syntax is defined in [x].

```

module: _3gpp-common-managed-element
  +--rw ManagedElement* [id]
    +--rw id string
    +--rw attributes
      +--rw dnPrefix? types3gpp:DistinguishedName
      +--rw userLabel? string
      +--ro locationName? string
      +--ro managedBy* types3gpp:DistinguishedName
      +--ro managedElementTypeList* string
      +--ro supportedMeasurementsGPs* [measurementType] {MeasurementsUnderManagedElement}?
        +--ro measurementType string
        +--ro supportedGPs* uint32
      +--ro vendorName? string
      +--rw userDefinedState? string
      +--ro swVersion? string
      +--rw priorityLabel uint32
    +--rw MeasurementControl* [id] {MeasurementsUnderManagedElement}?
      +--rw id string
      +--rw attributes
        +--rw pMAAdministrativeState? types3gpp:AdministrativeState
        +--ro pMOperationalState types3gpp:OperationalState
        +--rw defaultFileLocation? string
        +--rw defaultFileBasedGP uint32
        +--rw defaultFileReportingPeriod uint32
        +--rw defaultStreamTarget? string {StreamingSupported}?
        +--rw defaultStreamBasedGP uint32 {StreamingSupported}?
      +--rw MeasurementReader* [id]
        +--rw id string
        +--rw attributes
          +--rw measurementTypes* string
          +--rw managedObjectDNsBasic* types3gpp:DistinguishedName
          +--rw managedObjectDNs* types3gpp:DistinguishedName
          +--rw fileLocation? string
          +--rw fileBasedGP uint32
          +--rw fileReportingPeriod uint32
          +--rw streamTarget? string
          +--rw streamBasedGP uint32
module: _3gpp-common-subnetwork
  +--rw SubNetwork* [id]
    +--rw id string
    +--rw attributes
      +--rw dnPrefix? types3gpp:DistinguishedName
      +--rw userLabel? string
      +--rw userDefinedNetworkType? string
      +--ro supportedMeasurementsGPs* [measurementType]
        +--ro measurementType string
        +--ro supportedGPs* uint32
      +--rw setOfMcc* types3gpp:Mcc
      +--rw priorityLabel uint32
      +--rw parents* -> ../../../../SubNetwork/id
      +--rw containedChildren* -> ../../../../SubNetwork/id
    +--rw MeasurementControl* [id] {MeasurementsUnderSubNetwork}?

```

```
+-rw id string
+-rw attributes
| +-rw pMAAdministrativeState? types3gpp:AdministrativeState
| +-ro pMOperationalState types3gpp:OperationalState
| +-rw defaultFileLocation? string
| +-rw defaultFileBasedGP uint32
| +-rw defaultFileReportingPeriod uint32
| +-rw defaultStreamTarget? string {StreamingSupported}?
| +-rw defaultStreamBasedGP uint32 {StreamingSupported}?
+-rw MeasurementReader* [id]
+-rw id string
+-rw attributes
+-rw measurementTypes* string
+-rw managedObjectDNsBasic* types3gpp:DistinguishedName
+-rw managedObjectDNs* types3gpp:DistinguishedName
+-rw fileLocation? string
+-rw fileBasedGP uint32
+-rw fileReportingPeriod uint32
+-rw streamTarget? string
+-rw streamBasedGP uint32
```


Annex E (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2012-12					New version after approval	2.0.0	11.0.0
2013-06	SA#60	SP-130304	002	2	Correction of XML schema	11.0.0	11.1.0
2014-06	SA#64	SP-140332	003	1	upgrade XSD	11.1.0	11.2.0
		SP-140358	004	-	remove the feature support statements		
2014-09	SA#65	SP-140560	005	-	Update the link from Solution Set to Information Service due to the end of Release 12	11.2.0	12.0.0
2015-12	SA#70	SP-150691	006	1	Add missing id attribute	12.0.0	12.1.0
2016-01					Upgrade to Rel-13 (MCC)	12.1.0	13.0.0
2016-03	SA#71	SP-160031	010	1	Make the XML schema well formed	13.0.0	13.1.0

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2016-06	SA#72	SP-160407	0011	-	F	Update the link from IRP Solution Set to IRP Information Service	13.2.0
2017-03	SA#75	-	-	-	-	Promotion to Release 14 without technical change	14.0.0
2017-06	SA#76	SP-170510	0015	2	B	Modifications to align with IS to support Configuration Management for mobile networks that include virtualized network functions	14.1.0
2018-03	SA#79	SP-180060	0016	1	B	Add attribute peeParametersList to Solution Set definitions	15.0.0
2018-12	SA#82	SP-181042	0018	1	F	Update NRM root IOCs Solution Set to support priority	15.1.0
2019-03	SA#83	SP-190121	0020	1	F	Update Generic NRM Solution Set to support JSON	15.2.0
2019-09	SA#85	SP-190744	0022	2	F	Add IDL XML YANG solution	15.3.0
2019-09	SA#85	SP-190744	0023	3	F	generate JSON definition for generic NRM based on new style guideline	15.3.0
2019-09	SA#85	SP-190751	0028	-	F	Correct references and remove not need abbreviations	15.3.0
2019-12	SA#86	SP-191173	0030	-	F	Correct XML solution set for generic NRM	15.4.0
2019-12	SA#86	SP-191173	0036	1	F	Update the definition of attribute measurementsList	15.4.0
2020-09	SA#89e	SP-200727	0100	1	A	Clean-up definitions and references	15.5.0
2022-12	SA#98e	SP-221173	0198	1	F	Adding YANG begin and End markers	15.6.0

History

Document history		
V15.0.0	July 2018	Publication
V15.1.0	April 2019	Publication
V15.2.0	May 2019	Publication
V15.3.0	October 2019	Publication
V15.4.0	January 2020	Publication
V15.5.0	November 2020	Publication
V15.6.0	January 2023	Publication