

ETSI TS 128 626 V19.0.0 (2025-10)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
State management data definition
Integration Reference Point (IRP);
Solution Set (SS) definitions
(3GPP TS 28.626 version 19.0.0 Release 19)**



ReferenceRTS/TSGS-0528626vj00

KeywordsLTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver repository](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	5
Introduction	5
1 Scope	6
2 References	6
3 Definitions and abbreviations.....	7
3.1 Definitions	7
3.2 Abbreviations	7
4 Solution Set (SS) definitions	8
Annex A (normative): CORBA Solution Set (SS).....	9
A.1 Architectural features	9
A.1.1 Syntax for Distinguished Names	9
A.2 Mapping	9
A.2.1 General mapping	9
A.2.2 Information Object Class (IOC) mapping	9
A.3 Solution Set definitions	10
A.3.1 IDL definition structure	10
A.3.2 IDL specification “StateManagementIRPConstDefs.idl”	11
A.3.3 IDL specification “StateManagementIRPOptConstDefs.idl”	13
A.3.4 IDL specification “StateManagementIRPCommonConstDefs.idl”	15
Annex B (normative): XML definitions.....	17
B.0 General	17
B.1 Architectural features	17
B.1.0 Introduction	17
B.1.1 Syntax for Distinguished Names	17
B.2 Mapping	17
B.3 Solution Set definitions	17
B.3.1 XML definition structure.....	17
B.3.2 XML schema “stateManagementIRP.xsd”	18
Annex C (normative): JSON definitions.....	20
C.1 General	20
C.2 Architectural features	20
C.2.1 Introduction	20
C.2.2 Syntax for Distinguished Names	20
C.3 Mapping	20
C.3.1 Attributes mapping	20
C.4 Solution Set (SS) definitions	20
C.4.1 JSON definition structure	20
C.4.2 Graphical representation.....	20
C.4.3 JSON schema “stateManagementNrm.json”	21
Annex D (Informative): Change history.....	22

History23

Foreword

This Technical Specification (TS) has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- 28.624 State Management Data Definition Integration Reference Point (IRP); Requirements.
- 28.625 State Management Data Definition Integration Reference Point (IRP); Information Service (IS).
- 28.626 State Management Data Definition Integration Reference Point (IRP); Solution Set (SS) definitions.**

1 Scope

The present document specifies the Solution Set (SS) definitions for the IRP whose semantics is specified in State Management Data Definition IRP: Information Service (IS) (3GPP TS 28.625 [2]).

2 References

The following documents contain provisions, which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 28.623: "Generic Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions".
- [2] 3GPP TS 28.625: "Telecommunication management; State Management Data Definition Integration Reference Point (IRP): Information Service (IS)".
- [3] ITU-T Recommendation X.721: "Information technology - Open Systems Interconnection - Structure of management information: Definition of management information".
- [4] ITU-T Recommendation M.3100: "Generic network information model".
- [5] 3GPP TS 32.612: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); Information Service (IS)".
- [6] 3GPP TS 32.616: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP); Solution Set (SS) definitions".
- [7] W3C REC-xml11-20060816: "Extensible Markup Language (XML) 1.1 (Second Edition)".
- [8] Void.
- [9] W3C XML Schema Definition Language (XSD) 1.1 Part 1: Structures..
- [10] W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes.
- [11] W3C REC-xml-names-20060816: "Namespaces in XML 1.1 (Second Edition)".
- [12] ITU-T Recommendation X.721: "Information technology - Open Systems Interconnection - Structure of management information: Definition of management information".
- [13] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [14] 3GPP TS 32.158: "Management and orchestration; Design rules for REpresentational State Transfer (REST) Solution Sets (SS) ".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions defined in 3GPP TS 32.672 [2] apply, and the following XML terms and definitions apply:

XML file: See definition in TS 32.616 [6].

XML document: See definition in TS 32.616 [6].

XML declaration: See definition in TS 32.616 [6].

XML element: See definition in TS 32.616 [6].

empty XML element: See definition in TS 32.616 [6].

XML content (of an XML element): See definition of [1].

XML start-tag: See definition in TS 32.616 [6].

XML end-tag: See definition in TS 32.616 [6].

XML empty-element tag: See definition in TS 32.616 [6].

XML attribute specification: See definition in TS 32.616 [6].

DTD: See definition in TS 32.616 [6].

XML schema: See definition in TS 32.616 [6].

XML namespace: See definition in TS 32.616 [6].

XML complex type: See definition in TS 32.616 [6].

XML element type: See definition in TS 32.616 [6].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CM	Configuration Management
CORBA	Common Object Request Broker Architecture
DTD	Document Type Definition
EDGE	Enhanced Data for GSM Evolution
GERAN	GSM/EDGE Radio Access Network
GSM	Global System for Mobile communication
IDL	Interface Definition Language
IOC	Information Object Class
IRP	Integration Reference Point
IS	Information Service
NE	Network Element
NRM	Network Resource Model
OMG	Object Management Group
SS	Solution Set
UMTS	Universal Mobile Telecommunications System
UTRAN	Universal Terrestrial Radio Access Network
XML	eXtensible Markup Language

4 Solution Set (SS) definitions

This specification defines the following 3GPP State Management Data Definition IRP Solution Set definitions:

- 3GPP State Management Data Definition IRP CORBA SS (Annex A).
- 3GPP State Management Data Definition IRP XML definitions (Annex B).
- 3GPP State Management Data Definition IRP JSON definitions (Annex C).

Annex A (normative): CORBA Solution Set (SS)

A.1 Architectural features

The overall architectural feature of State Management Data Definition IRP is specified in 3GPP TS 28.625 [2].

This clause specifies features that are specific to the CORBA SS.

A.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [13].

A.2 Mapping

A.2.1 General mapping

None.

A.2.2 Information Object Class (IOC) mapping

Table 1 provides the mapping of the information object classes defined in the IS of the State Management IRP [2] to the equivalent of this CORBA Solution Set.

Table 1: Mapping of IOCs

IOCs defined in State Management Data Definition IRP IS [2]	CORBA SS Method
StateManagementEntity	No mapping applicable for this <<Archetype>> class.

Table 2: Mapping of Attributes

Attributes defined in State Management Data Definition IRP IS [2]	CORBA SS Method attributes	Qualifier
operationalState	OperationalState (ITU-T Recommendation X.721 [3])	M
operationalState	OperationalStateTypeOpt (ITU-T Recommendation X.721 [3])	O
usageState	UsageState (ITU-T Recommendation X.721 [3])	M
usageState	UsageStateTypeOpt (ITU-T Recommendation X.721 [3])	O
administrativeState	AdministrativeState (ITU-T Recommendation X.721 [3])	M
administrativeState	AdministrativeStateTypeOpt (ITU-T Recommendation X.721 [3])	O
alarmStatus	AlarmStatus (ITU-T Recommendation M.3100 [4])	M
alarmStatus	AlarmStatusTypeOpt (ITU-T Recommendation M.3100 [4])	O
proceduralStatus	ProceduralStatus (ITU-T Recommendation X.721 [3])	M
proceduralStatus	ProceduralStatusTypeOpt (ITU-T Recommendation X.721 [3])	O
availabilityStatus	AvailabilityStatus (ITU-T Recommendation X.721 [3])	M
availabilityStatus	AvailabilityStatusTypeOpt (ITU-T Recommendation X.721 [3])	O
controlStatus	ControlStatus (ITU-T Recommendation X.721 [3])	M
controlStatus	ControlStatusTypeOpt (ITU-T Recommendation X.721 [3])	O
standbyStatus	StandbyStatus (ITU-T Recommendation X.721 [3])	M
standbyStatus	StandbyStatusTypeOpt (ITU-T Recommendation X.721 [3])	O
unknownStatus	UnknownStatus (ITU-T Recommendation X.721 [3])	M
unknownStatus	UnknownStatusTypeOpt (ITU-T Recommendation X.721 [3])	O

A.3 Solution Set definitions

A.3.1 IDL definition structure

Clause A.3.2 contains const definitions for State Management Data Definition IRP.

Clause A.3.3 contains commonly used optional definitions for State Management Data Definition IRP.

Clause A.3.4 contains commonly used definitions for State Management Data Definition IRP.

A.3.2 IDL specification “StateManagementIRPConstDefs.idl”

```
//File:- StateManagementIRPConstDefs.idl
#ifndef _STATE_MANAGEMENT_IRP_CONST_DEFS_IDL_
#define _STATE_MANAGEMENT_IRP_CONST_DEFS_IDL_

#include "CosNotification.idl"
#include "ManagedGenericIRPConstDefs.idl"
#include <StateManagementIRPCommonConstDefs.idl>
#include <StateManagementIRPOptConstDefs.idl>

// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"

/* ## Module: StateManagementIRPConstDefs
This module contains commonly used definitions for State Management IRP
=====
*/
module StateManagementIRPConstDefs
{
/*
Constant definitions for state management notifications uses when populating the
Cos::Structured event.
The "name" party of the structured event carries the following constant definitions
appropriate to the state being notified.
Refer to TS 32.666 regarding how to populate the structured event
*/
    interface AttributeNameValue {
        const string OPERATIONAL_STATE      = "operationalState";
        const string USAGE_STATE             = "usageState";
        const string ADMINISTRATIVE_STATE    = "administrativeState";
        const string ALARM_STATUS            = "alarmStatus";
        const string PROCEDURAL_STATUS       = "proceduralStatus";
        const string AVAILABILITY_STATUS     = "availabilityStatus";
        const string CONTROL_STATUS          = "controlStatus";
        const string STANDBY_STATUS          = "standbyStatus";
        const string UNKNOWN_STATUS          = "unknownStatus";
    };

/*
The following structures provide the new state value,
and the optional old state value
The structures are passed in the value part of the cos structured event
*/
    struct OperationalStateOldNewValue{
        StateManagementIRPCommonConstDefs::OperationalState new;
        StateManagementIRPOptConstDefs::OperationalStateTypeOpt old;
    };

    struct UsageStateOldNewValue{
        StateManagementIRPCommonConstDefs::UsageState new;
        StateManagementIRPOptConstDefs::UsageStateTypeOpt old;
    };

    struct AdministrativeStateOldNewValue{
        StateManagementIRPCommonConstDefs::AdministrativeState new;
        StateManagementIRPOptConstDefs::AdministrativeStateTypeOpt old;
    };

    struct AlarmStatusOldNewValue{
        StateManagementIRPCommonConstDefs::AlarmStatus new;
        StateManagementIRPOptConstDefs::AlarmStatusTypeOpt old;
    };

    struct ProceduralStatusOldNewValue{
        StateManagementIRPCommonConstDefs::ProceduralStatusValues new;
        StateManagementIRPOptConstDefs::ProceduralStatusTypeOpt old;
    };

    struct AvailabilityStatusOldNewValue{
```

```
    StateManagementIRPCommonConstDefs::AvailabilityStatusValues new;  
    StateManagementIRPOptConstDefs:: AvailabilityStatusTypeOpt old;  
};  
  
struct ControlStatusOldNewValue{  
    StateManagementIRPCommonConstDefs::ControlStatusValues new;  
    StateManagementIRPOptConstDefs::ControlStatusTypeOpt old;  
};  
  
struct StandbyStatusOldNewValue{  
    StateManagementIRPCommonConstDefs::StandbyStatus new;  
    StateManagementIRPOptConstDefs::StandbyStatusTypeOpt old;  
};  
  
struct UnknownStatusOldNewValue{  
    StateManagementIRPCommonConstDefs::UnknownStatus new;  
    StateManagementIRPOptConstDefs::UnknownStatusTypeOpt old;  
};  
  
};  
#endif // _STATE_MANAGEMENT_IRP_CONST_DEFS_IDL_
```

A.3.3 IDL specification “StateManagementIRPOptConstDefs.idl”

```
//File:-StateManagementIRPOptConstDefs.idl
#ifndef _STATE_MANAGEMENT_IRP_OPT_CONST_DEFS_IDL_
#define _STATE_MANAGEMENT_IRP_OPT_CONST_DEFS_IDL_

#include "CosNotification.idl"
#include "ManagedGenericIRPConstDefs.idl"
#include "StateManagementIRPCommonConstDefs.idl"
// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"

/* ## Module: StateManagementIRPOptConstDefs
This module contains commonly used optional definitions for State Management IRP
=====
*/
module StateManagementIRPOptConstDefs
{
    /*
    Definition of Operational State based on X.721 [3], if optional.
    */
    union OperationalStateTypeOpt switch(boolean)
    {
        case TRUE: StateManagementIRPCommonConstDefs::OperationalState operational_state;
    };

    /*
    Definition of Usage State based on X.721 [3], if optional.
    */
    union UsageStateTypeOpt switch(boolean)
    {
        case TRUE: StateManagementIRPCommonConstDefs::UsageState usage_state;
    };

    /*
    Definition of Administrative State based on X.721 [3], if optional.
    */
    union AdministrativeStateTypeOpt switch(boolean)
    {
        case TRUE: StateManagementIRPCommonConstDefs::AdministrativeState administrative_state;
    };

    /*
    Definition of Alarm Status based on M.3100 [4], if optional.
    */
    union AlarmStatusTypeOpt switch(boolean)
    {
        case TRUE: StateManagementIRPCommonConstDefs::AlarmStatus alarm_status;
    };

    /*
    Definition of Procedural Status based on X.721 [3], if optional.
    */
    union ProceduralStatusTypeOpt switch(boolean)
    {
        case TRUE: StateManagementIRPCommonConstDefs::ProceduralStatus procedural_status;
    };

    /*
    Definition of Availability Status based on X.721 [3], if optional.
    */
    union AvailabilityStatusTypeOpt switch(boolean)
    {
        case TRUE: StateManagementIRPCommonConstDefs::AvailabilityStatus availability_status;
    };

    /*
    Definition of Control Status based on X.721 [3], if optional.
    */
    union ControlStatusTypeOpt switch(boolean)
    {
        case TRUE: StateManagementIRPCommonConstDefs::ControlStatus control_status;
    };

    /*
    Definition of Standby Status based on X.721 [3], if optional.
    */
}
```

```
*/
union StandbyStatusTypeOpt switch(boolean)
{
    case TRUE: StateManagementIRPCommonConstDefs::StandbyStatus standby_status;
};

/*
Definition of Unknown Status based on X.721 [3], if optional.
*/
union UnknownStatusTypeOpt switch(boolean)
{
    case TRUE: StateManagementIRPCommonConstDefs::UnknownStatus unknown_status;
};

};
#endif // _STATE_MANAGEMENT_IRP_OPT_CONST_DEFS_IDL_
```

A.3.4 IDL specification

“StateManagementIRPCommonConstDefs.idl”

```
//File: StateManagementIRPCommonConstDefs.idl
#ifndef _STATE_MANAGEMENT_IRP_COMMON_CONST_DEFS_IDL_
#define _STATE_MANAGEMENT_IRP_COMMON_CONST_DEFS_IDL_

// This statement must appear after all include statements
#pragma prefix "3gppsa5.org"

/* Module: StateManagementIRPCommonConstDefs
This module contains commonly used definitions for State Management IRP
=====
*/
module StateManagementIRPCommonConstDefs
{
    /*
    Definition of Operational State based on X.721 [3], if mandatory.
    */
    enum OperationalState
    {
        Disabled, Enabled
    };

    /*
    Definition of Usage State based on X.721 [3], if mandatory.
    */
    enum UsageState
    {
        Idle, Active, Busy
    };

    /*
    Definition of Administrative State based on X.721 [3], if mandatory.
    */
    enum AdministrativeState
    {
        Locked, Unlocked, ShuttingDown
    };

    /*
    Definition of Alarm Status based on M.3100 [4], if mandatory.
    */
    enum AlarmStatus
    {
        CLEARED, INDETERMINATE, WARNING, MINOR, MAJOR, CRITICAL
    };

    /*
    Definition of Procedural Status based on X.721 [3], if mandatory.
    */
    enum ProceduralStatusValues
    {
        InitializationRequired, NotInitialized, Initializing, Reporting,
        Terminating
    };
    typedef sequence <ProceduralStatusValues,5> ProceduralStatus;

    /*
    Definition of Availability Status based on X.721 [3], if mandatory.
    */
    enum AvailabilityStatusValues
    {
        InTest, Failed, PowerOff, OffLine, OffDuty, Dependency, Degraded,
        NotInstalled, LogFull
    };
    typedef sequence <AvailabilityStatusValues,9> AvailabilityStatus;

    /*
    Definition of Control Status based on X.721 [3], if mandatory.
    */
    enum ControlStatusValues
    {
        SubjectToTest, PartOfServicesLocked, ReservedForTest, Suspended
    };
    typedef sequence <ControlStatusValues,4> ControlStatus;
```

```
/*
Definition of Standby Status based on X.721 [3], if mandatory.
*/
enum StandbyStatus
{
    HotStandby, ColdStandby, ProvidingService
};

/*
Definition of Unknown Status based on X.721 [3], if mandatory
(if switch is TRUE then value equal to TRUE implies "unknown status").
*/
union UnknownStatus switch(boolean)
{
    case TRUE: boolean value;
};

};
#endif // _STATE_MANAGEMENT_IRP_COMMON_CONST_DEFS_IDL_
```

Annex B (normative): XML definitions

B.0 General

This annex specifies the XML file format definition for the Bulk Configuration Management IRP IS [5] for the IRP whose semantics is specified in State Management Data Definition IRP: Information Service (IS) (3GPP TS 28.625 [2]).

The XML file formats are based on XML [7], XML Schema [9][10] and XML Namespace [11] standards.

B.1 Architectural features

B.1.0 Introduction

The overall architectural feature of State Management IRP is specified in 3GPP TS 28.625 [2].

This clause specifies features that are specific to the XML Schema definitions.

B.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [13].

B.2 Mapping

The mapping is not present in the current version of this specification.

B.3 Solution Set definitions

B.3.1 XML definition structure

The overall description of the file format of configuration data XML files is provided by 3GPP TS 32.616 [6].

Clause B.3.2 defines the XML schema `stateManagementIRP.xsd` for the State Management IRP: Information Service (IS) defined in 3GPP TS 28.625 [2].

The definition of the XML element types complies with the generic mapping rules defined in 3GPP TS 32.616 [6].

B.3.2 XML schema “stateManagementIRP.xsd”

```

<?xml version="1.1" encoding="UTF-8"?>
<!--
  3GPP TS 28.626 State Management IRP
  Bulk CM Configuration data file XML schema
  stateManagementIRP.xsd
-->
<schema
  targetNamespace=
    "http://www.3gpp.org/ftp/specs/archive/28_series/28.626#stateManagementIRP"
  elementFormDefault="qualified"
  xmlns="http://www.w3.org/2001/XMLSchema"
  xmlns:sm=
    "http://www.3gpp.org/ftp/specs/archive/28_series/28.626#stateManagementIRP"
>
  <!-- State Management IRP related XML types -->
  <simpleType name="operationalStateType">
    <restriction base="string">
      <enumeration value="enabled"/>
      <enumeration value="disabled"/>
    </restriction>
  </simpleType>
  <simpleType name="usageStateType">
    <restriction base="string">
      <enumeration value="idle"/>
      <enumeration value="active"/>
      <enumeration value="busy"/>
    </restriction>
  </simpleType>
  <simpleType name="administrativeStateType">
    <restriction base="string">
      <enumeration value="locked"/>
      <enumeration value="unlocked"/>
      <enumeration value="shuttingDown"/>
    </restriction>
  </simpleType>
  <simpleType name="alarmStatusType">
    <restriction base="string">
      <enumeration value="cleared"/>
      <enumeration value="indeterminate"/>
      <enumeration value="warning"/>
      <enumeration value="minor"/>
      <enumeration value="major"/>
      <enumeration value="critical"/>
    </restriction>
  </simpleType>
  <simpleType name="proceduralStatusElementType">
    <restriction base="string">
      <enumeration value="initializationRequired"/>
      <enumeration value="notInitialized"/>
      <enumeration value="initializing"/>
      <enumeration value="reporting"/>
      <enumeration value="terminating"/>
    </restriction>
  </simpleType>
  <complexType name="proceduralStatusType">
    <sequence minOccurs="0" maxOccurs="5">
      <element name="proceduralStatusElement" type="sm:proceduralStatusElementType"/>
    </sequence>
  </complexType>
  <simpleType name="availabilityStatusElementType">
    <restriction base="string">
      <enumeration value="inTest"/>
      <enumeration value="failed"/>
      <enumeration value="powerOff"/>
      <enumeration value="offLine"/>
      <enumeration value="offDuty"/>
      <enumeration value="dependency"/>
      <enumeration value="degraded"/>
      <enumeration value="notInstalled"/>
      <enumeration value="logFull"/>
    </restriction>
  </simpleType>
  <complexType name="availabilityStatusType">
    <sequence minOccurs="0" maxOccurs="9">

```

```
<element name="availabilityStatusElement" type="sm:availabilityStatusElementType"/>
</sequence>
</complexType>
<simpleType name="controlStatusElementType">
  <restriction base="string">
    <enumeration value="subjectToTest"/>
    <enumeration value="partOfServicesLocked"/>
    <enumeration value="reservedForTest"/>
    <enumeration value="suspended"/>
  </restriction>
</simpleType>
<complexType name="controlStatusType">
  <sequence minOccurs="0" maxOccurs="4">
    <element name="controlStatusElement" type="sm:controlStatusElementType"/>
  </sequence>
</complexType>
<simpleType name="standbyStatusType">
  <restriction base="string">
    <enumeration value="hotStandby"/>
    <enumeration value="coldStandby"/>
    <enumeration value="providingService"/>
  </restriction>
</simpleType>
<simpleType name="unknownStatusType">
  <restriction base="boolean">
    <pattern value="true"/>
    <pattern value="false"/>
  </restriction>
</simpleType>
<element name="operationalState" type="sm:operationalStateType"/>
<element name="usageState" type="sm:usageStateType"/>
<element name="administrativeState" type="sm:administrativeStateType"/>
<element name="alarmStatus" type="sm:alarmStatusType"/>
<element name="proceduralStatus" type="sm:proceduralStatusType"/>
<element name="availabilityStatus" type="sm:availabilityStatusType"/>
<element name="controlStatus" type="sm:controlStatusType"/>
<element name="standbyStatus" type="sm:standbyStatusType"/>
<element name="unknownStatus" type="sm:unknownStatusType"/>
</schema>
```

Annex C (normative): JSON definitions

C.1 General

This annex specifies the JSON file format definition for the NRM whose semantics is specified in State Management Data Definition IRP: Information Service (IS) (3GPP TS 28.625 [2]).

C.2 Architectural features

C.2.1 Introduction

The overall architectural feature of State Management IRP is specified in 3GPP TS 28.625 [2].

This clause specifies features that are specific to the JSON Schema definitions.

C.2.2 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [13].

C.3 Mapping

C.3.1 Attributes mapping

Mapping from the attributes of IOCs defined in the information model to SS equivalent definitions are listed in the following table.

Object Attributes	JSON definitions' Name	JSON Type
operationalState	operationalState	OperationalState
usageState	usageState	UsageState
administrativeState	administrativeState	AdministrativeState
alarmStatus	alarmStatus	AlarmStatus
proceduralStatus	proceduralStatus	ProceduralStatus
availabilityStatus	availabilityStatus	AvailabilityStatus
controlStatus	controlStatus	ControlStatus
standbyStatus	standbyStatus	StandbyStatus
unknownStatus	unknownStatus	UnknownStatus

C.4 Solution Set (SS) definitions

C.4.1 JSON definition structure

JSON is used as resource representations format carried in the HTTP request and HTTP response message bodies. The properties (key-value pairs) on an object are defined using the properties keyword.

The definition of the JSON resource object complies with the generic rules defined in 3GPP TS 32.158 [14].

C.4.2 Graphical representation

The graphical representation is not present in the current version of the present document.

C.4.3 JSON schema "stateManagementNrm.json"

```
{
  "$schema": "http://json-schema.org/draft-05/schema#",
  "id": "http://3gpp.org/28626/stateManagementNrm.json",
  "description": "JSON based solution set definitions for State Management NRM",
  "definitions": {
    "AdministrativeState": {
      "enum": ["Locked", "Unlocked", "ShuttingDown"]
    },
    "OperationalState": {
      "enum": ["Enabled", "Disabled"]
    },
    "AvailabilityStatus": {
      "enum": ["InTest", "Failed", "PowerOff", "OffLine", "OffDuty", "Dependency", "Degraded",
        "NotInstalled", "LogFull"]
    },
    "UsageState": {
      "enum": ["Idle", "Active", "Busy"]
    },
    "AlarmStatus": {
      "enum": ["Cleared", "Indeterminate", "Warning", "Minor", "Major", "Critical"]
    },
    "ProceduralStatus": {
      "enum": ["InitialisationRequired", "NotInitialised", "Initialising", "Reporting",
        "Terminating"]
    },
    "ControlStatus": {
      "enum": ["SubjectToTest", "PartOfServicesLocked", "ReservedForTest", "Suspended"]
    },
    "StandbyStatus": {
      "enum": ["HotStandby", "ColdStandby", "ProvidingService"]
    },
    "UnknownStatus": {
      "enum": ["True", "False"]
    }
  }
}
```

Annex D (Informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2014-06	SA#64	SP-140332	001	-	upgrade XSD	11.0.0	11.1.0
		SP-140358	002	-	remove the feature support statements		
2014-09	SA#65	SP-140560	003	-	Update the link from Solution Set to Information Service due to the end of Release 12	11.1.0	12.0.0
2016-01	SA#70				Upgrade to Rel-13(MCC)	12.0.0	13.0.0

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2016-06	SA#72	SP-160407	0004	-	F	Update the link from IRP Solution Set to IRP Information Service	13.1.0
2017-03	SA#75	-	-	-	-	Promotion to Release 14 without technical change	14.0.0
2017-06	SA#76	SP-170514	0005	-	F	Update link from IRP SS to IS	14.1.0
2018-06	-	-	-	-	-	Update to Rel-15 version (MCC)	15.0.0
2019-03	-		0007	1	F	Update State management data definition Solution Set to support JSON	15.1.0
2020-07	-	-	-	-	-	Update to Rel-16 version (MCC)	16.0.0
2022-03	-	-	-	-	-	Update to Rel-17 version (MCC)	17.0.0
2024-04	-	-	-	-	-	Update to Rel-18 version (MCC)	18.0.0
2024-09	SA#105	SP-241164	0009	1	A	Rel-18 CR TS 28.626 Correction of XML references	18.1.0
2025-09	SA#109	-	-	-	-	Update to Rel-19 version (MCC)	19.0.0

History

Document history		
V19.0.0	October 2025	Publication