

ETSI TS 128 667 V19.0.0 (2025-10)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Radio Planning Tool Access (RPTA)
Integration Reference Point (IRP);
Requirements
(3GPP TS 28.667 version 19.0.0 Release 19)**



ReferenceRTS/TSGS-0528667vj00

KeywordsLTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver repository](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	5
4 Concepts and background	6
4.1 General	6
4.2 Architecture	6
4.3 Functionality	6
5 Business level requirements	6
5.1 Requirements.....	6
5.2 Actor roles	6
5.3 Telecommunications resources	6
5.4 High-level use cases	7
5.4.1 Use Case: Read planned data from the RPT	7
6 Specification level requirements	7
6.1 Requirements.....	7
6.2 Actor roles	7
6.3 Telecommunications resources	7
6.4 Use cases	8
6.4.1 Use Case 1: Read planned site data	8
6.4.2 Use Case 2: Read planned antenna data.....	8
6.4.3 Use Case 3: Find out the planned antennas supporting a planned cell.....	8
6.4.4 Use Case 4: Find out the planned cells supported by a planned antenna	8
6.4.5 Use Case 5: Find out the RAT of a planned cell.....	8
Annex A (informative): Relation of RPT Planned Data, ARCF data and configuration data	9
Annex B (informative): Change history	10
History	11

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

28.667 Radio Planning Tool Access (RPTA) Integration Reference Point (IRP); Requirements

28.668 Radio Planning Tool Access (RPTA) Integration Reference Point (IRP); Information Service (IS)

28.669 Radio Planning Tool Access (RPTA) Integration Reference Point (IRP); Solution Set (SS) definitions

1 Scope

The present document specifies the requirements of the Radio Planning Tool Access (RPTA) Integration Reference Point (IRP). This IRP allows to read site and antenna data from RPTs.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [3] 3GPP TS 32.501: "Telecommunication management; Self-configuration of network elements; Concepts and requirements".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

Radio Planning Tool: The tool which is used for radio network planning, where the planning process typically includes radio frequencies assigning, sites and site locations determination, traffic planning, interference analysis, and configuration parameters planning to provide sufficient coverage and capacity for a radio network.

Planned Data: It is the data exposed by the RPT for read access by the NM.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

NMLS	Network Management Layer Service
RPT	Radio Planning Tool
RPTA	Radio Planning Tool Access (RPTA)
SC	Service Consumer
SP	Service Provider

4 Concepts and background

4.1 General

The initial planning of radio parameters is typically done with specialized tools called Radio Planning Tools (RPTs). RPTs generate throughput and capacity estimations as well as predictions for coverage and interference maps. RPTs utilize site and antenna (equipment) information, as well as geographic data (e.g. terrain data, type of land usage, building data and road data). This data has to be entered into the tools.

In order to improve the initial network planning, planned site and antenna data are adjusted until the estimated system performance meets the requirements within the given deployment constraints.

Information about the sites and antennas is needed also by other applications, like SON applications or CM applications on NM level. For this reason it is beneficial if this data can be read via standardized interfaces.

In contrast to configuration information it is normally not possible to read this data from the network elements.

The only place where this data is available in many deployment scenarios is in the RPT. Though this data represents initial planning, site data and antenna data are not likely to be changed very often, so that there is a fair chance that the data stored by the RPT represents also the actual situation in the network.

For this reason it is beneficial to have a read access to site and antenna data stored by the RPT.

It is to be noted that this TS series is only about the read access to site and antenna data. It is not concerned with any other functionality the RPT might have, nor with how the read data is used, nor if the read data represents the actual information about the network or if the data is outdated. Reading of site and antenna data stored by the RPT is hence the only use case in scope.

4.2 Architecture

The RPT is a kind of NMLS (see TS 32.101 [2]).

4.3 Functionality

The RPT offers a capability allowing read access to site and antenna data. The RPT is a Service Provider (SP) and the NM a Service Consumer (SC). The RPTA IRP specifies the information model exposed by the RPT, and the operations to access it.

5 Business level requirements

5.1 Requirements

REQ-RPT_NRM-CON-001: The RPT shall support a capability allowing the NM to retrieve planned data from the RPT.

5.2 Actor roles

The function at the NM requesting to read planned data from the RPT.

5.3 Telecommunications resources

RPT: The Radio Planning Tool storing the planned data and exposing it by its Service Provider (SP) function.

NM: The Network Manager requesting the planned data by its Service Consumer (SC) function.

SP in the RPT: The Service Provider (SP) in the RPT offering read access to planned data in the RPT.

SC in the NM: The Service Consumer (SC) in the NM using services offered by the RPT.

5.4 High-level use cases

5.4.1 Use Case: Read planned data from the RPT

Use case stage	Evolution/Specification	<<Uses>> Related use
Goal	The NM reads planned data from the RPT.	
Actors and Roles	The function in the NM requesting to read planned data from the RPT.	
Telecom resources	RPT, NM, SP in the RPT, SC in the NM.	
Assumptions	Connectivity exists between RPT SP and the NM SC, so that SP and SC can communicate.	
Pre-conditions	The network is planned and the planned data is stored and available in the RPT.	
Begins when	The NM SC requests the RPT SP to provide certain planned data stored in the RPT by sending an appropriate request message to the RPT SP.	
Step 1 (M)	The RPT SP receives the request message.	
Step 2 (M)	The RPT processes the request message, identifies the requested planned data and retrieves the requested planned data.	
Step 3 (M)	The RPT SP sends back to the NM SC the requested planned data in a response message.	
Ends when	The NM SC has received the requested planned data.	
Exceptions	The NM SC does not receive the requested planned data. Numerous failure reasons may be indicated.	
Post-conditions	The requested planned data has been returned. The planned data stored in RPT before and after the exchange of the request/response messages are identical.	
Traceability	Requirement REQ-RPT_NRM-CON-001 in clause 5.1.	

6 Specification level requirements

6.1 Requirements

REQ-RPT_NRM-FUN-001: The RPT shall support a capability allowing the NM to retrieve planned site data (e.g. site latitude, site longitude) from the RPT.

REQ-RPT_NRM-FUN-002: The RPT shall support a capability allowing the NM to retrieve planned antenna data (e.g. antenna latitude, antenna longitude, antenna type, pattern label, antenna tilt) from the RPT.

REQ-RPT_NRM-FUN-003: The RPT shall support a capability allowing the NM to find out the planned antennas supporting a planned cell.

REQ-RPT_NRM-FUN-004: The RPT shall support a capability allowing the NM to find out the planned cells supported by a planned antenna.

REQ-RPT_NRM-FUN-005: The RPT shall support a capability allowing the NM to find out the RAT of a planned cell.

6.2 Actor roles

See clause 5.2.

6.3 Telecommunications resources

See clause 5.3.

6.4 Use cases

6.4.1 Use Case 1: Read planned site data

The use case in clause 5.4.1 describes in generic fashion the use case on reading planned data from the RPT. In the use case "Read planned site data" this information is planned site data.

6.4.2 Use Case 2: Read planned antenna data

The use case in clause 5.4.1 describes in generic fashion the use case on reading planned data from the RPT. In the use case "Read planned antenna data" this information is planned antenna data.

6.4.3 Use Case 3: Find out the planned antennas supporting a planned cell

The use case in clause 5.4.1 describes in generic fashion the use case on reading planned data from the RPT. In the use case "Find out the planned antennas supporting a planned cell" this information is data about which planned antennas support a planned cell. The data returned contains thus for each cell identifier a set of antenna identifiers.

6.4.4 Use Case 4: Find out the planned cells supported by a planned antenna

The use case in clause 5.4.1 describes in generic fashion the use case on reading planned data from the RPT. In the use case "Find out the planned cells supported by a planned antenna" this information is data about which planned cells are supported by a planned antenna. The data returned contains thus for each antenna identifier a set of cell identifiers.

6.4.5 Use Case 5: Find out the RAT of a planned cell

The use case in clause 5.4.1 describes in generic fashion the use case on reading planned data from the RPT. In the use case "Find out the RAT of a planned cell" this information is data about the RATs of the planned cells.

Annex A (informative): Relation of RPT Planned Data, ARCF data and configuration data

There are several kinds of data defined in 32- and 28-series standards.

ARCF data are the data which are required for successful activation (of e.g. cell, eNB) that require coordination between several cells and cannot be generated below Itf-N. Some of the ARCF data may be used directly as eNodeB configuration data and some of the ARCF data may be used to generate more other eNodeB configuration data. eNodeB will use the ARCF data together with other configuration data as initial eNodeB radio configuration data. The eNodeB initial radio configuration data will be used for self-configuration.

Configuration data are normally defined as NRM IRP data.

Planned Data, which is the data exposed by the RPT for read access by the NM, may be different from those used during NM normal operation of the actual network.

The relation between different kinds of data is:

- 1) The Planned Data are stored in RPT. NM or other NM layer applications can retrieve Planned Data from RPT. Some of the Planned Data retrieved from RPT can be used directly as configuration data or ARCF data (e.g. antenna data like antennaAzimuth and antennaTilt).
- 2) Some of the ARCF data are used as configuration data directly and other ARCF data are used to generate more other configuration data, see TS 32.501 [3].

Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2014-12	SA#66	SP-140792			Presented for approval	1.2.0	2.0.0
					Version after approval	2.0.0	12.0.0
2016-01	SA#70				Upgrade to Rel-13(MCC)	12.0.0	13.0.0

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2017-03	SA#75					Promotion to Release 14 without technical change	14.0.0
2018-06	-	-	-	-	-	Update to Rel-15 version (MCC)	15.0.0
2020-07	-	-	-	-	-	Update to Rel-16 version (MCC)	16.0.0
2022-03	-	-	-	-	-	Update to Rel-17 version (MCC)	17.0.0
2024-04	-	-	-	-	-	Update to Rel-18 version (MCC)	18.0.0
2025-09	SA#109	-	-	-	-	Update to Rel-19 version (MCC)	19.0.0

History

Document history		
V19.0.0	October 2025	Publication