

ETSI TS 128 680 V17.0.0 (2022-04)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Wireless Local Area Network (WLAN) management;
Concepts and requirements
(3GPP TS 28.680 version 17.0.0 Release 17)**



Reference

RTS/TSGS-0528680vh00

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2022.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	5
4 Concepts and background	6
4.1 Overview	6
4.2 Mapping Function	6
4.3 WLAN alarm notification	6
5 Requirements.....	10
Annex A (informative): Change history	11
History	12

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project Technical Specification Group Services and System Aspects, Telecommunication management; as identified below:

TS 28.680: Telecommunication management; Wireless Local Area Network (WLAN) management; Concepts and requirements

TS 28.681: Telecommunication management; Wireless Local Area Network (WLAN) Network Resource Model (NRM) Integration Reference Point (IRP); Requirements.

TS 28.682: Telecommunication management; Wireless Local Area Network (WLAN) Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS).

TS 28.683: Telecommunication management; Wireless Local Area Network (WLAN) Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions.

1 Scope

The present document describes the concepts and requirements of WLAN management that focus on WLAN performance monitoring and alarm notifications.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [3] 3GPP TS 32.150: "Telecommunication management; IRP Concept and definitions".
- [4] IETF RFC 2863: "The Interfaces Group MIB".
- [5] 3GPP TS 32.111-2: "Fault Management; Part 2: Alarm Integration Reference Point (IRP): Information Service (IS)".
- [6] IETF RFC 3877: "Alarm Management Information Base (MIB)", September, 2004.
- [7] 3GPP TS 32.102: "Telecommunication management; Architecture".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1], 3GPP TS 32.101 [2], 3GPP TS 32.102 [7], and 3GPP TS 32.150 [3] apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

AC	Access Controller
AP	Access Point
IOC	Information Object Class
IRP	Integration Reference Point
NE	Network Element

4 Concepts and background

4.1 Overview

The architecture for management of WLAN AP is conformant to the Management reference model as defined in Figure 1 of TS 32.101 [2] where the WLAN AP is depicted as NE. The system context of the WLAN management is in compliance with the System Context A, defined in Figure 4.7.1 in TS 32.150 [3].

4.2 Mapping Function

Figure 4.2-1 provides an example of 3GPP – WLAN mapping function. The mapping function is to map the relevant management data produced by WLAN AP in a form suitable for distribution via the Type-2 interface to IRPManager(s). The mapping function is a logical function. Its location, as well as its internal and external interfaces, if any, are out the scope of 3GPP specification.




Figure 4.2-1: Example of 3GPP – WLAN Mapping Function

4.3 WLAN alarm notification

WLAN AP alarms can be generated from `ifOperStatus` (RFC 2863 [4]) object. The following examples extracted from RFC 3877 [6] shows that the WLAN AP embeds the `ifOperStatus` object in the `linkUp/linkDown` notifications to report the WLAN AP alarms.

"6.1. Alarms Based on linkUp/linkDown Notifications

```

linkDown NOTIFICATION-TYPE
  OBJECTS { ifIndex, ifAdminStatus, ifOperStatus }
  STATUS current
  DESCRIPTION
    ""
  ::= { snmpTraps 3 }

linkUp NOTIFICATION-TYPE

```

```

OBJECTS { ifIndex, ifAdminStatus, ifOperStatus }
STATUS current
DESCRIPTION
  ""
 ::= { snmpTraps 4 }"

alarmModelIndex 3
alarmModelState 1
alarmModelNotificationId linkUp
alarmModelVarbindIndex 0
alarmModelVarbindValue 0
alarmModelDescription "linkUp"
alarmModelSpecificPointer ituAlarmEntry.3.1
alarmModelVarbindSubtree ifIndex (1.3.6.1.2.1.2.2.1.1)
alarmModelResourcePrefix 0.0
alarmModelRowStatus active (1)
ituAlarmEventType communicationsAlarm (2)
ituAlarmPerceivedSeverity cleared (1)
ituAlarmGenericModel alarmModelEntry.3.1

alarmModelIndex 3
alarmModelState 3
alarmModelNotificationId linkDown
alarmModelVarbindIndex 2
alarmModelVarbindValue up (1)
alarmModelDescription "linkDown - confirmed problem"
alarmModelSpecificPointer ituAlarmEntry.3.3
alarmModelVarbindSubtree ifIndex (1.3.6.1.2.1.2.2.1.1)
alarmModelResourcePrefix 0.0
alarmModelRowStatus active (1)
ituAlarmEventType communicationsAlarm (2)
ituAlarmPerceivedSeverity critical (3)
  ituAlarmGenericModel alarmModelEntry.3.3"

```

WLAN AP will send a notification when ifOperStatus object changes its value. The value of ifOperStatus object is shown below (see RFC 2863 [4]).

```

ifOperStatus OBJECT-TYPE
  SYNTAX INTEGER {
    up(1),          -- ready to pass packets
    down(2),
    testing(3),    -- in some test mode
    unknown(4),    -- status can not be determined
                  -- for some reason.
    dormant(5),
    notPresent(6), -- some component is missing
    lowerLayerDown(7) -- down due to state of
                  -- lower-layer interface(s)
  }
  MAX-ACCESS read-only
  STATUS current
  DESCRIPTION
    "The current operational state of the interface. The
    testing(3) state indicates that no operational packets can
    be passed. If ifAdminStatus is down(2) then ifOperStatus
    should be down(2). If ifAdminStatus is changed to up(1)
    then ifOperStatus should change to up(1) if the interface is
    ready to transmit and receive network traffic; it should
    change to dormant(5) if the interface is waiting for
    external actions (such as a serial line waiting for an
    incoming connection); it should remain in the down(2) state
    if and only if there is a fault that prevents it from going
    to the up(1) state; it should remain in the notPresent(6)
    state if the interface has missing (typically, hardware)
    components."
  ::= { ifEntry 8 }

```

The following tables show that IRPAgent, together with the mapping function will map the IETF alarm notification attributes for down (2) and up (1) to the 3GPP alarm parameters as defined in TS 32.111-2 [5]. For each table, it also includes the example of on what conditions the 3GPP alarm notification will be sent.

1) notifyNewAlarm

IETF alarm notification attribute	Value	3GPP AlarmInformation Attribute	Legal Value
		objectClass	Carry the object class name of the IOC
		objectInstance	Carrying the Distinguished Name (DN) of this object instance
		notificationId	Carry the identifier for the notification
alarmActiveDateAndTime	DateAndTime (It indicates the local date and time when the alarm occurred)	eventTime	Convey the same semantic as DateAndTime
		systemDN	Carry either (1) the IRPagent instance containing that Interface IRP instance, or (2) the DN of that particular Interface IRP instance responsible for the emission of the notification
alarmModelVarbindValue	down (2)	notificationType	"notifyNewAlarm"
		probableCause	Communication Subsystem Failure
ituAlarmPerceivedSeverity	ituAlarmPerceivedSeverity (It indicates the alarm severity as defined in ITU Recommendation X.733)	perceivedSeverity	Convey the same semantic as ituAlarmPerceivedSeverity
ituAlarmEventType	communicationsAlarm (2)	alarmType	"Communications Alarm "
		specificProblem	Absent
		correlatedNotifications	Absent
		backedUpStatus	Absent
		backUpObject	Absent
		trendIndication	Absent
		thresholdInfo	Absent
		stateChangeDefinition	Absent
		monitoredAttributes	Absent
		proposedRepairActions	Absent
		additionalText	Absent
		additionalInformation	Absent
		alarmId	Mapping function allocates the alarm ID

If there exists no AlarmInformation [5] in AlarmList [5] corresponding to IETF alarm notification, and the IETF alarm notification is down (2), then the IRPagent will send notifyNewAlarm to the IRPManager, who has a subscription with NotificationIRP.

2) notifyChangedAlarm

IETF alarm notification attribute	Value	3GPP AlarmInformation Attribute	Legal Value
		objectClass	Carry the object class name of the IOC
		objectInstance	Carrying the Distinguished Name (DN) of this object instance
		notificationId	Carry the identifier for the notification
alarmActiveDateAndTime	DateAndTime (It indicates the local date and time when the alarm occurred)	eventTime	Convey the same semantic as DateAndTime
		systemDN	Carry either (1) the IRPagent instance containing that Interface IRP instance, or (2) the DN of that particular Interface IRP instance responsible for the emission of the notification
alarmModelVarbindValue	down (2)	notificationType	"notifyChangedAlarm".
		probableCause	Communication Subsystem Failure
ituAlarmPerceivedSeverity	See reference in ituAlarmPerceivedSeverity (It indicates the alarm severity as defined in ITU Recommendation X.733)	perceivedSeverity	Convey the same semantic as ituAlarmPerceivedSeverity
ituAlarmEventType	See reference in communicationsAlarm (2)	alarmType	"Communications Alarm "
		alarmId	Mapping function uses the alarm ID previously allocated

It there exists an AlarmInformation [5] in AlarmList [5] corresponding to IETF alarm notification, and the IETF alarm severity ituAlarmPerceivedSeverity has been changed, then the IRPagent will send notifyChangedAlarm to the IRPManager, who has a subscription with NotificationIRP.

3) notifyClearedAlarm

IETF alarm notification attribute	Value	3GPP AlarmInformation Attribute	Legal Value
		objectClass	Carry the object class name of the IOC
		objectInstance	Carrying the Distinguished Name (DN) of this object instance
		notificationId	Carry the identifier for the notification
alarmActiveDateAndTime	DateAndTime (It indicates the local date and time when the alarm occurred)	eventTime	Convey the same semantic as DateAndTime
		systemDN	Carry either (1) the IRPAgent instance containing that Interface IRP instance, or (2) the DN of that particular Interface IRP instance responsible for the emission of the notification
alarmModelVarbindValue	up (1)	notificationType	"notifyClearedAlarm".
		probableCause	Communication Subsystem Failure
ituAlarmPerceivedSeverity	See reference in ituAlarmPerceivedSeverity (It indicates the alarm severity as defined in ITU Recommendation X.733)	perceivedSeverity	"cleared"
ituAlarmEventType	See reference in communicationsAlarm (2)	alarmType	"Communications Alarm "
		correlated Notifications	Absent
		clearUserId	Absent
		clearSystemId	Absent
		alarmId	Mapping function uses the alarm ID previously allocated

If there exists an AlarmInformation [5] in AlarmList [5] corresponding to IETF alarm notification, and the IETF alarm notification is up (1), then the IRPAgent will send notifyClearedAlarm to the IRPManager, who has a subscription with NotificationIRP.

5 Requirements

REQ-WLAN_NRM_CON-001

The NRM defined by this IRP shall contain WLAN specific classes and related definitions.

Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
12-2015	SA-70	SP-150680			Presented for approval	1.1.0	2.0.0
					Upgrade to Rel-13	2.0.0	13.0.0

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2017-03	SA#75					Promotion to Release 14 without technical change	14.0.0
2018-12	-	-	-	-	-	Update to Rel-15 version (MCC)	15.0.0
2020-07	-	-	-	-	-	Update to Rel-16 version (MCC)	16.0.0
2022-03	-	-	-	-	-	Update to Rel-17 version (MCC)	17.0.0

History

Document history		
V17.0.0	April 2022	Publication