

ETSI TS 128 733 V18.0.0 (2024-05)



**Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Transport Network (TN) interface
Network Resource Model (NRM)
Integration Reference Point (IRP);
Solution Set (SS) definitions
(3GPP TS 28.733 version 18.0.0 Release 18)**



Reference

RTS/TSGS-0528733vi00

Keywords

LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2024.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

| | |
|---|-----------|
| Intellectual Property Rights | 2 |
| Legal Notice | 2 |
| Modal verbs terminology..... | 2 |
| Foreword..... | 4 |
| Introduction | 4 |
| 1 Scope | 5 |
| 2 References | 5 |
| 3 Definitions and abbreviations..... | 6 |
| 3.1 Definitions | 6 |
| 3.2 Abbreviations | 6 |
| 4 Solution Set Definitions | 7 |
| Annex A (normative): CORBA Solution Set | 8 |
| A.0 General | 8 |
| A.1 Architectural features | 8 |
| A.1.0 Introduction | 8 |
| A.1.1 Syntax for Distinguished Names | 8 |
| A.1.2 Rules for NRM extensions | 8 |
| A.2 Mapping | 8 |
| A.2.1 General mapping | 8 |
| A.2.2 Information Object Class (IOC) mapping | 8 |
| A.2.2.1 IOC TransportNetworkInterface | 8 |
| A.2.2.2 IOC ATMChannelTerminationPoint | 9 |
| A.2.2.3 IOC ATMPATHTerminationPoint | 9 |
| A.3 Solution Set definitions | 10 |
| A.3.1 IDL definition structure..... | 10 |
| A.3.2 IDL specification "TransportNetworkResourcesNRMDefs.idl"..... | 11 |
| Annex B (normative): XML Definitions | 12 |
| B.0 General | 12 |
| B.1 Architectural features | 12 |
| B.1.0 Introduction | 12 |
| B.1.1 Syntax for Distinguished Names | 12 |
| B.2 Mapping | 12 |
| B.2.1 General mapping..... | 12 |
| B.2.2 Information Object Class (IOC) mapping..... | 12 |
| B.3 Solution Set definitions | 12 |
| B.3.1 XML definition structure..... | 12 |
| B.3.2 Graphical Representation | 13 |
| B.3.3 XML Schema "transportNrm.xsd" | 14 |
| Annex A (informative): Change history | 18 |
| History | 19 |

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

- 28.731: Transport Network (TN) interface Network Resource Model (NRM) Integration Reference Point (IRP); Requirements.
- 28.732: Transport Network (TN) interface Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS).
- 28.733: Transport Network (TN) interface Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions.**

1 Scope

The present document is part of an Integration Reference Point (IRP) named Transport Network (TN) interface Network Resource Model (NRM) IRP, through which an `IRPAgent` can communicate configuration management information to one or several `IRPManagers` concerning TN resources. The TN NRM IRP comprises a set of specifications defining Requirements, a protocol neutral Information Service and one or more Solution Set(s).

The present document specifies the Solution Sets for the TN NRM IRP.

This specification is related to 3GPP TS 28.732 [4] V14.0.X.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".
- [4] 3GPP TS 28.732: "Telecommunication management; Transport Network (TN) Interface Network Resource Model (NRM) Integration Reference Point (IRP); Information Service (IS)".
- [5] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [6] OMG Notification Service, Version 1.0.
- [7] OMG CORBA services: Common Object Services Specification, Update: November 22, 1996.
- [8] The Common Object Request Broker: Architecture and Specification (for specification of valid version, see [1]).
- [9] 3GPP TS 32.306: "Telecommunication management; Configuration Management (CM); Notification Integration Reference Point (IRP): Solution Set (SS) definitions".
- [10] 3GPP TS 32.612: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP): Information Service (IS)".
- [11] 3GPP TS 32.616: "Telecommunication management; Configuration Management (CM); Bulk CM Integration Reference Point (IRP): Solution Set (SS) definitions".
- [12] W3C REC-xml11-20060816: "Extensible Markup Language (XML) 1.1 (Second Edition)".
- [13] Void
- [14] W3C XML Schema Definition Language (XSD) 1.1 Part 1: Structures.
- [15] W3C XML Schema Definition Language (XSD) 1.1 Part 2: Datatypes.
- [16] W3C REC-xml-names-20060816: "Namespaces in XML 1.1 (Second Edition)".

- [17] 3GPP TS 28.623: “Generic Network Resource Model (NRM) Integration Reference Point (IRP); Solution Set (SS) definitions”.

3 Definitions and abbreviations

3.1 Definitions

For terms and definitions please refer to 3GPP TS 32.101 [1], TS 32.102 [2], TS 32.600 [3] and TS 32.712 [4] and the following apply.

XML file: See definition of [17].

XML document: See definition of [17].

XML declaration: See definition of [17].

XML element: See definition of [17].

empty XML element: See definition of [17].

XML content (of an XML element): See definition of [17].

XML start-tag: See definition of [17].

XML end-tag: See definition of [17].

XML empty-element tag: See definition of [17].

XML attribute specification: See definition of [17].

DTD: See definition of [17].

XML schema: See definition of [17].

XML namespace: See definition of [17].

XML complex type: See definition of [17].

XML element type: See definition of [17].

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

| | |
|-------|---|
| CM | Configuration Management |
| CORBA | Common Object Request Broker Architecture |
| DN | Distinguished Name |
| DTD | Document Type Definition |
| EDGE | Enhanced Data for GSM Evolution |
| GERAN | GSM/EDGE Radio Access Network |
| GSM | Global System for Mobile communication |
| IS | Information Service |
| IDL | Interface Definition Language (OMG) |
| IOC | Information Object Class |
| IRP | Integration Reference Point |
| MO | Managed Object |
| MOC | Managed Object Class |
| NRM | Network Resource Model |
| OMG | Object Management Group |
| SS | Solution Set |
| TN | Transport Network |

| | |
|-------|--|
| UMTS | Universal Mobile Telecommunications System |
| UTRAN | Universal Terrestrial Radio Access Network |
| XML | eXtensible Markup Language |

4 Solution Set Definitions

This specification defines the following 3GPP TN NRM IRP Solution Set Definitions:

- 3GPP TN NRM IRP CORBA SS (Annex A)
- 3GPP TN NRM IRP XML Definitions (Annex B)

Annex A (normative): CORBA Solution Set

A.0 General

This annex contains the CORBA Solution Set for the IRP whose semantics is specified in TN NRM IRP: Information Service (TS 32.712 [4]).

A.1 Architectural features

A.1.0 Introduction

The overall architectural feature of Transport Network Resources IRP is specified in 3GPP TS 28.712 [4]. This clause specifies features that are specific to the CORBA SS.

A.1.1 Syntax for Distinguished Names

See clause A.1.1 of [17].

A.1.2 Rules for NRM extensions

See clause A.1.2 of [17].

A.2 Mapping

A.2.1 General mapping

See clause A.2.1 of [17].

A.2.2 Information Object Class (IOC) mapping

A.2.2.1 IOC TransportNetworkInterface

Table A.2.2.1: Mapping from NRM IOC TransportNetworkInterface attributes to SS equivalent MOC TransportNetworkInterface attributes

| NRM Attributes of IOC TransportNetworkInterface in 3GPP TS 28.732 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|---|-----------------------------|---------|-------------------|------|-------|
| id | transportNetworkInterfaceId | string | M | M | - |
| userLabel | userLabel | string | M | M | M |
| transportNetworkType | transportNetworkType | string | M | M | - |

A.2.2.2 IOC ATMChannelTerminationPoint

Table A.2.2.2: Mapping from NRM IOC ATMChannelTerminationPoint attributes and associations to SS equivalent MOC ATMTerminationPoint attributes

| NRM Associations/Attributes of IOC ATMChannelTerminationPoint in 3GPP TS 28.732 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|---|---|--|-------------------|------|-------|
| id | aTMChannelTerminationPointId | string | M | M | — |
| usageChannel | usageChannel | string | M | M | — |
| virtualPathId | virtualPathId | long | M | M | O |
| virtualChannelId | virtualChannelId | long | M | M | O |
| physicalPortId | physicalPortId | string | M | M | O |
| physicalInterfaceType | physicalLinkType | string | M | M | O |
| serviceCategoryIn | serviceCategoryIn | long | M | M | O |
| serviceCategoryEg | serviceCategoryEg | long | M | M | O |
| usedAAL | usedAAL | long | M | M | O |
| peakCellRateIn | peakCellRateIn | long | M | M | O |
| peakCellRateEg | peakCellRateEg | long | M | M | O |
| sustainableCellRateIn | sustainableCellRateIn | long | O | M | O |
| sustainableCellRateEg | sustainableCellRateEg | long | O | M | O |
| maximumBurstSizeIn | maximumBurstSizeIn | long | M | M | O |
| maximumBurstSizeEg | maximumBurstSizeEg | long | M | M | O |
| minimumDesiredCellRateIn | minimumDesiredCellRateIn | long | O | M | O |
| minimumDesiredCellRateEg | minimumDesiredCellRateEg | long | O | M | O |
| minimumCellRateIn | minimumCellRateIn | long | O | M | O |
| minimumCellRateEg | minimumCellRateEg | long | O | M | O |
| aTMChannelTerminationPoint-ATMPATHTerminationPoint | aTMChannelTerminationPointATMPATHTerminationPoint | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReference | M | M | - |
| aTMChannelTerminationPoint-lubLink | aTMChannelTerminationPointlubLink | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | M | M | - |

A.2.2.3 IOC ATMPATHTerminationPoint

Table A.2.2.3: Mapping from NRM IOC ATMPATHTerminationPoint attributes and associations to SS equivalent MOC ATMTerminationPoint attributes

| NRM Associations/Attributes of IOC ATMPATHTerminationPoint in 3GPP TS 28.732 [4] | SS Attributes | SS Type | Support Qualifier | Read | Write |
|--|---|--|-------------------|------|-------|
| id | aTMPATHTerminationPointId | string | M | M | — |
| virtualPathId | virtualPathId | long | M | M | O |
| physicalPortIdList | physicalPortIdList | string | M | M | O |
| peakCellRateIn | peakCellRateIn | long | M | M | O |
| peakCellRateEg | peakCellRateEg | long | M | M | O |
| aTMPATHTerminationPoint-ATMChannelTerminationPoint | aTMPATHTerminationPointATMChannelTerminationPoint | GenericNetworkResourcesIRPSystem::AttributeTypes::MOReferenceSet | M | M | - |

A.3 Solution Set definitions

A.3.1 IDL definition structure

Clause A.3.2 defines the MO classes for the TN NRM IRP.

A.3.2 IDL specification

“TransportNetworkResourcesNRMDefs.idl”

```

//File: TransportNetworkResourcesNRMDefs.idl
#ifndef _TRANSPORT_NETWORK_RESOURCES_NRM_DEFS_IDL_
#define _TRANSPORT_NETWORK_RESOURCES_NRM_DEFS_IDL_
#include "GenericNetworkResourcesNRMDefs.idl"
#pragma prefix "3gppsa5.org"
/**
 * This module defines constants for each MO class name and
 * the attribute names for each defined MO class.
 */
module TransportNetworkResourcesNRMDefs
{
    /**
     * Definitions for MO class TransportNetworkInterface
     */
    interface TransportNetworkInterface : GenericNetworkResourcesNRMDefs::ManagedFunction
    {
        const string CLASS = "TransportNetworkInterface";
        // Attribute Names
        //
        const string transportNetworkInterfaceId = "transportNetworkInterfaceId";
        const string transportNetworkType= "transportNetworkType";
    };
    /**
     * Definitions for MO class ATMChannelTerminationPoint
     */
    interface ATMChannelTerminationPoint
    {
        const string CLASS = "ATMChannelTerminationPoint";
        // Attribute Names
        //
        const string atmChannelTerminationPointId = "atmChannelTerminationPointId";
        const string usageChannel= "usageChannel";
        const string virtualPathId= "virtualPathId";
        const string virtualChannelId= "virtualChannelId";
        const string physicalPortId= "physicalPortId";
        const string physicalLinkType= "physicalLinkType";
        const string serviceCategoryIn= "serviceCategoryIn";
        const string serviceCategoryEg= "serviceCategoryEg";
        const string usedAAL= "usedAAL";
        const string peakCellRateIn= "peakCellRateIn";
        const string peakCellRateEg= "peakCellRateEg";
        const string sustainableCellRateIn= "sustainableCellRateIn";
        const string sustainableCellRateEg= "sustainableCellRateEg";
        const string maximumBurstSizeIn= "maximumBurstSizeIn";
        const string maximumBurstSizeEg= "maximumBurstSizeEg";
        const string minimumDesiredCellRateIn= "minimumDesiredCellRateIn";
        const string minimumDesiredCellRateEg= "minimumDesiredCellRateEg";
        const string minimumCellRateIn= "minimumCellRateIn";
        const string minimumCellRateEg= "minimumCellRateEg";
        const string atmChannelTerminationPointATMPATHTerminationPoint =
"atmChannelTerminationPointATMPATHTerminationPoint";
        const string atmChannelTerminationPointIubLink = "atmChannelTerminationPointIubLink";
    };
    /**
     * Definitions for MO class ATMPATHTerminationPoint
     */
    interface ATMPATHTerminationPoint
    {
        const string CLASS = "ATMPATHTerminationPoint";
        // Attribute Names
        //
        const string atMPATHTerminationPointId = "atMPATHTerminationPoint";
        const string virtualPathId= "virtualPathId";
        const string physicalPortIdList= "physicalPortIdList";
        const string peakCellRateIn= "peakCellRateIn";
        const string peakCellRateEg= "peakCellRateEg";
        const string atMPATHTerminationPointATMChannelTerminationPoint =
"atMPATHTerminationPointATMChannelTerminationPoint";
    };
};
#endif // _TRANSPORT_NETWORK_RESOURCES_NRM_DEFS_IDL_

```

Annex B (normative): XML Definitions

B.0 General

This annex contains the XML Definitions for the TN NRM IRP as it applies to Itf-N, in accordance with TN NRM IRP Information Service (TS 32.712 [4]).

The XML file formats are based on XML [12], XML Schema [14] [15] and XML Namespace [16] standards.

B.1 Architectural features

B.1.0 Introduction

The overall architectural feature of Transport Network Resources IRP is specified in 3GPP TS 32.712 [4]. This clause specifies features that are specific to the XML Definitions.

B.1.1 Syntax for Distinguished Names

The syntax of a Distinguished Name is defined in 3GPP TS 32.300 [5].

B.2 Mapping

B.2.1 General mapping

An IOC maps to an XML element of the same name as the IOC's name in the IS. An IOC attribute maps to a sub-element of the corresponding IOC's XML element, and the name of this sub-element is the same as the attribute's name in the IS.

B.2.2 Information Object Class (IOC) mapping

The mapping is not present in the current version of this specification.

B.3 Solution Set definitions

B.3.1 XML definition structure

The overall description of the file format of configuration data XML files is provided by 3GPP TS 32.616 [11].

Annex B.3.3 of the present document defines the NRM-specific XML schema `transportNrm.xsd` for the Transport interface Network Resources IRP NRM defined in 3GPP TS 32.712 [4].

XML schema `transportNrm.xsd` explicitly declares NRM-specific XML element types for the related NRM.

The definition of those NRM-specific XML element types complies with the generic mapping rules defined in 3GPP TS 32.616 [11].

B.3.2 Graphical Representation

The graphical representation is not present in the current version of this specification.

B.3.3 XML Schema "transportNrm.xsd"

```

<?xml version="1.1" encoding="UTF-8"?>

<!--
3GPP TS 28.733 Transport Network Interface NRM IRP
Bulk CM Configuration data file NRM-specific XML schema
transportNrm.xsd
-->

<schema
  targetNamespace="http://www.3gpp.org/ftp/specs/archive/28_series/28.733#transportNrm"
  elementFormDefault="qualified"
  xmlns="http://www.w3.org/2001/XMLSchema"
  xmlns:xn="http://www.3gpp.org/ftp/specs/archive/28_series/28.623#genericNrm"
  xmlns:tn="http://www.3gpp.org/ftp/specs/archive/28_series/28.733#transportNrm"
>

  <import
    namespace=
"http://www.3gpp.org/ftp/specs/archive/28_series/28.623#genericNrm"
  />

<!--Transport Network Interface Resources IRP NRM attribute related XML types -->

<simpleType name="transportNetworkType">
  <restriction base="string">
    <enumeration value="ATM"/>
    <enumeration value="IP"/>
  </restriction>
</simpleType>

<simpleType name="serviceCategoryIn">
  <restriction base="string">
    <enumeration value="CBR"/>
    <enumeration value="RT-VBR"/>
    <enumeration value="NRT-VBR"/>
    <enumeration value="ABR"/>
    <enumeration value="UBR"/>
    <enumeration value="GFR"/>
  </restriction>
</simpleType>

<simpleType name="serviceCategoryEg">
  <restriction base="string">
    <enumeration value="CBR"/>
    <enumeration value="RT-VBR"/>
    <enumeration value="NRT-VBR"/>
    <enumeration value="ABR"/>
    <enumeration value="UBR"/>
    <enumeration value="GFR"/>
  </restriction>
</simpleType>

<simpleType name="usedAAL">
  <restriction base="string">
    <enumeration value="Null"/>
    <enumeration value="AAL1"/>
    <enumeration value="AAL2"/>
    <enumeration value="AAL3"/>
    <enumeration value="AAL4"/>
    <enumeration value="AAL5"/>
  </restriction>
</simpleType>

<simpleType name="virtualPathId">
  <restriction base="integer">
    <minInclusive value="0"/>
  </restriction>
</simpleType>

<simpleType name="virtualChannelId">
  <restriction base="integer">
    <minInclusive value="0"/>
  </restriction>
</simpleType>

```

```

<complexType name="physicalPortIdList">
  <sequence>
    <element name="physicalPortId" type="string" minOccurs="1" maxOccurs="unbounded">
    </element>
  </sequence>
</complexType>

<simpleType name="peakCellRateIn">
  <restriction base="integer">
    <minInclusive value="1"/>
  </restriction>
</simpleType>

<simpleType name="peakCellRateEg">
  <restriction base="integer">
    <minInclusive value="1"/>
  </restriction>
</simpleType>

<simpleType name="sustainableCellRateIn">
  <restriction base="integer">
    <minInclusive value="1"/>
  </restriction>
</simpleType>

<simpleType name="sustainableCellRateEg">
  <restriction base="integer">
    <minInclusive value="1"/>
  </restriction>
</simpleType>

<simpleType name="maximumBurstSizeIn">
  <restriction base="integer">
    <minInclusive value="1"/>
  </restriction>
</simpleType>

<simpleType name="maximumBurstSizeEg">
  <restriction base="integer">
    <minInclusive value="1"/>
  </restriction>
</simpleType>

<simpleType name="minimumCellRateIn">
  <restriction base="integer">
    <minInclusive value="1"/>
  </restriction>
</simpleType>

<simpleType name="minimumCellRateEg">
  <restriction base="integer">
    <minInclusive value="1"/>
  </restriction>
</simpleType>

<simpleType name="minimumDesiredCellRateIn">
  <restriction base="integer">
    <minInclusive value="1"/>
  </restriction>
</simpleType>

<simpleType name="minimumDesiredCellRateEg">
  <restriction base="integer">
    <minInclusive value="1"/>
  </restriction>
</simpleType>

<!-- Transport Network Interface Resources IRP NRM class associated XML elements -->

<element
  name="TransportNetworkInterface"
  substitutionGroup="xn:ManagedElementOptionallyContainedNrmClass"
>
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">

```



```

    <complexType>
      <all>
        <element name="userLabel" type="string"/>
        <element name="vnfParametersList" type="xn:vnfParametersListType" minOccurs="0"/>
        <element
          name="transportNetworkType"
          type="tn:transportNetworkType"
        />
      </all>
    </complexType>
  </element>
  <choice minOccurs="0" maxOccurs="unbounded">
    <element ref="tn:ATMPATHTerminationPoint"/>
    <element ref="tn:ATMChannelTerminationPoint"/>
    <element ref="xn:VsDataContainer"/>
  </choice>
</sequence>
</extension>
</complexType>
</element>
<element name="ATMChannelTerminationPoint">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element name="usageChannel" type="string"/>
                <element
                  name="virtualPathId"
                  type="tn:virtualPathId"
                />
                <element
                  name="virtualChannelId"
                  type="tn:virtualChannelId"
                />
                <element
                  name="physicalPortId"
                  type="string"
                />
                <element name="physicalInterfaceType" type="string" minOccurs="0"/>
                <element
                  name="serviceCategoryIn"
                  type="tn:serviceCategoryIn"
                />
                <element
                  name="serviceCategoryEg"
                  type="tn:serviceCategoryEg"
                />
                <element
                  name="usedAAL"
                  type="tn:usedAAL"
                />
                <element
                  name="peakCellRateIn"
                  type="tn:peakCellRateIn"
                />
                <element
                  name="peakCellRateEg"
                  type="tn:peakCellRateEg"
                />
                <element
                  name="sustainableCellRateIn"
                  type="tn:sustainableCellRateIn"
                  minOccurs="0"
                />
                <element
                  name="sustainableCellRateEg"
                  type="tn:sustainableCellRateEg"
                  minOccurs="0"
                />
                <element
                  name="maximumBurstSizeIn"
                  type="tn:maximumBurstSizeIn"
                />
              </all>
            </complexType>
          </element>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>

```

```

    <element
      name="maximumBurstSizeEg"
      type="tn:maximumBurstSizeEg"
    />
    <element
      name="minimumDesiredCellRateIn"
      type="tn:minimumDesiredCellRateIn"
      minOccurs="0"
    />
    <element
      name="minimumDesiredCellRateEg"
      type="tn:minimumDesiredCellRateEg"
      minOccurs="0"
    />
    <element
      name="minimumCellRateIn"
      type="tn:minimumCellRateIn"
      minOccurs="0"
    />
    <element
      name="minimumCellRateEg"
      type="tn:minimumCellRateEg"
      minOccurs="0"
    />
    <element name="aTMChannelTerminationPointATMPATHTerminationPoint" type="xn:dn"/>
    <element name="aTMChannelTerminationPointIubLink" type="xn:dnList"/>
  </all>
</complexType>
</element>
<choice>
  <element ref="xn:VsDataContainer" minOccurs="0" maxOccurs="unbounded"/>
</choice>
</sequence>
</extension>
</complexContent>
</complexType>
</element>

<element name="ATMPATHTerminationPoint">
  <complexType>
    <complexContent>
      <extension base="xn:NrmClass">
        <sequence>
          <element name="attributes" minOccurs="0">
            <complexType>
              <all>
                <element
                  name="virtualPathId"
                  type="tn:virtualPathId"
                />
                <element
                  name="physicalPortIdList"
                  type="tn:physicalPortIdList"
                />
                <element
                  name="peakCellRateIn"
                  type="tn:peakCellRateIn"
                />
                <element
                  name="peakCellRateEg"
                  type="tn:peakCellRateEg"
                />
                <element name="aTMPathTerminationPointATMChannelTerminationPoint"
type="xn:dnList"/>
              </all>
            </complexType>
          </element>
          <choice minOccurs="0" maxOccurs="unbounded">
            <element ref="xn:VsDataContainer"/>
          </choice>
        </sequence>
      </extension>
    </complexContent>
  </complexType>
</element>
</schema>

```

Annex A (informative): Change history

| Change history | | | | | | | |
|----------------|---------|-----------|------|-----|-----|---|---------------|
| Date | Meeting | TDoc | CR | Rev | Cat | Subject/Comment | New version |
| 2014-06 | SA#64 | SP-140358 | 001 | - | F | Upgrade W3C XML Schema version from 1.0 to 1.1 | 11.1.0 |
| | | SP-140332 | 002 | - | F | remove the feature support statements | 11.1.0 |
| 2014-09 | SA#65 | SP-140560 | 003 | - | C | Update the link from Solution Set to Information Service due to the end of Release 12 | 12.0.0 |
| 2016-01 | | | | | | Update to Rel-13 (MCC) | 13.0.0 |
| 2016-03 | SA#71 | SP-160031 | 006 | - | A | Make the XML schema well formed | 13.1.0 |
| 2016-06 | SA#72 | SP-160407 | 0007 | - | F | Update the link from IRP Solution Set to IRP Information Service | 13.2.0 |
| 2017-03 | SA#75 | - | - | - | - | Promotion to Release 14 without technical change | 14.0.0 |
| 2017-06 | SA#76 | SP-170514 | 0008 | - | F | Update the link from IRP Solution Set to IRP Information Service | 14.1.0 |
| 2017-06 | SA#76 | SP-170510 | 0009 | 1 | B | Update the XML Schema definitions to align with IS to support Configuration Management for mobile networks that include virtualized network functions | 14.1.0 |
| 2018-06 | - | - | - | - | - | Update to Rel-15 version (MCC) | 15.0.0 |
| 2020-07 | - | - | - | - | - | Update to Rel-16 version (MCC) | 16.0.0 |
| 2022-03 | - | - | - | - | - | Update to Rel-17 version (MCC) | 17.0.0 |
| 2024-04 | - | - | - | - | - | Update to Rel-18 version (MCC) | 18.0.0 |

History

| Document history | | |
|-------------------------|----------|-------------|
| V18.0.0 | May 2024 | Publication |
| | | |
| | | |
| | | |
| | | |