
ETSITS 129 199-10 V6.3.0 (2006-06)

Technical Specification

Universal Mobile Telecommunications System (UMTS);
Open Service Access (OSA);
Parlay X web services;
Part 10: Call handling
(3GPP TS 29.199-10 version 6.3.0 Release 6)



Reference RTS/TSGC-0529199-10v630 Keywords UMTS

ETSI

650 Route des Lucioles F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C Association à but non lucratif enregistrée à la Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from: <u>http://www.etsi.org</u>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

http://portal.etsi.org/tb/status/status.asp

Copyright Notification

No part may be reproduced except as authorized by written permission. The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2006. All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members. **TIPHON**TM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members. **3GPP**TM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (http://webapp.etsi.org/IPR/home.asp).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under http://webapp.etsi.org/key/queryform.asp.

Contents

Intelle	ectual Property Rights	2
Forew	vord	2
Forew	vord	4
Introd	luction	4
1	Scope	5
_	References	
2		
3	Definitions and abbreviations	
3.1 3.2	Definitions	
_		
4	Detailed service description	6
5	Namespaces	6
6	Sequence diagrams	7
6.1	Setup call handling, query and clear rules	7
7	XML Schema data type definition	8
7.1	ConditionalForward structure	
7.2	UnconditionalForward structure	
7.3	InteractionContent enumeration	8
7.4	TextInteraction structure	8
7.5	VoiceInteraction union	
7.6	CallHandlingRules structure	9
7.7	SetRulesResult structure	9
8	Web Service interface definition.	9
8.1	Interface: CallHandling	
8.1.1	Operation: SetRules	
8.1.1.1	•	
8.1.1.2		
8.1.1.3		
8.1.2	Operation: SetRulesForGroup	
8.1.2.1	1	
8.1.2.2		
8.1.2.3	• • •	
8.1.3	Operation: GetRules	10
8.1.3.1	Input message: GetRulesRequest	10
8.1.3.2	2 Output message: GetRulesResponse	11
8.1.3.3	Referenced faults	11
8.1.4	Operation: ClearRules	
8.1.4.1	I Input message: ClearRulesRequest	11
8.1.4.2		
8.1.4.3	Referenced faults	11
9	Fault definitions	11
10	Service policies	12
Anne	ex A (normative): WSDL for Call handling	13
Anne	x B (informative): Change history	14
Uictor	pry	15

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

3GPP acknowledges the contribution of the Parlay X Web Services specifications from The Parlay Group. The Parlay Group is pleased to see 3GPP acknowledge and publish the present document, and the Parlay Group looks forward to working with the 3GPP community to improve future versions of the present document.

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part 10 of a multi-part deliverable covering the 3rd Generation Partnership Project; Technical Specification Group Core Network; Open Service Access (OSA); Parlay X Web Services, as identified below:

```
Part 1:
                 "Overview and common data definitions";
Part 2:
                 "Third party call";
Part 3:
                 "Call Notification";
Part 4:
                 "Short Messaging";
Part 5:
                 "Multimedia Messaging";
Part 6:
                 "Payment";
Part 7:
                 "Account management";
                 "Terminal Status";
Part 8:
Part 9:
                 "Terminal location";
Part 10:
                 "Call handling":
Part 11:
                 "Audio call":
Part 12:
                 "Multimedia conference";
                 "Address list management";
Part 13:
Part 14:
                 "Presence".
```

1 Scope

The present document is Part 10 of the Stage 3 Parlay X Web Services specification for Open Service Access (OSA).

The OSA specifications define an architecture that enables application developers to make use of network functionality through an open standardized interface, i.e. the OSA APIs. The concepts and the functional architecture for the OSA are contained in 3GPP TS 23.198 [3]. The requirements for OSA are contained in 3GPP TS 22.127 [2].

The present document specifies the Call Handling Web Service aspects of the interface. All aspects of the Call Handling Web Service are defined here, these being:

- Name spaces.
- Sequence diagrams.
- Data definitions.
- Interface specification plus detailed method descriptions.
- Fault definitions.
- Service policies.
- WSDL Description of the interfaces.

The present document has been defined jointly between 3GPP TSG CT WG5, ETSI TISPAN and The Parlay Group.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 22.127: "Service Requirement for the Open Services Access (OSA); Stage 1".
- [3] 3GPP TS 23.198: "Open Service Access (OSA); Stage 2".
- [4] 3GPP TS 22.101: "Service aspects; Service principles".
- [5] W3C Recommendation (2 May 2001): "XML Schema Part 2: Datatypes".

NOTE: Available at http://www.w3.org/TR/2001/REC-xmlschema-2-20010502/.

[6] 3GPP TS 29.199-1: "Open Service Access (OSA); Parlay X Web Services; Part 1: Common".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 29.199-1 [6] apply.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TS 29.199-1 [6] apply.

4 Detailed service description

The Call Handling Web Service provides a mechanism for an application to specify how calls are to be handled for a specific number. Call handling includes commonly utilized actions:

- Call accepting only accepting calls from a list of numbers.
- Call blocking blocking calls if they are on a blocking list.
- Conditional call forwarding changing the destination of a call to another number for a specific calling number.
- Unconditional call forwarding changing the destination of a call to another number.
- Play audio initiate audio with the caller (e.g. an announcement or menu).

The set of rules are provided to the Web Service which is responsible for establishing the call handling function. Only one action is taken for a call, and once this action is started the rules will stop being processed.

There is a specific order in which these rules are processed, providing a predictable call handling expectation for rules provided. The processing is done as follows.

- 1) Call accepting determines if the call is accepted or rejected. If the caller is not on the accept list, the call is rejected and rule processing ends.
- 2) Call blocking determines if the call is rejected. If the caller is on the block list, the call is rejected and rule processing ends.
- 3) Conditional call forwarding each calling number that has a specific forwarding instruction is checked, and the call is forwarded on a match, and rule processing ends.
- 4) Unconditional call forwarding the called number is changed to the call forwarding number and rule processing ends.
- 5) Play audio the call is handled by a voice system, which handles all further processing of the call. Rule processing ends when the call is handled off.
- 6) Continue processing call, to complete call to the original called number.

If no rules are specified in a particular area, then that step is skipped. If the rule processing ends without any action being indicated, then the call will continue to the called number.

Call Handling provides its function without further interaction with the Application. This is in contrast to the Call Notification interfaces which provide notifications to the Application for processing.

5 Namespaces

The Call Handling interface uses the namespace:

http://www.csapi.org/wsdl/parlayx/call_handling/v2_3

The data types are defined in the namespace:

http://www.csapi.org/schema/parlayx/call_handling/v2_3


The 'xsd' namespace is used in the present document to refer to the XML Schema data types defined in XML Schema [5]. The use of the name 'xsd' is not semantically significant.

6 Sequence diagrams

6.1 Setup call handling, query and clear rules

Pattern: Request / Response.

This sequence shows the application setting up Call Handling with rules to be processed., querying those rules and clearing them.



7 XML Schema data type definition

7.1 ConditionalForward structure

Information on handling of forwarding for specific calling numbers.

Element name	Element type	Optional	Description
CallingAddress	xsd:anyURI	No	Address that call is placed from
ForwardingAddress	xsd:anyURI	No	Address to forward call to
OnBusyAddress	xsd:anyURI	No	If line is busy at forwarding address, forward to this address
OnNoAnswerAddress	xsd:anyURI	No	If no answer at forwarding address, forward to this address

7.2 UnconditionalForward structure

Information for handling of forwarding unconditionally.

Element name	t name Element type Optional		Description
ForwardingAddress	xsd:anyURI	No	Address to forward call to
OnBusyAddress xsd:anyURI No I		No	If line is busy at forwarding address, forward to this address
OnNoAnswerAddress	xsd:anyURI	No	If no answer at forwarding address, forward to this address

7.3 InteractionContent enumeration

The following are the types of content that may be used for user interaction.

Enumeration	Description		
TextInfo	Text to be processed by a Text-To-Speech engine		
VoiceXml	VoiceXML to be processed by a VoiceXML browser		
Audio	Audio file to be played by an audio processor		

7.4 TextInteraction structure

Information for processing by a text to speech engine.

Element name	Element type	Optional	Description
Text	xsd:string	No	Text to play through a Text-To-Speech engine
Language	xsd:string	No	Language of text

7.5 VoiceInteraction union

For a call that is to be handled by an interactive voice system, the information to provide to that system.

Element name	Element type	Optional	Description
UnionElement	InteractionContent	No	Type of content provided (one of the following)
TextInfo	TextInteraction	Yes	Announcement to play through a Text-To-Speech engine
VoiceXml	xsd:anyURI	Yes	Location of VoiceXML to use in a VoiceXML browser
Audio	xsd:anyURI	Yes	Location of audio content (WAV or MP3 file)

7.6 CallHandlingRules structure

Structure containing set of rules that are applied when the call is handled.

Element name	Element type	Optional	Description
AcceptList	xsd:anyURI [0unbounded]	Yes	List of addresses to accept calls from
BlockList	xsd:anyURI [0unbounded]	Yes	List of addresses to block calls from
ForwardList	ConditionalForward	Yes	List of conditional forwarding addresses and
	[0unbounded]		destinations
Forward	UnconditionalForward	Yes	Unconditional call forwarding address
VoiceInteractionContent	VoiceInteraction	Yes	Forward call to a user interaction system with
			information on content

7.7 SetRulesResult structure

Result of SetRulesRequest for each address.

Element name	Element type	Optional	Description
Address	xsd:anyURI	No	Address to be set
Successful	xsd:boolean	No	Successfully set rules or not
Error	common:ServiceError	Yes	Error message if unsuccessful

8 Web Service interface definition

8.1 Interface: CallHandling

CallHandling provides a rule based processing capability that is accessible to Applications through a set of operations that allow definition of discrete rules.

8.1.1 Operation: SetRules

Set the call handling rules for an address (the destination for the call). If a set of rules is already in place for any of the **Address**, then this operation will replace the old rules with the set provided in this operation.

The Address may not specify a group. If a group is specified, a PolicyException will be returned.

8.1.1.1 Input message: SetRulesRequest

Part name	Part type	Optional	Description
Address	xsd:anyURI	No	Address to handle calls for
Rules	CallHandlingRules	No	Rules to apply for this address

8.1.1.2 Output message: SetRulesResponse

Part name	Part type	Optional	Description
None			

8.1.1.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

• SVC0001: Service error.

• SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

• POL0001: Policy error.

• POL0006: Groups not allowed.

8.1.2 Operation: SetRulesForGroup

Set the call handling rules for multiple addresses (the destination for calls). If a set of rules is already in place for any of the **Addresses**, then this operation will replace the old rules with the set provided in this operation.

The **Addresses** may include groups, with members using the 'tel:' and 'sip:' URIs in the manner defined in 3GPP TS 29.119-1 [6]. Wildcards may not be used to specify addresses.

8.1.2.1 Input message: SetRulesForGroupRequest

Part name	Part type	Optional	Description
Addresses	xsd:anyURI [1unbounded]	No	Addresses to handle calls for
Rules	CallHandlingRules	No	Rules to apply for these addresses

8.1.2.2 Output message: SetRulesForGroupResponse

Part name	Part type	Optional	Description
Result	SetRulesResult [1unbounded]	No	Result of setup for each of addresses provided

8.1.2.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

• SVC0001: Service error.

• SVC0002: Invalid input value.

• SVC0004: No valid addresses.

• SVC0006: Invalid group.

PolicyException from 3GPP TS 29.199-1 [6]:

• POL0001: Policy error.

• POL0006: Groups not allowed.

• POL0007: Nested groups not allowed.

8.1.3 Operation: GetRules

Get the call handling rules for an address (the destination for the call).

The Address may not specify a group. If a group is specified, a PolicyException will be returned.

8.1.3.1 Input message: GetRulesRequest

Part name	Part type	Optional	Description		
Address	xsd:anyURI	No	Address to handle calls for		

8.1.3.2 Output message: GetRulesResponse

Part name	Part type	Optional	Description
Rules	CallHandlingRules	No	Rules being applied for this address

8.1.3.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

• SVC0001: Service error.

• SVC0002: Invalid input value.

PolicyException from 3GPP TS 29.199-1 [6]:

• POL0001: Policy error.

• POL0006: Groups not allowed.

8.1.4 Operation: ClearRules

Clear the call handling rules associated with the addresses specified. If no rules have been set for an address, this operation silently ignores the request, and does not return an error or fault message.

The **Addresses** may include groups, with members using the 'tel:' and 'sip:' URIs in the manner defined in 3GPP TS 29.199-1 [6]. Wildcards may not be used to specify addresses.

8.1.4.1 Input message: ClearRulesRequest

Part name	Part type	Optional	Description
Addresses	xsd:anyURI [1unbounded]	No	Addresses to clear call handling for

8.1.4.2 Output message: ClearRulesResponse

Part name	Part type	Optional	Description
None			

8.1.4.3 Referenced faults

ServiceException from 3GPP TS 29.199-1 [6]:

• SVC0001: Service error.

• SVC0002: Invalid input value.

• SVC0006: Invalid group.

PolicyException from 3GPP TS 29.199-1 [6]:

• POL0001: Policy error.

POL0006: Groups not allowed.

• POL0007: Nested groups not allowed.

9 Fault definitions

No new faults defined for this service.

10 Service policies

Name	Туре	Description
VoiceMailAvailable	xsd:boolean	Voice mail available or not
TextToSpeechAvailable	xsd:boolean	Service accepts text as an input for processing with a Text-To-Speech engine
AudioContentAvailable	xsd:boolean	Service accepts audio content for playing with an audio player
VoiceXmlAvailable	xsd:boolean	Service accepts VoiceXML for processing with a VoiceXML browser
AudioFormatsSupported	xsd:string	Comma separated string of audio formats supported (e.g. WAV,MP3,AU)
GroupSupport	xsd:boolean	Groups may be included with addresses
NestedGroupSupport	xsd:boolean	Are nested groups supported in group definitions

Annex A (normative): WSDL for Call handling

The document/literal WSDL representation of this interface specification is compliant to 3GPP TS 29.199-1 [6] and is contained in text files (contained in archive 29199-10-630-doclit.zip) which accompanies the present document.

Annex B (informative): Change history

	Change history							
Date	TSG#	TSG Doc.	CR	Rev	Subject/Comment	Cat	Old	New
Sep 2004	CN_25	NP-040360		-	Draft v100 submitted to TSG CN#25 for Approval.		1.0.0	6.0.0
Jun 2005	CT_28	CP-050221	0001		Optionals for Part 10	F	6.0.0	6.1.0
Dec 2005	CT_30	CP-050575	0002		Make elements of the VoiceInteraction & CallHandlingRules structure	F	6.1.0	6.2.0
					optional			
Dec 2005	CT_30	CP-050575	0003	1	Inconsistent part naming in PX response messages	F	6.1.0	6.2.0
Jun 2006	CT_32	CP-060202	0004		Change reference to OSA Stage 2 from 23.127 to 23.198	F	6.2.0	6.3.0
Jun 2006	CT_32	CP-060202	0005		Apply Union data type element naming convention	F	6.2.0	6.3.0

History

	Document history				
V6.0.0	January 2005	Publication			
V6.1.0	June 2005	Publication			
V6.2.0	December 2005	Publication			
V6.3.0	June 2006	Publication			