

ETSI TS 129 329 V5.1.0 (2002-09)

Technical Specification

**Digital cellular telecommunications system (Phase 2+);
Universal Mobile Telecommunications System (UMTS);
Sh interface based on the Diameter protocol
(3GPP TS 29.329 version 5.1.0 Release 5)**



ReferenceRTS/TSGN-0429329v510

KeywordsGSM, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, send your comment to:

editor@etsi.fr

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2002.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under www.etsi.org/key.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	4
1 Scope	5
2 References	5
3 Definitions, symbols and abbreviations	5
3.1 Definitions	5
3.2 Abbreviations	6
4 General	6
5 Use of the Diameter base protocol	6
6 Diameter application for Sh interface	6
6.1 Command-Code values	6
6.1.1 User-Data-Request (UDR) Command	7
6.1.2 User-Data-Answer (UDA) Command	7
6.1.3 Profile-Update-Request (PUR) Command.....	8
6.1.4 Profile-Update-Answer (PUA) Command.....	8
6.1.5 Subscribe-Notifications-Request (SNR) Command	8
6.1.6 Subscribe-Notifications-Answer (SNA) Command.....	9
6.1.7 Push-Notification-Request (PNR) Command.....	9
6.1.8 Push-Notifications-Answer (PNA) Command.....	9
6.2 Result-Code AVP values.....	10
6.2.1 Success.....	10
6.2.2 Permanent Failures	10
6.2.2.DIAMETER_USER_DATA_NOT_RECOGNIZED (5100).....	10
DIAMETER_OPERATION_NOT_ALLOWED (5101)	10
DIAMETER_USER_DATA_CANNOT_BE_READ (5102).....	10
DIAMETER_USER_DATA_CANNOT_BE_MODIFIED (5103)	10
DIAMETER_USER_DATA_CANNOT_BE_NOTIFIED (5104).....	10
6.2.3 Transient Failures	10
6.3 AVPs	11
6.3.1 User-Identity AVP	11
6.3.2 MSISDN AVP	11
6.3.3 User-Data AVP.....	11
6.3.4 Data-Reference AVP	12
6.3.5 Service-Indication AVP	12
6.3.6 Subs-Req-Type AVP	12
6.3.7 Requested-Domain AVP.....	12
6.3.8 Current-Location AVP.....	12
6.4 Use of namespaces	13
6.4.1 AVP codes	13
6.4.2 Vendor-Specific-Result-Code AVP values.....	13
7 Special Requirements	13
7.1 Version Control	13
Annex A (informative): Change history	14
History	15

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document defines a transport protocol for use in the IP multimedia (IM) Core Network (CN) subsystem based on Diameter.

The present document is applicable to:

- The Sh interface between an AS and the HSS.
- The Sh interface between an SCS and the HSS.

Whenever it is possible this document specifies the requirements for this protocol by reference to specifications produced by the IETF within the scope of Diameter. Where this is not possible, extensions to Diameter are defined within this document.

2 References

The following documents contain provisions, which through reference in this text constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 29.328 “IP Multimedia (IM) Subsystem Sh interface; signalling flows and message contents (Release 5)”
- [2] 3GPP TS 33.210 “3G Security; Network Domain Security; IP Network Layer Security (Release 5)”
- [3] IETF RFC 2960 “Stream Control Transmission Protocol”
- [4] draft-ietf-aaa-diameter-10.txt, “Diameter Base Protocol”, work in progress
- [5] IETF RFC 2234 “Augmented BNF for syntax specifications”
- [6] 3GPP TS 29.229 “Cx and Dx Interfaces based on the Diameter protocol; protocol details (Release 5)”

3 Definitions, symbols and abbreviations

3.1 Definitions

Refer to [4] for the definitions of some terms used in this document.

For the purposes of the present document, the following terms and definitions apply.

Attribute-Value Pair: see [4], it corresponds to an Information Element in a Diameter message.

Server: SIP-server.

User data: user profile data.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

AAA	Authentication, Authorization and Accounting
AS	Application Server
ABNF	Augmented Backus-Naur Form
AVP	Attribute-Value Pair
CN	Core Network
HSS	Home Subscriber Server
IANA	Internet Assigned Numbers Authority
IETF	Internet Engineering Task Force
IMS	IP Multimedia Subsystem
NDS	Network Domain Security
RFC	Request For Comment
SCTP	Stream Control Transport Protocol
UCS	Universal Character Set
URL	Uniform Resource Locator
UTF	UCS Transformation Formats

4 General

The Diameter Base Protocol as specified in [4] shall apply except as modified by the defined support of the methods and the defined support of the commands and AVPs, result and event codes specified in clause 5 of this specification. Unless otherwise specified, the procedures (including error handling and unrecognised information handling) are unmodified.

5 Use of the Diameter base protocol

The same clarifications of section 5 of 3GPP TS 29.229 [6] shall apply to the Sh interface. An exception is that the application identifier for this application is defined in chapter 6.

6 Diameter application for Sh interface

This clause specifies a Diameter application that allows a Diameter server and a Diameter client:

- to download and update transparent and non-transparent user data
- to request and send notifications on changes on user data

The Sh interface protocol is defined as an IETF vendor specific Diameter application, where the vendor is 3GPP. The vendor identifier assigned by IANA to 3GPP (<http://www.iana.org/assignments/enterprise-numbers>) is 10415.

The Diameter application identifier assigned to the Sh interface protocol is number 2.

6.1 Command-Code values

This section defines Command-Code values for this Diameter application.

Every command is defined by means of the ABNF syntax [5], according to the rules in [4]. Whenever the definition and use of an AVP is not specified in this document, what is stated in [4] or [6] shall apply.

The following Command Codes are defined in this specification:

Table 6.1.1: Command-Code values

Command-Name	Abbreviation	Code	Section
User-Data-Request	UDR	1	6.1.1
User-Data-Answer	UDA	1	6.1.2
Profile-Update-Request	PUR	2	6.1.3
Profile-Update-Answer	PUA	2	6.1.4
Subscribe-Notifications-Request	SNR	3	6.1.5
Subscribe-Notifications-Answer	SNA	3	6.1.6
Push-Notification-Request	PNR	4	6.1.7
Push-Notification-Answer	PNA	4	6.1.8

6.1.1 User-Data-Request (UDR) Command

The User-Data-Request (UDR) command, indicated by the Command-Code field set to 1 and the 'R' bit set in the Command Flags field, is sent by a Diameter client to a Diameter server in order to request user data.

Message Format

```

< User-Data -Request > ::= < Diameter Header: 10415: 1, REQ, PXY >
    < Session-Id >
    { Vendor-Specific-Application-Id }
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    [ Destination-Host ]
    { Destination-Realm }
    { User-Identity }
    [ Service-Indication ]
    1*[ Data-Reference ]
    *[ Requested-Domain ]
    [ Current-Location ]
    *[ AVP ]
    *[ Proxy-Info ]
    *[ Route-Record ]

```

6.1.2 User-Data-Answer (UDA) Command

The User-Data-Answer (SAA) command, indicated by the Command-Code field set to 1 and the 'R' bit cleared in the Command Flags field, is sent by a server in response to the User-Data-Request command. The Result-Code or Vendor-Specific-Result AVP may contain one of the values defined in section 6.2 in addition to the values defined in [6].

Message Format

```

< User-Data-Answer > ::= < Diameter Header: 10415: 1 >
    < Session-Id >
    { Vendor-Specific-Application-Id }
    [ Result-Code ]
    [ Vendor-Specific-Result ]
    { Auth-Session-State }
    { Origin-Host }
    { Origin-Realm }
    [ User-Data ]

```



```
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]
```

6.1.3 Profile-Update-Request (PUR) Command

The Profile-Update-Request (PUR) command, indicated by the Command-Code field set to 2 and the 'R' bit set in the Command Flags field, is sent by a Diameter client to a Diameter server in order to update user data in the server.

Message Format

```
< Profile-Update-Request > ::= < Diameter Header: 10415: 2, REQ, PXY >
< Session-Id >
{ Vendor-Specific-Application-Id }
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
{ Destination-Host }
{ Destination-Realm }
{ Public-Identity }
{ User-Data }
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]
```

6.1.4 Profile-Update-Answer (PUA) Command

The Profile-Update-Answer (PUA) command, indicated by the Command-Code field set to 2 and the 'R' bit cleared in the Command Flags field, is sent by a client in response to the Profile-Update-Request command. The Result-Code or Vendor-Specific-Result AVP may contain one of the values defined in section 6.2 in addition to the values defined in [6].

Message Format

```
< Profile-Update-Answer > ::= < Diameter Header: 10415: 2 >
< Session-Id >
{ Vendor-Specific-Application-Id }
[ Result-Code ]
[ Vendor-Specific-Result ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]
```

6.1.5 Subscribe-Notifications-Request (SNR) Command

The Subscribe-Notifications-Request (SNR) command, indicated by the Command-Code field set to 3 and the 'R' bit set in the Command Flags field, is sent by a Diameter client to a Diameter server in order to request notifications of changes in user data.

Message Format

```
< Subscribe-Notifications-Request > ::= < Diameter Header: 10415: 3, REQ, PXY >
< Session-Id >
{ Vendor-Specific-Application-Id }
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
[ Destination-Host ]
{ Destination-Realm }
{ Public-Identity }
```

```

[ Service-Indication ]
{ Subs-Req-Type }
1*[ Data-Reference ]
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.1.6 Subscribe-Notifications-Answer (SNA) Command

The Subscribe-Notifications-Answer command, indicated by the Command-Code field set to 2 and the 'R' bit cleared in the Command Flags field, is sent by a client in response to the Subscribe-Notifications-Request command. The Result-Code or Vendor-Specific-Result AVP may contain one of the values defined in section 6.2 in addition to the values defined in [6].

Message Format

```

< Subscribe-Notifications-Answer > ::=          < Diameter Header: 10415: 3 >
< Session-Id >
{ Vendor-Specific-Application-Id }
{ Auth-Session-State }
[ Result-Code ]
[ Vendor-Specific-Result ]
{ Origin-Host }
{ Origin-Realm }
*[ Data-Reference ]
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.1.7 Push-Notification-Request (PNR) Command

The Push-Notification-Request (PNR) command, indicated by the Command-Code field set to 1 and the 'R' bit set in the Command Flags field, is sent by a Diameter server to a Diameter client in order to notify changes in the user data in the server.

Message Format

```

< Push-Notification-Request > ::=          < Diameter Header: 10415: 4, REQ, PXY >
< Session-Id >
{ Vendor-Specific-Application-Id }
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
{ Destination-Host }
{ Destination-Realm }
{ Public-Identity }
{ User-Data }
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.1.8 Push-Notifications-Answer (PNA) Command

The Push-Notifications-Answer (PNA) command, indicated by the Command-Code field set to 2 and the 'R' bit cleared in the Command Flags field, is sent by a client in response to the Push-Notification-Request command. The Result-Code or Vendor-Specific-Result AVP may contain one of the values defined in section 6.2 in addition to the values defined in [6].

Message Format

```

< Push-Notification-Answer > ::=          < Diameter Header: 10415: 4 >
< Session-Id >

```

```

{ Vendor-Specific-Application-Id }
[ Result-Code ]
[ Vendor-Specific-Result ]
{ Auth-Session-State }
{ Origin-Host }
{ Origin-Realm }
*[ AVP ]
*[ Proxy-Info ]
*[ Route-Record ]

```

6.2 Result-Code AVP values

This section defines new result code values that must be supported by all Diameter implementations that conform to this specification. The result codes defined in 3GPP TS 29.229 are also applicable. When one of the result codes defined here is included in a response, it shall be inside a Vendor-Specific-Result AVP and Result-Code AVP shall be absent.

6.2.1 Success

Errors that fall within the Success category are used to inform a peer that a request has been successfully completed.

No errors within this category have been defined so far.

6.2.2 Permanent Failures

Errors that fall within the Permanent Failures category are used to inform the peer that the request failed, and should not be attempted again.

6.2.2.1 DIAMETER_USER_DATA_NOT_RECOGNIZED (5100)

The data required, in the XLM schema, does not match that which is specified within the HSS.

DIAMETER_OPERATION_NOT_ALLOWED (5101)

The requested operation is not allowed for the user

DIAMETER_USER_DATA_CANNOT_BE_READ (5102)

The requested user data is not allowed to be read.

DIAMETER_USER_DATA_CANNOT_BE_MODIFIED (5103)

The requested user data is not allowed to be modified

DIAMETER_USER_DATA_CANNOT_BE_NOTIFIED (5104)

The requested user data is not allowed to be notified on changes

6.2.3 Transient Failures

Errors that fall within the transient failures category are those used to inform a peer that the request could not be satisfied at the time that it was received. The request may be able to be satisfied in the future.

6.2.3.1 DIAMETER_USER_DATA_NOT_AVAILABLE (4100) The requested user data is not available at this time to satisfy the requested operation.

6.3 AVPs

The following table describes the Diameter AVPs defined for the Sh interface protocol, their AVP Code values, types, possible flag values and whether the AVP may or not be encrypted.

Table 6.3.1: Diameter Multimedia Application AVPs

Attribute Name	AVP Code	Section defined	Value Type	AVP Flag rules				
				Must	May	Should not	Must not	May Encr.
User-Identity	100	6.3.1	Grouped	M, V				N
MSISDN	101	6.3.2	OctetString	M, V				N
User-Data	102	6.3.3	OctetString	M, V				N
Data-Reference	103	6.3.4	Enumerated	M, V				
Service-Indication	104	6.3.5	OctetString	M, V				N
Subs-Req-Type	105	6.3.6	Enumerated	M, V				N
Requested-Domain	106	6.3.7	Enumerated	M, V				N
Current-Location	107	6.3.8	Enumerated	M, V				N

NOTE 1: The AVP header bit denoted as 'M', indicates whether support of the AVP is required. The AVP header bit denoted as 'V', indicates whether the optional Vendor-ID field is present in the AVP header. For further details, see [6].

NOTE 2: Depending on the concrete command.

6.3.1 User-Identity AVP

The User-Identity AVP (AVP Code 100) is of type Grouped. This AVP contains a user public identity.

AVP format

User-Identity ::= <AVP header: 100 10415>

*[Public-Identity]

*[MSISDN]

*[AVP]

6.3.2 MSISDN AVP

The MSISDN AVP (AVP Code 101) is of type OctetString. This AVP contains an MSISDN with the format described in 3GPP TS 23.003.

6.3.3 User-Data AVP

The User-Data AVP (AVP Code 102) is of type OctetString. This AVP contains the user data requested in the UDR and SNR operations and the data to be modified in the UPR operation. The exact content and format of this AVP is described in 3GPP TS 29.328 [1].

6.3.4 Data-Reference AVP

The Data-Reference AVP (AVP code 103) is of type Enumerated, and indicates the type of the requested user data in the operation UDR and SNR. Its exact values and meaning is defined in 3GPP TS 29.328. The following values are defined (more details are given in 3GPP TS 29.328):

RepositoryData (0)

PublicIdentifiers (10)

This value is used to request the read or notification of changes in the IMS public identities fields

RegistrationState (11)

S-CSCFName (12)

InitialFilterCriteria (13)

LocationInformation (14)

6.3.5 Service-Indication AVP

The Service-Indication AVP (AVP code 104) is of type OctetString. This AVP contains the Service Indication that identifies a service in an AS.

6.3.6 Subs-Req-Type AVP

The Subs-Req-Type AVP (AVP code 105) is of type Enumerated, and indicates the type of the subscription-to-notifications request. The following values are defined:

Subscribe (0)

This value is used by an AS to subscribe to notifications of changes in data.

Unsubscribe (1)

This value is used by an AS to unsubscribe to notifications of changes in data.

6.3.7 Requested-Domain AVP

The Requested-Domain AVP (AVP code 106) is of type Enumerated, and indicates the access domain for which certain data (e.g. user state) are requested. The following values are defined:

CS-Domain (0)

The requested data apply to the CS domain.

PS-Domain (1)

The requested data apply to the PS domain.

6.3.8 Current-Location AVP

The Current-Location AVP (AVP code 107) is of type Enumerated, and indicates whether an active location retrieval has to be initiated or not:

DoNotNeedInitiateActiveLocationRetrieval (0) The request indicates that the initiation of an active location retrieval is required.

InitiateActiveLocationRetrieval (1)

It is requested that an active location retrieval is initiated.

6.4 Use of namespaces

This clause contains the namespaces that have either been created in this specification, or the values assigned to existing namespaces managed by IANA.

This specification assigns the values 1-4 from the Command Code namespace managed by 3GPP for its Diameter vendor-specific application number 2. See section 6.1 for the assignment of the namespace in this specification.

6.4.1 AVP codes

This specification assigns the values 100-107 from the AVP Code namespace managed by 3GPP for its Diameter vendor-specific application number 2. See section 6.3 for the assignment of the namespace in this specification.

6.4.2 Vendor-Specific-Result-Code AVP values

This specification has assigned Vendor-Specific-Result-Code AVP values 4100 and 5100-5104. See section 6.2.

7 Special Requirements

7.1 Version Control

The same mechanisms specified in 3GPP TS 29.229 [6] apply to this specification.

Annex A (informative): Change history

Date	TSG #	TSG Doc.	CR#	Rev	Subject/Comment	In	Out
June 2002	CN#16	NP-020266			Version 2.0.1 present in CN#16 for approval	2.0.1	5.0.0
Sep 2002	CN#17	NP-020450	2	1	Cancellation of subscriptions to notifications	5.0.0	5.1.0
Sep 2002	CN#17	NP-020450	3	1	Addition of AVPs to User-Data-Request	5.0.0	5.1.0

History

Document history		
V5.0.0	June 2002	Publication
V5.1.0	September 2002	Publication