

ETSI TS 129 332 V6.3.0 (2005-09)

Technical Specification

Universal Mobile Telecommunications System (UMTS); Media Gateway Control Function (MGCF) - IM Media Gateway (IM-MGW) Mn interface (3GPP TS 29.332 version 6.3.0 Release 6)



Reference

RTS/TSGC-0429332v630

Keywords

UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005.
All rights reserved.

DECTTM, **PLUGTESTS**TM and **UMTS**TM are Trade Marks of ETSI registered for the benefit of its Members.
TIPHONTM and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPPTM is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	5
1 Scope	6
2 References	6
3 Definitions, symbols and abbreviations	7
3.1 Definitions.....	7
3.2 Symbols.....	7
3.3 Abbreviations	7
4 UMTS capability set.....	8
4.1 Profile Identification.....	8
5 Naming conventions.....	8
5.1 MGCF/IM-MGW naming conventions	8
5.2 Termination names	8
5.2.1 Termination naming convention	8
5.2.2 Termination naming convention for TDM terminations.....	8
6 Topology descriptor	8
7 Transaction timers	8
8 Transport	9
9 Multiple Virtual MG	9
10 Formats and codes	9
10.1 Signalling Objects	9
10.2 Codec Parameters.....	10
10.2.1 AMR Codec.....	10
10.2.1 DTMF Codec.....	11
11 Mandatory Support of SDP and H.248 Annex C information elements	11
12 General on packages and Transactions.....	11
12.1 Profile Details.....	11
13 Void.....	11
14 Call independent H.248 transactions.....	11
15 Transactions towards IM CN Subsystem	12
15.1 Procedures related to a termination towards IM CN Subsystem	12
15.1.1 Reserve IMS Connection Point	13
15.1.2 Configure IMS Resources	14
15.1.3 Reserve IMS Connection Point and configure remote resources.....	15
15.1.4 Release IMS Termination	16
15.2 IMS packages	16
16 Transactions towards ISUP	17
16.1 Procedures related to a termination towards ISUP	17
16.1.1 Reserve TDM Circuit.....	17
16.1.2 Release TDM Termination	18
16.2 ISUP packages.....	18
17 Transactions towards BICC.....	19
17.1 Procedures related to a termination towards BICC	19
17.2 BICC packages	20
Annex A (Normative): Profile Description	21
A.1 Profile Identification.....	21
A.2 Summary	21

A.3	Gateway Control Protocol Version	21
A.4	Connection Model	21
A.5	Context Attributes	21
A.6	Terminations.....	21
A.6.1	Termination Names.....	21
A.6.2	Multiplexed terminations	21
A.7	Descriptors	22
A.7.1	Stream Descriptor	22
A.7.1.1	Local Control Descriptor.....	22
A.7.2	Events Descriptor.....	22
A.7.3	EventBuffer Descriptor.....	23
A.7.4	Signals Descriptor.....	23
A.7.5	DigitMap Descriptor	24
A.7.6	Statistics Descriptor	24
A.7.7	ObservedEvents Descriptor	24
A.7.8	Topology Descriptor	24
A.7.9	Error Descriptor	24
A.8	Command API.....	24
A.8.1	Add	24
A.8.2	Modify	25
A.8.3	Subtract.....	25
A.8.4	Move.....	25
A.8.5	Auditvalue.....	26
A.8.6	Auditcapabilities	26
A.8.7	Notify.....	26
A.8.8	Service Change	27
A.8.9	Manipulating and auditing context attributes.....	28
A.9	Generic command syntax and encoding	28
A.10	Transactions	28
A.11	Messages	28
A.12	Transport	29
A.13	Security	29
A.14	Packages	29
A.14.1	Generic Package	30
A.14.2	Base Root Package.....	31
A.14.3	Basic DTMF Generator Package	32
A.14.4	Basic DTMF Detection Package.....	32
A.14.5	TDM Circuit Package	33
A.14.6	MGW Congestion Package.....	34
A.14.7	Continuity Package	34
A.14.8	Announcement Package.....	35
A.14.9	Bearer Characteristics Package.....	36
A.14.10	Generic Bearer Connection Package.....	36
A.14.11	Call Progress Tones Generator Package v1	37
A.14.12	Basic Call Progress Tones Generator with Directionality	38
A.14.13	Expanded Call Progress Tones Generator Package	38
A.14.14	Basic Services Tones Generation Package	39
A.14.15	Bearer Control Tunnelling Package	40
A.14.16	Expanded Services Tones Generation Package	40
A.14.17	Intrusion Tones Generation Package	41
A.14.18	3GUP Package	42
A.14.19	Modification of Link Characteristics Bearer Capability	42
A.15	Mandatory support of SDP and Annex C information elements	43
A.16	Optional support of SDP and Annex C information elements.....	43
A.17	Procedures	43
A.17.1	Call Independent Procedures	43
A.17.2	IMS Terminations Procedures	43
A.17.3	TDM Terminations Procedures.....	43
A.17.4	BICC Terminations Procedures	44
Annex B (informative): Change history		45
History		46

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document describes the protocol to be used on the Media Gateway Control Function (MGCF) – IM Media Gateway (IM-MGW) interface. The basis for this protocol is the H.248 protocol as specified in ITU-T. The IMS architecture is described in 23.228. The interaction of the MGCF-IM MGW interface signalling procedures in relation to the SIP, and BICC/ISUP signalling at the MGCF are described in 29.163.[4]

This specification describes the application of H.248 on the Mn interface. Required extensions use the H.248 standard extension mechanism. In addition certain aspects of the base protocol H.248 are not needed for this interface and thus excluded by this profile.

The present document is valid for a 3rd generation PLMN (UMTS) complying with Release 6 and later.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS); Stage 2".
- [2] 3GPP TS 29.007: "General requirements on interworking between the Public Land Mobile Network (PLMN) and the Integrated Services Digital Network (ISDN) or Public Switched Telephone Network (PSTN)".
- [3] 3GPP TS 29.205: "Application of Q.1900 series to Bearer Independent CS Network architecture; Stage 3"
- [4] 3GPP TS 29.163: "Interworking between the IM CN subsystem and CS networks – Stage 3".
- [5] 3GPP TS 29.232: "Media Gateway Controller (MGC); Media Gateway (MGW) interface; Stage 3".
- [6] 3GPP TS 26.226: "Cellular Text Telephone Modem; General Description".
- [7] 3GPP TS 26.103: "Speech codec list for GSM and UMTS".
- [8] 3GPP TS 29.202: "Application of Q.1900 series to Bearer Independent CS Network architecture; Stage 3".
- [9] ITU-T Recommendation H.248.1 (05/02): "Gateway Control Protocol: Version 2".
- [10] ITU-T Recommendation H.248.8: "Error Codes and Service Change Reason Description".
- [11] ITU-T Recommendation H.248.2: "Facsimile, text conversation and call discrimination packages".
- [12] ITU-T Recommendation H.248.10: "Media Gateway Resource Congestion Handling Package".
- [13] ITU-T Recommendation T.140: "Text conversation protocol for multimedia application".
- [14] ITU-T Recommendation Q.1950 (12/2002) "Call Bearer Control Protocol".
- [15] IETF RFC 2960: "Stream Control Transmission Protocol".

- [16] IETF RFC 3267: "Real-Time Transport Protocol (RTP) Payload Format and File Storage Format for the Adaptive Multi-Rate (AMR) and Adaptive Multi-Rate Wideband (AMR-WB) Audio Codecs".
- [17] IETF RFC 2327: "SDP: Session Description Protocol".
- [18] IETF RFC 2833: "RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals".
- [20] 3GPP TS 26.236: "Packet switched conversational multimedia applications; Transport protocols".
- [21] 3GPP TS 29.415: "Core Network Nb Interface User Plane Protocols".
- [22] 3GPP TS 23.153: "Out of band transcoder control".
- [23] IETF RFC 768: "User Datagram Protocol".
- [24] IETF RFC 3332: "Signaling System 7 (SS7) Message Transfer Part 3 (MTP3) - User Adaptation Layer (M3UA)".
- [25] 3GPP TS 29.202: "SS7 Signalling Transport in Core Network".
- [26] ITU-T Recommendation H.248.7: "Generic Announcement Package".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the [following] terms and definitions [given in ... and the following] apply.

Context (H.248): A context is an association between a number of Terminations. The context describes the topology (who hears/sees whom) and the media mixing and/or switching parameters if more than two terminations are involved in the association.

Package (H.248): Different types of gateways may implement terminations which have differing characteristics. Variations in terminations are accommodated in the protocol by allowing terminations to have optional properties. Such options are grouped into packages, and a termination may realise a set of such packages.

Termination (H.248): A termination is a logical entity on an MGW which is the source and/or sink of media and/or control streams. A termination is described by a number of characterising properties, which are grouped in a set of descriptors which are included in commands. Each termination has a unique identity (TerminationID).

Termination Property (H.248): Termination properties are used to describe terminations. Related properties are grouped into descriptors. Each termination property has a unique identity (PropertyID).

3.2 Symbols

For the purposes of the present document, the following symbols apply:

Mn	Interface between the media gateway control function and the IMS media gateway.
Mg	Interface between the MGCF and the CSCF
Mj	Interface between the MGCF and the BGCF

3.3 Abbreviations

For the purposes of the present document, the following abbreviations apply:

BICC	Bearer Independent Call Control
IM-MGW	IP Multimedia Media Gateway
ISUP	ISDN User Part
MGCF	Media Gateway Control Function
RFC	Request For Comment; this includes both discussion documents and specifications in the IETF domain

4 UMTS capability set

The support of the Mn interface capability set shall be identified by the Mn profile and support of this profile shall be indicated in ServiceChange procedure.

The mandatory parts of this capability set shall be used in their entirety whenever it is used within the H.248 profile. Failure to do so will result in a non-standard implementation.

ITU-T Recommendation H.248.1 (05/02) [9] is the basis for this Capability Set. The compatibility rules for packages, signals, events, properties and statistics and the H.248 protocol are defined in ITU-T Recommendation H.248.1 [9]. Their use or exclusion for this interface is clarified in clause 12.

4.1 Profile Identification

Table 4.1: Profile Identification

Profile name:	threegimscsiw
Version:	1

5 Naming conventions

5.1 MGCF/IM-MGW naming conventions

The MGCF shall be named according to the naming structure of the underlying transport protocol which carries the H.248 protocol.

5.2 Termination names

5.2.1 Termination naming convention

For definition on termination naming convention see 3GPP TS 29.232 [5]

5.2.2 Termination naming convention for TDM terminations

For the definition of TDM terminations see 3GPP TS 29.232[5]

6 Topology descriptor

The Topology Descriptor shall be supported by the IM-MGW and MGCF.

7 Transaction timers

All transaction timers specified in H.248 shall be supported in this subset of the protocol.

8 Transport

Each implementation of the Mn interface should provide SCTP (as defined in IETF RFC2960 [14]). An implementation alternative may provide UDP (as defined in IETF RFC 768 [23]). The M3UA layer may also be added to SCTP for pure IP signalling transport (as defined in IETF RFC 3332 [24] with options detailed in 3GPP TS 29.202 [25]).

See also Clause 12.1

9 Multiple Virtual MG.

Not Applicable

10 Formats and codes

10.1 Signalling Objects

Table 10.1 shows the parameters which are required.

The coding rules applied in ITU-T Recommendation H.248.1 [9] for the applicable coding technique shall be followed for the UMTS capability set.

Table 10.1: required parameters

Signalling Object	H.248 Descriptor	Coding
Codec List	Local Descriptor or Remote Descriptor	<fmt list> in a single SDP m-line. For a fixed RTP payload type, the codec type is implied by the RTP payload type. For a dynamic RTP payload type, for each codec information on the codec type shall be provided in a separate SDP "a=rtpmap"-line and possibly additional SDP "a=fmtp"-line(s). See Clause 10.2.
Bearer Service Characteristics	Local Descriptor or Remote Descriptor	As per Q.1950 [14]. For TMR, only values "3.1 kHz audio" or "speech" are required.
Context ID	NA	Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A. Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B.
IP Address	Local Descriptor or Remote Descriptor	<connection address> in SDP "c-line"
Port	Local Descriptor or Remote Descriptor	<port> in SDP m-line. <transport> in SDP m-line shall be set to value "RTP/AVP"
Reserve_Value	Local Control	ITU-T Recommendation H.248.1 [9] Mode property. Binary Encoding: Encoding as per ITU-T Recommendation H.248.1 Annex A "reserveValue" Textual Encoding: Encoding as per ITU-T Recommendation H.248.1 Annex B "reservedValueMode".
RtcpbwRS	Local Descriptor or Remote Descriptor	<bandwidth> in SDP "b:RS"-line.
RtcpbwRR	Local Descriptor or Remote Descriptor	<bandwidth> in SDP "b:RR"-line.
RTPpayload	Local Descriptor or Remote Descriptor	<fmt list> in SDP m-line
Termination ID	NA	Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A. Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B.
Transaction ID	NA	Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A. Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B.
Note	For binary encoding, the SDP equivalents "SDP_V", "SDP_M", "SDP_C", "SDP_A", and SDP_B" in ITU-T Recommendation H.248.1 [9], Annex C.11, shall be used to encode the corresponding SDP lines. Other SDP equivalents shall not be used. The SDP equivalents shall be used in the order specified for the corresponding SDP lines in IETF RFC 2327 [17]. Rules for the usage of SDP in ITU-T Recommendation H.248.1 [9] shall also be applied to the SDP equivalents.	

10.2 Codec Parameters

10.2.1 AMR Codec

On IMS terminations, the AMR codec is transported according to the IETF AMR RTP profile, IETF RFC 3267 [16]. 3GPP TS 26.236 [20] selects options applicable within 3GPP.

IETF RFC 3267 contains the MIME registration of the IETF AMR RTP profile with media type "audio" and media subtype "AMR". The AMR codec shall be signaled accordingly in the SDP "a=rtpmap"-line and a dynamic RTP payload type shall be used.

The selected options are expressed as MIME parameters in SDP "a=fmtp"-line. The following MIME parameters shall be supported on the Mn interface:

- "mode-set"

For compatibility with GSM peers, the IM-MGW shall perform mode changes only in every second sent package.

10.2.1 DTMF Codec

On IMS terminations, DTMF is transported according to the IETF RFC 2833 [18] "telephone event" format.

IETF RFC 2833[18] contains the MIME registration with media type "audio" and media subtype "telephone-event". DTMF shall be signaled accordingly in the SDP "a=rtpmap"-line and a dynamic RTP payload type shall be used.

An IM-MGW supporting DTMF shall support the default options of the IETF RFC 2833 [18] "telephone event" format. Therefore, a support of optional MIME parameters of "telephone-event" is not required at the Mn interface.

11 Mandatory Support of SDP and H.248 Annex C information elements

This section shall be in accordance with the subclause "Mandatory Support of SDP and ITU-T Recommendation H.248.1 Annex C information elements" in ITU-T Recommendation Q.1950 [14].

12 General on packages and Transactions

The base root package (0x0002) properties shall be provisioned in the MGW.

H.248 Statistics shall not be audited via the Mn interface.

The use of "Overspecified" (e.g. range of values) and "Underspecified" (e.g. "?") parameter specification shall not be permitted except where explicitly indicated in or referenced by the Mn interface specification.

The use of wildcarding for the Termination Id shall be performed using 1 octet only.

12.1 Profile Details

VOID.

NOTE: Profile now defined in Normative Annex A.

13 Void

14 Call independent H.248 transactions

Table 14 shows the relationship between each non call-related procedure in 3GPP TS 29.232 [5] and the corresponding procedure defined in 3GPP TS 29.163 [4].

For further description of error codes and service change reasons, refer to ITU-T Recommendation H.248.8 [14].

Table 14: Non call-related transaction reused from 3GPP TS 29.232 [5]

Procedure defined in 3GPP TS 29.163 [4]	Procedure defined in 3GPP TS 29.232 [5]	Support	Comment
IM-MGW Out of service	MGW Out of Service	Mandatory	
IM-MGW Communication Up	MGW Communication Up	Mandatory	
IM-MGW Restoration	MGW Restoration	Mandatory	
IM-MGW Register	MGW Register	Mandatory	
IM-MGW Re-register	MGW Re-register	Mandatory	
MGCF Ordered Re-register	(G)MSC Server Ordered Re-register	Mandatory	
MGCF Restoration	(G)MSC Server Restoration	Optional	
MGCF Out of Service	(G)MSC Server Out of Service	Optional	
Termination Out-of-Service	Termination Out-of-Service	Mandatory	
Termination Restoration	Termination Restoration	Mandatory	
Audit Value	Audit Value	Mandatory	Only For Audit of Termination Service State.
Audit Capability	Audit Capability	Optional	
Command Rejected	Command Rejected	Mandatory	The "Command Rejected" procedure may be used in response both to call-related and non-call-related ITU-T Recommendation H.248 Commands
IM-MGW Capability Change	Capability Update	Optional	
IM-MGW Resource Congestion Handling - Activate	MGW Resource Congestion Handling - Activate	Mandatory	
IM-MGW Resource Congestion Handling - Indication	MGW Resource Congestion Handling - Indication	Mandatory	

15 Transactions towards IM CN Subsystem

15.1 Procedures related to a termination towards IM CN Subsystem

Table 1 shows the relationship between each call-related procedure in ITU-T Recommendation Q.1950 [14] (see 3GPP TS 29.205 [3]) or TS 29.232 [5] and the corresponding stage 2 procedure defined in 3GPP TS 29.163 [4].

Table 15.1.1: Correspondence between ITU-T Recommendation Q.1950 [13] or 29.232 [5] call-related transactions and 3GPP TS 29.163 [4] procedures

Procedure defined in 3GPP TS 29.163 [4]	Transaction used in Q.1950 [14]	Transaction used in TS 29.232 [5]	Supported	Comment
Reserve IMS Connection point	Not defined	n. a. for reuse	Mandatory	See 13.2.1.1
Configure IMS Resources	Not Defined	n. a. for reuse	Mandatory	See 13.2.1.2
Reserve IMS Connection Point and configure remote resources	Not defined	n. a. for reuse	Mandatory	See 13.2.1.3
Release IMS termination	n. a. for reuse	n. a. for reuse	Mandatory	See 13.2.1.4
Change IMS ThroughConnection	Cut Through	n. a. for reuse	Mandatory	
Detect IMS RTP Tel Event	Detect Digit	n. a. for reuse	Optional	Only applicable if termination towards IMS is connected with a termination towards a BICC network.
Notify IMS RTP Tel Event	Detected digit(BIWF)	n. a. for reuse	Optional	Only applicable if termination towards IMS is connected with a termination towards a BICC network.
Send IMS RTP Tel Event	n.a. for reuse	Send DTMF	FFS	Restrictions defined for minimum interval to follow 3G TS 23.014. Maximum interval shall be controlled by MGW if required by network
Stop IMS RTP Tel Event	n.a.for reuse	Stop DTMF	FFS	The signal descriptor shall not include any signal. The MGW shall ensure the minimum duration timing and minimum interval timing is achieved in accordance with the DTMF timing defined in TS 23.014 [27]. Maximum duration shall also be controlled by the MGW if required by the network
NOTE: A procedure defined in table 13.2.1 can be combined with another procedure in the same table. This means that they can share the same contextID and termination ID(s) and that they can be combined in the same H.248 command.				

15.1.1 Reserve IMS Connection Point

When the procedure “Reserve IMS Connection Point” is required the following procedure is initiated:

The MGCF sends an Add.req command with the following information.

1 Add.req (Reserve IMS Connection Point) MGCF to IM-MGW

Table 15.1.2: Reserve IMS Connection Point Request

Address Information	Control information	Bearer information
Local Descriptor { Port = ? IP Address = ? }	Transaction ID = z Termination ID = ? <u>If Context Requested:</u> Context ID = ? <u>If Context Provided:</u> Context ID = c1 If Resources for multiple Codecs shall be reserved: Reserve_Value	Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR }

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Add.resp (Reserve IMS Connection Point Ack)

Table 15.1.3: Reserve IMS Connection Point Acknowledge

Address Information	Control information	Bearer information
Local Descriptor { Port IP Address }	Transaction ID Termination ID Context ID	Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR }

15.1.2 Configure IMS Resources

When the procedure "Configure IMS Resources" is required the following procedure is initiated:

The MGCF sends an Mod.req command with the following information.

1 Mod.req (Configure IMS Resources) MGCF to IM-MGW

Table 15.1.4: Configure IMS Resources Request

Address Information	Control information	Bearer information
If local resources are modified: Local Descriptor { Port IP Address } If remote resources are modified: Remote Descriptor { Port IP Address }	Transaction ID Termination ID Context ID If Resources for multiple Codecs shall be reserved: Reserve_Value	If local resources are modified: Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR } If remote resources are modified: Remote Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR }

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Mod.resp (Configure IMS Resources Ack)

Table 15.1.5: Configure IMS Resources Acknowledge

Address Information	Control information	Bearer information
If local resources were provided in request: Local Descriptor { Port IP Address } If remote resources were provided in request: Remote Descriptor { Port IP Address }	Transaction ID Context ID	If local resources were provided in request: Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR } If remote resources were provided in request: Remote Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR }

15.1.3 Reserve IMS Connection Point and configure remote resources

When the procedure "Reserve IMS Connection Point and configure remote resources" is required the following procedure is initiated:

The MGCF sends a Mod.req command with the following information.

- 1 Add.req (Reserve IMS Connection Point and configure remote resources) MGCF to IM-MGW

Table 15.1.6: Reserve IMS Connection Point and configure remote resources Request

Address Information	Control information	Bearer information
Local Descriptor { Port = ? IP Address = ? } Remote Descriptor { Port IP Address }	Transaction ID Termination ID = ? <u>If Context Requested:</u> Context ID = ? <u>If Context Provided:</u> Context ID = c1 If Resources for multiple Codecs shall be reserved: Reserve_Value	Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR } Remote Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR }

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

- 2 Add.resp (Reserve IMS Connection Point and configure remote resources Ack)

Table 15.1.7: Reserve IMS Connection Point and configure remote resources Acknowledge

Address Information	Control information	Bearer information
Local Descriptor { Port IP Address } Remote Descriptor { Port IP Address }	Transaction ID Termination ID Context ID	Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR } Remote Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR }

15.1.4 Release IMS Termination

When the procedure “Release IMS Termination” is required the following procedure is initiated:

The MGCF sends an Sub.req command with the following information.

- 1 Sub.req (Release IMS Termination) MGCF to IM-MGW

Table 15.1.8: Release IMS Termination Request

Address Information	Control information	Bearer information
	Transaction ID Termination ID Context ID	

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

- 2 Sub.resp (Release IMS Termination) IM-MGW to MGCF

Table 13.2.9: Release IMS Termination Acknowledge

Address Information	Control information	Bearer information
	Transaction ID Termination ID Context ID	

15.2 IMS packages

None

16 Transactions towards ISUP

Table 16.1: Correspondence between ITU-T Recommendation Q.1950 [13] or 29.232 [5] call-related transactions and 3GPP TS 29.163 [4] procedures related to a termination towards an ISUP network

Procedure defined in 3GPP TS 29.163 [4]	Transaction used in ITU-T Q.1950 [14]	Transaction used in TS 29.232 [5]	Support	Comment
Reserve TDM Circuit	n. a. for reuse	n. a. for reuse, (NOTE2)	Optional (NOTE 4)	See Clause 13.2.2.1
Change TDM Through-connection	Cut Through (CSM Controlled)	Change Through-connection	Optional (NOTE 4)	
Activate TDM voice-processing function	Echo Cancellor	n. a. for reuse	Optional (NOTE 4)	
Send TDM Tone	Insert_Tone	n. a. for reuse	Optional (NOTE 4)	Only H.248 MOD command to an existing termination
Stop TDM Tone	Insert_Tone	n. a. for reuse	Optional (NOTE 4)	Only H.248 MOD command to an existing termination
Play TDM Announcement	Insert_Announcement	n. a. for reuse	Optional (NOTE 4)	Only H.248 MOD command to an existing termination
TDM Announcement Completed	Signal_Completion	n. a. for reuse	Optional (NOTE 4)	
Stop TDM Announcement	Insert Announcement	n. a. for reuse	Optional (NOTE 4)	Only H.248 MOD command to an existing termination
Continuity Check	Continuity Check Tone	n. a. for reuse	Optional (NOTE 4)	The addition to "Prepare BNC Notify" defined in Annex B.7.1.1 of Q.1950 [10] shall be applied instead to "Reserve TDM Circuit", as defined in Clause 13.2.2.1
Continuity Check Verify	Continuity Check Verify	n. a. for reuse	Optional (NOTE 4)	
Continuity Check Response	Continuity Check Response	n. a. for reuse	Optional (NOTE 4)	The addition to "Prepare BNC Notify" defined in Annex B.7.1.2 of Q.1950 [10] shall be applied instead to "Reserve TDM Circuit", as defined in Clause 13.2.2.1
Release TDM Termination	n. a. for reuse	n. a. for reuse	Optional (NOTE 4)	See Clause 13.2.2.2
Termination Out Of Service	BIWF_Service_Cancellation_Indication	n. a. for reuse	Optional (NOTE 4)	
NOTE 1: A procedure defined in table 13.2.2 can be combined with another procedure in the same table. This means that they can share the same contextID and termination ID(s) and that they can be combined in the same H.248 command.				
NOTE 2: The reserve circuit procedure of 29.232 is not to be used only a reduced set of the parameters is required for reserve TDM circuit.				
NOTE 3: Enhanced to include Camel Prepaid, otherwise same as Q.1950				
NOTE 4: Necessary for optional terminations towards ISUP				

16.1 Procedures related to a termination towards ISUP

16.1.1 Reserve TDM Circuit

When the procedure "Reserve TDM Circuit" is required the following procedure is initiated:

The MGCF sends an Add.req command with the following information.

1 Add.req (Reserve TDM Circuit) MGCF to IM-MGW

Address Information	Control information	Bearer information
	Transaction ID Termination ID <u>If Context Requested:</u> Context ID = ? <u>If Context Provided:</u> Context ID = c1	Bearer Service Characteristics

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Add.resp (Reserve TDM Circuit) IM-MGW to MGCF

Address Information	Control information	Bearer information
	Transaction ID Termination ID Context ID	

16.1.2 Release TDM Termination

When the procedure "Release TDM Termination" is required the following procedure is initiated:

The MGCF sends an Sub.req command with the following information.

1 Sub.req (Release TDM Termination) MGCF to IM-MGW

Address Information	Control information	Bearer information
	Transaction ID Termination ID Context ID	

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Sub.resp (Release TDM Termination) IM-MGW to MGCF

Address Information	Control information	Bearer information
	Transaction ID Termination ID Context ID	

16.2 ISUP packages

None

17 Transactions towards BICC

17.1 Procedures related to a termination towards BICC

Table 17.1: Correspondence between ITU-T Recommendation Q.1950 [13] or 3GPP TS 29.232 [5] call-related transactions and 3GPP TS 29.163 [4] procedures related to a termination towards a BICC network

Procedure defined in 3GPP TS 29.163 [4]	Transaction used in Q.1950 [14]	Transaction used in TS 29.232 [5]	Support	Comment
Establish Bearer	Establish_BNC_Notify +(tunnel)	Establish Bearer (NOTE 1)	Optional (NOTE 5)	
Prepare Bearer	Prepare_BNC_Notify +(tunnel)	Prepare Bearer (NOTE 1), (NOTE 2)	Optional (NOTE 5)	
Change Through-Connection	Cut_Through	Change Through-Connection	Optional (NOTE 5)	
Release Bearer	Cut_BNC (MOD H.248 Command).	Release Bearer	Optional (NOTE 5)	(NOTE 3)
Release Termination	Cut_BNC (SUB H.248 Command).	Release Termination	Optional (NOTE 5)	Statistics about "Ctmbits" are not applicable in Sub.resp
Bearer Established	BNC Established	Bearer Established	Optional (NOTE 5)	(NOTE 3)
Bearer Released	BNC Release	Bearer Released	Optional (NOTE 5)	(NOTE 3)
Send Tone	Insert_Tone	n. a. for reuse	Optional (NOTE 5)	Only H.248 MOD command to an existing termination
Stop Tone	Insert Tone	n. a. for reuse	Optional (NOTE 5)	Only H.248 MOD command to an existing termination
Play Announcement	Insert_Announcement	n. a. for reuse	Optional (NOTE 5)	Only H.248 MOD command to an existing termination
Stop Announcement	Insert Announcement	n. a. for reuse	Optional (NOTE 5)	Only H.248 MOD command to an existing termination
Announcement Completed	Signal Completion	n. a. for reuse	Optional (NOTE 5)	(NOTE 3)
Bearer Modification Support	Not defined	Bearer Modification Support	Optional (NOTE 5)	
Confirm Char	Confirm_Char	Confirm Bearer Characteristics (NOTE 1)	Optional (NOTE 6)	
Modify Bearer Characteristics	Modify Char	Modify Bearer Characteristics (NOTE 1)	Optional (NOTE 6)	
Reserve Char	Reserve_Char_Notify	Reserve Bearer Characteristics (NOTE 1)	Optional (NOTE 6)	
Bearer Modified	BNC Modified	Bearer Modified	Optional (NOTE 6)	
Activate Voice Processing Function	Echo Canceller	n. a. for reuse	Optional (NOTE 5)	
Tunnel Information Down	Tunnel (MGC-MGW)	Tunnel Information Down	Optional (NOTE 7)	For IP Transport at BICC termination
Tunnel Information Up	Tunnel (MGW-MGC)	Tunnel Information Up	Optional (NOTE 7)	For IP Transport at BICC termination
Termination Out-of-Service	BIWF Service Cancellation Indication	n. a. for reuse	Optional (NOTE 5)	

- NOTE 1: The procedure is only applicable if the Nb framing protocol is applied at the BICC termination. Only requesting of Observed events defined in the corresponding TS 29.232 and parameters defined in the "3GUP" package of TS 29.232 are applicable in addition the parameters of the corresponding Q.1950 procedure. Those parameters shall be applies as follows: UP mode = Supported mode; UP versions = 2; interface = CN;
- NOTE 2: Parameters and Observed events defined for Cellular Text telephone Modem Text Transport in the corresponding procedure of TS 29.232 are not applicable.
- NOTE 3: Resp in Q1950 contains no terminationID. However, according to H248.1, terminationID is mandatory! Therefore, termination ID shall be provided.
- NOTE 4: Enhanced to include Camel Prepaid, otherwise same as Q.1950
- NOTE 5: Necessary for optional terminations towards BICC
- NOTE 6: Optional for optional terminations towards BICC
- NOTE 7: Necessary for optional terminations towards BICC network with IP transport

17.2 BICC packages

This Clause is only applicable for terminations towards BICC Networks. The support of terminations towards BICC networks is optional.

No new packages for terminations towards BICC Networks are defined in the present specification. See Clause 12.1.14 for reused packages from other specifications.

If the Nb framing protocol (see 3GPP TS 29.415 [21]) is applied at the termination towards the BICC network, the following package shall be applied:

3GUP package (see subclause 15.1.1 of 3GPP TS 29.232 [5]); To enable bearer modification at OoBTC capable networks on Nb interface (see 3GPP TS 23.153 [22]) at the termination towards the BICC network, the following package shall be applied:

- Modification of Link Characteristics Bearer Capability (see subclause 15.1.5 of 3GPP TS 29.232 [5]);

Annex A (Normative): Profile Description

A.1 Profile Identification

Table A.1: Profile version

Profile name:	threegimscsiw
Version:	1

A.2 Summary

This Profile describes the minimum mandatory settings and procedures required to fulfil the requirements for the IMS-CS interworking gateway control.

A.3 Gateway Control Protocol Version

ITU Recommendation H.248.1 Version 2

A.4 Connection Model

Table A.4: Connection Model

Maximum number of contexts:	FFS<integer>
Maximum number of terminations per context:	32
Allowed terminations type combinations in a Context	All

A.5 Context Attributes

Table A.5: Context attributes

Context Attribute	Supported	Values Supported
Topology	Yes	All
Priority Indicator	Yes	
Emergency Indicator	Yes	

A.6 Terminations

A.6.1 Termination Names

See Clause 5.

A.6.2 Multiplexed terminations

Table A.6.2: Multiplexed terminations

MultiplexTerminations Supported	No
--	----

A.7 Descriptors

A.7.1 Stream Descriptor

Table A.7.1: Stream descriptors

Maximum number of streams per termination type	1
--	---

A.7.1.1 Local Control Descriptor

Table A.7.1.1/1: Local Control Descriptor

		Termination Type	Stream Type
Reserve group used:	No		
Reserve value used:	Yes	ALL	ALL

Table A.7.1.1/2: Allowed Stream Modes

Termination Type <Type>	Stream Type <Type>	Allowed StreamMode Values SendOnly, RecvOnly, SendRecv, Inactive

A.7.2 Events Descriptor

Table A.7.2/1: Events Descriptor

Events settable on termination types and stream types:	Yes		
	Event ID	Termination Type	Stream Type
	Detect_Digit(Digit)	ALL	ALL
	BNC Established	Terminations towards BICC network	ALL
	BNC Modification Failed	Terminations towards BICC network	ALL
	BNC Modified	Terminations towards BICC network	ALL
	BNC Release	Terminations towards BICC network	ALL
	Tunnel	Terminations towards BICC network with IP transport	ALL
	Signal Completion	ALL	ALL

Table A.7.2/2: Event Buffer Control

Event Buffer Control used:	No
----------------------------	----

Table A.7.2/3: Keep active

Keepactive used on events:	Yes
----------------------------	-----

Table A.7.2/4: Embedded events

Embedded events in an event descriptor:	No
---	----

Table A.7.2/5: Embedded signals

Embedded signals in an event descriptor:	No
--	----

A.7.3 EventBuffer Descriptor

Table A.7.3: Event Buffer Descriptor

Event Buffer descriptor used:	No
-------------------------------	----

A.7.4 Signals Descriptor

Table A.7.4/1: Signals Descriptor

Signals settable dependant on termination or streams types:	No Signals on ROOT termination shall not be supported
---	--

Table A.7.4/2: Signal Lists

Signals Lists supported:		Yes
<i>If yes</i>	Termination Type Supporting Lists:	ALL
	Stream Type Supporting lists:	ALL
	Maximum number of signals to a signal list:	FFS<integer>
	Intersignal delay parameter supported:	FFS<Yes/No>

Table A.7.4/3: Overriding Signal type and duration

Signal type and duration supported:	Optional
-------------------------------------	----------

Table A.7.4/4: Notify completion

Notify completion supported:		Yes
<i>If yes</i>	SignalID	Type of completion supported
	ALL	ALL ? or <TO, EV, ED, NC, PI>
RequestID Parameter Supported:	NO	

Table A.7.4/5: Signals played simultaneously

Signals played simultaneously:	No
--------------------------------	----

Table A.7.6/6: Keep active

Keepactive used on signals:	Yes
-----------------------------	-----

A.7.5 DigitMap Descriptor

Table A.7.5: DigitMAP Descriptor

Digit Maps supported:	No
------------------------------	----

A.7.6 Statistics Descriptor

Table A.7.6: Statistics Descriptor

Statistics reported on subtract:	No
---	----

A.7.7 ObservedEvents Descriptor

Table A.7.7: Observed Events Descriptor

Event detection time supported:	Yes
--	-----

A.7.8 Topology Descriptor

Table A.7.8: Topology Descriptor

Allowed triples:	ALL
-------------------------	-----

A.7.9 Error Descriptor

Table A.7.9/1: Error Codes Sent by MGCF

Supported H.248.8 Error Codes:	FFS <ALL H.248.8, list of individual numbers>
Supported Error Codes defined in packages:	FFS<Reference to the appropriate clause >

Table A.7.9/2: Error Codes Sent by MGW:

Supported H.248.8 Error Codes:	FFS<ALL H.248.8, list of individual numbers>
Supported Error Codes defined in packages:	FFS<Reference to the appropriate clause >

A.8 Command API

A.8.1 Add

Table A.8.1/1: Descriptors used by Command Add Request

Descriptors used by Add Request:	Events, Signals, Media (LocalControl, Local And Remote), Error, Audit, Topology
---	---

Table A.8.1/2: Descriptors used by Command Add Reply

Descriptors used by Add Reply:	Events, Signals, Media (LocalControl, Local And Remote), Error, Audit, Topology When command request excludes an Audit Descriptor, the MGW response shall only include descriptors which contained underspecified or overspecified properties in the command request, with the exception of the Error Descriptor. Furthermore, only those properties that were underspecified or overspecified in the request shall be sent in the reply.
---------------------------------------	--

A.8.2 Modify

Table A.8.2/1: Descriptors used by Command Modify Request

Descriptors used by Modify Request:	Events, Signals, Media (LocalControl, Local And Remote), Error, Audit, Topology
--	---

Table A.8.2/2: Descriptors used by Command Modify Reply

Descriptors used by Modify Reply:	Events, Signals, Media (LocalControl, Local And Remote), Error, Audit, Topology When command request excludes an Audit Descriptor, the MGW response shall only include descriptors which contained underspecified or overspecified properties in the command request, with the exception of the Error Descriptor. Furthermore, only those properties that were underspecified or overspecified in the request shall be sent in the reply.
--	--

A.8.3 Subtract

Table A.8.3/1: Descriptor used by Command Subtract Request

Descriptors used by Subtract Request:	AUDIT (empty)
--	---------------

Table A.8.3/2: Descriptor used by Command Subtract Reply

Descriptors used by Subtract Reply:	None
--	------

A.8.4 Move

Table A.8.4/1: Command Move

Move command used:	Yes
---------------------------	-----

Table A.8.4/2: Descriptors used by Move Request

Descriptors used by Move Request:	Events, Signals, Media (LocalControl, Local And Remote), Error, Audit, Topology
--	---

Table A.8.4/3: Descriptors used by Move Reply

Descriptors used by Move Reply:	Events, Signals, Media (LocalControl, Local And Remote), Error, Audit, Topology
--	---

A.8.5 Auditvalue

Table A.8.5: Auditvalue

Audited Properties:	Property Name and Identity	Descriptor
Termination ID	TerminationState: - TDM: ALL (indicating 1 TDM group) - ATM/IP: individual termination The ServiceState property within the TerminationState descriptor shall not take the value "Test".	TerminationState Descriptor
Termination ID	For Packages: - Root	Packages Descriptor
Audited Statistics:	None	
Audited Signals:	None	
Audited Events:	FFS<Event name and Identity e.g. Generic Error Event (g/cause, 0x0001/0x0001), ALL or None>	
Packages Audit Possible	FFS<Yes/No>	

A.8.6 Auditcapabilities

Table A.8.6: Auditcapabilities

Audited Properties:	Property Name and Identity	Descriptor
	FFS	FFS
Audited Statistics:	None	
Audited Signals:	None	
Audited Events:	None	

A.8.7 Notify

Table A.8.7: Descriptors Used Notify

Descriptors used by Notify Request or Reply:	<ObservedEvents, Error>
---	-------------------------

A.8.8 Service Change

Table A.8.8/1: Service Change Methods and Reasons Sent By MGCF

ServiceChange Methods supported:	ServiceChange Reasons supported:
Graceful, Forced, Restart, Disconnected, Handoff(not involving more than 1 MGCF), Failover When a Service Change command on the Root termination with a method other than Graceful is sent, the command shall always be sent as the only command in a message. The sending node shall always wait for the reply to a Service Change command on the Root termination with a method other than Graceful before sending further command requests. A Service Change command on the Root termination with method Graceful may be combined with other commands in a single message.	900-910, 913-917

Table A.8.8/2: Service Change Methods and Reasons Sent By MGW

ServiceChange Methods supported:	ServiceChange Reasons supported:
Graceful, Forced, Restart, Disconnected, Handoff(not involving more than 1 MGW), Failover (except for 'MG impending failure') When a Service Change command on the Root termination with a method other than Graceful is sent, the command shall always be sent as the only command in a message. The sending node shall always wait for the reply to a Service Change command on the Root termination with a method other than Graceful before sending further command requests. A Service Change command on the Root termination with method Graceful may be combined with other commands in a single message.	900-910, 913-917

Table A.8.8/3: Service Change Address

ServiceChangeAddress used:	No
-----------------------------------	----

Table A.8.8/4: Service Change Delay

ServiceChangeDelay used:	No
---------------------------------	----

Table A.8.8/5: Service Change Incomplete Flag

ServiceChange Incomplete Flag used:	No
--	----

Table A.8.8/6: Service Change Version

Version used in ServiceChangeVersion:	2
--	---

Table A.8.8/7: Profile negotiation

Profile negotiation as per H.248.18:	No
---	----

A.8.9 Manipulating and auditing context attributes

Table A.8.9: Manipulating and auditing context attributes

Context Attributes Manipulated:	None
Context Attributes Audited:	None

A.9 Generic command syntax and encoding

Table A.9: Encodings

Supported Encodings:	Binary (optional) Text (optional)
-----------------------------	--------------------------------------

A.10 Transactions

Table A.10/1: Transactions per Message

Maximum number of TransactionRequests / TransactionReplies / TransResponseAcks / Segment Replies per message:	TBD
--	-----

Table A.10/2: Commands per Transaction Requests

Maximum number of commands per Transaction request:	TBD
--	-----

Table A.10/3: Commands per Transaction Reply

Maximum number of commands per Transaction reply:	TBD
--	-----

Table A.10/4: Optional Commands

Commands able to be marked "Optional":	None
---	------

Table A.10/5: Transaction Timers

Transaction Timer:	Value
normalMGExecutionTime	Provisioned
normalMGCExecutionTime	Provisioned
MGOriginatedPendingLimit	Provisioned
MGCEOriginatedPendingLimit	Provisioned
MGProvisionalResponseTimerValue	Provisioned
MGCProvisionalResponseTimerValue	Provisioned

A.11 Messages

The MGCF/MGW Naming Conventions (MID addressing associated with the names of the MGCF/MGW) shall be in accordance with underlying transport. See Clause 8.

A.12 Transport

Table A.12/1: Transport

Supported Transports:	SCTP(recommended), SCTP/M3UA(optional), UDP(optional)
------------------------------	---

Table A.12/2: Segmentation

Segmentation Supported:	No
--------------------------------	----

A.13 Security

Table A.13: Security

Supported Security:	None
----------------------------	------

A.14 Packages

Table A.14/1: Mandatory packages

Package Name	Package ID	Version
Generic (see ITU-T Recommendation H.248.1 [9] Annex E.1);		v1
Base Root Package (see ITU-T Recommendation H.248.1 [9] Annex E.2);		v1
Tone Detection Package (see ITU-T Recommendation H.248.1 [9] Annex E.4);	This package is "extension only". It must be supported if extended but shall not be published over the protocol. It is here for information only.	v1
Basic DTMF Generator Package (see ITU-T Recommendation H.248.1 [9] Annex E.5);		v1
DTMF Detection Package (see ITU-T Recommendation H.248.1 [9] Annex E.6);		v1
TDM Circuit Package (see ITU-T Recommendation H.248.1 [9] Annex E.13);		v1
Media Gateway Resource Congestion Handling Package (see ITU-T Recommendation H.248.10 [12]).		v1
Basic Continuity Package (see ITU-T Recommendation H.248.1 [9] Annex E.10);		v1
Generic Announcement Package (see ITU-T Recommendation H.248.7 [28]). Only Fixed Part is Mandatory		v1

Table A.14/2: Optional packages

Package Name	Package ID	Version	Support dependent on:
Bearer Characteristics Package (see ITU-T Recommendation Q.1950 [23] annex A..3).		v1	
Generic Bearer Connection Package (see ITU-T Recommendation Q.1950 [23] annex A.6).		v1	Interworking with BICC
Tone Generator Package (see ITU-T Recommendation H.248.1 [9] Annex E.3);		v1	This package is "extension only". It must be supported if extended but shall not be published over the protocol. It is here for information only.
Call Progress Tones Generator Package (see ITU-T Recommendation H.248.1 [10] annex E.7).		v1	
Basic Call Progress Tones Generator with Directionality, (see ITU-T Recommendation Q.1950 [23] annex A.8).		v1	Services provided by network
Expanded Call Progress tones Generator Package (see ITU-T Recommendation Q.1950 [23] annex A.9).		v1	Services provided by network
Basic Services Tones Generation Package, (see ITU-T Recommendation Q.1950 [23] annex A.10).		v1	Services provided by network
Bearer Control Tunnelling Package (see ITU-T Recommendation Q.1950 [23] annex A.7).		v1	Interworking with BICC and IP transport
Expanded Services Tones Generation Package (see ITU-T Recommendation Q.1950 [23] annex A.11).		v1	Services provided by network
Intrusion Tones Generation Package (see ITU-T Recommendation Q.1950 [23] annex A.12).		v1	Services provided by network
3GUP package (see subclause 15.1.1 of 3GPP TS 29.232 [5]);		v1	Interworking with BICN PLMN
Modification of Link Characteristics Bearer Capability (see subclause 15.1.5 of 3GPP TS 29.232 [5])		v1	Interworking with BICN PLMN with Codec Modification

Table A.14/3: Package Provisioning Information

Package Name	Property, Parameter, Signal, Event ID	Provisioned Value:
Generic Announcement (H.248.7)	Fixed Announcement Play, AV	Provisioned

A.14.1 Generic Package

Table A.14.1: Package Usage Information For Generic Package

Properties	Mandatory/Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>

Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>	
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>	<Values / ALL >	
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.2 Base Root Package

Table A.14.2: Package Usage Information For Base Root Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>	
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>	<Values / ALL >	
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.3 Basic DTMF Generator Package

Table A.14.3: Package Usage Information For Basic DTMF Generator Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>	<Values / ALL >	
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.4 Basic DTMF Detection Package

Table A.14.4: Package Usage Information For Basic DTMF Generator Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:

	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>		<Values / ALL >
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.5 TDM Circuit Package

Table A.14.5: Package Usage Information For TDM Circuit Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>		<Values / ALL >
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.6 MGW Congestion Package

Table A.14.6: Package Usage Information For Media Gateway Overload Control Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>	<Values / ALL >	
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.7 Continuity Package

Table A.14.7: Package Usage Information For Basic Continuity Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:

	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>		<Values / ALL >
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.8 Announcement Package

Table A.14.8: Package Usage Information For Announcement Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>		<Values / ALL >
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.9 Bearer Characteristics Package

Table A.14.9: Package Usage Information For Bearer Characteristics Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>	<Values / ALL >	
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.10 Generic Bearer Connection Package

Table A.14.10: Package Usage Information For Generic Bearer Connection Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:

	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>		<Values / ALL >
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.11 Call Progress Tones Generator Package v1

Table A.14.11: Package Usage Information For Call Progress Tones Generator Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>		<Values / ALL >
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.12 Basic Call Progress Tones Generator with Directionality

Table A.14.12: Package Usage Information For Basic Call Progress Tones Generator with Directionality Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>	
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>	
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>	<Values / ALL >	
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.13 Expanded Call Progress Tones Generator Package

Table A.14.13: Package Usage Information For Expanded Call Progress Tones Generator Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>	

Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>	
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>	<Values / ALL >	
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.14 Basic Services Tones Generation Package

Table A.14.14: Package Usage Information For Basic Services Tones Generation Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>	
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>	<Values / ALL >	
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.15 Bearer Control Tunnelling Package

Table A.14.15: Package Usage Information For Bearer Control Tunnelling Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>	<Values / ALL >	
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.16 Expanded Services Tones Generation Package

Table A.14.16: Package Usage Information For Expanded Services Tones Generation Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:

	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>		<Values / ALL >
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.17 Intrusion Tones Generation Package

Table A.14.17: Package Usage Information For Intrusion Tones Generation Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>		<Values / ALL >
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.18 3GUP Package

Table A.14.18: Package Usage Information For 3GUP Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>	<Values / ALL >	
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.14.19 Modification of Link Characteristics Bearer Capability

Table A.14.19: Package Usage Information For Modification of Link Characteristics Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
<name and Identity e.g. Packets Sent (rtp/ps, 0x00c/0x0004), ALL or None>	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>	<Values / ALL >	<Value / Not Applicable>
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, AUDITVALUE, AUDITCAP>		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Events	Mandatory/ Optional	Used in command:		
<name and Identity >	<M/O>	<ADD, MOD, MOVE, NOTIFY, AUDITVALUE, AUDITCAP>		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:

	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	<name and Identity>	<M/O>	<Values / ALL>	<Value / Not Applicable>
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
<name and Identity >	<M/O>	<ADD, MOD, MOVE, SUBTRACT, AUDITVALUE, AUDITCAP>		<Values / ALL >
Error Codes	Mandatory/ Optional			
<number>	<M/O>			

A.15 Mandatory support of SDP and Annex C information elements

Table A.15: Supported Annex C and SDP information elements

Information Element	Annex C Support	SDP Support
v-line	"SDP_V "	
m-line	"SDP_M "	<port> <transport> and <fmt-list> are required. Both static and dynamic payload types shall be supported.
c-line	"SDP_C "	<connection address> required
a-line	"SDP_A "	For a dynamic RTP payload type, for each codec information on the codec type shall be provided in a separate SDP "a=rtpmap "-line and possibly additional SDP "a=fmtp "-line(s). See Clause 10.2.
b-line	"SDP_B "	B:RS and b:RR bandwidth modifiers required
NOTE: SDP or SDP_equivalents are only used for terminations towards the IM CN Subsystem.		

A.16 Optional support of SDP and Annex C information elements

Table A.16: Optional Supported Annex C and SDP information elements

Information Element	Annex C Support	SDP Support

A.17 Procedures

A.17.1 Call Independent Procedures

See clause 14.

A.17.2 IMS Terminations Procedures

See clause 15.

A.17.3 TDM Terminations Procedures

See clause 16.

A.17.4 BICC Terminations Procedures

See clause 17.

Annex B (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2004-09	CN#25				Approved in CN#25	2.0.0	6.0.0
2005-03	CN#27	NP-050045	001	1	Introduction Of Formal Profile	6.0.0	6.1.0
			002	1	Corrections to Mn Specification		
2005-06	CT#28	CP-050208	0001	4	Introduction Of Formal Profile	6.1.0	6.2.0
		CP-050208	0005		Inclusion of Insert Digit Procedure at IMS termination		
2005-09	CT#29	CP-050442	0007	3	Alignment of Mn Profile with ITU template and Mc interface decisions	6.2.0	6.3.0

History

Document history		
V6.0.0	January 2005	Publication
V6.1.0	March 2005	Publication
V6.2.0	June 2005	Publication
V6.3.0	September 2005	Publication