

ETSI TS 129 332 V14.0.0 (2017-04)



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
Media Gateway Control Function (MGCF)
- IM Media Gateway;
Mn interface
(3GPP TS 29.332 version 14.0.0 Release 14)**



Reference

RTS/TSGC-0429332ve00

Keywords

GSM,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:
<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the only prevailing document is the print of the Portable Document Format (PDF) version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at
<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:
<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2017.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.
3GPP™ and **LTE™** are Trade Marks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.
GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Foreword.....	2
Modal verbs terminology.....	2
Foreword.....	7
1 Scope	8
2 References	8
3 Definitions, symbols and abbreviations	11
3.1 Definitions	11
3.2 Symbols.....	11
3.3 Abbreviations	11
4 UMTS capability set.....	12
4.1 Capability set.....	12
5 Naming conventions.....	13
5.1 MGCF/IM-MGW naming conventions	13
5.2 Void.....	13
6 Topology descriptor	13
7 Transaction timers	13
8 Transport	13
9 Multiple Virtual MG	13
10 Formats and codes	13
10.1 Signalling Objects	13
10.2 Codec Parameters	17
10.2.1 AMR and AMR-WB Codecs.....	17
10.2.2 DTMF Payload Type	18
10.2.3 Other Codecs	18
10.2.3.1 G.711 Codec.....	19
10.2.3.2 Clearmode	19
10.2.3.3 Silence suppression and comfort noise	19
10.2.3.4 VBD codec.....	19
10.2.3.5 Real-Time Text Telephony Media	20
10.2.3.6 T.38 FAX	20
11 Mandatory Support of SDP and H.248 Annex C information elements	21
12 General on packages and Transactions.....	21
12.1 Profile Details.....	21
13 Void.....	21
14 Call independent H.248 transactions.....	21
15 Transactions towards IM CN Subsystem	21
15.2 IMS packages	21
16 Transactions towards ISUP	22
16.1 Procedures relating to a termination towards ISUP	22
16.2 ISUP packages.....	22
17 Transactions towards BICC.....	22
17.1 Procedures related to a termination towards BICC	22
17.2 BICC packages	22

Annex A (normative):	Profile Description	23
A.1	Profile Identification.....	23
A.2	Summary	23
A.3	Gateway Control Protocol Version	23
A.4	Connection Model	23
A.5	Context Attributes	24
A.6	Terminations.....	24
A.6.1	Termination Names.....	24
A.6.1.1	General.....	24
A.6.1.2	ASN.1 Encoding	24
A.6.1.2.1	General Structure.....	24
A.6.1.2.2	Termination naming convention for TDM terminations	25
A.6.1.3	ABNF coding:	25
A.6.1.3.1	General Structure.....	25
A.6.1.3.2	Termination Naming Convention for TDM Terminations	25
A.6.1.3.1.1	Naming Structure.....	25
A.6.1.3.1.2	Syntactical Specification.....	26
A.6.1.3.1.3	Wildcarding	27
A.6.1.3.1.4	Heterogeneous TDM Port Configurations	27
A.6.1.3.2	Termination Naming Convention for Ephemeral Terminations	27
A.6.1.3.2.1	Naming Structure	27
A.6.1.3.2.2	Syntactical Specification.....	27
A.6.2	Multiplexed terminations	28
A.7	Descriptors	28
A.7.1	Stream Descriptor	28
A.7.1.1	Local Control Descriptor.....	28
A.7.2	Events Descriptor.....	29
A.7.3	EventBuffer Descriptor.....	30
A.7.4	Signals Descriptor.....	30
A.7.5	DigitMap Descriptor	32
A.7.6	Statistics Descriptor	32
A.7.7	ObservedEvents Descriptor	32
A.7.8	Topology Descriptor	32
A.7.9	Error Descriptor	32
A.7.10	TerminationState Descriptor.....	33
A.8	Command API.....	33
A.8.1	Add	33
A.8.2	Modify	33
A.8.3	Subtract.....	34
A.8.4	Move.....	34
A.8.5	Auditvalue.....	35
A.8.6	Auditcapability	35
A.8.7	Notify.....	35
A.8.8	Service Change	36
A.8.9	Manipulating and auditing context attributes.....	37
A.9	Generic command syntax and encoding.....	37
A.10	Transactions	38
A.11	Messages	38
A.12	Transport	39
A.13	Security	39
A.14	Packages.....	40
A.14.1	Generic Package	44
A.14.2	Base Root Package.....	45
A.14.3	Basic DTMF Generator Package	46
A.14.4	Basic DTMF Detection Package.....	47
A.14.5	TDM Circuit Package	47
A.14.6	MGW Congestion Package.....	48
A.14.7	Continuity Package	48
A.14.8	Announcement Package.....	49
A.14.9	Bearer Characteristics Package.....	49
A.14.10	Generic Bearer Connection Package.....	50
A.14.11	Call Progress Tones Generator Package v1	51

A.14.12	Basic Call Progress Tones Generator with Directionality	51
A.14.13	Expanded Call Progress Tones Generator Package	52
A.14.14	Basic Services Tones Generation Package	53
A.14.15	Bearer Control Tunnelling Package	53
A.14.16	Expanded Services Tones Generation Package	54
A.14.17	Intrusion Tones Generation Package	54
A.14.18	3GUP Package	55
A.14.19	Modification of Link Characteristics Bearer Capability	56
A.14.20	Hanging Termination Detection Package	56
A.14.21	TFO package	57
A.14.22	Media Gateway Overload Control Package	58
A.14.23	Inactivity Timer Package	58
A.14.24	MGC Information Package	59
A.14.25	RTP Package	59
A.14.26	Tone Generator Package	60
A.14.27	Tone Detection Package	60
A.14.28	H324 Package	62
A.14.29	H.245 Transport Package	63
A.14.30	IP domain connection	63
A.14.31	H.245 Transport Package for SPC use	64
A.14.32	MONA preference package	65
A.14.33	3G Interface Type package	67
A.14.34	RTCP Feedback Message package	67
A.14.35	Explicit Congestion Notificationfor RTP-over-UDP Support (ecnrous)	69
A.14.36	Differentiated Services (ds)	71
A.14.37	MG Act-as STUN Server (mgastuns)	71
A.14.38	Originate STUN Continuity Check (ostuncc)	72
A.14.39	Enhanced Revised Offer/Answer SDP Support (eroas)	73
A.15	Mandatory support of SDP and H.248 Annex C information elements	74
A.16	Optional support of SDP and H.248 Annex C information elements	77
A.17	Procedures	77
A.17.1	Call Independent Procedures	77
A.17.1.2	Profile registration	78
A.17.2	IMS Terminations Procedures	79
A.17.2.1	Summary of Procedures related to a termination towards IM CN Subsystem	79
A.17.2.2	Reserve IMS Connection Point	82
A.17.2.3	Configure IMS Resources	84
A.17.2.4	Reserve IMS Connection Point and configure remote resources	86
A.17.2.5	VOID	88
A.17.2.6	Termination heartbeat indication	88
A.17.2.7	Request RTCP-Interworking	89
A.17.2.8	Notify RTCP-Interworking	89
A.17.2.9	Signal H.245-Interworking	90
A.17.2.10	ECN Failure Indication	90
A.17.2.11	ICE Connectivity Check Result Notification	91
A.17.2.12	ICE New Peer Reflexive Candidate Notification	91
A.17.3	TDM Terminations Procedures	92
A.17.3.1	Summary Procedures related to a termination towards ISUP	92
A.17.3.2	Reserve TDM Circuit	93
A.17.3.3	Release TDM Termination	93
A.17.3.4	Termination heartbeat indication	93
A.17.4	BICC Terminations Procedures	95
A.17.4.1	Procedures related to a termination towards BICC	95
A.17.5	Multiplex Termination Procedures	97
A.17.5.1	Procedures related to a Multiplex termination	97
A.17.5.2	Add Multiplex Termination	97
A.17.5.3	Configure Multiplex Termination	99
A.17.5.4	Signal H245 Message	99
A.17.5.5	Notify H.245 Message	100
A.17.5.6	Notify MONA Preference Reception	100
A.17.5.7	Notify MONA Preference Completed	101
A.17.5.8	Signal SPC	101

A.17.5.9	Notify SPC	102
A.17.5.10	Notify MPC	102
A.17.5.11	Notify Detection of Legacy Interworking	103
A.17.5.12	Stop MPC	103
A.17.5.13	Stop SPC	104
A.17.5.14	Stop MONA Negotiation	105
A.17.6	SIP-I on Nc Terminations Procedures	106
A.17.6.1	Summary of Procedures related to a termination towards SIP-I on Nc CN Subsystem	106
Annex B (normative):	Void	108
Annex C (normative):	Void	109
Annex D (informative):	Change history	110
History		113

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

1 Scope

The present document describes the protocol to be used on the Media Gateway Control Function (MGCF) – IM Media Gateway (IM-MGW) interface. This interface provides the Media Gateway Control for interworking between the IP Multimedia Subsystem (IMS) and CS domain (ISUP, BICC and SIP-I). The basis for this protocol is the H.248 protocol as specified in ITU-T. The IMS architecture is described in 3GPP TS 23.228 [1]. The interaction of the MGCF-IM MGW interface signalling procedures in relation to the SIP, and BICC/ISUP signalling at the MGCF are described in 3GPP TS 29.163[4].

The interaction of the MGCF-IM MGW interface signalling procedures in relation to the IMS SIP and SIP-I on Nc at the MGCF are described in 3GPP TS 29.235[47].

This specification describes the application of H.248 on the Mn interface. Required extensions use the H.248 standard extension mechanism. In addition certain aspects of the base protocol H.248 are not needed for this interface and thus excluded by this profile.

In addition this profile provides support for PSTN/ISDN Emulation as required by ETSI TISPAN.

The specification contains a normative Annex defining the H.248.1 Profile in accordance with ITU-T recommendations for H.248.1 applications. Where there exists any contradiction between the normative Annex A and the rest of the specification, the Normative Annex shall take precedence. The main body of the specification provides an introduction to the use of the profile for the Mn interface and introduces any specific functionality (e.g. new packages) associated to the Mn.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 23.228: "IP Multimedia Subsystem (IMS); Stage 2".
- [2] 3GPP TS 29.007: "General requirements on interworking between the Public Land Mobile Network (PLMN) and the Integrated Services Digital Network (ISDN) or Public Switched Telephone Network (PSTN)".
- [3] 3GPP TS 29.205: "Application of Q.1900 series to Bearer Independent CS Network architecture; Stage 3".
- [4] 3GPP TS 29.163: "Interworking between the IM CN subsystem and CS networks – Stage 3".
- [5] 3GPP TS 29.232: "Media Gateway Controller (MGC); Media Gateway (MGW) interface; Stage 3".
- [6] 3GPP TS 26.226: "Cellular Text Telephone Modem; General Description".
- [7] 3GPP TS 26.103: "Speech codec list for GSM and UMTS".
- [8] Void
- [9] ITU-T Recommendation H.248.1 (05/2002): "Gateway Control Protocol: Version 2" including the Corrigendum1 for Version 2 (03/04).
- [10] ITU-T Recommendation H.248.8 (09/2005): "Error Codes and Service Change Reason Description".

- [11] ITU-T Recommendation H.248.2 (01/2005): "Facsimile, text conversation and call discrimination packages".
- [12] ITU-T Recommendation H.248.10 (07/2001): "Media Gateway Resource Congestion Handling Package".
- [13] Void
- [14] ITU-T Recommendation Q.1950 (12/2002): "Call Bearer Control Protocol".
- [15] IETF RFC 2960: "Stream Control Transmission Protocol".
- [16] IETF RFC 4867: "RTP Payload Format and File Storage Format for the Adaptive Multi-Rate (AMR) and Adaptive Multi-Rate Wideband (AMR-WB) Audio Codecs".
- [17] IETF RFC 4566: "SDP: Session Description Protocol".
- [18] IETF RFC 2833: "RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals".
- [19] Void
- [20] Void
- [21] 3GPP TS 29.415: "Core Network Nb Interface User Plane Protocols".
- [22] 3GPP TS 23.153: "Out of band transcoder control".
- [23] IETF RFC 768: "User Datagram Protocol".
- [24] IETF RFC 3332: "Signaling System 7 (SS7) Message Transfer Part 3 (MTP3) - User Adaptation Layer (M3UA)".
- [25] 3GPP TS 29.202: "SS7 Signalling Transport in Core Network".
- [26] ITU-T Recommendation H.248.7 (03/2004): "Generic Announcement Package".
- [27] ITU-T Recommendation H.248.36 (09/2005): "Hanging Termination Detection Package".
- [28] ITU-T Recommendation H.248.11 (11/2002): "Media gateway overload control package".
- [29] ITU-T Recommendation H.248.14 (03/2009): "Inactivity timer package".
- [30] ITU-T Recommendation H.248.45 (05/2006): "MGC Information Package".
- [31] Void
- [32] IETF RFC 3555: "MIME Type Registration of RTP Payload Formats".
- [33] IETF RFC 3551: "RTP Profile for Audio and Video Conferences with Minimal Control".
- [34] Void
- [35] IETF RFC 4040: "RTP Payload Format for a 64 kbit/s Transparent Call".
- [36] IETF RFC 3389: "Real-time Transport Protocol (RTP) Payload for Comfort Noise (CN)".
- [37] ITU-T Recommendation V.152 (01/2005): "Procedures for supporting voice-band data over IP networks" including Corrigendum 1.
- [38] ITU-T Recommendation H.248.4 (12/2009): "Gateway control protocol: Transport over Stream Control Transmission Protocol (SCTP)".
- [39] IETF RFC 3556: "Session Description Protocol (SDP) Bandwidth Modifiers for RTP Control Protocol (RTCP) Bandwidth".
- [40] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".

- [41] ITU-T Recommendation H.248.12 (07/2001): "Gateway control protocol: H.248.1 packages for H.323 and H.324 interworking".
- [42] ITU-T Recommendation H.248.12 Amendment 2 (08/2007): "Gateway control protocol: H.248.1 packages for H.323 and H.324 interworking Amendment 2: Transport Mechanism".
- [43] IETF RFC 3309: "Stream Control Transmission Protocol (SCTP) Checksum Change".
- [44] ITU-T Recommendation H.248.41 (05/2006): "IP Domain Connection package".
- [45] Void
- [46] ITU-T Recommendation H.248.72 (12/2009): "Gateway control protocol: ITU-T H.248 support for media-oriented negotiation acceleration (MONA)".
- [47] 3GPP TS 29.235: "Interworking between SIP-I based circuit-switched core network and other networks".
- [48] 3GPP TS 23.231: "SIP-I based circuit-switched core network; Stage 2".
- [49] ITU-T Recommendation H.248.71 (02/2010): "Gateway Control Protocol: RTCP support packages".
- [50] IETF RFC 4103: "RTP Payload for Text Conversation".
- [51] ITU-T Recommendation T.140: "Text conversation presentation protocol".
- [52] IETF RFC 4102: "Registration of the text/red MIME Sub-Type".
- [53] IETF RFC 2198: "RTP Payload for Redundant Audio Data".
- [54] ITU-T Recommendation V.18 (11/00): "Operational and interworking requirements for DCEs operating in the text telephone mode" including V.18 (2000) Amendment 1 (11/02): "Harmonization with ANSI TIA/EIA-825 (2000) text phones".
- [55] ITU-T Recommendation G.168 (03/2009): "Digital network echo cancellers".
- [56] Void
- [57] Void
- [58] Void
- [59] IETF RFC 4145: "TCP-Based Media Transport in the Session Description Protocol (SDP)".
- [60] IETF RFC 4585: "Extended RTP Profile for Real-time Transport Control Protocol (RTCP) - Based Feedback (RTP/AVPF)".
- [61] ITU-T Recommendation X.690: "ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)".
- [62] 3GPP TS 26.114: "IP Multimedia Subsystem (IMS); Multimedia Telephony; Media handling and interaction".
- [63] 3GPP TS 22.153: "Multimedia Priority Service".
- [64] ITU-T Recommendation H.248.52 (06/2008): "Gateway control protocol: QoS support packages".
- [65] ITU-T Recommendation T.38 (09/2010): "Procedures for real-time Group 3 facsimile communication over IP networks".
- [66] ITU-T Recommendation H.248.82 (03/2013): "Gateway control protocol: Explicit Congestion Notification Support".
- [67] ITU-T Recommendation H.248.50 (2010) Corrigendum 1 (02/12): "Gateway control protocol: NAT traversal toolkit packages".

- [68] IETF RFC 5245: "Interactive Connectivity Establishment (ICE): A Protocol for Network Address Translator (NAT) Traversal for Offer/Answer Protocols".
- [69] 3GPP TS 24.229: "IP Multimedia Call Control Protocol based on SIP and SDP".
- [70] IETF RFC 5939: "Session Description Protocol (SDP) Capability Negotiation".
- [71] ITU-T Recommendation H.248.80 (01/2014): "Gateway control protocol: Usage of the revised SDP offer/answer model with ITU-T H.248".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the [following] terms and definitions [given in ... and the following] apply.

Context (H.248): A context is an association between a number of Terminations. The context describes the topology (who hears/sees whom) and the media mixing and/or switching parameters if more than two terminations are involved in the association.

Package (H.248): Different types of gateways may implement terminations which have differing characteristics. Variations in terminations are accommodated in the protocol by allowing terminations to have optional properties. Such options are grouped into packages, and a termination may realise a set of such packages.

Termination (H.248): A termination is a logical entity on an MGW which is the source and/or sink of media and/or control streams. A termination is described by a number of characterising properties, which are grouped in a set of descriptors which are included in commands. Each termination has a unique identity (TerminationID).

Termination Property (H.248): Termination properties are used to describe terminations. Related properties are grouped into descriptors. Each termination property has a unique identity (PropertyID).

For the purposes of the present document, the following terms and definitions as defined in 3GPP TS 29.163 [4] apply:

ICE lite

Full ICE.

3.2 Symbols

For the purposes of the present document, the following symbols apply:

Mn Interface between the media gateway control function and the IMS media gateway.

3.3 Abbreviations

For the purposes of the present document, the following abbreviations given in TR 21.905 [40] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [40].

AMR	Adaptive MultiRate
BICC	Bearer Independent Call Control
CN	Core Network
CS	Circuit-Switched
DTMF	Dual Tone Multi Frequency
CE	Congestion Experienced
ECN	Explicit Congestion Notification
FFS	For further study
GSM	Global System for Mobile communications

ICE	Interactive Connectivity Establishment
IETF	Internet Engineering Task Force
IM	IP Multimedia
IM-MGW	IP Multimedia Media Gateway
IMS	IP Multimedia Subsystem
IP	Internet Protocol
ISDN	Integrated Services Digital Network
ISUP	ISDN User Part
MG/MGW	Media GateWay
MGC	Media Gateway Controller
MGCF	Media Gateway Control Function
MIME	Multipurpose Internet Mail Extensions
MPS	Multimedia Priority Service
n.a.	not applicable
PDH	Plesiochronous Digital Hierarchy
PES	PSTN/ISDN Emulation Subsystem
PSTN	Public Switched Telephone Network
PT	Payload Type
R2	(ETSI TISPAN NGN) Release 2
RFC	Request For Comment; this includes both discussion documents and specifications in the IETF domain
RTCP	RTP Control Protocol
RTP	Real-time Transport Protocol
SCTP	Stream Control Transmission Protocol
SDH	Synchronous Digital Hierarchy
SDP	Session Description Protocol
SDPCapNeg	SDP Capability Negotiation
SIP	Session Initiation Protocol
SONET	Synchronous Optical NETwork
SS	Silence Suppression
SS7	Signalling System No. 7
STUN	Session Traversal Utilities for NAT
TDM	Time Division Multiplexing
TISPAN	Telecommunications and Internet converged Services and Protocols for Advanced Networking
TMGW	Trunking MGW
TS	Technical Specification (3GPP, ETSI)
VBD	VoiceBand Data

4 UMTS capability set

4.1 Capability set

The support of the Mn interface capability set shall be identified by the Mn profile and support of this profile shall be indicated in ServiceChange procedure.

The mandatory parts of this capability set shall be used in their entirety whenever it is used within the H.248 profile. Failure to do so will result in a non-standard implementation.

ITU-T Recommendation H.248.1 (05/02) [9] is the basis for this Capability Set. The compatibility rules for packages, signals, events, properties and statistics and the H.248 protocol are defined in ITU-T Recommendation H.248.1 [9]. Their use or exclusion for this interface is clarified in clause 12.

5 Naming conventions

5.1 MGCF/IM-MGW naming conventions

The MGCF shall be named according to the naming structure of the underlying transport protocol which carries the H.248 protocol.

For further definition of the Termination Names see Annex A.6.

5.2 Void

6 Topology descriptor

No special behaviour, for definition of use see Annex A. 5.

7 Transaction timers

No special behaviour, for definition of timers see Annex A.10.

8 Transport

Each implementation of the Mn interface should provide SCTP (as defined in IETF RFC2960 [15] and as updated by RFC3309 [43]), however other options are permitted within the profile. For further definition see Annex A12.

9 Multiple Virtual MG.

The support of multiple virtual MGW outlined in the subclause "Multiple virtual MGW" in ITU-T Recommendation H.248.1 [9] is optional.

10 Formats and codes

10.1 Signalling Objects

Table 10.1 shows the parameters which are required.

The coding rules applied in ITU-T Recommendation H.248.1 [9] for the applicable coding technique shall be followed for the UMTS capability set.

Table 10.1: required parameters

Signalling Object	H.248 Descriptor	Coding
Additional Bandwidth Properties	Remote Descriptor	The "a=bw-info" SDP attribute defined in 3GPP TS 26.114 [62], see table A.15/1.
Allowed RTCP APP message types	Remote Descriptor	The "a=3gpp_mtsi_app_adapt" SDP attribute defined in 3GPP TS 26.114 [62].
Bearer Service Characteristics	Local Descriptor or Remote Descriptor	As per Q.1950 [14]. For TMR, only values "3.1 kHz audio" or "speech" are required.
BNC Release	EventDescriptor	As for the EventsDescriptor in subclause E.1.2.1/H.248.1 "Cause"
BNC Release	ObservedEvent descriptor	As for the ObservedEventsDescriptor in subclause E.1.2.1/H.248.1 "Cause"
Codec List	Local Descriptor or Remote Descriptor	<fmt list> in a single SDP m-line. For a static RTP payload type, the codec type should be implied by the RTP payload type, if not then each codec type shall be provided in a separate SDP "a=rtpmap"-line and possibly additional SDP "a=fmtp"-line(s). See Clause 10.2. For a dynamic RTP payload type, for each codec information on the codec type shall be provided in a separate SDP "a=rtpmap"-line and possibly additional SDP "a=fmtp"-line(s). See Clause 10.2. For T.38, additional SDP attributes listed in subclause 10.2.3.6 may be provided.
Context ID	NA	Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A. Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B.
Diffserv Code Point	Local Control	Defined according to the <i>Differentiated Services Code Point</i> property in ITU-T Recommendation H.248.52 [64].
ECN Enabled	Local Descriptor or Remote Descriptor	Defined according to the "ECN Enabled" property in ITU-T Recommendation H.248.82 [66].
ECN Failure	Events, Observed Events	Defined according to the "ECN Failure" Event in ITU-T Recommendation H.248.82 [66].
ECN Failure Type	ObservedEvents Descriptor	As for the ObservedEventsDescriptor Parameter "Failure Type" in ITU-T Recommendation H.248.82 [66].
ECN Initiation Method	Local Descriptor or Remote Descriptor	Defined according to "Initiation Method" property in ITU-T Recommendation H.248.82 [66].
Forward media in MPC	Signal descriptor	As for the signal "Forward Media in Preconfigured Channel" in H.248.72 [46] subclause 7.3.2
Highest Multiplex Level	Termination state	As for property "Highest multiplexing Level" in subclause 4.1.2/H.248.12 [41]
H245 message content	ObservedEvent descriptor	As for the ObservedEventDescriptor in subclause A.8.2.1.2/H.248.12a2 [42] "Contents of H.245 message".
ICE host candidate request	Local Descriptor	The "a=candidate" SDP attribute defined in IETF RFC 5245 [68] of type "host" with the transport, port and priority parameters with wildcard sign "\$" to request the allocation of a host candidate
ICE host candidate	Local Descriptor	The "a=candidate" SDP attribute defined in IETF RFC 5245 [68]
ICE lite indication	Local Descriptor	The "a=ice-lite" SDP attribute defined in IETF RFC 5245 [68].
ICE password request	Local Descriptor	The "a=ice-pwd" SDP attribute defined in IETF RFC 5245 [68] with wildcard sign "\$".
ICE password	Local Descriptor	The "a=ice-pwd" SDP attribute defined in IETF RFC 5245 [68].
ICE received candidate	Remote Descriptor	The "a=candidate" SDP attribute defined in IETF RFC 5245 [68]
ICE received password	Remote Descriptor	The "a=ice-pwd" SDP attribute defined in IETF RFC 5245 [68].
ICE received Ufrag	Remote Descriptor	The "a=ice-ufraq" SDP attribute defined in IETF RFC 5245 [68].
ICE Ufrag request	Local Descriptor	The "a=ice-ufraq" SDP attribute defined in IETF RFC 5245 [68] with wildcard sign "\$".
ICE Ufrag	Local Descriptor	The "a=ice-ufraq" SDP attribute defined in IETF RFC 5245 [68].
ICE Connectivity Check Result	Events, Observed Events	Defined according to <i>Connectivity Check Result</i> event in ITU-T Recommendation H.248.50 [67].
ICE Send Connectivity Check	Signals	Defined as the ostuncc/scc signal in ITU-T Recommendation H.248.50 [67].
ICE New Peer Reflexive Candidate	Events, Observed Events	Defined according to <i>New Peer Reflexive Candidate</i> event in ITU-T Recommendation H.248.50 [67].
ICE Send Additional Connectivity Check	Signals	Defined as the ostuncc/sacc signal in ITU-T Recommendation H.248.50 [67].
Inactivity timeout	EventDescriptor	As for the EventsDescriptor in subclause 6.2/H.248.14 "Inactivity Timeout"
Inactivity timeout	ObservedEvent descriptor	As for the ObservedEventDescriptor in subclause 6.2/H.248.14 "Inactivity Timeout "

Incoming H245 message	Event descriptor	As for the EventDescriptor in subclause A.8.2.1/H.248.12a2 [42] "Incoming H.245 message"
Incoming Multiplex table	Local Control	As for property "Incoming Multiplex Table" in subclause 4.1.5/H.248.12 [41]
Interwork H.245-RTCP	Signal descriptor	As for the EventDescriptor parameter in subclause 8.2.1.1.1/H.248.71[49] "Feedback Message Type".
IP Address	Local Descriptor or Remote Descriptor	<connection address> in SDP "c-line"
IP interface	Local control	As for the property "IP interface type" in subclause 15.2.11.1 in 3GPP TS 29.232 [5]
IP realm identifier	Local control	As for the property "IP realm identifier " in subclause 5.1.1/H.248.41[44]
Legacy Interworking Detected	Event descriptor	As for the EventDescriptor in H.248. 72 [46] subclause 7.2.3 "Legacy Detected"
mediatype	Local Descriptor or Remote Descriptor	<media> in sdp m-line "audio" for voice service, "video" for video service and "image" for T.38 service.
Mona Preference Channel reception	Event descriptor	As for the EventDescriptor in H.248. 72 [46] subclause 7.2.4 "MPC reception"
MONA Preference completed	Event descriptor	As for the EventDescriptor in H.248.72 [46] subclause 7.2.2 "MONA Preference negotiation completed"
MONA preference message content	ObservedEvent descriptor	As for the ObservedEventDescriptor in H.248.72 [46] subclause 7.2.1.2.1 "Contents of MONA preference message".
MONA Preference recv	Event descriptor	As for the EventDescriptor in H.248. 72 [46] subclause 7.2.2.1 "MONA Preference reception"
MPC MUX Code	Signal descriptor	As for the additional parameter of the signal "Forward Media in Preconfigure Channel" in H.248.72 [46] subclause 7.3.2.1
Muxcode	ObservedEvent descriptor	As for the ObservedEventDescriptor in H.248. 72 [46] subclause 7.2.4.2.1 "Mux Code".
Muxdescriptor	Multiplex Descriptor	Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A. Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B.
Outgoing H245 message	Signal descriptor	As for the signal "Outgoing H.245 Message " in subclause A.8.3.1/H.248.12a2 [42]
Outgoing H245 message content	Signal descriptor	As for the additional parameter of the signal "Outgoing H.245 Message " in subclause A.8.3.1.1/H.248.12a2 [42]
Outgoing MONA preference content	Signal descriptor	As for the additional parameter of the signal " Outgoing MONA preference message" in H.248. 72 [46] subclause 7.3.1.1.1
Outgoing MONA preferences	Signal descriptor	As for the signal "Outgoing MONA preference message " in H.248. 72 [46] subclause 7.3.1
Outgoing multiplex table	Local Control	As for property "Outgoing Multiplex Table" in subclause 4.1.6/H.248.12 [41]
Port	Local Descriptor or Remote Descriptor	<port> in SDP m-line. <transport> in SDP m-line shall be set to value "RTP/AVP" for voice or video service, and set to value "UDPTL" or "TCPTL"for T.38 service.
Priority Information	NA	Priority Indicator (subclause 6.1.1 of ITU-T Recommendation H.248.1 [9]) Binary Encoding: Encoding as per ITU-T Recommendation H.248.1 [9] Annex A "priority" context attribute Textual Encoding: Encoding as per ITU-T Recommendation H.248.1 [9] Annex B "priority" context attribute
Remote H223 capability	Local Control	As for property "Remote H.223 capability" in subclause 4.1.4/H.248.12 [41]
Reserve_Value	Local Control	ITU-T Recommendation H.248.1 [9] Mode property. Binary Encoding: Encoding as per ITU-T Recommendation H.248.1 Annex A "reserveValue" Textual Encoding: Encoding as per ITU-T Recommendation H.248.1 Annex B "reservedValueMode".
RtcpbwRR	Local Descriptor or Remote Descriptor	<bandwidth> in SDP "b:RR"-line as per IETF RFC 3556 [39].
RtcpbwRS	Local Descriptor or Remote Descriptor	<bandwidth> in SDP "b:RS"-line as per IETF RFC 3556 [39].
RTCP Filter	Event descriptor	As for the EventDescriptor parameter in subclause 8.2.1.1.1/H.248.71[49] "Feedback Message Type".

RTPpayload	Local Descriptor or Remote Descriptor	<fmt list> in SDP m-line
SCP	Event descriptor	As for the EventDescriptor parameter in H.248. 72 [46] subclause 6.2.1. 1 "SCP".
SDPCapNeg configuration	Local Descriptor or Remote Descriptor	The SDP attributes for SDP capability negotiation according to IETF RFC 5939 [70].
SDPCapNeg Supported Capabilities	Termination State	Defined according to <i>SDPCapNeg Extensions</i> property in ITU-T Recommendation H.248.80 [71].
SPC In	Observed event descriptor	As for the ObservedEventDescriptor parameter in H.248. 72 [46] subclause 6.2.2.1 "Incoming H.245 message"
SPC Out	Signal descriptor	As for the additional parameter of the signal "Outgoing H.245 Message " in H.248. 72 [46] subclause 6.3.1.1
Stream ID	Stream Descriptor	Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A. Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B.
Termination ID	NA	Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A. Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B.
Transaction ID	NA	Binary Encoding: As per ITU-T Recommendation H.248.1 [9] Annex A. Textual Encoding: As per ITU-T Recommendation H.248.1 [9] Annex B.
UpdatePicture_Event	ObservedEvent descriptor	As for the EventDescriptor parameter in subclause 8.2.1.2.1/H.248.71[49] "Update Picture ".
UpdatePicture_Signal	Signal descriptor	As for the SignalDescriptor parameter "Update Picture " in subclause 8.3.1.1.1/H.248.71[49].
NOTE: For binary encoding, the SDP equivalents "SDP_V", "SDP_M", "SDP_C", "SDP_A", and "SDP_B" in ITU-T Recommendation H.248.1 [9], Annex C.11, shall be used to encode the corresponding SDP lines. Other SDP equivalents may be used, for details see Annex A. The SDP equivalents shall be used in the order specified for the corresponding SDP lines in IETF RFC 2327 [17]. Rules for the usage of SDP in ITU-T Recommendation H.248.1 [9] shall also be applied to the SDP equivalents. SDP description types (v=, m=, a= etc.) are not encoded. CR/LF are not encoded.		

10.2 Codec Parameters

10.2.1 AMR and AMR-WB Codecs

On IMS terminations, the AMR and AMR-WB codecs are transported according to the IETF AMR RTP profile, IETF RFC 4867 [16], 3GPP TS 26.114 [62] selects options applicable within 3GPP.

IETF RFC 4867 [16] contains the MIME registration of the IETF AMR RTP profile with media type "audio" and media subtype of "AMR" and "AMR-WB". The AMR and AMR-WB codecs shall be signaled accordingly in the SDP "a=rtpmap"-line and a dynamic RTP payload type shall be used.

The selected options are expressed as MIME parameters in SDP "a=fmtp"-line. The following MIME parameters shall be supported on the Mn interface:

- "mode-set"
- "mode-change-period"

In addition the following MIME parameters may be supported on the Mn interface:

- "octet-align"
- "mode-change-neighbor" (for IMS this parameter shall be included and set to 1)
- "maxptime"
- "ptime"

For compatibility with GSM peers, the IM-MGW shall perform mode changes only in every second sent package.

Example of encoding of AMR codec

ABNF:

```

Local {
    v=0
    c=IN IP4 $
    m=audio $ RTP/AVP 96
    a=rtpmap:96 AMR/8000
    a=fmtp:96 mode-set=0,2,5,7;mode-change-period=2;mode-change-neighbor=1
a=maxptime:20
}

```

ASN.1:

```

LocalDescriptor{
    PropertyParams{
        PkgdName=0x000B001          /*SDP_V */
        value= "0"
        PkgdName=0x000B008          /*SDP_C */
        value= "IN IP4 $"
        PkgdName=0x000B00F          /*SDP_M */
        value= "audio $ RTP/AVP 96"
        PkgdName=0x000B00C          /*SDP_A */
        value= "rtpmap:96 AMR/8000"
        PkgdName=0x000B00C          /*SDP_A */
        value= "fmtp:96 mode-set=0,2,5,7;mode-change-period=2;mode-change-neighbor=1"
        PkgdName=0x000B00C          /*SDP_A */
        value= "maxptime:20"
    }}

```

NOTE: The c-line may be provided after m-line.

On RTP-CN (SIP-I) terminations speech codecs are supported according to 3GPP TS 29.232 [5] subclause 10.2.1.

10.2.2 DTMF Payload Type

On IMS and RTP-CN (SIP-I) terminations, DTMF is transported according to the IETF RFC 2833 [18] "telephone event" format.

IETF RFC 2833[18] contains the MIME registration with media type "audio" and media subtype "telephone-event". DTMF shall be signaled accordingly in the SDP "a=rtpmap"-line and a dynamic RTP payload type shall be used.

An IM-MGW supporting DTMF shall support the default options of the IETF RFC 2833 [18] "telephone event" format. Therefore, a support of optional MIME parameters of "telephone-event" is not required at the Mn interface.

10.2.3 Other Codecs

On IMS terminations, other codecs such as ITU-T codecs are transported according to the RTP payload formats in IETF RFC 3555[32]. 3GPP TS 29.163[4], clause B.2.5.4, specifies the options applicable within 3GPP.

IETF RFC 3555[32] contains the MIME registration with media type "audio" and corresponding media subtype.

For dynamic payload type being used the ITU-T codecs shall be signaled accordingly in the SDP "a=rtpmap"-line, where the selected options are expressed as MIME parameters in SDP "a=fmtp"-line.

For static payloads type being used ITU-T codecs shall be allowed to be signaled accordingly in the SDP "a=rtpmap"-line, when the selected options are expressed as MIME parameters in SDP "a=fmtp"-line. Otherwise the codec type is implied by the RTP payload type.

10.2.3.1 G.711 Codec

On IMS and RTP-CN (SIP-I) terminations, G.711 codec is transported according to IETF RFC 3551[33].

10.2.3.2 Clearmode

On IMS and RTP-CN (SIP-I) terminations, Clearmode codec is transported according to IETF RFC 4040[35].

When the MGC determines that a 64 kbit/s unrestricted bearer service is requested, the clearmode codec shall be used. A Dynamic Payload type with CLEARMODE as encoding name shall be included in both the local and remote descriptor.

The behaviour of the MGW shall then conform to IETF RFC 4040[35]. All voice and signal processing functions such as silence suppression, comfort noise insertion and gain adjustment shall be automatically turned off. The MGW shall inherit the same QoS objectives as the ISDN bearer service.

10.2.3.3 Silence suppression and comfort noise

On RTP-CN (SIP-I) terminations silence suppression and comfort noise are supported according to 3GPP TS 29.232 [5] subclause 10.2.3.4. For IMS terminations the following text applies.

Silence Suppression (SS) mode is direction-independent and shall be supported call/bearer individually. Silence suppression mode must be explicitly enabled and disabled. Default shall be a disabled SS mode.

If a codec has built-in support for silence suppression and comfort noise insertion, and an a=line has been defined in IETF RFC3551[33] or IETF RFC 3555 [32] to activate or de-activate these features, the activation or deactivation of these features shall be indicated using the a= line according to IETF RFC 3551[33] and IETF RFC 3555[32]. If the selected codec does not have built in support for silence suppression and comfort noise (CN) insertion, the CN payload code defined in RFC 3389[36] may be included in the media description.

E.g (for ITU-T Recommendation G.711 A-law codec):

```
v=0
c=IN <address type> <connection address>
m=audio <port number> RTP/AVP 8 13
a=ptime: 10
```

If the CN payload is included in the Local Descriptor, the MGW shall be prepared to receive CN packets during silence periods. This action corresponds to an implicit enabling of the SS mode in receiving direction.

If the CN payload is included in the Remote Descriptor, the MGW shall send CN packets during silence periods. This action corresponds to an implicit enabling of the SS mode in sending direction.

Comfort noise generation, voice activity detection and discontinuous transmission algorithms are outside the scope of the present document.

10.2.3.4 VBD codec

Voiceband data refers to traffic from facsimile, modem or text telephony applications.

On IMS terminations, voiceband data traffic is transported for facsimile /modem or data/ modem (but not text/modem, see sub clause 10.2.3.5) according to ITU-T Recommendation V.152 [37] and its Corrigendum 1. ITU-T Recommendation G.711 must be used as VBD codec. The RTP Payload Type (PT) codepoint, "0" or "8" or a value from the dynamic PT range, is used in the MG.

NOTE 1: Use of "0" or "8" is indicating to the MG that only inband-based VBD stimuli must be detected. Both peering MGs are consequently not directly synchronized in their state transitions between "voice" and "VBD" modes.

NOTE 2: Use of "a value from the dynamic PT range" is indicating a VBD RTP packet according to ITU-T Recommendation V.152 [37]. The MGW may offer then an enhanced VBD service.

Upon detection of voiceband facsimile/modem or data/modem data traffic, the Media Gateway shall autonomously switch from Audio mode to VBD mode with VBD codec.

Transitioning between Audio mode and VBD mode is possible in both directions. The procedures for transitioning between these two operation modes are described in ITU-T Recommendation V.152 clause 10/V.152 [37]. Any state transition requires the detection of a "VBD stimuli" (see ITU-T Recommendation V.152 clause 9/V.152 [37]). The IM-MGW shall be compliant with ITU-T Recommendation G.168 [55] on detecting VBD.

For Real-Time Text Telephony support within IMS at the IMS termination see subclause 10.2.3.5.

10.2.3.5 Real-Time Text Telephony Media

On IMS terminations, text is transported according to IETF RFC 4103 [50] "text/t140" conversation RTP payload format and coded according to ITU-T Recommendation T.140 [51].

If redundancy is used per IETF RFC 2198 [53], another payload type number needs to be provided for the redundancy format.

IETF RFC 4103 [50] contains the MIME registration with media type "text" and media subtype "t140". IETF RFC 4102 [52] contains the MIME registration with media type "text" and media subtype "red" (for redundancy coding variant).

RTP- Real-Time Text shall be signalled in a distinct SDP m-line accordingly in the SDP "a=rtpmap"-line and a dynamic RTP payload type shall be used.

Example of SDP which describes RTP Real-Time Text transport on port 11000 without redundancy:

```
m=text 11000 RTP/AVP 98
a=rtpmap:98 t140/1000
```

Example of SDP which describes RTP Real-Time Text transport on port 11000, but also utilizes IETF RFC 2198 [53] to provide two levels of redundancy for the text packets:

```
m=text 11000 RTP/AVP 100 98
a=rtpmap:98 t140/1000
a=rtpmap:100 red/1000
a=fmtp:100 98/98/98
```

When Real-Time Text Telephony is configured at the IMS Termination in the IM-MGW and G.711 encoding is configured at peer CS side Termination and the terminations are through-connected the IM-MGW shall

- monitor the CS side termination incoming PCM streams for text telephony in accordance with provisioned inband text telephony tone types at the CS side termination and, if multiple inband text telephony tone types are provisioned, in accordance with ITU-T Recommendation V.18 [54];
- forward any detected incoming text telephony media at the CS side termination towards the IMS termination text stream; and
- multiplex any Real Time Text payload received from the IMS side to the CS side termination outgoing PCM streams for text telephony in accordance with provisioned inband text telephony tone type at the CS side termination in accordance with ITU-T Recommendation V.18 [54].

10.2.3.6 T.38 FAX

FAX according to ITU-T recommendation T.38 [65] may be supported at IMS terminations at an IM-MGW and at the MGCF according to the procedures in the present Clause.

Version 2 or higher of T.38 is recommended.

An IM-MGW supporting T.38 shall support the "UDPTL/UDP" and may support "TPKT/TCP" transport of FAX.

To configure FAX terminations, the MGCF shall signal "udptl" or "tcp" in an SDP m-line and may signal the T.38 SDP attributes listed in Table 10.2.3.6.1 to the IM-MGW.

Table 10.2.3.6.1: Applicable T.38 SDP attributes at the Mn Interface.

Attribute	Remarks
T38FaxVersion	T.38 SDP attributes shall only be provisioned for Version 2 or higher. Version 0 applies if attribute is omitted.
T38MaxBitRate	
T38FaxMaxBuffer	
T38FaxMaxDatagram	
T38FaxMaxIFP	Only if T.38 version 4 is supported by the IM-MGW
T38FaxUdpEC	
T38FaxUdpECDepth	Only if T.38 version 4 is supported by the IM-MGW
T38FaxUdpFECMaxSpan	Only if T.38 version 4 is supported by the IM-MGW
T38ModemType	Only if T.38 version 4 is supported by the IM-MGW

11 Mandatory Support of SDP and H.248 Annex C information elements

See Annex A.15.

12 General on packages and Transactions

The use of "Overspecified" (e.g. range of values) and "Underspecified" (e.g. "?") parameter specification shall not be permitted except where explicitly indicated in or referenced by the Mn interface specification.

Commands on ROOT Termination shall only use the NULL Context.

12.1 Profile Details

VOID.

NOTE: Profile now defined in normative Annex A.

13 Void

14 Call independent H.248 transactions

See section A.17.1

15 Transactions towards IM CN Subsystem

15.1 Procedures related to a termination towards IM CN SubsystemFor Transactions towards IM CN Subsystem see A.17.2.

15.2 IMS packages

None

16 Transactions towards ISUP

16.1 Procedures relating to a termination towards ISUP

See section A.17.3.

16.2 ISUP packages

None

17 Transactions towards BICC

17.1 Procedures related to a termination towards BICC

See section A.17.4

17.2 BICC packages

This Clause is only applicable for terminations towards BICC Networks. The support of terminations towards BICC networks is optional.

No new packages for terminations towards BICC Networks are defined in the present specification. See Clause 12.1.14 for reused packages from other specifications.

If the Nb framing protocol (see 3GPP TS 29.415 [21]) is applied at the termination towards the BICC network, the following package shall be applied:

3GUP package (see subclause 15.1.1 of 3GPP TS 29.232 [5]); To enable bearer modification at OoBTC capable networks on Nb interface (see 3GPP TS 23.153 [22]) at the termination towards the BICC network, the following package shall be applied:

Modification of Link Characteristics Bearer Capability (see subclause 15.1.5 of 3GPP TS 29.232 [5]);

Annex A (normative): Profile Description

A.1 Profile Identification

Table A.1/1: Profile version

Profile name:	threegimscsiw
Version:	6

A.2 Summary

This Profile describes the minimum mandatory settings and procedures required to fulfil the Media Gateway control requirements for a) the interworking scenario between 3GPP IMS and 3GPP CS or PSTN/ISDN and b) the interworking scenario between NGN and PSTN/ISDN (i.e ETSI IMS-PSTN/ISDN, ETSI PES-PSTN/ISDN).

In addition optional settings and procedures are described which fulfil optional features and where supported, the minimum mandatory settings within the optional procedures and packages are identified that must be supported in order to support that feature.

"Optional" or "O" means that it is optional for either the sender or the receiver to implement an element. If the receiving entity receives an optional element that it has not implemented it should send an Error Code (e.g. 445 "Unsupported or Unknown Property", 501 "Not Implemented", etc.). "Mandatory" or "M" means that it is mandatory for the receiver to implement an element. Whether it is mandatory for the sender to implement depends on specific functions; detail of whether elements of the core protocol are mandatory to be sent are defined in the stage 2 procedures, stage 3 procedures and/or the descriptions of individual packages.

The setting or modification of elements described in the profile under the heading "Used in Command" has the meaning that the property can be set/modified with that command. The property may be present in other commands (in order to preserve its value in accordance with ITU-T H.248.1[9]) when those commands are used for other procedures that affect the same descriptor.

This profile supports Explicit Congestion Notification, Multimedia Priority Service and Rate Adaptation for Media Endpoints using Enhanced Bandwidth Negotiation.

A.3 Gateway Control Protocol Version

ITU Recommendation H.248.1 Version 2 [9] shall be the version supported.

A.4 Connection Model

Table A.4/1: Connection Model

Maximum number of contexts:	No restriction
Maximum number of terminations per context:	2 (NOTE 1) 32 (NOTE 2)
Allowed terminations type combinations in a Context	All (NOTE 3)
<p>NOTE 1: Support of 2 terminations per context is required for TISPAN. Support of more than two terminations per context (e.g. for monitoring) is optional.</p> <p>NOTE 2: Support of 32 termination per context is required for 3GPP</p> <p>NOTE 3: For TISPAN NGN R2 only the following is required:</p> <ul style="list-style-type: none"> - Context[a](IMS, TDM), - Context[b](TDM, TDM), - Context [c] (TDM), - Context [d] (IMS). 	

A.5 Context Attributes

Table A.5/1: Context attributes

Context Attribute	Supported	Values Supported
Topology	Optional (NOTE 1)	All
Priority Indicator	Optional (NOTE 2)	0-15 (NOTE 3)
Emergency Indicator	Yes	Not Applicable
NOTE 1: The "Topology" attribute is optional for example support of monitoring. If requested and not supported error code 444 shall be returned.		
NOTE 2: This Context Attribute parameter is used for MPS as specified in 3GPP TS 22.153 [63].		
NOTE 3: Priority values 11 – 15 of the Priority Indicator are reserved for MPS.		

A.6 Terminations

A.6.1 Termination Names

A.6.1.1 General

The Termination ID structure is provisioned in the MGC and MG and is known by the MG and the MGC at or before start up.

With ephemeral ATM/AAL2 and IP endpoint bearer types the internal structure of Termination ID is irrelevant for MGW and MGC and therefore Termination ID is only a numeric identifier for the termination. When bearer type is a physical timeslot within TDM circuit the Termination ID structure shall follow the Termination naming convention for TDM circuit bearer.

Ephemeral terminations are further denoted in the profile by the following:

- BICC (meaning applies to terminations towards BICC)
- BICC ATM (meaning applies to terminations towards BICC with ATM transport)
- BICC IP (meaning applies to terminations towards BICC with IP transport)
- IMS (meaning applies to terminations toward IMS)
- Multiplex (meaning applies to terminations performing multiplexing)
- RTP-CN (meaning applies to terminations towards SIP-I on Nc)

A.6.1.2 ASN.1 Encoding

A.6.1.2.1 General Structure

The following general structure of TerminationID shall be used:

4 octets shall be used for the termination ID. The following defines the general structure for the termination ID:

Termination type	X
------------------	---

Termination type:

Length 3 bits

Values:

000 Reserved

001 Ephemeral termination

010 TDM termination

011 - 110 Reserved

111 Reserved for ROOT termination Id (ROOT Termination Id = 0xFFFFFFFF)

X:

Length 29 bits.

Usage dependent on Termination type. TDM terminations specified below in subclause 5.2.2. Other usage unspecified.

The use of wildcarding for the Termination Id shall be performed using 1 octet only.

A.6.1.2.2 Termination naming convention for TDM terminations

Table C.6.1.2.2/1 ASN.1 coding

Termination type (=010)	PCM system	Individual
-------------------------	------------	------------

PCM system:

Length 24 bits

Usage unspecified. Uniquely identifies PCM interface in MGW

Individual:

Length: 5 bits

Max. of 32 individuals (timeslots) per PCM system (max. 24 for a 24 channel system)

A.6.1.3 ABNF coding:

A.6.1.3.1 General Structure

The following general structure of termination ID shall be used:

TerminationID = "ROOT" / pathName / "\$" / "*" ; according to ITU-T H.248.1 [9] Annex B.

A.6.1.3.2 Termination Naming Convention for TDM Terminations

A.6.1.3.1.1 Naming Structure

A hierarchical naming structure is recommended for physical Terminations.

The PCMSystem is recommended to follow the following physical and digital signal hierarchy:

PCMSystem = <unit-type1>_<unit #>/<unit-type2>_<unit #>/...

The <unit-type> identifies the particular hierarchy level.

Some example values of <unit-type> are:

"s", "su", "stm4", "stm1", "oc3", "ds3", "e3", "ds2", "e2", "ds1", "e1" where "s" indicates a slot number and "su" indicates a sub-unit within a slot.

Leading zeroes MUST NOT be used in any of the numbers ("#") above.

The <unit #> is a decimal number which is used to reference a particular instance of a <unit-type> at that level of the hierarchy. Value ranges always starting with one.

The number of levels and naming of those levels is based on the physical hierarchy within the Media Gateway.

Here are some examples of the Termination structure:

1. TDM Terminations at SDH STM-1 ports:

tdm/s_<Card ID>/stm1_<STM1 ID>/e1_<E1 ID>/<channel #>

e.g., tdm/s_2/stm1_3/e1_17/25

2. TDM Terminations at PDH E1 ports (e.g., for "PCM system" only applications):

tdm/s_<Card ID>/e1_<E1 ID>/<channel #>

e.g., tdm/s_2/e1_17/25

NOTE 1: This Termination naming convention may be used to align with ASN.1 TDM Termination names as defined in A.6.1.2.2. The alignment must take into account the numbering scheme of "<E1 ID>" with the "PCM system" field, and the upper level(s) are regarded as prefix ("tdm/s-<Card ID>" versus "3-bit codepoint for "TDM"").

NOTE 2: See also clause 3/H.248.33 concerning "PCM system" definition.

3. TDM Terminations at SONET OC-3 ports:

tdm/s_<Card ID>/oc3_<OC3 ID>/ds1_<DS1 ID>/<channel #>

e.g., tdm/s_2/oc3_3/ds1_17/22

A.6.1.3.1.2 Syntactical Specification

The syntax specification may be used for the population of valid TDM TerminationID structures for.

ABNF (IETF RFC 4234) is used for the syntax specification.

pathName = TDMTOKEN SLASH (PCMSYSTEM / "*")

TDMTOKEN = "tdm"

PCMSYSTEM = 0*(HierarchyLevelHIGHTOKEN SLASH) HierarchyLevelLOWTOKEN

HierarchyLevelHIGHTOKEN = (UnitTypeToken "_" UnitNumber)

HierarchyLevelLOWTOKEN = (UnitTypeToken "_" Wildcard) / Channel / Wildcard

UnitTypeToken = "ChassisToken" / "SDHTOKEN" / "SONETToken" / "PDHTOKEN"

ChassisToken = "s" / "su" ; slot, sub-unit within slot

SDHTOKEN = "stm4" / "stm1" ; relevant is capacity, but not electrical or optical interface type

SONETToken = "oc12" / "oc3"

PDHTOKEN = "ds3" / "e3" / "ds2" / "e2" / "ds1" / "e1" ; ANSI & ETSI

UnitNumber = 1*DIGIT

Channel = %d0-31 / %d0-23 ; value range E1/T1 system

Wildcard = "*"

A.6.1.3.1.3 Wildcarding

Wildcarding (CHOOSE, ALL) is allowed for number fields ("`<unit #>`").

Examples for wildcarding:

1. TDM Terminations at SDH STM-1 ports:

e.g., wildcarding on top level: `tdm/*`

e.g., wildcarding on slot level: `tdm/s_3/*`

e.g., wildcarding on STM-1 level: `tdm/s_3/stm1_4/*`

e.g., wildcarding on E1 level: `tdm/s_2/stm1_4/e1_49/*`

2. TDM Terminations at PDH E1 ports:

e.g., wildcarding on E1 level: `tdm/s_1/e1_2/*`

A.6.1.3.1.4 Heterogeneous TDM Port Configurations

An homogeneous TDM port configuration relates to a MGW with a single port type for physical Terminations. There is therefore a single TDM Termination name structure in use.

Heterogeneous TDM configurations means different port types, either by different signal hierarchies, like SDH/STM-1 and SDH/STM-4, and/or a mix of SDH and PDH interfaces. The number of port types in use is determining the number of TDM Termination name structures. With heterogeneous configurations the TDM Termination name structure may be aligned, for instance, by using the "highest common digital signal hierarchy" as highest Termination name hierarchical level. There is consequently a single TDM Termination name structure with a "flattened" hierarchy.

Example:

MGW with SDH/STM-1 and PDH/E1 ports. Common denominator is "e1", a selected TDM Termination name might be therefore a common two-level structure with "`tdm/e1_<E1 ID>/<channel #>`". The unit types "s", "su" or "stm1" are not used here.

NOTE: This concept is followed in A.6.1.2.2, ASN.1 for TDM Terminations.

A.6.1.3.2 Termination Naming Convention for Ephemeral Terminations

A.6.1.3.2.1 Naming Structure

An alphanumeric pathname structure is recommended for Ephemeral terminations:

`ephemeral/<string of alphanumeric characters or "/>`

e.g., `Ephemeral/1/0/40000`

A.6.1.3.2.2 Syntactical Specification

The syntax rules may be used for the population of valid ephemeral TerminationID structures for. ABNF (IETF RFC 4234) is used for the syntax specification.

ABNF coding:

`pathName = EphToken SLASH EPHsystem`

`EphToken = "Ephemeral" ; so called prefix`

`; The maximum length of 'pathname' is defined in Annex B.2/H.248.1.`

`EPHsystem = 0*(HierarchyLevelHIGHToken SLASH) HierarchyLevelLOWToken`

HierarchyLevelHIGHToken = 1*alphanum

HierarchyLevelLOWToken = Individual / Wildcard

alphanum = ALPHA / DIGIT

Individual = 1*DIGIT

Wildcard = "\$" / "*"

A.6.2 Multiplexed terminations

Table A.6.2/1: Multiplexed terminations

MultiplexTerminations Supported	Yes (NOTE)
NOTE : Yes for multimedia interworking and No for voice interworking.	

Table A.6.2/2: Multiplex Types Supported

Multiplex types supported:	H.223
Maximum number of terminations connected to multiplex:	TBD (NOTE)
NOTE: It is not clear what is the exact purpose of this parameter; further clarification within H.248.1 core protocol is required before this property shall be used.	

A.7 Descriptors

A.7.1 Stream Descriptor

Table A.7.1/1: Stream descriptors

Maximum number of streams per termination type	2 (NOTE)
NOTE : Value 2 for multimedia interworking and Real-Time Text interworking and value 1 for voice interworking.	

A.7.1.1 Local Control Descriptor

Table A.7.1.1/1: Local Control Descriptor

		Termination Type	Stream Type
Reserve group used:	No		
Reserve value used:	Yes (NOTE 1)	Terminations Toward IMS and RTP-CN	Not Applicable
NOTE 1: The "Reserve value" parameter is, inter alia, required for negotiation of multiple payload types, ie ITU-T Rec. G.711, comfort noise (according ITU-T Rec. G.711 Appendix II), DTMF tone relay (see RFC2833 [18]).			

Table A.7.1.1/2: Allowed Stream Modes

Termination Type	Stream Type	Allowed StreamMode Values
TDM	Not Applicable	SendOnly, RecvOnly, SendRecv, Inactive
IMS	Audio, Video, Text (NOTE 1)	SendOnly, RecvOnly, SendRecv, Inactive
BICC IP, RTP-CN	Not Applicable	SendOnly, RecvOnly, SendRecv, Inactive
BICC ATM	Not Applicable	SendOnly, RecvOnly, SendRecv, Inactive
Multiplex (NOTE 2)	Audio, Video	SendOnly, RecvOnly, SendRecv, Inactive
NOTE 1: Audio and Video for multimedia interworking, Audio and Text for Real-Time Text interworking, and Not applicable for voice interworking.		
NOTE 2: Specific for multimedia interworking.		

A.7.2 Events Descriptor

Table A.7.2/1: Events Descriptor

Events settable on termination types and stream types:	Yes		
	Event ID	Termination Type	Stream Type
	Detect_Digit(Digit) (d0 to dd, inclusive)	ALL except ROOT	Not Applicable
	BNC Established	Terminations towards BICC network	Not Applicable
	BNC Modification Failed	Terminations towards BICC network	Not Applicable
	BNC Modified	Terminations towards BICC network	Not Applicable
	Tunnel	Terminations towards BICC network with IP transport	Not Applicable
	g/cause	ALL except ROOT	Not Applicable
	g/sc	ALL except ROOT	Not Applicable
	ct/cmp	TDM	Not Applicable
	chp/mgcon	ROOT	Not Applicable
	Hangterm/thb	ALL except ROOT	Not Applicable
	ocp/mg_overload	ROOT	Not Applicable
	it/ito	ROOT	Not Applicable
	Start tone detected (tonedet/std)	RTP-CN, IMS, TDM, BICC	Only applicable to audio stream
	End Tone detected (tonedet/etd)	IMS	RTP-CN, TDM, BICC Only applicable to audio stream
	Optimal Codec Event (threegtfc/codec_modify)	TDM, BICC, RTP-CN	Not Applicable
	Codec List Event (threegtfc/distant_codec_list)	TDM, BICC, RTP-CN	Not Applicable
	TFO Status Event (threegtfc/TFO_status)	TDM, BICC, RTP-CN	Not Applicable
	Incoming H.245 message (h245tp/h245msgin, 0x00b4/0x0001)	Multiplex	Not Applicable
	MONA Preference reception (monapref/monaprefmsgin, 0x00f8/0x0001)	Multiplex	Not Applicable
	MONA Preference negotiation completed (monapref/monaprefcompl, 0x00f8/0x0002)	Multiplex	Not Applicable

	Legacy Detected (monapref/Legdet, 0x00f8/0x0003)	Multiplex	Not Applicable
	MPC reception (monapref/mpcrec, 0x00f8/0x0004)	Multiplex	Not Applicable
	RTCP Feedback Message Detection (rtcpfb/det, 0x00f6/0x0001)	IP	Not Applicable
	ECN Failure(ecnrousfail, 0x010b/0x0001)	IP	Audio, Video
	ICE New Peer Reflexive Candidate (ostuncc/nprc, 0x00c3/0x0002) – See subclause A.14.38	IP	Only applicable for full ICE
	ICE Connectivity Check Result (ostuncc/ccr, 0x00c3/0x0001) – See subclause A.14.38	IP	Only applicable for full ICE
NOTE: Events for Terminations towards BICC network dependent on option to support such interworking, e.g. not required for TISPAN NGN R2 TMGW.			
NOTE1: BNC Release event is defined in formats and codes table 10.1 and refers to the g/cause event.			

Table A.7.2/2: Event Buffer Control

Event Buffer Control used:	No
-----------------------------------	----

Table A.7.2/3: Keep active

Keepactive used on events:	Conditional (NOTE 1)
NOTE 1: Required for 3GPP, not required by TISPAN NGN R2 TMGW.	

Table A.7.2/4: Embedded events

Embedded events in an event descriptor:	No
--	----

Table A.7.2/5: Embedded signals

Embedded signals in an event descriptor:	Yes
NOTE: Used if MONA procedures are supported in the Add Multiplex Termination procedure.	

A.7.3 EventBuffer Descriptor

Table A.7.3/1: Event Buffer Descriptor

Event Buffer descriptor used:	No
--------------------------------------	----

A.7.4 Signals Descriptor

Table A.7.4/1: Signals Descriptor

Signals settable dependant on termination or streams types:		Yes	
		NOTE: "Yes" means any signal not listed below may be played on any termination or stream, except Signals on ROOT termination shall not be supported.	
<i>If yes</i>	Signal ID	Termination Type	Stream Type / ID
	ct/*	TDM	Not Applicable

	gb/*	BICC	Not Applicable
	bt/*	BICC IP	Not Applicable
	cg/rt cg/bt cg/ct	TDM	Not Applicable
	an/apf	ALL except ROOT and Multiplex	Not Applicable
	Outgoing H.245 Message (h245tp/h245msgout, 0x00b4/0x0001)	Multiplex	Not Applicable
	Outgoing MONA preference message (monapref/monaprefmsgout, 0x00f8/0x0001)	Multiplex	Not Applicable
	Forward Media in Preconfigured Channel (monapref/Preconfchannelmedia, 0x00f8/0x0002)	Multiplex	Not Applicable
	Feedback Message Sending (rtcpfb/fbmesssend, 0x00f6/0x0001)	IP	Not Applicable
	Send Additional Connectivity Check (ostuncc/sacc, 0x00c3/0x0002)	IP	Only applicable for full ICE
	Send Connectivity Check (ostuncc/scc, 0x00c3/0x0001)	IP	Only applicable for full ICE

Table A.7.4/2: Signal Lists

Signals Lists supported:		Conditional (NOTE 1)
<i>If yes</i>	Termination Type Supporting Lists:	ALL except ROOT
	Stream Type Supporting lists:	ALL
	Maximum number of signals to a signal list:	FFS<integer>
	Intersignal delay parameter supported:	No
NOTE 1: Required for 3GPP, not required for TISPAN NGN R2 TMGW.		
NOTE 2: This field requires at least version 3 of the H.248.1 protocol		

Table A.7.4/3: Overriding Signal type and duration

Signal type and duration supported:	Optional
NOTE: Not required for TISPAN NGN R2 TMGW.	

Table A.7.4/4: Notify completion

Notify completion supported:		Yes
<i>If yes</i>	SignalID	Type of completion supported
	All Tones and Announcements	TO, EV, SD and NC
RequestID Parameter Supported:	NO	
NOTE: This field requires at least version 3 of the H.248.1 protocol.		

Table A.7.4/5: Signals played simultaneously

Signals played simultaneously:	No
---------------------------------------	----

Table A.7.6/6: Keep active

Keepactive used on signals:	Conditional (NOTE 1)
NOTE 1: Required for 3GPP, not required for TISPAN NGN R2 TMGW.	

A.7.5 DigitMap Descriptor

Table A.7.5/1: DigitMap Descriptor

Digit Maps supported:	No
------------------------------	----

A.7.6 Statistics Descriptor

Table A.7.6/1: Statistics Descriptor

Statistics reported on subtract:	No (for TDM Terminations) Optional For Ephemeral Terminations (NOTE 1)
NOTE 1: This is required for TISPAN NGN R2 TMGW	

A.7.7 ObservedEvents Descriptor

Table A.7.7/1: Observed Events Descriptor

Event detection time supported:	No
--	----

A.7.8 Topology Descriptor

Table A.7.8/1: Topology Descriptor

Allowed triples:	Optional (NOTE 1) : (T1, T2, isolate) (T1, T2, oneway) (T1, T2, bothway)
NOTE 1: If not supported then error code 444 shall be returned.	

A.7.9 Error Descriptor

Table A.7.9/1: Error Codes Sent by MGCF

Supported H.248.8 Error Codes:	FFS < list of individual numbers >
Supported Error Codes defined in packages:	All error codes defined in supported packages shall be supported.

Table A.7.9/2: Error Codes Sent by MGW:

Supported H.248.8 Error Codes:	FFS < list of individual numbers >
Supported Error Codes defined in packages:	All error codes defined in supported packages shall be supported.

A.7.10 TerminationState Descriptor

Table A.7.10/1: TerminationState Descriptor

TerminationState: ServiceStates:	InService/OutOfService
TerminationState: EventBufferControl:	OFF

A.8 Command API

A.8.1 Add

Table A.8.1/1: Descriptors used by Command Add Request

Descriptors used by Add Request:	Events, Signals, Media (LocalControl, Local And Remote), Audit
---	--

Table A.8.1/2: Descriptors used by Command Add Reply

Descriptors used by Add Reply:	<p>Events, Signals, Media (LocalControl, Local And Remote), Error, Audit</p> <p>When command request excludes an Audit Descriptor, the MGW response shall only include descriptors which contained underspecified or overspecified properties in the command request. Furthermore, only those properties that were underspecified or overspecified in the request shall be sent in the reply. Exceptions to this rule are:</p> <ul style="list-style-type: none"> - The Error Descriptor - SDP properties returned in "Reserve IMS Connection Point" and "Reserve IMS Connection Point and Configure Remote Resources" procedures, as specified in A.17.2.2 and A.17.2.4
---------------------------------------	--

A.8.2 Modify

Table A.8.2/1: Descriptors used by Command Modify Request

Descriptors used by Modify Request:	Events, Signals, Media (LocalControl, Local And Remote), Audit
--	--

Table A.8.2/2: Descriptors used by Command Modify Reply

Descriptors used by Modify Reply:	<p>Events, Signals, Media (LocalControl, Local And Remote), Error, Audit</p> <p>When command request excludes an Audit Descriptor, the MGW response shall only include descriptors which contained underspecified or overspecified properties in the command request. Furthermore, only those properties that were underspecified or overspecified in the request shall be sent in the reply. Exceptions to this rule are:</p> <ul style="list-style-type: none"> - The Error Descriptor - SDP properties returned in "Configure IMS Resources" procedure as specified in A.17.2.3.
--	---

A.8.3 Subtract

Table A.8.3/1: Descriptor used by Command Subtract Request

Descriptors used by Subtract Request:	AUDIT (empty) or NONE
--	-----------------------

Table A.8.3/2: Descriptor used by Command Subtract Reply

Descriptors used by Subtract Reply:	None or Statistics When command request contains "Audit(empty)", then no statistics are returned. Otherwise, connection statistics are returned in the Subtract reply dependent on the supported packages (see clause A.14).
--	---

A.8.4 Move

Table A.8.4/1: Command Move

Move command used:	Optional(NOTE)
NOTE: If not supported then error code 443 shall be returned.	

Table A.8.4/2: Descriptors used by Move Request

Descriptors used by Move Request:	Events, Signals, Media (LocalControl, Local And Remote), Audit
--	--

Table A.8.4/3: Descriptors used by Move Reply

Descriptors used by Move Reply	Events, Signals, Media (LocalControl, Local And Remote), Error, Audit. When command request excludes an Audit Descriptor, the MGW response shall only include descriptors which contained underspecified or overspecified properties in the command request, with the exception of the Error Descriptor. Furthermore, only those properties that were underspecified or overspecified in the request shall be sent in the reply.
---------------------------------------	---

A.8.5 Auditvalue

Table A.8.5/1: Auditvalue

Audited Properties:	Property Name and Identity	Descriptor
Termination ID	TerminationState: - TDM: ALL (indicating 1 TDM group NOTE3), individual termination (NOTE 4) - ATM/IP: individual termination - Root (MGW Audit)	TerminationState Descriptor
Termination ID	MGC information (mgcinfo) TDM: Individual Termination	<u>LocalControl</u> Descriptor
Termination ID	For Packages: - Root - TDM/ATM/IP: individual termination (NOTE1)	Packages Descriptor (NOTE2)
Termination ID	None (MGW Audit) : - Root	Audit (empty) Descriptor
Termination ID	SDPCapNeg Extensions: - sdpe/*	TerminationState Descriptor
Audited Statistics:		None
Audited Signals:		None
Audited Events:		None
Packages Audit Possible		Yes
NOTE1: The purpose to audit an individual Termination is to retrieve MGC Information if supported.		
NOTE2: Support of this capability is optional.		
NOTE3: TDM Group equates to an E1 or T1 PCM System.		
NOTE 4: Auditing a single termination of a TDM group is an alternative to the wildcarded audit (TDM: ALL) to derive the service state of the TDM group. All the terminations of the TDM group share the same service state.		

A.8.6 Auditcapability

Table A.8.6/1: Auditcapability

Audited Properties:	Property Name and Identity	Descriptor
	FFS	FFS
Audited Statistics:		None
Audited Signals:		None
Audited Events:		None
NOTE: AuditCapability command is not supported by the ETSI TISPAN profile.		

A.8.7 Notify

Table A.8.7/1: Descriptors Used Notify

Descriptors used by Notify Request or Reply:	ObservedEvents, Error
NOTE : The Error Descriptor shall not be used in Notify Request.	

A.8.8 Service Change

Table A.8.8/1: Service Change Methods and Reasons Sent By MGCF

ServiceChange Methods supported:	ServiceChange Reasons supported:
Restart (NOTE1)	"901 Cold Boot" (Optional) "902 Warm Boot" (Optional)
Handoff (NOTE1, NOTE 2)	"903 MGC Directed Change" (Mandatory)
Forced (NOTE1)	"905 Termination Taken Out Of Service" (Optional)
Graceful (NOTE1)	"905 Termination Taken Out Of Service" (Optional)
<p>NOTE : When a Service Change command on the Root termination with a method other than Graceful is sent, the command shall always be sent as the only command in a message. The sending node shall always wait for the reply to a Service Change command on the Root termination with a method other than Graceful before sending further command requests. A Service Change command on the Root termination with method Graceful may be combined with other commands in a single message.</p> <p>NOTE 1: ROOT Only.</p> <p>NOTE 2: Not involving more than 1 MGCF. No support of handoff relates to a network deployment scenario with "primary H.248 systems only", which translates to no geographic redundancy of the MGCF.</p>	

Table A.8.8/2: Service Change Methods and Reasons Sent By MGW

ServiceChange Methods supported:	ServiceChange Reasons supported:
Restart	"900 Service Restored" (Mandatory) "901 Cold Boot" (Mandatory) (NOTE1) "902 Warm Boot" (Mandatory) (NOTE1) "910 Media Capability Failure " ALL except ROOT (Optional) "913 Signal Capability Failure " ALL except ROOT (Optional) "914 Event Capability Failure " ALL except ROOT (Optional)"916 Packages Change (Optional) "917 Capability Change (Optional)
Graceful	"904 Termination Malfunction" ,ALL except ROOT, (Mandatory) "905 Termination Taken Out Of Service", (Mandatory) "906 Loss Of Lower Layer Connectivity" , ALL except ROOT, (Mandatory) "907 Transmission Failure" ALL except ROOT, (Mandatory) "908 MG Impending Failure" ROOT only (Mandatory)
Forced	"904 Termination Malfunction" ,ALL except ROOT, (Mandatory) "905 Termination Taken Out Of Service" (Mandatory) "906 Loss Of Lower Layer Connectivity" ALL except ROOT, (Mandatory) "907 Transmission Failure" ALL except ROOT, (Mandatory) "908 MG Impending Failure" ROOT only (Mandatory)
Handoff (NOTE1, NOTE 2)	"903 MGC Directed Change" (Mandatory)
Disconnected (NOTE1)	"900 Service Restored" (Mandatory) "916 Packages Change (Optional) "917 Capability Change (Optional)
<p>NOTE : When a Service Change command on the Root termination with a method other than Graceful is sent, the command shall always be sent as the only command in a message. The sending node shall always wait for the reply to a Service Change command on the Root termination with a method other than Graceful before sending further command requests. A Service Change command on the Root termination with method Graceful may be combined with other commands in a single message.</p> <p>NOTE 1: ROOT Only.</p> <p>NOTE 2: In response to a MGC Ordered Re-Register.</p>	

Table A.8.8/3: Service Change Address

ServiceChangeAddress used:	No

Table A.8.8/4: Service Change Delay

ServiceChangeDelay used:	No
---------------------------------	----

Table A.8.8/5: Service Change Incomplete Flag

ServiceChange Incomplete Flag used:	No
NOTE: This field requires at least version 3 of the H.248.1 protocol.	

Table A.8.8/6: Service Change Version

Version used in ServiceChangeVersion:	2
--	---

Table A.8.8/6: Service Change Profile

ServiceChangeProfile mandatory:	Yes
--	-----

Table A.8.8/8: H.248.18 Profile negotiation

Profile negotiation as per H.248.18:	No
---	----

A.8.9 Manipulating and auditing context attributes

Table A.8.9/1: Manipulating and auditing context attributes

Context Attributes Manipulated:	Topology (Optional) , Emergency Indicator, Priority Indicator
Context Attributes Audited:	None

A.9 Generic command syntax and encoding

Table A.9/1: Encodings

Supported Encodings:	Binary (optional) (NOTE 1) Text (optional) (NOTE 2) : The receiver shall support: Short Token Notation Long Token Notation
If binary encoding, is indefinite length encoding supported:	Yes (NOTE3)
NOTE 1: For 3GPP Mn interface binary encoding is strongly recommended if only one encoding is selected to ensure interoperability.	
NOTE 2: Text encoding is required by TISPAN NGN R2 TMGW. For implementations providing both 3GPP Mn and TISPAN functionality text encoding is required as a minimum.	
NOTE3: The binary encoding rules which are applicable to the defined Abstract Syntaxes are the Basic Encoding Rules for Abstract Syntax Notation One, defined in ITU-T Recommendation X.690 [61]. Specifically in accordance with ITU-T Recommendation X.690 [61] section 7.3, alternative encodings based on the definite and indefinite form of length are permitted by the basic encoding rules as a sender's option. Receivers shall support both alternatives.	

A.10 Transactions

Table A.10/1: Transactions per Message

Maximum number of TransactionRequests / TransactionReplies / TransResponseAcks / Segment Replies per message:	2(NOTE 1) 10(NOTE 2)
NOTE 1: Maximum required by TISPAN NGN R2	
NOTE 2: Maximum required by 3GPP	

Table A.10/2: Commands per Transaction Requests

Maximum number of commands per Transaction request:	2(NOTE 1) Unspecified(NOTE 2)
NOTE 1: Maximum required by TISPAN NGN R2	
NOTE 2: Not specified by 3GPP	

Table A.10/3: Commands per Transaction Reply

Maximum number of commands per Transaction reply:	2 (NOTE 1) Unspecified (NOTE 2)
NOTE 1: Maximum required by TISPAN NGN R2	
NOTE 2: Not specified by 3GPP however for auditing with wildcarded requests (e.g TDM E1) then the reply may include up to 32 commands to indicate the termination state.	

Table A.10/4: Commands for Wildcarded Responses

Wildcarded responses may be requested for:	Modify, Subtract, AuditValue
---	------------------------------

Table A.10/5: Procedures for Wildcarded Responses

Procedures that make use of wildcarded responses:	Release Bearer, Release Termination, Audit Value, Release IMS Termination, Release TDM Termination
NOTE: Used when multiple terminations are released with one command and in audit responses where multiple terminations are implied by the audit request.	

Table A.10/6: Optional Commands

Commands able to be marked "Optional":	ALL
---	-----

Table A.10/7: Transaction Timers

Transaction Timer:	Value
normalMGExecutionTime	Provisioned
normalMGCEExecutionTime	Provisioned
MGOriGinatedPendingLimit	Provisioned
MGCOrGinatedPendingLimit	Provisioned
MGPProvisionalResponseTimerValue	Provisioned
MGCProvisionalResponseTimerValue	Provisioned

A.11 Messages

The MGC/MGW may be named according to the naming structure of the underlying transport protocol which carries the H.248 protocol.

It is however recommended that MGC and MG names are in the form of fully qualified domain names. For example the domain name of the MGC may be of the form mgc1.whatever.net and the name of the MG may be of the form mg1.whatever.net.

The "Message Identifier" in the H.248 messages may be used by the MGC and MG to identify the originator of the message.

A.12 Transport

Table A.12/1: Transport

Supported Transports:	SCTP(recommended) (NOTE1). SCTP/M3UA(optional) optional – as defined in IETF RFC 3332 [24] with options detailed in 3GPP TS 29.202 [25] (NOTE2). UDP(optional).
NOTE:	If using SCTP as defined in IETF RFC 2960 [15] the MGW shall always be the node to perform the "Initiation".
NOTE1	H.248 is "SCTP user" in this case of H.248/SCTP/IP based transport according ITU-T Rec. H.248.4 [38]. The number of used SCTP Streams for traffic of the H.248 Control Association must be defined, see § 8/H.248.4 [38]. A single SCTP Stream is the default assumption ("Single-Stream Mode") in this Profile.
NOTE2	This is slightly different with regards to SCTP encapsulation. H.248 is "M3UA user" in this case of H.248/M3UA/SCTP/IP based transport. H.248 Messages are corresponding to M3UA user protocol data units. "SCTP multistreaming" may be also applied (see § 1.4.7/RFC 3332). If not then the complete M3UA traffic is mapped on a single SCTP Stream, i.e., the Single-Stream Mode.
NOTE3	Checksum calculation for SCTP shall be supported as specified in RFC 3309 [43] instead of the method specified in RFC 2960 [15].

Table A.12/2: Segmentation

Segmentation Supported:	No
NOTE:	This field requires at least version 3 of the H.248.1 protocol.

Table A.12/3: Support of Control Association Monitoring

Control Association Monitoring Supported:	Monitoring mechanism is dependent on used H.248 transport (see Table A.12/1): SCTP: inherent capability of SCTP (NOTE 1) SCTP/M3UA: inherent capability of SCTP UDP: <ol style="list-style-type: none"> 1. H.248.14 (MGW-driven monitoring) 2. Empty AuditValue on ROOT (MGC-driven monitoring)
NOTE 1:	Use of H.248.14 [29] for this is FFS

A.13 Security

Table A.13/1: Security

Supported Security:	None
----------------------------	------

A.14 Packages

Table A.14/1: Mandatory packages

Package Name	Package ID	Version
Generic (see ITU-T Recommendation H.248.1 [9] Annex E.1);	g, (0x0001)	v1
Base Root Package (see ITU-T Recommendation H.248.1 [9] Annex E.2);	root, (0x0002)	v2
Basic Continuity Package (see ITU-T Recommendation H.248.1 [9] Annex E.10);	ct, (0x000a)	v1
TDM Circuit Package (see ITU-T Recommendation H.248.1 [9] Annex E.13);	tdmc, (0x000d)	v1
Hanging Termination Detection package (see ITU-T Recommendation H.248.36 [27]).	hangterm (0x0098)	v1

Table A.14/2: Optional packages

Package Name	Package ID	Version	Support dependent on:
Tone Detection Package (see ITU-T Recommendation H.248.1 [9] Annex E.4);	tonedet, (0x0004) This package is "extension only". It must be supported if extended but shall not be published over the protocol. It is here for information only.	v1	Mandatory for 3GPP
Basic DTMF Generator Package (see ITU-T Recommendation H.248.1 [9] Annex E.5);	dg, (0x0005)	v1	Mandatory for 3GPP
DTMF Detection Package (see ITU-T Recommendation H.248.1 [9] Annex E.6);	dd, (0x0006)	v1	Mandatory for 3GPP
Media Gateway Resource Congestion Handling Package (see ITU-T Recommendation H.248.10 [12]).	chp, (0x0029)	v1	Mandatory for 3GPP
Generic Announcement Package (see ITU-T Recommendation H.248.7 [26]). Only Fixed Part is required.	an(0x001d)	v1	3GPP applications
Bearer Characteristics Package (see ITU-T Recommendation Q.1950 [14] annex A.3).	bcp (0x001e)	v2	Terminations Towards BICC
Generic Bearer Connection Package (see ITU-T Recommendation Q.1950 [14] annex A.6).	Gb, (0x0021)	v1	Interworking with BICC
Tone Generator Package (see ITU-T Recommendation H.248.1 [9] Annex E.3);	tongen, (0x0003)	v1	This package is "extension only". It must be supported if extended but shall not be published over the protocol. It is here for information only.
Call Progress Tones Generator Package (see ITU-T Recommendation H.248.1 [9] annex E.7).	Cg, (0x0007)	v1	
Basic Call Progress Tones Generator with Directionality, (see ITU-T Recommendation Q.1950 [14] annex A.8).	bcb, (0x0023)	v1	Services provided by network
Expanded Call Progress tones Generator Package (see ITU-T Recommendation Q.1950 [14] annex A.9).	xcb, (0x0024)	v1	Services provided by network
Basic Services Tones Generation Package, (see ITU-T Recommendation Q.1950 [14] annex A.10).	srvt, (0x0025)	v1	Services provided by network
Bearer Control Tunnelling Package (see ITU-T Recommendation Q.1950 [14] annex A.7).	Bt, (0x0022)	v1	Interworking with BICC and IP transport
Expanded Services Tones Generation Package (see ITU-T Recommendation Q.1950 [14] annex A.11).	xsrvt, (0x0026)	v1	Services provided by network
Intrusion Tones Generation Package (see ITU-T Recommendation Q.1950 [14] annex A.12).	Int, (0x0027)	v1	Services provided by network
3GUP package (see subclause 15.1.1 of 3GPP TS 29.232 [5])	threegup, (0x002f)	v1	Interworking with BICN PLMN
Modification of Link Characteristics Bearer Capability (see subclause 15.1.5 of 3GPP TS 29.232 [5])	threegmlc, (0x0046)	v1	Interworking with BICN PLMN with Codec Modification
Inactivity timer package (see ITU-T Recommendation H.248.14 [29])	it, (0x0045)	v1	Only applicable for UDP transport.
TFO package (see subclause 15.2.2 of 3GPP TS 29.232 [5])	threegtfo, (0x0031)	v2	
Media Gateway Overload Control Package (see ITU-T Recommendation H.248.11 [28]).	ocp, (0x0051)	v1	

MGC Information Package (see ITU-T Recommendation H.248.45 [30])	mgcinfo, (0x00a0)	v1	This package may be supported as an operator option. For this Profile the information string shall be limited to 32 octets in length.
RTP (ITU-T Recommendation H.248.1 [9] Annex E.12) (NOTE 1)	rtp, (0x000c)	v1	Used for connection statistics
H324 package (see ITU-T Recommendation H.248.12 [41])	h324,(0x002c)	v1	Multimedia calls
H.245 Transport Package (see ITU-T Recommendation H.248.12a2 [42])	h245tp, (0x00b4)	v1	Multimedia calls
IP Domain connection package (see ITU-T Recommendation H.248.41 [44])	ipdc, (0x009d)	v1	Multiple IP realms supported
H.245 Transport Package for SPC use (see ITU-T Recommendation H.248.72 [46] subclause 6)	h245tpspc, (0x00f7)	v1	Multimedia calls with MONA
MONA preference package (see ITU-T Recommendation H.248.72 [46] subclause 7)	monapref, (0x00f8)	v1	Multimedia calls with MONA
3G Interface Type package (see subclause 15.2.11 of 3GPP TS 29.232 [5])	threegint (0x00e3)	v1	
RTCP Feedback Message package (see ITU-T Recommendation H.248.71 [49] subclause 8)	rtcpfb, (0x00f6)	v1	Multimedia interworking between the H.245 messages in 3G-324M at the CS side and the corresponding RTCP messages used by MTSI terminals at the IMS side
Explicit Congestion Notification for RTP-over-UDP Support (see ITU-T Recommendation H.248.82 [66])	ecnrous(0x010b)	v1	Support of ECN feature
Diffserv (ITU-T Recommendation H.248.52 [64])	ds, (0x008b)	v2	Support of MPS
MG Act-as STUN Server (ITU-T Recommendation H.248.50 [67])	mgastuns (0x00c2)	v1	Support of incoming STUN connectivity checks. Applicable for ICE lite and full ICE
Originate STUN Continuity Check (see ITU-T Recommendation H.248.50 [67])	ostuncc (0x00c3)	v1	Support of originating STUN connectivity checks Only applicable for full ICE
Enhanced Revised Offer/Answer SDP Support (ITU-T Recommendation H.248.80 [71])	eroas, (0x0109)	v1	Support of the SDP Capability Negotiation syntax
NOTE 1: support of RTP Package does not require support of Network Package.			

Table A.14/3: Package Provisioning Information

Package Name	Property, Parameter, Signal, Event ID	Provisioned Value:
Generic Announcement (see ITU-T Recommendation H.248.7 [26])	Fixed Announcement Play, AV	Provisioned
NOTE: This may not be required by TISPAN NGN R2 TMGW.		

A.14.1 Generic Package

Table A.14.1/1: Package Usage Information For Generic Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-	-	-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
	M	ADD, MOD, NOTIFY		
Cause (g/cause. 0x0001/0x0001) (NOTE)	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Generalcause	M	"NR" Normal Release (0x0001) "UR" Unavailable Resources (0x0002) "FT" Failure, Temporary (0x0003) "FP" Failure, Permanent (0x0004) "IW" Interworking Error (0x0005) "UN" Unsupported (0x0006)	Not Applicable
	Failure Cause (FailureCause, 0x0002)	O	Octet String	Not Applicable
Events	Mandatory/ Optional	Used in command:		
	M	ADD, MOD, MOVE, NOTIFY		
Signal Completion. (g/sc, 0x0001/0x0002)	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Signal Identity	M	pkgdName syntax	-
	Termination Method	M	"TO" (0x0001) Signal timed out or otherwise completed on its own "EV" (0x0002) Interrupted by event "SD" (0x0003) Halted by new Signals descriptor "NC" (0x0004) Not completed, other cause	-
	Signal List Id	O	Integer	-

Statistics	Mandatory/ Optional	Used in command:	Supported Values:
None	-	-	-
Error Codes	Mandatory/ Optional		
-	-		
NOTE: This event may also be used to report temporary errors in the MGW for both IMS, BICC and TDM connections where the termination is not out of service and thus sending a Service Change is inappropriate. On receipt of this event, the MGC is expected to release the connection in the MGW and force release the associated call. An example of such an error could be loss of RTP on an IMS termination.			

A.14.2 Base Root Package

Table A.14.2/1: Package Usage Information For Base Root Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
root/maxNumberOfContexts	O	AuditValue	1 and up	Implementation Specific
root/maxTerminationPerContext	O	AuditValue	See A.4	Implementation Specific
root/normalMGExecutionTime	O	MOD	Integer	Operator Defined
root/normalMGCExecutionTime	O	MOD	Integer	Operator Defined
root/MGProvisionalResponseTimerValue	O	MOD	Integer(NormalMGExecutionTime + networkdelay)	Operator Defined
root/MGCProvisionalResponseTimerValue	O	MOD	Integer(NormalMGCExecutionTime + networkdelay)	Operator Defined
root/MGCOriginatedPendingLimit	O	MOD	Integer	Operator Defined
root/MGOriginatedPendingLimit	O	MOD	Integer	Operator Defined
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
-	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-		-
Error Codes	Mandatory/ Optional			
None	-			
NOTE : All transaction timers specified in H.248 shall be supported for 3GPP				

A.14.3 Basic DTMF Generator Package

Table A.14.3/1: Package Usage Information For Basic DTMF Generator Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
DTMF character 0 ,d0	M	ADD, MOD, MOVE		
DTMF character 1 d1	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
DTMF character 2 d2	None	-	-	-
DTMF character 3 d3				
DTMF character 4 d4				
DTMF character 5 d5				
DTMF character 6 d6				
DTMF character 7 d7				
DTMF character 8 d8				
DTMF character 9 d9				
DTMF character * ds				
DTMF character # do				
DTMF character A da				
DTMF character B db				
DTMF character C dc				
DTMF character D dd				
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			
NOTE: Only the DTMF Signal Ids shall be used, not the Tone Ids within the PlayTone Signal Id.				

A.14.4 Basic DTMF Detection Package

Table A.14.4/1: Package Usage Information For Basic DTMF Generator Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-	-	-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
d0, "0" d1, "1" d2, "2" d3, "3" d4, "4" d5, "5" d6, "6" d7, "7" d8, "8" d9, "9" ds, "*" do, "#" da, "A" or "a" db, "B" or "b" dc, "C" or "c" dd, "D" or "d"	M	ADD, MOD, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.5 TDM Circuit Package

Table A.14.5/1: Package Usage Information For TDM Circuit Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
Echo Cancellation, tdmc/ec	M	ADD, MOD, MOVE	ALL	Default= Off (False)
Gain Control, tdmc/gc	Not Used	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-

Statistics	Mandatory/ Optional	Used in command:	Supported Values:
None	-	-	-
Error Codes	Mandatory/ Optional		
None	-		

A.14.6 MGW Congestion Package

Table A.14.6/1: Package Usage Information For Media Gateway Overload Control Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
MG Congestion, chp/mgcon(0x0001)	M/	MOD, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Reduction (0x0001)	M	0-100	Not Applicable
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.7 Continuity Package

Table A.14.7.1: Package Usage Information For Basic Continuity Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Continuity Test, ct/ct Respond, ct/rsp	M	ADD, MOD, MOVE		Default
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	None	-	-	-
Events	Mandatory/ Optional	Used in command:		
Completion, ct/cmp(0x0005)	M/	ADD, MOD, MOVE, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	result, res(0x0008)	M	success, failure	Not Applicable

Statistics	Mandatory/ Optional	Used in command:	Supported Values:
None	-	-	-
Error Codes	Mandatory/ Optional		
None	-		

A.14.8 Announcement Package

Table A.14.8/1: Package Usage Information For Announcement Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Fixed Announcement Play, apf(0x0001)	M	ADD, MOD, MOVE		<Value / Not Applicable>
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	Announcement name, an(0x0001)	M	enumeration	<Value / Not Applicable>
	Number Of Cycles, noc(0x0002)	M	Any Integer	-
	Announcement Variant, av(0x0003)	O	string	-
Announcement Direction, di(0x0004)	M	Internal, External	-	-
Events	Mandatory/ Optional	Used in command:		
None	-	-		-
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
-	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.9 Bearer Characteristics Package

Table A.14.9/1: Package Usage Information For Bearer Characteristics Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
BNC Characteristics (BCP/BNCChar,0x001e/0x01)	M	ADD	AAL type 2 / IP/RTP	Not Applicable
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
-	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-

	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-		-
Error Codes	Mandatory/ Optional			
None	-			

A.14.10 Generic Bearer Connection Package

Table A.14.10/1: Package Usage Information For Generic Bearer Connection Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Establish BNC (GB/EstBNC,0x0021/0x01)	M	ADD, MOD		Not Applicable
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	Not Applicable	-	-	Not Applicable
Modify BNC (GB/ModBNC,0x0021/0x02)	O	MOD		Not Applicable
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	Not Applicable	-	-	Not Applicable
Release BNC (GB/RelBNC,0x0021/0x03)	M (NOTE 1)	MOD		Not Applicable
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	General cause (Generalcause,0x01)	O	Normal Release/ Unavailable Resources/ Failure Temporary/ Failure Permanent/ Interworking Error/ Unsupported	Not Applicable
	Failure Cause (Failurecause,0x02)	O	OCTET STRING	Not Applicable
	Reset (Reset,0x03)	O	0/ 1	Not Applicable
Events	Mandatory/ Optional	Used in command:		
BNC Change (GB/BNCCChange,0x0021/0x01)	M	ADD, MOD, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Type (Type ,0x01)	M	Bearer Established / Bearer Modified/ Bearer Modification Failure	Not Applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Type (Type,0x01)	M/	Bearer Established / Bearer Modified/ Bearer Modification Failure	Not Applicable
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None				
Error Codes	Mandatory/ Optional			
None				
NOTE 1: Mandatory for BICC ATM Terminations, not used otherwise				

A.14.11 Call Progress Tones Generator Package v1

Table A.14.11/1: Package Usage Information For Call Progress Tones Generator Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Ringing Tone, cg/rt	M	ADD, MOD, MOVE		Not Applicable
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Busy Tone, cg/bt	O	ADD, MOD, MOVE		Not Applicable
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Congestion Tone, cg/ct	O	ADD, MOD, MOVE		Not Applicable
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.12 Basic Call Progress Tones Generator with Directionality

Table A.14.12/1: Package Usage Information For Basic Call Progress Tones Generator with Directionality Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
	O	ADD, MOD, MOVE		Value
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:

Dial Tone (bcg/bdt, 0x0023/0x0040) Ringing Tone (bcg/brt,0x0023/0x0041) Busy Tone (bcg/bbt,0x0023/0x0042) Congestion Tone (bcg/bct,0x0023/0x0043) Special Information Tone (bcg/bsit,0x0023/0x0044) Warning Tone (bcg/bwt,0x0023/0x0045) Payphone Recognition Tone (bcg/bpt,0x0023/0x0046) Call Waiting Tone (bcg/bcw,0x0023/0x0047) Caller Waiting Tone (bcg/bcr, 0x0023/0x0048) Pay Tone (bcg/bpy, 0x0023/0x0049)	Tone Direction (btd, 0x0001)	M	Internal / External	Default=External
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-		-
Error Codes	Mandatory/ Optional			
None	-			

A.14.13 Expanded Call Progress Tones Generator Package

Table A.14.13/1: Package Usage Information For Expanded Call Progress Tones Generator Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Comfort Tone (xcg/cmft,0x0024/0x004a) Off-hook warning Tone (xcg/roh, 0x0024/0x004b) Negative Acknowledgement (xcg/nack,0x0024/0x004c) Vacant Number Tone (xcg/vac, 0x0024/0x004d) Special Conditions Dial Tone (xcg/spec,0x0024/0x004e)	O	ADD, MOD, MOVE		Value
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	Tone Direction (btd, 0x0001)	M	Internal / External	Default=External
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-

	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.14 Basic Services Tones Generation Package

Table A.14.14/1: Package Usage Information For Basic Services Tones Generation Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Recall Dial Tone (srvtn/rdt,0x0025/0x004f)	O	ADD, MOD, MOVE		Value
Confirmation Tone (srvtn/conf,0x0025/0x0050)	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
Held Tone (srvtn/ht,0x0025/0x0051)	Tone Direction (btd, 0x0001)	M	Internal / External	Default=External
Message Waiting Tone (srvtn/mwt,0x0025/0x0052)				
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.15 Bearer Control Tunnelling Package

Table A.14.15/1: Package Usage Information For Bearer Control Tunnelling Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
Tunneling Options (BT/TunOpt, 0x0022/0x01)	M	ADD, MOD	1 / 2	Not Applicable
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Bearer Information Transport (BT/BIT, 0x0022/0x01)	M	ADD, MOD		Not Applicable
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
Bearer Information Tunnel (BIT,0x01)		M	Octet String	Not Applicable
Events	Mandatory/ Optional	Used in command:		
Tunnel Indication (BT/TIND. 0x0022/0x01)	M	ADD, MOD, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Not applicable	-	-	-

	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Bearer Information transport (BIT,0x01)	M	Octet String	Not Applicable
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-		-
Error Codes	Mandatory/ Optional			
None	-			

A.14.16 Expanded Services Tones Generation Package

Table A.14.16/1: Package Usage Information For Expanded Services Tones Generation Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Call Transfer Dial Tone (xsrvtv/xferdt,0x0026/0x0053) Call Forward Tone (xsrvtv/cft,0x0026/0x0054) Credit Card service Tone (xsrvtv/ccst,0x0026/0x0055) Special Recall Dial Tone (xsrvtv/srdt,0x0026/0x0056)	O	ADD, MOD, MOVE		Value
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	Tone Direction (btd, 0x0001)	M	Internal / External	Default=External
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
-	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-		-
Error Codes	Mandatory/ Optional			
None	-			

A.14.17 Intrusion Tones Generation Package

Table A.14.17/1: Package Usage Information For Intrusion Tones Generation Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
	O	ADD, MOD, MOVE		Value
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:

Intrusion Pending Tone (int/pend,0x0027/0x0057) Intrusion Tone (int/int,0x0027/0x0058) Intrusion Reminder Tone (int/rem,0x0027/0x0059) Toll Break-In Tone (int/tbi,0x0027/0x005a) Intrusion Queue Tone (int/intque,0x0027/0x005b) Busy Verification Tone (int/bv,0x0027/0x005c)	Tone Direction (btd, 0x0001)	M	Internal / External	Default=External
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-		-
Error Codes	Mandatory/ Optional			
None	-			

A.14.18 3GUP Package

Table A.14.18/1: Package Usage Information For 3GUP Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
UP Mode of operation (threegup/mode, 0x002f/0x0001)	M	ADD, MOD, MOVE	See 3GPP TS 29.232	See 3GPP TS 29.232
UP versions (threegup/ upversions, 0x002f/0x0002)	M	ADD, MOD, MOVE	See 3GPP TS 29.232	See 3GPP TS 29.232
Delivery of erroneous SDUs (threegup/ delerrsdu, 0x002f/0x0003)	M	ADD, MOD, MOVE	See 3GPP TS 29.232	See 3GPP TS 29.232
Interface (threegup/ interface, 0x002f/0x0004)	M	ADD, MOD, MOVE	See 3GPP TS 29.232	See 3GPP TS 29.232
Initialisation Direction (threegup/ initdir, 0x002f/0x0005)	M	ADD, MOD, MOVE	See 3GPP TS 29.232	See 3GPP TS 29.232
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-

Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-		-
Error Codes	Mandatory/ Optional			
None	-			

A.14.19 Modification of Link Characteristics Bearer Capability

Table A.14.19/1: Package Usage Information For Modification of Link Characteristics Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
-	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
Bearer Modification Support Event. (threegmlc/mod_link_supp, 0x0046/0x0001)	M	ADD, MOD, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
None	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-		-
Error Codes	Mandatory/ Optional			
None	-			

A.14.20 Hanging Termination Detection Package

Table A.14.20/1: Package Usage Information For Hanging Termination Detection Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
-	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
Termination Heartbeat	M	ADD, MOD, MOVE, AUDITVALUE, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Timer X	M	ALL	0 (no heartbeat message)

	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None				
Error Codes	Mandatory/ Optional			

A.14.21 TFO package

Table A.14.21/1: Package Usage Information For TFO

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
TFO Activity Control (threegtfocontrol / tfoenable, (0x0031/0x0001))	M	ADD, MOD, MOVE	See 3GPP TS 29.232	See 3GPP TS 29.232
TFO Codec List (threegtfoclist / codeclist, (0x0031/0x0002))	M	ADD, MOD, MOVE	See 3GPP TS 29.232	See 3GPP TS 29.232
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None				
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
Events	Mandatory/ Optional	Used in command:		
Optimal Codec Event (threegtfoevent / codec_modify, (0x0031/0x0010))	O	ADD, MOD, MOVE, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None			
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Optimal Codec Type	M	See 3GPP TS 29.232	See 3GPP TS 29.232
Codec List Event (threegtfoevent / distant_codec_list, (0x0031/0x0012))	O	ADD, MOD, MOVE, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None			
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Distant Codec List	M	See 3GPP TS 29.232	See 3GPP TS 29.232
TFO Status Event (threegtfoevent / TFO_status) (0x0031/0x0014)	O	ADD, MOD, MOVE, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None			
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	TFO Status	M	See 3GPP TS 29.232	See 3GPP TS 29.232
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None				
Error Codes	Mandatory/ Optional			

A.14.22 Media Gateway Overload Control Package

Table A.14.22/1: Media Gateway Overload Control Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-	-	-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
MG_Overload ocp/mg_overload	M	MOD, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-	-	-
Error Codes	Mandatory/Optional			
None	-			

A.14.23 Inactivity Timer Package

Table A.14.23/1: Inactivity Timer Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-	-	-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
Inactivity Timeout, it/ito	M	MOD, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Maximum Inactivity Time, mit	M	Any integer	Unspecified, if not sent a value must be provisioned.
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-	-	-
Error Codes	Mandatory/ Optional			
None	-			

A.14.24 MGC Information Package

Table A.14.24/1: MGC Information Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
Data Block, MGInfo/db	M	ADD, MOD, AUDITVALUE	A range of 0 to 32 octets	An empty string
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.25 RTP Package

Table A.14.25/1: RTP Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
Payload Transition, rtp/pltrans	-	NA		
	Event Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	rtppayload, rtppltype	-	A valid encoding name	-

Statistics	Mandatory/ Optional	Used in command:	Supported Values:
Packets Sent, rtp/ps	M	SUBTRACT REPLY	ALL
Packets Received, rtp/pr	M	SUBTRACT REPLY	ALL
Packet Loss, rtp/pl	M	SUBTRACT REPLY	ALL
Jitter, rtp/jit	M	SUBTRACT REPLY	ALL
Delay, rtp/delay	M	SUBTRACT REPLY	ALL
Error Codes	Mandatory/ Optional		
None	-		

A.14.26 Tone Generator Package

Table A.14.26/1: Package Usage Information For Tone Generator Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Play Tone (tonegen/pt,0x0003/0x0001)	Not Used	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
-	-	-	-	
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.27 Tone Detection Package

Table C.14.27/1: Package Usage Information For Tone Detection Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:

None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
Start tone detected (tonedet/std, 0x0004/0x0001)	O	ADD, MOD, MOVE, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Tone ID List (tl,0x0001)	M	wildcard	Not Applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Tone ID (tid,0x0003)	M	Value	Not Applicable
Events	Mandatory/ Optional	Used in command:		
End Tone detected (tonedet/etd, 0x0004/0x0002)	M	ADD, MOD, MOVE, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Tone ID List (tl,0x0001)	M	wildcard	Not Applicable
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Tone ID (tid,0x0003)	M	Value	Not Applicable
	Duration (dur,0x0002)	O	Value	Not Applicable
Events	Mandatory/ Optional	Used in command:		
Long Tone detected (tonedet/ltd, 0x0004/0x0003)	Not Used	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:

	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.28 H324 Package

Table A.14.28/1: Package Usage Information For H324 Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
Communication mode (h324/cmod,0x002c/0x0001)	Not used	-	-	-
Highest Multiplexing Level (h324/muxlv,0x002c/0x0002)	Not Used	-	-	Based on capability of IM-MGW
Demultiplex (h324/demux,0x002c/0x0003)	Not used	-	-	-
Remote H.223 capability (h324/h223capr,0x002c/0x0004)	M	MOD	OCTET STRING	Not Applicable
Incoming Multiplex Table (h324/muxtbl_in,0x002c/0x0005)	M	MOD	OCTET STRING	Not Applicable
Outgoing Multiplex Table (h324/muxtbl_out,0x002c/0x0006)	M	MOD	OCTET STRING	Not Applicable
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
MUXPDU sent (h324/muxsent,0x002c/0x0001)	Not used	-	-	
MUXPDU received (h324/muxrec,0x002c/0x0002)	Not used	-	-	
MUXPDU error (h324/muxerr,0x002c/0x0003)	Not used	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.29 H.245 Transport Package

Table A.14.29/1: Package Usage Information For H.245 Transport Package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Outgoing H.245 Message (h245tp/h245msgout, 0x00b4/0x0001)	M	MOD		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	Contents of H.245 message (h245mc,0x0001)	M	OCTET STRING	-
Events	Mandatory/ Optional	Used in command:		
Incoming H.245 message (h245tp/h245msgin, 0x00b4/0x0001)	M	ADD, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Contents of H.245 message (h245mc,0x0001)	M	OCTET STRING	Not Applicable
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.30 IP domain connection

Table C.14.30: Package usage information for IP domain connection package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
IP Realm Identifier (ipdc /realm, 0x009d /0x0001)	M	ADD	String	Operator Defined (NOTE1)
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-

	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			
NOTE1: A default IP realm may be configured such that if the MGW has not received the IP realm identifier and the MGW supports multiple IP realms then the default IP realm shall be used.				

A.14.31 H.245 Transport Package for SPC use

Table A.14.31/1: Package Usage Information For H.245 Transport Package for SPC use

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None (NOTE 1)	M	MOD		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	Signalling Preconfigured Channel (spc, 0x0002)	O	ON OFF	OFF
	Repetition (rep, 0x0003)	O	ON OFF	ON
Events	Mandatory/ Optional	Used in command:		

None (NOTE 2)	M	ADD, NOTIFY		
	Event Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:
	Signalling Preconfigured Channel (spc, 0x0001)	O	H245, SPC, Both	H245
	ObservedEvent Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:
	Signalling Preconfigured Channel (spc, 0x0002)	O	ON OFF	OFF
Statistics	Mandatory/Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			
NOTE 1: The package does not define any new signal. The defined signal parameter can be used in the Outgoing H.245 Message signal (h245tpspc/h245msgout, 0x00f7/0x0001) defined in the base package (H.245 Transport package).				
NOTE 2: The package does not define any new event. The defined event and observed event parameters can be used in the Incoming H.245 Message event (h245tpspc/h245msgin, 0x00f7/0x0001) defined in the base package (H.245 Transport package).				

A.14.32 MONA preference package

Table A.14.32/1: Package Usage Information for MONA preference Package

Properties	Mandatory/Optional	Used in command:	Supported Values:	Provisioned Value:
MONA Class (monapref/class, 0x00f8/0x0001)	Not used	-	-	-
Supported Media Preconfigured Channels Receive (monapref/mpcrx, 0x00f8/0x0002)	Not used	-	-	-
Supported Media Preconfigured Channels Transmit (monapref/mpctx, 0x00f8/0x0003)	Not used	-	-	-
Signals	Mandatory/Optional	Used in command:		Duration Provisioned Value:
Outgoing MONA preference message (monapref/monaprefmsgout, 0x00f8/0x0001)	M	MOD		-
	Signal Parameters	Mandatory/Optional	Supported Values:	Duration Provisioned Value:

	Contents of MONA preference message (prefmsgc,0x0001)	M	OCTET STRING	-
Forward Media in Preconfigured Channel (monapref/Preconfchannelmedia, 0x00f8/0x0002)	O	MOD		-
	Signal Parameters	Mandatory/Optional	Supported Values:	Duration Provisioned Value:
	Mux Code (muxcode,0x0003)	M	sub-list of OCTET STRING	-
Events	Mandatory/Optional	Used in command:		
MONA Preference reception (monapref/monaprefmsgin, 0x00f8/0x0001)	M	ADD, NOTIFY		
	Event Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:
	Contents of MONA preference message (prefmsgc,0x0001)	M	OCTET STRING	Not Applicable
MONA Preference negotiation completed (monapref/monaprefcompl, 0x00f8/0x0002)	M	ADD, NOTIFY		
	Event Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:
	None	-	-	-
Legacy Detected (monapref/legdet, 0x00f8/0x0003)	M	ADD, NOTIFY		
	Event Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:
	None	-	-	-
MPC reception (monapref/mpcrec, 0x00f8/0x0004)	O	ADD, NOTIFY		
	Event Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:
	None	-	-	-
	ObservedEvent Parameters	Mandatory/Optional	Supported Values:	Provisioned Value:

	Mux Code (muxcode,0x0001)	M	OCTET STRING	Not Applicable
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-		-
Error Codes	Mandatory/ Optional			
None	-			

A.14.33 3G Interface Type package

Table A.14.31/1: Package Usage Information For 3G Interface Type

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
IP Interface Type (threegint /ipint, (0x00e3/0x0001)	M	ADD, MOD	"NboIP" (0x0001) "MboIP" (0x0003)	None
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
None	-	-		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	-	-	-	-
Events	Mandatory/ Optional	Used in command:		
None	-	-		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	-	-	-	-
Statistics	Mandatory/ Optional	Used in command:	Supported Values:	
None	-	-	-	
Error Codes	Mandatory/ Optional			
None	-			

A.14.34 RTCP Feedback Message package

Table A.14.34/1: Package Usage Information for RTCP Feedback Message package

Properties	Mandatory/ Optional	Used in command:	Supported Values:	Provisioned Value:
None	-	-	-	-
Signals	Mandatory/ Optional	Used in command:		Duration Provisioned Value:
Feedback Message Sending (rtcpfb/fbmesssend, 0x00f6/0x0001)	M	MOD		-
	Signal Parameters	Mandatory/ Optional	Supported Values:	Duration Provisioned Value:
	Update Picture (upic,0x0001)	O	Enumeration	-
	Max Bitrate (mbr,0x0002)	O	Unsigned Integer	-

Events	Mandatory/ Optional	Used in command:		
RTCP Feedback Message Detection (rtcpfb/det, 0x00f6/0x0001)	M	MOD, NOTIFY		
	Event Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Feedback Message Type (type,0x0001)	M	Sub-list of String	-
	ObservedEvent Parameters	Mandatory/ Optional	Supported Values:	Provisioned Value:
	Update Picture (upic,0x0001)	O	Enumeration	-
	Max Bitrate (mbr,0x0002)	O	Unsigned Integer	-
Statistics	Mandatory/ Optional	Used in command:		Supported Values:
None	-	-		-
Error Codes	Mandatory/ Optional			
None	-			

A.14.35 Explicit Congestion Notification for RTP-over-UDP Support (ecnrous)

Table A.14.35.1: Explicit Congestion Notification for RTP-over-UDP Support package

Properties	Mandatory/Optional	Used in command	Supported Values	Provisioned Value
ECN Enabled (ecnrou/ecnen, 0x010b/0x0001)	M	ADD, MODIFY	True, False	-
Congestion Response Method (ecnrou/crm, 0x010b/0x0002)	Not Signalled	-	-	"RDCC"(0x0002) NOTE
Initiation Method (ecnrou/initmethod, 0x010b/0x0003)	M	ADD, MODIFY	"leap"	"leap"
ECN Mode (ecnrou/mode, 0x010b/0x0004)	Not Signalled	-	-	"setonly" (0x0001) in the Remote Descriptor and "readonly" (0x0002) in the Local Descriptor
ECT Marking (ecnrou/ectmark, 0x010b/0x0005)	Not Signalled	-	-	"0" (0x0002)
ECN Congestion Marking (ecnrou/congestmark, 0x010b/0x0006)	Not Signalled	-	-	"nomark" (0x0003)
ECN SDP Usage (ecnrou/ecnsdp, 0x010b/0x0007)	Not Signalled	-	-	"P" (0x0001)
Signals	Mandatory/Optional	Used in command		Duration Provisioned Value
None	-	-		-
	Signal Parameters	Mandatory/Optional	Supported Values	Duration Provisioned Value
	-	-	-	-
Events	Mandatory/Optional	Used in command		
ECN Failure (ecnrou/fail, 0x010b/0x0001)	M	ADD, MODIFY, NOTIFY		
	Event Parameters	Mandatory/Optional	Supported Values	Provisioned Value
	-	-	-	-
	-	-	-	-
	ObservedEvent Parameters	Mandatory/Optional	Supported Values	Provisioned Value
	Failure Type (type,0x0001)	Mandatory	INIT, USE	-
	Media Sender SSRC (ssrc, 0x0002)	Not Supported	-	-
Statistics	Mandatory/Optional	Used in command	Supported Values	
Source (ecnrou/ssrc, 0x010b/0x0001)	Not Supported	-	-	
CE Counter (ecnrou/cecount, 0x010b/0x0002)	Not Supported	-	-	
ECT0 Counter (ecnrou/ectzero, 0x010b/0x0003)	Not Supported	-	-	
ECT1 Counter (ecnrou/ectone, 0x010b/0x0004)	Not Supported	-	-	
Not-ECT Counter (ecnrou/notect, 0x010b/0x0005)	Not Supported	-	-	
Lost Packets Counter (ecnrou/lost 0x010b/0x0006)	Not Supported	-	-	
Extended Highest Sequence number (ecnrou/ehsn, 0x010b/0x0007)	Not Supported	-	-	
Duplication Counter (ecnrou/dup, 0x010b/0x0008)	Not Supported	-	-	
Error Codes	Mandatory/Optional			
None	-			
NOTE: Application Specific Rate Adaptation shall be applied in accordance with 3GPP TS 26.114 [62]. For speech this requires support of CMR and TMMBR for video.				

A.14.36 Differentiated Services (ds)

Table A.14.36.1: Differentiated Services package

Properties	Mandatory/Optional	Used in command	Supported Values	Provisioned Value
Differentiated Services Code Point (ds/dscp, 0x008b/0x0001)	M	ADD, MODIFY	ALL	Yes
Tagging Behaviour (ds/tb, 0x008b/0x0002)	Not signalled	-	-	"MARK" (0x0000)
Signals	Mandatory/Optional	Used in command		Duration Provisioned Value
None	-	-		-
	Signal Parameters	Mandatory/Optional	Supported Values	Duration Provisioned Value
	-	-	-	-
Events	Mandatory/Optional	Used in command		
None	-	-		
	Event Parameters	Mandatory/Optional	Supported Values	Provisioned Value
	-	-	-	-
	ObservedEvent Parameters	Mandatory/Optional	Supported Values	Provisioned Value
-	-	-	-	-
Statistics	Mandatory/Optional	Used in command	Supported Values	
None	-	-	-	
Error Codes	Mandatory/Optional			
None	-			

A.14.37 MG Act-as STUN Server (mgastuns)

Table A.14.37.1: MG Act-as STUN Server

Properties	Mandatory/Optional	Used in command	Supported Values	Provisioned Value
Act-as STUN Server (mgastuns/astuns, 0x00c2/0x0001)	M	ADD, MODIFY	ALL	-
Signals	Mandatory/Optional	Used in command		Duration Provisioned Value
None	-	-		-
	Signal Parameters	Mandatory/Optional	Supported Values	Duration Provisioned Value
	-	-	-	-
Events	Mandatory/Optional	Used in command		
None	-	-		
	Event Parameters	Mandatory/Optional	Supported Values	Provisioned Value
	-	-	-	-
	-	-	-	-
	ObservedEvent Parameters	Mandatory/Optional	Supported Values	Provisioned Value
-	-	-	-	-
Statistics	Mandatory/Optional	Used in command	Supported Values	
None	-	-	-	
Error Codes	Mandatory/Optional			
None	-			

A.14.38 Originate STUN Continuity Check (ostuncc)

Table A.14.3.38.1: Originate STUN Continuity Check Package

Properties	Mandatory/Optional	Used in command	Supported Values	Provisioned Value
Host Candidate Realm (ostuncc/hcr, 0x00c3/0x0001)	O	ADD, MODIFY	ALL	Yes
Signals	Mandatory/Optional	Used in command		Duration Provisioned Value
Send Connectivity Check (ostuncc/scc, 0x00c3/0x0001)	M	ADD, MODIFY		Not Applicable
	Signal Parameters	Mandatory/Optional	Supported Values	Duration Provisioned Value
	Control (cntrl, 0x0001)	O	"controlling", "controlled"	Not Applicable
Send Additional Connectivity Check (ostuncc/sacc, 0x00c3/0x0002)	Mandatory/Optional	Used in command		Duration Provisioned Value
	M	MODIFY		Not Applicable
	Signal Parameters	Mandatory/Optional	Supported Values	Duration Provisioned Value
	Control (cntrl, 0x0001)	O	"controlling", "controlled"	Not Applicable
Events	Mandatory/Optional	Used in command		
Connectivity Check Result (ostuncc/ccr, 0x00c3/0x0001)	M	ADD, MODIFY, NOTIFY		
	Event Parameters	Mandatory/Optional	Supported Values	Provisioned Value
	-	-	-	-
	ObservedEvent Parameters	Mandatory/Optional	Supported Values	Provisioned Value
	Candidate/Transport Pair (ctp, 0x0001)	M	ALL	Not applicable
New Peer Reflexive Candidate (ostuncc/nprc, 0x00c3/0x0002)	Mandatory/Optional	Used in command		
	M	ADD, MODIFY, NOTIFY		
	Event Parameters	Mandatory/Optional	Supported Values	Provisioned Value
	-	-	-	-
	ObservedEvent Parameters	Mandatory/Optional	Supported Values	Provisioned Value
	Candidate (can, 0x0001)	M	ALL	Not applicable
Statistics	Mandatory/Optional	Used in command	Supported Values	
None	-	-	-	
Error Codes	Mandatory/Optional			
None	-			

A.14.39 Enhanced Revised Offer/Answer SDP Support (eroas)

Table A.14.39/1: Enhanced Revised Offer/Answer SDP Support package

Properties	Mandatory/Optional	Used in command	Supported Values	Provisioned Value
SDPCapNeg Extensions (eroas/sdpe, 0x0109/0x0001)	M	AuditValue	"cap-v0"	"cap-v0"
Signals	Mandatory/Optional	Used in command		Duration Provisioned Value
None	-	-		-
	Signal Parameters	Mandatory/Optional	Supported Values	Duration Provisioned Value
	-	-	-	-
Events	Mandatory/Optional	Used in command		
None	-	-		
	Event Parameters	Mandatory/Optional	Supported Values	Provisioned Value
	-	-	-	-
	ObservedEvent Parameters	Mandatory/Optional	Supported Values	Provisioned Value
	-	-	-	-
Statistics	Mandatory/Optional	Used in command	Supported Values	
None	-	-	-	
Error Codes	Mandatory/Optional			
None	-			

A.15 Mandatory support of SDP and H.248 Annex C information elements

Table A.15/1: Supported Annex C and SDP information elements

Information Element	Annex C Support	SDP Support
v-line	"SDP_V "	The value must always be equal to zero: v=0.
m-line	"SDP_M "	<port> <transport> and <fmt-list> are required. Both static and dynamic payload types shall be supported. The MGC may underspecify the <fmt-list> subfield in place of a single dynamic payload type. In this case the mapping between the underspecified payload type and the <encoding name>/<clock rate> shall be provided in the rtpmap attribute. For <transport> see table 5.15/2.
c-line	"SDP_C "	<nettype> <addrtype> and <connection address> are required The network type shall be set to "IN". The address type may be IPv4 or IPv6. The MGC may apply parameter underspecification to the <address type> subfield. (NOTE 2)
a-line	"SDP_A "	For a dynamic RTP payload type, for each codec information on the codec type shall be provided in a separate SDP "a=rtpmap "-line and possibly additional SDP "a=fmtp "-line(s). See Clause 10.2. For AVPF transport, the "rtcp-fb" SDP attribute defined in IETF RFC 4585 [60] may be used to provide the feedback message types the MG is allowed to send and to indicate RTCP timing information. (NOTE 3) For T.38, additional SDP attributes listed in subclause 10.2.3.6 may be provided. ICE support The attributes "a=candidate", "a=ice-pwd", and "a=ice-ufrag" (see IETF RFC 5245 [68]) may be provided for an SDP m-line in the local and remote descriptor if the IM-MGW supports ICE, see also 3GPP TS 24.229 [69]. In the local descriptor, the MGC shall provide "a=ice-pwd", and "a=ice-ufrag" with wildcard sign "\$" to request the allocation of a password and user name fragment, and the "a=candidate" of type "host" with the transport, port and priority parameters with wildcard sign "\$" to request the allocation of a host candidate. The IM-MGW shall then reply with completed "a=ice-pwd", and "a=ice-ufrag" and "a=candidate" attributes in the local descriptor, and shall include "a=ice-lite" if it only supports ICE lite. In the remote descriptor, the MGC may provide the "a=candidate", "a=ice-pwd", and "a=ice-ufrag". Rate adaptation for media endpoints: If the IM-MGW performs media transcoding and if the rate adaptation for media endpoints using the enhanced bandwidth negotiation is supported by the IM-MGW, attribute(s) "a=bw-info" with direction "send" or "sendrecv" may be provided for an m-line and the selected IP payload type and applicable IP version in the remote descriptor. The following bandwidth properties, as defined in 3GPP TS 26.114 [62], clause 19, may be included in "a=bw-info" line: <payload type> <dir> <MaxSupBw>, <MaxDesBw>, <MinDesBw>, <MinSupBw> and <IpVer>. SDP Capability Negotiation: The attributes of "a=acap", "a=tcap", "a=pcfg" and "a=acfg" (see IETF RFC 5939 [70]) may be provided in the local descriptor and/or remote descriptor.

b-line	"SDP_B "	<p>(NOTE1). B:RS and b:RR bandwidth modifiers required Bandwidth information shall be supplied by the MGC if the required bandwidth cannot be immediately derived from the information contained in the m= line. If the MGC is using parameter underspecification, the MG shall assume a reasonable default bandwidth value for well-known codecs and shall provide this value in the response sent to the MGC. The Modifier field shall be set to "AS". The Bandwidth Value field shall be set to the maximum bandwidth requirement of the media stream in kbit/s and shall take into account all headers down to the IP layer.</p> <p>The MGC may also supply additional RTCP bandwidth modifiers (i.e. RR and RS, see IETF RFC 3556 [39]). If the RTCP modifiers are not supplied, the bandwidth value for the AS modifier shall take into account an extra 5% bandwidth for RTCP packets.</p>
o-line	"SDP_O"	<p>The origin line consists of 6 fields: <i>o= <user name> <session ID> <version> <network type> <address type> <address></i>.</p> <p>The MGC is not required to supply this line but shall accept it.</p> <p>The MG shall return the value received from the MGC or if there is no o-line sent by the MGC, the MG shall populate this line as follows:</p> <ul style="list-style-type: none"> - <user name> should contain an hyphen - <session ID> and <version> should contain one or more digits as described in RFC 4566 [17] - <network type> shall be set to IN - <address type> shall be set to IP4 or IP6 The Address Type shall be set to "IP4" or "IP6" depending on the addressing scheme used by the network to which the MG is connected. - <address> should contain the fully qualified domain name or IP address of the gateway.
s-line	"SDP_S"	<p>The session name (s=) line contains a single field: <i>s= <session-name></i>.</p> <p>The MGC is not required to supply a session name but shall accept one. This line may be used to convey correlation information for use in CDRs.</p> <p>The MG shall return the value received from the MGC or if there is no s-line sent by the MGC, the MG shall populate this line as follows: - "s="</p>
t-line	"SDP_T"	<p>The time (t=) line consists of two fields: <i>t= <start-time> <stop-time></i>.</p> <p>The MGC is not required to supply a time description but shall accept one.</p> <p>The MG shall return the value received from the MGC or if there is no t-line sent by the MGC, the MG shall populate this line as follows: - "t=0 0"</p>

NOTE a: SDP or SDP_equivalents are only used for terminations towards the IM CN Subsystem.
 NOTE b: For BICC terminations, mandatory support of SDP and Annex C information elements shall be in accordance with the subclause "Mandatory Support of SDP and H.248.1 annex C information elements" in ITU-T Recommendation Q.1950 [14]. For IP the IANA ICP IDI format of the NSAP addressing format as specified in X.213 [33] shall be used. For Ipv4 networks the IPv4 format recommended by X.213 shall be adopted.
 The BIR length shall be fixed at 4 Octets and the NSAP length shall be fixed at 20 Octets..
 NOTE 1: b-line is optional in TISPN NGN R2.
 NOTE 2: The address type may be IPv4 or IPv6. The default IP version (i.e. IPv4 or IPv6) may be provisioned in the H.248 MG. The MGC may apply H.248 parameter underspecification. If the MGC does require a different IP version than the provisioned default, then the MGC applies complete H.248 parameter specification.
 NOTE3: Support is optional and dependent on RTCP-fb support as described in 3GPP TS 26.114 [62]. The list of feedback types supported by the MG is preconfigured in the MGC. The "rtcp-fb" SDP attribute shall be sent from MGC when applicable.

Table A.15/2: Transport Protocol

Transport Protocol <proto> in m-line:	If the MG does not support the requested transport protocol, it shall reject the command with error code 449.
TCP	(NOTE 1, NOTE 2)
RTP/AVP	RTP profile according IETF RFC 3551 [33].
RTP/AVPF	Extended RTP profile for RTCP-based Feedback (RTP/AVPF) according IETF RFC 4585 [60]. (NOTE 1).
udptl	(NOTE 1)
NOTE 1: support optional.	
NOTE 2: Upper case TCP is defined by IETF RFC 4145 [59] and registered by IANA. .	

A.16 Optional support of SDP and H.248 Annex C information elements

Table A.16/1: Optional Supported Annex C and SDP information elements

Information Element	Annex C Support	SDP Support

A.17 Procedures

A.17.1 Call Independent Procedures

Table A.17.1/1 shows the relationship between each non call-related procedure in 3GPP TS 29.232 [5] and the corresponding procedure defined in 3GPP TS 29.163 [4].

For further description of error codes and service change reasons, refer to ITU-T Recommendation H.248.8 [10].

Table A.17.1/1: Non call-related transaction reused from 3GPP TS 29.232 [5]

Procedure defined in 3GPP TS 29.163 [4]	Procedure defined in 3GPP TS 29.232 [5]	Support	Comment
IM-MGW Out of service	MGW Out of Service	Mandatory	
IM-MGW Communication Up	MGW Communication Up	Mandatory	
IM-MGW Restoration	MGW Restoration	Mandatory	
IM-MGW Register	MGW Register	Mandatory	
IM-MGW Re-register	MGW Re-register	Mandatory	
MGCF Ordered Re-register	(G)MSC Server Ordered Re-register	Mandatory	
MGCF Restoration	(G)MSC Server Restoration	Optional	
MGCF Out of Service	(G)MSC Server Out of Service	Optional	
Termination Out-of-Service	Termination Out-of-Service	Mandatory	
Termination Restoration	Termination Restoration	Mandatory	
Audit Value	Audit Value	Mandatory	Mandatory support only for audit of Termination Service State and for periodic audit of MGW (empty Audit descriptor). Optional support for audit of Packages or to retrieve MGC Information.
Audit Capability	Audit Capability	Optional	
Command Rejected	Command Rejected	Mandatory	The "Command Rejected" procedure may be used in response both to call-related and non-call-related ITU-T Recommendation H.248 Commands
IM-MGW Capability Change	Capability Update	Optional	
IM-MGW Resource Congestion Handling - Activate	MGW Resource Congestion Handling - Activate	Mandatory	
IM-MGW Resource Congestion Handling - Indication	MGW Resource Congestion Handling - Indication	Mandatory	
Inactivity Timeout - Activate	Inactivity Timeout - Activate	Optional	
Inactivity Timeout - Indication	Inactivity Timeout - Indication	Optional	

A.17.1.2 Profile registration

The following description is based on H.248.1 profile registration procedure with some clarifications. The reply to the ServiceChange Request containing the SCP parameter indicates if the MGCF supports the requested profile or if it does not support it and wants to propose an alternative profile. The profile (name and version) is only returned in the reply if the MGCF cannot support the specified profile in the ServiceChangeRequest. The returned reply shall indicate the profile and version supported. Upon reception of a profile in the reply, if the IM-MGW supports the indicated profile, it shall issue a new ServiceChange Request with the agreed profile to explicitly confirm the acceptance of the profile to the MGCF ; otherwise, if the IM-MGW does not support the indicated profile, it may continue the registration or re-registration procedure by issuing a new ServiceChange Request with an alternative profile ; until such procedure is successfully completed the IM-MGW shall remain out of service. If the profile is not returned the MGCF shall use the capabilities specified by the Profile indicated in the service change request.

NOTE: It should be observed that the profile registration is not a "cold calling" negotiation; it is expected that the operator will have configured the network to support certain profiles and so the profile registration within the Mn interface permits network upgrade scenarios but otherwise is simply a means to confirm the connection of the profile to be used over the Mn interface between MGCF and IM-MGW.

A.17.2 IMS Terminations Procedures

A.17.2.1 Summary of Procedures related to a termination towards IM CN Subsystem

Table 1 shows the relationship between each call-related procedure in ITU-T Recommendation Q.1950 [14] (see 3GPP TS 29.205 [3]) or TS 29.232 [5] and the corresponding stage 2 procedure defined in 3GPP TS 29.163 [4].

Table A.17.2.1/1: Correspondence between ITU-T Recommendation Q.1950 [14] or 29.232 [5] call-related transactions and 3GPP TS 29.163 [4] procedures

Procedure defined in 3GPP TS 29.163 [4]	Transaction used in Q.1950 [14]	Transaction used in TS 29.232 [5]	Supported	Comment
Reserve IMS Connection point	Not defined	Not Defined	Mandatory	See A.17.2. 2
Configure IMS Resources	Not Defined	Not Defined	Mandatory	See A.17.2. 3
Reserve IMS Connection Point and configure remote resources	Not defined	Not Defined	Mandatory	See A.17.2. 4
Release IMS termination	n. a. for reuse	Release Termination	Mandatory	See A.17.2. 5
Change IMS ThroughConnection	n. a. for reuse	Change Through Connection	Mandatory	only the Explicit (MGC Controlled Cut-Through) procedure is supported
Detect IMS RTP Tel Event	n. a. for reuse	Detect DTMF	Optional	Only applicable if termination towards IMS is connected with a termination towards a BICC network.
End IMS RTP Tel Event	n. a. for reuse	Stop Detect DTMF	Optional	Only applicable if termination towards IMS is connected with a termination towards a BICC network.
Notify IMS RTP Tel Event	n. a. for reuse	Report DTMF	Optional	Only applicable if termination towards IMS is connected with a termination towards a BICC network.
Send IMS RTP Tel Event	n. a. for reuse	Send DTMF	FFS	
Stop IMS RTP Tel Event	n. a. for reuse	Stop DTMF	FFS	
IMS Send Tone	n. a. for reuse	Send Tone	Optional	
IMS Stop Tone	n. a. for reuse	Stop Tone	Optional	
IMS Tone Completed	n. a. for reuse	Tone Completed	Optional	
Termination heartbeat Indication	Not defined	Termination heartbeat Indication	Mandatory	To allow detection of hanging contexts and terminations in the MGW that may result e.g. from a loss of communication between the MGCF and the IM-MGW.
IMS Bearer Released	n. a. for reuse.	Bearer Released	Mandatory	
Request RTCP-Interworking	Not defined	Not defined	Optional	Only applicable if RTCP AVPF message to feedback on the quality of the media distribution from the IMS side is required to be interworked with corresponding H.245 message towards the CS side.
Notify of RTCP-Interworking	Not defined	Not defined	Optional	Only applicable if RTCP AVPF message to feedback on the quality of the media distribution from the IMS side is required to be interworked with corresponding H.245 message towards the CS side.
Signal H.245-Interworking	Not defined	Not defined	Optional	Only applicable if H.245 message to feedback on the quality of the media distribution from the CS side is required to be interworked with corresponding RTCP AVPF message towards the IMS side.

ECN Failure Indication	Not defined	ECN Failure Indication	Optional	Only applicable if ECN capability is supported.
ICE Connectivity Check Result Notification	Not defined	Optional	Optional	See A.17.2.11 Only applicable if full ICE is supported
ICE New Peer Reflexive Candidate Notification	Not defined	Optional	Optional	See A.17.2.12 Only applicable if full ICE is supported
NOTE 1: A procedure defined in table 13.2.1 can be combined with another procedure in the same table. This means that they can share the same contextID and termination ID(s) and that they can be combined in the same H.248 command.				

A.17.2.2 Reserve IMS Connection Point

When the procedure "Reserve IMS Connection Point" is required the following procedure is initiated:

The MGCF sends an Add.req command with the following information.

- 1 Add.req (Reserve IMS Connection Point) MGCF to IM-MGW

Table A.17.2.2/1: Reserve IMS Connection Point Request

Address Information	Control information	Bearer information
Stream ID Local Descriptor { Port = ? IP Address = ? }	Transaction ID = z Termination ID = ? <u>If Context Requested:</u> Context ID = ? <u>If Context Provided:</u> Context ID = c1 If MPS call/session: Priority Indicator = x If IP Interface Type: IP interface = "IP interface type" If Resources for multiple Codecs shall be reserved: Reserve_Value NotificationRequested (Event ID = x, "termination heartbeat") If indication on Bearer Released requested: NotificationRequested (Event ID = x, "BNC Release (Cause)") – as defined in ITU-T Recommendation Q.1950 If multiple IP realms: IP realm Identifier = required IP realm identifier If ECN Endpoint support required ECN Enable = "True" Initiation Method = "ECN Initiation Method" If notification of ECN Failure Report: NotificationRequested (Event ID = x, "ECN Failure") If diffserv required: Diffserv Code Point If ICE is applied: STUN server request	Stream ID Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR If ICE is applied: ICE host candidate request ICE password request ICE Ufrag request If SDPCapNeg is signalled to the gateway: SDPCapNeg configuration }

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Add.resp (Reserve IMS Connection Point Ack)

Table A.17.2.2/2: Reserve IMS Connection Point Acknowledge

Address Information	Control information	Bearer information
Stream ID Local Descriptor { Port IP Address }	Transaction ID Termination ID Context ID	Stream ID Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR If ICE is applied: ICE host candidate ICE password ICE Ufrag If ICE lite implementation ICE lite indication If SDPCapNeg is signalled to the gateway: SDPCapNeg configuration }

A.17.2.3 Configure IMS Resources

When the procedure "Configure IMS Resources" is required the following procedure is initiated:

The MGCF sends a Mod.req command with the following information.

- 1 Mod.req (Configure IMS Resources) MGCF to IM-MGW

Table A.17.2.3/1: Configure IMS Resources Request

Address Information	Control information	Bearer information
If local resources are modified: Stream ID Local Descriptor { Port IP Address } If remote resources are modified: Remote Descriptor { Port IP Address }	Transaction ID Termination ID Context ID If IP Interface Type: IP interface = "IP interface type"(NOTE 1) If Resources for multiple Codecs shall be reserved: Reserve_Value If ECN Endpoint support required ECN Enable = "True" Initiation Method = "ECN Initiation Method" If notification of ECN Failure Report: NotificationRequested (Event ID = x, "ECN Failure") If full ICE is applied: Send Connectivity Check ("Control") If notification of ICE Connectivity Check Result Report: NotificationRequested (Event ID= xx, "Connectivity Check Result") If notification of New Peer Reflexive Candidate: NotificationRequested (Event ID = xy, " New Peer Reflexive Candidate ") Send Additional Connectivity Check ("Control")	If local resources are modified: Stream ID Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR If SDPCapNeg is signalled to the gateway: SDPCapNeg configuration } If remote resources are modified: Remote Descriptor { Codec List RTP Payloads If rate adaptation for media endpoints: Additional Bandwidth Properties (NOTE 3) RtcpbwRS RtcpbwRR If RTCP APP messages allowed Allowed RTCP APP message types If ICE is applied: ICE received candidate ICE received password ICE received Ufrag (NOTE 2) If SDPCapNeg is signalled to the gateway: SDPCapNeg configuration }
NOTE 1: If this property is included within the "Reserve IMS Connection Point" procedure or the "Reserve IMS Connection Point and configure remote resource" procedure then it shall not be modified by this procedure. NOTE 2: The support of ICE received candidate, ICE received password, ICE received Ufrag are optional for ICE lite, as specified in 3GPP TS 23.232 [5]. NOTE 3: The support of rate adaptation for media endpoints using the additional bandwidth properties is optional for the IM-MGW. If media transcoding is required the MGCF may provide for the selected payload type and the used IP version the additional bandwidth properties.		

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Mod.resp (Configure IMS Resources Ack)

Table A.17.2.3/2: Configure IMS Resources Acknowledge

Address Information	Control information	Bearer information
If local resources were provided in request: Stream ID Local Descriptor { Port IP Address } If remote resources were provided in request: Remote Descriptor { Port IP Address }	Transaction ID Context ID Termination ID	If local resources were provided in request: Stream ID Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR } If SDPCapNeg is signalled to the gateway: SDPCapNeg configuration } If remote resources were provided in request: Remote Descriptor { Codec List RTP Payloads If rate adaptation for media endpoints: Additional Bandwidth Properties RtcpbwRS RtcpbwRR } If SDPCapNeg is signalled to the gateway: SDPCapNeg configuration }

A.17.2.4 Reserve IMS Connection Point and configure remote resources

When the procedure "Reserve IMS Connection Point and configure remote resources" is required the following procedure is initiated:

The MGCF sends an Add.req command with the following information.

- 1 Add.req (Reserve IMS Connection Point and configure remote resources) MGCF to IM-MGW

Table A.17.2.4/1: Reserve IMS Connection Point and configure remote resources Request

Address Information	Control information	Bearer information
Stream ID Local Descriptor { Port = ? IP Address = ? } Remote Descriptor { Port IP Address }	Transaction ID Termination ID = ? If Context Requested: Context ID = ? If Context Provided: Context ID = c1 If MPS call/session: Priority Indicator = x If IP Interface Type: IP interface = "IP interface type" If Resources for multiple Codecs shall be reserved: Reserve_Value NotificationRequested (Event ID = x, "termination heartbeat") If indication on Bearer Released requested: NotificationRequested (Event ID = x, "BNC Release (Cause)") – as defined in ITU-T Recommendation Q.1950 If multiple IP realms: IP realm Identifier = required IP realm identifier If ECN Endpoint support required ECN Enable = "True" Initiation Method = "ECN Initiation Method" If notification of ECN Failure Report: NotificationRequested (Event ID = x, "ECN Failure") If diffserv required: Diffserv Code Point If ICE is applied: STUN server request If full ICE is applied Send Connectivity Check ("Control") notification of ICE Connectivity Check Result Report: NotificationRequested (Event ID = xx, "Connectivity Check Result") If notification of New Peer Reflexive Candidate: NotificationRequested (Event ID = xy, " New Peer Reflexive Candidate ")	Stream ID Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR If ICE is applied: ICE host candidate request ICE password request ICE Ufrag request If SDPCapNeg is signalled to the gateway: SDPCapNeg configuration } Remote Descriptor { Codec List RTP Payloads If rate adaptation for media endpoints: Additional Bandwidth Properties (NOTE 2) RtcpbwRS RtcpbwRR If RTCP APP messages allowed Allowed RTCP APP message types If ICE is applied: ICE received candidate ICE received password ICE received Ufrag (NOTE 1) If SDPCapNeg is signalled to the gateway: SDPCapNeg configuration }
NOTE 1: The support of ICE received candidate, ICE received password, ICE received Ufrag are optional for ICE lite, as specified in 3GPP TS 23.232 [5]. NOTE 2: The support of rate adaptation for media endpoints using the additional bandwidth properties is optional for the IM-MGW. If media transcoding is required the MGCF may provide for the selected payload type and the used IP version the additional bandwidth properties.		

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Add.resp (Reserve IMS Connection Point and configure remote resources Ack)

Table A.17.2.4/2: Reserve IMS Connection Point and configure remote resources Acknowledge

Address Information	Control information	Bearer information
Stream ID Local Descriptor { Port IP Address } Remote Descriptor { Port IP Address }	Transaction ID Termination ID Context ID	Stream ID Local Descriptor { Codec List RTP Payloads RtcpbwRS RtcpbwRR If ICE is applied: ICE host candidate ICE password ICE Ufrag If ICE lite implementation ICE lite indication If SDPCapNeg is signalled to the gateway: SDPCapNeg configuration } Remote Descriptor { Codec List RTP Payloads If rate adaptation for media endpoints: Additional Bandwidth Properties RtcpbwRS RtcpbwRR If SDPCapNeg is signalled to the gateway: SDPCapNeg configuration }

A.17.2.5 VOID

A.17.2.6 Termination heartbeat indication

When the procedure "Termination heartbeat indication" is required the following procedure is initiated: the MGW sends a NOT.req command with the following information.

Table A.17.2.6/1: NOT.req (Termination heartbeat) MGW to MGC

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = bearer1 Event_ID (Event ID = x, "termination heartbeat")	

When the processing of command is complete, the MGC initiates the following procedure.

Table A.17.2.6/2: NOT.resp (Termination heartbeat)MGC to MGW

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = bearer1	

The heartbeat timer shall be configured to a value much greater than the mean call holding time.

The MGCF is in charge of correcting any detected mismatch, by subtracting hanging terminations or clearing hanging contexts as specified for the hanging termination detection procedure in 3GPP TS 29.163 [4].

A.17.2.7 Request RTCP-Interworking

When the procedure "Request RTCP-Interworking" is required the following procedure is initiated:

the MGCF sends a Mod.req command with the following information.

Table A.17.2.7/1: Request RTCP-Interworking Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = bearer1 NotificationRequested (Event ID = x, "Incoming RTCP Interworking (RTCP Filter)")	

When the processing of command is complete, the IM-MGW initiates the following procedure.

Table A.17.2.7/2: Request RTCP-Interworking Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = bearer1	

A.17.2.8 Notify RTCP-Interworking

When the procedure "Notify RTCP-Interworking" is required the following procedure is initiated:

the IM-MGW sends a NOT.req command with the following information.

Table A.17.2.8/1: Notify RTCP-Interworking Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = bearer1 if RTCP PLI message received and the interworking required: Update Picture = UpdatePicture_Event if RTCP TMMBR message received and the interworking required: Max BitRate = MaxBitRate_Event	

When the processing of command is complete, the MGCF initiates the following procedure.

Table A.17.2.8/2: Notify RTCP-Interworking Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = bearer1	

The MGCF is in charge of sending the corresponding H.245 message to the CS side to request for the media adaption, as specified for the "Interworking between RTCP messages and H.245 messages" in 3GPP TS 29.163 [4].

A.17.2.9 Signal H.245-Interworking

When the procedure "Signal H.245-Interworking" is required the following procedure is initiated:

the MGCF sends a Mod.req command with the following information.

Table A.17.2.9/1: Signal H.245-Interworking Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = bearer1 if H.245 VideoFastUpdatePicture message received and the interworking required: Interwork H.245-RTCP (UpdatePicture_Signal) if H.245 Flow Control Command received and the interworking required: Interwork H.245-RTCP (MaxBitRate_Signal)	

When the processing of command is complete, the IM-MGW initiates the following procedure.

Table A.17.2.9/2: Signal H.245-Interworking Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = bearer1	

The IM-MGW is in charge of constructing and sending the corresponding RTCP message to the IMS side to request for the media adaptation as specified for the "Interworking between RTCP messages and H.245 messages" in 3GPP TS 29.163 [4].

A.17.2.10 ECN Failure Indication

The IM-MGW sends a NOTIFY request command as in Table A.17.2.10.1.

Table A.17.2.10.1: ECN Failure Indication

Address Information	Control information	Bearer information
	Transaction ID = x Context ID = C1 Termination ID = T1 Event_ID (Event ID = x, "ECN Failure (ECN Failure Type)")	

The MGCF responds as in Table A.17.2.10.2

Table A.17.2.10.2: ECN Failure Indication Ack

Address Information	Control information	Bearer information
	Transaction ID = x Context ID = C1 Termination ID = T1	

A.17.2.11 ICE Connectivity Check Result Notification

The IM-MGW sends a NOTIFY request command as defined in Table A.17.2.11.1.

Table A.17.2.11.1: ICE Connectivity Check Result Notification

Address Information	Control information	Bearer information
	Transaction ID = x Context ID= C1 Termination ID = T1 Event_ID (Event ID = x, " Connectivity Check Result (Candidate/Transport Pair)")	

The MGCF responds as defined in Table A.17.2.11.2

Table A.17.2.11.2: ICE Connectivity Check Result Notification Ack

Address Information	Control information	Bearer information
	Transaction ID = x Context ID = C1 Termination ID = T1	

A.17.2.12 ICE New Peer Reflexive Candidate Notification

The IM-MGW sends a NOTIFY request command as defined in Table A.17.2.12.1.

Table A.17.2.12.1: ICE New Peer Reflexive Candidate Notification

Address Information	Control information	Bearer information
	Transaction ID = x Context ID= C1 Termination ID = T1 Event_ID (Event ID = x, " New Peer Reflexive Candidate (Candidate)")	

The MGCF responds as defined in Table 5.17.2.12.2

Table A.17.2.12.2: ICE New Peer Reflexive Candidate Ack

Address Information	Control information	Bearer information
	Transaction ID = x Context ID = C1 Termination ID = T1	

A.17.3 TDM Terminations Procedures

A.17.3.1 Summary Procedures related to a termination towards ISUP

Table A.17.3.1/1: Correspondence between ITU-T Recommendation Q.1950 [14] or 29.232 [5] call-related transactions and 3GPP TS 29.163 [4] procedures related to a termination towards an ISUP network

Procedure defined in 3GPP TS 29.163 [4]	Transaction used in ITU-T Q.1950 [14]	Transaction used in TS 29.232 [5]	Support	Comment
Reserve TDM Circuit	n. a. for reuse	n. a. for reuse, (NOTE 2)	Optional (NOTE 4)	See Clause A.17.3.2
Change TDM Through-connection	n. a. for reuse	Change Through-connection	Optional (NOTE 4)	only the Explicit (MGC Controlled Cut-Through) procedure is supported
Activate TDM voice-processing function	n. a. for reuse	Activate Voice Processing Function	Optional (NOTE 4)	
Send TDM Tone	n. a. for reuse	Send Tone	Optional (NOTE 4)	
Stop TDM Tone	n. a. for reuse	Stop Tone	Optional (NOTE 4)	
TDM Tone Completed	n. a. for reuse	Tone Completed	Optional (NOTE 4)	
Play TDM Announcement	n. a. for reuse	Play Announcement	Optional (NOTE 4)	
TDM Announcement Completed	n. a. for reuse	Announcement Completed	Optional (NOTE 4)	
Stop TDM Announcement	n. a. for reuse	Stop Announcement	Optional (NOTE 4)	
Continuity Check	Continuity Check Tone	n. a. for reuse	Optional (NOTE 4)	The addition to "Prepare BNC Notify" defined in Annex B.7.1.1 of Q.1950 [14] shall be applied instead to "Reserve TDM Circuit", as defined in Clause A.17.3.2
Continuity Check Verify	Continuity Check Verify	Continuity Check Verify	Optional (NOTE 4)	
Continuity Check Response	Continuity Check Response	n. a. for reuse	Optional (NOTE 4)	The addition to "Prepare BNC Notify" defined in Annex B.7.1.2 of Q.1950 [14] shall be applied instead to "Reserve TDM Circuit", as defined in Clause A.17.3.2
Release TDM Termination	n. a. for reuse	n. a. for reuse	Optional (NOTE 4)	See Clause A.17.3.3
Termination heartbeat Event	Not defined	Termination heartbeat Indication	Optional	See Clause A.17.3.4
Not defined	Not defined	TFO Activation	Optional	See Clause A.14.21
Not defined	Not defined	Codec Modify	Optional	See Clause A.14.21
Not defined	Not defined	Optimal Codec and Distant List_Notify	Optional	See Clause A.14.21
Not defined	Not defined	Distant Codec List	Optional	See Clause A.14.21
Not defined	Not defined	TFO status Notify	Optional	See Clause A.14.21
Not defined	Not defined	TFO status	Optional	See Clause A.14.21
Bearer Released	n. a. for reuse.	Bearer Released	Optional (NOTE 4)	
<p>NOTE 1: A procedure defined in table 13.2.2 can be combined with another procedure in the same table. This means that they can share the same contextID and termination ID(s) and that they can be combined in the same H.248 command.</p> <p>NOTE 2: The reserve circuit procedure of 29.232 is not to be used only a reduced set of the parameters is required for reserve TDM circuit.</p> <p>NOTE 3: VOID</p> <p>NOTE 4: Required for TDM terminations towards an ISUP based network</p>				

A.17.3.2 Reserve TDM Circuit

When the procedure "Reserve TDM Circuit" is required the following procedure is initiated:

The MGCF sends an Add.req command with the following information.

Table A.17.3.2/1: Add.req (Reserve TDM Circuit) MGCF to IM-MGW

Address Information	Control information	Bearer information
	Transaction ID Termination ID If Context Requested: Context ID = ? If Context Provided: Context ID = c1 If detection of hanging termination is requested: NotificationRequested (Event ID = x, "termination heartbeat") If indication on Bearer Released requested: NotificationRequested (Event ID = x, "BNC Release (Cause)") – as defined in ITU-T Recommendation Q.1950	Bearer Service Characteristics

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

Table A.17.3.2/2: Add.resp (Reserve TDM Circuit) IM-MGW to MGCF

Address Information	Control information	Bearer information
	Transaction ID Termination ID Context ID	

A.17.3.3 Release TDM Termination

When the procedure "Release TDM Termination" is required the following procedure is initiated:

The MGCF sends an Sub.req command with the following information.

Table A.17.3.3/1: Sub.req (Release TDM Termination) MGCF to IM-MGW

Address Information	Control information	Bearer information
	Transaction ID Termination ID Context ID	

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

Table A.17.3.3/2: Sub.resp (Release TDM Termination) IM-MGW to MGCF

Address Information	Control information	Bearer information
	Transaction ID Termination ID Context ID	

A.17.3.4 Termination heartbeat indication

When the procedure "Termination heartbeat indication" is required the following procedure is initiated: the MGW sends a NOT.req command with the following information.

Table A.17.3.4/1: NOT.req (Termination heartbeat) MGW to MGC

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = bearer1 Event_ID (Event ID = x, "termination heartbeat")	

When the processing of command is complete, the MGC initiates the following procedure.

Table A.17.3.4/2: NOT.resp (Termination heartbeat)MGC to MGW

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = bearer1	

The heartbeat timer shall be configured to a value much greater than the mean call holding time.

The MGC is in charge of correcting any detected mismatch, by subtracting hanging terminations or clearing hanging contexts as specified for the hanging termination detection procedure in 3GPP TS 29.163 [4].

A.17.4 BICC Terminations Procedures

A.17.4.1 Procedures related to a termination towards BICC

Table A.17.4.1/1: Correspondence between ITU-T Recommendation Q.1950 [14] or 3GPP TS 29.232 [5] call-related transactions and 3GPP TS 29.163 [4] procedures related to a termination towards a BICC network

Procedure defined in 3GPP TS 29.163 [4]	Transaction used in Q.1950 [14]	Transaction used in TS 29.232 [5]	Support	Comment
Establish Bearer	Establish_BNC_Notify +(tunnel)	Establish Bearer (NOTE 1)	Optional (NOTE 5)	
Prepare Bearer	Prepare_BNC_Notify +(tunnel)	Prepare Bearer (NOTE 1), (NOTE 2)	Optional (NOTE 5)	
Change Through-Connection	n. a. for reuse	Change Through-Connection	Optional (NOTE 5)	only the Explicit (MGC Controlled Cut-Through) procedure is supported
Release Bearer	n. a. for reuse	Release Bearer	Optional (NOTE 5)	(NOTE 3)
Release Termination	n. a. for reuse	Release Termination	Optional (NOTE 5)	Includes Subtract in the transaction. Statistics about "Ctmbits" are not applicable in Sub.resp
Bearer Established	n. a. for reuse	Bearer Established	Optional (NOTE 5)	
Bearer Released	n. a. for reuse	Bearer Released	Optional (NOTE 5)	
Send Tone	n. a. for reuse	Send Tone	Optional (NOTE 5)	
Stop Tone	n. a. for reuse	Stop Tone	Optional (NOTE 5)	
Tone Completed	n. a. for reuse	Tone Completed	Optional (NOTE 5)	
Play Announcement	n. a. for reuse	Play Announcement	Optional (NOTE 5)	
Stop Announcement	n. a. for reuse	Stop Announcement	Optional (NOTE 5)	
Announcement Completed	n. a. for reuse	Announcement Completed n	Optional (NOTE 5)	
Bearer Modification Support	Not defined	Bearer Modification Support	Optional (NOTE 5)	
Confirm Char	Confirm_Char	Confirm Bearer Characteristics (NOTE 1)	Optional (NOTE 6)	
Modify Bearer Characteristics	Modify Char	Modify Bearer Characteristics (NOTE 1)	Optional (NOTE 6)	
Reserve Char	Reserve_Char_Notify	Reserve Bearer Characteristics (NOTE 1)	Optional (NOTE 6)	
Bearer Modified	BNC Modified	Bearer Modified	Optional (NOTE 6)	
Activate Voice Processing Function	n. a. for reuse	Activate Voice Processing Function	Optional (NOTE 5)	
Tunnel Information Down	Tunnel (MGC-MGW)	Tunnel Information Down	Optional (NOTE 7)	For IP Transport at BICC termination
Tunnel Information Up	Tunnel (MGW-MGC)	Tunnel Information Up	Optional (NOTE 7)	For IP Transport at BICC termination
Termination heartbeat	Not defined	Termination heartbeat indication	Mandatory	
Not defined	Not defined	TFO Activation	Optional	
Not defined	Not defined	Codec Modify	Optional	
Not defined	Not defined	Optimal Codec and Distant List_Notify	Optional	
Not defined	Not defined	Distant Codec List	Optional	
Not defined	Not defined	TFO status Notify	Optional	
Not defined	Not defined	TFO status	Optional	

NOTE 1: The procedure is only applicable if the Nb framing protocol is applied at the BICC termination. Only requesting of Observed events defined in the corresponding TS 29.232 and parameters defined in the "3GUP" package of TS 29.232 are applicable in addition the parameters of the corresponding Q.1950 procedure. Those parameters shall be applies as follows: UP mode = Supported mode; UP versions = 2; interface = CN;

NOTE 2: Parameters and Observed events defined for Cellular Text telephone Modem Text Transport in the corresponding procedure of TS 29.232 are not applicable.

NOTE 3: VOID

NOTE 4: VOID

NOTE 5: Necessary for optional terminations towards BICC

NOTE 6: Optional for optional terminations towards BICC

NOTE 7: Necessary for optional terminations towards BICC network with IP transport

A.17.5 Multiplex Termination Procedures

A.17.5.1 Procedures related to a Multiplex termination

Table A.17.5.1/1: Correspondence between ITU-T Recommendation Q.1950 [14] or 3GPP TS 29.232 [5] call-related transactions and 3GPP TS 29.163 [4] procedures related to a multiplex termination

Procedure defined in 3GPP TS 29.163 [4]	Transaction used in Q.1950 [14]	Transaction used in TS 29.232 [5]	Support	Comment
Add Multiplex Termination	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.2
Configure Multiplex Termination	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.3
Signal H245 Message	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.4
Notify H245 message	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.5
Notify MONA Preference Reception	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.6
Notify MONA Preference Completed	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.7
Signal SPC	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.8
Notify SPC	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.9
Notify MPC	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.10
Notify Detection of Legacy Interworking	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.11
Stop MPC	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.12
Stop SPC	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.13
Stop MONA Negotiation	Not defined	Not defined	Optional (NOTE 1)	See A.17.5.14

NOTE 1: Necessary for interworking of multimedia calls

A.17.5.2 Add Multiplex Termination

When the procedure "Add Multiplex Termination" is required the following procedure is initiated:

The MGCF sends an Add.req command with the following information.

- 1 Add.req (Add Multiplex Termination) MGCF to IM-MGW

Table A.17.5.2/1: Add Multiplex Termination Request

Address Information	Control information	Bearer information
	<p>Transaction ID = z Context ID = c1 Termination ID = ?</p> <p>Muxdescriptor</p> <p>If MONA procedures not supported: NotificationRequested (Event ID = x, "Incoming H245 message")</p> <p>f MONA procedures supported: NotificationRequested (Event ID = x, "Incoming H245 message (SPC=Both)")</p> <p>NotificationRequested (Event ID = x, "termination heartbeat")</p> <p>If indication on Bearer Released requested: NotificationRequested (Event ID = x, "BNC Release (Cause)") – as defined in ITU-T Recommendation Q.1950</p> <p>If MONA procedures supported: Signal = Outgoing MONA preferences (Outgoing MONA preference content) (NOTE) NotificationRequested (Event ID = x, "MONA Preference recv")</p> <p>NotificationRequested (Event ID = x, "MONA Preference completed")</p> <p>NotificationRequested (Event ID = x, "Legacy Interworking Detected" (Signal = Outgoing H245 message (Outgoing H.245 message content)))</p> <p>NotificationRequested (Event ID = x, "Mona Preference Channel reception")</p> <p>Signal = Forward media in MPC (MPC MUX Code)</p> <p>Incoming Multiplex Table</p>	
<p>NOTE: The frequent retransmissions of MONA preference messages required by MONA procedures are to be performed by the IM-MGW autonomously to avoid unnecessary load at the Mn interface and the MGCF.</p>		

On receipt of this procedure, and the setting of the muxdescriptor, the IM-MGW shall initiate the H.324 negotiation, with connection mode H.324M and predefined Highest Multiplexing Level.

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Add.resp (Add Multiplex Termination Ack)

Table A.17.5.2/2: Add Multiplex Termination Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.3 Configure Multiplex Termination

When the procedure "Configure Multiplex Termination" is required the following procedure is initiated:

The MGCF sends an Mod.req command with the following information.

1 Mod.req (Configure Multiplex Termination) MGCF to IM-MGW

Table A.17.5.3/1: Configure Multiplex Termination Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 If MONA completed or MONA not supported: Remote H223 Capability Incoming Multiplex table Outgoing Multiplex table If MONA MPC sending is requested: Signal = Forward media in MPC (MPC MUX Code)	

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Mod.resp (Configure Multiplex Termination Ack)

Table A.17.5.3/2: Configure Multiplex Termination Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.4 Signal H245 Message

When the procedure "Signal H245 Message" is required the following procedure is initiated:

The MGCF sends an Mod.req command with the following information.

1 Mod.req (Signal H245 Message) MGCF to IM-MGW

Table A.17.5.4/1: Signal H245 Message Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 Signal = Outgoing H245 message (Outgoing H.245 message content)	

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Mod.resp (Signal H245 Message Ack)

Table A.17.5.4/2: Signal H245 Message Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.5 Notify H.245 Message

When the procedure "Notify H.245 message" is required the following procedure is initiated: the IM-MGW sends a NOT.req command with the following information.

1 Not.req (Notify H245 Message) IM-MGW to MGCF

Table A.17.5.5/1: Notify H245 Message Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 Event_ID (Event ID = x, "Incoming H245 message (H245 message content)")	

When the processing of command is complete, the MGCF initiates the following procedure.

2 Not.resp (Notify H245 Message Ack) MGCF to IM-MGW

Table A.17.5.5/2: Notify H245 Message Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.6 Notify MONA Preference Reception

When the procedure "Notify MONA Preference Reception" is required the following procedure is initiated: the IM-MGW sends a NOT.req command with the following information.

1 Not.req (Notify MONA Preference Reception) IM-MGW to MGCF

Table A.17.5.6/1: Notify MONA Preference Reception Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 Event_ID (Event ID = x, "MONA Preference recv (MONA preference message content)")	

When the processing of command is complete, the MGCF initiates the following procedure.

- 2 Not.resp (Notify MONA Preference Reception) MGCF to IM-MGW

Table A.17.5.6/2: Notify MONA Preference Reception Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.7 Notify MONA Preference Completed

When the procedure "Notify MONA Preference Completed" is required the following procedure is initiated: the IM-MGW sends a NOT.req command with the following information.

- 1 Not.req (Notify MONA Preference Completed) IM-MGW to MGCF

Table A.17.5.7/1: Notify MONA Preference Completed Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 Event_ID (Event ID = x, "MONA Preference completed ")	

When the processing of command is complete, the MGCF initiates the following procedure.

- 2 Not.resp (Notify MONA Preference Completed) MGCF to IM-MGW

Table A.17.5.7/2: Notify MONA Preference Completed Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.8 Signal SPC

When the procedure "Signal SPC" is required the following procedure is initiated:

The MGCF sends an Mod.req command with the following information.

- 1 Mod.req (Signal SPC) MGCF to IM-MGW

Table A.17.5.8/1: Signal SPC Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 Signal = Outgoing H245 message (Outgoing H.245 message content, SPC Out=ON)	

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Mod.resp (Signal SPC Ack)

Table A.17.5.8/2: Signal SPC Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.9 Notify SPC

When the procedure "Notify SPC" is required the following procedure is initiated: the IM-MGW sends a NOT.req command with the following information.

1 Not.req (Notify SPC) IM-MGW to MGCF

Table A.17.5.9/1: Notify SPC Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 Event_ID (Event ID = x, "(Incoming H245 message (H245 message content, SPC In=ON)")	

When the processing of command is complete, the MGCF initiates the following procedure.

2 Not.resp (Notify SPC Ack) MGCF to IM-MGW

Table A.17.5.9/2: Notify SPC Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.10 Notify MPC

When the procedure "Notify MPC" is required the following procedure is initiated: the IM-MGW sends a NOT.req command with the following information.

1 Not.req (Notify MPC) IM-MGW to MGCF

Table A.17.5.10/1: Notify MPC Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 Event_ID (Event ID = x, "Mona Preference Channel reception (Muxcode)")	

When the processing of command is complete, the MGCF initiates the following procedure.

- 2 Not.resp (Notify MPC Ack) MGCF to IM-MGW

Table A.17.5.10/2: Notify MPC Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.11 Notify Detection of Legacy Interworking

When the procedure "Notify Detection of Legacy Interworking " is required the following procedure is initiated: the IM-MGW sends a NOT.req command with the following information.

- 1 Not.req (Notify Detection of Legacy Interworking) IM-MGW to MGCF

Table A.17.5.11/1: Notify Detection of Legacy Interworking Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 Event_ID (Event ID = x, "Legacy Interworking Detected ")	

When the processing of command is complete, the MGCF initiates the following procedure.

- 2 Not.resp (Notify Detection of Legacy Interworking) MGCF to IM-MGW

Table A.17.5.11/2: Notify Detection of Legacy Interworking Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.12 Stop MPC

When the procedure "Stop MPC" is required the following procedure is initiated:

The MGCF sends an Mod.req command with the following information.

- 1 Mod.req (Stop MPC) MGCF to IM-MGW

Table A.17.5.12/1: Stop MPC Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 Signal = x, NOTE 1 NotificationRequested (Event ID = x, NOTE 2)	
NOTE 1: The signal descriptor shall not include the "Forward media in MPC" signal. NOTE 2: The event descriptor shall not include the "Mona Preference Channel reception" event.		

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Mod.resp (Stop MPC Ack)

Table A.17.5.12/2: Stop MPC Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.13 Stop SPC

When the procedure "Stop SPC" is required the following procedure is initiated:

The MGCF sends a Mod.req command with the following information.

1 Mod.req (Stop SPC)MGCF to IM-MGW

Table A.17.5.13/1: Stop SPC Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 If legacy H.245 or accelerated H.245 required: Signal = Outgoing H245 message (Outgoing H.245 message content, SPC Out=OFF) NotificationRequested (Event ID = x, "Incoming H245 message (SPC=H245)") NOTE 3 If legacy H.245 or accelerated H.245 not required: Signal = x, NOTE 1 NotificationRequested (Event ID = x, NOTE 2)	
NOTE 1: The signal descriptor shall not include the "Outgoing H.245 message" signal. NOTE 2: The event descriptor shall not include the "Incoming H.245 message" event. NOTE 3: SPC parameter may be omitted, as SPC=H245 is the default value.		

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Mod.resp (Stop SPC Ack)

Table A.17.5.13/2: Stop SPC Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.5.14 Stop MONA Negotiation

When the procedure "Stop MONA negotiation" is required the following procedure is initiated:

The MGCF sends a Mod.req command with the following information.

1 Mod.req (Stop MONA Negotiation) MGCF to IM-MGW

Table A.17.5.14/1: Stop MONA Negotiation Request

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1 Signal = x, NOTE 1 NotificationRequested (Event ID = x, NOTE 2) If legacy H.245 or accelerated H.245 required: Signal = Outgoing H245 message (Outgoing H.245 message content, SPC Out=OFF) NotificationRequested (Event ID = x, "Incoming H245 message (SPC=H245)") NOTE 3	
NOTE 1: The signal descriptor shall not include any of the signals "Outgoing MONA preferences" and "Forward media in MPC". If legacy H.245 or accelerated H.245 is not required the signal descriptor shall also not include the "Outgoing H.245 message" signal. NOTE 2: The event descriptor shall not include any of the events "MONA Preference rcv", "MONA Preference completed" and "Mona Preference Channel reception". If legacy H.245 or accelerated H.245 is not required the event descriptor shall also not include the "Incoming H.245 message" event. NOTE 3: SPC parameter may be omitted, as SPC=H245 is the default value.		

When the processing of command (1) is complete, the IM-MGW initiates the following procedure.

2 Mod.resp (Stop MONA Negotiation Ack)

Table A.17.5.14/2: Stop MONA Negotiation Acknowledge

Address Information	Control information	Bearer information
	Transaction ID = z Context ID = c1 Termination ID = mux1	

A.17.6 SIP-I on Nc Terminations Procedures

A.17.6.1 Summary of Procedures related to a termination towards SIP-I on Nc CN Subsystem

The interworking between IMS domain and SIP-I on Nc is specified by 3GPP TS 29.235 [47] which requires the procedures for SIP-I on Nc as specified in 3GPP TS 23.231 [48] Clause 15.2.

Table A.17.6.1/1 shows the relationship between each call-related procedure in ITU-T Recommendation Q.1950 [14] (see 3GPP TS 29.205 [3]) or TS 29.232 [5] and the corresponding stage 2 procedure defined in 3GPP TS 23.231 [48].

Table A.17.6.1/1: Correspondence between ITU-T Recommendation Q.1950 [14] or 29.232 [5] call-related transactions and 3GPP TS 23.231 [48] procedures

Procedure defined in 3GPP TS 23.231 [48]	Transaction used in Q.1950 [14]	Transaction used in TS 29.232 [5]	Supported	Comment
Reserve RTP Connection Point	Not defined	Reserve RTP Connection Point (NOTE 2)	Optional (NOTE1)	See A.17.2. 2
Configure RTP Connection Point	Not Defined	Configure RTP Connection Point (NOTE 2)	Optional (NOTE1)	See A.17.2. 3
Reserve and Configure RTP Connection Point	Not defined	Reserve and Configure RTP Connection Point (NOTE 2)	Optional (NOTE1)	See A.17.2. 4
Release Termination	n. a. for reuse	Release Termination	Mandatory	Includes Subtract in the transaction. Statistics about "Ctmbits" are not applicable in Sub.resp
Change Through-Connection	n. a. for reuse	Change Through-Connection	Optional (NOTE 1)	only the Explicit (MGC Controlled Cut-Through) procedure is supported
Bearer Released	n. a. for reuse	Bearer Released	Optional (NOTE 1)	
Send Tone	n. a. for reuse	Send Tone	Optional (NOTE 1)	
Stop Tone	n. a. for reuse	Stop Tone	Optional (NOTE 1)	
Tone Completed	n. a. for reuse	Tone Completed	Optional (NOTE 1)	
Play Announcement	n. a. for reuse	Play Announcement	Optional (NOTE 1)	
Stop Announcement	n. a. for reuse	Stop Announcement	Optional (NOTE 1)	
Announcement Completed	n. a. for reuse	Announcement Completed n	Optional (NOTE 1)	
Activate Voice Processing Function	n. a. for reuse	Activate Voice Processing Function	Optional (NOTE 1)	
Termination heartbeat	Not defined	Termination heartbeat indication	Mandatory	
Not defined	Not defined	TFO Activation	Optional	
Not defined	Not defined	Codec Modify	Optional	
Not defined	Not defined	Optimal Codec and Distant List_Notify	Optional	
Not defined	Not defined	Distant Codec List	Optional	
Not defined	Not defined	TFO status Notify	Optional	
Not defined	Not defined	TFO status	Optional	
NOTE 1: Mandatory for connections towards SIP-I on Nc.				
NOTE 2: The existing IMS Connection Point Procedures are functionally similar to these 29.232 procedures as they were derived from the IMS ones.				

Annex B (normative):
Void

Annex C (normative):
Void

Annex D (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2004-09	CN#25				Approved in CN#25	2.0.0	6.0.0
2005-03	CN#27	NP-050045	001	1	Introduction Of Formal Profile	6.0.0	6.1.0
			002	1	Corrections to Mn Specification		
2005-06	CT#28	CP-050208	0001	4	Introduction Of Formal Profile	6.1.0	6.2.0
		CP-050208	0005		Inclusion of Insert Digit Procedure at IMS termination		
2005-09	CT#29	CP-050442	0007	3	Alignment of Mn Profile with ITU template and Mc interface decisions	6.2.0	6.3.0
		CP-050454	0008	3	Alignment of Mn Profile with TISPAN TMGW	6.3.0	7.0.0
2005-12	CT#30	CP-050630	0015	3	Clean-up of hanging contexts and terminations	7.0.0	7.1.0
		CP-050619	0017	1	Addition of TFO procedure		
		CP-050630	0019	2	Add virtual media gateway function		
		CP-050619	0022		Alignment with TISPAN		
		CP-050619	0023		Open Mn		
2006-03	CT#31	CP-060077	0024	1	Add the UDPTL/TCPTL transport and mediatype for T.38	7.1.0	7.2.0
		CP-060077	0026	2	Clarification the SDP used in the BICC termination		
		CP-060077	0028		Remove the redundant symbols		
		CP-060066	0030	1	Bearer Released Event to Reserve TDM Circuit procedure		
		CP-060066	0032	1	BICC packages in Mn profile		
		CP-060066	0034		Service Change Method "Disconnected" and "Failover" removal from Service Changes sent by MGCF		
2006-06	CT#32	CP-060314	0037	1	Alignment with TISPAN TGW profile	7.2.0	7.3.0
		CP-060306	0036	1	Corrections to Mn Specification for Inter Vendor Operability		
			0041		Update of Mn profile with packages defined in 29.232		
			0044	1	Adding of Bearer Released Event to Procedures related to a termination towards IM CN Subsystem		
			0046	1	Mode-change-period support on Mn interface		
2006-09	CT#33	CP-060401	0048	1	AuditValue procedure	7.3.0	7.4.0
		CP-060410	0051		Alignment Mn towards TISPAN Endorsement		
		CP-060410	0052	2	Removal of duplicated functionality in body of specification		
		CP-060401	0053	1	Definition of the use of mandatory and optional in Mn Profile Template		
		CP-060401	0054	1	Missing Procedures Towards IMS		
		CP-060410	0055	2	Correction to Terminations chapter		
		CP-060401	0058	1	Corrections to Profile Description: Descriptors		
		CP-060401	0060		Corrections to Profile Description: Command API		
		CP-060401	0062	1	Corrections to Profile Description: Packages		
2006-12	CT#34	CP-060570	0068	1	Alignment of Mn towards TISPAN Endorsement	7.4.0	7.5.0
		CP-060570	0069	1	Setting of 3GPP mandatory parameters to conditional		
		CP-060570	0074		CR miss implementation Call independent procedures and packages		
		CP-060570	0075	2	Removal of TBD for Number of Commands Per Transaction		
		CP-060570	0080		Missing Procedures Towards IMS		
		CP-060725	0071	1	Profile registration procedure		
		CP-060725	0073	2	Rules for SDP equivalents		
		CP-060725	0077	3	Codec Parameters		
2007-03	CT#35	CP-070013	0081	1	Further Alignment of Mn Towards TISPAN Endorsement	7.5.0	7.6.0
2007-06	CT#36	CP-070323	0087	1	Addition of missing references and text corrections	7.6.0	7.7.0
		CP-070434	0088	3	Multimedia interworking Mn procedures		
		CP-070323	0089	1	Wrong implementation of CP-060401 / C4-060998 (CR 0048r1 29.332 Rel-7)		
		CP-070315	0091		RFC 3309 for SCTP checksum		
2007-09	CT#37	CP-070538	0092	1	Corrections to Multimedia Interworking	7.7.0	7.8.0
			0094	3	Service Change Methods and Reasons		
			0095		Correction to Package Ids		
			0097		Priority Indicator in Context Attributes		
			0099	1	H.248 Message Encoding		
			0101	2	Correction to Reuse of Procedures		
			0103	1	Correction to Signals Descriptor		
			0105	1	Correction to Events Descriptor		
			0107	1	Clarification of Message Identifier		
			010	1	IP realm connection indication		
			011	2	Correction of parameter in Sending H.245 Message		
			0112	2	Mn profile corrections		
			0117	1	Corrections to maxptime syntax in SDP of encoding of AMR codec		
2007-12	CT#38	CP-070742	0123	1	Properties returned in commands	7.8.0	7.9.0
		CP-070746	0119	1	Inactivity timeout procedures – Alignment to Mc profile		
		CP-070746	0125	1	Audit of individual TDM terminations		
2007-12	CT#38	CP-070757	0118		Termination heartbeat – Alignment to Mc profile	7.9.0	8.0.0
2008-03	CT#39	CP-080023	0126		IP version in SDP_C	8.0.0	8.1.0
		CP-080012	0129	1	Correction on the Mn profile: BNC Release event		
2008-06	CT#40	CP-080272	0130		Updating Mn interface profile "threegimscsiw" to version 3	8.1.0	8.2.0

2008-09	CT#41	CP-080469	0131	2	Mona H.248 package definitions	8.2.0	8.3.0
		CP-080454	0134		Service Change Reason in (G)MSC Server Out of Service		
2008-12	CT#42	CP-080704	0135	1	Mona H.248 package definitions update	8.3.0	8.4.0
		CP-080704	0136		Mn profile update for Mona H.248 package definitions		
		CP-080701	0137	1	Clarification of RTCP messages usage in the interworking gateways		
		CP-080686	0138	3	Alignment of stage 3 MGCF-IM_MGW protocol with Stage 2 for SIP-I on Nc interworking to IMS		
2009-03	CT#43	CP-090031	0139	1	Mn profile update for H.245 and RTCP Interactions H.248 package definitions	8.4.0	8.5.0
			0140		Updating H.248.12 amendment 2 to reference list		
2009-06	CT#44	CP-090298	0141	1	Update of stage 3 MONA to newest H.248.72 (ex. H.248.MONA) draft	8.5.0	8.6.0
			0142		Update of MONA stage 3 due to MONA procedures stage 2 changes		
2009-12	CT#46	CP-090967	0147		Correction to Profile for Commands marked optional	8.6.0	8.7.0
		CP-090763	0148		Commands Using IP Interface Type		
2009-12	CT#46				Upgraded unchanged from Rel-8	8.7.0	9.0.0
2010-03	CT#47	CP-100028	0152		MONA H.248 package update	9.0.0	9.1.0
		CP-100028	0154	1	ASN.1 encoding of RTCP Feedback Message package		
		CP-100028	0157		MONA alignments to H.324		
		CP-100037	0150	1	Global Text Telephony Interworking between IMS and Circuit Switched		
		CP-100037	0155	1	Resolution of External TISPAN Referencing		
2010-09	CT#47	CP-100450	0159	-	ITU-T H.248.71 and H.248.72 publication	9.1.0	9.2.0
2011-03	CT#51	CP-110276	0160	10	ECN Support in Mn Interface	9.2.0	10.0.0
		CP-110070	0161	1	Complete Inactivity Timeout Indication Procedure		
		CP-110058	0163	1	Handling of rtcp-fb SDP attribute and SDP attribute for RTCP APP feedback messages		
2011-06	CT#52	CP-110352	0168	1	Missing Tone Completed procedures	10.0.0	10.1.0
		CP-110368	0165	1	ECN Failure improvements		
		CP-110368	0170	1	Alignment of 3GPP profiles with SG16 ECN package definition		
2011-09	CT#53	CP-110568	0171	1	Solving Incorrect references	10.1.0	10.2.0
2011-12	CT#54	CP-110798	0172	-	Explicit Congestion Notification		
		CP-110789	0173	1	Reference update: 26.114	10.2.0	10.3.0
2012-06	CT#56	CP-120226	0175	1	Reference update: draft-ietf-avtcore-ecn-for-rtp	10.3.0	10.4.0
					Editorial fix to history table	10.4.0	10.4.1
2012-09	CT#57	CP-120443	0181	-	Reference alignment for RTP Payload Format for AMR and AMR-WB Audio Codecs	10.4.1	10.5.0
2012-09	CT#57	CP-120478	0176	3	Support of Multimedia Priority Service (MPS) over Mn Interface – Stage 3	10.5.0	11.0.0
		CP-120684	0178	1	Support of T.38 related SDP attributes		
2012-12	CT#58	CP-120723	0185	-	Mn interface updates of ECN Support Package	11.0.0	11.1.0
		CP-120738	0186	-	T.38 default version		
2013-03	CT#59	CP-130013	0192	1	Support of RTCP-FB for MTSI	11.1.0	11.2.0
2013-06	CT#60	CP-130294	0188	2	ECN relying reference change	11.2.0	11.3.0
2014-06	CT#64	CP-140248	0193	2	ICE support in Mn interface	11.3.0	12.0.0
2014-06	CT#66	CP-140788	0194	1	Adding support for EVS codec	12.0.0	12.1.0
2015-09	CT#69	CP-150430	0196	1	Correction on SDP for Real-Time Text	12.1.0	13.0.0
2016-03	CT#71	CP-160048	0197	-	Removal of references to TS 26.236	13.0.0	13.1.0
2016-03	CT#71	CP-160034	0198	1	Support of enhanced bandwidth negotiation mechanism for MTSI sessions	13.0.0	13.1.0
2016-03	CT#71	CP-160021	0199	1	Mn stage 3 to support SDP Capability Negotiation	13.0.0	13.1.0
2016-06	CT#72	CP-160229	0200	-	Rate adaptation clarification	13.1.0	13.2.0
2016-06	CT#72	CP-160229	0201	-	Clarifications related to the rate adaptation for media endpoints	13.1.0	13.2.0
2017-03	CT#75	-	-	-	Update to Rel-14 version (MCC)	13.2.0	14.0.0

History

Document history		
V14.0.0	April 2017	Publication