

# ETSI TS 129 520 V15.11.0 (2023-04)



**5G;  
5G System;  
Network Data Analytics Services;  
Stage 3  
(3GPP TS 29.520 version 15.11.0 Release 15)**



---

**Reference**

RTS/TSGC-0329520vfb0

---

**Keywords**

5G

**ETSI**

650 Route des Lucioles  
F-06921 Sophia Antipolis Cedex - FRANCE

---

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B  
Association à but non lucratif enregistrée à la  
Sous-Préfecture de Grasse (06) N° w061004871

---

**Important notice**

The present document can be downloaded from:

<https://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at [www.etsi.org/deliver](http://www.etsi.org/deliver).

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommitteeSupportStaff.aspx>

If you find a security vulnerability in the present document, please report it through our  
Coordinated Vulnerability Disclosure Program:

<https://www.etsi.org/standards/coordinated-vulnerability-disclosure>

---

**Notice of disclaimer & limitation of liability**

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

---

**Copyright Notification**

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2023.  
All rights reserved.

---

# Intellectual Property Rights

## Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

## Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

**DECT™**, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™** and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

---

# Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <https://webapp.etsi.org/key/queryform.asp>.

---

# Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

# Contents

Intellectual Property Rights .....	2
Legal Notice .....	2
Modal verbs terminology.....	2
Foreword.....	6
1 Scope .....	7
2 References .....	7
3 Definitions and abbreviations.....	8
3.1 Definitions .....	8
3.2 Abbreviations .....	8
4 Services offered by the NWDAF .....	8
4.1 Introduction .....	8
4.2 Nnwdaf_EventsSubscription Service .....	9
4.2.1 Service Description.....	9
4.2.1.1 Overview.....	9
4.2.1.2 Service Architecture.....	9
4.2.1.3 Network Functions.....	10
4.2.1.3.1 Network Data Analytics Function (NWDAF).....	10
4.2.1.3.2 NF Service Consumers .....	10
4.2.2 Service Operations .....	10
4.2.2.1 Introduction.....	10
4.2.2.2 Nnwdaf_EventsSubscription_Subscribe service operation .....	11
4.2.2.2.1 General .....	11
4.2.2.2.2 Subscription for event notifications.....	11
4.2.2.2.3 Update subscription for event notifications.....	12
4.2.2.3 Nnwdaf_EventsSubscription_Unsubscribe service operation.....	12
4.2.2.3.1 General .....	12
4.2.2.3.2 Unsubscribe from event notifications.....	12
4.2.2.4 Nnwdaf_EventsSubscription_Notify service operation .....	13
4.2.2.4.1 General .....	13
4.2.2.4.2 Notification about subscribed event .....	13
4.3 Nnwdaf_AnalyticsInfo Service .....	14
4.3.1 Service Description.....	14
4.3.1.1 Overview.....	14
4.3.1.2 Service Architecture.....	14
4.3.1.3 Network Functions.....	15
4.3.1.3.1 Network Data Analytics Function (NWDAF).....	15
4.3.1.3.2 NF Service Consumers .....	15
4.3.2 Service Operations .....	15
4.3.2.1 Introduction.....	15
4.3.2.2 Nnwdaf_AnalyticsInfo_Request service operation .....	15
4.3.2.2.1 General .....	15
4.3.2.2.2 Request and get from NWDAF Analytics information .....	16
5 API Definitions .....	16
5.1 Nnwdaf_EventsSubscription Service API.....	16
5.1.1 Introduction.....	16
5.1.2 Usage of HTTP.....	17
5.1.2.1 General .....	17
5.1.2.2 HTTP standard headers .....	17
5.1.2.2.1 General .....	17
5.1.2.2.2 Content type .....	17
5.1.2.3 HTTP custom headers .....	17
5.1.3 Resources.....	18
5.1.3.1 Resource Structure .....	18

5.1.3.2	Resource: NWDAF Events Subscriptions.....	18
5.1.3.2.1	Description .....	18
5.1.3.2.2	Resource definition.....	18
5.1.3.2.3	Resource Standard Methods .....	19
5.1.3.2.3.1	POST.....	19
5.1.3.2.4	Resource Custom Operations .....	19
5.1.3.3	Resource: Individual NWDAF Event Subscription .....	19
5.1.3.3.1	Description .....	19
5.1.3.3.2	Resource definition.....	19
5.1.3.3.3	Resource Standard Methods .....	19
5.1.3.3.3.1	DELETE .....	19
5.1.3.3.3.2	PUT .....	20
5.1.3.3.4	Resource Custom Operations .....	21
5.1.4	Custom Operations without associated resources .....	21
5.1.5	Notifications .....	21
5.1.5.1	General .....	21
5.1.5.2	Event Notification .....	21
5.1.5.2.1	Description .....	21
5.1.5.2.2	Operation Definition.....	21
5.1.6	Data Model .....	22
5.1.6.1	General .....	22
5.1.6.2	Structured data types .....	22
5.1.6.2.1	Introduction .....	22
5.1.6.2.2	Type NnwdafEventsSubscription .....	23
5.1.6.2.3	Type EventSubscription .....	23
5.1.6.2.4	Type NnwdafEventsSubscriptionNotification .....	24
5.1.6.2.5	Type EventNotification .....	24
5.1.6.2.6	Type SliceLoadLevelInformation.....	24
5.1.6.3	Simple data types and enumerations .....	24
5.1.6.3.1	Introduction .....	24
5.1.6.3.2	Simple data types.....	24
5.1.6.3.3	Enumeration: NotificationMethod.....	25
5.1.6.3.4	Enumeration: NwdafEvent .....	25
5.1.7	Error handling.....	25
5.1.7.1	General .....	25
5.1.7.2	Protocol Errors .....	25
5.1.7.3	Application Errors.....	25
5.1.8	Feature negotiation .....	25
5.1.9	Security .....	26
5.2	Nnwdaf_AnalyticsInfo Service API.....	26
5.2.1	Introduction.....	26
5.2.2	Usage of HTTP.....	26
5.2.2.1	General .....	26
5.2.2.2	HTTP standard headers .....	26
5.2.2.2.1	General .....	26
5.2.2.2.2	Content type .....	27
5.2.2.3	HTTP custom headers .....	27
5.2.3	Resources.....	27
5.2.3.1	Resource Structure .....	27
5.2.3.2	Resource: NWDAF Analytics.....	27
5.2.3.2.1	Description .....	27
5.2.3.2.2	Resource definition.....	27
5.2.3.2.3	Resource Standard Methods .....	28
5.2.3.2.3.1	GET.....	28
5.2.3.2.4	Resource Custom Operations .....	28
5.2.4	Custom Operations without associated resources .....	28
5.2.5	Notifications .....	28
5.2.6	Data Model .....	28
5.2.6.1	General .....	28
5.2.6.2	Structured data types .....	29
5.2.6.2.1	Introduction .....	29
5.2.6.2.2	Type AnalyticsData .....	29

5.2.6.2.3	Type EventFilter .....	29
5.2.6.3	Simple data types and enumerations .....	30
5.2.6.3.1	Introduction .....	30
5.2.6.3.2	Simple data types.....	30
5.2.6.3.3	Enumeration: EventId.....	30
5.2.7	Error handling .....	30
5.2.7.1	General .....	30
5.2.7.2	Protocol Errors .....	30
5.2.7.3	Application Errors.....	30
5.2.8	Feature negotiation .....	30
5.2.9	Security .....	31
<b>Annex A (normative):</b>	<b>OpenAPI specification.....</b>	<b>32</b>
A.1	General .....	32
A.2	Nnwdaf_EventsSubscription API.....	32
A.3	Nnwdaf_AnalyticsInfo API.....	36
<b>Annex B (informative):</b>	<b>Change history .....</b>	<b>39</b>
History .....		40

---

# Foreword

This Technical Specification has been produced by the 3<sup>rd</sup> Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
  - 1 presented to TSG for information;
  - 2 presented to TSG for approval;
  - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

---

# 1 Scope

The present specification provides the stage 3 definition of the Network Data Analytics Function Services of the 5G System.

The 5G System Architecture is defined in 3GPP TS 23.501 [2]. The stage 2 definition and related procedures for Network Data Analytics Function Services are specified in 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4].

The 5G System stage 3 call flows are provided in 3GPP TS 29.513 [5].

The Technical Realization of the Service Based Architecture and the Principles and Guidelines for Services Definition are specified in 3GPP TS 29.500 [6] and 3GPP TS 29.501 [7].

The Network Data Analytics Function Services are provided by the Network Data Analytics Function (NWDAF). These services provide NWDAF slice congestion events notification and NWDAF specific analytics.

---

# 2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.501: "System Architecture for the 5G System; Stage 2".
- [3] 3GPP TS 23.502: "Procedures for the 5G System; Stage 2".
- [4] 3GPP TS 23.503: "Policy and Charging Control Framework for the 5G System; Stage 2".
- [5] 3GPP TS 29.513: "5G System; Policy and Charging Control signalling flows and QoS parameter mapping; Stage 3".
- [6] 3GPP TS 29.500: "5G System; Technical Realization of Service Based Architecture; Stage 3".
- [7] 3GPP TS 29.501: "5G System; Principles and Guidelines for Services Definition; Stage 3".
- [8] 3GPP TS 29.571: "5G System; Common Data Types for Service Based Interfaces; Stage 3".
- [9] IETF RFC 7540: "Hypertext Transfer Protocol Version 2 (HTTP/2)".
- [10] IETF RFC 8259: "The JavaScript Object Notation (JSON) Data Interchange Format".
- [11] OpenAPI, "OpenAPI 3.0.0 Specification", <https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.0.md>.
- [12] 3GPP TS 29.510: "5G System; Network Function Repository Services; Stage 3".
- [13] 3GPP TS 33.501: "Security architecture and procedures for 5G system".
- [14] IETF RFC 6749: "The OAuth 2.0 Authorization Framework".
- [15] IETF RFC 7807: "Problem Details for HTTP APIs".
- [16] 3GPP TR 21.900: "Technical Specification Group working methods".



## 3 Definitions and abbreviations

### 3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in 3GPP TR 21.905 [1].

### 3.2 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

API	Application Programming Interface
JSON	JavaScript Object Notation
HTTP	Hypertext Transfer Protocol
NF	Network Function
NRF	Network Repository Function
NWDAF	Network Data Analytics Function
NSSF	Network Slice Selection Function
PCF	Policy Control Function

## 4 Services offered by the NWDAF

### 4.1 Introduction

The Nnwdaf services are used for the NWDAF to provide network data analytics (i.e. load level information). These services provide NWDAF slice congestion events notification and NWDAF specific analytics.

The following services are specified for NWDAF:

**Table 4.1-1: Services provided by NWDAF**

Service Name	Description	Service Operations	Operation Semantics	Example Consumer(s)
Nnwdaf_EventsSubscription	This service enables the NF service consumers to subscribe/unsubscribe for network slice specific congestion events notification from the NWDAF.	Subscribe	Subscribe / Notify	PCF, NSSF
		Unsubscribe		
		Notify		
Nnwdaf_AnalyticsInfo	This service enables the NF service consumers to request and get specific analytics from NWDAF.	Request	Request / Response	PCF, NSSF

## 4.2 Nnwdaf\_EventsSubscription Service

### 4.2.1 Service Description

#### 4.2.1.1 Overview

The Nnwdaf\_EventsSubscription Service as defined in 3GPP TS 23.501 [2], 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4], is provided by the Network Data Analytics Function (NWDAF).

This service:

- allows NF consumers to subscribe to and unsubscribe from load events of network slice; and
- notifies NF consumers with a corresponding subscription about observed events.

The types of observed events include:

- Load level of network slice.

#### 4.2.1.2 Service Architecture


The 5G System Architecture is defined in 3GPP TS 23.501 [2]. The Policy and Charging related 5G architecture is also described in 3GPP TS 23.503 [4] and 3GPP TS 29.513 [5].

The Nnwdaf\_EventsSubscription service is part of the Nnwdaf service-based interface exhibited by the Network Data Analytics Function (NWDAF).


Known consumers of the Nnwdaf\_EventsSubscription service are:

- Policy Control Function (PCF)
- Network Slice Selection Function (NSSF)

The PCF accesses the Nnwdaf\_EventsSubscription service at the NWDAF via the N23 Reference point. The NSSF accesses the Nnwdaf\_EventsSubscription service at the NWDAF via the N34 Reference point.



**Figure 4.2.1.2-1: Reference Architecture for the Nnwdaf\_EventsSubscription Service; SBI representation**



**Figure 4.2.1.2-2: Reference Architecture for the Nnwdaf\_EventsSubscription Service: reference point representation**

### 4.2.1.3 Network Functions

#### 4.2.1.3.1 Network Data Analytics Function (NWDAF)

The Network Data Analytics Function (NWDAF) provides:

- Identifier of network slice; and
- load level information for that network slice.

The Network Data Analytics Function (NWDAF) allows NF consumers to subscribe to and unsubscribe from periodic notification and/or notification when a threshold is exceeded.

#### 4.2.1.3.2 NF Service Consumers

The Policy Control Function (PCF):

- Supports taking input from Network Data Analytics Function (NWDAF) into consideration for policies on assignment of network resources and for traffic steering policies.

NOTE: How this information is used by the PCF is not standardized in this release of the specification.

The Network Slice Selection Function (NSSF):

- supports taking load level information from Network Data Analytics Function (NWDAF) into consideration for slice selection.

## 4.2.2 Service Operations

### 4.2.2.1 Introduction

**Table 4.2.2.1-1: Operations of the Nnwdaf\_EventsSubscription Service**

Service operation name	Description	Initiated by
Nnwdaf_EventsSubscription_Subscribe	This service operation is used by an NF to subscribe or update subscription for event notifications for a specified network slice. Periodic notification and notification upon threshold exceeded can be subscribed.	NF consumer (PCF, NSSF)
Nnwdaf_EventsSubscription_UnSubscribe	This service operation is used by an NF to unsubscribe from event notifications.	NF consumer (PCF, NSSF)
Nnwdaf_EventsSubscription_Notify	This service operation is used by an NWDAF to notify NF consumers about subscribed events.	NWDAF

## 4.2.2.2 Nnwdaq\_EventsSubscription\_Subscribe service operation

### 4.2.2.2.1 General

The Nnwdaq\_EventsSubscription\_Subscribe service operation is used by an NF service consumer to subscribe or update subscription for event notifications. The following are the types of events for which a subscription may be made:

- Load level of network slice.

### 4.2.2.2.2 Subscription for event notifications

Figure 4.2.2.2.2-1 shows a scenario where the NF service consumer sends a request to the NWDAF to subscribe for event notifications (see also 3GPP TS 23.502 [3] figure 4.19.1-1 step 1).



**Figure 4.2.2.2.2-1: NF service consumer subscribes to notifications**

The NF service consumer shall invoke the Nnwdaq\_EventsSubscription\_Subscribe service operation to subscribe to event notification(s). The NF service consumer shall send an HTTP POST request with "{apiRoot}/nnwdaq-eventssubscription/v1/subscriptions" as Resource URI representing the "NWDAF Events Subscriptions", as shown in figure 4.2.2.2.2-1, step 1, to create a subscription for an "Individual NWDAF Event Subscription" according to the information in message body. The NnwdaqEventsSubscription data structure provided in the request body shall include:

- a description of the subscribed events as "eventSubscriptions" attribute that for each event shall include
  - a) an event identifier as "event" attribute;
  - b) identification of network slice(s) to which the subscription applies via:
    - 1) identification of network slice(s) by "snssais" attribute; or
    - 2) any slices indication via the "anySlice" attribute;

and that may include:

- a) event notification method (periodic, upon threshold exceeded) as "notificationMethod" attribute;

NOTE: If the event notification method is not supplied, the default value "upon threshold exceed" applies.

- an URI where to receive the requested notifications as "notificationURI" attribute; and
- a list of supported features by the service consumer as "supportedFeatures" attribute.

Upon the reception of an HTTP POST request with: "{apiRoot}/nnwdaq-eventssubscription/v1/subscriptions" as Resource URI and NnwdaqEventsSubscription data structure as request body, the NWDAF shall:


- create a new subscription;
- assign an event subscriptionId;
- store the subscription.

If the NWDAF created an "Individual NWDAF Event Subscription" resource, the NWDAF shall respond with "201 Created" with the message body containing a representation of the created subscription, as shown in figure 4.2.2.2.2-1,

step 2. The NWDAF shall include a Location HTTP header field. The Location header field shall contain the URI of the created subscription i.e. "{apiRoot}/nwdaf-eventssubscription/v1/subscriptions/{subscriptionId}".

#### 4.2.2.2.3 Update subscription for event notifications

Figure 4.2.2.2.3-1 shows a scenario where the NF service consumer sends a request to the NWDAF to update the subscription for event notifications (see also 3GPP TS 23.502 [3] figure 4.19.1-1 step 1).



**Figure 4.2.2.2.3-1: NF service consumer updates subscription to notifications**

The NF service consumer shall invoke the `Nnwdaf_EventsSubscription_Subscribe` service operation to update subscription to event notifications. The NF service consumer shall send an HTTP PUT request with "{apiRoot}/nwdaf-eventssubscription/v1/subscriptions/{subscriptionId}" as Resource URI representing the "Individual NWDAF Event Subscription", as shown in figure 4.2.2.2.3-1, step 1, to update the subscription for an "Individual NWDAF Event Subscription" resource identified by the {subscriptionId}. The `NnwdafEventsSubscription` data structure provided in the request body shall include the same contents as described in subclause 4.2.2.2.2:

Upon the reception of an HTTP PUT request with: "{apiRoot}/nwdaf-eventssubscription/v1/subscriptions/{subscriptionId}" as Resource URI and `NnwdafEventsSubscription` data structure as request body, the NWDAF shall:

- update the subscription of corresponding subscriptionId; and
- store the subscription.

If the NWDAF updated an "Individual NWDAF Event Subscription" resource, the NWDAF shall respond with:

- a) HTTP "200 OK" status code with the message body containing a representation of the updated subscription, as shown in figure 4.2.2.2.3-1, step 2a; or
- b) HTTP "204 No Content" status code, as shown in figure 4.2.2.2.3-1, step 2b.

If the Individual NWDAF Event Subscription resource does not exist, the NWDAF shall respond with "404 Not Found".


### 4.2.2.3 Nnwdaf\_EventsSubscription\_Unsubscribe service operation

#### 4.2.2.3.1 General

The `Nnwdaf_EventsSubscription_Unsubscribe` service operation is used by an NF service consumer to unsubscribe from event notifications.

#### 4.2.2.3.2 Unsubscribe from event notifications

Figure 4.2.2.3.2-1 shows a scenario where the NF service consumer sends a request to the NWDAF to unsubscribe from event notifications (see also 3GPP TS 23.502 [3] figure 4.19.1-1 step 1).



**Figure 4.2.2.3.2-1: NF service consumer unsubscribes from notifications**

The NF service consumer shall invoke the `Nnwdaf_EventsSubscription_UnSubscribe` service operation to unsubscribe to event notifications. The NF service consumer shall send an HTTP DELETE request with: "`{apiRoot}/nwdaf-eventssubscription/v1/subscriptions/{subscriptionId}`" as Resource URI, where "`{subscriptionId}`" is the event subscriptionId of the existing subscription that is to be deleted.

Upon the the reception of an HTTP DELETE request with: "`{apiRoot}/nwdaf-eventssubscription/v1/subscriptions/{subscriptionId}`" as Resource URI, the NWDAF shall:

- remove the corresponding subscription.

If the HTTP request message from the NF service consumer is accepted, the NWDAF shall respond with "204 No Content".

If the Individual NWDAF Event Subscription resource does not exist, the NWDAF shall respond with "404 Not Found".


#### 4.2.2.4 Nnwdaf\_EventsSubscription\_Notify service operation

##### 4.2.2.4.1 General

The `Nnwdaf_EventsSubscription_Notify` service operation is used by an NWDAF to notify NF consumers about subscribed events.

##### 4.2.2.4.2 Notification about subscribed event

Figure 4.2.2.4.2-1 shows a scenario where the NWDAF sends a request to the NF Service Consumer to notify for event notifications (see also 3GPP TS 23.502 [3] figure 4.19.1-1 step 2).



**Figure 4.2.2.4.2-1: NWDAF notifies the subscribed event**

The NWDAF shall invoke the `Nnwdaf_EventsSubscription_Notify` service operation to notify the subscribed event. The NWDAF shall send an HTTP POST request with "`{notificationURI}`" received in the `Nnwdaf_EventsSubscription_Subscribe` service operation as Resource URI, as shown in figure 4.2.2.2.2-1, step 1. The `NnwdafEventsSubscriptionNotification` data structure provided in the request body that shall include:

- a description of the notified event as "eventNotifications" attribute that for each event shall include:

- a) an event identifier as "event" attribute;
- b) identification of network slice(s) to which the notification applies as "snssais" attribute;
- c) load level information as "loadLevelInformation" attribute; and
- an event subscriptionId as "subscriptionId" attribute.

Upon the reception of an HTTP POST request with: "{notificationURI}" as Resource URI and NnwdafEventsSubscriptionNotification data structure as request body, the NF Service Consumer shall:

- store the notification.

If the HTTP request message from the NWDAF is accepted, the NF Service Consumer shall respond with "204 No Content".

## 4.3 Nnwdaf\_AnalyticsInfo Service

### 4.3.1 Service Description

#### 4.3.1.1 Overview

The Nnwdaf\_AnalyticsInfo Service as defined in 3GPP TS 23.501 [2], 3GPP TS 23.502 [3] and 3GPP TS 23.503 [4], is provided by the Network Data Analytics Function (NWDAF).

This service:

- allows NF consumers to request and get load level information of network slice.

#### 4.3.1.2 Service Architecture


The 5G System Architecture is defined in 3GPP TS 23.501 [2]. The Policy and Charging related 5G architecture is also described in 3GPP TS 23.503 [4] and 3GPP TS 29.513 [5].

The Nnwdaf\_AnalyticsInfo service is part of the Nnwdaf service-based interface exhibited by the Network Data Analytics Function (NWDAF).


Known consumers of the Nnwdaf\_AnalyticsInfo service are:

- Policy Control Function (PCF)
- Network Slice Selection Function (NSSF)

The PCF accesses the Nnwdaf\_AnalyticsInfo service at the NWDAF via the N23 Reference point. The NSSF accesses the Nnwdaf\_AnalyticsInfo service at the NWDAF via the N34 Reference point.



**Figure 4.3.1.2-1: Reference Architecture for the Nnwdaf\_AnalyticsInfo Service; SBI representation**



**Figure 4.3.1.2-2: Reference Architecture for the Nnwdaf\_AnalyticsInfo Service: reference point representation**

### 4.3.1.3 Network Functions

#### 4.3.1.3.1 Network Data Analytics Function (NWDAF)

The Network Data Analytics Function (NWDAF) provides specific analytics:

- Identifier of network slice; and
- load level information for that network slice.

#### 4.3.1.3.2 NF Service Consumers

The Policy Control Function (PCF):

- Supports taking input from Network Data Analytics Function (NWDAF) into consideration for policies on assignment of network resources and for traffic steering policies.

NOTE: How this information is used by the PCF is not standardized in this release of the specification.

The Network Slice Selection Function (NSSF):

- supports taking load level information from Network Data Analytics Function (NWDAF) into consideration for slice selection.

## 4.3.2 Service Operations

### 4.3.2.1 Introduction

**Table 4.3.2.1-1: Operations of the Nnwdaf\_AnalyticsInfo Service**

Service operation name	Description	Initiated by
Nnwdaf_AnalyticsInfo_Request	This service operation is used by an NF to request and get specific analytics from NWDAF.	NF consumer (PCF, NSSF)

#### 4.3.2.2 Nnwdaf\_AnalyticsInfo\_Request service operation


##### 4.3.2.2.1 General

The Nnwdaf\_AnalyticsInfo\_Request service operation is used by an NF service consumer to request and get specific analytics information from the NWDAF.



#### 4.3.2.2.2 Request and get from NWDAF Analytics information

Figure 4.3.2.2.2-1 shows a scenario where the NF service consumer (e.g. PCF) sends a request to the NWDAF to request and get from NWDAF analytics information (see also 3GPP TS 23.502 [3] figure 4.19.2-1 step 1).



**Figure 4.3.2.2.2-1: Requesting a NWDAF Analytics information**

The NF service consumer (e.g. PCF) shall invoke the `Nnwdaf_AnalyticsInfo_Request` service operation when requesting the NWDAF analytics information of particular network slice. The NF service consumer shall send an HTTP GET request on the resource URI "`{apiRoot}/nnwdaf-analyticsinfo/v1/analytics`" representing the "NWDAF Analytics" (as shown in figure 4.3.2.2.2-1, step 1), to request analytics data according to the query parameter value of the "event-id" attribute. The "event-filter" attribute provided as a query parameter in the request shall include:

- identification of network slice(s) when the event-id is "LOAD\_LEVEL\_INFORMATION" via:
  - 1) identification of network slice(s) by "snssais" attribute; or
  - 2) any slices indication via the "anySlice" attribute.

The request may include the "supported-features" attribute as query parameter to indicate the features supported by the service consumer.

Upon the the reception of the HTTP GET request, the NWDAF shall:

- analyse the requested analytic data. For event-id of "LOAD\_LEVEL\_INFORMATION", the NWDAF shall analyse the load level information of corresponding network slice(s).

If the HTTP request message from the NF service consumer is accepted, the NWDAF shall respond with "200 OK" status code with the message body containing the analytics with parameters as relevant for the requesting NF service consumer. The AnalyticsData data structure in the response body shall include:

- analytics with parameters indicated in the request. For event-id of "LOAD\_LEVEL\_INFORMATION", the analytics shall include the load level information of corresponding network slice.

If the request NWDAF Analytics data does not exist, the NWDAF shall respond with "204 No Content".

## 5 API Definitions

### 5.1 Nnwdaf\_EventsSubscription Service API

#### 5.1.1 Introduction

The Nnwdaf\_EventsSubscription Service shall use the Nnwdaf\_EventsSubscription API.

The request URI used in each HTTP request from the NF service consumer towards the NWDAF shall have the structure defined in subclause 4.4.1 of 3GPP TS 29.501 [7], i.e.:

`{apiRoot}/{apiName}/{apiVersion}/{apiSpecificResourceUriPart}`

with the following components:

- The {apiRoot} shall be set as described in 3GPP TS 29.501 [7].
- The {apiName} shall be "nnwdaf-eventssubscription".
- The {apiVersion} shall be "v1".
- The {apiSpecificResourceUriPart} shall be set as described in subclause 5.1.3.

## 5.1.2 Usage of HTTP

### 5.1.2.1 General

HTTP/2, IETF RFC 7540 [9], shall be used as specified in clause 5 of 3GPP TS 29.500 [6].

HTTP/2 shall be transported as specified in subclause 5.3 of 3GPP TS 29.500 [6].

The OpenAPI [11] specification of HTTP messages and content bodies for the Nnwdaf\_EventsSubscription is contained in Annex A.

### 5.1.2.2 HTTP standard headers

#### 5.1.2.2.1 General

See subclause 5.2.2 of 3GPP TS 29.500 [6] for the usage of HTTP standard headers.

#### 5.1.2.2.2 Content type

JSON, IETF RFC 8259 [10], shall be used as content type of the HTTP bodies specified in the present specification as specified in subclause 5.4 of 3GPP TS 29.500 [6]. The use of the JSON format shall be signalled by the content type "application/json".

"Problem Details" JSON object shall be used to indicate additional details of the error in a HTTP response body and shall be signalled by the content type "application/problem+json", as defined in IETF RFC 7807 [15].


### 5.1.2.3 HTTP custom headers

The Nnwdaf\_EventsSubscription Service API shall support HTTP custom header fields specified in subclause 5.2.3.2 of 3GPP TS 29.500 [6].

In this release of the specification, no specific custom headers are defined for the Nnwdaf\_EventsSubscription Service API.

### 5.1.3 Resources

#### 5.1.3.1 Resource Structure



**Figure 5.1.3.1-1: Resource URI structure of the Nnwdaf\_EventsSubscription API**

Table 5.1.3.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 5.1.3.1-1: Resources and methods overview**

Resource name	Resource URI	HTTP method or custom operation	Description
NWDAF Events Subscriptions	{apiRoot}/nnwdaf-eventssubscription/v1/subscriptions	POST	Creates a new Individual NWDAF Events Subscription resource.
Individual NWDAF Event Subscription	{apiRoot}/nnwdaf-eventssubscription/v1/subscriptions/{subscriptionId}	DELETE	Deletes an Individual NWDAF Events Subscription identified by subresource {subscriptionId}.
		PUT	Modifies an existing Events Subscription subresource.

#### 5.1.3.2 Resource: NWDAF Events Subscriptions

##### 5.1.3.2.1 Description

The NWDAF Events Subscriptions resource represents all subscriptions to the Nnwdaf\_EventsSubscription Service at a given NWDAF.

##### 5.1.3.2.2 Resource definition

Resource URI: **{apiRoot}/nnwdaf-eventssubscription/v1/subscriptions**

This resource shall support the resource URI variables defined in table 5.1.3.2.2-1.

**Table 5.1.3.2.2-1: Resource URI variables for this resource**

Name	Definition
apiRoot	See subclause 5.1.1

### 5.1.3.2.3 Resource Standard Methods

#### 5.1.3.2.3.1 POST

This method shall support the URI query parameters specified in table 5.1.3.2.3.1-1.

**Table 5.1.3.2.3.1-1: URI query parameters supported by the POST method on this resource**

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 5.1.3.2.3.1-2 and the response data structures and response codes specified in table 5.1.3.2.3.1-3.

**Table 5.1.3.2.3.1-2: Data structures supported by the POST Request Body on this resource**

Data type	P	Cardinality	Description
NnwdafEventsSubscription	M	1	Create a new Individual NWDAF Event Subscription resource.

**Table 5.1.3.2.3.1-3: Data structures supported by the POST Response Body on this resource**

Data type	P	Cardinality	Response codes	Description
NnwdafEventsSubscription	M	1	201 Created	The creation of an Individual NWDAF Event Subscription resource is confirmed and a representation of that resource is returned.
NOTE: The mandatory HTTP error status codes for the POST method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [6] also apply.				

#### 5.1.3.2.4 Resource Custom Operations

None in this release of the specification.

### 5.1.3.3 Resource: Individual NWDAF Event Subscription

#### 5.1.3.3.1 Description

The Individual NWDAF Events Subscription resource represents a single subscription to the Nnwdaf\_EventsSubscription Service at a given NWDAF.

#### 5.1.3.3.2 Resource definition

Resource URI: {apiRoot}/nnwdaf-eventsubscription/v1/subscriptions/{subscriptionId}

This resource shall support the resource URI variables defined in table 5.1.3.3.2-1.

**Table 5.1.3.3.2-1: Resource URI variables for this resource**

Name	Definition
apiRoot	See subclause 5.1.1
subscriptionId	String identifying a subscription to the NnwdafEventsSubscription Service

### 5.1.3.3.3 Resource Standard Methods

#### 5.1.3.3.3.1 DELETE

This method shall support the URI query parameters specified in table 5.1.3.3.3.1-1.

**Table 5.1.3.3.3.1-1: URI query parameters supported by the DELETE method on this resource**

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 5.1.3.3.3.1-2 and the response data structures and response codes specified in table 5.1.3.3.3.1-3.

**Table 5.1.3.3.3.1-2: Data structures supported by the DELETE Request Body on this resource**

Data type	P	Cardinality	Description
n/a			

**Table 5.1.3.3.3.1-3: Data structures supported by the DELETE Response Body on this resource**

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	Successful case: The Individual NWDAF Event Subscription resource matching the subscriptionId was deleted.
ProblemDetails	M	1	404 Not Found	The Individual NWDAF Event Subscription resource does not exist. (NOTE 2)
NOTE 1: The mandatory HTTP error status codes for the DELETE method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [6] also apply.				
NOTE 2: Failure cases are described in subclause 5.1.7.				

#### 5.1.3.3.3.2 PUT

This method shall support the URI query parameters specified in table 5.1.3.3.3.2-1.

**Table 5.1.3.3.3.2-1: URI query parameters supported by the PUT method on this resource**

Name	Data type	P	Cardinality	Description
n/a				

This method shall support the request data structures specified in table 5.1.3.3.3.2-2 and the response data structures and response codes specified in table 5.1.3.3.3.2-3.

**Table 5.1.3.3.3.2-2: Data structures supported by the PUT Request Body on this resource**

Data type	P	Cardinality	Description
NnwdafeventsSubscription	M	1	Parameters to replace a subscription to NWDAF Event Subscription resource.

**Table 5.1.3.3.3.2-3: Data structures supported by the PUT Response Body on this resource**

Data type	P	Cardinality	Response codes	Description
NnwdafeventsSubscription	M	1	200 OK	The Individual NWDAF Event Subscription resource was modified successfully and a representation of that resource is returned.
n/a			204 No Content	The Individual NWDAF Event Subscription resource was modified successfully.
ProblemDetails	M	1	404 Not Found	The Individual NWDAF Event Subscription resource does not exist. (NOTE 2)
NOTE 1: The mandatory HTTP error status codes for the PUT method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [6] also apply.				
NOTE 2: Failure cases are described in subclause 5.1.7.				

#### 5.1.3.3.4 Resource Custom Operations

None in this release of the specification.

### 5.1.4 Custom Operations without associated resources

None in this release of the specification.

## 5.1.5 Notifications

### 5.1.5.1 General

Notifications shall comply with subclause 6.2 of 3GPP TS 29.500 [6] and subclause 4.6.2.3 of 3GPP TS 29.501 [7].

**Table 5.3.3.4.1-1: Notifications**

Custom operation URI	Mapped HTTP method	Description
{notificationURI}	POST	Report one or several observed Events.

### 5.1.5.2 Event Notification

#### 5.1.5.2.1 Description

The Event Notification is used by the NWDAF to report one or several observed Events to a NF service consumer that has subscribed to such Notifications via the Individual NWDAF Event Subscription Resource.

#### 5.1.5.2.2 Operation Definition

URI: {notificationURI}

The operation shall support the URI variables defined in table 5.1.5.2.2-1, the request data structures specified in table 5.1.5.2.2-2 and the response data structure and response codes specified in table 5.1.5.2.2-3.

**Table 5.1.5.2.2-1: URI variables**

Name	Definition
notificationURI	String formatted as URI with the Notification Uri as assigned within the Individual NWDAF Event Subscription and described within the Nnwdaf_EventsSubscription type (see table 5.1.6.2.2-1).

**Table 5.1.5.2.2-2: Data structures supported by the POST Request Body on this resource**

Data type	P	Cardinality	Description
array(NnwdafEventsSubscriptionNotification)	M	1..N	Provides Information about observed events

**Table 5.1.5.2.2-3: Data structures supported by the POST Response Body on this resource**

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	The receipt of the Notification is acknowledged.
NOTE: The mandatory HTTP error status codes for the POST method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [6] also apply.				

## 5.1.6 Data Model

### 5.1.6.1 General

This subclause specifies the application data model supported by the API.

Table 5.1.6.1-1 specifies the data types defined for the Nnwdaf\_EventsSubscription service based interface protocol.

**Table 5.1.6.1-1: Nnwdaf\_EventsSubscription specific Data Types**

Data type	Section defined	Description	Applicability
AnySlice	5.1.6.3.2	Represents the any slices.	
EventNotification	5.1.6.2.5	Describes Notifications about events that occurred.	
EventSubscription	5.1.6.2.3	Represents the subscription to a single event.	
LoadLevelInformation	5.1.6.3.2	Represents load level information of the network slice.	
NwdafEvent	5.1.6.3.4	Describes the NWDAF Events.	
NnwdafEventsSubscription	5.1.6.2.2	Represents an Individual NWDAF Event Subscription resource.	
NnwdafEventsSubscriptionNotification	5.1.6.2.4	Represents an Individual NWDAF Event Subscription Notification resource.	
NotificationMethod	5.1.6.3.3	Represents the notification methods that can be subscribed.	
SliceLoadLevelInformation	5.1.6.2.6	Represents the slices and thier load level information.	

Table 5.1.6.1-2 specifies data types re-used by the Nnwdaf\_EventsSubscription service based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the Nnwdaf service based interface.

**Table 5.1.6.1-2: Nnwdaf\_EventsSubscription re-used Data Types**

Data type	Reference	Comments	Applicability
DurationSec	3GPP TS 29.571 [8]		
ProblemDetails	3GPP TS 29.571 [8]	Used in error responses to provide more detailed information about an error.	ProblemDetails
Snsai	3GPP TS 29.571 [8]	Identifies the S-NSSAI (Single Network Slice Selection Assistance Information).	
SupportedFeature	3GPP TS 29.571 [8]	Used to negotiate the applicability of the optional features defined in table 5.1.8-1.	
Uri	3GPP TS 29.571 [8]		

### 5.1.6.2 Structured data types

#### 5.1.6.2.1 Introduction

This subclause defines the structures to be used in resource representations.

## 5.1.6.2.2 Type NnwdafEventsSubscription

Table 5.1.6.2.2-1: Definition of type NnwdafEventsSubscription

Attribute name	Data type	P	Cardinality	Description	Applicability
eventSubscriptions	array(EventSubscription)	M	1..N	Subscribed events	
notificationURI	Uri	C	0..1	Identifies the recipient of Notifications sent by the NWDAF. This parameter shall be supplied by the NF service consumer in the HTTP POST requests that create the subscriptions for event notifications and in the HTTP PUT requests that update the subscriptions for event notifications.	
supportedFeatures	SupportedFeatures	C	0..1	List of Supported features used as described in subclause 5.1.8. This parameter shall be supplied by NF service consumer in the POST request that request the creation of an NWDAF Event Subscriptions resource, and shall be supplied by the NWDAF in the reply of corresponding request.	

## 5.1.6.2.3 Type EventSubscription

Table 5.1.6.2.3-1: Definition of type EventSubscription

Attribute name	Data type	P	Cardinality	Description	Applicability
anySlice	AnySlice	C	0..1	Default is "false". (NOTE 1)	
event	NwdafEvent	M	1	Event that is subscribed.	
loadLevelThreshold	integer	C	0..1	Shall be supplied for notification method "THRESHOLD". Indicates that the NWDAF shall report the corresponding network slice load level to the NF service consumer where the load level of the network slice identified by snssai is reached.	
notificationMethod	NotificationMethod	O	0..1	Indicate the notification method. (NOTE 2)	
repetitionPeriod	DurationSec	C	0..1	Shall be supplied for notification Method "PERIODIC".	
snssais	array(Snssai)	C	1..N	Identification(s) of network slice to which the subscription applies. (NOTE 1)	
NOTE 1: When subscribed event is "SLICE_LOAD_LEVEL", either information about slice(s) identified by snssais, or anySlice set to "true" shall be included.					
NOTE 2: When notificationMethod is not supplied, the default value is "THRESHOLD".					



## 5.1.6.2.4 Type NnwdafEventsSubscriptionNotification

**Table 5.1.6.2.4-1: Definition of type NnwdafEventsSubscriptionNotification**

Attribute name	Data type	P	Cardinality	Description	Applicability
eventNotifications	array(EventNotifications)	M	1..N	Notifications about Individual Events	
subscriptionId	string	M	1	String identifying a subscription to the Nnwdaf_EventsSubscription Service	

## 5.1.6.2.5 Type EventNotification

**Table 5.1.6.2.5-1: Definition of type EventNotification**

Attribute name	Data type	P	Cardinality	Description	Applicability
event	NnwdafEvent	M	1	Event that is notified.	
sliceLoadLevelInfo	SliceLoadLevelInformation	M	1	The slices and there load level information.	

## 5.1.6.2.6 Type SliceLoadLevelInformation

**Table 5.1.6.2.6-1: Definition of type SliceLoadLevelInformation**

Attribute name	Data type	P	Cardinality	Description	Applicability
loadLevelInformation	LoadLevelInformation	M	1	Load level information of the network slice identified by snssais.	
snssais	array(Snssai)	M	1..N	Identification(s) of network slice to which the subscription applies.	

## 5.1.6.3 Simple data types and enumerations

## 5.1.6.3.1 Introduction

This subclause defines simple data types and enumerations that can be referenced from data structures defined in the previous subclauses.

## 5.1.6.3.2 Simple data types

The simple data types defined in table 5.1.6.3.2-1 shall be supported.

**Table 5.1.6.3.2-1: Simple data types**

Type Name	Type Definition	Description	Applicability
AnySlice	boolean	"false" represents not applicable for all slices. "true" represents applicable for all slices.	
LoadLevelInformation	integer	Load level information of the network slice.	

## 5.1.6.3.3 Enumeration: NotificationMethod

**Table 5.1.6.3.3-1: Enumeration NotificationMethod**

Enumeration value	Description	Applicability
PERIODIC	The subscribe of NWDAF Event is periodically. The periodic of the notification is identified by repetitionPeriod defined in subclause 5.1.6.2.3.	
THRESHOLD	The subscribe of NWDAF Event is upon threshold exceeded. The threshold of the notification is identified by loadLevelThreshold defined in subclause 5.1.6.2.3.	

## 5.1.6.3.4 Enumeration: NwdafEvent

**Table 5.1.6.3.4-1: Enumeration NwdafEvent**

Enumeration value	Description	Applicability
SLICE_LOAD_LEVEL	Indicates that the event subscribed is load level information of Network Slice.	

## 5.1.7 Error handling

## 5.1.7.1 General

HTTP error handling shall be supported as specified in subclause 5.2.4 of 3GPP TS 29.500 [6].

For the Nnwdaf\_EventsSubscription API, HTTP error responses shall be supported as specified in subclause 4.8 of 3GPP TS 29.501 [7]. Protocol errors and application errors specified in table 5.2.7.2-1 of 3GPP TS 29.500 [6] shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in table 5.2.7.1-1 of 3GPP TS 29.500 [6]. In addition, the requirements in the following subclauses shall apply.

## 5.1.7.2 Protocol Errors

In this Release of the specification, there are no additional protocol errors applicable for the Nnwdaf\_EventsSubscription API.

## 5.1.7.3 Application Errors

The application errors defined for the Nnwdaf\_EventsSubscription API are listed in table 5.1.7.3-1. The NWDAF shall include in the HTTP status code a "ProblemDetails" data structure with the "cause" attribute indicating the application error as listed in table 5.1.7.3-1.

**Table 5.1.7.3-1: Application errors**

Application Error	HTTP status code	Description
SUBSCRIPTION_NOT_FOUND	404 Not Found	Indicates the Individual NWDAF Event Subscription resource does not exist. (NOTE)
NOTE: This application error is included in the responses to the PUT request (see subclause 4.2.2.2.3) and the DELETE request (see subclause 4.2.2.3.2).		

## 5.1.8 Feature negotiation

The optional features in table 5.1.8-1 are defined for the Nnwdaf\_EventsSubscription API. They shall be negotiated using the extensibility mechanism defined in subclause 6.6 of 3GPP TS 29.500 [6].

Table 5.1.8-1: Supported Features

Feature number	Feature Name	Description

## 5.1.9 Security

As indicated in 3GPP TS 33.501 [13] and 3GPP TS 29.500 [6], the access to the Nnwdaf\_EventsSubscription API may be authorized by means of the OAuth2 protocol (see IETF RFC 6749 [14]), based on local configuration, using the "Client Credentials" authorization grant, where the NRF (see 3GPP TS 29.510 [12]) plays the role of the authorization server.

If OAuth2 is used, a n NF Service Consumer, prior to consuming services offered by the Nnwdaf\_EventsSubscription API, shall obtain a "token" from the authorization server, by invoking the Access Token Request service, as described in 3GPP TS 29.510 [12], subclause 5.4.2.2.

NOTE: When multiple NRFs are deployed in a network, the NRF used as authorization server is the same NRF that the NF Service Consumer used for discovering the Nnwdaf\_EventsSubscription service.

The Nnwdaf\_EventsSubscription API defines a single scope "nnwdaf-eventssubscription" for the entire service, and it does not define any additional scopes at resource or operation level.

## 5.2 Nnwdaf\_AnalyticsInfo Service API

### 5.2.1 Introduction

The Nnwdaf\_AnalyticsInfo Service shall use the Nnwdaf\_AnalyticsInfo API.

The request URI used in each HTTP request from the NF service consumer towards the NWDAF shall have the structure defined in subclause 4.4.1 of 3GPP TS 29.501 [7], i.e.:

**{apiRoot}/{apiName}/{apiVersion}/{apiSpecificResourceUriPart}**

with the following components:

- The {apiRoot} shall be set as described in 3GPP TS 29.501 [7].
- The {apiName} shall be "nnwdaf-analyticsinfo".
- The {apiVersion} shall be "v1".
- The {apiSpecificResourceUriPart} shall be set as described in subclause 5.2.3.

### 5.2.2 Usage of HTTP

#### 5.2.2.1 General

HTTP/2, IETF RFC 7540 [9], shall be used as specified in clause 5 of 3GPP TS 29.500 [6].

HTTP/2 shall be transported as specified in subclause 5.3 of 3GPP TS 29.500 [6].

The OpenAPI [11] specification of HTTP messages and content bodies for the Nnwdaf\_AnalyticsInfo is contained in Annex A.

#### 5.2.2.2 HTTP standard headers

##### 5.2.2.2.1 General

See subclause 5.2.2 of 3GPP TS 29.500 [6] for the usage of HTTP standard headers.

### 5.2.2.2.2 Content type

JSON, IETF RFC 8259 [10], shall be used as content type of the HTTP bodies specified in the present specification as specified in subclause 5.4 of 3GPP TS 29.500 [6]. The use of the JSON format shall be signalled by the content type "application/json".

"Problem Details" JSON object shall be used to indicate additional details of the error in a HTTP response body and shall be signalled by the content type "application/problem+json", as defined in IETF RFC 7807 [15].

### 5.2.2.3 HTTP custom headers


The Nnwdaf\_AnalyticsInfo Service API shall support HTTP custom header fields specified in subclause 5.2.3.2 of 3GPP TS 29.500 [6].

In this release of the specification, no specific custom headers are defined for the Nnwdaf\_AnalyticsInfo Service API.

## 5.2.3 Resources

### 5.2.3.1 Resource Structure

{apiRoot}/nnwdaf-analyticsinfo/v1



**Figure 5.2.3.1-1: Resource URI structure of the Nnwdaf\_AnalyticsInfo API**

Table 5.2.3.1-1 provides an overview of the resources and applicable HTTP methods.

**Table 5.2.3.1-1: Resources and methods overview**

Resource name	Resource URI	HTTP method or custom operation	Description
NWDAF Analytics	{apiRoot}/nnwdaf-analyticsinfo/v1/analytics	GET	Retrieve the NWDAF analytics

### 5.2.3.2 Resource: NWDAF Analytics

#### 5.2.3.2.1 Description

The NWDAF Analytics resource represents the analytics to the Nnwdaf\_AnalyticsInfo Service at a given NWDAF.

#### 5.2.3.2.2 Resource definition

Resource URI: {apiRoot}/nnwdaf-analyticsinfo/v1/analytics

This resource shall support the resource URI variables defined in table 5.2.3.2.2-1.

**Table 5.2.3.2.2-1: Resource URI variables for this resource**

Name	Definition
apiRoot	See subclause 5.2.1

### 5.2.3.2.3 Resource Standard Methods

#### 5.2.3.2.3.1 GET

This method shall support the URI query parameters specified in table 5.2.3.2.3.1-1.

**Table 5.2.3.2.3.1-1: URI query parameters supported by the GET method on this resource**

Name	Data type	P	Cardinality	Description
event-id	EventId	M	1	Shall be included to identify the analytics.
event-filter	EventFilter	C	0..1	Shall be included to identify the analytics when the event-id is "LOAD_LEVEL_INFORMATION".
supported-features	SupportedFeatures	O	0..1	To filter irrelevant responses related to unsupported features.

This method shall support the request data structures specified in table 5.2.3.2.3.1-2 and the response data structures and response codes specified in table 5.2.3.2.3.1-3.

**Table 5.2.3.2.3.1-2: Data structures supported by the GET Request Body on this resource**

Data type	P	Cardinality	Description
n/a			

**Table 5.2.3.2.3.1-3: Data structures supported by the GET Response Body on this resource**

Data type	P	Cardinality	Response codes	Description
AnalyticsData	M	1	200 OK	Containing the analytics with parameters as relevant for the requesting NF service consumer
n/a			204 No Content	If the request NWDAF Analytics data does not exist, the NWDAF shall respond with "204 No Content".
NOTE: The mandatory HTTP error status codes for the GET method listed in table 5.2.7.1-1 of 3GPP TS 29.500 [6] also apply.				

#### 5.2.3.2.4 Resource Custom Operations

None in this release of the specification.

### 5.2.4 Custom Operations without associated resources

None in this release of the specification.

### 5.2.5 Notifications

None in this release of the specification.

### 5.2.6 Data Model

#### 5.2.6.1 General

This subclause specifies the application data model supported by the API.

Table 5.2.6.1-1 specifies the data types defined for the Nnwdaf\_AnalyticsInfo service based interface protocol.

**Table 5.2.6.1-1: Nnwdaf\_AnalyticsInfo specific Data Types**

Data type	Section defined	Description	Applicability
EventId	5.2.6.3.3	Describes the type of analytics.	
EventFilter	5.2.6.2.3	Represents the event filters used to identify the requested analytics.	
AnalyticsData	5.2.6.2.2	Describes analytics with parameters indicated in the request	

Table 5.2.6.1-2 specifies data types re-used by the Nnwdaf\_AnalyticsInfo service based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the Nnwdaf service based interface.

Re-used data types of clause 5.1.6 refer here to requests instead of subscriptions.

**Table 5.2.6.1-2: Nnwdaf\_AnalyticsInfo re-used Data Types**

Data type	Reference	Comments	Applicability
AnySlice	5.1.6.3.2		
ProblemDetails	3GPP TS 29.571 [8]	Used in error responses to provide more detailed information about an error.	
SupportedFeatures	3GPP TS 29.571 [8]	Used to negotiate the applicability of the optional features defined in table 5.2.8-1.	
Snssai	3GPP TS 29.571 [8]		
SliceLoadLevelInformation	5.1.6.2.6		

## 5.2.6.2 Structured data types

### 5.2.6.2.1 Introduction

This subclause defines the structures to be used in resource representations.

### 5.2.6.2.2 Type AnalyticsData

**Table 5.2.6.2.2-1: Definition of type AnalyticsData**

Attribute name	Data type	P	Cardinality	Description	Applicability
sliceLoadLevelInfos	array(SliceLoadLevelInformation)	C	1..N	The slices and the load level information. Shall be present when the requested event is "LOAD_LEVEL_INFORMATION".	

### 5.2.6.2.3 Type EventFilter

**Table 5.2.6.2.3-1: Definition of type EventFilter**

Attribute name	Data type	P	Cardinality	Description	Applicability
anySlice	AnySlice	C	0..1	Default is "false". (NOTE)	
snssais	array(Snssai)	C	1..N	Identification(s) of network slice to which the subscription belongs. (NOTE)	
NOTE: When event-id in the request is "LOAD_LEVEL_INFORMATION", either information about slice(s) identified by snssais, or anySlice set to "true" shall be included.					

### 5.2.6.3 Simple data types and enumerations

#### 5.2.6.3.1 Introduction

This subclause defines simple data types and enumerations that can be referenced from data structures defined in the previous subclauses.

#### 5.2.6.3.2 Simple data types

The simple data types defined in table 5.2.6.3.2-1 shall be supported.

**Table 5.2.6.3.2-1: Simple data types**

Type Name	Type Definition	Description	Applicability
n/a			

#### 5.2.6.3.3 Enumeration: EventId

**Table 5.2.6.3.3-1: Enumeration EventId**

Enumeration value	Description	Applicability
LOAD_LEVEL_INFORMATION	Represent the analytics of load level information of corresponding network slice.	

## 5.2.7 Error handling

### 5.2.7.1 General

HTTP error handling shall be supported as specified in subclause 5.2.4 of 3GPP TS 29.500 [6].

For the Nnwdaf\_AnalyticsInfo API, HTTP error responses shall be supported as specified in subclause 4.8 of 3GPP TS 29.501 [7]. Protocol errors and application errors specified in table 5.2.7.2-1 of 3GPP TS 29.500 [6] shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in table 5.2.7.1-1 of 3GPP TS 29.500 [6]. In addition, the requirements in the following subclauses shall apply.

### 5.2.7.2 Protocol Errors

In this Release of the specification, there are no additional protocol errors applicable for the Nnwdaf\_AnalyticsInfo API.

### 5.2.7.3 Application Errors

The application errors defined for the Nnwdaf\_AnalyticsInfo API are listed in table 5.2.7.3-1. The NWDAF shall include in the HTTP status code a "ProblemDetails" data structure with the "cause" attribute indicating the application error as listed in table 5.2.7.3-1.

**Table 5.2.7.3-1: Application errors**

Application Error	HTTP status code	Description
n/a		

## 5.2.8 Feature negotiation

The optional features in table 5.2.8-1 are defined for the Nnwdaf\_AnalyticsInfo API. They shall be negotiated using the extensibility mechanism defined in subclause 6.6 of 3GPP TS 29.500 [6].

**Table 5.2.8-1: Supported Features**

Feature number	Feature Name	Description

## 5.2.9 Security

As indicated in 3GPP TS 33.501 [13] and 3GPP TS 29.500 [6], the access to the Nnwdaf\_AnalyticsInfo API may be authorized by means of the OAuth2 protocol (see IETF RFC 6749 [14]), based on local configuration, using the "Client Credentials" authorization grant, where the NRF (see 3GPP TS 29.510 [12]) plays the role of the authorization server.

If OAuth2 is used, a n NF Service Consumer, prior to consuming services offered by the Nnwdaf\_AnalyticsInfo API, shall obtain a "token" from the authorization server, by invoking the Access Token Request service, as described in 3GPP TS 29.510 [12], subclause 5.4.2.2.

**NOTE:** When multiple NRFs are deployed in a network, the NRF used as authorization server is the same NRF that the NF Service Consumer used for discovering the Nnwdaf\_AnalyticsInfo service.

The Nnwdaf\_AnalyticsInfo API defines a single scope "nnwdaf-analyticsinfo" for the entire service, and it does not define any additional scopes at resource or operation level.



# Annex A (normative): OpenAPI specification

## A.1 General

The present Annex contains an OpenAPI [11] specification of HTTP messages and content bodies used by the Nnwdaf\_EventsSubscription and the Nnwdaf\_AnalyticsInfo API.

This Annex shall take precedence when being discrepant to other parts of the specification with respect to the encoding of information elements and methods within the API(s).

NOTE 1: The semantics and procedures, as well as conditions, e.g. for the applicability and allowed combinations of attributes or values, not expressed in the OpenAPI definitions but defined in other parts of the specification also apply.

Informative copies of the OpenAPI specification files contained in this 3GPP Technical Specification are available on the public 3GPP file server in the following locations (see clause 5B of the 3GPP TR 21.900 [16] for further information):

- <https://www.3gpp.org/ftp/Specs/archive/OpenAPI/<Release>/>, and
- <https://www.3gpp.org/ftp/Specs/<Plenary>/<Release>/OpenAPI/>.

NOTE 2: To fetch the OpenAPI specification file after CT#83 plenary meeting for Release 15 in the above links <Plenary> must be replaced with the date the CT Plenary occurs, in the form of year-month (yyyy-mm), e.g. for CT#83 meeting <Plenary> must be replaced with value "2019-03" and <Release> must be replaced with value "Rel-15".

## A.2 Nnwdaf\_EventsSubscription API

```

openapi: 3.0.0
info:
  version: 1.0.5
  title: Nnwdaf_EventsSubscription
  description: |
    Nnwdaf_EventsSubscription Service API.
    © 2023, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
    All rights reserved.
externalDocs:
  description: 3GPP TS 29.520 V15.11.0; 5G System; Network Data Analytics Services.
  url: 'http://www.3gpp.org/ftp/Specs/archive/29_series/29.520/'
security:
  - {}
  - oAuth2ClientCredentials:
    - nnwdaf-eventssubscription
servers:
  - url: '{apiRoot}/nnwdaf-eventssubscription/v1'
    variables:
      apiRoot:
        default: https://example.com
        description: apiRoot as defined in subclause 4.4 of 3GPP TS 29.501.
paths:
  /subscriptions:
    post:
      requestBody:
        required: true
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/NnwdafEventsSubscription'
      responses:
        '201':
          description: Create a new Individual NWDAF Event Subscription resource.
          headers:
            Location:

```

```

    description: 'Contains the URI of the newly created resource, according to the
structure: {apiRoot}/nnwdaf-eventssubscription/v1/subscriptions/{subscriptionId}'
    required: true
    schema:
      type: string
  content:
    application/json:
      schema:
        $ref: '#/components/schemas/NnwdafEventsSubscription'
  '400':
    $ref: 'TS29571_CommonData.yaml#/components/responses/400'
  '401':
    $ref: 'TS29571_CommonData.yaml#/components/responses/401'
  '403':
    $ref: 'TS29571_CommonData.yaml#/components/responses/403'
  '404':
    $ref: 'TS29571_CommonData.yaml#/components/responses/404'
  '411':
    $ref: 'TS29571_CommonData.yaml#/components/responses/411'
  '413':
    $ref: 'TS29571_CommonData.yaml#/components/responses/413'
  '415':
    $ref: 'TS29571_CommonData.yaml#/components/responses/415'
  '429':
    $ref: 'TS29571_CommonData.yaml#/components/responses/429'
  '500':
    $ref: 'TS29571_CommonData.yaml#/components/responses/500'
  '503':
    $ref: 'TS29571_CommonData.yaml#/components/responses/503'
  default:
    $ref: 'TS29571_CommonData.yaml#/components/responses/default'
  callbacks:
    myNotification:
      '{$request.body#/notificationURI}':
        post:
          requestBody:
            required: true
            content:
              application/json:
                schema:
                  type: array
                  items:
                    $ref: '#/components/schemas/NnwdafEventsSubscriptionNotification'
                  minItems: 1
  responses:
    '204':
      description: The receipt of the Notification is acknowledged.
    '400':
      $ref: 'TS29571_CommonData.yaml#/components/responses/400'
    '401':
      $ref: 'TS29571_CommonData.yaml#/components/responses/401'
    '403':
      $ref: 'TS29571_CommonData.yaml#/components/responses/403'
    '404':
      $ref: 'TS29571_CommonData.yaml#/components/responses/404'
    '411':
      $ref: 'TS29571_CommonData.yaml#/components/responses/411'
    '413':
      $ref: 'TS29571_CommonData.yaml#/components/responses/413'
    '415':
      $ref: 'TS29571_CommonData.yaml#/components/responses/415'
    '429':
      $ref: 'TS29571_CommonData.yaml#/components/responses/429'
    '500':
      $ref: 'TS29571_CommonData.yaml#/components/responses/500'
    '503':
      $ref: 'TS29571_CommonData.yaml#/components/responses/503'
    default:
      $ref: 'TS29571_CommonData.yaml#/components/responses/default'
/subscriptions/{subscriptionId}:
  delete:
    parameters:
      - name: subscriptionId
        in: path
        description: String identifying a subscription to the Nnwdaf_EventsSubscription Service
        required: true
        schema:
          type: string

```

```

responses:
  '204':
    description: No Content. The Individual NWDAF Event Subscription resource matching the
subscriptionId was deleted.
  '400':
    $ref: 'TS29571_CommonData.yaml#/components/responses/400'
  '401':
    $ref: 'TS29571_CommonData.yaml#/components/responses/401'
  '403':
    $ref: 'TS29571_CommonData.yaml#/components/responses/403'
  '404':
    description: The Individual NWDAF Event Subscription resource does not exist.
    content:
      application/problem+json:
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
  '429':
    $ref: 'TS29571_CommonData.yaml#/components/responses/429'
  '500':
    $ref: 'TS29571_CommonData.yaml#/components/responses/500'
  '501':
    $ref: 'TS29571_CommonData.yaml#/components/responses/501'
  '503':
    $ref: 'TS29571_CommonData.yaml#/components/responses/503'
default:
  $ref: 'TS29571_CommonData.yaml#/components/responses/default'
put:
  requestBody:
    required: true
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/NnwdafEventsSubscription'
  parameters:
    - name: subscriptionId
      in: path
      description: String identifying a subscription to the Nnwdaf_EventsSubscription Service
      required: true
      schema:
        type: string
  responses:
    '200':
      description: The Individual NWDAF Event Subscription resource was modified successfully
and a representation of that resource is returned.
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/NnwdafEventsSubscription'
    '204':
      description: The Individual NWDAF Event Subscription resource was modified successfully.
    '400':
      $ref: 'TS29571_CommonData.yaml#/components/responses/400'
    '401':
      $ref: 'TS29571_CommonData.yaml#/components/responses/401'
    '403':
      $ref: 'TS29571_CommonData.yaml#/components/responses/403'
    '404':
      description: The Individual NWDAF Event Subscription resource does not exist.
      content:
        application/problem+json:
          schema:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
    '411':
      $ref: 'TS29571_CommonData.yaml#/components/responses/411'
    '413':
      $ref: 'TS29571_CommonData.yaml#/components/responses/413'
    '415':
      $ref: 'TS29571_CommonData.yaml#/components/responses/415'
    '429':
      $ref: 'TS29571_CommonData.yaml#/components/responses/429'
    '500':
      $ref: 'TS29571_CommonData.yaml#/components/responses/500'
    '501':
      $ref: 'TS29571_CommonData.yaml#/components/responses/501'
    '503':
      $ref: 'TS29571_CommonData.yaml#/components/responses/503'
default:
  $ref: 'TS29571_CommonData.yaml#/components/responses/default'

```

```

components:
  securitySchemes:
    oAuth2ClientCredentials:
      type: oauth2
      flows:
        clientCredentials:
          tokenUrl: '{nrfApiRoot}/oauth2/token'
          scopes:
            nnwdaf-eventssubscription: Access to the Nnwdaf_EventsSubscription API
  schemas:
    NnwdafEventsSubscription:
      type: object
      properties:
        eventSubscriptions:
          type: array
          items:
            $ref: '#/components/schemas/EventSubscription'
          minItems: 1
          description: Subscribed events
        notificationURI:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Uri'
        supportedFeatures:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/SupportedFeatures'
      required:
        - eventSubscriptions
    EventSubscription:
      type: object
      properties:
        anySlice:
          $ref: '#/components/schemas/AnySlice'
        event:
          $ref: '#/components/schemas/NwdafEvent'
        loadLevelThreshold:
          type: integer
          description: Shall be supplied for notification method "THRESHOLD". Indicates that the
NWDAF shall report the corresponding network slice load level to the NF service consumer where the
load level of the network slice identified by snssai is reached.
        notificationMethod:
          $ref: '#/components/schemas/NotificationMethod'
        repetitionPeriod:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/DurationSec'
        snssaia:
          type: array
          items:
            $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
          minItems: 1
          description: Identification(s) of network slice to which the subscription applies. When
subscribed event is "SLICE_LOAD_LEVEL", either information about slice(s) identified by snssai, or
anySlice set to "true" shall be included. It corresponds to snssais in the data model definition of
3GPP TS 29.520.
      required:
        - event
    NnwdafEventsSubscriptionNotification:
      type: object
      properties:
        eventNotifications:
          type: array
          items:
            $ref: '#/components/schemas/EventNotification'
          minItems: 1
          description: Notifications about Individual Events
        subscriptionId:
          type: string
          description: String identifying a subscription to the Nnwdaf_EventsSubscription Service
      required:
        - eventNotifications
        - subscriptionId
    EventNotification:
      type: object
      properties:
        event:
          $ref: '#/components/schemas/NwdafEvent'
        sliceLoadLevelInfo:
          $ref: '#/components/schemas/SliceLoadLevelInformation'
      required:
        - event
        - sliceLoadLevelInfo
    SliceLoadLevelInformation:

```

```

    type: object
    properties:
      loadLevelInformation:
        $ref: '#/components/schemas/LoadLevelInformation'
      snssais:
        type: array
        items:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
        minItems: 1
        description: Identification(s) of network slice to which the subscription applies.
    required:
      - loadLevelInformation
      - snssais
  AnySlice:
    type: boolean
    description: false represents not applicable for all slices. true represents applicable for
all slices.
  LoadLevelInformation:
    type: integer
    description: Load level information of the network slice.
  NotificationMethod:
    anyOf:
      - type: string
        enum:
          - PERIODIC
          - THRESHOLD
      - type: string
        description: >
          This string provides forward-compatibility with future
          extensions to the enumeration but is not used to encode
          content defined in the present version of this API.
    description: >
      Possible values are
      - PERIODIC: The subscribe of NWDAF Event is periodically. The periodic of the notification is
identified by repetitionPeriod defined in subclause 5.1.6.2.3.
      - THRESHOLD: The subscribe of NWDAF Event is upon threshold exceeded. The threshold of the
notification is identified by loadLevelThreshold defined in subclause 5.1.6.2.3.
  NwdafEvent:
    anyOf:
      - type: string
        enum:
          - SLICE_LOAD_LEVEL
      - type: string
        description: >
          This string provides forward-compatibility with future
          extensions to the enumeration but is not used to encode
          content defined in the present version of this API.
    description: >
      Possible values are
      - SLICE_LOAD_LEVEL: Indicates that the event subscribed is load level information of Network
Slice.

```

---

## A.3 Nnwdaf\_AnalyticsInfo API

```

openapi: 3.0.0
info:
  version: 1.0.4
  title: Nnwdaf_AnalyticsInfo
  description: |
    Nnwdaf_AnalyticsInfo Service API.
    © 2022, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
    All rights reserved.
externalDocs:
  description: 3GPP TS 29.520 V15.10.0; 5G System; Network Data Analytics Services.
  url: 'http://www.3gpp.org/ftp/Specs/archive/29_series/29.520/'
security:
  - {}
  - oAuth2ClientCredentials:
      - nnwdaf-analyticsinfo
servers:
  - url: '{apiRoot}/nnwdaf-analyticsinfo/v1'
    variables:
      apiRoot:
        default: https://example.com
        description: apiRoot as defined in subclause 4.4 of 3GPP TS 29.501.
paths:

```

```

/analytics:
  get:
    parameters:
      - name: event-id
        in: query
        description: Identify the analytics.
        required: true
        schema:
          $ref: '#/components/schemas/EventId'
      - name: event-filter
        in: query
        description: Identify the analytics.
        required: false
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/EventFilter'
      - name: supported-features
        in: query
        description: To filter irrelevant responses related to unsupported features
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/SupportedFeatures'
    responses:
      '200':
        description: Containing the analytics with parameters as relevant for the requesting NF
service consumer.
        content:
          application/json:
            schema:
              $ref: '#/components/schemas/AnalyticsData'
      '204':
        description: No Content (The request NWDAF Analytics data does not exist)
      '400':
        $ref: 'TS29571_CommonData.yaml#/components/responses/400'
      '401':
        $ref: 'TS29571_CommonData.yaml#/components/responses/401'
      '403':
        $ref: 'TS29571_CommonData.yaml#/components/responses/403'
      '404':
        description: Indicates that the NWDAF Analytics resource does not exist.
        content:
          application/problem+json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/ProblemDetails'
      '406':
        $ref: 'TS29571_CommonData.yaml#/components/responses/406'
      '414':
        $ref: 'TS29571_CommonData.yaml#/components/responses/414'
      '429':
        $ref: 'TS29571_CommonData.yaml#/components/responses/429'
      '500':
        $ref: 'TS29571_CommonData.yaml#/components/responses/500'
      '503':
        $ref: 'TS29571_CommonData.yaml#/components/responses/503'
      default:
        $ref: 'TS29571_CommonData.yaml#/components/responses/default'
components:
  securitySchemes:
    oAuth2ClientCredentials:
      type: oauth2
      flows:
        clientCredentials:
          tokenUrl: '{nrfApiRoot}/oauth2/token'
          scopes:
            nnwdaf-analyticsinfo: Access to the Nnwdaf_AnalyticsInfo API
  schemas:
    AnalyticsData:
      type: object
      properties:
        sliceLoadLevelInfos:
          type: array
          items:
            $ref:
'TS29520_Nnwdaf_EventsSubscription.yaml#/components/schemas/SliceLoadLevelInformation'
          minItems: 1
      description: The slices and their load level information.
    EventFilter:
      type: object

```

```
properties:
  anySlice:
    $ref: 'TS29520_Nnwdaf_EventsSubscription.yaml#/components/schemas/AnySlice'
  snssais:
    type: array
    items:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/Snssai'
    minItems: 1
    description: Identification(s) of network slice.
  not:
    required: [anySlice, snssais]
EventId:
  anyOf:
  - type: string
  enum:
    - LOAD_LEVEL_INFORMATION
  - type: string
  description: >
    This string provides forward-compatibility with future
    extensions to the enumeration but is not used to encode
    content defined in the present version of this API.
  description: >
    Possible values are
    - LOAD_LEVEL_INFORMATION: Represent the analytics of load level information of corresponding
network slice.
```

## Annex B (informative): Change history

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2017-10						TS skeleton of Network Data Analytics Services.	0.0.0
2017-11	CT3#92					Inclusion of documents agreed in CT3#92 C3-175356.	0.1.0
2017-12	CT3#93					Inclusion of documents agreed in CT3#93 C3-176166, C3-176260, C3-176324, C3-176325, C3-176326, and C3-176327.	0.2.0
2018-01	CT3#94					Inclusion of documents agreed in CT3#94 C3-180252, C3-180253, C3-180254, C3-180255, C3-180256, C3-180257, C3-180344, C3-180345, C3-180346, C3-180323 and C3-180347.	0.3.0
2018-03	CT3#95					Inclusion of documents agreed in CT3#95 C3-181253, C3-181255, C3-181256, C3-181257, C3-181260, C3-181312, C3-181342 and C3-181343.	0.4.0
2018-03	CT3#96					Inclusion of documents agreed in CT3#96 C3-182379 and C3-182380.	0.5.0
2018-05	CT3#97					Inclusion of documents agreed in CT3#97 C3-183285, C3-183532, C3-183533, C3-183534 and C3-183535.	0.6.0
2018-06	CT#80	CP-181032				TS sent to plenary for approval	1.0.0
2018-06	CT#80	CP-181032				TS approved by plenary	15.0.0
2018-09	CT#81	CP-182015	0001	3	F	Clarification on mandatory HTTP error status codes	15.1.0
2018-09	CT#81	CP-182209	0002	4	B	OpenAPI for TS 29.520	15.1.0
2018-09	CT#81	CP-182015	0003	1	F	Description of Structured data types	15.1.0
2018-09	CT#81	CP-182015	0004	1	F	Resource structure presentation	15.1.0
2018-12	CT#82	CP-183205	0006		F	Default value for apiRoot	15.2.0
2018-12	CT#82	CP-183205	0007	2	F	Correct Nnwdaf service	15.2.0
2018-12	CT#82	CP-183205	0008	1	F	Cardinality	15.2.0
2018-12	CT#82	CP-183205	0009		F	API version	15.2.0
2018-12	CT#82	CP-183205	0010		F	ExternalDocs OpenAPI field	15.2.0
2018-12	CT#82	CP-183205	0011	1	F	Security	15.2.0
2018-12	CT#82	CP-183205	0012	1	F	Supported content types	15.2.0
2018-12	CT#82	CP-183205	0013	2	F	HTTP Error responses	15.2.0
2018-12	CT#82	CP-183205	0014	2	F	Correct NWDaf resource	15.2.0
2018-12	CT#82	CP-183205	0016	1	F	Adding HTTP status code "204 No Content"	15.2.0
2018-12	CT#82	CP-183205	0019		F	Location header field in OpenAPI	15.2.0
2019-03	CT#83	CP-190113	0020		F	Support of NSSF as the service consumer	15.3.0
2019-03	CT#83	CP-190113	0021	1	F	Formatting of structured data types in query	15.3.0
2019-03	CT#83	CP-190113	0022		F	OpenAPI info version update	15.3.0
2019-03	CT#83	CP-190213	0023	1	F	Correction of Location header in Nnwdaf_EventsSubscription OpenAPI	15.3.0
2019-06	CT#84	CP-191078	0024	1	F	Correction of Nnwdaf_EventsSubscription OpenAPI	15.4.0
2019-06	CT#84	CP-191078	0026	7	F	Additional Corrections on TS 29.520	15.4.0
2019-06	CT#84	CP-191078	0029	7	F	Corrections on TS 29.520	15.4.0
2019-06	CT#84	CP-191078	0035	1	F	Precedence of OpenAPI file	15.4.0
2019-06	CT#84	CP-191078	0037	1	F	Copyright Note in YAML files	15.4.0
2019-06	CT#84	CP-191078	0038	1	F	OpenAPI version number update	15.4.0
2019-09	CT#85	CP-192146	0040	2	F	Correct cardinality in NnwdafEventsSubscription	15.5.0
2019-09	CT#85	CP-192172	0053		F	OpenAPI version update TS 29.520 Rel-15	15.5.0
2020-06	CT#88e	CP-201221	0168	1	F	Correct supported feature in AnalyticsData	15.6.0
2020-09	CT#89e	CP-202054	0219		F	ResourceURI correction during subscription update	15.7.0
2020-12	CT#90e	CP-203117	0224	1	F	Correction to notificationURI attribute	15.8.0
2021-06	CT#92e	CP-211206	0276	1	F	Correction on 404 Not Found	15.9.0
2021-06	CT#92e	CP-211206	0283	1	F	Correction to Load Level Information	15.9.0
2021-06	CT#92e	CP-211263	0303		F	Update of OpenAPI version and TS version in externalDocs field	15.9.0
2022-06	CT#96	CP-221119	0534	1	F	Correction to the re-used data types for the re-using Nnwdaf_AnalyticsInfo API	15.10.0
2022-06	CT#96	CP-221149	0540		F	Update of the info and externalDocs field	15.10.0
2023-03	CT#99	CP-230129	0652		F	Invalid JSON value	15.11.0
2023-03	CT#99	CP-230158	0684		F	Update of OpenAPI version and TS version in externalDocs field	15.11.0



---

# History

<b>Document history</b>		
V15.0.0	July 2018	Publication
V15.1.0	October 2018	Publication
V15.2.0	April 2019	Publication
V15.3.0	April 2019	Publication
V15.4.0	October 2019	Publication
V15.5.0	October 2019	Publication
V15.6.0	August 2020	Publication
V15.7.0	November 2020	Publication
V15.8.0	January 2021	Publication
V15.9.0	August 2021	Publication
V15.10.0	June 2022	Publication
V15.11.0	April 2023	Publication