

ETSI TS 129 550 V16.2.0 (2020-11)



**5G;
5G System;
Steering of roaming application function services;
Stage 3
(3GPP TS 29.550 version 16.2.0 Release 16)**



Reference

RTS/TSGC-0429550vg20

Keywords

5G

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

The present document can be downloaded from:

<http://www.etsi.org/standards-search>

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format at www.etsi.org/deliver.

Users of the present document should be aware that the document may be subject to revision or change of status.

Information on the current status of this and other ETSI documents is available at

<https://portal.etsi.org/TB/ETSIDeliverableStatus.aspx>

If you find errors in the present document, please send your comment to one of the following services:

<https://portal.etsi.org/People/CommiteeSupportStaff.aspx>

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2020.

All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members.

3GPP™ and **LTE™** are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

oneM2M™ logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners.

GSM® and the GSM logo are trademarks registered and owned by the GSM Association.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<https://ipr.etsi.org/>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	5
1 Scope	7
2 References	7
3 Definitions, symbols and abbreviations	8
3.1 Terms.....	8
3.2 Symbols.....	8
3.3 Abbreviations	8
4 Overview	8
4.1 Introduction	8
5 Services offered by the SOR-AF.....	9
5.1 Introduction	9
5.2 Nsoraf_SteeringOfRoaming Service	9
5.2.1 Service Description.....	9
5.2.2 Service Operations.....	9
5.2.2.1 Introduction.....	9
5.2.2.2 Get.....	9
5.2.2.2.1 General	9
5.2.2.2.2 SoR Information Retrieval.....	10
5.2.2.3 Info	10
5.2.2.3.1 General	10
5.2.2.3.2 SoR Acknowledgment Reception Notification.....	11
6 API Definitions	11
6.1 Nsoraf_SteeringOfRoaming Service API.....	11
6.1.1 Introduction.....	11
6.1.2 Usage of HTTP	12
6.1.2.1 General	12
6.1.2.2 HTTP standard headers	12
6.1.2.2.1 General	12
6.1.2.2.2 Content type	12
6.1.2.2.3 Cache-Control	12
6.1.2.3 HTTP custom headers	12
6.1.3 Resources	12
6.1.3.1 Overview	12
6.1.3.2 Resource: sor-information.....	13
6.1.3.2.1 Description	13
6.1.3.2.2 Resource Definition.....	13
6.1.3.2.3 Resource Standard Methods	14
6.1.3.2.3.1 GET.....	14
6.1.3.3 Resource: sor-ack	14
6.1.3.3.1 Description	14
6.1.3.3.2 Resource Definition.....	14
6.1.3.3.3 Resource Standard Methods	15
6.1.3.3.3.1 PUT.....	15
6.1.4 Custom Operations without associated resources	15
6.1.5 Notifications	15
6.1.5.1 General	15
6.1.6 Data Model	15
6.1.6.1 General	15
6.1.6.2 Structured data types	16

6.1.6.2.1	Introduction	16
6.1.6.2.2	Type: SorInformation	17
6.1.6.2.3	Type: SorAckInfo	17
6.1.6.3	Simple data types and enumerations	17
6.1.6.3.1	Introduction	17
6.1.6.3.2	Simple data types.....	18
6.1.6.3.3	Enumeration: SorAckStatus	18
6.1.7	Error Handling	18
6.1.7.1	General	18
6.1.7.2	Protocol Errors	18
6.1.7.3	Application Errors.....	18
6.1.8	Feature negotiation.....	18
6.1.9	Security	19
Annex A (normative):	OpenAPI specification.....	20
A.1	General	20
A.2	Nsoraf_SOR API.....	20
Annex B (informative):	Change history	23
History		24

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

In the present document, modal verbs have the following meanings:

- shall** indicates a mandatory requirement to do something
- shall not** indicates an interdiction (prohibition) to do something

The constructions "shall" and "shall not" are confined to the context of normative provisions, and do not appear in Technical Reports.

The constructions "must" and "must not" are not used as substitutes for "shall" and "shall not". Their use is avoided insofar as possible, and they are not used in a normative context except in a direct citation from an external, referenced, non-3GPP document, or so as to maintain continuity of style when extending or modifying the provisions of such a referenced document.

- should** indicates a recommendation to do something
- should not** indicates a recommendation not to do something
- may** indicates permission to do something
- need not** indicates permission not to do something

The construction "may not" is ambiguous and is not used in normative elements. The unambiguous constructions "might not" or "shall not" are used instead, depending upon the meaning intended.

- can** indicates that something is possible
- cannot** indicates that something is impossible

The constructions "can" and "cannot" are not substitutes for "may" and "need not".

- will** indicates that something is certain or expected to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- will not** indicates that something is certain or expected not to happen as a result of action taken by an agency the behaviour of which is outside the scope of the present document
- might** indicates a likelihood that something will happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

might not indicates a likelihood that something will not happen as a result of action taken by some agency the behaviour of which is outside the scope of the present document

In addition:

is (or any other verb in the indicative mood) indicates a statement of fact

is not (or any other negative verb in the indicative mood) indicates a statement of fact

The constructions "is" and "is not" do not indicate requirements.

1 Scope

The present document specifies the stage 3 protocol and data model for the Nsoraf Service Based Interface. It provides stage 3 protocol definitions and message flows, and specifies the API for each service offered by the SOR-AF.

The 5G System stage 2 architecture and procedures are specified in 3GPP TS 23.501 [2] and 3GPP TS 23.502 [3]. The stage 2 architecture and procedures for 5G Steering of Roaming are specified in 3GPP TS 23.122 [14].

The Technical Realization of the Service Based Architecture and the Principles and Guidelines for Services Definition are specified in 3GPP TS 29.500 [4] and 3GPP TS 29.501 [5].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 23.501: "System Architecture for the 5G System; Stage 2".
- [3] 3GPP TS 23.502: "Procedures for the 5G System; Stage 2".
- [4] 3GPP TS 29.500: "5G System; Technical Realization of Service Based Architecture; Stage 3".
- [5] 3GPP TS 29.501: "5G System; Principles and Guidelines for Services Definition; Stage 3".
- [6] OpenAPI: "OpenAPI 3.0.0 Specification", <https://github.com/OAI/OpenAPI-Specification/blob/master/versions/3.0.0.md>.
- [7] 3GPP TR 21.900: "Technical Specification Group working methods".
- [8] 3GPP TS 33.501: "Security architecture and procedures for 5G system".
- [9] IETF RFC 6749: "The OAuth 2.0 Authorization Framework".
- [10] 3GPP TS 29.510: "5G System; Network Function Repository Services; Stage 3".
- [11] IETF RFC 7540: "Hypertext Transfer Protocol Version 2 (HTTP/2)".
- [12] IETF RFC 8259: "The JavaScript Object Notation (JSON) Data Interchange Format".
- [13] IETF RFC 7807: "Problem Details for HTTP APIs".
- [14] 3GPP TS 23.122: "Non-Access-Stratum (NAS) functions related to Mobile Station (MS) in idle mode".
- [15] 3GPP TS 29.503: "5G System; Unified Data Management Services; Stage 3".
- [16] 3GPP TS 29.571: "5G System; Common Data Types for Service Based Interfaces Stage 3".
- [17] 3GPP TS 31.115: "Secured packet structure for (Universal) Subscriber Identity Module (U)SIM Toolkit applications".

3 Definitions, symbols and abbreviations

3.1 Terms

SoR Information: In this specification, this refers to the following HPLMN information:

- a) an indication of whether the SOR-AF requires the UDM to request an acknowledgement from the UE for successful reception of the Steering of Roaming information; and
- b) one of the following:
 - a list of preferred PLMN/access technology combinations with an indication that it is included;
 - a secured packet with an indication that it is included; or
 - the HPLMN indication that 'no change of the "Operator Controlled PLMN Selector with Access Technology" list stored in the UE is needed and thus no list of preferred PLMN/access technology combinations is provided'.

NOTE: The secured packet contains the list of preferred PLMN/access technology combinations encapsulated with a security mechanism as described in 3GPP TS 31.115 [17].

3.2 Symbols

Void.

3.3 Abbreviations

For the purposes of the present document, the abbreviations given in 3GPP TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in 3GPP TR 21.905 [1].

NF	Network Function
JSON	Javascript Object Notation
SOR-AF	Steering Of Roaming Application Function
SoR	Steering of Roaming
SUPI	Subscription Permanent Identifier
UE	User Equipment
UDM	Unified Data Management

4 Overview

4.1 Introduction

Within the 5GC, the Steering Of Roaming Application Function (SOR-AF) provides services (see 3GPP TS 23.122 [14]) to NF service consumers (e.g. UDM) via the Nsoraf service based interface.

NOTE: The generation and calculation of the SoR information and associated roaming business logic are out of scope of this document.

Figure^o4.1-1 depicts the reference architecture of the SOR-AF.




Figure 4.1-1: Reference model – SOR-AF

5 Services offered by the SOR-AF

5.1 Introduction

The SOR-AF offers the following services to NF consumers (e.g. UDM) via the Nsoraf service based interface:

- Nsoraf_SteeringOfRoaming

Table 5.1-1 summarizes the corresponding APIs defined for this specification.

Table 5.1-1: APIs Description

Service Name	Clause	Description	OpenAPI Specification File	apiName	Annex
Nsoraf_SteeringOfRoaming	6.1	Nsoraf Steering Of Roaming Service	TS29550_Nsoraf_SOR.yaml	nsoraf-sor	A.2

5.2 Nsoraf_SteeringOfRoaming Service

5.2.1 Service Description

The Nsoraf_SteeringOfRoaming (Nsoraf_SOR) service provides Steering of Roaming services to NF consumers (e.g. UDM) to enable the retrieval of SoR information (i.e. the list of preferred PLMN/access technology combinations or an indication that no update to the list of preferred PLMN/access technology combinations is needed) to be conveyed to the UE, as specified in Annex C of 3GPP°TS°23.122 [14]. The latter specifies the 5GS control plane mechanism for Steering of Roaming that aims at allowing the HPLMN to update the "Operator Controlled PLMN Selector with Access Technology" list in the UE by providing and updating this list of preferred PLMN/access technology combinations.

5.2.2 Service Operations

5.2.2.1 Introduction

For the Nsoraf_SteeringOfRoaming service, the following service operations are defined:

- Get
- Info

5.2.2.2 Get

5.2.2.2.1 General

This service operation is used by a NF consumer (e.g. UDM) to retrieve SoR information.

The returned information can consist of either:

- a list of preferred PLMN/access technology combinations;

- a secured packet;
- neither of them.

NOTE: The secured packet contains the list of preferred PLMN/access technology combinations encapsulated with a security mechanism as described in 3GPP TS 31.115 [17].

The following procedures are supported using the "Get" service operation:

- SoR Information Retrieval

5.2.2.2.2 SoR Information Retrieval

Figure 5.2.2.2.2-1 depicts a scenario where a NF consumer (e.g. UDM) sends a request to the SOR-AF to retrieve the SoR information for a UE (see also clause C.2 in Annex C of 3GPP TS 23.122 [14]).

The request contains the UE's identity ($\{supi\}$) and a set of query parameters (e.g. PLMN ID of the visited PLMN the UE is roaming in).




Figure 5.2.2.2.2-1: SoR Information Retrieval Procedure

1. The NF service consumer (e.g. UDM) sends a GET request to the resource representing the SoR information (sor-information), with query parameters indicating the PLMN ID and other relevant information (e.g. Access type).
- 2a. On success, the SOR-AF responds with the HTTP status code "200 OK" with the message body containing the SoR information for the concerned UE. The response also contains a Cache-Control HTTP header set to the value "no-cache" instructing the NF consumer (e.g. UDM) to not cache the received SoR information.
- 2b. If there is no valid SoR information for the UE (e.g. the resource does not exist, the SUPI is unknown to the SOR-AF), the SOR-AF responds with the HTTP status code "404 Not Found" including additional error information in the response body (within the "ProblemDetails" IE).

NOTE: An operator configurable timer shall be used by the NF Service Consumer (e.g. UDM) to control the acceptable time during which it shall wait for the GET response from the SOR-AF, as specified in clause C.2 of 3GPP TS 23.122 [14] (step 3d of the procedure description). The default value and range of this timer is operator specific and shall take into account the importance of the related procedure (e.g. registration procedure).

On failure, the appropriate HTTP status code indicating the error shall be returned and appropriate additional error information should be returned in the GET response body.

5.2.2.3 Info

5.2.2.3.1 General

This service operation is used by a NF consumer (e.g. UDM) to provide the SOR-AF with the reception status of the acknowledgment on successful reception of SoR information by the UE, in case an acknowledgment was requested to the UE.

The following procedures are supported using the "Info" service operation:

- SoR Acknowledgment Reception Notification

5.2.2.3.2 SoR Acknowledgment Reception Notification

Figure 5.2.2.3.2-1 depicts a scenario where a NF consumer (e.g. UDM) sends an indication to the SOR-AF on the reception status of SoR information by the UE (see also clauses C.2 and C.3 in Annex C of 3GPP°TS°23.122°[14]).

The request contains the UE's identity ($\{/supi\}$), the type of acknowledgment ($\{/sor-information/sor-ack\}$) and the indication (SorAckInfo).




Figure 5.2.2.3.2-1: SoR Acknowledgment Reception Notification procedure

1. The NF service consumer (e.g. UDM) sends a PUT request to the resource representing the SoR information acknowledgment ($\{/supi\}/sor-information/sor-ack$) with the SorAckInfo containing an indication on the reception status of SoR information by the UE.
- 2a. The SOR-AF responds with the HTTP status code "204 No Content".
- 2b. If there is an error (e.g. the SUPI is unknown to the SOR-AF), the SOR-AF shall respond with the HTTP status code "404 Not Found" including additional error information in the response body (within the "ProblemDetails" IE).

On failure, the appropriate HTTP status code indicating the error shall be returned and appropriate additional error information should be returned in the PUT response body.

6 API Definitions

6.1 Nsoraf_SteeringOfRoaming Service API

6.1.1 Introduction

The Nsoraf_SOR service shall use the Nsoraf_SOR service API.

The request URI used in HTTP request from the NF service consumer towards the NF service producer shall have the structure defined in clause 4.4.1 of 3GPP TS 29.501 [5], i.e.:

{apiRoot}/<apiName>/<apiVersion>/<apiSpecificResourceUriPart>

with the following components:

- The {apiRoot} shall be set as described in 3GPP TS 29.501 [5].
- The <apiName> shall be "nsoraf-sor".
- The <apiVersion> shall be "v1".
- The <apiSpecificResourceUriPart> shall be set as described in clause 6.1.3.

6.1.2 Usage of HTTP

6.1.2.1 General

HTTP/2, IETF RFC 7540 [11], shall be used as specified in clause 5 of 3GPP TS 29.500 [4].

HTTP/2 shall be transported as specified in clause 5.3 of 3GPP TS 29.500 [4].

The OpenAPI [6] specification of HTTP messages and content bodies for the Nsoraf_SOR API is contained in Annex A.

6.1.2.2 HTTP standard headers

6.1.2.2.1 General

See clause 5.2.2 of 3GPP TS 29.500 [4] for the usage of HTTP standard headers.

6.1.2.2.2 Content type

JSON, IETF RFC 8259 [12], shall be used as content type of the HTTP bodies specified in the present specification as specified in clause 5.4 of 3GPP TS 29.500 [4]. The use of the JSON format shall be signalled by the content type "application/json".

"Problem Details" JSON object shall be used to indicate additional details of the error in a HTTP response body and shall be signalled by the content type "application/problem+json", as defined in IETF RFC 7807 [13].

6.1.2.2.3 Cache-Control

The "Cache-Control" header set to the value "no-cache" shall be included in HTTP responses for resources that shall not be cached (e.g. SorInformation).

6.1.2.3 HTTP custom headers

The mandatory HTTP custom header fields specified in clause 5.2.3.2 of 3GPP TS 29.500 [4] shall be applicable.

6.1.3 Resources

6.1.3.1 Overview

The structure of the Resource URIs of the "Nsoraf_SOR" service is depicted in Figure 6.1.3.1-1.




Figure 6.1.3.1-1: Resource URI structure of the Nsoraf_SOR API

Table 6.1.3.1-1 provides an overview of the resources and applicable HTTP methods.

Table 6.1.3.1-1: Resources and methods overview

Resource name	Resource URI	HTTP method or custom operation	Description
sor-information (Document)	/{supi}/sor-information	GET	Retrieve the SoR information.
sor-ack (Document)	/{supi}/sor-information/sor-ack	PUT	Inform the SOR-AF of the reception status of the Acknowledgment of successful reception of SoR information by the UE.

6.1.3.2 Resource: sor-information

6.1.3.2.1 Description

This resource represents the SoR information for a SUPI. It is used by NF consumers (e.g. UDM) to:

- request the retrieval of the SoR information during registration in a VPLMN as specified in clause C.2 in Annex C of 3GPP TS 23.122 [14].

6.1.3.2.2 Resource Definition

Resource URI: **{apiRoot}/nsoraf-sor/v1/{supi}/sor-information**

This resource shall support the resource URI variables defined in table 6.1.3.2.2-1.

Table 6.1.3.2.2-1: Resource URI variables for this resource

Name	Data type	Definition
apiRoot	string	See clause 6.1.1
supi	Supi	Represents the Subscription Permanent Identifier (see 3GPP TS 23.501 [2] clause 5.9.2) pattern: "^imsi-[0-9]{5,15}nai-.[.+]\$"

6.1.3.2.3 Resource Standard Methods

6.1.3.2.3.1 GET

This method shall support the URI query parameters specified in table 6.1.3.2.3.1-1.

Table 6.1.3.2.3.1-1: URI query parameters supported by the GET method on this resource

Name	Data type	P	Cardinality	Description	Applicability
supported-features	SupportedFeatures	O	0..1	See 3GPP TS 29.500 [4] clause 6.6.	
plmn-id	PlmnId	M	1	PLMN identity of the PLMN serving the UE.	
access-type	AccessType	O	0..1	Access type used by the UE.	

This method shall support the request data structures specified in table 6.1.3.2.3.1-2 and the response data structures and response codes specified in table 6.1.3.2.3.1-3.

Table 6.1.3.2.3.1-2: Data structures supported by the GET Request Body on this resource

Data type	P	Cardinality	Description
n/a			

Table 6.1.3.2.3.1-3: Data structures supported by the GET Response Body on this resource

Data type	P	Cardinality	Response codes	Description
SorInformation	M	1	200 OK	Upon success, a response with "200 OK" status code and a response body containing the SoR information as requested by the NF consumer (e.g. UDM) shall be returned by the SOR-AF.
ProblemDetails	O	0..1	404 Not Found	The "cause" attribute may be set to one of the following application errors: - USER_NOT_FOUND
NOTE: The mandatory HTTP error status code for the GET method listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [4] also apply.				

Table 6.1.3.2.3.1-4: Headers supported by the 200 Response Code on this resource

Name	Data type	P	Cardinality	Description
Cache-Control	string	M	1	The Cache-Control HTTP header is set to the value "no-cache" instructing the NF consumer (e.g. UDM) to not cache the received SoR information.

6.1.3.3 Resource: sor-ack

6.1.3.3.1 Description

This resource represents the notification from the NF consumer (e.g. UDM) of the reception status of the acknowledgment of successful reception of SoR information by the UE as specified in in Annex C of 3GPP TS 23.122 [14].

6.1.3.3.2 Resource Definition

Resource URI: **{apiRoot}/nsoraf-sor/v1/{supi}/sor-information/sor-ack**

This resource shall support the resource URI variables defined in table 6.1.3.3.2-1.

Table 6.1.3.3.2-1: Resource URI variables for this resource

Name	Data type	Definition
apiRoot	string	See clause 6.1.1
supi	Supi	Represents the Subscription Permanent Identifier (see 3GPP TS 23.501 [2] clause 5.9.2) pattern: "^{(imsi-[0-9]{5,15}) nai-.[.+]})\$"

6.1.3.3.3 Resource Standard Methods

6.1.3.3.3.1 PUT

This method shall support the URI query parameters specified in table 6.1.3.3.3.1-1.

Table 6.1.3.3.3.1-1: URI query parameters supported by the PUT method on this resource

Name	Data type	P	Cardinality	Description	Applicability
n/a					

This method shall support the request data structures specified in table 6.1.3.3.3.1-2 and the response data structures and response codes specified in table 6.1.3.3.3.1-3.

Table 6.1.3.3.3.1-2: Data structures supported by the PUT Request Body on this resource

Data type	P	Cardinality	Description
SorAckInfo	M	1	Contains an indication on the reception status of the acknowledgment of successful reception of SoR information by the UE.

Table 6.1.3.3.3.1-3: Data structures supported by the PUT Response Body on this resource

Data type	P	Cardinality	Response codes	Description
n/a			204 No Content	Upon success, a response with "204 No Content" status code shall be returned.
ProblemDetails	O	0..1	404 Not Found	The "cause" attribute may be set to the following application error: - USER_NOT_FOUND
NOTE: The mandatory HTTP error status code for the PUT method listed in Table 5.2.7.1-1 of 3GPP TS 29.500 [4] also apply.				

6.1.4 Custom Operations without associated resources

No custom operations without associated resources are defined for the Nsoraf_SOR Service.

6.1.5 Notifications

6.1.5.1 General

In this release of this specification, no notifications are defined for the Nsoraf_SOR Service.

6.1.6 Data Model

6.1.6.1 General

This clause specifies the application data model supported by the API.

Table 6.1.6.1-1 specifies the data types defined for the Nsoraf_SOR service based interface protocol.

Table 6.1.6.1-1: N_{soraf} specific Data Types

Data type	Clause defined	Description	Applicability
SorInformation	6.1.6.2.2	Contains the SoR information to be conveyed to the UE.	
SorAckInfo	6.1.6.2.3	Contains an indication to the SOR-AF on the reception status of the acknowledgment of successful reception of SoR Information by the UE.	
SorAckStatus	6.1.6.3.3	Contains the reception status of the acknowledgment of successful reception of SoR Information by the UE.	

Table 6.1.6.1-2 specifies data types re-used by the N_{soraf}_SOR service based interface protocol from other specifications, including a reference to their respective specifications and when needed, a short description of their use within the N_{soraf} service based interface.

Table 6.1.6.1-2: N_{soraf} re-used Data Types

Data type	Reference	Comments	Applicability
PlmnId	3GPP TS 29.571 [16]	PLMN Identity	
ProblemDetails	3GPP TS 29.571 [16]	Common data type used in response bodies	
SupportedFeatures	3GPP TS 29.571 [16]	see 3GPP TS 29.500 [4] clause 6.6	
SteeringContainer	3GPP TS 29.503 [15]	Contains the SoR Information	
Supi	3GPP TS 29.571 [16]	Contains the SUPI information.	
DateTime	3GPP TS 29.571 [16]	Date Time	
AccessType	3GPP TS 29.571 [16]	Access type (e.g. 3GPP)	

6.1.6.2 Structured data types

6.1.6.2.1 Introduction

This clause defines the structures to be used in resource representations.

6.1.6.2.2 Type: SorInformation

Table 6.1.6.2.2-1: Definition of type SorInformation

Attribute name	Data type	P	Cardinality	Description	Applicability
steeringContainer	SteeringContainer	C	0..1	When present, this attribute contains the information needed to update the "Operator Controlled PLMN Selector with Access Technology" list stored in the UE, either as an array of preferred PLMN/Access Technologies combinations in priority order (with the first entry in the array indicating the highest priority and the last entry indicating the lowest) or a secured packet. If no change of the "Operator Controlled PLMN Selector with Access Technology" list stored in the UE is needed, then this attribute shall be absent.	
sorAckIndication	Boolean	M	1	This attribute indicates to the NF consumer (e.g. UDM) whether an Acknowledgment of successful reception of SoR information shall be requested to the UE (when set to "True") or not (when set to "False").	
sorSendingTime	DateTime	M	1	Contains the date and time at which SOR-AF returns SorInformation. It is used to correlate the SoR acknowledgement with the associated SoR information.	

6.1.6.2.3 Type: SorAckInfo

Table 6.1.6.2.3-1: Definition of type SorAckInfo

Attribute name	Data type	P	Cardinality	Description	Applicability
sorAckStatus	SorAckStatus	M	1	Contains the reception status of the acknowledgment of successful reception of SoR Information by the UE.	
sorSendingTime	DateTime	M	1	Contains the date and time at which SOR-AF sent the SorInformation to which the acknowledgment status relates.	

6.1.6.3 Simple data types and enumerations

6.1.6.3.1 Introduction

This clause defines simple data types and enumerations that can be referenced from data structures defined in the previous clauses.

6.1.6.3.2 Simple data types

The simple data types defined in table 6.1.6.3.2-1 shall be supported.

Table 6.1.6.3.2-1: Simple data types

Type Name	Type Definition	Description	Applicability
n/a			

6.1.6.3.3 Enumeration: SorAckStatus

The enumeration SorAckStatus represents an indication to the SOR-AF on whether the acknowledgment of successful reception of SoR information was received from the UE. It shall comply with the provisions defined in table 6.1.6.3.3-1.

Table 6.1.6.3.3-1: Enumeration SorAckStatus

Enumeration value	Description	Applicability
"ACK_SUCCESSFUL"	Indicates to the SOR-AF that the acknowledgment of successful reception of SoR information was received from the UE and the integrity check was successful.	
"ACK_NOT_RECEIVED"	Indicates to the SOR-AF that the acknowledgment of successful reception of SoR information was NOT received from the UE.	
"ACK_NOT_SUCCESSFUL"	Indicates to the SOR-AF that the acknowledgment of successful reception of SoR information was received from the UE and the integrity check was NOT successful.	

6.1.7 Error Handling

6.1.7.1 General

For the Nsoraf_SOR API, HTTP error responses shall be supported as specified in clause 4.8 of 3GPP TS 29.501 [5]. Protocol errors and application errors specified in table 5.2.7.2-1 of 3GPP TS 29.500 [4] shall be supported for an HTTP method if the corresponding HTTP status codes are specified as mandatory for that HTTP method in table 5.2.7.1-1 of 3GPP TS 29.500 [4].

In addition, the requirements in the following clauses are applicable for the Nsoraf_SOR API.

6.1.7.2 Protocol Errors

No specific procedures for the Nsoraf_SOR service are specified.

6.1.7.3 Application Errors

The application errors defined for the Nsoraf_SOR service are listed in Table 6.1.7.3-1.

Table 6.1.7.3-1: Application errors

Application Error	HTTP status code	Description
USER_NOT_FOUND	404 Not Found	The user does not exist This error is applicable to all Nsoraf_SOR operations.

6.1.8 Feature negotiation

The optional features in table 6.1.8-1 are defined for the Nsoraf_SOR API. They shall be negotiated using the extensibility mechanism defined in clause 6.6 of 3GPP TS 29.500 [4].

Table 6.1.8-1: Supported Features

Feature number	Feature Name	Description
n/a		

6.1.9 Security

As indicated in 3GPP TS 33.501 [8] and 3GPP TS 29.500 [4], the access to the Nsoraf_SOR API may be authorized by means of the OAuth2 protocol (see IETF RFC 6749 [9]), based on local configuration, using the "Client Credentials" authorization grant, where the NRF (see 3GPP TS 29.510 [10]) plays the role of the authorization server.

If OAuth2 is used, an NF Service Consumer, prior to consuming services offered by the Nsoraf_SOR API, shall obtain a "token" from the authorization server, by invoking the Access Token Request service, as described in 3GPP TS 29.510 [10], clause 5.4.2.2.

NOTE: When multiple NRFs are deployed in a network, the NRF used as authorization server is the same NRF that the NF Service Consumer used for discovering the Nsoraf_SOR service.

The Nsoraf_SOR API defines a single scope "nsoraf-sor" for the entire service, and it does not define any additional scopes at resource or operation level.

Annex A (normative): OpenAPI specification

A.1 General

This Annex specifies the formal definition of the API(s) defined in the present specification. It consists of OpenAPI 3.0.0 specifications in YAML format.

This Annex takes precedence when being discrepant to other parts of the specification with respect to the encoding of information elements and methods within the API(s).

NOTE: The semantics and procedures, as well as conditions, e.g. for the applicability and allowed combinations of attributes or values, not expressed in the OpenAPI definitions but defined in other parts of the specification also apply.

Informative copies of the OpenAPI specification files contained in this 3GPP Technical Specification are available on a Git-based repository hosted in ETSI Forge, that uses the GitLab software version control system (see 3GPP TS 29.501 [5] clause 5.3.1 and 3GPP TR 21.900 [7] clause 5B).

A.2 Nsoraf_SOR API

```

openapi: 3.0.0
info:
  title: 'Nsoraf_SOR'
  version: 1.0.0
  description: |
    Nsoraf Steering Of Roaming Service.
    © 2020, 3GPP Organizational Partners (ARIB, ATIS, CCSA, ETSI, TSDSI, TTA, TTC).
    All rights reserved.
externalDocs:
  description: 3GPP TS 29.550 V16.1.0; Steering Of Roaming Application Function Services.
  url: http://www.3gpp.org/ftp/Specs/archive/29_series/29.550/
servers:
- url: '{apiRoot}/nsoraf-sor/v1'
  variables:
    apiRoot:
      default: https://example.com
      description: apiRoot as defined in clause 4.4 of 3GPP TS 29.501
security:
- {}
- oAuth2ClientCredentials:
  - nsoraf-sor
paths:
  /{supi}/sor-information:
    get:
      summary: retrieve the steering of roaming information for a UE
      operationId: GetSorInformation
      tags:
      - SoR Information Retrieval
      parameters:
      - name: supi
        in: path
        description: Identifier of the UE
        required: true
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Supi'
      - name: supported-features
        in: query
        description: Supported Features
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/SupportedFeatures'
      - name: plmn-id
        in: query
        description: serving PLMN ID
        required: true
        content:
          application/json:
            schema:
              $ref: 'TS29571_CommonData.yaml#/components/schemas/PlmnId'

```

```

- name: access-type
  in: query
  description: Access type used by the UE
  content:
    application/json:
      schema:
        $ref: 'TS29571_CommonData.yaml#/components/schemas/AccessType'
responses:
  '200':
    description: Expected response to a valid request
    content:
      application/json:
        schema:
          $ref: '#/components/schemas/SorInformation'
    headers:
      Cache-Control:
        description: Cache-Control (as described in RFC 7234) with value "no-cache" to
        indicate that the returned SoR information should not be cached
        schema:
          type: string
  '400':
    $ref: 'TS29571_CommonData.yaml#/components/responses/400'
  '404':
    $ref: 'TS29571_CommonData.yaml#/components/responses/404'
  '500':
    $ref: 'TS29571_CommonData.yaml#/components/responses/500'
  '503':
    $ref: 'TS29571_CommonData.yaml#/components/responses/503'
  default:
    description: Unexpected error
/{supi}/sor-information/sor-ack:
  put:
    summary: SoR Acknowledgment Reception Notification
    operationId: SorAckInfo
    tags:
      - Providing the reception status of the acknowledgement of Steering of Roaming information
      reception by the UE
    parameters:
      - name: supi
        in: path
        description: Identifier of the UE
        required: true
        schema:
          $ref: 'TS29571_CommonData.yaml#/components/schemas/Supi'
    requestBody:
      required: true
      content:
        application/json:
          schema:
            $ref: '#/components/schemas/SorAckInfo'
    responses:
      '204':
        description: Successful reception of the indication
      '400':
        $ref: 'TS29571_CommonData.yaml#/components/responses/400'
      '404':
        $ref: 'TS29571_CommonData.yaml#/components/responses/404'
      '500':
        $ref: 'TS29571_CommonData.yaml#/components/responses/500'
      '503':
        $ref: 'TS29571_CommonData.yaml#/components/responses/503'
      default:
        description: Unexpected error
components:
  securitySchemes:
    oAuth2ClientCredentials:
      type: oauth2
      flows:
        clientCredentials:
          tokenUrl: '{nrfApiRoot}/oauth2/token'
          scopes:
            nsoraf-sor: Access to the Nsoraf_SOR API
schemas:
  # API specific definitions
  SorInformation:
    type: object
    required:
      - sorAckIndication

```

```
- sorSendingTime
properties:
  steeringContainer:
    $ref: 'TS29503_Nudm_SDM.yaml#/components/schemas/SteeringContainer'
  sorAckIndication:
    type: boolean
  sorSendingTime:
    $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
SorAckInfo:
  type: object
  required:
    - sorAckStatus
    - sorSendingTime
  properties:
    sorAckStatus:
      $ref: '#/components/schemas/SorAckStatus'
    sorSendingTime:
      $ref: 'TS29571_CommonData.yaml#/components/schemas/DateTime'
SorAckStatus:
  anyOf:
    - type: string
      enum:
        - ACK_SUCCESSFUL
        - ACK_NOT_RECEIVED
        - ACK_NOT_SUCCESSFUL
    - type: string
```

Annex B (informative): Change history

Change history							
Date	Meeting	TDoc	CR	Rev	Cat	Subject/Comment	New version
2019-11	CT4#95	C4-195242				Initial Draft.	0.1.0
2020-03	CT4#96e	C4-200833				Pseudo-CR on the scope part of SOR-AF API	0.2.0
2020-03	CT4#96e	C4-201197				Pseudo-CR on the overview part of SOR-AF API	0.2.0
2020-03	CT4#96e	C4-201198				Pseudo-CR on the definition of Nsoraf service	0.2.0
2020-03	CT4#96e	C4-201206				Pseudo-CR on the resources part of SOR-AF API	0.2.0
2020-03	CT4#96e	C4-201208				Pseudo-CR on the data model aspects of SOR-AF API	0.2.0
2020-03	CT4#96e	C4-201209				Pseudo-CR on the OpenAPI part of SOR-AF API	0.2.0
2020-03	CT-87e	CP-200063				TS presented for information and approval	1.0.0
2020-03	CT-87e					Approved at CT#87e	16.0.0
2020-07	CT#88e	CP-201042	0001		F	SoR Information wording clarification	16.1.0
2020-07	CT#88e	CP-201042	0002	1	F	Storage of YAML files in ETSI Forge	16.1.0
2020-07	CT#88e	CP-201042	0003		F	Miscellaneous Corrections	16.1.0
2020-07	CT#88e	CP-201042	0006	1	F	Add Data type column in the URI variables tables	16.1.0
2020-07	CT#88e	CP-201042	0007	1	F	Add supported headers tables	16.1.0
2020-07	CT#88e	CP-201042	0008		F	Add API descriptions table	16.1.0
2020-07	CT#88e	CP-201042	0009	2	B	Remaining input parameters to Nsoraf_SOR_Get service operation	16.1.0
2020-07	CT#88e	CP-201042	0010	1	B	SoR retrieval response timing control	16.1.0
2020-07	CT#88e	CP-201073	0011		F	29.550 Rel-16 API version and External doc update	16.1.0
2020-09	CT#89e	CP-202115	0012		F	Miscellaneous Corrections	16.2.0

History

Document history		
V16.1.0	July 2020	Publication
V16.2.0	November 2020	Publication