

ETSI TS 132 584 V8.1.0 (2009-10)

Technical Specification

**Universal Mobile Telecommunications System (UMTS);
Telecommunications management;
Home Node B (HNB) Operations, Administration, Maintenance
and Provisioning (OAM&P);
XML definitions for Type 1 interface
HNB to HNB Management System (HMS)
(3GPP TS 32.584 version 8.1.0 Release 8)**



ReferenceRTS/TSGS-0532584v810

KeywordsUMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:

<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status. Information on the current status of this and other ETSI documents is available at

<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:

http://portal.etsi.org/chaicor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2009.
All rights reserved.

DECT™, **PLUGTESTS™**, **UMTS™**, **TIPHON™**, the TIPHON logo and the ETSI logo are Trade Marks of ETSI registered for the benefit of its Members.

3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

LTE™ is a Trade Mark of ETSI currently being registered

for the benefit of its Members and of the 3GPP Organizational Partners.

GSM® and the GSM logo are Trade Marks registered and owned by the GSM Association.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under <http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	6
3.1 Definitions	6
3.2 Abbreviations	6
4 CM data format definition.....	6
4.1 File content description	6
4.2 XML schema based CM data file format definition.....	8
4.2.1 CM data file XML diagram	8
4.2.2 CM data file XML schema	10
4.2.3 CM data file XML header.....	21
5 PM data format definition	21
5.1 Mapping table.....	21
5.2 XML schema based PM data file format definition	23
5.2.1 PM data file XML diagram.....	23
5.2.2 PM data file XML schema.....	23
5.2.2 PM data file XML header	23
Annex A (informative): Examples.....	24
A.1 XML schema based CM data file.....	24
A.2 XML schema based PM data file	24
Annex B (informative): XML schema electronic files.....	25
Annex C (informative): Change history	26
History	27

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project Technical Specification Group Services and System Aspects, Telecommunication Management; as identified below:

- 32.581: "Telecommunications management; Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P); Concepts and requirements for Type 1 interface HNB to HNB Management System (HMS)"
- 32.582: "Telecommunications management; Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P); Information model for Type 1 interface HNB to HNB Management System (HMS)"
- 32.583: "Telecommunications management; Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P); Procedure flows for Type 1 interface HNB to HNB Management System (HMS)"
- 32.584: "Telecommunications management; Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P); XML definitions for Type 1 interface HNB to HNB Management System (HMS)"

1 Scope

The present document describes the data format for Configuration Management and Performance Management for Home Node B (HNB). The XML definitions captured in this document shall be met via Type 1 interface between HNB and HNB Management System (HMS).

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TR 21.905: "Vocabulary for 3GPP Specifications".
- [2] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [3] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [4] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [6] 3GPP TR R3.020, Home (e)NodeB
- [7] TR-069 Amendment 2, CPE WAN Management Protocol v1.1, Broadband Forum
- [8] 3GPP TS 32.435: "Telecommunication management; Performance measurement: eXtensible Markup Language (XML) file format definition"
- [9] 3GPP TS 32.582: "Telecommunications management; Home Node B (HNB) Operations, Administration, Maintenance and Provisioning (OAM&P); Information model for Type 1 interface HNB to HNB Management System (HMS)"
- [10] W3C REC-xml-20001006: "Extensible Markup Language (XML) 1.0 (Second Edition)".
- [11] W3C REC-xmlschema-0-20010502: "XML Schema Part 0: Primer".
- [12] W3C REC-xmlschema-1-20010502: "XML Schema Part 1: Structures".
- [13] W3C REC-xmlschema-2-20010502: "XML Schema Part 2: Datatypes".
- [14] W3C REC-xml-names-19990114: "Namespaces in XML".
- [15] WT-157, Component Objects for CWMP, Broadband Forum
- [16] TR-098 Amendment 2, "Internet Gateway Device Data Model for TR-069", Broadband Forum
- [17] 3GPP TS 32.622: "Telecommunication management; Configuration Management (CM); Generic network resources Integration Reference Point (IRP); Network Resource Model (NRM)"

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in TR 21.905 [1] and the following apply. A term defined in the present document takes precedence over the definition of the same term, if any, in TR 21.905 [1].

Home NodeB, 3G Home NodeB: These terms, their derivations and abbreviations are used synonymously throughout this document.

3.2 Abbreviations

For the purposes of the present document, the abbreviations given in TR 21.905 [1] and the following apply. An abbreviation defined in the present document takes precedence over the definition of the same abbreviation, if any, in TR 21.905 [1].

DM	Domain Manager
EM	Element Manager
FFS	For Further Study
HNB	Home Node B
HMS	HNB Management System
IP	Internet Protocol
LTE	Long Term Evolution
MME	Mobile Management Entity
NGMN	Next Generation Mobile Networks
PnP	Plug and Play
SAE	System Architecture Evolution
SON	Self-Organising Networks
TBD	To Be Discussed
UMTS	Universal Mobile Telecommunications System
UTRAN	UMTS Radio Access Network

4 CM data format definition

This clause describes the format of Configuration Management data.

4.1 File content description

Table 4.1 lists all the file content items, provides an explanation of the individual items, and maps the file content items to those used in the XML schema based file format definitions. XML tag attributes are useful where data values bind tightly to its parent element. They have been used where appropriate.

Table 4.1 File Content Description and Mapping of File Content Items to XML tags

File Content Item	XML schema based XML tag	Description
configDataCollection	configDataFile	This is the top-level tag, which identifies the file as a collection of config data. The file content is made up of a header ("configFileHeader"), the collection of configuration items ("configData"), and a configfile footer ("configFileFooter").
configFileHeader	fileHeader	This is the configuration data file header to be inserted in each file. It includes a version indicator, the sender name, and vendor name of the sending network node.

File Content Item	XML schema based XML tag	Description
configData	configData	The "configData" construct represents the sequence of zero or more configuration parameter items contained in the file. Each "configData" element contains the name of the NE ("nEId") and the list of parameters to be created, modified or deleted which pertaining to that NE The "configData" consists of DeviceData, DiagnosticsData, and FAPServiceData
configFileFooter	fileFooter	The configuration data file footer to be inserted in each file. It includes a time stamp, which refers to the time when the file is closed for sending to the NE.
fileFormatVersion	fileHeader fileFormatVersion	This parameter identifies the file format version applied by the sender. The format version defined in the present document shall be the abridged number and version of this 3GPP document (see below). The abridged number and version of a 3GPP document is constructed from its version specific full reference "3GPP [...]" (yyyy-mm) by: - removing the leading "3GPP TS" - removing everything including and after the version third digit, representing editorial only changes, together with its preceding dot character - from the resulting string, removing leading and trailing white space, replacing every multi character white space by a single space character and changing the case of all characters to uppercase. e.g. "32.584 V8.0"
senderName	fileHeader senderName	The senderName uniquely identifies the NE or EM that assembled this alarm reporting file by its Distinguished Name (DN), according to the definitions in 3GPP TS 32.300 [4]. In the case of the NE-based approach, it is identical to the sender's "nEDistinguishedName".
vendorName	fileHeader vendorName	The "vendorName" identifies the vendor of the equipment that provided the measurement file. The string may be empty (i.e. string size =0) if the "vendorName" is not configured in the sender. For the XML schema based XML format, XML attribute specification "vendorName" may be absent in case the "vendorName" is not configured in the sender.
neld	managedElement	The unique identification of the NE in the system. It includes the user name ("nEUserName"), the distinguished name ("nEDistinguishedName") and the software version ("nESoftwareVersion") of the NE.
neUserName	managedElement userLabel	This is the user definable name ("userLabel") defined for the NE in 3GPP TS 32.622 [17]. The string may be empty (i.e. string size =0) if the "nEUserName" is not configured in the CM applications. For the XML schema based XML format, XML attribute specification "userLabel" may be absent in case the "nEUserName" is not configured in the CM applications.
neDistinguishedName	managedElement localDn	This is the Distinguished Name (DN) defined for the NE in 3GPP TS 32.300 [4]. It is unique across an operator's 3G network. The string may be empty (i.e. string size =0) if the "nEDistinguishedName" is not configured in the CM applications. For the XML schema based XML format, the DN is split into the DN prefix and the Local DN (LDN) (see 3GPP TS 32.300 [4]). XML attribute specification "localDn" may be absent in case the LDN is not configured in the CM applications.

File Content Item	XML schema based XML tag	Description
neSoftwareVersion	managedElement swVersion	This is the software version ("swVersion") defined for the NE in 3GPP TS 32.622 [17]. This is an optional parameter which allows post-processing systems to take care of vendor specific measurements modified between software versions. For the XML schema based XML format, XML attribute specification "swVersion" may be absent in case the "neSoftwareVersion" is not configured in the CM applications.
Modifier	configData modifier	This element is present if the HMS is required to inform the NE whether the parameter information should be used to create, update or delete an specific object instance on the HNB.. If not present the NE will assume the modification action is update
HNBDataParameters	configData DeviceInfo configData ManagementServer configData Time FAPService DNPrefix FAPService FAPControl FAPService AccessMgmt FAPService CellConfig FAPService Transport FAPService REM FAPService GPS	These elements are present if the HMS requires to modify the specific configuration parameters The XML file format definitions implement the configuration structure and parameter definitions defined in broadband forum 3GPP TS 32.582 [9] and TR-098 Amendment 2 [16].
timestamp	fileFooter dateTime	

A vendor MAY extend the standardized parameter list with vendor-specific parameters and objects. Vendor-specific parameters and objects MAY be defined either in a separate naming hierarchy or within the standardized naming hierarchy of the XML File Format.

The name of a vendor-specific parameter or object not contained within another vendor-specific object MUST have the following form to align with the Vendor Specific Parameter Definition of TR-098 Amendment 2 [16].

- X_<VENDOR>_VendorSpecificName

4.2 XML schema based CM data file format definition

4.2.1 CM data file XML diagram

Figure 4.1 describes the XML element structure of the CM data file.




Figure 4.1: XML diagram of the configuration data file

4.2.2 CM data file XML schema

The following XML schema configData.xsd is the schema for CM data XML files:

```
<?xml version="1.0" encoding="UTF-8"?>

<!--
  3GPP TS 32.584 Configuration Data XML file format definition
  data file XML schema
  configData.xsd
-->
<schema xmlns:cd="http://www.3gpp.org/ftp/specs/archive/32_series/32.584#configData"
xmlns="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://www.3gpp.org/ftp/specs/archive/32_series/32.584#configData"
elementFormDefault="qualified">
  <!-- Config data XML elements -->
  <element name="AccessMode">
    <simpleType>
      <restriction base="string">
        <enumeration value="Open Access"/>
        <enumeration value="Closed Access"/>
        <enumeration value="Hybrid Access"/>
      </restriction>
    </simpleType>
  </element>
  <element name="BandIndicator">
    <simpleType>
      <restriction base="string">
        <enumeration value="GSM 850"/>
        <enumeration value="GSM 900"/>
        <enumeration value="DCS 1800"/>
        <enumeration value="PCS 1900"/>
      </restriction>
    </simpleType>
  </element>
  <element name="InServiceHandling">
    <simpleType>
      <restriction base="string">
        <enumeration value="Immediate"/>
        <enumeration value="Delayed"/>
      </restriction>
    </simpleType>
  </element>
  <element name="MeasurementQuantity-Inter">
    <simpleType>
      <restriction base="string">
        <enumeration value="CPICH Ec/No"/>
        <enumeration value="CPICH RSCP"/>
      </restriction>
    </simpleType>
  </element>
  <element name="MeasurementQuantity-Intra">
    <simpleType>
      <restriction base="string">
        <enumeration value="CPICH Ec/No"/>
        <enumeration value="CPICH RSCP"/>
        <enumeration value="Pathloss"/>
      </restriction>
    </simpleType>
  </element>
  <element name="Modifier">
    <simpleType>
      <restriction base="string">
        <enumeration value="create"/>
        <enumeration value="delete"/>
        <enumeration value="update"/>
      </restriction>
    </simpleType>
  </element>
  <element name="NonCSGUEAccessDecision">
    <simpleType>
      <restriction base="string">
        <enumeration value="Local"/>
        <enumeration value="Query FAP-GW"/>
        <enumeration value="By Core"/>
      </restriction>
    </simpleType>
  </element>
</schema>
```

```

</element>
<element name="NonHCSTCRMax">
  <simpleType>
    <restriction base="string">
      <enumeration value="not used"/>
      <enumeration value="30"/>
      <enumeration value="60"/>
      <enumeration value="120"/>
      <enumeration value="180"/>
      <enumeration value="240"/>
    </restriction>
  </simpleType>
</element>
<element name="NonHCSTCRMaxHyst">
  <simpleType>
    <restriction base="string">
      <enumeration value="not used"/>
      <enumeration value="10"/>
      <enumeration value="20"/>
      <enumeration value="30"/>
      <enumeration value="40"/>
      <enumeration value="50"/>
      <enumeration value="60"/>
      <enumeration value="70"/>
    </restriction>
  </simpleType>
</element>
<element name="NumberOfPSCs">
  <simpleType>
    <restriction base="string">
      <enumeration value="5"/>
      <enumeration value="10"/>
      <enumeration value="15"/>
      <enumeration value="20"/>
      <enumeration value="30"/>
      <enumeration value="40"/>
      <enumeration value="50"/>
      <enumeration value="64"/>
      <enumeration value="80"/>
      <enumeration value="120"/>
      <enumeration value="160"/>
      <enumeration value="256"/>
      <enumeration value="alltherest"/>
      <enumeration value="spare3"/>
      <enumeration value="spare2"/>
      <enumeration value="spare1"/>
    </restriction>
  </simpleType>
</element>
<element name="PLMNType">
  <simpleType>
    <restriction base="string">
      <enumeration value="GSM-MAP"/>
      <enumeration value="ANSI-41"/>
    </restriction>
  </simpleType>
</element>
<element name="QualityMeasureCPICH">
  <simpleType>
    <restriction base="string">
      <enumeration value="Ec/No"/>
      <enumeration value="RSCP"/>
    </restriction>
  </simpleType>
</element>
<element name="TCRMax">
  <simpleType>
    <restriction base="string">
      <enumeration value="not used"/>
      <enumeration value="30"/>
      <enumeration value="60"/>
      <enumeration value="120"/>
      <enumeration value="180"/>
      <enumeration value="240"/>
    </restriction>
  </simpleType>
</element>
<element name="TCRMaxHyst">

```

```

<simpleType>
  <restriction base="string">
    <enumeration value="not used"/>
    <enumeration value="10"/>
    <enumeration value="20"/>
    <enumeration value="30"/>
    <enumeration value="40"/>
    <enumeration value="50"/>
    <enumeration value="60"/>
    <enumeration value="70"/>
  </restriction>
</simpleType>
</element>
<element name="TransferTypeFilter">
  <simpleType>
    <restriction base="string">
      <enumeration value="Upload"/>
      <enumeration value="Download"/>
      <enumeration value="Both"/>
    </restriction>
  </simpleType>
</element>
<element name="DeviceInfo">
  <complexType>
    <sequence>
      <element name="ProvisioningCode" type="string" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="AutonomousTransferCompletePolicy">
  <complexType>
    <sequence>
      <element name="Enable" type="boolean" minOccurs="0"/>
      <element ref="cd:TransferTypeFilter" minOccurs="0"/>
      <element name="FileTypeFilter" type="string" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="ManagementServer">
  <complexType>
    <sequence>
      <element name="URL" type="string" minOccurs="0"/>
      <element name="Username" type="string" minOccurs="0"/>
      <element name="Password" type="string" minOccurs="0"/>
      <element name="PeriodicInformEnable" type="boolean" minOccurs="0"/>
      <element name="PeriodicInformInterval" type="unsignedInt" minOccurs="0"/>
      <element name="PeriodicInformTime" type="dateTime" minOccurs="0"/>
      <element name="ConnectionRequestUsername" type="string" minOccurs="0"/>
      <element name="ConnectionRequestPassword" type="string" minOccurs="0"/>
      <element name="DefaultActiveNotificationThrottle" type="unsignedInt" minOccurs="0"/>
      <element ref="cd:AutonomousTransferCompletePolicy" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="Time">
  <complexType>
    <sequence>
      <element name="Enable" type="boolean" minOccurs="0"/>
      <element name="NTPServer1" type="string" minOccurs="0"/>
      <element name="NTPServer2" type="string" minOccurs="0"/>
      <element name="NTPServer3" type="string" minOccurs="0"/>
      <element name="NTPServer4" type="string" minOccurs="0"/>
      <element name="NTPServer5" type="string" minOccurs="0"/>
      <element name="LocalTimeZoneName" type="string" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="DNPrefix" type="string"/>
<element name="Gateway">
  <complexType>
    <sequence>
      <element name="SecGWServer1" type="string" minOccurs="0"/>
      <element name="SecGWServer2" type="string" minOccurs="0"/>
      <element name="SecGWServer3" type="string" minOccurs="0"/>
      <element name="FAPGWServer1" type="string" minOccurs="0"/>
      <element name="FAPGWServer2" type="string" minOccurs="0"/>
      <element name="FAPGWServer3" type="string" minOccurs="0"/>
      <element name="FAPGWPort" type="unsignedInt" minOccurs="0"/>
    </sequence>
  </complexType>

```

```

    </sequence>
  </complexType>
</element>
<element name="SelfConfig">
  <complexType>
    <sequence>
      <element name="UARFCNSelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="PrimaryScramblingCodeSelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="MaxFAPTxPowerSelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="PCPICHPowerSelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="MaxULTxPowerSelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="LACRACURASelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="NeighborListSelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="CellReSelectionSelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="IntraFreqMeasSelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="InterFreqMeasSelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="InterRATMeasSelfConfigEnable" type="boolean" minOccurs="0"/>
      <element name="UEInternalMeasConfigEnable" type="boolean" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="UMTS">
  <complexType>
    <sequence>
      <element ref="cd:SelfConfig" minOccurs="0"/>
      <element ref="cd:Gateway" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="AdminState" type="boolean"/>
<element name="SelfConfigEvents" type="string"/>
<element name="EnclosureTamperingDetected" type="boolean"/>
<element name="FAPControl">
  <complexType>
    <sequence>
      <element ref="cd:AdminState" minOccurs="0"/>
      <element ref="cd:SelfConfigEvents" minOccurs="0"/>
      <element ref="cd:EnclosureTamperingDetected" minOccurs="0"/>
      <element ref="cd:UMTS" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="CSGMembershipDeterminedLocally" type="boolean"/>
<element name="HNBNName" type="string"/>
<element name="HomeZoneName" type="string"/>
<element name="MaxConcurrentCSGUsers" type="integer"/>
<element name="CSGID" type="unsignedInt"/>
<element name="AccessControlList" type="string"/>
<element name="MemberDetail">
  <complexType>
    <sequence>
      <element ref="cd:Modifier" minOccurs="0"/>
      <element name="Enable" type="boolean" minOccurs="0"/>
      <element name="IMSI" type="string" minOccurs="0"/>
      <element name="MSISDN" type="string" minOccurs="0"/>
      <element name="MembershipExpires" type="dateTime" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="AccessMgmt">
  <complexType>
    <sequence>
      <element ref="cd:AccessMode" minOccurs="0"/>
      <element ref="cd:NonCSGUEAccessDecision" minOccurs="0"/>
      <element ref="cd:CSGMembershipDeterminedLocally" minOccurs="0"/>
      <element ref="cd:HNBNName" minOccurs="0"/>
      <element ref="cd:HomeZoneName" minOccurs="0"/>
      <element ref="cd:MaxConcurrentCSGUsers" minOccurs="0"/>
      <element ref="cd:CSGID" minOccurs="0"/>
      <element ref="cd:AccessControlList" minOccurs="0"/>
      <element ref="cd:MemberDetail" minOccurs="0" maxOccurs="unbounded"/>
    </sequence>
  </complexType>
</element>
<element name="CN">
  <complexType>
    <sequence>
      <element ref="cd:PLMNType" minOccurs="0"/>
    </sequence>
  </complexType>
</element>

```

```

<element name="PLMNID" type="string" minOccurs="0"/>
<element name="EquivPLMNID" type="string" minOccurs="0"/>
<element name="SAC" type="unsignedInt" minOccurs="0"/>
<element name="LACRAC" type="string" minOccurs="0"/>
<element name="CSDomain" minOccurs="0">
  <complexType>
    <sequence>
      <element name="T3212" type="unsignedInt" minOccurs="0"/>
      <element name="IMSIAttachDetachEnable" type="boolean" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="PSDomain" minOccurs="0">
  <complexType>
    <sequence>
      <element name="NetworkModeOperationCombined" type="boolean"
minOccurs="0"/>
    </sequence>
  </complexType>
</element>
</sequence>
</complexType>
</element>
</sequence>
</complexType>
</element>
<element name="CSG">
  <complexType>
    <sequence>
      <element name="UARFCNDLList" type="string" minOccurs="0"/>
      <element name="CSGPSCSplitInfo" minOccurs="0">
        <complexType>
          <sequence>
            <element name="StartPSCRangeCoefficient" type="unsignedInt"
minOccurs="0"/>
            <element ref="cd:NumberOfPSCs" minOccurs="0"/>
            <element name="PSCRange2Offset" type="unsignedInt" minOccurs="0"/>
          </sequence>
        </complexType>
      </element>
    </sequence>
  </complexType>
</element>
<element name="CellSelection">
  <complexType>
    <sequence>
      <element ref="cd:QualityMeasureCPICH" minOccurs="0"/>
      <element name="QqualMin" type="integer" minOccurs="0"/>
      <element name="QqualMinOffset" type="unsignedInt" minOccurs="0"/>
      <element name="QRxLevMin" type="integer" minOccurs="0"/>
      <element name="DeltaQRxLevMin" type="integer" minOccurs="0"/>
      <element name="QRxLevMinOffset" type="unsignedInt" minOccurs="0"/>
      <element name="QHyst1s" type="unsignedInt" minOccurs="0"/>
      <element name="QHyst2s" type="unsignedInt" minOccurs="0"/>
      <element name="TReselections" type="unsignedInt" minOccurs="0"/>
      <element name="SIntrasearch" type="integer" minOccurs="0"/>
      <element name="SIntersearch" type="integer" minOccurs="0"/>
      <element name="SSearchHCS" type="integer" minOccurs="0"/>
      <element name="SSearchRAT" type="integer" minOccurs="0"/>
      <element name="SHCSRAT" type="integer" minOccurs="0"/>
      <element name="SLimitSearchRAT" type="integer" minOccurs="0"/>
      <element ref="cd:NonHCSTCRMax" minOccurs="0"/>
      <element name="NonHCSNCR" type="unsignedInt" minOccurs="0"/>
      <element ref="cd:NonHCSTCRMaxHyst" minOccurs="0"/>
      <element name="QHCS" type="unsignedInt" minOccurs="0"/>
      <element name="UseOfHCS" type="boolean" minOccurs="0"/>
      <element name="HCSPrrio" type="unsignedInt" minOccurs="0"/>
      <element ref="cd:TCRMax" minOccurs="0"/>
      <element name="NCR" type="unsignedInt" minOccurs="0"/>
      <element ref="cd:TCRMaxHyst" minOccurs="0"/>
      <element name="UETxPwrMaxRACH" type="integer" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="RRCTimers">
  <complexType>
    <sequence>
      <element name="T300" type="unsignedInt" minOccurs="0"/>
      <element name="T301" type="unsignedInt" minOccurs="0"/>
      <element name="T302" type="unsignedInt" minOccurs="0"/>
      <element name="T304" type="unsignedInt" minOccurs="0"/>
    </sequence>
  </complexType>
</element>

```

```

<element name="T305" type="unsignedInt" minOccurs="0"/>
<element name="T307" type="unsignedInt" minOccurs="0"/>
<element name="T308" type="unsignedInt" minOccurs="0"/>
<element name="T309" type="unsignedInt" minOccurs="0"/>
<element name="T310" type="unsignedInt" minOccurs="0"/>
<element name="T311" type="unsignedInt" minOccurs="0"/>
<element name="T312" type="unsignedInt" minOccurs="0"/>
<element name="T313" type="unsignedInt" minOccurs="0"/>
<element name="T314" type="unsignedInt" minOccurs="0"/>
<element name="T315" type="unsignedInt" minOccurs="0"/>
<element name="T316" type="unsignedInt" minOccurs="0"/>
<element name="T317" type="unsignedInt" minOccurs="0"/>
<element name="N300" type="unsignedInt" minOccurs="0"/>
<element name="N301" type="unsignedInt" minOccurs="0"/>
<element name="N302" type="unsignedInt" minOccurs="0"/>
<element name="N304" type="unsignedInt" minOccurs="0"/>
<element name="N310" type="unsignedInt" minOccurs="0"/>
<element name="N312" type="unsignedInt" minOccurs="0"/>
<element name="N313" type="unsignedInt" minOccurs="0"/>
<element name="N315" type="unsignedInt" minOccurs="0"/>
<element name="WaitTime" type="unsignedInt" minOccurs="0"/>
</sequence>
</complexType>
</element>
<element name="DRX">
  <complexType>
    <sequence>
      <element name="DRXCycleLengthCoefficientCS" type="unsignedInt" minOccurs="0"/>
      <element name="DRXCycleLengthCoefficientPS" type="unsignedInt" minOccurs="0"/>
      <element name="UTRANDRXCycleLengthCoefficient" type="unsignedInt" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="PowerControl">
  <complexType>
    <sequence>
      <element name="ConstantValue" type="integer" minOccurs="0"/>
      <element name="PowerRampStepUp" type="unsignedInt" minOccurs="0"/>
      <element name="PreambleRetransMax" type="unsignedInt" minOccurs="0"/>
      <element name="PersistenceScaleFactor" type="unsignedInt" minOccurs="0"/>
      <element name="MMax" type="unsignedInt" minOccurs="0"/>
      <element name="NB01Min" type="unsignedInt" minOccurs="0"/>
      <element name="NB01Max" type="unsignedInt" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="CellRestriction">
  <complexType>
    <sequence>
      <element name="CellBarred" type="boolean" minOccurs="0"/>
      <element name="IntraFreqCellReselectionIndicator" type="boolean" minOccurs="0"/>
      <element name="TBarred" type="unsignedInt" minOccurs="0"/>
      <element name="AccessClassBarredListCS" type="string" minOccurs="0"/>
      <element name="AccessClassBarredListPS" type="string" minOccurs="0"/>
      <element name="CellReservedForOperatorUse" type="boolean" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="IntraFreqMeas">
  <complexType>
    <sequence>
      <element ref="cd:MeasurementQuantity-Intra" minOccurs="0"/>
      <element name="FilterCoefficient" type="unsignedInt" minOccurs="0"/>
      <element name="IntraFrequencyEventIdentity" type="string" minOccurs="0"/>
      <element name="TriggeringCondition2Event1a" type="string" minOccurs="0"/>
      <element name="TriggeringCondition1Event1b" type="string" minOccurs="0"/>
      <element name="TriggeringCondition2Event1e" type="string" minOccurs="0"/>
      <element name="TriggeringCondition1Event1f" type="string" minOccurs="0"/>
      <element name="ReportingRangeEvent1a" type="unsignedInt" minOccurs="0"/>
      <element name="ReportingRangeEvent1b" type="unsignedInt" minOccurs="0"/>
      <element name="WeightingFactorEvent1a" type="unsignedInt" minOccurs="0"/>
      <element name="WeightingFactorEvent1b" type="unsignedInt" minOccurs="0"/>
      <element name="ReportDeactivationThresholdEvent1a" type="unsignedInt"
minOccurs="0"/>
      <element name="ReportingAmountEvent1a" type="integer" minOccurs="0"/>
      <element name="ReportingAmountEvent1c" type="integer" minOccurs="0"/>
      <element name="ReportingIntervalEvent1a" type="unsignedInt" minOccurs="0"/>
      <element name="ReportingIntervalEvent1c" type="unsignedInt" minOccurs="0"/>
    </sequence>
  </complexType>
</element>

```



```

    <element name="HysteresisEvent1a" type="unsignedInt" minOccurs="0"/>
    <element name="HysteresisEvent1b" type="unsignedInt" minOccurs="0"/>
    <element name="HysteresisEvent1c" type="unsignedInt" minOccurs="0"/>
    <element name="HysteresisEvent1e" type="unsignedInt" minOccurs="0"/>
    <element name="HysteresisEvent1f" type="unsignedInt" minOccurs="0"/>
    <element name="TimeToTriggerEvent1a" type="unsignedInt" minOccurs="0"/>
    <element name="TimeToTriggerEvent1b" type="unsignedInt" minOccurs="0"/>
    <element name="TimeToTriggerEvent1c" type="unsignedInt" minOccurs="0"/>
    <element name="TimeToTriggerEvent1e" type="unsignedInt" minOccurs="0"/>
    <element name="TimeToTriggerEvent1f" type="unsignedInt" minOccurs="0"/>
    <element name="ThresholdUsedFrequencyEvent1e" type="integer" minOccurs="0"/>
    <element name="ThresholdUsedFrequencyEvent1f" type="integer" minOccurs="0"/>
    <element name="ReplacementActivationThresholdEvent1c" type="unsignedInt"
minOccurs="0"/>
  </sequence>
</complexType>
</element>
<element name="InterFreqMeas">
  <complexType>
    <sequence>
      <element ref="cd:MeasurementQuantity-Inter" minOccurs="0"/>
      <element name="FilterCoefficient" type="unsignedInt" minOccurs="0"/>
      <element name="InterFrequencyEventIdentity" type="string" minOccurs="0"/>
      <element name="WeightingFactorEvent2a" type="unsignedInt" minOccurs="0"/>
      <element name="WeightingFactorEvent2b" type="unsignedInt" minOccurs="0"/>
      <element name="WeightingFactorEvent2d" type="unsignedInt" minOccurs="0"/>
      <element name="WeightingFactorEvent2f" type="unsignedInt" minOccurs="0"/>
      <element name="HysteresisEvent2a" type="unsignedInt" minOccurs="0"/>
      <element name="HysteresisEvent2b" type="unsignedInt" minOccurs="0"/>
      <element name="HysteresisEvent2d" type="unsignedInt" minOccurs="0"/>
      <element name="HysteresisEvent2f" type="unsignedInt" minOccurs="0"/>
      <element name="TimeToTriggerEvent2a" type="unsignedInt" minOccurs="0"/>
      <element name="TimeToTriggerEvent2b" type="unsignedInt" minOccurs="0"/>
      <element name="TimeToTriggerEvent2d" type="unsignedInt" minOccurs="0"/>
      <element name="TimeToTriggerEvent2f" type="unsignedInt" minOccurs="0"/>
      <element name="ThresholdUsedFrequencyEvent2b" type="integer" minOccurs="0"/>
      <element name="ThresholdUsedFrequencyEvent2d" type="integer" minOccurs="0"/>
      <element name="ThresholdUsedFrequencyEvent2f" type="integer" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="InterRATMeas">
  <complexType>
    <sequence>
      <element name="GSMFilterCoefficient" type="unsignedInt" minOccurs="0"/>
      <element name="BSICVerificationRequired" type="boolean" minOccurs="0"/>
      <element name="WeightingFactor" type="unsignedInt" minOccurs="0"/>
      <element name="Hysteresis" type="unsignedInt" minOccurs="0"/>
      <element name="TimeToTrigger" type="unsignedInt" minOccurs="0"/>
      <element name="ThresholdOwnSystem" type="integer" minOccurs="0"/>
      <element name="ThresholdOtherSystem" type="integer" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="UEInternalMeas">
  <complexType>
    <sequence>
      <element name="FilterCoefficient" type="unsignedInt" minOccurs="0"/>
      <element name="UETxPwrThresholdEvent6a" type="integer" minOccurs="0"/>
      <element name="TimeToTriggerEvent6a" type="unsignedInt" minOccurs="0"/>
      <element name="UETxPwrThresholdEvent6b" type="integer" minOccurs="0"/>
      <element name="TimeToTriggerEvent6b" type="unsignedInt" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="RF">
  <complexType>
    <sequence>
      <element name="UARFCNDL" type="string" minOccurs="0"/>
      <element name="UARFCNDLToProtect" type="string" minOccurs="0"/>
      <element name="PrimaryScramblingCode" type="string" minOccurs="0"/>
      <element name="MaxFAPTxPower" type="string" minOccurs="0"/>
      <element name="MaxULTxPower" type="string" minOccurs="0"/>
      <element name="PCPICHPower" type="string" minOccurs="0"/>
      <element name="PowerOffsetPilotDPDCH" type="unsignedInt" minOccurs="0"/>
      <element name="FAPCoverageTarget" type="unsignedInt" minOccurs="0"/>
      <element name="PSCHPower" type="integer" minOccurs="0"/>
      <element name="SSCHPower" type="integer" minOccurs="0"/>
    </sequence>
  </complexType>
</element>

```

```

    <element name="PICHPower" type="integer" minOccurs="0"/>
    <element name="PCHPower" type="integer" minOccurs="0"/>
    <element name="FACHPower" type="integer" minOccurs="0"/>
    <element name="BCHPower" type="integer" minOccurs="0"/>
    <element name="AICHPower" type="integer" minOccurs="0"/>
    <element name="CTCHAllocationPeriod" type="unsignedInt" minOccurs="0"/>
    <element name="CBSFrameOffset" type="unsignedInt" minOccurs="0"/>
    <element name="MaxTTT" type="unsignedInt" minOccurs="0"/>
  </sequence>
</complexType>
</element>
<element name="IntraFreqCell">
  <complexType>
    <sequence>
      <element ref="cd:Modifier" minOccurs="0"/>
      <element name="Enable" type="boolean" minOccurs="0"/>
      <element name="MustInclude" type="boolean" minOccurs="0"/>
      <element name="PLMNID" type="string" minOccurs="0"/>
      <element name="RNCID" type="unsignedInt" minOccurs="0"/>
      <element name="CID" type="unsignedInt" minOccurs="0"/>
      <element name="LAC" type="unsignedInt" minOccurs="0"/>
      <element name="RAC" type="unsignedInt" minOccurs="0"/>
      <element name="URA" type="unsignedInt" minOccurs="0"/>
      <element name="PCPICHScramblingCode" type="unsignedInt" minOccurs="0"/>
      <element name="PCPICHTxPower" type="integer" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="InterFreqCell">
  <complexType>
    <sequence>
      <element ref="cd:Modifier" minOccurs="0"/>
      <element name="Enable" type="boolean" minOccurs="0"/>
      <element name="MustInclude" type="boolean" minOccurs="0"/>
      <element name="PLMNID" type="string" minOccurs="0"/>
      <element name="RNCID" type="unsignedInt" minOccurs="0"/>
      <element name="CID" type="unsignedInt" minOccurs="0"/>
      <element name="LAC" type="unsignedInt" minOccurs="0"/>
      <element name="RAC" type="unsignedInt" minOccurs="0"/>
      <element name="URA" type="unsignedInt" minOccurs="0"/>
      <element name="UARFCNUL" type="unsignedInt" minOccurs="0"/>
      <element name="UARFCNDL" type="unsignedInt" minOccurs="0"/>
      <element name="PCPICHScramblingCode" type="unsignedInt" minOccurs="0"/>
      <element name="PCPICHTxPower" type="integer" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="InterRATCell">
  <complexType>
    <sequence>
      <element name="GSM" minOccurs="0" maxOccurs="unbounded">
        <complexType>
          <sequence>
            <element ref="cd:Modifier" minOccurs="0"/>
            <element name="Enable" type="boolean" minOccurs="0"/>
            <element name="MustInclude" type="boolean" minOccurs="0"/>
            <element name="PLMNID" type="string" minOccurs="0"/>
            <element name="LAC" type="unsignedInt" minOccurs="0"/>
            <element name="BSIC" type="unsignedInt" minOccurs="0"/>
            <element name="CI" type="unsignedInt" minOccurs="0"/>
            <element ref="cd:BandIndicator" minOccurs="0"/>
            <element name="BCCHARFCN" type="unsignedInt" minOccurs="0"/>
          </sequence>
        </complexType>
      </element>
    </sequence>
  </complexType>
</element>
<element name="NeighborList">
  <complexType>
    <sequence>
      <element ref="cd:IntraFreqCell" minOccurs="0" maxOccurs="unbounded"/>
      <element ref="cd:InterFreqCell" minOccurs="0" maxOccurs="unbounded"/>
      <element ref="cd:InterRATCell" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="FDDFAP">

```

```

<complexType>
  <sequence>
    <element name="HSFlag" type="boolean" minOccurs="0"/>
    <element name="HSEnable" type="boolean" minOccurs="0"/>
    <element name="NumOfHSPDSCHs" type="unsignedInt" minOccurs="0"/>
    <element name="NumOfHSSCCCHs" type="unsignedInt" minOccurs="0"/>
    <element ref="cd:CellSelection" minOccurs="0"/>
    <element ref="cd:RRCTimers" minOccurs="0"/>
    <element ref="cd:DRX" minOccurs="0"/>
    <element ref="cd:PowerControl" minOccurs="0"/>
    <element ref="cd:CellRestriction" minOccurs="0"/>
    <element ref="cd:IntraFreqMeas" minOccurs="0"/>
    <element ref="cd:InterFreqMeas" minOccurs="0"/>
    <element ref="cd:InterRATMeas" minOccurs="0"/>
    <element ref="cd:UEInternalMeas" minOccurs="0"/>
    <element ref="cd:RF" minOccurs="0"/>
    <element ref="cd:NeighborList" minOccurs="0"/>
  </sequence>
</complexType>
</element>
<element name="RAN">
  <complexType>
    <sequence>
      <element name="URAList" type="string" minOccurs="0"/>
      <element name="RNCID" type="unsignedInt" minOccurs="0"/>
      <element name="CellID" type="unsignedInt" minOccurs="0"/>
      <element name="HNBIDRealm" type="string" minOccurs="0"/>
      <element name="TRatC" type="unsignedInt" minOccurs="0"/>
      <element name="TRafC" type="unsignedInt" minOccurs="0"/>
      <element name="NRafC" type="unsignedInt" minOccurs="0"/>
      <element name="TigOR" type="unsignedInt" minOccurs="0"/>
      <element name="TinTR" type="unsignedInt" minOccurs="0"/>
      <element name="TDataFwd" type="unsignedInt" minOccurs="0"/>
      <element name="TRelocPrep" type="unsignedInt" minOccurs="0"/>
      <element name="TRelocOverall" type="unsignedInt" minOccurs="0"/>
      <element ref="cd:CSG" minOccurs="0"/>
      <element ref="cd:FDDFAP" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="CellConfig">
  <complexType>
    <sequence>
      <element name="UMTS" minOccurs="0">
        <complexType>
          <sequence>
            <element ref="cd:CN" minOccurs="0"/>
            <element ref="cd:RAN" minOccurs="0"/>
          </sequence>
        </complexType>
      </element>
    </sequence>
  </complexType>
</element>
<element name="SCTP">
  <complexType>
    <sequence>
      <element name="Enable" type="boolean" minOccurs="0"/>
      <element name="HBInterval" type="unsignedInt" minOccurs="0"/>
      <element name="MaxAssociationRetransmits" type="unsignedInt" minOccurs="0"/>
      <element name="MaxInitRetransmits" type="unsignedInt" minOccurs="0"/>
      <element name="MaxPathRetransmits" type="unsignedInt" minOccurs="0"/>
      <element name="RTOInitial" type="unsignedInt" minOccurs="0"/>
      <element name="RTOMax" type="unsignedInt" minOccurs="0"/>
      <element name="RTOMin" type="unsignedInt" minOccurs="0"/>
      <element name="ValCookieLife" type="unsignedInt" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="RealTime">
  <complexType>
    <sequence>
      <element name="RTCPEnable" type="boolean" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="Packet">
  <complexType>

```

```

        <sequence>
          <element name="EchoInterval" type="unsignedInt" minOccurs="0"/>
        </sequence>
      </complexType>
    </element>
    <element name="Tunnel">
      <complexType>
        <sequence>
          <element name="VirtualInterface" minOccurs="0" maxOccurs="unbounded">
            <complexType>
              <sequence>
                <element name="Enable" type="boolean" minOccurs="0"/>
                <element ref="cd:Modifier" minOccurs="0"/>
                <element name="CryptoProfile" type="string" minOccurs="0"/>
                <element name="DSCPMarkPolicy" type="integer" minOccurs="0"/>
              </sequence>
            </complexType>
          </element>
        </sequence>
      </complexType>
    </element>
    <element name="Security">
      <complexType>
        <sequence>
          <element name="Secret" minOccurs="0" maxOccurs="unbounded">
            <complexType>
              <sequence>
                <element name="Enable" type="boolean" minOccurs="0"/>
              </sequence>
            </complexType>
          </element>
          <element name="Pkey" minOccurs="0" maxOccurs="unbounded">
            <complexType>
              <sequence>
                <element name="Enable" type="boolean" minOccurs="0"/>
              </sequence>
            </complexType>
          </element>
          <element name="CryptoProfile" minOccurs="0" maxOccurs="unbounded">
            <complexType>
              <sequence>
                <element ref="cd:Modifier" minOccurs="0"/>
                <element name="Enable" type="boolean" minOccurs="0"/>
                <element name="AuthMethod" type="string"/>
                <element name="MaxChildSA" type="unsignedInt" minOccurs="0"/>
                <element name="IKEEncrypt" type="string"/>
                <element name="IKEPRF" type="string"/>
                <element name="IKEIntegrity" type="string"/>
                <element name="IKEDH" type="string"/>
                <element name="ESPEncrypt" type="string"/>
                <element name="ESPIntegrity" type="string"/>
                <element name="IPsecWindowSize" type="unsignedInt" minOccurs="0"/>
                <element name="IKERekeyLifetime" type="unsignedInt" minOccurs="0"/>
                <element name="IPsecRekeyLifetimeByte" type="unsignedInt"
minOccurs="0"/>
                <element name="IPsecRekeyLifetimeTime" type="unsignedInt"
minOccurs="0"/>
                <element name="DPDTimer" type="unsignedInt" minOccurs="0"/>
                <element name="NATTKeepaliveTimer" type="unsignedInt" minOccurs="0"/>
              </sequence>
            </complexType>
          </element>
        </sequence>
      </complexType>
    </element>
    <element name="Transport">
      <complexType>
        <sequence>
          <element ref="cd:SCTP" minOccurs="0"/>
          <element ref="cd:RealTime" minOccurs="0"/>
          <element ref="cd:Packet" minOccurs="0"/>
          <element ref="cd:Tunnel" minOccurs="0"/>
          <element ref="cd:Security" minOccurs="0"/>
        </sequence>
      </complexType>
    </element>
    <element name="WCDMAFDD">
      <complexType>

```

```

    <sequence>
      <element ref="cd:InServiceHandling" minOccurs="0"/>
      <element name="ScanOnBoot" type="boolean" minOccurs="0"/>
      <element name="ScanPeriodically" type="boolean" minOccurs="0"/>
      <element name="PeriodicInterval" type="unsignedInt" minOccurs="0"/>
      <element name="PeriodicTime" type="dateTime" minOccurs="0"/>
      <element name="REMPLMNList" type="string" minOccurs="0"/>
      <element name="REMBandList" type="string" minOccurs="0"/>
      <element name="UARFCNDLList" type="string" minOccurs="0"/>
      <element name="ScanTimeout" type="unsignedInt" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="GSM">
  <complexType>
    <sequence>
      <element ref="cd:InServiceHandling" minOccurs="0"/>
      <element name="ScanOnBoot" type="boolean" minOccurs="0"/>
      <element name="ScanPeriodically" type="boolean" minOccurs="0"/>
      <element name="PeriodicInterval" type="unsignedInt" minOccurs="0"/>
      <element name="PeriodicTime" type="dateTime" minOccurs="0"/>
      <element name="REMPLMNList" type="string" minOccurs="0"/>
      <element name="REMBandList" type="string" minOccurs="0"/>
      <element name="ARFCNList" type="string" minOccurs="0"/>
      <element name="ScanTimeout" type="unsignedInt" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="REM">
  <complexType>
    <sequence>
      <element ref="cd:WCDMAFDD" minOccurs="0"/>
      <element ref="cd:GSM" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<element name="GPS">
  <complexType>
    <sequence>
      <element name="ScanOnBoot" type="boolean" minOccurs="0"/>
      <element name="ScanPeriodically" type="boolean" minOccurs="0"/>
      <element name="PeriodicInterval" type="unsignedInt" minOccurs="0"/>
      <element name="PeriodicTime" type="dateTime" minOccurs="0"/>
      <element name="ContinuousGPS" type="boolean" minOccurs="0"/>
      <element name="ScanTimeout" type="unsignedInt" minOccurs="0"/>
    </sequence>
  </complexType>
</element>
<!-- Configuration data file root XML element -->
<element name="configDataFile">
  <complexType>
    <sequence>
      <element name="fileHeader">
        <complexType>
          <attribute name="fileFormatVersion" type="string" use="required"/>
          <attribute name="senderName" type="string" use="optional"/>
          <attribute name="vendorName" type="string" use="optional"/>
        </complexType>
      </element>
      <element name="configData" minOccurs="0" maxOccurs="unbounded">
        <complexType>
          <sequence>
            <element name="managedElement">
              <complexType>
                <attribute name="localDn" type="string" use="optional"/>
                <attribute name="userLabel" type="string" use="optional"/>
                <attribute name="swVersion" type="string" use="optional"/>
              </complexType>
            </element>
            <element ref="cd:DeviceInfo" minOccurs="0"/>
            <element ref="cd:ManagementServer" minOccurs="0"/>
            <element ref="cd:Time" minOccurs="0"/>
            <element name="FAPService" minOccurs="0" maxOccurs="unbounded">
              <complexType>
                <sequence>
                  <element ref="cd:DNPrefix" minOccurs="0"/>
                  <element ref="cd:FAPControl" minOccurs="0"/>
                  <element ref="cd:AccessMgmt" minOccurs="0"/>
                </sequence>
              </complexType>
            </element>
          </sequence>
        </complexType>
      </element>
    </sequence>
  </complexType>
</element>

```

```

        <element ref="cd:CellConfig" minOccurs="0"/>
        <element ref="cd:Transport" minOccurs="0"/>
        <element ref="cd:REM" minOccurs="0"/>
        <element ref="cd:GPS" minOccurs="0"/>
    </sequence>
</complexType>
</element>
</sequence>
</complexType>
</element>
<element name="fileFooter">
    <complexType>
        <attribute name="dateTime" type="dateTime" use="required"/>
    </complexType>
</element>
</sequence>
</complexType>
</element>
</schema>

```

4.2.3 CM data file XML header

The following header shall be used in actual XML CM data files:

```

<?xml version="1.0" encoding="UTF-8"?>
<?xml-stylesheet type="text/xsl" href="configData.xsl"?>
<ConfigDataFile
  xmlns=
"http://www.3gpp.org/ftp/specs/archive/32_series/32.584#configData"
>

```

5 PM data format definition

5.1 Mapping table

Table 5.1 maps the PM file content items in the 3GPP TS 32.582 [9] document to those used in the XML schema based file format definitions. XML tag attributes are useful where data values bind tightly to its parent element. They have been used where appropriate.

Table 5.1 Mapping of File Content Items to XML tags

File Content Item	XML schema based XML tag	Description
measDataCollection	measCollecFile	
measFileHeader	fileHeader	
measData	measData	
measFileFooter	fileFooter	
fileFormatVersion	fileHeader fileFormatVersion	
senderName	fileHeader dnPrefix and fileSender localDn	For the XML schema based XML format, the DN is split into the DN prefix and the Identifier of the Managed Object (see 3GPP TS 32.582 [9]). XML attribute specification "dnPrefix" may be absent in case the DN prefix is not configured in the sender. XML attribute specification "localDn" may be absent in case the Identifier of the Managed Object is not configured in the sender.
senderType	fileSender elementType	For the XML schema based XML format, XML attribute specification "elementType" may be absent in case the "senderType" is not configured in the sender.
vendorName	fileHeader vendorName	For the XML schema based XML format, XML attribute specification "vendorName" may be absent in case the "vendorName" is not configured in the sender.
collectionBeginTime	measCollec beginTime	3GPP TS 32.582 [9] clause 6.3.2.1 Period Statistics "ReportStartTime"
neld	managedElement	

File Content Item	XML schema based XML tag	Description
neUserName	managedElement userLabel	For the XML schema based XML format, XML attribute specification "userLabel" may be absent in case the "neUserName" is not configured in the CM applications. Not used in HNB PM file
neDistinguishedName	fileHeader dnPrefix and managedElement localDn	For the XML schema based XML format, the DN is split into the DN prefix and the Identifier of the Managed Object (see 3GPP TS 32.582 [9]). XML attribute specification "localDn" may be absent in case the Identifier of the Managed Object is not configured in the CM applications.
neSoftwareVersion	managedElement swVersion	For the XML schema based XML format, XML attribute specification "swVersion" may be absent in case the "neSoftwareVersion" is not configured in the CM applications. Not used in HNB PM file
measInfo	measInfo	
measInfofold	measInfofold	
measTimeStamp	granPeriod endTime	Calculated from the 3GPP TS 32.582 [9] clause 6.3.2.1 Period Statistics "ReportStartTime" + accumulation of the 3GPP TS 32.582 [9] clause 6.3.2.1 Period Statistics "SampleSeconds"
jobId	Job jobId	Not used in HNB PM file
granularityPeriod	granPeriod duration	For the XML schema based XML format, the value of XML attribute specification "duration" shall use the truncated representation "PTnS" (see [13]). 3GPP TS 32.582 [9] clause 6.3.2.1 Period Statistics "SampleInterval"
reportingPeriod	repPeriod duration	For the XML schema based XML format, the value of XML attribute specification "duration" shall use the truncated representation "PTnS" (see [13]). 3GPP TS 32.582 [9] clause 6.3.1.1 Period Upload Interval
measTypes	measTypes or measType	For the XML schema based XML format, depending on sender's choice for optional positioning presence, either XML element "measTypes" or XML elements "measType" will be used. 3GPP TS 32.582 [9] clause 6.3.2.2 Period Statistics Reference
measValues	measValue	
measObjInstId	measValue measObjLdn	Identifier of the Managed Object (see 3GPP TS 32.582 [9])
measResults	measResults or R	For the XML schema based XML format, depending on sender's choice for optional positioning presence, either XML element "measResults" or XML elements "r" will be used. Broadband Forum data Model WT-157 [15] PeriodicStatistics.SampleSet.{i}.Parameter.{j}.Values
suspectFlag	Suspect	Not used in HNB PM file
timeStamp	measCollec endTime	3GPP TS 32.582 [9] clause 6.3.2.1 Period Statistics ReportEndTime
There is no corresponding File Content Item.	measType p	An optional positioning XML attribute specification of XML element "measType" (XML schema based), used to identify a measurement type for the purpose of correlation to a result. The value of this XML attribute specification is expected to be a non-zero, non-negative integer value that is unique for each instance of XML element "measType" that is contained within the measurement data collection file. Not used in HNB PM file
There is no corresponding File Content Item.	r p	An optional positioning XML attribute specification of XML element "r", used to correlate a result to a measurement type. The value of this XML attribute specification should match the value of XML attribute specification "p" of the corresponding XML element "measType" (XML schema based). Not used in HNB PM file

The representation of all timestamps in PM files shall follow the representations allowed by the ISO 8601 [abc].

The precise format for timestamp representation shall be determined by the technology used for encoding the PM file (e.g. XML DTD, XML Schema). The choice of technology should ensure that this representation is derived from ISO 8601 [abc]. Based on the representation used, the timestamp shall refer to either UTC time or local time or local time with offset from UTC.

5.2 XML schema based PM data file format definition

5.2.1 PM data file XML diagram

For the purposes of the present document XML diagram in TS 32.435 [8] section 4.2.1 applies.

5.2.2 PM data file XML schema

For the purposes of the present document XML schema in TS 32.435 [8] section 4.2.2 applies.

5.2.2 PM data file XML header

For the purposes of the present document XML header in TS 32.435 [8] section 4.2.3 applies.

Annex A (informative): Examples

A.1 XML schema based CM data file

```
<?xml version="1.0" encoding="UTF-8"?>
<?xml-stylesheet type="text/xsl" href="ConfigData.xsl"?>
<configDataFile xmlns="http://www.3gpp.org/ftp/specs/archive/32_series/32.584# onfigData"
xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:schemaLocation="http://www.3gpp.org/ftp/specs/archive/32_series/32.584#configData"
http://www.3gpp.org/ftp/specs/archive/32_series/32.584#configData">
  <fileHeader fileFormatVersion="32.584 V1.0" vendorName="Company NN" >
    </fileHeader>
  <configData>
    <managedElement localDn="SubNetwork=CountryNN,MeContext=MEC-Gbg-1,ManagedElement=RNC-Gbg-1"
userLabel="RNC Telecomville"/>
    <DeviceInfo>
      <ProvisioningCode>0101</ProvisioningCode>
    </DeviceInfo>
  </configData>
  <fileFooter dateTime="2000-03-01T14:15:00+02:00">
    </fileFooter>
</configDataFile>
```

A.2 XML schema based PM data file

For the purposes of the present document the examples in TS 32.435 [8] Annex A apply.

Annex B (informative): XML schema electronic files

The electronic files corresponding to the normative XML schemas defined in the present document are available in native form in the following archive:

http://www.3gpp.org/ftp/specs/archive/32_series/32.584/schema/32584-800-XMLSchema.zip

Annex C (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
2009-06	SA#44	SP-090302	--	--	Presentation for information and approval	1.0.0	8.0.0
2009-09	SA#45	SP-090534			Correct global modifier of XML file for CM to instance specific modifier	8.0.0	8.1.0
2009-09	SA#45	SP-090534	1	-			
2009-09	SA#45	SP-090534	2	-	Correct FAPService.{i}.Transport.Security.Secret.{j}. object definitions	8.0.0	8.1.0
2009-09	SA#45	SP-090539	3	-	Change CM file per contribution to BBF	8.0.0	8.1.0

History

Document history		
V8.0.0	July 2009	Publication
V8.1.0	October 2009	Publication