



**Digital cellular telecommunications system (Phase 2+) (GSM);
Universal Mobile Telecommunications System (UMTS);
LTE;
Telecommunication management;
Configuration Management (CM);
Bulk CM Integration Reference Point (IRP): Requirements
(3GPP TS 32.611 version 19.0.0 Release 19)**



Reference

RTS/TSGS-0532611vj00

Keywords

GSM,LTE,UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - APE 7112B
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° w061004871

Important notice

The present document can be downloaded from the
[ETSI Search & Browse Standards application](#).

The present document may be made available in electronic versions and/or in print. The content of any electronic and/or print versions of the present document shall not be modified without the prior written authorization of ETSI. In case of any existing or perceived difference in contents between such versions and/or in print, the prevailing version of an ETSI deliverable is the one made publicly available in PDF format on [ETSI deliver repository](#).

Users should be aware that the present document may be revised or have its status changed,
this information is available in the [Milestones listing](#).

If you find errors in the present document, please send your comments to
the relevant service listed under [Committee Support Staff](#).

If you find a security vulnerability in the present document, please report it through our
[Coordinated Vulnerability Disclosure \(CVD\)](#) program.

Notice of disclaimer & limitation of liability

The information provided in the present deliverable is directed solely to professionals who have the appropriate degree of experience to understand and interpret its content in accordance with generally accepted engineering or other professional standard and applicable regulations.

No recommendation as to products and services or vendors is made or should be implied.

No representation or warranty is made that this deliverable is technically accurate or sufficient or conforms to any law and/or governmental rule and/or regulation and further, no representation or warranty is made of merchantability or fitness for any particular purpose or against infringement of intellectual property rights.

In no event shall ETSI be held liable for loss of profits or any other incidental or consequential damages.

Any software contained in this deliverable is provided "AS IS" with no warranties, express or implied, including but not limited to, the warranties of merchantability, fitness for a particular purpose and non-infringement of intellectual property rights and ETSI shall not be held liable in any event for any damages whatsoever (including, without limitation, damages for loss of profits, business interruption, loss of information, or any other pecuniary loss) arising out of or related to the use of or inability to use the software.

Copyright Notification

No part may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm except as authorized by written permission of ETSI.

The content of the PDF version shall not be modified without the written authorization of ETSI.

The copyright and the foregoing restriction extend to reproduction in all media.

© ETSI 2025.
All rights reserved.

Intellectual Property Rights

Essential patents

IPRs essential or potentially essential to normative deliverables may have been declared to ETSI. The declarations pertaining to these essential IPRs, if any, are publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: *"Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards"*, which is available from the ETSI Secretariat. Latest updates are available on the [ETSI IPR online database](#).

Pursuant to the ETSI Directives including the ETSI IPR Policy, no investigation regarding the essentiality of IPRs, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Trademarks

The present document may include trademarks and/or tradenames which are asserted and/or registered by their owners. ETSI claims no ownership of these except for any which are indicated as being the property of ETSI, and conveys no right to use or reproduce any trademark and/or tradename. Mention of those trademarks in the present document does not constitute an endorsement by ETSI of products, services or organizations associated with those trademarks.

DECT™, **PLUGTESTS™**, **UMTS™** and the ETSI logo are trademarks of ETSI registered for the benefit of its Members. **3GPP™**, **LTE™** and **5G™** logo are trademarks of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners. **oneM2M™** logo is a trademark of ETSI registered for the benefit of its Members and of the oneM2M Partners. **GSM®** and the GSM logo are trademarks registered and owned by the GSM Association.

Legal Notice

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities. These shall be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between 3GPP and ETSI identities can be found at [3GPP to ETSI numbering cross-referencing](#).

Modal verbs terminology

In the present document "**shall**", "**shall not**", "**should**", "**should not**", "**may**", "**need not**", "**will**", "**will not**", "**can**" and "**cannot**" are to be interpreted as described in clause 3.2 of the [ETSI Drafting Rules](#) (Verbal forms for the expression of provisions).

"**must**" and "**must not**" are **NOT** allowed in ETSI deliverables except when used in direct citation.

Contents

Intellectual Property Rights	2
Legal Notice	2
Modal verbs terminology.....	2
Foreword.....	4
Introduction	4
1 Scope	5
2 References	5
3 Definitions and abbreviations.....	5
3.1 Definitions	5
3.2 Abbreviations	7
4 Bulk CM and Itf-N Interface	8
4.1 Bulk CM principles	8
4.2 Overview of IRPs related to Bulk CM	8
4.3 Bulk CM Requirements	8
Annex A (informative): Change history	11
History	12

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of a TS-family covering the 3rd Generation Partnership Project; Technical Specification Group Services and System Aspects; Telecommunication management; as identified below:

32.611: "Configuration Management (CM); Bulk CM Integration Reference Point (IRP): Requirements".

32.612: "Configuration Management (CM); Bulk CM Integration Reference Point (IRP): Information Service (IS)".

32.616: "Configuration Management (CM); Bulk CM Integration Reference Point (IRP): Solution Set (SS) definitions".

Configuration Management (CM), in general, provides the operator with the ability to assure correct and effective operation of the 3G network as it evolves. CM actions have the objective to control and monitor the actual configuration on the Network Elements (NEs) and Network Resources (NRs), and they may be initiated by the operator or by functions in the Operations Systems (OSs) or NEs.

CM actions may be requested as part of an implementation programme (e.g. additions and deletions), as part of an optimisation programme (e.g. modifications), and to maintain the overall Quality of Service (QoS). The CM actions are initiated either as single actions on single NEs of the 3G network, or as part of a complex procedure involving actions on many resources/objects in one or several NEs.

1 Scope

The present document describes the Bulk Configuration Management (CM) requirements for managing a 3G network. This is described from the management perspective in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2].

The Itf-N for CM is built up by a number of Integration Reference Points (IRPs) and a related Name Convention 3GPP TS 32.300 [3], which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2]. For CM, a number of IRPs (and a Name Convention) are defined, used by this as well as by other specifications for Telecom Management produced by 3GPP. These IRPs are defined in separate 3GPP specifications, and listed in the table in the Introduction clause above. This document defines the requirements for the Bulk CM IRP.

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
- For a specific reference, subsequent revisions do not apply.
- For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.

- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] 3GPP TS 32.300: "Telecommunication management; Configuration Management (CM); Name convention for Managed Objects".
- [4] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".

3 Definitions and abbreviations

3.1 Definitions

For the purposes of the present document, the following terms and definitions apply.

Data: is any information or set of information required to give software or equipment or combinations thereof a specific state of functionality.

Element Manager (EM): provides a package of end-user functions for management of a set of closely related types of Network Elements (NEs). These functions can be divided into two main categories:

- *Element Management Functions* for management of NEs on an individual basis. These are basically the same functions as supported by the corresponding local terminals.
- *Sub-Network Management Functions* that are related to a network model for a set of NEs constituting a clearly defined sub-network, which may include relations between the NEs. This model enables additional functions on the sub-network level (typically in the areas of network topology presentation, alarm correlation, service impact analysis and circuit provisioning).

Firmware: is a term used in contrast to software to identify the hard-coded program, which is not downloadable on the system.

Hardware: is each and every tangible item.

IRP Information Model: See 3GPP TS 32.101 [1].

IRP Information Service: See 3GPP TS 32.101 [1].

IRP Solution Set: See 3GPP TS 32.101 [1].

Managed Object (MO): an abstract entity, which may be accessed through an open interface between two or more systems, and representing a Network Resource (NR) for the purpose of management. The Managed Object (MO) is an instance of a Managed Object Class (MOC) as defined in a Management Information Model (MIM). The MIM does not define how the MO or NR is implemented; only what can be seen in the interface.

Management Information Base (MIB): the set of existing managed objects in a management domain, together with their attributes, constitutes that management domain's MIB. The MIB may be distributed over several OS/NEs.

Management Information Model (MIM): also referred to as NRM – see the definition below. There is a slight difference between the meaning of MIM and NRM – the term MIM is generic and can be used to denote any type of management model, while NRM denotes the model of the actual managed telecommunications Network Resources (NRs).

Network Element (NE): is a discrete telecommunications entity, which can be, managed over a specific interface e.g. the RNC.

Network Manager (NM): provides a package of end-user functions with the responsibility for the management of a network, mainly as supported by the EM(s) but it may also involve direct access to the NEs. All communication with the network is based on open and well-standardised interfaces supporting management of multi-vendor and multi-technology NEs.

Network Resource (NR): is a component of a NE, which can be identified as a discrete separate entity and is in an object oriented environment for the purpose of management represented by an abstract entity called Managed Object (MO).

Network Resource Model (NRM): a model representing the actual managed telecommunications Network Resources (NRs) that a System is providing through the subject IRP. An NRM describes Managed Object Classes (MOC), their associations, attributes and operations. The NRM is also referred to as "MIM" (see above) which originates from the ITU-T TMN.

Object Management Group (OMG): see <http://www.omg.org>.

Operations System (OS): indicates a generic management system, independent of its location level within the management hierarchy.

Operator: is either

- a human being controlling and managing the network; or
- a company running a network (the 3G network operator).

Optimisation: of the network is each up-date or modification to improve the network handling and/or to enhance subscriber satisfaction. The aim is to maximise the performance of the system.

Re-configuration: is the re-arrangement of the parts, hardware and/or software that make up the 3G network. A re-configuration can be of the parts of a single NE or can be the re-arrangement of the NEs themselves, as the parts of the 3G network. A re-configuration may be triggered by a human operator or by the system itself.

Reversion: is a procedure by which a configuration, which existed before changes were made, is restored.

Software: is a term used in contrast to firmware to refer to all programs which can be loaded to and used in a particular system.

Up-Dates: generally consist of software, firmware, equipment and hardware, designed only to consolidate one or more modifications to counter-act errors. As such, they do not offer new facilities or features and only apply to existing NEs.

Up-Grades: can be of the following types:

- enhancement - the addition of new features or facilities to the 3G network;
- extension - the addition of replicas of existing entities.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CM	Configuration Management
CORBA	Common Object Request Broker Architecture
EM	Element Manager
FM	Fault Management
FW	Firmware
HW	Hardware
IRP	Integration Reference Point
ITU-T	International Telecommunication Union, Telecommunication Standardisation Sector
MIB	Management Information Base
MIM	Management Information Model
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NM	Network Manager
NR	Network Resource
NRM	Network Resource Model
OMG	Object Management Group
OS	Operations System
OSF	Operations System Function
PM	Performance Management
RNC	Radio Network Controller
SW	Software
TM	Telecom Management
TRX	Transceiver
UML	Unified Modelling Language (OMG)
UMTS	Universal Mobile Telecommunications System

4 Bulk CM and Itf-N Interface

4.1 Bulk CM principles

The Itf-N (see ref. 3GPP TS 32.102 [2]) is an object oriented interface, i.e. all resources of the 3G network (functional and physical resources) whose management is standardised by the present document are represented as Managed Object Instances (MOI) of a Network Resource Model (NRM).

The NRM shall be highly simplified for the purpose of the NM, based on the assumption that all of the detailed CM actions are performed by an Element Manager (EM), which knows the vendor-specific NRM and configuration.

There are two types of CM functions - *Passive CM* and *Active CM* (see 3GPP TS 32.600 [4] for definitions).

There are also at least two approaches to CM - *Basic CM* and *Bulk CM*. Refer to 3GPP TS 32.600 [4] for Basic CM.

Bulk CM is characterised by

- Bulk (file-oriented) data retrieval (configuration parameters) over Interface-N from single NEs, a collection of NEs or the whole network. (The passive aspect of Bulk CM.)
- Bulk (file-oriented) data download of configuration parameters to EM/NEs over Interface-N. (An active aspect of Bulk CM.)
- The network-wide activation of those parameters through a single operation. (An active aspect of Bulk CM.)
- The ability to fallback to a previous stable configuration through a single operation. (An active aspect of Bulk CM.)

This document describes the specific functional requirements related to Bulk CM of Network Resources (NRs) on the Itf-N.

4.2 Overview of IRPs related to Bulk CM

The Itf-N for CM is built up by a number of Integration Reference Points (IRPs) and a related Name Convention, which realise the functional capabilities over this interface. The basic structure of the IRPs is defined in 3GPP TS 32.101 [1] and 3GPP TS 32.102 [2]. For CM, a number of IRPs (and a Name Convention) are defined, used by this as well as other specifications For Telecom Management (TM) produced by 3GPP. All these IRPs are defined in separate 3GPP specifications, and listed in the Introduction clause.

4.3 Bulk CM Requirements

Interface-N shall provide efficient mechanisms to upload current CM data from the IRP Agent and download new CM data to the IRP Agent.

It shall be possible to transfer a CM file containing parameters for any specified Network Resource Model (e.g. radio network, Core Network) from the NM to the IRP Agent using a standardised file format and transfer mechanism. The IRP Agent shall also be capable of making the necessary configuration changes in its managed NEs, using the parameters and information contained in the transferred CM file.

The following requirements have been identified regarding the file format and transfer control mechanism over Interface-N.

1. It shall be possible to initiate the upload (IRP Agent to NM) of CM data over Interface-N.
2. It shall be possible to scope the Objects to be uploaded from the IRP Agent, e.g. parameters for a Cell, an RNC, or all the NEs managed by the IRP Agent.
3. It shall be possible to initiate the download (NM to IRP Agent) of CM data over Interface-N.
4. The parameters in the file for downloading to the IRP Agent may relate to creating Managed Objects, deleting Managed Objects or changing some or all modifiable attributes of existing Managed Objects. These parameters may be applicable to some or all the Managed Objects controlled by the IRP Agent, e.g. a Cell, an RNC, or all NEs managed by the IRP Agent.

5. The IRP Agent should check the consistency, syntax and semantic of the downloaded file to ensure that the configuration changes contained in the file can be implemented in the network.
6. It shall be possible to activate a previously downloaded configuration file in the EM/NE via a control facility.
7. Two activation modes may be defined for this IRP, distinguishable by their impact on network services in a live network. In the first activation mode the IRP Agent shall attempt to keep impact on service to a minimum, e.g. by the IRP Agent executing only one command or configuration change at a time in a NE. In the second activation mode all configuration changes contained in the file shall be implemented in the network in the minimum possible time, regardless of impact on service.
8. Activation shall employ a best effort mechanism, i.e. if parts of the activation cannot be successfully completed, the remainder shall still be attempted, where possible. Optionally, other activation strategies may also be supported.
9. The Bulk CM IRP shall specify an optional capability to achieve as near an “all or none” activation strategy as possible. This strategy may be achieved by the use of a pre-activation operation that provides the maximum possible verification that the subsequent activate operation will succeed.
10. The activation of the new configuration in the NEs shall be logged, the objective being to enable an operator (if necessary) to analyse the log (e.g. analyse failed commands) and to subsequently achieve a full activation. Note that “activation” means execution of each command in the downloaded file, and the result of each command execution shall be logged, whether successful or unsuccessful.
11. It shall be possible to selectively retrieve the information contained in the log, e.g. only unsuccessful operations.
12. It shall be possible to check the status of a configuration file operation.
13. It shall be possible for the IRP Agent to fallback to a previously known working configuration, initiated by the IRP Manager.
14. Interface-N shall support notifications, e.g. to indicate completion of an operation, error cases.
15. The file format shall be flexible enough to include all possible CM parameter types, i.e. standard parameters as well as vendor specific parameters. The meaning, syntax, units, etc. of standard parameters shall be specified. The representation of vendor specific parameters will be proprietary. A uniform mechanism for handling vendor specific parameters shall be specified.
16. Since the files are transferred via a machine-machine interface, the file format shall be machine readable using industry standard tools, e.g. XML parser.
17. Moreover, the files shall be formatted in a human readable way, i.e. to allow manual editing of its contents by the IRPManager before downloading.
18. The file format shall be specified by using a standardised language, e.g. the Extensible Mark-up Language (XML), in order to provide the possibility of visualisation in a web browser.
19. The same file format shall be used for the upload and download to the IRP Agent.
20. The file format shall be independent of the data transfer protocol used to carry the file from one system to another.
21. The file transfer facility shall be implemented using a commonly available protocol, e.g. FTP.
22. The Managed Object Class identifiers used in the file shall be the same as those used for Basic CM, Fault Management and Performance Management.
23. Bulk CM IRP shall be sufficient to configure a complete radio network, including vendor specific parameters of the UTRAN.
24. For security considerations, notifications should be generated by the IRP Agent whenever download, activate or fallback operations are initiated during a Bulk CM session. These notifications shall be available to any IRPManager that has subscribed to Bulk CM IRP notifications and shall include the session id, the identity of the IRPManager invoking the operation, and the type of operation.

25. For security considerations, the IRPAgent shall ensure that only the IRPManager that started a Bulk CM session is subsequently allowed to send commands related to that session. This check shall be made for each command issued during the session. If the IRPManager is not the same, the command shall not be performed and the session state shall not be changed, and a security alarm issued.
26. For security considerations, if the IRPAgent has the information that a downloaded file has been changed during a session before pre-activation or activation, the pre-activation or activation command shall not be performed and the session state shall not be changed and a security alarm shall be issued.
27. For security considerations, the IRPAgent should maintain a log of sessions, i.e. identity of IRPManager initiating a session, session start and end times, Bulk CM operations (e.g. activate, fallback) performed during a session including their start and end times. This requirement may be partially satisfied by Notification Log IRP.

Annex A (informative): Change history

Change history							
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New
Jun 2001	S_12	SP-010283	--	--	Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0
Jun 2002	S_16	SP-020295	001	--	Adding Bulk CM IRP requirements for Rel-5	4.0.0	5.0.0
Sep 2002	S_17	SP-020486	002	--	Additional Bulk CM IRP requirements for Rel-5	5.0.0	5.1.0
Mar 2004	S_23	SP-040105	--	--	Automatic upgrade to Rel-6 (no CR)	5.1.0	6.0.0
Sep 2004	S_25	SP-040571	003	--	Enhancements to Bulk CM IRP for Security	6.0.0	6.1.0
Dec 2004	--	--	--	--	Word XP "Open and Repair" & added the TS-family to Introduction. Reference updates. Editorial cosmetics	6.1.0	6.1.1
Jun 2007	SA_36	--	--	--	Automatic upgrade to Rel-7 (no CR) at freeze of Rel-7. Deleted reference to CMIP SS, discontinued from R7 onwards.	6.1.1	7.0.0
Mar 2009	SA_43	SP-090207	004	--	Include reference to SOAP Solution Set specification	7.0.0	8.0.0
2009-12	-	-	-	-	Update to Rel-9 version (MCC)	8.0.0	9.0.0
2011-03	-	-	-	-	Update to Rel-10 version (MCC)	9.0.0	10.0.0
2012-09	-	-	-	-	Update to Rel-11 version (MCC)	10.0.0	11.0.0
2014-10	-	-	-	-	Update to Rel-12 version (MCC)	11.0.0	12.0.0
2016-01	-	-	-	-	Update to Rel-13 version (MCC)	12.0.0	13.0.0
2017-04	SA#75	-	-	-	Promotion to Release 14 without technical change	13.0.0	14.0.0
2018-06	-	-	-	-	Update to Rel-15 version (MCC)	14.0.0	15.0.0
2020-07	-	-	-	-	Update to Rel-16 version (MCC)	15.0.0	16.0.0
2022-04	-	-	-	-	Update to Rel-17 version (MCC)	16.0.0	17.0.0
2024-04	-	-	-	-	Update to Rel-18 version (MCC)	17.0.0	18.0.0
2025-09	SA#109	-	-	-	Update to Rel-19 version (MCC)	18.0.0	19.0.0

History

Document history		
V19.0.0	October 2025	Publication