

ETSI TS 132 634 V5.4.0 (2005-03)

Technical Specification

**Digital cellular telecommunications system (Phase 2+);
Universal Mobile Telecommunications System (UMTS);
Telecommunication management;
Configuration Management (CM);
Core network resources Integration Reference Point (IRP);
Common Management Information Protocol (CMIP)
Solution Set (SS)
(3GPP TS 32.634 version 5.4.0 Release 5)**



Reference

RTS/TSGS-0532634v540

Keywords

GSM, UMTS

ETSI

650 Route des Lucioles
F-06921 Sophia Antipolis Cedex - FRANCE

Tel.: +33 4 92 94 42 00 Fax: +33 4 93 65 47 16

Siret N° 348 623 562 00017 - NAF 742 C
Association à but non lucratif enregistrée à la
Sous-Préfecture de Grasse (06) N° 7803/88

Important notice

Individual copies of the present document can be downloaded from:
<http://www.etsi.org>

The present document may be made available in more than one electronic version or in print. In any case of existing or perceived difference in contents between such versions, the reference version is the Portable Document Format (PDF). In case of dispute, the reference shall be the printing on ETSI printers of the PDF version kept on a specific network drive within ETSI Secretariat.

Users of the present document should be aware that the document may be subject to revision or change of status.
Information on the current status of this and other ETSI documents is available at
<http://portal.etsi.org/tb/status/status.asp>

If you find errors in the present document, please send your comment to one of the following services:
http://portal.etsi.org/chaircor/ETSI_support.asp

Copyright Notification

No part may be reproduced except as authorized by written permission.
The copyright and the foregoing restriction extend to reproduction in all media.

© European Telecommunications Standards Institute 2005.
All rights reserved.

DECT™, PLUGTESTS™ and UMTS™ are Trade Marks of ETSI registered for the benefit of its Members.
TIPHON™ and the **TIPHON logo** are Trade Marks currently being registered by ETSI for the benefit of its Members.
3GPP™ is a Trade Mark of ETSI registered for the benefit of its Members and of the 3GPP Organizational Partners.

Intellectual Property Rights

IPRs essential or potentially essential to the present document may have been declared to ETSI. The information pertaining to these essential IPRs, if any, is publicly available for **ETSI members and non-members**, and can be found in ETSI SR 000 314: "*Intellectual Property Rights (IPRs); Essential, or potentially Essential, IPRs notified to ETSI in respect of ETSI standards*", which is available from the ETSI Secretariat. Latest updates are available on the ETSI Web server (<http://webapp.etsi.org/IPR/home.asp>).

Pursuant to the ETSI IPR Policy, no investigation, including IPR searches, has been carried out by ETSI. No guarantee can be given as to the existence of other IPRs not referenced in ETSI SR 000 314 (or the updates on the ETSI Web server) which are, or may be, or may become, essential to the present document.

Foreword

This Technical Specification (TS) has been produced by ETSI 3rd Generation Partnership Project (3GPP).

The present document may refer to technical specifications or reports using their 3GPP identities, UMTS identities or GSM identities. These should be interpreted as being references to the corresponding ETSI deliverables.

The cross reference between GSM, UMTS, 3GPP and ETSI identities can be found under
<http://webapp.etsi.org/key/queryform.asp>.

Contents

Intellectual Property Rights	2
Foreword.....	2
Foreword.....	7
Introduction	7
1 Scope	8
2 References	8
3 Definitions, symbols and abbreviations	9
3.1 Definitions.....	9
3.2 Abbreviations	9
4 Basic aspects	9
4.1 Architectural Aspects	9
4.2 Mapping	9
4.2.1 Mapping of Information Object Classes	9
4.2.2 Mapping of Information Object Class Attributes.....	10
4.2.2.1 Attribute Mapping of the IOC <i>MscServerFunction</i>	10
4.2.2.2 Attribute Mapping of the IOC <i>HlrFunction</i>	11
4.2.2.3 Attribute Mapping of the IOC <i>VlrFunction</i>	11
4.2.2.4 Attribute Mapping of the IOC <i>AucFunction</i>	11
4.2.2.5 Attribute Mapping of the IOC <i>EirFunction</i>	11
4.2.2.6 Attribute Mapping of the IOC <i>SmsIwmscFunction</i>	11
4.2.2.7 Attribute Mapping of the IOC <i>SmsGmscFunction</i>	12
4.2.2.8 Attribute Mapping of the IOC <i>SgsnFunction</i>	12
4.2.2.9 Attribute Mapping of the IOC <i>GgsnFunction</i>	12
4.2.2.10 Attribute Mapping of the IOC <i>BgFunction</i>	12
4.2.2.11 Attribute Mapping of the IOC <i>GmscFunction</i>	12
4.2.2.12 Attribute Mapping of the IOC <i>SmlcFunction</i>	13
4.2.2.13 Attribute Mapping of the IOC <i>GmlcFunction</i>	13
4.2.2.14 Attribute Mapping of the IOC <i>ScfFunction</i>	13
4.2.2.15 Attribute Mapping of the IOC <i>SrfFunction</i>	13
4.2.2.16 Attribute Mapping of the IOC <i>CbcFunction</i>	13
4.2.2.17 Attribute Mapping of the IOC <i>CgfFunction</i>	14
4.2.2.18 Attribute Mapping of the IOC <i>ImsMgwFunction</i>	14
4.2.2.19 Attribute Mapping of the IOC <i>GmscServerFunction</i>	14
4.2.2.20 Attribute Mapping of the IOC <i>IwfFunction</i>	14
4.2.2.21 Attribute Mapping of the IOC <i>MnpSrfFunction</i>	14
4.2.2.22 Attribute Mapping of the IOC <i>NpdbFunction</i>	15
4.2.2.23 Attribute Mapping of the IOC <i>SgwFunction</i>	15
4.2.2.24 Attribute Mapping of the IOC <i>SsfFunction</i>	15
4.2.2.25 Attribute Mapping of the IOC <i>BsFunction</i>	15
4.2.2.26 Attribute Mapping of the IOC <i>IucsLink</i>	15
4.2.2.27 Attribute Mapping of the IOC <i>IupsLink</i>	16
4.2.2.28 Attribute Mapping of the IOC <i>IubcLink</i>	16
4.2.2.29 Attribute Mapping of the IOC <i>ALink</i>	16
4.2.2.30 Attribute Mapping of the IOC <i>GbLink</i>	16
4.2.2.31 Attribute Mapping of the IOC <i>CsMgwFunction</i>	16
4.2.3 Mapping of Name Containments	17
5 GDMO Definitions.....	18
5.1 Information Object Classes (IOCs)	18
5.1.1 smlcFunction.....	18
5.1.2 gmlcFunction	18
5.1.3 scfFunction	18
5.1.4 srfFunction.....	18

5.1.5	cbcFunction.....	19
5.1.6	cgfFunction	19
5.1.7	imsMgwFunction.....	19
5.1.8	gmscFunction.....	19
5.1.9	iwfFunction.....	20
5.1.10	mnpSrfFunction	20
5.1.11	npdbFunction	20
5.1.12	rSgwFunction.....	21
5.1.13	ssfFunction.....	21
5.1.14	bsFunction.....	21
5.1.15	aucFunction.....	21
5.1.16	bgFunction	22
5.1.17	eirFunction.....	22
5.1.18	ggsnFunction.....	22
5.1.19	hlrFunction.....	22
5.1.20	mscServerFunction	23
5.1.21	sgsnFunction.....	23
5.1.22	smsGmscFunction.....	23
5.1.23	smsIwmscFunction	23
5.1.24	vlrFunction.....	24
5.1.25	gbLink.....	24
5.1.26	aLink.....	24
5.1.27	iucsLink	24
5.1.28	iupsLink	25
5.1.29	iubcLink.....	25
5.1.30	csMgwFunction	25
5.1.31	GmscServerFunction	26
5.2	Packages	26
5.2.1	smlcFunctionBasicPackage	26
5.2.2	gmlcFunctionBasicPackage	26
5.2.3	scfFunctionBasicPackage	26
5.2.4	srfFunctionBasicPackage.....	26
5.2.5	cbcFunctionBasicPackage	27
5.2.6	cgfFunctionBasicPackage	27
5.2.7	imsMgwFunctionBasicPackage.....	27
5.2.8	gmscFunctionBasicPackage.....	27
5.2.9	iwfFunctionBasicPackage	27
5.2.10	mnpSrfFunctionBasicPackage	28
5.2.11	npdbFunctionBasicPackage	28
5.2.12	rSgwFunctionBasicPackage	28
5.2.13	ssfFunctionBasicPackage.....	28
5.2.14	bsFunctionBasicPackage	28
5.2.15	aucFunctionBasicPackage	29
5.2.16	bgFunctionBasicPackage	29
5.2.17	eirFunctionBasicPackage	29
5.2.18	ggsnFunctionBasicPackage	29
5.2.19	hlrFunctionBasicPackage	29
5.2.20	mscServerFunctionBasicPackage	30
5.2.21	mscServerFunctionAssociationPackage	30
5.2.22	sgsnFunctionBasicPackage	30
5.2.23	sgsnFunctionAssociationPackage	30
5.2.24	smsGmscFunctionBasicPackage.....	31
5.2.25	smsIwmscFunctionBasicPackage	31
5.2.26	vlrFunctionBasicPackage.....	31
5.2.27	gbLinkBasicPackage.....	31
5.2.28	gbLinkAssociationPackage	31
5.2.29	aLinkBasicPackage	32
5.2.30	aLinkAssociationPackage	32
5.2.31	iucsLinkBasicPackage	32
5.2.32	iucsLinkAssociationPackage	32
5.2.33	iupsLinkBasicPackage	32
5.2.34	iupsLinkAssociationPackage	33

5.2.35	iubcLinkBasicPackage.....	33
5.2.36	iubcLinkAssociationPackage.....	33
5.2.37	csMgwFunctionBasicPackage	33
5.2.38	csMgwFunctionAssociationPackage	33
5.2.39	gmscServerFunctionBasicPackage	34
5.3	Attributes	34
5.3.1	smlcFunctionId	34
5.3.2	gmlcFunctionId	34
5.3.3	scfFunctionId	34
5.3.4	srfFunctionId	35
5.3.5	cbcFunctionId	35
5.3.6	cgfFunctionId.....	35
5.3.7	imsMgwFunctionId.....	35
5.3.8	gmscFunctionId	35
5.3.9	iwfFunctionId	36
5.3.10	mnpSrfFunctionId	36
5.3.11	npdbFunctionId.....	36
5.3.12	rSgwFunctionId	36
5.3.13	ssfFunctionId	36
5.3.14	bsFunctionId	37
5.3.15	aucFunctionId	37
5.3.16	bgFunctionId	37
5.3.17	eirFunctionId	37
5.3.18	ggsnFunctionId	37
5.3.19	hlrFunctionId	38
5.3.20	mscServerFunctionId	38
5.3.21	vlrFunctionId	38
5.3.22	sgsnFunctionId.....	38
5.3.23	smsGmscFunctionId	39
5.3.24	smsIwmscFunctionId	39
5.3.25	gbLinkId	39
5.3.26	aLinkId.....	39
5.3.27	iucsLinkId	39
5.3.28	iupsLinkId	40
5.3.29	iubcLinkId.....	40
5.3.30	csMgwFunctionId	40
5.3.31	gmscServerFunctionId	40
5.3.32	mccList	40
5.3.33	mncList	41
5.3.34	lacList	41
5.3.35	sacList	41
5.3.36	uraList	41
5.3.37	gcaList	41
5.3.38	mscId	42
5.3.39	mscServerFunction-GSMcell.....	42
5.3.40	mscServerFunction-ExternalGSMcell	42
5.3.41	mscServerFunction-CsMgwFunction	42
5.3.42	racList	42
5.3.43	sgsnId	43
5.3.44	sgsnFunction-GSMcell	43
5.3.45	sgsnFunction-ExternalGSMcell	43
5.3.46	connectedBss	43
5.3.47	connectedRnc	44
5.3.48	csMgwFunction-MscServerFunction	44
5.3.49	csMgwFunction-IucsLink	44
5.3.50	csMgwFunction-Alink	44
5.4	Name Binding	45
5.4.1	smlcFunction - managedElement	45
5.4.2	gmlcFunction - managedElement	45
5.4.3	scfFunction - managedElement.....	45
5.4.4	srfFunction - managedElement	46
5.4.5	cbcFunction - managedElement.....	46

5.4.6	cgfFunction - managedElement	46
5.4.7	imsMgwFunction - managedElement	46
5.4.8	gmscFunction - managedElement	47
5.4.9	iwfFunction - managedElement	47
5.4.10	mnpSrfFunction - managedElement	47
5.4.11	npdbFunction - managedElement	48
5.4.12	rSgwFunction - managedElement	48
5.4.13	ssfFunction - managedElement	48
5.4.14	bsFunction - managedElement	49
5.4.15	aucFunction - managedElement	49
5.4.16	bgFunction - managedElement	49
5.4.17	eirFunction - managedElement	50
5.4.18	ggsnFunction - managedElement	50
5.4.19	hlrFunction - managedElement	50
5.4.20	mscServerFunction - managedElement	51
5.4.21	vlrFunction - managedElement	51
5.4.22	sgsnFunction - managedElement	51
5.4.23	smsGmscFunction - managedElement	51
5.4.24	smsIwmscFunction - managedElement	52
5.4.25	gbLink - managedElement	52
5.4.26	aLink - managedElement	52
5.4.27	iucsLink - managedElement	53
5.4.28	iupsLink - managedElement	53
5.4.29	iubcLink - managedElement	53
5.4.30	gmscServerFunction - managedElement	54
5.4.31	csMgwFunction - managedElement	54
6	ASN.1 Definitions	54
Annex A (informative):	List of assigned Object Identifiers	56
Annex B (informative):	Change history	61
History	62	

Foreword

This Technical Specification has been produced by the 3rd Generation Partnership Project (3GPP).

The contents of the present document are subject to continuing work within the TSG and may change following formal TSG approval. Should the TSG modify the contents of the present document, it will be re-released by the TSG with an identifying change of release date and an increase in version number as follows:

Version x.y.z

where:

- x the first digit:
 - 1 presented to TSG for information;
 - 2 presented to TSG for approval;
 - 3 or greater indicates TSG approved document under change control.
- y the second digit is incremented for all changes of substance, i.e. technical enhancements, corrections, updates, etc.
- z the third digit is incremented when editorial only changes have been incorporated in the document.

Introduction

The present document is part of the 32.63x-series covering the 3rd Generation Partnership Project Technical Specification Group Services and System Aspects, Telecommunication management; Configuration Management (CM); as identified below:

- 32.631: "Core network resources Integration Reference Point (IRP): Requirements";
- 32.632: "Core network resources Integration Reference Point (IRP): Network Resource Model (NRM)";
- 32.633: "Core network resources Integration Reference Point (IRP): Common Object Request Broker Architecture (CORBA) Solution Set (SS)";
- 32.634: "Core network resources Integration Reference Point (IRP): Common Management Information Protocol (CMIP) Solution Set (SS)".**
- 32.635: "Core network resources Integration Reference Point (IRP): Bulk CM eXtensible Markup Language (XML) file format definition".

A 3G network is composed of a multitude of different network elements (NE). For a successful operation of the network the operator must be provided with mechanisms allowing him to manage the network. These management activities can be grouped into several areas: configuration management, fault management, performance management, and accounting management and security management.

The present document is part of a set of technical specifications defining the telecommunication management (TM) of 3G systems. The TM principles are described in 3GPP TS 32.101 [1]. The TM architecture is described in 3GPP TS 32.102 [2]. The other specifications define the interface (Itf-N) between the managing system (manager), which is in general the network manager (NM) and the managed system (agent), which is either an element manager (EM) or the managed NE itself. The Itf-N is composed of a number of integration reference points (IRPs) defining the information in the agent that is visible for the manager, the operations that the manager may perform on this information and the notifications that are sent from the agent to the manager. One of these IRPs is the Core Network Resources IRP.

Each IRP is specified by five TS: Requirements, IS, CORBA SS, CMIP SS and the XML file format definition.

1 Scope

The present document specifies the Common Management Information Protocol (CMIP) Solution Set (SS) for the CN Network Resource Integration Reference Point (IRP): Network Resource Model defined in 3GPP TS 32.632 [4]. In detail:

- Clause 4 contains an introduction to some concepts that are the base for some specific aspects of the CMIP interfaces.
- Clause 5 contains the GDMO definitions for the Alarm Management over the CMIP interfaces
- Clause 6 contains the ASN.1 definitions supporting the GDMO definitions provided in clause 5.

This Solution Set specification is related to 3GPP TS 32.632 V5.7.X [4].

2 References

The following documents contain provisions which, through reference in this text, constitute provisions of the present document.

- References are either specific (identified by date of publication, edition number, version number, etc.) or non-specific.
 - For a specific reference, subsequent revisions do not apply.
 - For a non-specific reference, the latest version applies. In the case of a reference to a 3GPP document (including a GSM document), a non-specific reference implicitly refers to the latest version of that document *in the same Release as the present document*.
- [1] 3GPP TS 32.101: "Telecommunication management; Principles and high level requirements".
- [2] 3GPP TS 32.102: "Telecommunication management; Architecture".
- [3] Void.
- [4] 3GPP TS 32.632: "Telecommunication management; Configuration Management (CM); Core Network Resources Integration Reference Point (IRP): Network Resource Model (NRM)".
- [5] ITU-T Recommendation X.710 (1991): "Common Management Information Service Definition for CCITT Applications".
- [6] ITU-T Recommendation X.721 (02/92): "Information Technology - Open Systems Interconnection – Structure of Management Information: Definition of Management Information".
- [7] ITU-T Recommendation X.730 (01/92): "Information Technology - Open Systems Interconnection – Systems Management: Object Management Function".
- [8] ITU-T Recommendation X.733 (02/92): "Information Technology - Open Systems Interconnection - Alarm Reporting Function".
- [9] ITU-T Recommendation M.3100 (07/95): "Maintenance Telecommunications Management Network – Generic Network Information Model".
- [10] 3GPP TS 32.600: "Telecommunication management; Configuration Management (CM); Concept and high-level requirements".

3 Definitions, symbols and abbreviations

3.1 Definitions

For the purposes of the present document, the terms and definitions given in 3GPP TS 32.600 [10] and 3GPP TS 32.632 [4] apply.

3.2 Abbreviations

For the purposes of the present document, the following abbreviations apply:

CMIP	Common Management Information Protocol
DN	Distinguished Name
GDMO	Guidelines for the Definition of Managed Objects
IDL	Interface Definition Language
IEC	International Electrotechnical Commission
IOC	Information Object Class
ISO	International Standards Organization
ITU-T	International Telecommunication Union, Telecommunication Sector
MGW	Media GateWay
MIB	Management Information Base
MIM	Management Information Model
MIT	Management Information Tree (or Naming Tree)
MOC	Managed Object Class
MOI	Managed Object Instance
NE	Network Element
NR	Network Resource
NRM	Network Resource Model
TMN	Telecommunications Management Network
UTRAN	UMTS Terrestrial Radio Access Network

4 Basic aspects

4.1 Architectural Aspects

A technology independent CN network resource model is defined in 3GPP TS 32.632 [4] for 3G networks. This document provides an implementation of this CN network resource model by using CMIP technology.

4.2 Mapping

The semantic of the CN Network Resource Model is defined in 3GPP TS 32.632 [4]. The specification of the information object classes defined there is independent of any implementation technology and protocol. This clause maps these technology and protocol independent definitions onto the equivalencies of the CMIP Solution Set of the UTRAN Network Resource IRP.

4.2.1 Mapping of Information Object Classes

Table 4.1 maps the Information Object Classes (IOCs) defined in the CN Network Resource Model onto the equivalent IOCs of the CMIP Solution Set.

Table 4.1: Mapping of IOCs

IS IOC	CMIP SS MOC
AucFunction	aucFunction
ALink	aLink
IucsLink	iucsLink
IupsLink	iupsLink
IubcLink	iubcLink
BgFunction	bgFunction
EirFunction	eirFunction
GbLink	gbLink
GgsnFunction	ggsnFunction
GmscFunction	gmscFunction
HlrFunction	hlrFunction
MscServerFunction	mscServerFunction
GmscServerFunction	gmscServerFunction
SgsnFunction	sgsnFunction
SmsGmscFunction	smsGmscFunction
SmsIwmscFunction	smsIwmscFunction
VlrFunction	vlrFunction
SmlcFunction	smlcFunction
GmlcFunction	gmlcFunction
ScfFunction	scfFunction
SrfFunction	srfFunction
CbcFunction	cbcFunction
CqfFunction	cqfFunction
CsMgwFunction	csMgwFunction
ImsMgwFunction	ImsMgwFunction
GmscFunction	gmscFunction
IwfFunction	iwfFunction
MnpSrfFunction	mnpSrfFunction
NpdbFunction	npdbFunction
RSgwFunction	rSgwFunction
SsfFunction	ssfFunction
BsFunction	bsFunction

4.2.2 Mapping of Information Object Class Attributes

4.2.2.1 Attribute Mapping of the IOC *MscServerFunction*

Attribute mapping of the IOC *MscServerFunction*

IS Attribute	CMIP SS Attributes	Support Qualifier	Read Qualifier	Write Qualifier
mscServerFunctionId	mscServerFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
mccList	mccList	M	M	M
mncList	mncList	M	M	M
lacList	lacList	M	M	M
sacList	sacList	M	M	M
gcaList	gcaList	M	M	M
mscld	mscld	M	M	M
mscServerFunction-GsmCell	mscServerFunction-GSMcell	M	M	--
mscServerFunction-ExternalGsmCell	mscServerFunction-ExternalGSMcell	M	M	--
mscServerFunction-CsMgwFunction	mscServerFunction-CsMgwFunction	M	M	--

4.2.2.2 Attribute Mapping of the IOC *HlrFunction*

Attribute mapping of the IOC *HlrFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
hlrFunctionId	hlrFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.3 Attribute Mapping of the IOC *VlrFunction*

Attribute mapping of the IOC *VlrFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
vlrFunctionId	vlrFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.4 Attribute Mapping of the IOC *AucFunction*

Attribute mapping of the IOC *AucFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
aucFunctionId	aucFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.5 Attribute Mapping of the IOC *EirFunction*

Attribute mapping of the IOC *EirFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
eirFunctionId	eirFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.6 Attribute Mapping of the IOC *SmsIwmscFunction*

Attribute mapping of the IOC *SmsIwmscFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
smsIwmscFunctionId	smsIwmscFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.7 Attribute Mapping of the IOC *SmsGmscFunction*

Attribute mapping of the IOC *SmsGmscFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
smsGmscFunctionId	smsGmscFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.8 Attribute Mapping of the IOC *SgsnFunction*

Attribute mapping of the IOC *SgsnFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
sgsnFunctionId	sgsnFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
mccList	mccList	M	M	M
mncList	mncList	M	M	M
lacList	lacList	M	M	M
racList	racList	M	M	M
sacList	sacList	M	M	M
sgsnId	sgsnId	M	M	M
sgsnFunction-GsmCell	sgsnFunction-GSMCell	M	M	--
sgsnFunction-ExternalGsmCell	sgsnFunction-ExternalGSMCell	M	M	--

4.2.2.9 Attribute Mapping of the IOC *GgsnFunction*

Attribute mapping of the IOC *GgsnFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
ggsnFunctionId	ggsnFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.10 Attribute Mapping of the IOC *BgFunction*

Attribute mapping of the IOC *BgFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
bgFunctionId	bgFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.11 Attribute Mapping of the IOC *GmscFunction*

Attribute mapping of the IOC *GmscFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
gmScFunctionId	gmScFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.12 Attribute Mapping of the IOC *SmlcFunction*

Attribute mapping of the IOC *SmlcFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
smlcFunctionId	smlcFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.13 Attribute Mapping of the IOC *GmlcFunction*

Attribute mapping of the IOC *GmlcFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
gmlcFunctionId	gmlcFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.14 Attribute Mapping of the IOC *ScfFunction*

Attribute mapping of the IOC *ScfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
scfFunctionId	scfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.15 Attribute Mapping of the IOC *SrfFunction*

Attribute mapping of the IOC *SrfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
srfFunctionId	srfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.16 Attribute Mapping of the IOC *CbcFunction*

Attribute mapping of the IOC *CbcFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
cbcFunctionId	cbcFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.17 Attribute Mapping of the IOC *CgfFunction*

Attribute mapping of the IOC *CgfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
cfgFunctionId	cfgFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.18 Attribute Mapping of the IOC *ImsMgwFunction*

Attribute mapping of the IOC *ImsMgwFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
imsMgwFunctionId	imsMgwFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.19 Attribute Mapping of the IOC *GmscServerFunction*

Attribute mapping of the IOC *GmscServerFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
gmscServerFunctionId	gmscServerFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.20 Attribute Mapping of the IOC *IwfFunction*

Attribute mapping of the IOC *IwfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
iwfFunctionId	iwfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.21 Attribute Mapping of the IOC *MnpSrfFunction*

Attribute mapping of the IOC *MnpSrfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
mnpSrfFunctionId	mnpSrfFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.22 Attribute Mapping of the IOC *NpdbFunction*

Attribute mapping of the IOC *NpdbFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
npdbFunctionId	npdbFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.23 Attribute Mapping of the IOC *SgwFunction*

Attribute mapping of the IOC *SgwFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
sgwFunctionId	sgwFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.24 Attribute Mapping of the IOC *SsfFunction*

Attribute mapping of the IOC *SsfFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
ssfFunctionId	ssfFunctionId	M	M	--
userLabel	UserLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.25 Attribute Mapping of the IOC *BsFunction*

Attribute mapping of the IOC *BsFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
bsFunctionId	bsFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M

4.2.2.26 Attribute Mapping of the IOC *IucsLink*

Attribute mapping of the IOC *IucsLink*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
iucsLinkId	iucsLinkId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
connectedRnc	connectedRnc	M	M	--
connectedBss	connectedBss	M	M	--

4.2.2.27 Attribute Mapping of the IOC *iupsLink*

Attribute mapping of the IOC *iupsLink*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
iupsLinkId	iupsLinkId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
connectedRnc	connectedRnc	O	M	--
connectedBss	connectedBss	O	M	--

4.2.2.28 Attribute Mapping of the IOC *iubcLink*

Attribute mapping of the IOC *iubcLink*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
iubcLinkId	iubcLinkId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
connectedRnc	connectedRnc	M	M	--

4.2.2.29 Attribute Mapping of the IOC *ALink*

Attribute mapping of the IOC *ALink*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
aLinkId	aLinkId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
connectedBss	connectedBss	M	M	--

4.2.2.30 Attribute Mapping of the IOC *GbLink*

Attribute mapping of the IOC *GbLink*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
gbLinkId	gbLinkId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
connectedBss	connectedBss	M	M	--

4.2.2.31 Attribute Mapping of the IOC *CsMgwFunction*

Attribute mapping of the IOC *CsMgwFunction*

IS Attribute	CMIP SS Attribute	Support Qualifier	Read Qualifier	Write Qualifier
csMgwFunctionId	CsmgwFunctionId	M	M	--
userLabel	userLabel (ITU-T Rec. M.3100 [9])	M	M	M
csMgwFunction-MscServerFunction	csMgwFunction-mscServerFunction	M	M	--
csMgwFunction-lucsLink	csMgwFunction-iucsLink	M	M	--
csMgwFunction-ALink	csMgwFunction-ALink	M	M	--

4.2.3 Mapping of Name Containments

Mapping of name containments

IS Name Containment	CMIP SS Name Binding
smlcFunction - managedElement	smlcFunction-managedElement
gmlcFunction - managedElement	gmlcFunction-managedElement
scfFunction - managedElement	scfFunction-managedElement
srfFunction - managedElement	srfFunction-managedElement
cbcFunction - managedElement	cbcFunction-managedElement
cbcFunction - managedElement	cbcFunction-managedElement
cfgFunction - managedElement	cfgFunction-managedElement
imsMgwFunction - managedElement	imsMgwFunction-managedElement
gmscFunction - managedElement	gmscFunction-managedElement
iwfFunction - managedElement	iwfFunction-managedElement
mnpSrfFunction - managedElement	mnpSrfFunction-managedElement
npdbFunction - managedElement	npdbFunction-managedElement
rSgwFunction - managedElement	rSgwFunction-managedElement
ssfFunction - managedElement	ssfFunction-managedElement
bsFunction - managedElement	bsFunction-managedElement
bsFunction - managedElement	bsFunction-managedElement
bsFunction - managedElement	bsFunction-managedElement
aucFunction - managedElement	aucFunction-managedElement
bgFunction - managedElement	bgFunction-managedElement
eirFunction - managedElement	eirFunction-managedElement
ggsnFunction - managedElement	ggsnFunction-managedElement
hlrFunction - managedElement	hlrFunction-managedElement
mscServerFunction - managedElement	mscServerFunction-managedElement
vlrFunction - managedElement	vlrFunction-managedElement
sgsnFunction - managedElement	sgsnFunction-managedElement
smsGmscFunction - managedElement	smsGmscFunction-managedElement
smsGmscFunction - managedElement	smsGmscFunction-managedElement
smsIwmSCFunction - managedElement	smsIwmSCFunction-managedElement
gbLink - managedElement	gbLink-managedElement
aLink - managedElement	aLink-managedElement
iucsLink - managedElement	iucsLink-managedElement
iupsLink - managedElement	iupsLink-managedElement
iubcLink - managedElement	iubcLink-managedElement
gmscServerFunction - managedElement	gmscServerFunction-managedElement
csMgwFunction - managedElement	csMgwFunction-managedElement

5 GDMO Definitions

5.1 Information Object Classes (IOCs)

5.1.1 smlcFunction

```
smlcFunction MANAGED OBJECT CLASS
DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
    smlcFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
        "the objectCreation and the objectDeletion notifications defined in
         ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
        "the attributeValueChange notification defined in ITU-T Rec. X.721
         is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 1};
```

5.1.2 gmlcFunction

```
gmlcFunction MANAGED OBJECT CLASS
DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
    gmlcFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
        "the objectCreation and the objectDeletion notifications defined in
         ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
        "the attributeValueChange notification defined in ITU-T Rec. X.721
         is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 2};
```

5.1.3 scfFunction

```
scfFunction MANAGED OBJECT CLASS
DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
    scfFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
        "the objectCreation and the objectDeletion notifications defined in
         ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
        "the attributeValueChange notification defined in ITU-T Rec. X.721
         is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 3};
```

5.1.4 srfFunction

```
srfFunction MANAGED OBJECT CLASS
DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
```

```

srfFunctionBasicPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 4};

```

5.1.5 cbcFunction

```

cbcFunction MANAGED OBJECT CLASS
DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
cbcFunctionBasicPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 5};

```

5.1.6 cfgFunction

```

cfgFunction MANAGED OBJECT CLASS
DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
cfgFunctionBasicPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 6};

```

5.1.7 imsMgwFunction

```

imsMgwFunction MANAGED OBJECT CLASS
DERIVED FROM
"3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
imsMgwFunctionBasicPackage,
"3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
"the objectCreation and the objectDeletion notifications defined in
ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
"the attributeValueChange notification defined in ITU-T Rec. X.721
is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 70503};

```

5.1.8 gmscFunction

```

gmscFunction MANAGED OBJECT CLASS

```

```

DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  gmscFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
       ITU-T Rec. X.721 are supported by an instance of this class." ,
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
       is supported by an instance of this class." ;
REGISTERED AS {ts32-634ObjectClass 8};

```

5.1.9 iwfFunction

```

iwfFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  iwfFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
       ITU-T Rec. X.721 are supported by an instance of this class." ,
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
       is supported by an instance of this class." ;
REGISTERED AS {ts32-634ObjectClass 9};

```

5.1.10 mnpSrfFunction

```

mnpSrfFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  mnpSrfFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
       ITU-T Rec. X.721 are supported by an instance of this class." ,
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
       is supported by an instance of this class." ;
REGISTERED AS {ts32-634ObjectClass 10};

```

5.1.11 npdbFunction

```

npdbFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  npdbFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
    PRESENT IF
      "the objectCreation and the objectDeletion notifications defined in
       ITU-T Rec. X.721 are supported by an instance of this class." ,
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
    PRESENT IF
      "the attributeValueChange notification defined in ITU-T Rec. X.721
       is supported by an instance of this class." ;
REGISTERED AS {ts32-634ObjectClass 11};

```

5.1.12 rSgwFunction

```
rSgwFunction MANAGED OBJECT CLASS
DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
    rSgwFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
        PRESENT IF
            "the objectCreation and the objectDeletion notifications defined in
             ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
        PRESENT IF
            "the attributeValueChange notification defined in ITU-T Rec. X.721
             is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 12};
```

5.1.13 ssfFunction

```
ssfFunction MANAGED OBJECT CLASS
DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
    ssfFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
        PRESENT IF
            "the objectCreation and the objectDeletion notifications defined in
             ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
        PRESENT IF
            "the attributeValueChange notification defined in ITU-T Rec. X.721
             is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 13};
```

5.1.14 bsFunction

```
bsFunction MANAGED OBJECT CLASS
DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
    bsFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
        PRESENT IF
            "the objectCreation and the objectDeletion notifications defined in
             ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
        PRESENT IF
            "the attributeValueChange notification defined in ITU-T Rec. X.721
             is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 14};
```

5.1.15 aucFunction

```
aucFunction MANAGED OBJECT CLASS
DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
    aucFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
        PRESENT IF
            "the objectCreation and the objectDeletion notifications defined in
             ITU-T Rec. X.721 are supported by an instance of this class.",
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
        PRESENT IF
            "the attributeValueChange notification defined in ITU-T Rec. X.721
```

```
    is supported by an instance of this class.";  
REGISTERED AS {ts32-634ObjectClass 15};
```

5.1.16 bgFunction

```
bgFunction MANAGED OBJECT CLASS  
DERIVED FROM  
    "3GPP TS 32.624": managedFunction;  
CHARACTERIZED BY  
    bgFunctionBasicPackage,  
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;  
CONDITIONAL PACKAGES  
    "Rec. M.3100: 1995":createDeleteNotificationsPackage  
    PRESENT IF  
        "the objectCreation and the objectDeletion notifications defined in  
        ITU-T Rec. X.721 are supported by an instance of this class.",  
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage  
    PRESENT IF  
        "the attributeValueChange notification defined in ITU-T Rec. X.721  
        is supported by an instance of this class."  
REGISTERED AS {ts32-634ObjectClass 16};
```

5.1.17 eirFunction

```
eirFunction MANAGED OBJECT CLASS  
DERIVED FROM  
    "3GPP TS 32.624": managedFunction;  
CHARACTERIZED BY  
    eirFunctionBasicPackage,  
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;  
CONDITIONAL PACKAGES  
    "Rec. M.3100: 1995":createDeleteNotificationsPackage  
    PRESENT IF  
        "the objectCreation and the objectDeletion notifications defined in  
        ITU-T Rec. X.721 are supported by an instance of this class.",  
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage  
    PRESENT IF  
        "the attributeValueChange notification defined in ITU-T Rec. X.721  
        is supported by an instance of this class."  
REGISTERED AS {ts32-634ObjectClass 17};
```

5.1.18 ggsnFunction

```
ggsnFunction MANAGED OBJECT CLASS  
DERIVED FROM  
    "3GPP TS 32.624": managedFunction;  
CHARACTERIZED BY  
    ggsnFunctionBasicPackage,  
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;  
CONDITIONAL PACKAGES  
    "Rec. M.3100: 1995":createDeleteNotificationsPackage  
    PRESENT IF  
        "the objectCreation and the objectDeletion notifications defined in  
        ITU-T Rec. X.721 are supported by an instance of this class.",  
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage  
    PRESENT IF  
        "the attributeValueChange notification defined in ITU-T Rec. X.721  
        is supported by an instance of this class."  
REGISTERED AS {ts32-634ObjectClass 18};
```

5.1.19 hlrFunction

```
hlrFunction MANAGED OBJECT CLASS  
DERIVED FROM  
    "3GPP TS 32.624": managedFunction;  
CHARACTERIZED BY  
    hlrFunctionBasicPackage,  
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;  
CONDITIONAL PACKAGES  
    "Rec. M.3100: 1995":createDeleteNotificationsPackage  
    PRESENT IF  
        "the objectCreation and the objectDeletion notifications defined in  
        ITU-T Rec. X.721 are supported by an instance of this class.",
```

```

"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
  "the attributeValueChange notification defined in ITU-T Rec. X.721
  is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 19};

```

5.1.20 mscServerFunction

```

mscFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  mscServerFunctionBasicPackage,
  mscServerFunctionAssociationPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
  "the objectCreation and the objectDeletion notifications defined in
  ITU-T Rec. X.721 are supported by an instance of this class.",

  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
  "the attributeValueChange notification defined in ITU-T Rec. X.721
  is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 20};

```

5.1.21 sgsnFunction

```

sgsnFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  sgsnFunctionBasicPackage,
  sgsnFunctionAssociationPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
  "the objectCreation and the objectDeletion notifications defined in
  ITU-T Rec. X.721 are supported by an instance of this class.",

  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
  "the attributeValueChange notification defined in ITU-T Rec. X.721
  is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 21};

```

5.1.22 smsGmcsFunction

```

smsGmcsFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  smsGmcsFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
  "the objectCreation and the objectDeletion notifications defined in
  ITU-T Rec. X.721 are supported by an instance of this class.",

  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
  "the attributeValueChange notification defined in ITU-T Rec. X.721
  is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 22};

```

5.1.23 smsIwmscFunction

```

smsIwmscFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  smsIwmscFunctionBasicPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;

```

CONDITIONAL PACKAGES

```

"Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
     ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
     is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 23};

```

5.1.24 vlrFunction

vlrFunction MANAGED OBJECT CLASS

```

DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
    vlrFunctionBasicPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
     ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
     is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 24};

```

5.1.25 gbLink

gbLink MANAGED OBJECT CLASS

```

DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
    gbLinkBasicPackage,
    gbLinkAssociationPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
     ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
     is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 25};

```

5.1.26 aLink

aLink MANAGED OBJECT CLASS

```

DERIVED FROM
    "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
    aLinkBasicPackage,
    aLinkAssociationPackage,
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
    "Rec. M.3100: 1995":createDeleteNotificationsPackage
PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
     ITU-T Rec. X.721 are supported by an instance of this class.",
"Rec. M.3100: 1995":attributeValueChangeNotificationPackage
PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
     is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 26};

```

5.1.27 iucsLink

iucsLink MANAGED OBJECT CLASS

```

DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  iucsLinkBasicPackage,
  iucsLinkAssociationPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
  PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
     ITU-T Rec. X.721 are supported by an instance of this class.",

  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
  PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
     is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 27};

```

5.1.28 iupsLink

```

iupsLink MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  iupsLinkBasicPackage,
  iupsLinkAssociationPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
  PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
     ITU-T Rec. X.721 are supported by an instance of this class.",

  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
  PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
     is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 28};

```

5.1.29 iubcLink

```

iubcLink MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  iubcLinkBasicPackage,
  iubcLinkAssociationPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
  PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
     ITU-T Rec. X.721 are supported by an instance of this class.",

  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
  PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
     is supported by an instance of this class.";
REGISTERED AS {ts32-634ObjectClass 29};

```

5.1.30 csMgwFunction

```

csMgwFunction MANAGED OBJECT CLASS
DERIVED FROM
  "3GPP TS 32.624": managedFunction;
CHARACTERIZED BY
  csMgwFunctionBasicPackage,
  csMgwFunctionAssociationPackage,
  "3GPP TS 32.111-4": x721AlarmNotificationsPackage;
CONDITIONAL PACKAGES
  "Rec. M.3100: 1995":createDeleteNotificationsPackage
  PRESENT IF
    "the objectCreation and the objectDeletion notifications defined in
     ITU-T Rec. X.721 are supported by an instance of this class.",

  "Rec. M.3100: 1995":attributeValueChangeNotificationPackage
  PRESENT IF
    "the attributeValueChange notification defined in ITU-T Rec. X.721
     is supported by an instance of this class.";

```

```
is supported by an instance of this class.";  
REGISTERED AS {ts32-634ObjectClass 30};
```

5.1.31 GmscServerFunction

```
gmscServerFunction MANAGED OBJECT CLASS  
DERIVED FROM  
    "3GPP TS 32.624": managedFunction;  
CHARACTERIZED BY  
    gmscServerFunctionBasicPackage,  
    "3GPP TS 32.111-4": x721AlarmNotificationsPackage;  
CONDITIONAL PACKAGES  
    "Rec. M.3100: 1995":createDeleteNotificationsPackage  
PRESENT IF  
    "the objectCreation and the objectDeletion notifications defined in  
    ITU-T Rec. X.721 are supported by an instance of this class.",  
    "Rec. M.3100: 1995":attributeValueChangeNotificationPackage  
PRESENT IF  
    "the attributeValueChange notification defined in ITU-T Rec. X.721  
    is supported by an instance of this class.";  
REGISTERED AS {ts32-634ObjectClass 31};
```

5.2 Packages

5.2.1 smlcFunctionBasicPackage

```
smlcFunctionBasicPackage PACKAGE  
BEHAVIOUR  
    smlcFunctionBasicPackageBehaviour;  
ATTRIBUTES  
    smlcFunctionId      GET;  
REGISTERED AS {ts32-634Package 1};  
  
smlcFunctionBasicPackageBehaviour BEHAVIOUR  
DEFINED AS  
    "The 'SmlcFunction' Information Object represents the SMLC functionality. For more information  
    about the SMLC, see 3GPP TS 23.002";
```

5.2.2 gmlcFunctionBasicPackage

```
gmlcFunctionBasicPackage PACKAGE  
BEHAVIOUR  
    gmlcFunctionBasicPackageBehaviour;  
ATTRIBUTES  
    gmlcFunctionId      GET;  
REGISTERED AS {ts32-634Package 2};  
  
gmlcFunctionBasicPackageBehaviour BEHAVIOUR  
DEFINED AS  
    "The 'GmlcFunction' Information Object represents the GMLC functionality. For more information  
    about the GMLC, see 3GPP TS 23.002";
```

5.2.3 scfFunctionBasicPackage

```
scfFunctionBasicPackage PACKAGE  
BEHAVIOUR  
    scfFunctionBasicPackageBehaviour;  
ATTRIBUTES  
    scfFunctionId      GET;  
REGISTERED AS {ts32-634Package 3};  
  
scfFunctionBasicPackageBehaviour BEHAVIOUR  
DEFINED AS  
    "The 'ScfFunction' Information Object represents the SCF functionality. For more information  
    about the SCF, see 3GPP TS 23.002";
```

5.2.4 srfFunctionBasicPackage

```
srfFunctionBasicPackage PACKAGE  
BEHAVIOUR
```

```

srfFunctionBasicPackageBehaviour;
ATTRIBUTES
  srfFunctionId      GET;
REGISTERED AS {ts32-634Package 4};

srfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'SrfFunction' Information Object represents the SRF functionality. For more information
   about the SRF, see 3GPP TS 23.002";

```

5.2.5 cbcFunctionBasicPackage

```

cbcFunctionBasicPackage PACKAGE
  BEHAVIOUR
    cbcFunctionBasicPackageBehaviour;
  ATTRIBUTES
    cbcFunctionId      GET;
REGISTERED AS {ts32-634Package 5};

cbcFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'CbcFunction' Information Object represents the SBC functionality. For more
   information about the SBC, see 3GPP TS 23.002";

```

5.2.6 cfgFunctionBasicPackage

```

cfgFunctionBasicPackage PACKAGE
  BEHAVIOUR
    cfgFunctionBasicPackageBehaviour;
  ATTRIBUTES
    cfgFunctionId      GET;
REGISTERED AS {ts32-634Package 6};

cfgFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'CfgFunction' Information Object represents the CGF functionality. For more information
   about the CGF, see 3GPP TS 23.002";

```

5.2.7 imsMgwFunctionBasicPackage

```

imsMgwFunctionBasicPackage PACKAGE
  BEHAVIOUR
    imsMgwFunctionBasicPackageBehaviour;
  ATTRIBUTES
    imsMgwFunctionId      GET;
REGISTERED AS {ts32-634Package 70503};

imsMgwFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'imsMgwFunction' Information Object represents the IMS-MGW functionality. For more
   information about the IMS-MGW, see 3GPP TS 23.002";

```

5.2.8 gmscFunctionBasicPackage

```

gmscFunctionBasicPackage PACKAGE
  BEHAVIOUR
    gmscFunctionBasicPackageBehaviour;
  ATTRIBUTES
    gmscFunctionId      GET;
REGISTERED AS {ts32-634Package 8};

gmscFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'GmscFunction' Information Object represents the GMSC functionality. For more information
   about the GMSC, see 3GPP TS 23.002";

```

5.2.9 iwfFunctionBasicPackage

```
iwfFunctionBasicPackage PACKAGE
```

```

BEHAVIOUR
    iwfFunctionBasicPackageBehaviour;
ATTRIBUTES
    iwfFunctionId      GET;
REGISTERED AS {ts32-634Package 9};

iwfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
    "The 'IwfFunction' Information Object represents the IWF functionality. For more information
     about the IWF, see 3GPP TS 23.002";

```

5.2.10 mnpSrfFunctionBasicPackage

```

mnpSrfFunctionBasicPackage PACKAGE
BEHAVIOUR
    mnpSrfFunctionBasicPackageBehaviour;
ATTRIBUTES
    mnpSrfFunctionId  GET;
REGISTERED AS {ts32-634Package 10};

mnpSrfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
    "The 'MnpSrfFunction' Information Object represents the MNPSRF functionality. For more
     information about the MNPSRF, see 3GPP TS 23.002";

```

5.2.11 npdbFunctionBasicPackage

```

npdbFunctionBasicPackage PACKAGE
BEHAVIOUR
    npdbFunctionBasicPackageBehaviour;
ATTRIBUTES
    npdbFunctionId  GET;
REGISTERED AS {ts32-634Package 11};

npdbFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
    "The 'NpdbFunction' Information Object represents the NPDB functionality. For more information
     about the NPDB, see 3GPP TS 23.002";

```

5.2.12 rSgwFunctionBasicPackage

```

rSgwFunctionBasicPackage PACKAGE
BEHAVIOUR
    rSgwFunctionBasicPackageBehaviour;
ATTRIBUTES
    rSgwFunctionId  GET;
REGISTERED AS {ts32-634Package 12};

rSgwFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
    "The 'RSgwFunction' Information Object represents the R-SGW functionality. For more information
     about the R-SGW, see 3GPP TS 23.002";

```

5.2.13 ssfFunctionBasicPackage

```

ssfFunctionBasicPackage PACKAGE
BEHAVIOUR
    ssfFunctionBasicPackageBehaviour;
ATTRIBUTES
    ssfFunctionId  GET;
REGISTERED AS {ts32-634Package 13};

ssfFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
    "The 'SsfFunction' Information Object represents the SSF functionality. For more information
     about the SSF, see 3GPP TS 23.002";

```

5.2.14 bsFunctionBasicPackage

```

bsFunctionBasicPackage PACKAGE
BEHAVIOUR

```

```

bsFunctionBasicPackageBehaviour;
ATTRIBUTES
  bsFunctionId      GET;
REGISTERED AS {ts32-634Package 14};

bsFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'BsFunction' Information Object represents the BS functionality. For more information about
  the BS, see 3GPP TS 23.002";

```

5.2.15 aucFunctionBasicPackage

```

aucFunctionBasicPackage PACKAGE
  BEHAVIOUR
    aucFunctionBasicPackageBehaviour;
  ATTRIBUTES
    aucFunctionId      GET;
REGISTERED AS {ts32-634Package 15};

aucFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'aucFunction' Information Object represents the AUC functionality. For more information
  about the AUC, see 3GPP TS 23.002";

```

5.2.16 bgFunctionBasicPackage

```

bgFunctionBasicPackage PACKAGE
  BEHAVIOUR
    bgFunctionBasicPackageBehaviour;
  ATTRIBUTES
    bgFunctionId      GET;
REGISTERED AS {ts32-634Package 16};

bgFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'bgFunction' Information Object represents the BG functionality. For more information about
  the BG, see 3GPP TS 23.002";

```

5.2.17 eirFunctionBasicPackage

```

eirFunctionBasicPackage PACKAGE
  BEHAVIOUR
    eirFunctionBasicPackageBehaviour;
  ATTRIBUTES
    eirFunctionId      GET;
REGISTERED AS {ts32-634Package 17};

eirFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'EirFunction' Information Object represents the EIR functionality. For more information
  about the EIR, see 3GPP TS 23.002";

```

5.2.18 ggsnFunctionBasicPackage

```

ggsnFunctionBasicPackage PACKAGE
  BEHAVIOUR
    ggsnFunctionBasicPackageBehaviour;
  ATTRIBUTES
    ggsnFunctionId      GET;
REGISTERED AS {ts32-634Package 18};

ggsnFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'GGSNFunction' Information Object represents the GGSN functionality. For more information
  about the GGSN, see 3GPP TS 23.002";

```

5.2.19 hlrFunctionBasicPackage

```

hlrFunctionBasicPackage PACKAGE
  BEHAVIOUR
    hlrFunctionBasicPackageBehaviour;

```

```

ATTRIBUTES
  hlrFunctionId      GET;
REGISTERED AS {ts32-634Package 19};



---


  hlrFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'HLRFunction' Information Object represents the HLR functionality. For more information
  about the HLR, see 3GPP TS 23.002";

```

5.2.20 mscServerFunctionBasicPackage

```

mscServerFunctionBasicPackage PACKAGE
BEHAVIOUR
  mscServerFunctionBasicPackageBehaviour;
ATTRIBUTES
  mscServerFunctionId      GET,
  mccList                  GET-REPLACE,
  mncList                  GET-REPLACE,
  lacList                  GET-REPLACE,
  sacList                  GET-REPLACE,
  gcaList                  GET-REPLACE,
  mscId                   GET-REPLACE;
REGISTERED AS {ts32-634Package 20};



---


  mscServerFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'MSCServerFunction' Information Object represents the MSCServer functionality.
  For more information about the MSCServer, see 3GPP TS 23.002";

```

5.2.21 mscServerFunctionAssociationPackage

```

mscServerFunctionAssociationPackage PACKAGE
BEHAVIOUR
  mscServerFunctionAssociationPackageBehaviour;
ATTRIBUTES
  mscServerFunction-GSMcell      GET,
  mscServerFunction-ExternalGSMcell  GET,
  mscServerFunction-CsMgwFunction    GET;
REGISTERED AS {ts32-634Package 21};



---


  mscServerFunctionAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'MscServerFunction' information object in
  relation with associations to GsmCell, ExternalGsmCell and CsMgwFunction information objects";

```

5.2.22 sgsnFunctionBasicPackage

```

sgsnFunctionBasicPackage PACKAGE
BEHAVIOUR
  sgsnFunctionBasicPackageBehaviour;
ATTRIBUTES
  sgsnFunctionId      GET,
  mccList            GET-REPLACE,
  mncList            GET-REPLACE,
  lacList            GET-REPLACE,
  racList            GET-REPLACE,
  sgsnId             GET-REPLACE,
  mscId              GET-REPLACE;
REGISTERED AS {ts32-634Package 22};



---


  sgsnFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'sgsnFunction' Information Object represents the SGSN functionality. For more information
  about the SGSN, see 3GPP TS 23.002";

```

5.2.23 sgsnFunctionAssociationPackage

```

sgsnFunctionAssociationPackage PACKAGE
BEHAVIOUR
  sgsnFunctionAssociationPackageBehaviour;
ATTRIBUTES
  sgsnFunction-GSMcell      GET,
  sgsnFunction-ExternalGSMcell  GET;

```

```

REGISTERED AS {ts32-634Package 23};

sgsnFunctionAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
"This Package contains the attributes of an 'SGSNFunction' information object in relation
with associations to GsmCell and ExternalGsmCell information objects.";
```

5.2.24 smsGmScFunctionBasicPackage

```

smsGmScFunctionBasicPackage PACKAGE
BEHAVIOUR
  smsGmScFunctionBasicPackageBehaviour;
ATTRIBUTES
  smsGmScFunctionId      GET;
REGISTERED AS {ts32-634Package 24};

smsGmScFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
"The 'smsGmScFunction' Information Object represents the SMS-GMSC functionality.
For more information about the SMS-GMSC, see 3GPP TS 23.002";
```

5.2.25 smsIwmscFunctionBasicPackage

```

smsIwmscFunctionBasicPackage PACKAGE
BEHAVIOUR
  smsIwmscFunctionBasicPackageBehaviour;
ATTRIBUTES
  smsIwmscFunctionId      GET;
REGISTERED AS {ts32-634Package 25};

smsIwmscFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
"The 'smsIwmscFunction' Information Object represents the SmsIwMSC functionality.
For more information about the SmsIwMsc, see 3GPP TS 23.002";
```

5.2.26 vlrFunctionBasicPackage

```

vlrFunctionBasicPackage PACKAGE
BEHAVIOUR
  vlrFunctionBasicPackageBehaviour;
ATTRIBUTES
  vlrFunctionId      GET;
REGISTERED AS {ts32-634Package 26};

vlrFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
"The 'vlrFunction' Information Object represents the VLR functionality. For more information
about the VLR, see 3GPP TS 23.002";
```

5.2.27 gbLinkBasicPackage

```

gbLinkBasicPackage PACKAGE
BEHAVIOUR
  gbLinkBasicPackageBehaviour;
ATTRIBUTES
  gbLinkId      GET;
REGISTERED AS {ts32-634Package 27};

gbLinkBasicPackageBehaviour BEHAVIOUR
DEFINED AS
"The 'gbLink' Information Object represents the Gb link functionality. For more information
about the Gb link, see 3GPP TS 23.002";
```

5.2.28 gbLinkAssociationPackage

```

gbLinkAssociationPackage PACKAGE
BEHAVIOUR
  gbLinkAssociationPackageBehaviour;
ATTRIBUTES
  connectedBss      GET;
REGISTERED AS {ts32-634Package 28};
```

```
gbLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'gbLink' information object in relation with
  associations to BssFunction or ExternalBssFunction objects";
```

5.2.29 aLinkBasicPackage

```
aLinkBasicPackage PACKAGE
  BEHAVIOUR
    aLinkBasicPackageBehaviour;
  ATTRIBUTES
    aLinkId      GET;
REGISTERED AS {ts32-634Package 29};

aLinkBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'aLink' Information Object represents the A link functionality. For more information
  about the A link, see 3GPP TS 23.002";
```

5.2.30 aLinkAssociationPackage

```
aLinkAssociationPackage PACKAGE
  BEHAVIOUR
    aLinkAssociationPackageBehaviour;
  ATTRIBUTES
    connectedBss      GET;
REGISTERED AS {ts32-634Package 30};

aLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'aLink' information object in relation with
  associations to BssFunction or ExternalBssFunction objects";
```

5.2.31 iucsLinkBasicPackage

```
iucsLinkBasicPackage PACKAGE
  BEHAVIOUR
    iucsLinkBasicPackageBehaviour;
  ATTRIBUTES
    iucsLinkId      GET;
REGISTERED AS {ts32-634Package 31};

iucsLinkBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'iucsLink' Information Object represents the Iu-cs link functionality. For more
  information about the Iu-cs link, see 3GPP TS 23.002";
```

5.2.32 iucsLinkAssociationPackage

```
iucsLinkAssociationPackage PACKAGE
  BEHAVIOUR
    iucsLinkAssociationPackageBehaviour;
  ATTRIBUTES
    connectedRnc      GET,
    connectedBss      GET;
REGISTERED AS {ts32-634Package 32};

iucsLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'iucsLink' information object in relation with
  associations to Bss/RncFunction or ExternalBssFunction objects";
```

5.2.33 iupsLinkBasicPackage

```
iupsLinkBasicPackage PACKAGE
  BEHAVIOUR
    iupsLinkBasicPackageBehaviour;
  ATTRIBUTES
    iupsLinkId      GET;
REGISTERED AS {ts32-634Package 33};
```

```
iupsLinkBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'iupsLink' Information Object represents the Iu-ps link functionality. For more
   information about the Iu-ps link, see 3GPP TS 23.002";
```

5.2.34 iupsLinkAssociationPackage

```
iupsLinkAssociationPackage PACKAGE
  BEHAVIOUR
    iupsLinkAssociationPackageBehaviour;
  ATTRIBUTES
    connectedRnc      GET,
    connectedBss     GET;
REGISTERED AS {ts32-634Package 34};

iupsLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'iupsLink' information object in relation with
   associations to Bss/RncFunction or ExternalBssFunction objects";
```

5.2.35 iubcLinkBasicPackage

```
iubcLinkBasicPackage PACKAGE
  BEHAVIOUR
    iubcLinkBasicPackageBehaviour;
  ATTRIBUTES
    iubcLinkId      GET;
REGISTERED AS {ts32-634Package 35};

iubcLinkBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'iubcLink' Information Object represents the Iu-bc link functionality. For more
   information about the Iu-bc link, see 3GPP TS 23.002";
```

5.2.36 iubcLinkAssociationPackage

```
iubcLinkAssociationPackage PACKAGE
  BEHAVIOUR
    iubcLinkAssociationPackageBehaviour;
  ATTRIBUTES
    connectedRnc      GET;
REGISTERED AS {ts32-634Package 36};

iubcLinkAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
  "This Package contains the attributes of an 'iubcLink' information object in relation with
   associations to RncFunction objects";
```

5.2.37 csMgwFunctionBasicPackage

```
csMgwFunctionBasicPackage PACKAGE
  BEHAVIOUR
    csMgwFunctionBasicPackageBehaviour;
  ATTRIBUTES
    csMgwFunctionId      GET;
REGISTERED AS {ts32-634Package 37};

csMgwFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
  "The 'csMgwFunction' Information Object represents the CS-MGW functionality. For more
   information about the CS-MGW, see 3GPP TS 23.002";
```

5.2.38 csMgwFunctionAssociationPackage

```
csMgwFunctionAssociationPackage PACKAGE
  BEHAVIOUR
    csMgwFunctionAssociationPackageBehaviour;
  ATTRIBUTES
    csMgwFunction-MscServerFunction      GET,
    csMgwFunction-IucsLink              GET,
```

```

csMgwFunction-Alink           GET;
REGISTERED AS {ts32-634Package 38};

csMgwFunctionAssociationPackageBehaviour BEHAVIOUR
DEFINED AS
"This Package contains the attributes of an 'csMgwFunction' information object in relation
with associations to mscServerFunction, iucsLink or aLink objects";

```

5.2.39 gmscServerFunctionBasicPackage

```

gmscServerFunctionBasicPackage PACKAGE
  BEHAVIOUR
    gmscServerFunctionBasicPackageBehaviour;
  ATTRIBUTES
    gmscServerFunctionId      GET;
REGISTERED AS {ts32-634Package 39};

gmscServerFunctionBasicPackageBehaviour BEHAVIOUR
DEFINED AS
"The 'gmscServerFunction' Information Object represents the GMSCServer functionality. For more
information about the GMSCServer, see 3GPP TS 23.002";

```

5.3 Attributes

5.3.1 smlcFunctionId

```

smlcFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    smlcFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 1};

smlcFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies a smlcFunction instance.";

```

5.3.2 gmlcFunctionId

```

gmlcFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    gmlcFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 2};

gmlcFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies a gmlcFunction instance.";

```

5.3.3 scfFunctionId

```

scfFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    scfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 3};

scfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies a scfFunction instance.";

```

5.3.4 srfFunctionId

```
srfFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    srfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 4};

srfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a srfFunction instance.";
```

5.3.5 cbcFunctionId

```
cbcFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    cbcFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 5};

cbcFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a cbcFunction instance.";
```

5.3.6 cfgFunctionId

```
cfgFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    cfgFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 6};

cfgFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a cfgFunction instance.";
```

5.3.7 imsMgwFunctionId

```
imsMgwFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    imsMgwFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 70503};

imsMgwFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies an imsMgwFunction instance.";
```

5.3.8 gmscFunctionId

```
gmscFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    gmscFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 8};

gmscFunctionIdBehaviour BEHAVIOUR
```

DEFINED AS
 "This attribute identifies a gmScFunction instance.";

5.3.9 iwfFunctionId

```
iwfFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    iwfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 9};

iwfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a iwfFunction instance.";
```

5.3.10 mnpSrfFunctionId

```
mnpSrfFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    mnpSrfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 10};

mnpSrfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a mnpSrfFunction instance.";
```

5.3.11 npdbFunctionId

```
npdbFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    npdbFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 11};

npdbFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a npdbFunction instance.";
```

5.3.12 rSgwFunctionId

```
rSgwFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    rSgwFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 12};

rSgwFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a rSgwFunction instance.";
```

5.3.13 ssfFunctionId

```
ssfFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
```

```

ssfFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 13};

ssfFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a ssfFunction instance.";
```

5.3.14 bsFunctionId

```

bsFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
        TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
        EQUALITY;
    BEHAVIOUR
        bsFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 14};

bsFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a bsFunction instance.";
```

5.3.15 aucFunctionId

```

aucFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
        TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
        EQUALITY;
    BEHAVIOUR
        aucFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 15};

aucFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a aucFunction instance.";
```

5.3.16 bgFunctionId

```

bgFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
        TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
        EQUALITY;
    BEHAVIOUR
        bgFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 16};

bgFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a bgFunction instance.";
```

5.3.17 eirFunctionId

```

eirFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
        TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
        EQUALITY;
    BEHAVIOUR
        eirFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 17};

eirFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a eirFunction instance.";
```

5.3.18 ggsnFunctionId

```

ggsnFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
```

```

TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
sgsnFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 18};

ggsnFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies a ggsnFunction instance.";
```

5.3.19 hlrFunctionId

```

hlrFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
hlrFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 19};

hlrFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies a hlrFunction instance.";
```

5.3.20 mscServerFunctionId

```

mscServerFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
mscServerFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 20};

mscServerFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies a mscServerFunction instance.";
```

5.3.21 vlrFunctionId

```

vlrFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
vlrFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 21};

vlrFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies a vlrFunction instance.";
```

5.3.22 sgsnFunctionId

```

sgsnFunctionId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
sgsnFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 22};

sgsnFunctionIdBehaviour BEHAVIOUR
DEFINED AS
"This attribute identifies a sgsnFunction instance.";
```

5.3.23 smsGmscFunctionId

```

smsGmscFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    smsGmscFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 23};

smsGmscFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a smsGmscFunction instance.";
```

5.3.24 smsIwmscFunctionId

```

smsIwmscFunctionId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    smsIwmscFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 24};

smsIwmscFunctionIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a smsIwmscFunction instance.";
```

5.3.25 gbLinkId

```

gbLinkId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    gbLinkIdBehaviour;
REGISTERED AS {ts32-634Attribute 25};

gbLinkIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a gbLink instance.";
```

5.3.26 aLinkId

```

aLinkId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    aLinkIdBehaviour;
REGISTERED AS {ts32-634Attribute 26};

aLinkIdBehaviour BEHAVIOUR
DEFINED AS
  "This attribute identifies a aLink instance.";
```

5.3.27 iucsLinkId

```

iucsLinkId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    iucsLinkIdBehaviour;
REGISTERED AS {ts32-634Attribute 27};
```

```
iucsLinkIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a iucsLink instance.";
```

5.3.28 iupsLinkId

```
iupsLinkId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
        TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
        EQUALITY;
    BEHAVIOUR
        iupsLinkIdBehaviour;
REGISTERED AS {ts32-634Attribute 28};

iupsLinkIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a iupsLink instance.";
```

5.3.29 iubcLinkId

```
iubcLinkId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
        TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
        EQUALITY;
    BEHAVIOUR
        iubcLinkIdBehaviour;
REGISTERED AS {ts32-634Attribute 29};

iubcLinkIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a iubcLink instance.";
```

5.3.30 csMgwFunctionId

```
csMgwFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
        TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
        EQUALITY;
    BEHAVIOUR
        csMgwFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 30};

csMgwFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a csMgwFunction instance.";
```

5.3.31 gmscServerFunctionId

```
gmscServerFunctionId ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
        TS32-634TypeModule.GeneralObjectId;
    MATCHES FOR
        EQUALITY;
    BEHAVIOUR
        gmscServerFunctionIdBehaviour;
REGISTERED AS {ts32-634Attribute 31};

gmscServerFunctionIdBehaviour BEHAVIOUR
DEFINED AS
    "This attribute identifies a gmscServerFunction instance.";
```

5.3.32 mccList

```
mccList ATTRIBUTE
    WITH ATTRIBUTE SYNTAX
        TS32-634TypeModule.MccList;
    MATCHES FOR
        EQUALITY;
```

```

BEHAVIOUR
  mccListBehaviour;
REGISTERED AS {ts32-634Attribute 32};

mccListBehaviour BEHAVIOUR
DEFINED AS
  "List of Mobile Country Codes, MCC. The MCC is part of the PLMN Id (Ref. 3 GPP TS 23.003).";

```

5.3.33 mncList

```

mncList ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.MncList;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    mncListBehaviour;
REGISTERED AS {ts32-634Attribute 33};

mncListBehaviour BEHAVIOUR
DEFINED AS
  "List of Mobile Network Code, MNC. The MNC is part of the PLMN Id (Ref. 3 GPP TS 23.003).";

```

5.3.34 lacList

```

lacList ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.LacList;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    lacListBehaviour;
REGISTERED AS {ts32-634Attribute 34};

lacListBehaviour BEHAVIOUR
DEFINED AS
  "List of Location Area Codes covered by SGSN (Ref. 3 GPP TS 23.003).";

```

5.3.35 sacList

```

sacList ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.SacList;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    sacListBehaviour;
REGISTERED AS {ts32-634Attribute 35};

sacListBehaviour BEHAVIOUR
DEFINED AS
  "List of Service Area Codes covered by SGSN (Ref. 3 GPP TS 23.003).";

```

5.3.36 uraList

Void.

5.3.37 gcaList

```

gcaList ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.CgaList;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    gcaListBehaviour;
REGISTERED AS {ts32-634Attribute 37};

gcaListBehaviour BEHAVIOUR
DEFINED AS
  "List of Group Call Area (Ref. 3 GPP TS 23.003).";

```

5.3.38 mscId

```
mscId ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectId;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    mscIdBehaviour;
REGISTERED AS {ts32-634Attribute 38};

mscIdBehaviour BEHAVIOUR
DEFINED AS
  "Unique MSC ID (Ref. 3 GPP TS 23.002).";
```

5.3.39 mscServerFunction-GSMcell

```
mscServerFunction-GSMcell ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    mscServerFunction-GSMcellBehaviour;
REGISTERED AS {ts32-634Attribute 39};

mscServerFunction-GSMcellBehaviour BEHAVIOUR
DEFINED AS
  "This value contains the DN of the related GSMcell instance. This is a reference attribute
  modelling the role (of the association AssociatedWith) that this MscServerFunction
  is associated with to 0-* GSMcell.";
```

5.3.40 mscServerFunction-ExternalGSMcell

```
mscServerFunction-ExternalGSMcell ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    mscServerFunction-ExternalGSMcellBehaviour;
REGISTERED AS {ts32-634Attribute 40};

mscServerFunction-ExternalGSMcellBehaviour BEHAVIOUR
DEFINED AS
  "This value contains the DN of the related ExternalGSMcell instance. This is a reference
  attribute modelling the role (of the association AssociatedWith) that this MscServerFunction
  is associated with to 0-* ExternalGSMcell.";
```

5.3.41 mscServerFunction-CsMgwFunction

```
mscServerFunction-CsMgwFunction ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    mscServerFunction-CsMgwFunctionBehaviour;
REGISTERED AS {ts32-634Attribute 41};

mscServerFunction-CsMgwFunctionBehaviour BEHAVIOUR
DEFINED AS
  "This value contains the DN of the related CsMgwFunction instance. This is a reference
  attribute modelling the role (of the association AssociatedWith) that this MscServerFunction
  is associated with to 0-* CsMgwFunction.";
```

5.3.42 racList

```
racList ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
```

```

TS32-634TypeModule.RacList;
MATCHES FOR
EQUALITY;
BEHAVIOUR
racListBehaviour;
REGISTERED AS {ts32-634Attribute 42};

racListBehaviour BEHAVIOUR
DEFINED AS
"List of Routing Area Codes covered by SGSN (Ref. 3 GPP TS 23.003).";

```

5.3.43 sgsnId

```

sgsnId ATTRIBUTE
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectId;
MATCHES FOR
EQUALITY;
BEHAVIOUR
sgsnIdBehaviour;
REGISTERED AS {ts32-634Attribute 43};

sgsnIdBehaviour BEHAVIOUR
DEFINED AS
"Unique SGSN ID (Ref. 3 GPP TS 23.002).";

```

5.3.44 sgsnFunction-GSMcell

```

sgsnFunction-GSMcell ATTRIBUTE
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectPointer;
MATCHES FOR
EQUALITY;
BEHAVIOUR
sgsnFunction-GSMcellBehaviour;
REGISTERED AS {ts32-634Attribute 44};

sgsnFunction-GSMcellBehaviour BEHAVIOUR
DEFINED AS
"This value contains the DN of the related GSMcell instance. This is a reference attribute
modelling the role (of the association AssociatedWith) that this SgsnFunction is associated
with to 0-* GSMcell.";

```

5.3.45 sgsnFunction-ExternalGSMcell

```

sgsnFunction-ExternalGSMcell ATTRIBUTE
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectPointer;
MATCHES FOR
EQUALITY;
BEHAVIOUR
sgsnFunction-ExternalGSMcellBehaviour;
REGISTERED AS {ts32-634Attribute 45};

sgsnFunction-ExternalGSMcellBehaviour BEHAVIOUR
DEFINED AS
"This value contains the DN of the related ExternalGSMcell instance. This is a reference
attribute modelling the role (of the association AssociatedWith) that this SgsnFunction
is associated with to 0-* ExternalGSMcell.";

```

5.3.46 connectedBss

```

connectedBss ATTRIBUTE
WITH ATTRIBUTE SYNTAX
TS32-634TypeModule.GeneralObjectPointer;
MATCHES FOR
EQUALITY;
BEHAVIOUR
connectedBssBehaviour;
REGISTERED AS {ts32-634Attribute 46};

connectedBssBehaviour BEHAVIOUR
DEFINED AS

```

"This value contains the DN of the related BssFunction or ExternalBssFunction instance. This is a reference attribute modelling the role (of the association AssociatedWith) that link is connected to 0-1 BssFunction or 0-1 ExternalBssFunction.";

5.3.47 connectedRnc

```
connectedRnc ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    connectedRncBehaviour;
REGISTERED AS {ts32-634Attribute 47};

connectedRncBehaviour BEHAVIOUR
DEFINED AS
  "This value contains the DN of the related RncFunction instance. This is a reference attribute modelling the role (of the association AssociatedWith) that link is connected to 0-1 RncFunction.";
```

5.3.48 csMgwFunction-MscServerFunction

```
csMgwFunction-MscServerFunction ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    csMgwFunction-MscServerFunctionBehaviour;
REGISTERED AS {ts32-634Attribute 48};

csMgwFunction-MscServerFunctionBehaviour BEHAVIOUR
DEFINED AS
  "This value contains the DN of the related mscServerFunction instance. This is a reference attribute modelling the role (of the association AssociatedWith) that this csMgwFunction is associated with to 0-* mscServerFunction.";
```

5.3.49 csMgwFunction-IucsLink

```
csMgwFunction-IucsLink ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    csMgwFunction-IucsLinkBehaviour;
REGISTERED AS {ts32-634Attribute 49};

csMgwFunction-IucsLinkBehaviour BEHAVIOUR
DEFINED AS
  "This value contains the DN of the related IucsLink instance. This is a reference attribute modelling the role (of the association AssociatedWith) that this csMgwFunction is connected to 0-* IucsLink.";
```

5.3.50 csMgwFunction-Alink

```
csMgwFunction-Alink ATTRIBUTE
  WITH ATTRIBUTE SYNTAX
    TS32-634TypeModule.GeneralObjectPointer;
  MATCHES FOR
    EQUALITY;
  BEHAVIOUR
    csMgwFunction-AlinkBehaviour;
REGISTERED AS {ts32-634Attribute 50};

csMgwFunction-AlinkBehaviour BEHAVIOUR
DEFINED AS
  "This value contains the DN of the related ALink instance. This is a reference attribute modelling the role (of the association AssociatedWith) that this csMgwFunction is connected to 0-* ALINK.";
```

5.4 Name Binding

5.4.1 smlcFunction - managedElement

```
smlcFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    smlcFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    smlcFunctionId;
  BEHAVIOUR
    smlcFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 1};

smlcFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  smlcFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.2 gmlcFunction - managedElement

```
gmlcFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    gmlcFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    gmlcFunctionId;
  BEHAVIOUR
    gmlcFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 2};

gmlcFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  gmlcFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.3 scfFunction - managedElement

```
scfFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    scfFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    scfFunctionId;
  BEHAVIOUR
    scfFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 3};

scfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  scfFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.4 srfFunction - managedElement

```
srfFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    srfFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    srfFunctionId;
  BEHAVIOUR
    srfFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 4};

srfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  srfFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.5 cbcFunction - managedElement

```
cbcFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    cbcFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    cbcFunctionId;
  BEHAVIOUR
    cbcFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 5};

cbcFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  cbcFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.6 cfgFunction - managedElement

```
cfgFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    cfgFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    cfgFunctionId;
  BEHAVIOUR
    cfgFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 6};

cfgFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  cfgFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.7 imsMgwFunction - managedElement

```
imsMgwFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
```

```

imsMgwFunction;
NAMED BY SUPERIOR OBJECT CLASS
"3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  imsMgwFunctionId;
BEHAVIOUR
  imsMgwFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 70503};

imsMgwFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
"The name binding represents a relationship in which a managedElement contains and controls an
mimsMgwFunction. When automatic instance naming is used, the choice of name bindings is left as
a local matter.";
```

5.4.8 gmscFunction - managedElement

```

gmscFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  gmscFunction;
NAMED BY SUPERIOR OBJECT CLASS
"3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  gmscFunctionId;
BEHAVIOUR
  gmscFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 8};

gmscFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
"The name binding represents a relationship in which a managedElement contains and controls a
gmscFunction. When automatic instance naming is used, the choice of name bindings is left as
a local matter.";
```

5.4.9 iwfFunction - managedElement

```

iwfFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  iwfFunction;
NAMED BY SUPERIOR OBJECT CLASS
"3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  iwfFunctionId;
BEHAVIOUR
  iwfFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 9};

iwfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
"The name binding represents a relationship in which a managedElement contains and controls a
iwfFunction. When automatic instance naming is used, the choice of name bindings is left as
a local matter.";
```

5.4.10 mnpSrfFunction - managedElement

```

mnpSrfFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  mnpSrfFunction;
NAMED BY SUPERIOR OBJECT CLASS
"3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  mnpSrfFunctionId;
```

```

BEHAVIOUR
  mnpSrfFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 10};

mnpSrfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  mnpSrfFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.11 npdbFunction - managedElement

```

npdbFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    npdbFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    npdbFunctionId;
BEHAVIOUR
  npdbFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 11};

npdbFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  npdbFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.12 rSgwFunction - managedElement

```

rSgwFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    rSgwFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    rSgwFunctionId;
BEHAVIOUR
  rSgwFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 12};

rSgwFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  rSgwFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.13 ssfFunction - managedElement

```

ssfFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    ssfFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    ssfFunctionId;
BEHAVIOUR
  ssfFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
```

```

ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 13};

ssfFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
"The name binding represents a relationship in which a managedElement contains and controls a
ssfFunction. When automatic instance naming is used, the choice of name bindings is left as
a local matter.";
```

5.4.14 bsFunction - managedElement

```

bsFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
bsFunction;
NAMED BY SUPERIOR OBJECT CLASS
"3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
bsFunctionId;
BEHAVIOUR
bsFunction-managedElementBehaviour;
CREATE
WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 14};

bsFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
"The name binding represents a relationship in which a managedElement contains and controls a
bsFunction. When automatic instance naming is used, the choice of name bindings is left as
a local matter.";
```

5.4.15 aucFunction - managedElement

```

aucFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
aucFunction;
NAMED BY SUPERIOR OBJECT CLASS
"3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
aucFunctionId;
BEHAVIOUR
aucFunction-managedElementBehaviour;
CREATE
WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 15};

aucFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
"The name binding represents a relationship in which a managedElement contains and controls a
aucFunction. When automatic instance naming is used, the choice of name bindings is left as
a local matter.";
```

5.4.16 bgFunction - managedElement

```

bgFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
bgFunction;
NAMED BY SUPERIOR OBJECT CLASS
"3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
bgFunctionId;
BEHAVIOUR
bgFunction-managedElementBehaviour;
CREATE
WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 16};

bgFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
```

"The name binding represents a relationship in which a managedElement contains and controls a eirFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";

5.4.17 eirFunction - managedElement

```
eirFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    eirFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    eirFunctionId;
  BEHAVIOUR
    eirFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 17};

eirFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a eirFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";
```

5.4.18 ggsnFunction - managedElement

```
ggsnFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    ggsnFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    ggsnFunctionId;
  BEHAVIOUR
    ggsnFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 18};

ggsnFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a ggsnFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";
```

5.4.19 hlrFunction - managedElement

```
hlrFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    hlrFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    hlrFunctionId;
  BEHAVIOUR
    hlrFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 19};

hlrFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a hlrFunction. When automatic instance naming is used, the choice of name bindings is left as a local matter.";
```

5.4.20 mscServerFunction - managedElement

```

mscServerFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    mscFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    mscServerFunctionId;
  BEHAVIOUR
    mscServerFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 20};

mscServerFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  mscServerFunction. When automatic instance naming is used, the choice of name bindings is left
  as a local matter.";
```

5.4.21 vlrFunction - managedElement

```

vlrFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    vlrFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    vlrFunctionId;
  BEHAVIOUR
    vlrFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 21};

vlrFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  vlrFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.22 sgsnFunction - managedElement

```

sgsnFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    sgsnFunction;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    sgsnFunctionId;
  BEHAVIOUR
    sgsnFunction-managedElementBehaviour;
  CREATE
    WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
  DELETE
    ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 22};

sgsnFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  sgsnFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.23 smsGmScFunction - managedElement

```

smsGmScFunction-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
```

```

smsGmscFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  smsGmscFunctionId;
BEHAVIOUR
  smsGmscFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 23};

smsGmscFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  smsGmscFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.24 smsIwmscFunction - managedElement

```

smsIwmscFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  smsIwmscFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  smsIwmscFunctionId;
BEHAVIOUR
  smsIwmscFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 24};

smsIwmscFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  smsIwmscFunction. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.25 gbLink - managedElement

```

gbLink-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  gbLink;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  gbLinkId;
BEHAVIOUR
  gbLink-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 25};

gbLink-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  gbLink. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.26 aLink - managedElement

```

aLink-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  aLink;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  aLinkId;
```

```

BEHAVIOUR
  aLink-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 26};

aLink-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  aLink. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.27 iucsLink - managedElement

```

iucsLink-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    iucsLink;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    iucsLinkId;
BEHAVIOUR
  iucsLink-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 27};

iucsLink-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  iucsLink. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.28 iupsLink - managedElement

```

iupsLink-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    iupsLink;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    iupsLinkId;
BEHAVIOUR
  iupsLink-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 28};

iupsLink-managedElementBehaviour BEHAVIOUR
DEFINED AS
  "The name binding represents a relationship in which a managedElement contains and controls a
  iupsLink. When automatic instance naming is used, the choice of name bindings is left as
  a local matter.";
```

5.4.29 iubcLink - managedElement

```

iubcLink-managedElement NAME BINDING
  SUBORDINATE OBJECT CLASS
    iubcLink;
  NAMED BY SUPERIOR OBJECT CLASS
    "3GPP TS 32.624": managedElement;
  WITH ATTRIBUTE
    iubcLinkId;
BEHAVIOUR
  iubcLink-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
```

```

ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 29};

iubcLink-managedElementBehaviour BEHAVIOUR
DEFINED AS
"The name binding represents a relationship in which a managedElement contains and controls a
iubcLink. When automatic instance naming is used, the choice of name bindings is left as
a local matter.";
```

5.4.30 gmscServerFunction - managedElement

```

gmscServerFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  gmscServerFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  gmscServerFunctionId;
BEHAVIOUR
  gmscServerFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 30};

gmscServerFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
"The name binding represents a relationship in which a managedElement contains and controls a
gmscServerFunction. When automatic instance naming is used, the choice of name bindings is left
as a local matter.";
```

5.4.31 csMgwFunction - managedElement

```

csMgwFunction-managedElement NAME BINDING
SUBORDINATE OBJECT CLASS
  csMgwFunction;
NAMED BY SUPERIOR OBJECT CLASS
  "3GPP TS 32.624": managedElement;
WITH ATTRIBUTE
  csMgwFunctionId;
BEHAVIOUR
  csMgwFunction-managedElementBehaviour;
CREATE
  WITH-REFERENCE-OBJECT, WITH-AUTOMATIC-INSTANCE-NAMING;
DELETE
  ONLY-IF-NO-CONTAINED-OBJECTS;
REGISTERED AS {ts32-634NameBinding 31};

csMgwFunction-managedElementBehaviour BEHAVIOUR
DEFINED AS
"The name binding represents a relationship in which a managedElement contains and controls a
csMgwFunction. When automatic instance naming is used, the choice of name bindings is left as
a local matter.";
```

6 ASN.1 Definitions

```

TS32-634TypeModule {ccitt (0) identified-organization (4) etsi (0) mobileDomain (0) umts-Operation-
Maintenance (3) ts32-634 (634) informationModel (0) asn1Module (2) version1 (1)}

DEFINITIONS IMPLICIT TAGS ::=

BEGIN

--EXPORTS everything

IMPORTS

GeneralObjectId, GeneralObjectPointer
FROM TS32-624TypeModule {ccitt(0) identified-organization(4) etsi(0) mobileDomain(0)
umts-Operation-Maintenance(3) ts32-624(624) informationModel(0) asn1Module(2) version1(1)}
```

```

MobileCountryCode, MobileNetworkCode, LocationAreaCode
  FROM GSM1220TypeModule {ccitt(0) identified-organization(4) etsi(0) mobileDomain(0)
  gsm-Operation-Maintenance(3) gsm-12-20(20) informationModel(0) asn1Module(2)
  asn1TypeModule(0)};

-- 3GPP TS 32.634 related Object Identifiers

baseNodeUMTS          OBJECT IDENTIFIER ::= {itu-t(0) identified-organization(4) etsi(0)
                                              mobileDomain(0) umts-Operation-Maintenance(3)}

ts32-634               OBJECT IDENTIFIER ::= {baseNodeUMTS ts32-634(634)}
ts32-634InfoModel      OBJECT IDENTIFIER ::= {ts32-634 informationModel(0)}

ts32-634ObjectClass    OBJECT IDENTIFIER ::= {ts32-634InfoModel managedObjectClass(3)}
ts32-634Package         OBJECT IDENTIFIER ::= {ts32-634InfoModel package(4)}
ts32-634Parameter       OBJECT IDENTIFIER ::= {ts32-634InfoModel parameter(5)}
ts32-634NameBinding     OBJECT IDENTIFIER ::= {ts32-634InfoModel nameBinding(6)}
ts32-634Attribute        OBJECT IDENTIFIER ::= {ts32-634InfoModel attribute(7)}
ts32-634Action           OBJECT IDENTIFIER ::= {ts32-634InfoModel action(9)}
ts32-634Notification     OBJECT IDENTIFIER ::= {ts32-634InfoModel notification(10)}

-- Start of 3GPP SA5 own definitions

MccList ::= SET OF MobileCountryCode
MncList ::= SET OF MobileNetworkCode
LacList ::= SET OF LocationAreaCode

Rac ::= INTEGER
RacList ::= SET OF Rac
Sac ::= INTEGER
SacList ::= SET OF Sac
Cga ::= INTEGER
CgaList ::= SET OF Cga

END -- of TS32-634TypeModule

```

Annex A (informative): List of assigned Object Identifiers

This annex provides a list with all Object Identifiers (OIDs) that have been assigned in TS 32.634 in Release 5. These OIDs shall not be assigned to new objects.

Basic Object Name	Name and OID of the current TS Version	Name and OIDs of previous TS Versions
		Managed Object Classes
smlcFunction	Name: smlcFunction OID : ts32-634ObjectClass 1	--
gmlcFunction	Name: gmlcFunction OID : ts32-634ObjectClass 2	--
scfFunction	Name: scfFunction OID : ts32-634ObjectClass 3	--
srfFunction	Name: srfFunction OID : ts32-634ObjectClass 4	--
cbcFunction	Name: cbcFunction OID : ts32-634ObjectClass 5	--
cfgFunction	Name: cfgFunction OID : ts32-634ObjectClass 6	--
mgwFunction	--	Name: mgwFunction OID : ts32-634ObjectClass 7
imsMgwFunction	Name: imsMgwFunction OID : ts32-634ObjectClass 70503	--
gmscFunction	Name: gmscFunction OID : ts32-634ObjectClass 8	--
iwfFunction	Name: iwfFunction OID : ts32-634ObjectClass 9	--
mnpSrfFunction	Name: mnpSrfFunction OID : ts32-634ObjectClass 10	--
npdbFunction	Name: npdbFunction OID : ts32-634ObjectClass 11	--
rSgwFunction	Name: rSgwFunction OID : ts32-634ObjectClass 12	--
ssfFunction	Name: ssfFunction OID : ts32-634ObjectClass 13	--
bsFunction	Name: bsFunction OID : ts32-634ObjectClass 14	--
aucFunction	Name: aucFunction OID : ts32-634ObjectClass 15	--
bgFunction	Name: bgFunction OID : ts32-634ObjectClass 16	--
eirFunction	Name: eirFunction OID : ts32-634ObjectClass 17	--
ggsnFunction	Name: ggsnFunction OID : ts32-634ObjectClass 18	--
hlrFunction	Name: hlrFunction OID : ts32-634ObjectClass 19	--
mscFunction	Name: mscFunction OID : ts32-634ObjectClass 20	--
sgsnFunction	Name: sgsnFunction OID : ts32-634ObjectClass 21	--
smsGmscFunction	Name: smsGmscFunction OID : ts32-634ObjectClass 22	--
smsIwmscFunction	Name: smsIwmscFunction OID : ts32-634ObjectClass 23	--
vlrFunction	Name: vlrFunction OID : ts32-634ObjectClass 24	--
gbLink	Name: gbLink OID : ts32-634ObjectClass 25	--
aLink	Name: aLink OID : ts32-634ObjectClass 26	--
iucsLink	Name: iucsLink OID : ts32-634ObjectClass 27	--

iupsLink	Name: iupsLink OID : ts32-634ObjectClass 28	--
iubcLink	Name: iubcLink OID : ts32-634ObjectClass 29	--
csMgwFunction	Name: csMgwFunction OID : ts32-634ObjectClass 30	--
gmscServerFunction	Name: gmscServerFunction OID : ts32-634ObjectClass 31	--
	Packages	
smlcFunctionBasicPackage	Name: smlcFunctionBasicPackage OID : ts32-634Package 1	--
gmlcFunctionBasicPackage	Name: gmlcFunctionBasicPackage OID : ts32-634Package 2	--
scfFunctionBasicPackage	Name: scfFunctionBasicPackage OID : ts32-634Package 3	--
srfFunctionBasicPackage	Name: srfFunctionBasicPackage OID : ts32-634Package 4	--
cbcFunctionBasicPackage	Name: cbcFunctionBasicPackage OID : ts32-634Package 5	--
cgfFunctionBasicPackage	Name: cgfFunctionBasicPackage OID : ts32-634Package 6	--
mgwFunctionBasicPackage	--	Name: mgwFunctionBasicPackage OID : ts32-634Package 7
imsMgwFunctionBasicPackage	Name: imsMgwFunctionBasicPackage OID : ts32-634Package 70503	--
gmscFunctionBasicPackage	Name: gmscFunctionBasicPackage OID : ts32-634Package 8	--
iwfFunctionBasicPackage	Name: iwfFunctionBasicPackage OID : ts32-634Package 9	--
mnpSrfFunctionBasicPackage	Name: mnpSrfFunctionBasicPackage OID : ts32-634Package 10	--
npdbFunctionBasicPackage	Name: npdbFunctionBasicPackage OID : ts32-634Package 11	--
rSgwFunctionBasicPackage	Name: rSgwFunctionBasicPackage OID : ts32-634Package 12	--
ssfFunctionBasicPackage	Name: ssfFunctionBasicPackage OID : ts32-634Package 13	--
bsFunctionBasicPackage	Name: bsFunctionBasicPackage OID : ts32-634Package 14	--
aucFunctionBasicPackage	Name: aucFunctionBasicPackage OID : ts32-634Package 15	--
bgFunctionBasicPackage	Name: bgFunctionBasicPackage OID : ts32-634Package 16	--
eirFunctionBasicPackage	Name: eirFunctionBasicPackage OID : ts32-634Package 17	--
ggsnFunctionBasicPackage	Name: ggsnFunctionBasicPackage OID : ts32-634Package 18	--
hlrFunctionBasicPackage	Name: hlrFunctionBasicPackage OID : ts32-634Package 19	--
mscServerFunctionBasicPackage	Name: mscServerFunctionBasicPackage OID : ts32-634Package 20	--
mscServerFunctionAssociationPackage	Name: mscServerFunctionAssociationPackage OID : ts32-634Package 21	--
sgsnFunctionBasicPackage	Name: sgsnFunctionBasicPackage OID : ts32-634Package 22	--
sgsnFunctionAssociationPackage	Name: sgsnFunctionAssociationPackage OID : ts32-634Package 23	--
smsGmscFunctionBasicPackage	Name: smsGmscFunctionBasicPackage OID : ts32-634Package 24	--
smsIwmscFunctionBasicPackage	Name: smsIwmscFunctionBasicPackage OID : ts32-634Package 25	--
vlrFunctionBasicPackage	Name: vlrFunctionBasicPackage OID : ts32-634Package 26	--
gbLinkBasicPackage	Name: gbLinkBasicPackage OID : ts32-634Package 27	--
gbLinkAssociationPackage	Name: gbLinkAssociationPackage OID : ts32-634Package 28	--

aLinkBasicPackage	Name: aLinkBasicPackage OID : ts32-634Package 29	--
aLinkAssociationPackage	Name: aLinkAssociationPackage OID : ts32-634Package 30	--
iucsLinkBasicPackage	Name: iucsLinkBasicPackage OID : ts32-634Package 31	--
iucsLinkAssociationPackage	Name: iucsLinkAssociationPackage OID : ts32-634Package 32	--
iupsLinkBasicPackage	Name: iupsLinkBasicPackage OID : ts32-634Package 33	--
iupsLinkAssociationPackage	Name: iupsLinkAssociationPackage OID : ts32-634Package 34	--
iubcLinkBasicPackage	Name: iubcLinkBasicPackage OID : ts32-634Package 35	--
iubcLinkAssociationPackage	Name: iubcLinkAssociationPackage OID : ts32-634Package 36	--
csMgwFunctionBasicPackage	Name: csMgwFunctionBasicPackage OID : ts32-634Package 37	--
csMgwFunctionAssociationPa ckage	Name: csMgwFunctionAssociationPackage OID : ts32-634Package 38	--
gmscServerFunctionBasicPac kage	Name: gmscServerFunctionBasicPackage OID : ts32-634Package 39	--

Actions**Notifications****Attributes**

smlcFunctionId	Name: smlcFunctionId OID : ts32-634Attribute 1	--
gmlcFunctionId	Name: gmlcFunctionId OID : ts32-634Attribute 2	--
scfFunctionId	Name: scfFunctionId OID : -634Attribute 3	--
srfFunctionId	Name: srfFunctionId OID : ts32-634Attribute 4	--
cbcFunctionId	Name: cbcFunctionId OID : ts32-634Attribute 5	--
cgfFunctionId	Name: cgfFunctionId OID : ts32-634Attribute 6	--
mgwFunctionId	--	Name: mgwFunctionId OID : ts32-634Attribute 7
imsMgwFunctionId	Name: imsMgwFunctionId OID : ts32-634Attribute 70503	--
gmscFunctionId	Name: gmscFunctionId OID : ts32-634Attribute 8	--
iwfFunctionId	Name: iwfFunctionId OID : ts32-634Attribute 9	--
mnpSrfFunctionId	Name: mnpSrfFunctionId OID : ts32-634Attribute 10	--
npdbFunctionId	Name: npdbFunctionId OID : ts32-634Attribute 11	--
rSgwFunctionId	Name: rSgwFunctionId OID : ts32-634Attribute 12	--
ssfFunctionId	Name: ssfFunctionId OID : ts32-634Attribute 13	--
bsFunctionId	Name: bsFunctionId OID : ts32-634Attribute 14	--
aucFunctionId	Name: aucFunctionId OID : ts32-634Attribute 15	--
bgFunctionId	Name: bgFunctionId OID : ts32-634Attribute 16	--
eirFunctionId	Name: eirFunctionId OID : ts32-634Attribute 17	--
ggsnFunctionId	Name: ggsnFunctionId OID : ts32-634Attribute 18	--
hlrFunctionId	Name: hlrFunctionId OID : ts32-634Attribute 19	--
mscServerFunctionId	Name: mscServerFunctionId OID : ts32-634Attribute 20	--

vlrFunctionId	Name: vlrFunctionId OID : ts32-634Attribute 21	--
sgsnFunctionId	Name: sgsnFunctionId OID : ts32-634Attribute 22	--
smsGmScFunctionId	Name: smsGmScFunctionId OID : ts32-634Attribute 23	--
smsIwmscFunctionId	Name: smsIwmscFunctionId OID : ts32-634Attribute 24	--
gbLinkId	Name: gbLinkId OID : ts32-634Attribute 25	--
aLinkId	Name: aLinkId OID : ts32-634Attribute 26	--
iucsLinkId	Name: iucsLinkId OID : ts32-634Attribute 27	--
iupsLinkId	Name: iupsLinkId OID : ts32-634Attribute 28	--
iubcLinkId	Name: iubcLinkId OID : ts32-634Attribute 29	--
csMgwFunctionId	Name: csMgwFunctionId OID : ts32-634Attribute 30	--
gmscServerFunctionId	Name: gmscServerFunctionId OID : ts32-634Attribute 31	--
mccList	Name: mccList OID : ts32-634Attribute 32	--
mncList	Name: mncList OID : ts32-634Attribute 33	--
lacList	Name: lacList OID : ts32-634Attribute 34	--
sacList	Name: sacList OID : ts32-634Attribute 35	--
uraList	--	Name: uraList OID : ts32-634Attribute 36
gcaList	Name: gcaList OID : ts32-634Attribute 37	--
mscId	Name: mscId OID : ts32-634Attribute 38	--
mscServerFunction-GSMcell	Name: mscServerFunction-GSMcell OID : ts32-634Attribute 39	--
mscServerFunction-ExternalGSMcell	Name: mscServerFunction-ExternalGSMcell OID : ts32-634Attribute 40	--
mscServerFunction-CsMgwFunction	Name: mscServerFunction-CsMgwFunction OID : ts32-634Attribute 41	--
racList	Name: racList OID : ts32-634Attribute 42	--
sgsnId	Name: sgsnId OID : -634Attribute 43	--
sgsnFunction-GSMcell	Name: sgsnFunction-GSMcell OID : ts32-634Attribute 44	--
sgsnFunction-ExternalGSMcell	Name: sgsnFunction-ExternalGSMcell OID : ts32-634Attribute 45	--
connectedBss	Name: connectedBss OID : ts32-634Attribute 46	--
connectedRnc	Name: connectedRnc OID : ts32-634Attribute 47	--
csMgwFunction-MscServerFunction	Name: csMgwFunction-MscServerFunction OID : ts32-634Attribute 48	--
csMgwFunction-lucsLink	Name: csMgwFunction-lucsLink OID : ts32-634Attribute 49	--
csMgwFunction-Alink	Name: csMgwFunction-Alink OID : ts32-634Attribute 50	--

Parameters

Name Bindings		
smlcFunction-managedElement	Name: smlcFunction-managedElement OID : ts32-634NameBinding 1	--
gmlcFunction-managedElement	Name: gmlcFunction-managedElement OID : ts32-634NameBinding 2	--
scfFunction-managedElement	Name: scfFunction-managedElement OID : ts32-634NameBinding 3	--

srfFunction-managedElement	Name: srfFunction-managedElement OID : ts32-634NameBinding 4	--
cbcFunction-managedElement	Name: cbcFunction-managedElement OID : ts32-634NameBinding 5	--
cfgFunction-managedElement	Name: cfgFunction-managedElement OID : ts32-634NameBinding 6	--
mgwFunction-managedElement	--	Name: mgwFunction-managedElement OID : ts32-634NameBinding 7
imsMgwFunction-managedElement	Name: imsMgwFunction-managedElement OID : ts32-634NameBinding 70503	--
gmscFunction-managedElement	Name: gmscFunction-managedElement OID : ts32-634NameBinding 8	--
iwfFunction-managedElement	Name: iwfFunction-managedElement OID : ts32-634NameBinding 9	--
mnpSrfFunction-managedElement	Name: mnpSrfFunction-managedElement OID : ts32-634NameBinding 10	--
npdbFunction-managedElement	Name: npdbFunction-managedElement OID : ts32-634NameBinding 11	--
rSgwFunction-managedElement	Name: rSgwFunction-managedElement OID : ts32-634NameBinding 12	--
ssfFunction-managedElement	Name: ssfFunction-managedElement OID : ts32-634NameBinding 13	--
bsFunction-managedElement	Name: bsFunction-managedElement OID : ts32-634NameBinding 14	--
aucFunction-managedElement	Name: aucFunction-managedElement OID : ts32-634NameBinding 15	--
bgFunction-managedElement	Name: bgFunction-managedElement OID : ts32-634NameBinding 16	--
eirFunction-managedElement	Name: eirFunction-managedElement OID : ts32-634NameBinding 17	--
ggsnFunction-managedElement	Name: ggsnFunction-managedElement OID : ts32-634NameBinding 18	--
hlrFunction-managedElement	Name: hlrFunction-managedElement OID : ts32-634NameBinding 19	--
mscServerFunction-managedElement	Name: mscServerFunction-managedElement OID : ts32-634NameBinding 20	--
vlrFunction-managedElement	Name: vlrFunction-managedElement OID : ts32-634NameBinding 21	--
sgsnFunction-managedElement	Name: sgsnFunction-managedElement OID : ts32-634NameBinding 22	--
smsGmscFunction-managedElement	Name: smsGmscFunction-managedElement OID : ts32-634NameBinding 23	--
smsIwmscFunction-managedElement	Name: smsIwmscFunction-managedElement OID : ts32-634NameBinding 24	--
gbLink-managedElement	Name: gbLink-managedElement OID : ts32-634NameBinding 25	--
aLink-managedElement	Name: aLink-managedElement OID : ts32-634NameBinding 26	--
iucsLink-managedElement	Name: iucsLink-managedElement OID : ts32-634NameBinding 27	--
iupsLink-managedElement	Name: iupsLink-managedElement OID : ts32-634NameBinding 28	--
iubcLink-managedElement	Name: iubcLink-managedElement OID : ts32-634NameBinding 29	--
gmscServerFunction-managedElement	Name: gmscServerFunction-managedElement OID : ts32-634NameBinding 30	--
csMgwFunction-managedElement	Name: csMgwFunction-managedElement OID : ts32-634NameBinding 31	--

Annex B (informative): Change history

Change history								
Date	TSG #	TSG Doc.	CR	Rev	Subject/Comment	Old	New	
Jun 2001	S_12	SP-010283	--	--	Approved at TSG SA #12 and placed under Change Control	2.0.0	4.0.0	
Sep 2001	S_13	SP-010478	001	--	Correction due to TS renumbering	4.0.0	4.1.0	
Sep 2002	--	--	--	--	Cosmetics/Styles	4.1.0	4.1.1	
Dec 2002	S_18	SP-020749	002	--	Alignment of the CMIP SS with the Rel-5 version of the IS in 32.632	4.1.1	5.0.0	
Dec 2003	S_22	SP-030642	003	--	Add notifications to functional objects - Align with 32.632 (IS)	5.0.0	5.1.0	
Mar 2004	S_23	SP-040130	004	--	Removal of the attribute uraList from the MOC MscServerFunction – Alignment with the IS 32.632	5.1.0	5.2.0	
Sep 2004	S_25	SP-040582	005	--	Correction of modelling of Media GateWay (MGW)	5.2.0	5.3.0	
Sep 2004	S_25	SP-040591	006	--	Removal of the 3GPP Release# cross references in the GDMO section	5.2.0	5.3.0	
Mar 2005	S_27	SP-050047	007	--	Align with 32.632, regarding the IS template and UML repertoire	5.3.0	5.4.0	
Mar 2005	S_27	SP-050047	008	--	Align with 32.632, with regards to ExternalRncFunction	5.3.0	5.4.0	

History

Document history		
V5.0.0	December 2002	Publication
V5.1.0	December 2003	Publication
V5.2.0	March 2004	Publication
V5.3.0	September 2004	Publication
V5.4.0	March 2005	Publication